

HITACHI PROGRAMMABLE CONTROLLER

HIDIC EH-150

APPLICATION MANUAL

NJI-281H (X)

○ Warranty period and coverage

The warranty period is the shorter period either 18 months from the date of manufacture or 12 months from the date of installation.

However within the warranty period, the warranty will be void if the fault is due to;

- (1) Incorrect use as directed in this manual and the application manual.
- (2) Malfunction or failure of external other devices than this unit.
- (3) Attempted repair by unauthorized personnel.
- (4) Natural disasters.

The warranty is for the PLC only, any damage caused to third party equipment by malfunction of the PLC is not covered by the warranty.

○ Repair

Any examination or repair after the warranty period is not covered. And within the warranty period any repair and examination which results in information showing the fault was caused by any of the items mentioned above, the repair and examination cost are not covered. If you have any questions regarding the warranty please contact either your supplier or the local Hitachi Distributor. (Depending on failure part, examination might be impossible.)

○ Ordering parts or asking questions

When contacting us for repair, ordering parts or inquiring about other items, please have the following details ready before contacting the place of purchase.

- (1) Model
- (2) Manufacturing number (MFG no.)
- (3) Details of the malfunction

Warning


- (1) This manual may not be reproduced in its entirety or any portion thereof without prior consent.
- (2) The content of this document may be changed without notice.
- (3) This document has been created with utmost care. However, if errors or questionable areas are found, please contact us.


MS-DOS®, Windows®, and Windows NT® are registered trademarks of America and other registered countries of Microsoft Corp. of the United States.


Safety Precautions

Read this manual and related documents thoroughly before installing, operating, performing preventive maintenance or performing inspection, and be sure to use the unit correctly. Use this product after acquiring adequate knowledge of the unit, all safety information, and all cautionary information. Also, make sure this manual enters the possession of the chief person in charge of safety maintenance.

Safety caution items are classified as “Danger” and “Caution” in this document.



 **DANGER** : Cases where if handled incorrectly a dangerous circumstance may be created, resulting in possible death or severe injury.



 **CAUTION** : Cases where if handled incorrectly a dangerous circumstance may be created, resulting in possible minor to medium injury to the body, or only mechanical damage.

However, depending on the circumstances, items marked with  **CAUTION** may result in major accidents.

In any case, they both contain important information, so please follow them closely.

Icons for prohibited items and required items are shown below:

 : Indicates prohibited items (items that may not be performed). For example, when open flames are prohibited,  is shown.

 : Indicates required items (items that must be performed). For example, when grounding must be performed,  is shown.

1. About installation

CAUTION

- Use this product in an environment as described in the catalog and this document.
If this product is used in an environment subject to high temperature, high humidity, excessive dust, corrosive gases, vibration or shock, it may result in electric shock, fire or malfunction.
- Perform installation according to this manual.
If installation is not performed adequately, it may result in dropping, malfunction or an operational error in the unit.
- Do not allow foreign objects such as wire chips to enter the unit.
They may become the cause of fire, malfunction or failure.

2. About wiring



REQUIRED

- Always perform grounding (FE terminal).
If grounding is not performed, there is a risk of electric shocks and malfunctions.



CAUTION

- Connect power supply that meets rating.
If a power supply that does not meet rating is connected, fire may be caused.
- The wiring operation should be performed by a qualified personnel.
If wiring is performed incorrectly, it may result in fire, damage, or electric shock.

3. Precautions when using the unit



DANGER

- Do not touch the terminals while the power is on.
There is risk of electric shock.
- Structure the emergency stop circuit, interlock circuit, etc. outside the programmable controller (hereinafter referred to as PLC).
Damage to the equipment or accidents may occur due to failure of the PLC.
However, do not interlock the unit to external load via relay drive power supply of the relay output module.



CAUTION

- When performing program change, forced output, RUN, STOP, etc., while the unit is running, be sure to verify safety.
Damage to the equipment or accidents may occur due to operation error.
- Supply power according to the power-up order.
Damage to the equipment or accidents may occur due to malfunctions.

4. About preventive maintenance

DANGER

- Do not connect the \oplus , \ominus of the battery in reverse. Also, do not charge, disassemble, heat, place in fire, or short circuit the battery.
There is a risk of explosion or fire.

PROHIBITED

- Do not disassemble or modify the unit.
These actions may result in fire, malfunction, or malfunction.

CAUTION

- Turn off the power supply before removing or attaching module/unit.
Electric shock, malfunction or failure may result.

Revision History

| No. | Description of Revision | Date of Revision | Manual Number |
|-----|--|------------------|---------------|
| 1 | Modules developed as second step were added. | 1999/05 | — |
| 2 | Modules developed as third step and the EH-CPU448 were added. | 2000/06 | NJI-281B(X) |
| 3 | The description that it apologized was modified. | 2001/01 | NJI-281C(X) |
| 4 | A precaution about EH-CPU448 was added. | 2001/04 | NJI-281D(X) |
| 5 | Description which runs short was added. | 2001/10 | NJI-281E(X) |
| 6 | The description that it apologized was modified | 2002/06 | NJI-281F(X) |
| 7 | Description of Enhanced CPU(EH-CPU***A) was added. | 2002/08 | NJI-281G(X) |
| 8 | Description of new modules (EH-CPU5**, EH-BS*A, EH-IOCH, and 3 I/O) were added. | 2003/09 | NJI-281H(X) |
| | | | |

Table of contents

| | | |
|-----------|--|-------------|
| Chapter 0 | New CPU(EH-CPU516/548) | 0-1 to 0- |
| | 0.1 Expanded function | 0 - 1 |
| Chapter 1 | Features | 1-1 to 1-2 |
| Chapter 2 | System Overview | 2-1 to 2-4 |
| | 2.1 Stand alone system | 2- 1 |
| | 2.2 Compatibility | 2 - 2 |
| | 2.3 Network system | 2 - 3 |
| Chapter 3 | Specifications | 3-1 to 3-8 |
| | 3.1 General Specifications | 3 - 1 |
| | 3.2 Function Specifications | 3 - 2 |
| | 3.3 Performance Specifications | 3 - 6 |
| Chapter 4 | Product lineup | 4-1 to 4-78 |
| | 4.1 Product lineup List | 4 - 1 |
| | 4.2 CPU Module..... | 4 - 5 |
| | 4.3 Memory Board..... | 4 - 8 |
| | 4.4 I/O Controller | 4 - 9 |
| | 4.5 AC Power Module | 4 - 10 |
| | 4.6 DC Power Module | 4 - 13 |
| | 4.7 Base Unit | 4 - 14 |
| | 4.8 Input Module | 4 - 17 |
| | 4.9 32-point Input Module | 4 - 20 |
| | 4.10 Euro-terminal 32-point Input Module | 4 - 22 |
| | 4.11 64-point Input Module | 4 - 24 |
| | 4.12 Output Module | 4 - 26 |
| | 4.13 32-point Output Module | 4 - 31 |
| | 4.14 Euro-terminal 32-point Output Module..... | 4 - 33 |
| | 4.15 64-point Output Module..... | 4 - 35 |
| | 4.16 Analog I/O Module..... | 4 - 37 |
| | 4.17 Resistance Temperature Detective Input Module | 4 - 43 |
| | 4.18 Counter Module..... | 4 - 45 |
| | 4.19 Single-Axis Pulse Positioning Module..... | 4 - 48 |
| | 4.20 4-Axes Pulse Positioning Module | 4 - 51 |
| | 4.21 Ethernet Module | 4 - 56 |
| | 4.22 DeviceNet Master Module..... | 4 - 59 |
| | 4.23 DeviceNet Slave Module..... | 4 - 61 |
| | 4.24 PROFIBUS Master Module..... | 4 - 63 |
| | 4.25 PROFIBUS Slave Module..... | 4 - 65 |
| | 4.26 CPU Link Module (Coaxial type)..... | 4 - 67 |
| | 4.27 CPU Link Module (Optical type) | 4 - 70 |
| | 4.28 Dummy Module..... | 4 - 73 |
| | 4.29 Expansion Cable..... | 4- 73 |
| | 4.30 Terminal Unit for 32 / 64 points I/O module..... | 4 - 74 |
| | 4.31 Cable for 32 / 64 points module (connector type) | 4 - 75 |
| | 4.32 Cable for 32 / 64 points module (open type) | 4 - 75 |
| | 4.33 Conversion Cable for Connecting between CPU and Programmer, etc..... | 4 - 77 |
| | 4.34 Cable for Connecting between CPU and PC (IBM-PC/AC Compatible Personal Computer)..... | 4 - 77 |

| | | |
|------|---------------------------|--------|
| 4.35 | Current consumption | 4 - 78 |
|------|---------------------------|--------|

| | | |
|------------------|-------------------------------|---------------------|
| Chapter 5 | Command Specifications | 5-1 to 5-308 |
|------------------|-------------------------------|---------------------|

| | | |
|-----|-------------------------------------|--------|
| 5.1 | Command Classifications | 5 - 1 |
| 5.2 | List of Commands..... | 5 - 2 |
| 5.3 | Command Specification Details | 5 - 20 |

| | | |
|------------------|---------------------------|-------------------|
| Chapter 6 | I/O Specifications | 6-1 to 6-4 |
|------------------|---------------------------|-------------------|

| | | |
|-----|-----------------------|-------|
| 6.1 | External I/O | 6 - 2 |
| 6.2 | Internal Output | 6 - 4 |

| | | |
|------------------|--------------------|-------------------|
| Chapter 7 | Programming | 7-1 to 7-6 |
|------------------|--------------------|-------------------|

| | | |
|-----|-------------------------|-------|
| 7.1 | Memory Capacity | 7 - 1 |
| 7.2 | Programming Method..... | 7 - 1 |

| | | |
|------------------|----------------------|--------------------|
| Chapter 8 | PLC Operation | 8-1 to 8-14 |
|------------------|----------------------|--------------------|

| | | |
|-------|---|--------|
| 8.1 | RUN Start | 8 - 2 |
| 8.1.1 | Scan operation | 8 - 3 |
| 8.1.2 | Setting System Processing Time (EH-CPU104A/208A/308A/316A/448)..... | 8 - 4 |
| 8.1.3 | Setting System Processing Time (EH-CPU308/316)..... | 8 - 5 |
| 8.1.4 | Normal Scan | 8 - 6 |
| 8.1.5 | Periodical Scan (In case of the EH-CPU104/208/308/316)..... | 8 - 7 |
| 8.1.6 | Periodical Scan (In case of the EH-CPU104A/208A/308A/316A/448)..... | 8 - 8 |
| 8.2 | Online Change in RUN..... | 8 - 9 |
| 8.2.1 | Cautionary Items for Changing Programs in RUN | 8 - 9 |
| 8.2.2 | HALT time..... | 8 - 10 |
| 8.3 | Instantaneous Power Failure..... | 8 - 11 |
| 8.4 | Operation Parameter | 8 - 12 |
| 8.5 | Test Operation | 8 - 13 |

| | | |
|------------------|--|--------------------|
| Chapter 9 | PLC Installation, Loading, Wiring | 9-1 to 9-10 |
|------------------|--|--------------------|

| | | |
|-----|--------------------------|-------|
| 9.1 | Installation | 9 - 1 |
| 9.2 | Loading the Module | 9 - 2 |
| 9.3 | Wiring..... | 9 - 3 |

| | | |
|-------------------|-------------------------------------|----------------------|
| Chapter 10 | Communication Specifications | 10-1 to 10-20 |
|-------------------|-------------------------------------|----------------------|

| | | |
|--------|--|---------|
| 10.1 | Features | 10 - 1 |
| 10.1.1 | Communication port functions..... | 10 - 1 |
| 10.1.2 | Port 1 setup method | 10 - 1 |
| 10.2 | Dedicated Port | 10 - 3 |
| 10.3 | General-Purpose Port..... | 10 - 5 |
| 10.3.1 | RS-232C interface..... | 10 - 6 |
| 10.3.2 | RS-422/485 interface | 10 - 6 |
| 10.3.3 | 1:N communication (RS-485)..... | 10 - 7 |
| 10.4 | Modem Control Function | 10 - 13 |
| 10.4.1 | Configuration..... | 10 - 13 |
| 10.4.2 | Connection specifications | 10 - 13 |
| 10.4.3 | Additional task codes..... | 10 - 14 |
| 10.4.4 | AT commands..... | 10 - 15 |
| 10.5 | Port and Peripheral Unit Connection..... | 10 - 18 |
| 10.6 | Connection method for RS-422/485 communication | 10 - 20 |

| | | |
|------------|--|---------------|
| Chapter 11 | Real Time Clock and Memory Board | 11-1 to 11-10 |
| 11.1 | Real Time Clock Function..... | 11 - 1 |
| 11.1.1 | Operation using a special internal output..... | 11 - 1 |
| 11.1.2 | Operation using task codes | 11 - 2 |
| 11.2 | Memory Board Function | 11 - 3 |
| 11.2.1 | Program transfer function | 11 - 3 |
| 11.2.2 | Logging Function..... | 11 - 5 |
| Chapter 12 | Error Code List | 12-1 to 12-6 |
| 12.1 | Error Codes..... | 12 - 1 |
| 12.2 | Grammar and Assemble Error Codes | 12 - 4 |
| 12.3 | Operation Error Codes..... | 12 - 5 |
| Chapter 13 | Special Internal Outputs | 13-1 to 13-10 |
| 13.1 | Bit Special Internal Output Area | 13 - 1 |
| 13.2 | Word Special Internal Output Area | 13 - 4 |
| 13.3 | Remote Error Flag Area..... | 13 - 9 |
| 13.4 | Link Error Flag Area | 13 - 10 |
| Chapter 14 | Troubleshooting | 14-1 to 14-14 |
| 14.1 | Error Indication and Countermeasure Procedures | 14 - 1 |
| 14.2 | Checklist when Abnormal Occur..... | 14 - 5 |
| 14.3 | Procedures to Solve Abnormals..... | 14 - 6 |
| Chapter 15 | Operation Examples | 15-1 to 15-16 |
| Chapter 16 | Daily and Periodic Inspection | 16-1 to 16-4 |
| Appendix 1 | Cable Connection Diagram | A-1 to A-4 |
| Appendix 2 | H-series Command Support Comparison Chart | A-5 to A-14 |
| Appendix 3 | Index of Instruction | A-15 to A-18 |

MEMO

Chapter 0 New CPU (EH-CPU516/548)

New CPU (EH-CPU516/548) had been released since Aug. 2003.

In this chapter, newly expanded and changed functions for the new CPU are described below. Other functions not described in this chapter are the same as old CPU.

0.1 Expanded function

Expanded function is described below.

0.1.1 Expansion base and max. slot number

The max. number of expansion base and slot are expanded for new CPU as follows.

Table 0.1 The maximum system configuration

| | Exp. base | Availability of 11 slot base | Max. slot number |
|--------------------------------------|--------------|---------------------------------|------------------|
| CPU104(A) | 0 | No | 8 |
| CPU208(A), 308(A), 316(A), CPU448(A) | 1 | No | 16 (8×2) |
| CPU516 | 2 | Yes | 33 (11×3) |
| CPU548 | 4 | Yes | 55 (11×5) |

Refer to the chapter 2 for further information.

0.1.2 Communication slot expanded

Communication slot is expanded for EH-BS*A as follows.

| Type | Communication slot |
|------------------|---|
| EH-BS3, BS5, BS8 | Slot 0-2 |
| EH-BS3A | Slot 0-2 |
| EH-BS5A | Slot 0-4 |
| EH-BS8A | Slot 0-7 |
| EH-BS11A | Slot 0-7 (Not allowed on slot 8, 9, A) |

Refer to chapter 2 for further information.

0.1.3 On delay timer : TM

2,048 points of new on delay timer TM is available in addition to existing timer TD. Time base can be selected from 0.01s, 0.1s and 1s for all TM0 to TM2047. Timer accumulator of TM is TV (0 to 65,535).

New timer TM is supported by LADDER EDITOR for Windows Ver.3.00 or newer. User program including TM does not work with CPU104(A)/208(A)/308(A)/316(A)/448(A) and LADDER EDITOR for Windows Ver.2.** or older.

0.1.4 Virtual remote I/O for internal output

Remote I/O area can be used as internal output like WM if empty slot is assigned as "Remote2". This is useful in case WR or WM memory spent a lot. Refer to the chapter 6 for further information.

0.1.5 Built-in termination resistor

Built-in resistor is added in port 1 of RS-422/485. This can be enabled by setting special internal output. Please refer to chapter 10 and 13 for further information.

0.1.6 Additional commands

The following commands are added.

(1) Inverter control command (FUN 190)

Several Hitachi inverters SJ300 and L300P series are controlled by serial communication from CPU port 1 via RS-485.

(2) Check code generating, verifying (FUN 22, 23)

New command of check code generating for data sending, check code verifying for data receiving. Useful with serial communication command (TRNS0/RECV0).

(3) DeviceNet Explicit message command (FUN 162, 163)

Special communication to DeviceNet slave modules

(4) Data search and table search command (FUN 20, 21)

Same commands supported by Big-H series.

Chapter 1 Features

1. Compact and space saving

The EH-150 has realized a compact size; 372.5 mm (W) × 100 mm (H) × 109 mm (D) with 1,024 I/Os. The standard I/O module accommodates both a terminal block and LED display as standard, the same as our previous series of programmable controllers. It can also be installed on a DIN rail.

Each module is enclosed in a capsule-type case for easier handling. By introducing a curved line on the front cover, the system can be neatly consolidated into an ultra high-tech image.

2. 2 communication ports provided as standard

The EH-150 comes standard with 2 communication ports (serial port 1 and serial port 2) supported by the same type communication method as that for connecting a programming device (personal computer). The display and programming device sold in the market that have been developed for the H series can both be used simultaneously to seamlessly construct a system.

The setting for the port 1 can be changed, which allows it to function as a general-purpose port that can be controlled by the user program. A communication program can be created for the specific device connected (printer, bar code reader, etc.).

3. Built-in modem connection interface function

The EH-CPU208(A)/308(A)/316(A)/448(A)/516/548, with a modem connected to the port 1, can communicate with a distant location via commercial phone lines. A system located some distance away can be monitored from an office or a monitor room.

4. Built-in RS-422/485 interface

By setting the special internal output, serial port 1 can perform communication as an RS-422/485 interface. By using the RS-422/485 interface, a small data link system can be formed between CPU modules or with personal computers via 1:N connection. (Supported by EH-CPU308(A)/316(A)/448(A)/516/548)

5. State-of-art technology and functions have been packed in a compact size.

The EH-150 contains 32-bit RISC processor (Super H series made by Hitachi, Ltd.) that allows high-speed operations. The user program is stored in FLASH memory so that the user program can be retained in case the battery goes dead. However, batteries are necessary when backing up the data memory.

6. Compatibility with H-series protects software properties

The EH-150 was developed as part of the H-series family. Those who are currently using the H-series can create and debug programs using the same concepts as they are now. Those who use the EH-150 for the first time, will find that using the H-series programmable controller will greatly broaden the applications of the software properties when they seek to expand their system in the future.

7. Memory board function is supported

The EH-CPU308(A)/316(A)/448(A)/516/548 can use the new memory boards (EH-MEMP/MEMD) that have been made available. The EH-MEMP is capable of storing up to 48 k steps of user programs. Also, by using the program transfer function, the programs can be copied without the use of peripheral devices. Furthermore, the EH-MEMD is capable of storing a maximum of 384 k words of data.

When using a memory board, the contents of the memory board are not changed during transfer of programs from peripheral devices or when RUN is in progress. (Only the program within the CPU will be changed.) If changes are necessary, copy the program within the CPU using the program transfer function of the memory board.

8. PID operation function is supported

PID control can be performed without the use of additional modules. A variety of process inputs and outputs can be supported by directly controlling the analog I/O module. By using this function, continuous control targets such as temperature and flow rate can be controlled in a prompt and smooth manner. (Supported by EH-CPU308(A)/316(A)/448(A)/516/548)

9. Ease of use to facilitate incorporation into other devices

The EH-150 is designed so that it can be installed on easy-to-use DIN rails.

The user programs can be retained even if he or she does not wish to use a battery with the system.

The EH-150 supports a “Online change in RUN” function that allows the user to change the program while it is running.

The standard I/O module uses a removable terminal block, which reduces wiring working drastically. LEDs are provided as standard to check operation status and wiring. Further, the battery can be replaced without having to remove the CPU module from the base unit. The battery is replaced from the front simply by opening the cover of the CPU module.

Chapter 2 System Overview

2.1 Stand alone system

The EH-150 is a module-type programmable controller with the basic configuration shown in Figure 2.1.




Figure 2.1 EH-150 System configuration diagram

| No. | Device name | Description of function |
|-----|-----------------|--|
| 1] | Power module | Converts power supply to the power to be used within the EH-150. |
| 2] | CPU module | Performs operations based on the contents of the user program, receives input and controls output. |
| 3] | I/O module | Input module, output module, analog module, etc. |
| 4] | Basic base | Base in which the power module, CPU module, I/O module, etc. are loaded. |
| 5] | Expansion base | Base in which the power module, I/O controller, I/O module, etc. are loaded. |
| 6] | Expansion cable | Cable that connects the I/O controllers for the basic base and expansion base. |
| 7] | I/O controller | Interface with expansion base and CPU module. |

* The basic base 4] and expansion base 5] are the same product.

Maximum system configuration


| | Expansion base | 11 slot base | Max. slot number |
|--------------------------------------|----------------|---------------|------------------|
| CPU104(A) | 0 | Not supported | 8 |
| CPU208(A), 308(A), 316(A), CPU448(A) | 1 | Not supported | 16 (8×2) |
| CPU516 | 2 | Supported | 33 (11×3) |
| CPU548 | 4 | Supported | 55 (11×5) |

2.2 Compatibility

Since the enhanced version products, EH-IOCH, EH-BS3A, 5A, 8A, has upper compatibility with standard products (previous products: EH-IOC, EH-BS3, 5, 8), the both can be mixed within the previous range of expansion, such as one expansion base, 16 slots total, slot 0-2 for communication slot.

If system configuration is beyond this range, such as 2nd to 4th expansion base, 11 slot base used and slot 0-7 for communication slot, be sure to use CPU5xx, EH-IOCH, EH-BS3A, 5A, 8A, 11A only.

(* Communication slot : Special slot for communication modules.)



"Standard products" and "Enhanced products" specified as follows.

| | Standard products | Enhanced products |
|-----------------|---|-------------------------------|
| CPU | CPU104(A) / CPU208(A) / CPU308(A) / CPU316(A) / CPU448(A) | CPU516 / CPU548 |
| Base | EH-BS3 / BS5 / BS8 | EH-BS3A / BS5A / BS8A / BS11A |
| I/O controller | EH-IOC | EH-IOCH |
| Expansion cable | EH-CB10 | EH-CB05A / CB10A / CB20A |

* If both CPU and basic base are enhanced products (incl. EH-BS11A), communication slot on basic base is effective even if expansion bases are standard products.

2.3 Network system

The EH-150 enables various network systems shown in Figure 2.2.




Figure 2.2 EH-150 Network diagram

MEMO

Chapter 3 Specifications


3.1 General Specifications

| Item | | Specification |
|---------------------------------------|--------------------|---|
| Power voltage | AC receiving power | 100/110/120 V AC (50/60 Hz), 200/220/240 V AC (50/60 Hz) |
| | DC receiving power | 24 V DC |
| Power voltage fluctuation range | | 85 to 264 V AC wide range |
| | | 21.6 to 26.4 V DC |
| Allowable instantaneous power failure | | 85 to 100 V AC: for a momentary power failure of less than 10 ms, operation continues 100 to 264 V AC: for a momentary power failure of less than 20 ms, operation continues |
| Operating ambient temperature | | 0 to 55 °C (Storage ambient temperature -10 to 75 °C) |
| Operating ambient humidity | | 20 to 90 % RH (no condensation) (Storage ambient humidity 10 to 90 % RH (no condensation)) |
| Vibration resistance | | Conforms to JIS C 0911 (16.7 Hz double amplitude 3 mm X, Y and Z each direction) |
| Noise resistance | | <ul style="list-style-type: none"> ○ Noise voltage 1,500 Vpp Noise pulse width 100 ns, 1 μs (Noise created by the noise simulator is applied across the power supply module's input terminals. This is determined by this company's measuring methods.) ○ Based on NEMA ICS 3-304 (with the exception of input module) ○ Static noise: 3,000 V at metal exposed area |
| Insulation resistance | | 20 M Ω or more between the AC external terminal and case ground (FE) terminal (based on 500 V DC mega) |
| Dielectric withstand voltage | | 1,500 V AC for 1 minute between the AC external terminal and case ground (FE) terminal |
| Grounding | | Class D grounding (ground with power supply module) |
| Usage environment | | No corrosive gases, no excessive dust |
| Structure | | Open, wall-mounted type |
| Cooling | | Natural air cooling |

3.2 Function Specifications

The functions available in the EH-150 are described in the table below.

| No. | Item | Description of function |
|-----|----------------------|---|
| 1 | Basic functions | <p>The following functions can be achieved when constructing a system using the EH-150.</p> <ol style="list-style-type: none"> 1] An input signal is received from the control object, operations are performed according to the contents of the program created by the user and the results are output as an output signal. Also, operation results and information during the process can be retained in the internal output area. 2] After power is supplied to the main module and system begins to run, the operation described above is performed continuously until the power is shut off or the system stops running. 3] The information retained internally can be extracted by a device connected externally or can be set in other information. Also, this information is initialized at the time the system begins running, but it can also be retained according to user settings. 4] Operating status can be confirmed with the LED display of the CPU module or I/O module or with an external device that is connected. |
| 2 | Setting and display | <p>The following have been provided for the user to set or confirm various types of operation status:</p> <ol style="list-style-type: none"> 1] Setting switch (CPU module) This sets the CPU communication function setting and operation mode, etc. It can also instruct run and stop. 2] LED display (Power module, CPU module, I/O module) Indicates the power system status, operating status and I/O operation status. 3] Connector (CPU module, basic base, I/O controller) This can connect external devices using RS-232C, etc. It can also add I/O modules. 4] Terminal block (Power module, I/O module) This performs the connections for supplying power, and for exchanging signals with the control object. |
| 3 | Number of I/O points | <p>The number of points that can be controlled with respect to the control object is as follows.</p> <ol style="list-style-type: none"> 1] External I/O If 64-point module is used, EH-CPU104 is able to handle 512 points, and EH-CPU208(A)/308(A)/316(A)/448(A) is 1,024 points, CPU516 is 2,112 points, and CPU548 is 3,520 points. Input is indicated by X, WX, DX and output is indicated by Y, WY, DY. 2] Internal outputs These are areas for temporarily storing information. The I/O numbers are M, WM, DM, R, WR, DR, etc. 3] A timer and a counter are provided internally. 4] Array (only corresponding to substitution statement) Array of I/O numbers can be indicated by placing parentheses () around them. |
| 4 | User program memory | <p>The program where the control contents have been described can be stored. The memory for this is in the CPU module and the capacity differs for each CPU module.</p> <ol style="list-style-type: none"> 1] The memory has a function whereby its contents are retained even if the battery dies. Because of this, it is necessary to initialize the memory since it may have uncertainties right after the unit is purchased. 2] Programming is performed using the programming software (LADDER EDITOR) and peripheral device, etc. for the H-series programmable controllers. 3] The commands that can be used are those designated by the H-series ladder. Refer to the list of EH-150 commands for details. |
| 5 | Back-up memory | <p>The contents of a user program can be maintained without a battery.</p> <ol style="list-style-type: none"> 1] A battery is not required to retain the contents of the user program. Always store the created programs to a floppy disk, etc. just in case something unexpected occurs. 2] When a user program is transferred from a peripheral device or the contents of a user program are changed in the RUN state, the EH-CPU448 writes the user program to the back-up memory without disturbing CPU running. It takes approximately two minutes to write the user program to the back-up memory. <p>* To protect a user program while writing it to the back-up memory (while the special internal output R7EF stays "1"), do not turn off the power of the system.</p> |


| No. | Item | Description of function |
|-----|----------------------|---|
| 5 | Back-up memory | <p>3] Several setting, such as communication port (WRF036, WRF037), system processing time (WRF038) and clear mode for link area (WRF07E), are automatically saved to the backup memory if they are changed.</p> <p>* WRF037 is valid only when just after power ON.</p> <div data-bbox="512 360 1388 499" style="border: 1px solid black; padding: 5px;"> <p> Note</p> <p>FLASH memory is used for the backup memory. If such special internal output values in FLASH memory are changed frequently by user program, the lifetime of FLASH memory will be shorter. Please refer to the chapter 13 in details.</p> </div> |
| 6 | Control method | <p>With the EH-150, the user programs are batch converted when operation begins, and the programs after conversion will be executed in order as they are read one by one.</p> <p>1] The method used for I/O data is that after the I/O data (information) is scanned (execution from the head of the program to the end), it is updated in group (refresh method). If refresh of external I/O is required in the middle of scanning, use the refresh command.</p> <p>2] Apart from the program that will be normally executed, a periodic scan program which interrupts the normal program at set time intervals and is executed, can be created. The time intervals are 10 ms, 20 ms, and 40 ms. (The EH-CPU448(A)/516/548 supports 5 ms.)</p> <p>3] The user program is executed from the head of the program to the end, and is once again repeated after the system processing that updates the lapsed timer value, refreshes I/O, and performs communication with peripheral devices, has been performed.</p> |
| 7 | Run/stop control | <p>Running and stopping of the CPU module is normally performed by the user.</p> <p>1] Turn the RUN switch on to begin operation. Turn the switch off to stop operation.</p> <p>2] The start and stop operation can be performed via communication from peripheral devices (PC) by changing to the REMOTE mode using the setting switch.</p> <p>3] The start and stop operation can be performed with designated external inputs or internal outputs by designating operation control inputs with a programming device.</p> <p>4] Apart from the above described operation, if a malfunction is detected in the system while it is running, operation stops and the outputs are shut down (OFF).</p> <p>5] If the power is shut off and then turned back on while the system is running, operation starts. When the power shuts off, turn off the power to the EH-150, then shut off the external input power. When turning the power back on, turn on the external input power before turning on the power to the EH-150.</p> <p>6] When starting operation, do so after clearing internal information which is not designated for storage during power failure. When stopping operation, leave the internal information as is, turn off the outputs and then stop.</p> <p>7] When the power has been cut off for longer than the time allowed for instantaneous power failure, then depending on the system load status, either operation continues or the system perceives that a power shut off has occurred and restarts operation. To ensure operation resumes correctly, have the power remain off for 1 minute or longer.</p> |
| 8 | Operation parameters | <p>Each type of condition for operating the EH-150 can be set. The possible settings for operation when an error occurs are given below.</p> <p>1] Operation can be continued when I/O information does not match.</p> <p>2] Overload check time can be set. The initial value is 100 ms and operation stops when the time for one scan takes longer than the set overload check time. (overload error)</p> <p>3] Operation can be made to continue when an overload error occurs.</p> <p>4] When a power failure (power shutoff) occurs, the internal output area for retaining information and the timer and the counter range can be designated.</p> <p>And, the setting below is possible.</p> <p>1] The name of the user program can be registered.</p> <p>2] A password can be set up so that a third party cannot reference the program.</p> <p>3] It is necessary to register the type of I/O module used as an I/O assignment table. In order to create this I/O assignment table, the type of I/O module that is connected can be read.</p> |

| No. | Item | Description of function |
|-----|--|---|
| 9 | Online change in RUN | <p>A section of a program can be revised while it is running.</p> <ol style="list-style-type: none"> 1] If revision is done with a programming device and the online change is performed in RUN, the user program in the CPU is changed and the altered program is switched internally at the end of scanning, and operation continues with the new program. 2] When a control command is to be included in the revisions to the program, make the changes after first performing the control command change procedure in the programming device and checking for safety. 3] Until operation starts to continue with the new program, a 'halt period' occurs when the module does not run. External input information is not being received during this time, so leave plenty of allowance in the timing for executing a online change in RUN. |
| 10 | Forced set/reset | Forced set and forced reset of the designated I/O can be performed from the programming device connected to the CPU module. |
| 11 | Forced output | Output can be forced with respect to the designated I/O number from the programming device connected to the CPU module. For I/O that are not designated, outputs are shut off. |
| 12 | Calendar clock function (Not supported by EH-CPU104(A)) | <p>EH-CPU208(A)/308(A)/316(A)/448(A)/516/548 has a calendar clock function.</p> <ol style="list-style-type: none"> 1] Year, month, date, day of the week, hour, minute and second can be set. 2] There is a function for making adjustments in 30 second units. 3] When a battery is not installed, the calendar clock information is not retained when power goes off. The calendar clock must be set again. |
| 13 | Dedicated port | <p>This is a communication port with dedicated protocol for the H-series. The communication command called the task code is defined in the port.</p> <ol style="list-style-type: none"> 1] A programming device can be connected. 2] The ports that can be used as dedicated ports are Port 1 and Port 2. Transmission speed, etc. can be switched using the setting switch. |
| 14 | General-purpose port | This is a serial port that can be controlled by the user program. The various settings for communication, actual transmit and receive processing are carried out by the user program. Port 1 can be assigned for this function by switching the setting switch. |
| 15 | Modem control (The EH-CPU 104/104A are not supported) | <p>A modem can be connected externally for use. It becomes operable when something arrives from outside, and after that, task code communication can be performed.</p> <p>When transmitting from the EH-150, set the port as a general-use port and have it controlled independently with the user program.</p> <p>Port 1 can be assigned for this function by switching the setting switch.</p> |
| 16 | Self-diagnosis | <p>Self-diagnostic tests for the following items are performed:</p> <ol style="list-style-type: none"> 1] Microcomputer check 2] System program area check 3] Memory check 4] User program check 5] Internal output area check 6] Mounted I/O check |
| 17 | Abnormal handling | <p>When an abnormal occurs, the error code that shows the error contents are output to special internal output WRF000 as a hexadecimal value. Also, the error is indicated to the outside by the ERR lamp, etc. If the error level is high, the CPU stops operation, but depending on the error, the operation may be continued using user settings.</p> <p>If multiple errors occur, the error code with higher error severity is set. The detailed information is also set to the special internal output. Also, this information is always recorded in the power failure memory, so the information can be referenced even after the power is cut off. (However, a battery is required.) The clearing of the error information can be conducted by turning on R7EC.</p> |

| No. | Item | Description of function |
|-----|--|---|
| 18 | Task code | By combining individual task codes, the following functions can be realized by the program in the host computer: 1] CPU control (RUN/STOP control of CPU, occupy/release, CPU status read, etc.) 2] I/O control (various types of monitoring) 3] Memory write (all clear, batch transfer, etc.) 4] Memory read (reading of programs, etc.) 5] Response (various responses from CPU) |
| 19 | Command | Programming can be performed for various purposes and uses by combining ladders and the command language. |
| 20 | Setting of System execution time (only EH-CPU104A/208A/308A/316A/448(A)/516/548) | EH-150 series CPU executes by periodic 10ms. Conventionally CPU executes system processing for peripheral equipment communication in former 5ms and user program operation in after 5 ms. Enhanced CPU can set any system processing time from 1 to 8 ms. The default is 2ms, in which calculation process becomes higher priority, thus scan time becomes faster and system processing time becomes slow. Set the value according to your application system. See chapter 0.2.4 Setting System Processing Time / 8.1.2 Setting System Processing Time. |


Note: The EH-150 does not support some functions that are supported by the rest of the H series (debugging, tracing, forcing and simulation functions).
Don't select the tracing function among them, because an occupy error will occur when peripheral devices are used and the trace function is selected. If an occupy error should occur, recover by first going off-line and then going back on-line and reconnecting.

3.3 Performance Specifications

| Model | Type | | EH-CPU104/104A | EH-CPU208/208A |
|-------------------------------------|---------------------|--|--|--|
| Control specifications | CPU | | 32-bit RISC processor | |
| | Processing method | | Stored program cyclic method | |
| | Processing speed | Basic commands | 1.0 μ s/command | |
| | | Application commands | Several 10 μ s/command | |
| | User program memory | | 3.5 k steps | 7.6 k steps |
| Operation processing specifications | Command language | Basic commands | 39 types such as LD, LDI, AND, ANI, OR, ORI, ANB, ORB, OUT, MPS, MRD, MPP | |
| | | Arithmetic command | 59 types such as arithmetic (+ - \times \div =, etc.), jump, subroutine, division, extraction, etc. | |
| | | Application commands | | |
| | Ladder | Basic commands | 39 types, such as  | |
| | | Arithmetic command Application commands | 59 types such as arithmetic (+ - \times \div =, etc.), jump, subroutine, division, extraction, etc. | |
| I/O processing specifications | External I/O | I/O processing method | | Refresh processing |
| | | 64 points I/O module | | 512 points max. 1,024 points max. |
| | | Expansion unit | | Not supported 1 |
| | Internal output | Bit | | 1,984 points (R0 to R7BF) |
| | | Word | | 4,096 words (WR0 to WRFFF) 8,192 words (WR0 to WR1FFF) |
| | | Special | Bit | 64 points (R7C0 to R7FF) |
| | | | Word | 512 words (WRF000 to WRF1FF) |
| | | CPU link | | 16,384 points 1,024 words \times 2 loops (L0 to L3FFF/L10000 to L13FFF, WL0 to WL3FF/WL1000 to WL13FF) |
| | | Remote I/O | | - |
| | | Bit/word shared | | 16,384 points 1,024 words (M0 to M3FFF, WM0 to WM3FF) |
| | Timer and counter | Number of points | | 512 points (TD + CU) (TD is up to 256 points *1) |
| | | Timer set value | | 0 to 65,535, time base 0.01s, 0.1s, 1s (64 points are maximum for 0.01 s. *2) |
| | | Counter set value | | 1 to 65,535 |
| | Edge detection | | 512 points (DIF0 to DIF511: decimal) + 512 points (DFN0 to DFN511: decimal) | |
| Peripheral devices | Program method | | Command language, ladder diagram | |
| | Peripheral device | | Programming software (LADDER EDITOR DOS version/Windows® version) Command language programmer, Portable graphic programmer, Graphic input device | |
| Maintenance functions | Self-diagnosis | | PC abnormal (LED display): microcomputer error, watchdog timer error, memory error, program error, system ROM/RAM error, scan time monitoring, battery under-voltage detection, and others | |


*1: The same numbers cannot be shared by the time and the counter. TD is 0 to 255.

*2: Only timers numbered 0 to 63 can use 0.01s for their time base.

| Model | Type | EH-CPU308/308A | EH-CPU316/316A |
|-------------------------------------|---------------------|--|--|
| Control specifications | CPU | 32-bit RISC processor | |
| | Processing method | Stored program cyclic method | |
| | Processing speed | Basic commands | 1.0 μ s/command |
| | | Application commands | Several 10 μ s/command |
| | User program memory | 7.6 k steps | 15.7 k steps |
| Operation processing specifications | Command language | Basic commands | 39 types such as LD, LDI, AND, ANI, OR, ORI, ANB, ORB, OUT, MPS, MRD, MPP |
| | | Arithmetic command Application commands | 59 types such as arithmetic (+ - \times \div =, etc.), jump, subroutine, division, extraction, etc. |
| | Ladder | Basic commands | 39 types, such as  |
| | | Arithmetic command Application commands | 59 types such as arithmetic (+ - \times \div =, etc.), jump, subroutine, division, extraction, etc. |
| I/O processing specifications | External I/O | I/O processing method | Refresh processing |
| | | 64 points I/O module | 1,024 points maximum |
| | | Expansion unit | 1 |
| | Internal output | Bit | 1,984 points (R0 to R7FF) |
| | | Word | 17,408 words (WR0 to WR43FF) |
| | | Special | 22,528 words (WR0 to WR57FF) |
| | | | 64 points (R7C0 to R7FF) |
| | | Word | 512 words (WRF000 to WRF1FF) |
| | | CPU link | 16,384 points 1,024 words \times 2 loops (L0 to L3FFF/L10000 to L13FFF, WL0 to WL3FF/WL1000 to WL13FF) |
| | | Remote I/O | - |
| | | Bit/word shared | 16,384 points 1,024 words (M0 to M3FFF, WM0 to WM3FF) |
| | Timer and counter | Number of points | 512 points (TD + CU) (TD is up to 256 points *1) |
| | | Timer set value | 0 to 65,535, time base 0.01s, 0.1s, 1s (64 points are maximum for 0.01 s. *2) |
| | | Counter set value | 1 to 65,535 |
| | Edge detection | | 512 points (DIF0 to DIF511: decimal) + 512 points (DFN0 to DFN511: decimal) |
| Peripheral devices | Program method | Command language, ladder diagram | |
| | Peripheral device | Programming software (LADDER EDITOR DOS version/Windows® version) Command language programmer, Portable graphic programmer, Graphic input device | |
| Maintenance functions | Self-diagnosis | PC abnormal (LED display): microcomputer error, watchdog timer error, memory error, program error, system ROM/RAM error, scan time monitoring, battery under-voltage detection, and others | |


*1: The same numbers cannot be shared by the time and the counter. TD is 0 to 255.

*2: Only timers numbered 0 to 63 can use 0.01s for their time base.

| Model | Type | | EH-CPU448/448A | |
|-------------------------------------|-------------------|--|--|--|
| Control specifications | CPU | | 32-bit RISC processor | |
| | Processing method | | Stored program cyclic method | |
| | Processing speed | Basic commands | 0.1 μs/command | |
| | | Application commands | Several 10 μs/command | |
| | | User program memory | | 48.5 k steps |
| Operation processing specifications | Command language | Basic commands | 39 types such as LD, LDI, AND, ANI, OR, ORI, ANB, ORB, OUT, MPS, MRD, MPP | |
| | | Arithmetic command Application commands | 113 types such as arithmetic (+ − × ÷ =, etc.), jump, subroutine, division, extraction, etc. | |
| | Ladder | Basic commands | 39 types, such as  | |
| | | Arithmetic command Application commands | 113 types such as arithmetic (+ − × ÷ =, etc.), jump, subroutine, division, extraction, etc. | |
| I/O processing specifications | External I/O | I/O processing method | | Refresh processing |
| | | 64 points I/O module | | 1,024 points maximum |
| | | Expansion unit | | 1 |
| | | | | |
| | Internal output | Bit | | 1,984 points (R0 to R7BF) |
| | | Word | | 50,176 words (WR0 to WRC3FF) |
| | | Special | Bit | 64 points (R7C0 to R7FF) |
| | | | Word | 512 words (WRF000 to WRF1FF) |
| | | CPU link | | 16,384 points 1,024 words × 2 loops (L0 to L3FFF/L10000 to L13FFF, WL0 to WL3FF/WL1000 to WL13FF) |
| | | Remote I/O | | - |
| | | Bit/word shared | | 16,384 points 1,024 words (M0 to M3FFF, WM0 to WM3FF) |
| | Timer and counter | Number of points | | 512 points (TD + CU) (TD is up to 256 points *1) |
| | | Timer set value | | 0 to 65,535, timer base 0.01s, 0.1s, 1s (64 points are maximum for 0.01 s. *2) |
| | | Counter set value | | 1 to 65,535 times |
| Edge detection | | 512 points (DIF0 to DIF511: decimal) + 512 points (DFN0 to DFN511: decimal) | | |
| Peripheral devices | Program method | | Command language, ladder diagram | |
| | Peripheral device | | Programming software (LADDER EDITOR DOS version/Windows® version) Command language programmer, Portable graphic programmer, Graphic input device | |
| Maintenance functions | Self-diagnosis | | PC abnormal (LED display): microcomputer error, watchdog timer error, memory error, program error, system ROM/RAM error, scan time monitoring, battery under-voltage detection, and others | |

*1: The same numbers cannot be shared by the timer and the counter. TD is 0 to 255.

*2: Only timers numbered 0 to 63 can use 0.01s for their time base.

| Model | Type | | EH-CPU516 | | EH-CPU548 | |
|-------------------------------------|---------------------|---|--|---|---|------------------------------|
| Control specifications | CPU | | 32-bit RISC processor | | | |
| | Processing method | | Stored program cyclic method | | | |
| | Processing speed | Basic commands | 0.1 μs/command | | | |
| | | Application commands | Several 10 μs/command | | | |
| | User program memory | | 15.7 k steps | | 48.5 k steps | |
| Operation processing specifications | Command language | Basic commands | 39 types such as LD, LDI, AND, ANI, OR, ORI, ANB, ORB, OUT, MPS, MRD, MPP | | | |
| | | Arithmetic command Application commands | 59 types such as arithmetic (+ − × ÷ =, etc.), jump, subroutine, division, extraction, etc. | | | |
| | Ladder | Basic commands | 39 types, such as  | | | |
| | | Arithmetic command Application commands | 59 types such as arithmetic (+ − × ÷ =, etc.), jump, subroutine, division, extraction, etc. | | | |
| I/O processing specifications | External I/O | I/O processing method | | Refresh processing | | |
| | | 64 points I/O module | | 2,112 points maximum | | 3,520 points maximum |
| | | Expansion unit | | 2 | | 4 |
| | Internal output | Bit | | 1,984 points (R0 to R7BF) | | |
| | | Word | | 22,528 words (WR0 to WR57FF) | | 50,176 words (WR0 to WRC3FF) |
| | | Special | Bit | 64 points (R7C0 to R7FF) | | |
| | | | Word | 512 words (WRF000 to WRF1FF) | | |
| | | CPU link | | 16,384 points 1,024 words × 2 loops (L0 to L3FFF/L10000 to L13FFF, WL0 to WL3FF/WL1000 to WL13FF) | | |
| | | Remote I/O | | 512 points × 4 master stations | | |
| | | Bit/word shared | | 16,384 points 1,024 words (M0 to M3FFF, WM0 to WM3FF) | | |
| | | Timer and counter | Number of points | | 512 points (TD + CU) (TD is up to 256 points *1) 2,048 points (TM) | |
| | Timer set value | | 0 to 65,535, time base 0.01s, 0.1s, 1s (64 points are maximum for 0.01 s. *2) | | | |
| | Counter set value | | 1 to 65,535 | | | |
| | Edge detection | | 512 points (DIF0 to DIF511: decimal) + 512 points (DFN0 to DFN511: decimal) | | | |
| | Peripheral devices | Program method | | Command language, ladder diagram | | |
| Peripheral device | | Programming software (LADDER EDITOR DOS version/Windows® version) Command language programmer, Portable graphic programmer, Graphic input device | | | | |
| Maintenance functions | Self-diagnosis | | PC abnormal (LED display): microcomputer error, watchdog timer error, memory error, program error, system ROM/RAM error, scan time monitoring, battery under-voltage detection, and others | | | |

*1: The same numbers cannot be shared by the time and the counter. TD is 0 to 255.

*2: Only timers numbered 0 to 63 can use 0.01s for their time base.

MEMO

Chapter 4 Product lineup

4.1 Product lineup List

(1) Basic devices

Table 4.1 List of system equipment (1/2)

| Product | Type | Specification | I/O assignment | Remarks |
|----------------|--------------|--|----------------|--|
| CPU module | EH-CPU104(A) | 512 I/O points max.*1, 4 k steps, 1.0μs/basic command (No exp. base possible.) | — | Fixed position *2 |
| | EH-CPU208(A) | 1,024 I/O points max.*1, 8 k steps, 1.0μs/basic command, clock function, 1 exp. base, modem control function | — | |
| | EH-CPU308(A) | 1,024 I/O points max.*1, 8 k steps, 1.0μs/basic command, clock function, 1 exp. base, modem control function, Memory board function, RS-422/485 port, PID command, floating point operation | | |
| | EH-CPU316(A) | 1,024 I/O points max.*1, 16 k steps, 1.0μs/basic command, clock function, 1 exp. base, modem control function, Memory board function, RS-422/485 port, PID command, floating point operation | — | |
| | EH-CPU448(A) | 1,024 I/O points max.*1, 48 k steps, 0.1μs/basic command, clock function, 1 exp. base, modem control function, Memory board function, RS-422/485 port, PID command, floating point operation | | |
| | EH-CPU516 | 2,112 I/O points max.*1, 16 k steps, 0.1μs/basic command, clock function, 2 exp. base, modem control function, Memory board function, RS-422/485 port, PID command, floating point operation | — | |
| | EH-CPU548 | 3,520 I/O points max.*1, 48 k steps, 0.1μs/basic command, clock function, 4 exp. base, modem control function, Memory board function, RS-422/485 port, PID command, floating point operation | — | |
| Memory board | EH-MEMP *4 | Program capacity 48 k steps | — | Mounted on optional slot *2 |
| | EH-MEMD *4 | Program capacity 16 k steps, Data capacity 384 k words | — | |
| I/O controller | EH-IOCH | I/O control module, 1 unit/exp. base | — | Fixed position on CPU slot *2 |
| Power module | EH-PSA | Input 100 to 240 V AC Output 5 V DC 3.8 A, 24 V DC 0.4 A | — | Fixed position *2 |
| | EH-PSD | Input 21.6 to 26.4 V DC Output 5 V DC 3.8 A | — | |
| Base unit | EH-BS3A | 3 I/O modules mounted | — | Common for both basic and expansion base |
| | EH-BS5A | 5 I/O modules mounted | — | |
| | EH-BS8A | 8 I/O modules mounted | — | |
| | EH-BS11A | 11 I/O modules mounted | — | |
| Input module | EH-XD8 | 8 points, 24 V DC input | X16 | |
| | EH-XD16 | 16 points, 24 V DC input | X16 | |
| | EH-XDL16 | 16 points, 24 V DC input, High cut filter | X16 | |
| | EH-XD32 | 32 points, 24 V DC input | X32 | |
| | EH-XD32E | 32 points, 24 V DC input, Euro-terminal | X32 | |
| | EH-XDL32E | 32 points, 24 V DC input, Euro-terminal, High cut filter | X32 | |
| | EH-XD64 | 64 points, 24 V DC input | X64 | |
| | EH-XA16 | 16 points, 100 to 120 V AC input | X16 | |
| Output module | EH-XAH16 | 16 points, 200 to 240 V AC input | X16 | |
| | EH-YT8 | 8 points, transistor output (sink type) | Y16 | |
| | EH-YR8B | 8 points, relay output, Separated type, Built-in varistor | | |
| | EH-YR12 | 12 points, relay output | Y16 | |
| | EH-YR16 | 16 points, relay output | | |
| | EH-YTP8 | 8 points, transistor output (source type) | Y16 | |
| | EH-YT16 | 16 points, transistor output (sink type) | Y16 | |
| | EH-YTP16 | 16 points, transistor output (source type) | Y16 | |
| | EH-YTP16S | 16 points, transistor output (source type), short-circuit protection | Y16 | Electric short circuit protection |
| | EH-YT32 | 32 points, transistor output (sink type), short-circuit protection *3 | Y32 | |
| | EH-YTP32 | 32 points, transistor output (source type), short-circuit protection *3 | Y32 | |

Table 2 Basic components (2/2)

| Product | Type | Specification | I/O assignment | Remarks |
|----------------------|------------|--|----------------|-----------------------------------|
| Output module | EH-YT32E | 32 points, transistor output (sink type), short-circuit protection, Euro-terminal | Y32 | Electric short circuit protection |
| | EH-YTP32E | 32 points, transistor output (source type), short-circuit protection Euro-terminal | Y32 | |
| | EH-YT64 | 64 points, transistor output (sink type), short-circuit protection | Y64 | |
| | EH-YTP64 | 64 points, transistor output (source type), short-circuit protection | Y64 | |
| | EH-YS4 | 4 points, triac output | Y16 | |
| | EH-YS16 | 16 points, triac output | Y16 | |
| Analog input module | EH-AX44 | 4 ch. Current input (0 - 3 ch.), 4 to 20 mA 4 ch. Voltage input (4 - 7 ch.), 0 to 10 VDC | X8W | |
| | EH-AX8V | 8 ch. Current output (0 - 7ch.), 0 to 10 VDC | X8W | |
| | EH-AX8H | 8 ch. Current output (0 - 7ch.), -10 to 10 VDC | X8W | |
| | EH-AX8I | 8 ch. Current input (0 - 7ch.), 4 to 20 mA | X8W | |
| | EH-AX8IO | 8 ch. Current input (0 - 7ch.), 0 to 22 mA | X8W | |
| Analog output module | EH-AY22 | 2 ch. Voltage output (0 - 1ch.), 0 to 10 VDC 2 ch. Current output (2 - 3 ch.), 4 to 20 mA | Y8W | |
| | EH-AY2H | 2 ch. Voltage output (0 - 1ch.), -10 to 10 VDC | Y8W | |
| | EH-AY4V | 4 ch. Voltage output (0 - 3 ch.), 0 to 10 VDC | Y8W | |
| | EH-AY4H | 4 ch. Voltage output (0 - 3 ch.), -10 to 10 VDC | Y8W | |
| | EH-AY4I | 4 ch. Current output (0 - 3 ch.), 4 to 20 mA | Y8W | |
| RTD Input Module | EH-PT4 | 4 ch. RTD input, Signed 15 bits, Pt 100 Ω /Pt 1000 Ω | X4W | |
| High function module | EH-CU | 2 ch. High speed counter input, maximum frequency of 100 kHz, 1/2-phase switchable, 4-point open collector output | FUN0 | |
| | EH-CUE | 1 ch. High speed counter input, maximum frequency of 100 kHz, 1/2-phase switchable, 2-point open collector output | FUN0 | |
| | EH-POS | Positioning module (Single Axis) | 4W/4W | |
| | EH-POS4 *5 | Positioning module (4 Axes) | 4W/4W | |
| | EH-ETH *5 | Ethernet module IEEE802.3 standard, 10BASE-T, 2 units/CPU | COMM | On slot 0-2 of EH-BS3/5/8. |
| | EH-LNK *5 | CPU link module (coaxial), Up to 2 units/CPU | LINK | |
| | EH-OLNK *5 | CPU link module (optical fiber), 2 units/CPU | LINK | On slot 0-7 of EH-BS3A/5A/8A/11A. |
| | EH-RMD *6 | Device Net master module 256/256 words in/output (LINK), Up to 2 units/CPU (LINK), 64 words in/output total (Remote2), Up to 4 units/CPU (Remote2) | LINK / Remote2 | |
| | EH-RMP *4 | PROFIBUS-DP master module 256/256 words in/output, Up to 2 units/CPU | LINK | |
| | EH-IOCD | Device Net slave module 256/256 words in/output | — | Fixed position on CPU slot *2 |
| | EH-IOCP | PROFIBUS-DP slave controller, 208 words in/output total | — | Fixed position on CPU slot *2 |
| Dummy module | EH-DUM | Module for open slots | Empty 16 | |

*1: I/O points in case of 64 points module used.

*2: Mounted on special fixed position.

*3: Short circuit protection is effective from May 2001 production or later (MFG No.01E**)

*4: Supported by CPU308(A)/316(A)/448(A)/516/548

*5: Supported by CPU308A/316A/448(A)/516/548

*6: Supported by CPU308(A)/316(A)/448(A)/516/548 for CPU LINK assignment. Supported by CPU516/548 for REMOTE2 assignment.

(2) Peripheral devices

Table 4.2 List of peripheral devices

| Product | Form | Specification | Remarks |
|---------------------------------------|------------|---|---------|
| Portable graphic programmer | PGM-GPH | Portable graphic programmer with a 2 m (6.56 ft.) connection cable (PGCB02H) | *7 |
| Command language programmer | PGM-CHH | Command language programmer | |
| Graphic input device support software | HL-PC3 | Ladder diagram/Command language editor LADDER EDITOR (for PC98 series) with CPU connection cable | |
| | HL-AT3E | Ladder diagram/Command language editor LADDER EDITOR (for PC/AT compatible personal computer) | |
| | HLW-PC3 | Ladder diagram/Command language editor LADDER EDITOR (for Windows® 95/NT 4.0) | |
| | HLW-PC3E | Ladder diagram/Command language editor (English version) LADDER EDITOR (for Windows® 95/98/NT) | |
| | HLW-PCR | Ladder diagram/Command language editor LADDER EDITOR (for Windows® 95/NT 4.0), CD-ROM Version. | |
| | HLW-PC3L05 | Ladder diagram/Command language editor LADDER EDITOR (for Windows® 95/NT 4.0), License Pack: 5 users | |
| | HLW-PC3L10 | Ladder diagram/Command language editor LADDER EDITOR (for Windows® 95/NT 4.0), License Pack: 10 users | |
| | HLW-PC3L30 | Ladder diagram/Command language editor Ladder Editor (for Windows® 95/NT 4.0), License Pack: 30 users | |
| | HLW-PC3L50 | Ladder diagram/Command language editor Ladder Editor (for Windows® 95/NT 4.0), License Pack: 50 users | |
| | Pro-H | IEC61131-3 | |

Note: MS-DOS, Windows® 95, and Windows NT® are registered trademarks of Microsoft Corporation in the United States.
 HI-LADDER (attached to GPCL01H) can also be used.

*7: Don't use the option box (model name: PGMIF1H) for the portable graphic programmer.
 Its high current may cause the EH-150 system to break down.

(3) Connection cable

Table 4.3 List of connection cables

| Product | Model name | Specification | Remarks |
|--|------------|---|---------|
| Cable for connecting basic base to I/O controller | EH-CB10/A | Length: 1 m (3.28 ft.) (Basic/exp. base - I/O controller) | *8 |
| | EH-CB05A | Length: 1 m (1.64 ft.) (Basic/exp. base - I/O controller) | |
| | EH-CB20A | Length: 1 m (6.56 ft.) (Basic/exp. base - I/O controller) | |
| I/O connector cable for EH-POS | EH-POC10 | Length: 1m (3.28 ft.) | |
| | EH-POC20 | Length: 2m (6.56 ft.) | |
| | EH-POC50 | Length: 5m (16.4 ft.) | |
| Conversion cable for connecting peripheral devices | EH-RS05 | Length: 0.5 m (19.69 in.) | *9 |
| For portable graphic programmer, command language programmer | PGCB02H | Length: 2 m (6.56 ft.), between CPU and programmer | |
| Peripheral devices | GPCB02H | Length: 2 m (6.56 ft.), between CPU and graphic input device | |
| | GPCB05H | Length: 5 m (16.40 ft.), between CPU and graphic input device | |
| | GPCB15H | Length: 15 m (49.22 ft.), between CPU and graphic input device | |
| | CBPGB | Length: 2 m (6.56 ft.), between graphic input device and printer | |
| | LP100 | Length: 2 m (6.56 ft.), between graphic input device and kanji printer | |
| | KBADPTH | Length: 15 m (49.22 ft.), between graphic input device and JIS keyboard | |
| | PCCB02H | Length: 2 m (6.56 ft.), between CPU and PC98 series | |
| | WPCB02H | Length: 2 m (6.56 ft.), between CPU and PC98 series (25-pin) | *10 |
| | WVCB02H | Length: 2 m (6.56 ft.), between CPU and DOS/V (9-pin) | *10 |
| | EH-VCB02 | Length: 2 m (6.56 ft.), between CPU (modular jack type) and DOS/V (9-pin) | *10 |

*8: EH-CB10 (without A version) can not be used with 2nd - 4th expansion bases.

*9: Required when connecting to programmer peripheral device (including PC98, DOS/V, and PC/AT compatibles)

*10: EH-VCB02, WPCB02H and WVCB02H are cables for LADDER EDITOR for Windows®

(4) . Save wiring equipment

Table 4.4 List of save wiring equipment





| Product | Model name | Specification | Remarks |
|--------------------------------|-------------|---|---------|
| Distributed I/O units | RDX16D | 16 points input, 24V DC, based on DeviceNet. | |
| | RDY16T | 16 points, transistor output 0.3 A (sink type), based on DeviceNet. | |
| | RDY16R | 16 points input, relay output 2 A DC, based on DeviceNet. | |
| Relay terminal block | HPX7DS-40V6 | Relay terminal for 32 / 64 points I/O module | |
| Cable for relay terminal block | EH-CBM01W | Length: 1m, both edges connector. | |
| | EH-CBM03W | Length: 3m, both edges connector. | |
| | EH-CBM05W | Length: 5m, both edges connector. | |
| | EH-CBM10W | Length: 10m, both edges connector. | |
| Cable for I/O wiring | EH-CBM01 | Length: 1m, one edge connector, (for 32 / 64 I/O module.) | |
| | EH-CBM03 | Length: 3m, one edge connector, (for 32 / 64 I/O module.) | |
| | EH-CBM05 | Length: 5m, one edge connector, (for 32 / 64 I/O module.) | |
| | EH-CBM10 | Length: 10m, both ends connector, (for 32 / 64 I/O module.) | |

(5) Others



Table 4.5 List of others

| Form | Usage | Remarks |
|---------|---|--|
| LIBAT-H | Lithium battery | The battery is used in common with the H series. |
| EH-LCN | L-type connector for the turn of coaxial connector. (for coaxial type CPU link module.) | |



4.2 CPU Module

| Name and function of each part | | Type | EH-CPU104/A | EH-CPU516 |
|--|--|--|------------------------------------|-----------|
|  | | EH-CPU208/A | EH-CPU548 | |
| | | EH-CPU308/A | | |
| | | EH-CPU316/A | | |
| | | EH-CPU448/A | | |
| Weight | | Approx. 0.18 kg (0.4 lb.) (EH-CPU448 weights approx. 0.20 kg (0.44 lb.).) | | |
| Current consumption | | 400 mA | | |
| Dimensions (mm (in.)) | |  | | |
|  | |  <u>Drawing of CPU module bottom</u> | | |
| No. | Name | Function | Remark2s | |
| 1] | RUN lamp | Indicates that the CPU is running. | Green | |
| 2] | ERR lamp | Indicates that the CPU is generating an abnormal. | Red | |
| 3] | Reset switch for the power failure memory protection | Clears the area designated for power failure memory. | Enabled only during a stoppage | |
| 4] | Serial port 1 | Connects a programming device, etc.. | Refer to the detailed explanation. | |
| 5] | Serial port 2 | Connects a programming device, etc.. | Refer to the detailed explanation. | |
| 6] | Front cover | This is used when operating the RUN switch or replacing the battery. | | |
| 7] | Lock button | This is used when removing the module from the base unit. | | |
| 8] | RUN switch | Used to control the running status. | | |
| 9] | Battery holder | Used for putting a battery in. | | |
| 10] | Battery | Retains power failure memory data or clock data. | | |
| 11] | Battery connector | Used to connect a battery. | | |
| 12] | Mode setting DIP-switch | Sets the operating status for the serial port, etc. | | |
| 13] | Port setting toggle-switch | Switches the operating status for the serial port 2. | | |
| 14] | Optional slot | Memory board is loaded. | | |
| 15] | Binding screw hole | Fix the memory board with binding screw. | | |

| No. | Item | Detailed explanation | Remarks | | | | | | |
|--|--|--|--|--|------------------------------|--------------------------|-------|--------|--|
| | Explanation of operation | Operations are performed according to the contents of the program created by the user. The programming device connected to the CPU module communication port writes and reads the user program. Memory is installed inside the CPU module in which the user program and internal output information are stored. The internal output data and clock information can be backed up with the battery. (The clock function is not available with the EH-CPU104) | | | | | | | |
| 1] | RUN lamp | This indicates the CPU is running and lights up during normal operation. | The lamp is green. | | | | | | |
| 2] | ERR lamp | The error contents can be determined by the combination of lighting and flashing of the ERR and RUN lamps. For details, refer to “Chapter 12 The Error Code List”. | The lamp is red. | | | | | | |
| 3] | Reset switch for the power failure memory protection | Pressing this switch when the operation is stopped, clears data from the area designated for power failure memory. The program information is retained as is. | | | | | | | |
| 4] | Serial port 1 | Can be switched to use as a dedicated port or general-purpose port using the mode setting switch. It is also equipped with modem control functions. (The modem control function is not available with the EH-CPU104(A)) | | | | | | | |
| 5] | Serial port 2 | Can be used as a dedicated port. A programming device can be connected and tasks such as CPU programming or monitoring can be performed. | | | | | | | |
| 6] | Front cover | Open and close the front cover when operating the RUN switch or replacing the battery. Keep the cover closed while the module is running. Also, when the cover is open, do not touch the printed wiring board with your hands. | | | | | | | |
| 7] | Lock button | When dismounting the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | | | | | | | |
| 8] | RUN switch | To designate run status, push this switch lever to the "RUN" side. The following conditions are necessary for the module to run correctly: 1. A user program must be written to the module. 2. When a run definition input has been set, the designated input must be on. 3. There should be no sources of errors. 4. The mode setting switch is set to the normal run status. 5. When the mode setting switch is set to "REMOTE," there should be a run start command from the personal computer, etc. that is connected. Also, to stop operation, set this switch lever to the "STOP" side. | | | | | | | |
| 9] 10] 11] | Battery holder Battery Battery connector | The module is shipped with the battery connector disconnected so as to prevent unnecessary consumption of battery during distribution or storage. When using the CPU module, check the battery and connect the lead connector on the battery to the mating connector on the circuit board. 1. Clock data is retained by battery power and thus has not been written to the clock element initially. When using the clock function, first write the clock data to the clock element. (The EH-CPU104/104A does not provide clock function.) See Chapter 11 for procedures for setting the clock data. 2. Use the reference table below to determine the remaining life of battery. As a guideline, replace the battery every two years even when the total power failure time is less than the guaranteed value shown in the table. <table><tr><th colspan="2">Battery life (Total power failure time) [Hr]</th></tr><tr><th>Guaranteed value (MIN) @55°C</th><th>Actual value (MAX) @25°C</th></tr><tr><td>2,000</td><td>32,000</td></tr></table> | Battery life (Total power failure time) [Hr] | | Guaranteed value (MIN) @55°C | Actual value (MAX) @25°C | 2,000 | 32,000 | |
| Battery life (Total power failure time) [Hr] | | | | | | | | | |
| Guaranteed value (MIN) @55°C | Actual value (MAX) @25°C | | | | | | | | |
| 2,000 | 32,000 | | | | | | | | |

| No. | Item | Detailed explanation | | | | | | | | | | Remarks | |
|-----|---------------------|--|--|----------------------|------------|-----|---|-----|-----|----|-----|--|---|
| 12] | Mode setting switch | The following operating modes are designated by setting this switch. Even if the switch setting is changed while the module is energizing, the operating mode will not change. To switch operating modes, turn the power off, then do the settings correctly. (When DR signal turns on, modifying the baud rate.) | | | | | | | | | | | |
| 13] | PHL switch | | | | | | | | | | | | |
| | | DIP switch | | | 1 | 2 | 3 | 4 | 5 | 6 | PHL | | |
| | | RUN/STOP | | Remote | ON | - | - | - | - | - | - | | |
| | | | | RUN switch | | off | - | - | - | - | - | - | |
| | | Port 1 | | Dedicated port * | 4,800 bps | - | - | ON | ON | ON | - | - | |
| | | | | | 9,600 bps | - | - | off | ON | ON | - | - | |
| | | | | | 19,200 bps | - | - | ON | off | ON | - | - | |
| | | | | | 38,400 bps | - | - | off | off | ON | - | - | |
| | | | | General purpose port | | | - | off | - | - | off | - | - |
| | | | | Modem mode | | | - | ON | - | - | off | - | - |
| | | Port 2 | | Dedicated port * | 4,800 bps | - | - | - | - | - | off | off | |
| | | | | | 9,600 bps | - | - | - | - | - | ON | off | |
| | | | | | 19,200 bps | - | - | - | - | - | off | ON | |
| | | | | | 38,400 bps | - | - | - | - | - | ON | ON | |
| | | Switch 7 and 8 should be always off. | | | | | | | | | | | |
| | | PHL switch ON  OFF  When PHL switch is on, +12V comes out from pin 4 of the port 1. | | | | | | | | | | | |
| | | Default setting of DIP switch is all off. (Port 1 : General purpose port, Port2 : 4800 bps dedicated port) * For programming or HMI panel communication | | | | | | | | | | | |
| 14] | Optional slot | The optional memory board is inserted in this slot. Install the memory board in the slot by sliding it in along the guide. <ul style="list-style-type: none">When installing the memory board First install the CPU module in the base unit, then insert the memory board in the optional slot. After installing the memory board, be sure to fix it securely using the binding screws (supplied with the memory board).When removing the memory board With the memory board still attached to the CPU module, remove the entire CPU module from the base unit Note on installing the memory board Do not install the CPU module in the base unit with the memory board still attached to the CPU module. Doing so may cause inappropriate connection at the base connector on the memory board. | | | | | | | | | | Memory board is supported by EH-CPU308(A)/316(A)/448(A)/516/548. | |
| 15] | Binding screw hole | | | | | | | | | | | | |

4.3 Memory Board

| Name and function of each part | | Type | EH-MEMP |
|---|----------------|-----------------------------|---|
|  | | EH-MEMD | |
| | | Weight | Approx. 0.05 kg (0.11 lb.) |
| | | Dimensions (mm(in.)) | |
| | | |  |
| No. | Name | Function | Remarks |
| 1] | DIP switch | Mode setting. | |
| 2] | Base connector | Connector with base unit. | |
| 3] | Metal clip | Screw bracket for CPU case. | |

Memory board specifications

| item | EH-MEMP | EH-MEMD |
|---|--|---------------|
| Program memory size | 48 kstep max. | 16 kstep max. |
| Data memory size | - | 384 kwords |
| Program copy (CPU→MEMP/D) * ¹ | ✓ | ✓ |
| Program copy (CPU←MEMP/D) * ¹ | ✓ | ✓ |
| Program verify (CPU←→MEMP/D) * ¹ | ✓ | ✓ |
| Data logging * ² | - | ✓ |
| Memory type | FLASH (100,000 times overwriting max.) | |

*¹ Selected by dip switch. It is effective only at power on.

*² EH-MEMD supports data logging (writing), reading and deleting.



When using the EH-MEMD for the first time, the RUN LED will rapidly flash (at 250 ms intervals) for Approx. 3 seconds for initialization of the memory board at power on.


* Since user program is kept in FLASH memory in CPU module, the memory board is not necessary in normal use. The memory board is useful when program copying and data logging.

* Be sure to turn off the power of the PLC when mounting or removing the memory board from the CPU module. When mounting to the CPU module, be sure to fix to the CPU module case by binding screw (M3 × 4) as attached. Additionally, do not install the CPU module in the base unit with the memory board attached. Otherwise, this could be cause of mal function due to bad connection.
When removing, remove whole CPU module at first and then lift out the memory board.

* Program and data are kept without power supplied because of flash memory. Max. data overwriting is approx. 100,000 times.




4.4 I/O controller



| Name and function of each part | | | Type | EH-IOC |
|---|--|--|--|---------------------------|
|  | | | | EH-IOCH |
| | | | Weight | Approx. 0.14 kg (0.31 lb) |
| | | | Current consumption | Approx. 30 mA (IOC) |
| | | | | Approx. 80 mA (IOCH) |
| | | | Dimensions (mm (ic.)) | |
| | | |  | |

| No. | Name | Function |
|-----|--------------------------|---|
| [1] | Lock button | When dismantling the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10mm) |
| [2] | Connector for exp. cable | Connector for expansion cable. |
| [3] | Unit number switch | <p>Rotary switch for unit number. Be sure to set 1 to 4 for expansion bases from CPU side.</p> <p><u>Note that other unit number than 1 to 4 may cause mal output because of undefined address.</u></p> <p>Since CPU reads always the switch information, be sure to set after power off. Expandability depends on CPU types as below.</p>  |

| No. | Item | Details | Remarks |
|----------|------|---|--|
| Function | | <p>The in/output controller sends output signal from CPU module to output modules on the exp. base, and reads input signals from input modules on the exp. base and sends back to the CPU module.</p> <p>This module is mounted on the next right to power supply module.</p> <p>EH-IOC and IOCH cannot be mixed in one system.</p> | EH-CPU104 does not support expansion unit. |


4.5 AC Power Module

| Name and function of each part | | Type | EH-PSA |
|---|-----------------------|--|----------------------------|
| | | Weight | Approx. 0.36 kg (0.79 lb.) |
| | | Dimensions (mm (in.)) | |
|  | |  | |
|  | | | |
| No. | Name | Function | Remarks |
| 1] | POWER lamp | This indicates that the AC power is supplied. | Green |
| 2] | Lock button | This is used when removing the power module from a base unit. | |
| 3] | Front cover | This is used when wiring. | |
| 4] | Front cover set screw | This is used to fix the front cover. When fixing is necessary, use M3 × 6 mm (0.24 in.) set screws. | |
| 5] | Power terminal block | This is used when power is supplied externally, for 24 V output wiring, and for the grounding wiring. | |

| No. | Item | Detailed explanation | Remarks | | | | | | | | | | | | | | | | | | | |
|-----------------------|---------------------------------------|--|--------------------|--|--|---|--------------------|-----------------------------------|---|----------------------|---|---------|--------------------------|---|----------|-----------------------------|---|----------|---|-----------------------|------------------------------|--|
| Operation explanation | | <p>Converts power supplied externally into the power (5 V DC) that can be used inside the EH-150. Also, it prepares power (24 V DC) for driving relays, etc. 100 V to 240 V AC can be used for the external supply voltage.</p> <p>When using the 24 V DC after conversion, connect it externally.</p> <p>The operating status can be confirmed with the POWER lamp on the front of the module.</p> <p>Refer to the specification table for the types of protective functions.</p> | | | | | | | | | | | | | | | | | | | | |
| 1] | POWER lamp | <p>Lighting : Power is supplied properly.</p> <p>Off : Power is not supplied or 24VDC output is shorted.</p> <p>Flashing: Output current over loaded</p> | The lamp is green. | | | | | | | | | | | | | | | | | | | |
| 2] | Lock button | When dismounting the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | | | | | | | | | | | | | | | | | | | | |
| 3] 4] | Front cover Front cover set screws | <p>Open and close the cover when performing cable wiring. During operation, keep the front cover closed. When opening the cover, shut the power off first to avoid getting an electric shock.</p> <p>When fixing is necessary, use M3 × 6 mm (0.24 in.) screws for the set screws.</p> | | | | | | | | | | | | | | | | | | | | |
| 5] | Power terminal block | <table><tr><td colspan="3">Upper side</td></tr><tr><td>1</td><td>24 V DC (+) output</td><td rowspan="2">Connect these when using 24 V DC.</td></tr><tr><td>2</td><td>24 V DC (GND) output</td></tr><tr><td>3</td><td>(Empty)</td><td>Do not connect anything.</td></tr><tr><td>4</td><td>AC input</td><td rowspan="2">Connect input power supply.</td></tr><tr><td>5</td><td>AC input</td></tr><tr><td>6</td><td>FE (functional earth)</td><td>Connect to a class D ground.</td></tr></table> <p>Lower side</p> <p>The recommended crimp terminal is indicated below.</p> <div><div></div><div>(Recommended)</div></div> <div><div></div><div>Care must be exercised when handling the terminal since it may fall off if the screw is loose.</div></div> <p>Unit: mm (in.)</p> | Upper side | | | 1 | 24 V DC (+) output | Connect these when using 24 V DC. | 2 | 24 V DC (GND) output | 3 | (Empty) | Do not connect anything. | 4 | AC input | Connect input power supply. | 5 | AC input | 6 | FE (functional earth) | Connect to a class D ground. | |
| Upper side | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 24 V DC (+) output | Connect these when using 24 V DC. | | | | | | | | | | | | | | | | | | | | |
| 2 | 24 V DC (GND) output | | | | | | | | | | | | | | | | | | | | | |
| 3 | (Empty) | Do not connect anything. | | | | | | | | | | | | | | | | | | | | |
| 4 | AC input | Connect input power supply. | | | | | | | | | | | | | | | | | | | | |
| 5 | AC input | | | | | | | | | | | | | | | | | | | | | |
| 6 | FE (functional earth) | Connect to a class D ground. | | | | | | | | | | | | | | | | | | | | |




Specification table



| Item | Specifications | |
|---------------------------------------|--|---------|
| Rated output voltage | 5 V DC | 24 V DC |
| Maximum DC output current | 3.8 A | 0.4 A |
| Efficiency | 65% or more (Load of 5 V 3.8 A, 24 V 0.4 A after energizing for 5 minutes at room temperature and humidity) | |
| Input voltage range | 85 to 264 V AC wide range | |
| Input current | 1 A or less (85 to 264 V AC) | |
| Input rush current | 50 A or less (Ta=25°C), 100 A or less (Ta=55°C) | |
| Output overcurrent protection | Output short circuit protection | |
| Instantaneous power failure guarantee | 10 ms or more (85 to 100 V AC), 20 ms (Exceed 100 V AC to 264 V AC) | |
| Input leak current | 3.5 mA or less (60 Hz, 264 V AC) | |
| Operating ambient temperature | 0 to 55°C (with rated load) | |
| Operating ambient humidity | 20% to 90% RH (Non condensing) | |
| Storage ambient temperature | -10 to 75°C | |
| Storage ambient humidity | 10% to 90% RH (Non condensing) | |
| Dielectric withstand voltage | 1 minute at 1,500 V AC between (AC input) and (DC output) 1 minute at 750 V AC between (DC output) and (FE) | |
| Insulation resistance | 20 M Ω or more (500 V DC) (1) Between AC input and FE (2) Between AC input and DC output | |
| Vibration resistance | Conforms to JIS C 0911 (16.7 Hz double amplitude 3 mm (0.12 in.) X, Y and Z each direction) Conforms to JIS C 0040 (10 to 57 Hz single amplitude 0.075 mm) (57 to 150 Hz constant acceleration 9.8 m/s ²) | |
| Shock resistance | Conforms to JIS C 0912 (10 G in X, Y and Z directions) Conforms to JIS C 0040 (15 G in X, Y and Z directions) | |



*1: The POWER lamp will not be lit when the fuse is blown. The module must be repaired. The fuse may not be replaced by the end user.


4.6 DC Power Module

| | | | |
|---|-----------------------|--|----------------------------|
| Name and function of each part | | Type | EH-PSD |
| | | Weight | Approx. 0.28 kg (0.62 lb.) |
| | | Dimensions (mm (in.)) | |
|  | |  | |
|  | | | |
| No. | Name | Function | Remarks |
| 1] | POWER lamp | This indicates that the DC power is supplied. | Green |
| 2] | Lock button | This is used when removing the power module from a base unit. | |
| 3] | Front cover | This is used when wiring. | |
| 4] | Front cover set screw | This is used to fix the front cover. When fixing is necessary, use M3 × 6 mm (0.24 in.) set screws. | |
| 5] | Power terminal block | This is used when power is supplied externally, and for the grounding wiring. | |

| No. | Item | Detailed explanation | | Remarks | | | | | | | | |
|-----------------------|---------------------------------------|--|--|--------------------|-------------------|-----------------------------|---|-------------------|---|-----------------------|---|---|
| Operation explanation | | Converts 24 V DC power supplied externally into the power (5 V DC) that can be used inside the EH-150. 21.6 V to 26.4 V DC can be used for the external power voltage. Connect the power supply (24 V DC) to drive relays, etc., directly with the external power supply. The operating status can be confirmed with the POWER lamp on the front of the module. | | | | | | | | | | |
| 1] | POWER lamp | Lighting : Off : | Power is supplied properly. Power is not supplied or 24VDC output is shorted or over voltage. | The lamp is green. | | | | | | | | |
| 2] | Lock button | When dismantling the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | | | | | | | | | | |
| 3] 4] | Front cover Front cover set screws | Open and close the cover when performing cable wiring. During operation, keep the front cover closed. When opening the cover, shut the power off first to avoid getting an electric shock. When fixing is necessary, use M3 × 6 mm (0.24 in.) screws for the set screws. | | | | | | | | | | |
| 5] | Power terminal block | <div>Upper side</div> <table><tr><td>1</td><td>24 V DC (+) input</td><td rowspan="2">Connect input power supply.</td></tr><tr><td>2</td><td>24 V DC (–) input</td></tr><tr><td>3</td><td>FE (functional earth)</td><td>Connect to a class D ground In order to comply with the CE marking, connect to 24 V DC (–). *1</td></tr></table> <div>Lower side</div> <p>The recommended crimp terminal is indicated below.</p> <div>(Recommended)</div> <div>{ Care must be exercised when handling the terminal since it may fall off if the screw is loose.</div> <div>Unit: mm (in.)</div> | | 1 | 24 V DC (+) input | Connect input power supply. | 2 | 24 V DC (–) input | 3 | FE (functional earth) | Connect to a class D ground In order to comply with the CE marking, connect to 24 V DC (–). *1 | *1:When performing insulation resistance measurements or dielectric withstand voltage measurements, always remove the connection between the FE and 24 VDC (–). |
| 1 | 24 V DC (+) input | Connect input power supply. | | | | | | | | | | |
| 2 | 24 V DC (–) input | | | | | | | | | | | |
| 3 | FE (functional earth) | Connect to a class D ground In order to comply with the CE marking, connect to 24 V DC (–). *1 | | | | | | | | | | |



Specification table

| Item | Specifications |
|---------------------------------------|--|
| Rated output voltage | 5 V DC |
| Maximum DC output current | 3.8 A |
| Efficiency | 70% or more (Load of 5 V DC 3.8 A) |
| Input voltage range | 21.6 to 26.4 V DC |
| Input current | 1.25 A or less (with 24 V DC) |
| Input rush current | 50 A or less (Ta=25°C), 100 A or less (Ta=55°C) |
| Output overcurrent protection | Output short circuit protection |
| Instantaneous power failure guarantee | 1 ms or more (21.6 to 26.4 V DC) |
| Operating ambient temperature | 0 to 55°C (with rated load) |
| Operating ambient humidity | 20% to 90% RH (Non condensing) |
| Storage ambient temperature | -10 to 75°C |
| Storage ambient humidity | 10% to 90% RH (Non condensing) |
| Dielectric withstand voltage | 1 minute at 1,500 V AC between DC input and FE |
| Insulation resistance | 20 M Ω or more (500 V DC) (Between DC input and FE) |
| Insulation type | No insulation |



*2: The POWER lamp will not light when the fuse is blown. The module must be repaired. The fuse may not be replaced by end users.



4.7 Base Unit



| Name and function of each part | | Type | EH-BS3(A) approx. 0.22kg (0.48 lb) | | | | | | | | | | | | | | | | |
|---|-----------------------|---|--|--|-----------------------|-------------------------|-----------|--------------|------------|-----------|---------------|-------------|-----------|---------------|-------------|------------|---------------|-------------|--|
|  | | (Weight) | EH-BS5(A) approx. 0.28 kg (0.62 lb.) | | | | | | | | | | | | | | | | |
| | | EH-BS8(A) approx. 0.36 kg (0.79 lb.) | | | | | | | | | | | | | | | | | |
| | | EH-BS11(A) approx. 0.4 kg (0.88 lb.) | | | | | | | | | | | | | | | | | |
| | | Current consumption | Approx. 200 mA | | | | | | | | | | | | | | | | |
| | | Dimensions (mm (in.)) |  | | | | | | | | | | | | | | | | |
| | | | <table><tr><th></th><th>L1 (Outer dimensions)</th><th>L2 (Mounted dimensions)</th></tr><tr><td>EH-BS3(A)</td><td>222.5 (8.76)</td><td>207 (8.15)</td></tr><tr><td>EH-BS5(A)</td><td>282.5 (11.12)</td><td>267 (10.51)</td></tr><tr><td>EH-BS8(A)</td><td>372.5 (14.67)</td><td>357 (14.06)</td></tr><tr><td>EH-BS11(A)</td><td>462.5 (18.21)</td><td>447 (17.60)</td></tr></table> | | L1 (Outer dimensions) | L2 (Mounted dimensions) | EH-BS3(A) | 222.5 (8.76) | 207 (8.15) | EH-BS5(A) | 282.5 (11.12) | 267 (10.51) | EH-BS8(A) | 372.5 (14.67) | 357 (14.06) | EH-BS11(A) | 462.5 (18.21) | 447 (17.60) | |
| | L1 (Outer dimensions) | L2 (Mounted dimensions) | | | | | | | | | | | | | | | | | |
| EH-BS3(A) | 222.5 (8.76) | 207 (8.15) | | | | | | | | | | | | | | | | | |
| EH-BS5(A) | 282.5 (11.12) | 267 (10.51) | | | | | | | | | | | | | | | | | |
| EH-BS8(A) | 372.5 (14.67) | 357 (14.06) | | | | | | | | | | | | | | | | | |
| EH-BS11(A) | 462.5 (18.21) | 447 (17.60) | | | | | | | | | | | | | | | | | |
| Communication slot (special slot for communication module) | | | | | | | | | | | | | | | | | | | |
| EH-BS3, 5, 8 | | Slot 0-2 | | | | | | | | | | | | | | | | | |
| EH-BS3A | | Slot 0-2 | | | | | | | | | | | | | | | | | |
| EH-BS5A | | Slot 0-4 | | | | | | | | | | | | | | | | | |
| EH-BS8A | | Slot 0-7 | | | | | | | | | | | | | | | | | |
| EH-BS11A | | Slot 0-7 (Not allowed on slot 8, 9, A) | | | | | | | | | | | | | | | | | |

| No. | Name | Function | | Remarks |
|-----|-------------------------------------|--|-------------------------------------|---|
| 1] | Connector for power module | This is the connector for loading the power module. | | |
| 2] | Connector for CPU module | This is the connector for loading the CPU module. When the unit is used as an expansion base, this becomes the connector for loading the I/O controller. | | |
| 3] | Connector for I/O module | This is the connector for loading the I/O module. | | |
| | | Type | Number of I/O modules to be mounted | |
| | | EH-BS3(A) | 3 | |
| | | EH-BS5(A) | 5 | |
| | | EH-BS8(A) | 8 | |
| | EH-BS11A | 11 | | |
| 4] | Expansion cable connector | Connector for the expansion cable. | | EH-CPU104(A) is not support expansion unit. |
| 5] | Mounting holes (4 points) | These are used when the base unit is attached to a panel, etc. Use M4 × 20 mm (0.79 in.) screws. | | |
| 6] | Mounting hook for DIN rail | This is used when attaching the unit to a DIN rail. | | |
| 7] | Cover for expansion cable connector | This cover is used for protecting the expansion cable connector when it is not used. | | |

| No. | Item | Details |
|-----------------------|------|---|
| Operation description | | This is the basic unit for loading all the modules. Using the base unit, power is supplied from the power module to each of the other modules. Also, signals are sent to each module from the CPU module or the I/O controller. Select the base unit according to the number of I/O modules that are used. |

4.8 Input Module



| Name and function of each part  | | Type | EH-XD8 EH-XD16, XDL16 EH-XA16 EH-XAH16 |
|---|----------------|--|--|
| | | Weight | Approx. 0.16 kg (0.35 lb.) (EH-XD**) Approx. 0.18 kg (0.4 lb.) (EH-XA**) |
| | | Dimensions (mm (in.)) |  |
| | | | |
| No. | Name | Function | Remarks |
| 1] | LED cover | This is the cover for the LED that displays the input status. When the input signal turns on, the LED for the relevant number lights up. The LED only lights when the module is energized. | |
| 2] | Lock button | When dismantling the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | |
| 3] | I/O cover | This is the cover attached to the terminal block area | |
| 4] | Terminal block | This is the terminal block for connecting input signals. The terminal block is removable. | |

| No. | Item | Detailed explanation | Remarks |
|-----------------------|------|--|---------|
| Operation explanation | | This module inputs digital signals. The LED's light up while the corresponding digital signal is ON. The CPU reads the status of the mounted modules. If the status accords with actual I/O configuration in the user program, the CPU inputs digital signals according to the user program. | |
| Terminal block | | <p>The screws for the terminal block are M3 screws. Use a crimp terminal that fits the screw diameter. The maximum thickness of the cable should be only up to 0.75 mm². (If you attach two crimp terminals to the same terminal, use a cable with the thickness of 0.5 mm².)</p> <p>The recommended crimp terminal is indicated below.</p> <div style="text-align: center;">  (Recommended) </div> <div style="text-align: center;">  Care must be exercised when handling the terminal since it may fall off if the screw is loose. </div> <p style="text-align: center;">Unit: mm (in.)</p> | |

Specification table

| Item | | Specification | | |
|---------------------------------------|-------------|---|--|---------------------------|
| Type | | EH-XD8 | EH-XD16 | EH-XDL16 |
| Input specification | | DC input | | |
| Input voltage | | 24 V DC | | |
| Allowable input voltage range | | 19.2 to 30 V DC | | |
| Input impedance | | Approx. 3.5 k Ω | Approx. 5.9 k Ω | |
| Input current | | Approx. 6.9 mA | Approx. 4.0 mA | |
| Operating voltage | ON voltage | 15 V or more | | |
| | OFF voltage | 5 V or less | | |
| Input lag | OFF → ON | 5 ms or less (4 ms TYP) | | 16 ms or less (13 ms TYP) |
| | ON → OFF | 5 ms or less (4 ms TYP) | | 16 ms or less (13 ms TYP) |
| Number of input points / module | | 8 points / module | 16 points / module | |
| Number of input points / common | | 8 points / common (2 common terminals *) | 16 points / common (2 common terminals *) | |
| Polarity | | None | | |
| Insulation system | | Photocoupler insulation | | |
| Input display | | LED (green) | | |
| External connection | | Removable type screw terminal block (M3) | | |
| Internal current consumption (5 V DC) | | Approx. 30 mA | Approx. 50 mA | |
| I/O assignment | | X16 | | |




* Common terminals are connected internally.

| Terminal layout | | Diagram of internal circuit | |
|---|-----|--|------------|
| | No. | Signal name | |
| | | EH-XD8 | EH-XD(L)16 |
|  | 1] | 0 | 0 |
| | 2] | 1 | 1 |
| | 3] | 2 | 2 |
| | 4] | 3 | 3 |
| | 5] | 4 | 4 |
| | 6] | 5 | 5 |
| | 7] | 6 | 6 |
| | 8] | 7 | 7 |
| | 9] | C | C |
| | 10] | NC | 8 |
| | 11] | NC | 9 |
| | 12] | NC | 10 |
| | 13] | NC | 11 |
| | 14] | NC | 12 |
| | 15] | NC | 13 |
| | 16] | NC | 14 |
| | 17] | NC | 15 |
| | 18] | C | C |
| | |  | |

Specification table

| Item | | Specification | |
|---------------------------------------|----------------------|---|---|
| Type | | EH-XA16 | EH-XAH16 |
| Input specification | | AC input | |
| Input voltage | | 100 to 120 V AC | 200 to 240 V AC |
| Allowable input voltage range | | 85 to 132 V AC | 170 to 264 V AC |
| Input impedance | | Approx. 16 k Ω (50 Hz)/ Approx. 13 k Ω (60 Hz) | Approx. 32 k Ω (50 Hz)/ Approx. 27 k Ω (60 Hz) |
| Input current | | 4.8 to 7.6 mA (100 V AC/50 Hz) | 4.3 to 8.0 mA (200 V AC/50 Hz) |
| Operating voltage | ON voltage | 79 V AC | 164 V AC |
| | OFF voltage | 20 V AC | 40 V AC |
| Input lag | OFF \rightarrow ON | 15 ms or less | |
| | ON \rightarrow OFF | 25 ms or less | |
| Number of input points / module | | 16 points / module | |
| Number of input points / common | | 16 points / common (2 common terminals *) | |
| Polarity | | None | |
| Insulation system | | Photocoupler insulation | |
| Input display | | LED (green) | |
| External connection | | Removable type screw terminal block (M3) | |
| Internal current consumption (5 V DC) | | Approx. 50 mA | |
| I/O assignment | | X16 | |

* Common terminals are connected internally.

| Terminal layout | | Diagram of internal circuit | |
|---|-----|--|-------------|
| | | No. | Signal name |
| | | | EH-XA16 |
| | | | EH-XAH16 |
|  | 1] | 0 | 0 |
| | 2] | 1 | 1 |
| | 3] | 2 | 2 |
| | 4] | 3 | 3 |
| | 5] | 4 | 4 |
| | 6] | 5 | 5 |
| | 7] | 6 | 6 |
| | 8] | 7 | 7 |
| | 9] | C | C |
| | 10] | 8 | 8 |
| | 11] | 9 | 9 |
| | 12] | 10 | 10 |
| | 13] | 11 | 11 |
| | 14] | 12 | 12 |
| | 15] | 13 | 13 |
| | 16] | 14 | 14 |
| | 17] | 15 | 15 |
| | 18] | C | C |
| | | EH-XA16 | |
| | |  | |
| | | EH-XAH16 | |
| | |  | |

4.9 32-point Input Module


| | |
|---|--|
| <div><div><div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></</div></div></div></div></div> | |
|---|--|


Specification table

| Item | | Specification |
|---------------------------------------|----------------------|--|
| Type | | EH-XD32 |
| Input specification | | DC input |
| Input voltage | | 24 V DC |
| Allowable input voltage range | | 19.2 to 30 V DC |
| Input impedance | | Approx. 5.6 k Ω |
| Input current | | Approx. 4.3 mA |
| Operating voltage | ON voltage | 15 V or more |
| | OFF voltage | 5 V or less |
| Input lag | OFF \rightarrow ON | 5 ms or less |
| | ON \rightarrow OFF | 5 ms or less |
| Number of input points / module | | 32 points / module |
| Number of input points / common | | 32 points / common (4 common terminals *1) |
| Polarity | | None |
| Insulation system | | Photocoupler insulation |
| Input display | | LED (green) *2 |
| External connection | | Connector |
| Internal current consumption (5 V DC) | | Approx. 60 mA |
| I/O assignment | | X32 |

*1: Common terminals are connected internally.

*2: There are 16 points of LED indication. The indication group is switched by toggle switch.

| Terminal layout | | Diagram of internal circuit | | |
|---|-----|-----------------------------|-----|-------------|
|  | No. | Signal name | No. | Signal name |
| | 1] | 0 | 21] | 16 |
| | 2] | 1 | 22] | 17 |
| | 3] | 2 | 23] | 18 |
| | 4] | 3 | 24] | 19 |
| | 5] | 4 | 25] | 20 |
| | 6] | 5 | 26] | 21 |
| | 7] | 6 | 27] | 22 |
| | 8] | 7 | 28] | 23 |
| | 9] | C | 29] | C |
| | 10] | 8 | 30] | 24 |
| | 11] | 9 | 31] | 25 |
| | 12] | 10 | 32] | 26 |
| | 13] | 11 | 33] | 27 |
| | 14] | 12 | 34] | 28 |
| | 15] | 13 | 35] | 29 |
| | 16] | 14 | 36] | 30 |
| | 17] | 15 | 37] | 31 |
| | 18] | C | 38] | C |
| | 19] | NC | 39] | NC |
| | 20] | NC | 40] | NC |

| | |
|--|--|
| EH-XD32 | |
|  | |

4.10 Euro-terminal 32 points input module



| | | | | | | | | | | | | |
|--|---------------------------|---|--|--------------------|---------------|-----|-----|---------|----|----|----------|--|
| <div><div>Name of each part</div><div><div>2] Lock button</div><div>3] LED indication switch</div><div>ON</div><div>OFF</div><div>1] LED cover</div><div>4] Connectors</div><div>0 1 2 3</div><div>4 5 6 7</div><div>8 9 10 11</div><div>12 13 14 15</div><div>+16</div></div></div> | | Type | EH-XD32E | | | | | | | | | |
| | | | EH-XDL32E | | | | | | | | | |
| | | Weight | 0.15 kg (033 lb.) | | | | | | | | | |
| | | Dimension (mm(in.)) | <div><div><div>30</div><div>100</div></div><div><div>104</div></div></div> | | | | | | | | | |
| | | | | | | | | | | | | |
| No. | Name | Function | Remarks | | | | | | | | | |
| 1] | LED cover | This is the cover for the LED that displays the input status and displayed group. When the input signal turns on, the LED for the relevant number lights up. The LED only lights when the module is energized. | | | | | | | | | | |
| 2] | Lock button | When dismantling the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | | | | | | | | | | |
| 3] | LED display switch | Effective LED group (16 points) is selected by this switch as follows. <div><table><tr><td>SW</td><td>LED <div>+16</div></td><td>Display group</td></tr><tr><td>OFF</td><td>OFF</td><td>0 to 15</td></tr><tr><td>ON</td><td>ON</td><td>16 to 31</td></tr></table></div> | SW | LED <div>+16</div> | Display group | OFF | OFF | 0 to 15 | ON | ON | 16 to 31 | |
| SW | LED <div>+16</div> | Display group | | | | | | | | | | |
| OFF | OFF | 0 to 15 | | | | | | | | | | |
| ON | ON | 16 to 31 | | | | | | | | | | |
| 4] | External wiring connector | A connector for input signals. It is attached to the product. Solid wire 0.5...1.0 mm ² Flexible wire 0.5...1.0 mm ² Insulation stripping length 7mm Cable ferrules cannot be used | Applicable connectors (Manufacturer: Weidmuller) <ul style="list-style-type: none">• Type B2L3.5/20AUOR• Pats No. 175736• Poles 20• Color Orange | | | | | | | | | |

Specification table


| Item | | Specification | |
|---------------------------------------|----------------------|---|---------------|
| Type | | EH-XD32E | EH-XDL32E |
| Input specification | | DC input | |
| Input voltage | | 24 V DC | |
| Allowable input voltage range | | 20.4 to 28.8 V DC | |
| Input impedance | | Approx. 5.6 k Ω | |
| Input current | | Approx. 4.3 mA | |
| Operating voltage | ON voltage | 15 V or more | |
| | OFF voltage | 5 V or less | |
| Input lag | OFF \rightarrow ON | 1 ms or less | 16 ms or less |
| | ON \rightarrow OFF | 1 ms or less | 16 ms or less |
| Number of input points / module | | 32 points / module | |
| Number of input points / common | | 8 points / common (2 common terminals per group *1) | |
| Polarity | | None | |
| Insulation system | | Photocoupler insulation | |
| Input display | | LED (green) *2 | |
| External connection | | Spring type connector (removable) | |
| Internal current consumption (5 V DC) | | Approx. 60 mA | |
| I/O assignment | | X32 | |

*1: 4 groups (C1-C4) are separated. 2 common terminals in one group are connected internally.

*2: There are 16 points of LED indication. The indication group is switched by toggle switch.

| Terminal layout | Diagram of internal circuit | | | |
|--|-----------------------------|-------------|------|-------------|
|  | No. | Signal name | No. | Signal name |
| | (1) | 0 | (21) | 16 |
| | (2) | 1 | (22) | 17 |
| | (3) | 2 | (23) | 18 |
| | (4) | 3 | (24) | 19 |
| | (5) | 4 | (25) | 20 |
| | (6) | 5 | (26) | 21 |
| | (7) | 6 | (27) | 22 |
| | (8) | 7 | (28) | 23 |
| | (9) | C1 | (29) | C3 |
| | (10) | C1 | (30) | C3 |
| | (11) | 8 | (31) | 24 |
| | (12) | 9 | (32) | 25 |
| | (13) | 10 | (33) | 26 |
| | (14) | 11 | (34) | 27 |
| | (15) | 12 | (35) | 28 |
| | (16) | 13 | (36) | 29 |
| | (17) | 14 | (37) | 30 |
| | (18) | 15 | (38) | 31 |
| | (19) | C2 | (39) | C4 |
| | (20) | C2 | (40) | C4 |
| <div>EH-XD32E EH-XDL32E</div>  | | | | |

4.11 64-point Input Module


| Name and function of each part | | Type | EH-XD64 | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|---|----------------------------|---------------|-------|-------|---------------|-----|-----|---------|---------|---------|----|-----|-----|---------|----------|-----|----|---------|-----|----------|----|----|-----|-----|----------|--|
|  | | Weight | Approx. 0.14 kg (0.31 lb.) | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | Dimensions (mm (in.)) | | | | | | | | | | | | | | | | | | | | | | | | | | |
| No. | Name | Function | Remarks | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1] | LED cover | This is the cover for the LED that displays the input status and displayed group. When the input signal turns on, the LED for the relevant number lights up. The LED only lights when the module is energized. | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2] | Lock button | When dismounting the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3] | LED display switch | Effective LED group (16 points) is selected by these switches as follows. <table border="1" data-bbox="542 1328 1096 1489"><thead><tr><th>SW1</th><th>SW2</th><th>LED16</th><th>LED32</th><th>Display group</th></tr></thead><tbody><tr><td>OFF</td><td>OFF</td><td>Not lit</td><td>Not lit</td><td>0 to 15</td></tr><tr><td>ON</td><td>OFF</td><td>Lit</td><td>Not lit</td><td>16 to 31</td></tr><tr><td>OFF</td><td>ON</td><td>Not lit</td><td>Lit</td><td>32 to 47</td></tr><tr><td>ON</td><td>ON</td><td>Lit</td><td>Lit</td><td>48 to 63</td></tr></tbody></table> | SW1 | SW2 | LED16 | LED32 | Display group | OFF | OFF | Not lit | Not lit | 0 to 15 | ON | OFF | Lit | Not lit | 16 to 31 | OFF | ON | Not lit | Lit | 32 to 47 | ON | ON | Lit | Lit | 48 to 63 | |
| SW1 | SW2 | LED16 | LED32 | Display group | | | | | | | | | | | | | | | | | | | | | | | | |
| OFF | OFF | Not lit | Not lit | 0 to 15 | | | | | | | | | | | | | | | | | | | | | | | | |
| ON | OFF | Lit | Not lit | 16 to 31 | | | | | | | | | | | | | | | | | | | | | | | | |
| OFF | ON | Not lit | Lit | 32 to 47 | | | | | | | | | | | | | | | | | | | | | | | | |
| ON | ON | Lit | Lit | 48 to 63 | | | | | | | | | | | | | | | | | | | | | | | | |
| 4] | External wiring connector – Caution – <ul style="list-style-type: none">Approx. 120 mm (4.72 in.) of space will be required in the front of the module for the connector and cable. Please choose the installation location (space) accordingly.Use a shielded cable and always use a Class D grounding. | Connector for input signals. Special cable with connector is optional. (Refer to chapter 4.31, 4.32.) If separate connector is needed, applicable connector type is below. Manufacturer 1 : Fujitsu Takamisawa Solder type Socket: FCN-361J040-AU Cover: FCN-360C040-E Crimp type Housing: FCN-363J040 Contact: FCN-363J-AU Cover: FCN-360C040-E Crimping tool : FCN-367J040-AU/F Manufacturer 2 : AMP Solder type : 1473381-1 | | | | | | | | | | | | | | | | | | | | | | | | | | |

Specification table



| Item | | Specification |
|---------------------------------------|----------------------|--|
| Type | | EH-XD64 |
| Input specification | | DC input |
| Input voltage | | 24 V DC |
| Allowable input voltage range | | 20.4 to 28.8 V DC |
| Input impedance | | Approx. 5.6 k Ω |
| Input derating | | See the derating diagram. |
| Input current | | Approx. 4.3 mA |
| Operating voltage | ON voltage | 15 V or more |
| | OFF voltage | 5 V or less |
| Input lag | OFF \rightarrow ON | 1 ms or less |
| | ON \rightarrow OFF | 1 ms or less |
| Number of input points / module | | 64 points / module |
| Number of input points / common | | 32 points / common (4 common terminals per group *1) |
| Polarity | | None |
| Insulation system | | Photocoupler insulation |
| Input display | | LED (green) *2 |
| External connection | | Connector |
| Internal current consumption (5 V DC) | | Approx. 80 mA |
| I/O assignment | | X64 |



*1: 2 groups (C1,C2) are separated. 4 common terminals in one group are connected internally.

*2: There are 16 points of LED indication. The indication group is switched by toggle switch.



4.12 Output Module

| Name and function of each part | | Type (Weight) | EH-YT8, EH-YTP8 (0.16 kg, 0.35 lb) EH-YT16, EH-YTP16 (0.16 kg, 0.35 lb) EH-YTP16S (0.16 kg, 0.35 lb) EH-YR8B (0.16 kg, 0.35 lb) EH-YR12 (0.20 kg, 0.44 lb) EH-YR16 (0.24 kg, 0.53 lb) EH-YS4 (0.18 kg, 0.40 lb) EH-YS16 (0.23 kg, 0.51 lb) |
|---|----------------|---|---|
|  | | Dimensions (mm (in.)) |  |
| | | | |
| No. | Name | Function | Remarks |
| 1] | LED cover | This is the cover for the LED that displays the output status. When the output signal turns on, the LED for the relevant number lights up. The LED only works when the module is energized. | |
| 2] | Lock button | When dismantling the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | |
| 3] | I/O cover | This is the cover attached to the terminal block area. | |
| 4] | Terminal block | This is the terminal block for connecting output signals. The terminal block is removable. | |

| No. | Item | Detailed explanation | Remarks |
|-----|-----------------------|--|---------|
| | Operation explanation | This module outputs digital signals. The LED's light up while the corresponding digital signal is ON. The CPU reads the status of the mounted modules. If the status accords with actual I/O configuration in the user program, the CPU outputs digital signals according to the user program. | |
| | Terminal block | <p>The screws for the terminal block are M3 screws. Use a crimp terminal that fits the screw diameter. The maximum thickness of the cable should be only up to 0.75 mm². (If you attach two crimp terminals to the same terminal, use a cable with the thickness of 0.5 mm².)</p> <p>The recommended crimp terminal is indicated below.</p> <div style="text-align: center;">  (Recommended) </div> <div style="text-align: center;">  Care must be exercised when handling the terminal since it may fall off if the screw is loose. </div> <p style="text-align: center;">Unit: mm (in.)</p> | |

Specification table (relay output module)

| Item | | Specification | | |
|--|-----------|--|---|---|
| Type | | EH-YR8B | EH-YR12 | EH-YR16 |
| Output specification | | Relay output | | |
| Rated load voltage | | 100/240 V AC, 24 V DC | | |
| Minimum switching current | | 1 mA | | |
| Leak current | | None | | |
| Maximum load current | 1 circuit | 2 A | | |
| | 1 common | 2 A | 5 A | 8A |
| Output response time | OFF → ON | 10 ms or less | | |
| | ON → OFF | 10 ms or less | | |
| Number of output points / module | | 8 points / module | 12 points / module | 16 points / module |
| Number of output points / common | | 1 point / common (channel separated) | 12 points / common (2 common terminals) *1 | 16 points / common (2 common terminals) *1 |
| Surge removal circuit | | Varistor (voltage characteristic of varistor : 423 - 517V) | None | |
| Fuse | | None | | |
| Insulation system | | Relay insulation | Photocoupler insulation | Relay insulation |
| Output display | | LED (green) | | |
| External connection | | Removable type screw terminal block (M3) | | |
| Internal current consumption (5 V DC) | | Approx. 220 mA | Approx. 40 mA | Approx. 430 mA |
| Externally supplied power *2 (For driving relays) | | Not used | 24 V DC (+10%, -5%) (maximum 70 mA) | Not used |
| I/O assignment | | Y16 | | |

*1: The common terminals are connected internally.

*2: 24 V DC must be supplied externally to drive the relays. (The 24 V output of the power module can be used.)

| Terminal layout | | Diagram of internal circuit | | |
|-----------------|-----|-----------------------------|----------|---------|
| | No. | Signal name | | |
| | | EH-YR8B | EH-YR12 | EH-YR16 |
| | 1] | 0 | 24 V DC+ | 0 |
| | 2] | 1 | NC | 1 |
| | 3] | 2 | 0 | 2 |
| | 4] | 3 | 1 | 3 |
| | 5] | 4 | 2 | 4 |
| | 6] | 5 | 3 | 5 |
| | 7] | 6 | 4 | 6 |
| | 8] | 7 | 5 | 7 |
| | 9] | NC | C | C |
| | 10] | C0 | 24V DC- | 8 |
| | 11] | C1 | NC | 9 |
| | 12] | C2 | 6 | 10 |
| | 13] | C3 | 7 | 11 |
| | 14] | C4 | 8 | 12 |
| | 15] | C5 | 9 | 13 |
| | 16] | C6 | 10 | 14 |
| | 17] | C7 | 11 | 15 |
| | 18] | NC | C | C |

Specification table (transistor output module)

| Item | | Specification | |
|---|-----------|--|--------------------|
| Type | | EH-YT8 | EH-YT16 |
| Output specification | | Transistor output (sink type) | |
| Rated load voltage | | 12/24 V DC (+10%, -15%) | |
| Minimum switching current | | 1 mA | |
| Leak current | | 0.1 mA | |
| Maximum load current | 1 circuit | 0.3 A (MFG No.02F** or older) *1 0.5 A (MFG No.02G** or newer) *1 | |
| | 1 common | 2.4 A | 4 A |
| Output response time | OFF → ON | 0.3 ms or less | |
| | ON → OFF | 1 ms or less | |
| Number of output points / module | | 8 points / module | 16 points / module |
| Number of output points / common | | 8 points / common | 16 points / common |
| Surge removal circuit | | Diode | |
| Fuse *2 | | 4 A/common | 8 A/common |
| Insulation system | | Photocoupler insulation | |
| Output display | | LED (green) | |
| External connection | | Removable type screw terminal block (M3) | |
| Internal current consumption (5 V DC) | | Approx. 30 mA | Approx. 50 mA |
| External power supply *3 (For supplying power to the S terminal) | | 12/24 V DC (+10%, -15%) (maximum 30 mA) *4 | |
| I/O assignment | | Y16 | |

*1: MFG No.02F** : Jun.2002 production, MFG No.02G** : Jul.2002 production

*2: The module needs to be repaired in case of fuse blown. It is not allowed for uses to replace the fuse.

*3: It is necessary to supply 12/24 V DC to the S terminal.

*4: This value is internal current consumption of the module. Additional current is necessary to drive other devices.

| Terminal layout | | Diagram of internal circuit | |
|-----------------|-----|-----------------------------|---------|
| | No. | Signal name | |
| | | EH-YT8 | EH-YT16 |
| | 1] | 0 | 0 |
| | 2] | 1 | 1 |
| | 3] | 2 | 2 |
| | 4] | 3 | 3 |
| | 5] | 4 | 4 |
| | 6] | 5 | 5 |
| | 7] | 6 | 6 |
| | 8] | 7 | 7 |
| | 9] | C | C |
| | 10] | NC | 8 |
| | 11] | NC | 9 |
| | 12] | NC | 10 |
| | 13] | NC | 11 |
| | 14] | NC | 12 |
| | 15] | NC | 13 |
| | 16] | NC | 14 |
| | 17] | NC | 15 |
| | 18] | S | S |
| | | | |

Specification table (transistor output module)

| Item | | Specification | | |
|---|-----------|--|--------------------|-----------|
| Type | | EH-YTP8 | EH-YTP16 | EH-YTP16S |
| Output specification | | Transistor output (source type) | | |
| Rated load voltage | | 12/24 V DC (+10%, -15%) | | |
| Minimum switching current | | 1 mA | | |
| Leak current | | 0.1 mA | | |
| Maximum load current | 1 circuit | 0.3 A (MFG No.02F** or older) *1 0.5 A (MFG No.02G** or newer) *1 | | 0.8 A |
| | 1 common | 2.4 A | 4 A | 5 A |
| Output response time | OFF → ON | 0.3 ms or less | | |
| | ON → OFF | 1 ms or less | | |
| Number of output points / module | | 8 points / module | 16 points / module | |
| Number of output points / common | | 8 points / common | 16 points / common | |
| Surge removal circuit | | Diode | | Built in |
| Fuse *2 | | 4 A/common | 8 A/common | None |
| Insulation system | | Photocoupler insulation | | |
| Output display | | LED (green) | | |
| External connection | | Removable type screw terminal block (M3) | | |
| Internal current consumption (5 V DC) | | Approx. 30 mA | Approx. 50 mA | |
| External power supply *3 (For supplying power to the S terminal) | | 12/24 V DC (+10%, -15%) (maximum 30 mA) *4 | | |
| I/O assignment | | Y16 | | |
| Short-circuit protection function | | Not available | | Available |

*1: MFG No.02F** : Jun.2002 production, MFG No.02G** : Jul.2002 production

*2: The module needs to be repaired in case of fuse blown. It is not allowed for uses to replace the fuse.

*3: It is necessary to supply 12/24 V DC to the S terminal.


*4: This value is internal current consumption of the module. Additional current is necessary to drive other devices.

| Terminal layout | | Diagram of internal circuit | |
|-----------------|-----|-----------------------------|-----------------------------|
| | | No. | Signal name |
| | | | EH-YTP8 EH-YTP16, YTP16S |
| | 1] | 0 | 0 |
| | 2] | 1 | 1 |
| | 3] | 2 | 2 |
| | 4] | 3 | 3 |
| | 5] | 4 | 4 |
| | 6] | 5 | 5 |
| | 7] | 6 | 6 |
| | 8] | 7 | 7 |
| | 9] | C | C |
| | 10] | NC | 8 |
| | 11] | NC | 9 |
| | 12] | NC | 10 |
| | 13] | NC | 11 |
| | 14] | NC | 12 |
| | 15] | NC | 13 |
| | 16] | NC | 14 |
| | 17] | NC | 15 |
| | 18] | S | S |
| | | | |

Specification table (SSR output module)

| Item | | Specification | |
|---------------------------------------|-----------|--|--|
| Type | | EH-YS4 | EH-YS16 |
| Output specification | | Triac output | |
| Rated load voltage | | 100/240 V AC (85 to 250 V AC) | |
| Minimum switching current | | 100 mA | 10 mA |
| Leak current | | 5 mA or less | 2 mA or less |
| Maximum load current | 1 circuit | 0.5 A | 0.3 A |
| | 1 common | 2 A | 4 A (ambient temp. 45 °C) See below derating curve. |
| Output response time | OFF → ON | 1 ms or less | |
| | ON → OFF | 1 ms+1/2 cycles or less | |
| Number of output points / module | | 4 points / module | 16 points / module |
| Number of output points / common | | 4 points / common | 16 points / common |
| Surge removal circuit | | Varistor | |
| Fuse | | 4 A | 6.3 A (Be sure to install an external fuse) |
| Insulation system | | Photo-triac insulation | |
| Output display | | LED (green) | |
| External connection | | Removable type screw terminal block (M3) | |
| Internal current consumption (5 V DC) | | Approx. 70 mA | Approx. 250 mA |
| I/O assignment | | Y16 | |


Terminal layout





| No. | Signal name | |
|-----|-------------|---------|
| | EH-YS4 | EH-YS16 |
| 1] | 0 | 0 |
| 2] | NC | 1 |
| 3] | 1 | 2 |
| 4] | NC | 3 |
| 5] | 2 | 4 |
| 6] | NC | 5 |
| 7] | 3 | 6 |
| 8] | NC | 7 |
| 9] | C | C |
| 10] | NC | 8 |
| 11] | NC | 9 |
| 12] | NC | 10 |
| 13] | NC | 11 |
| 14] | NC | 12 |
| 15] | NC | 13 |
| 16] | NC | 14 |
| 17] | NC | 15 |
| 18] | NC | C |

Diagram of internal circuit


EH-YS4



EH-YS16



4.13 32-point Output Module

| Name and function of each part | | Type | EH-YT32 EH-YTP32 | | | | | | | | | |
|---|--|--|----------------------------|--|------------------|-----|-----|---------|----|----|----------|--|
|  | | Weight | Approx. 0.12 kg (0.26 lb.) | | | | | | | | | |
| | | Dimensions (mm (in.)) | | | | | | | | | | |
| No. | Name | Function | Remarks | | | | | | | | | |
| 1] | LED cover | This is the cover for the LED that displays the output status. When the output signal turns on, the LED for the relevant number lights up. The LED only works when the module is energized. | | | | | | | | | | |
| 2] | Lock button | When dismantling the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | | | | | | | | | | |
| 3] | LED indication switch | Effective LED group (16 points) is selected by this switch as follows. <table border="1" data-bbox="574 1292 1074 1480"><thead><tr><th>SW</th><th>LED <input checked="" type="checkbox"/> 16</th><th>Indication group</th></tr></thead><tbody><tr><td>OFF</td><td>OFF</td><td>0 to 15</td></tr><tr><td>ON</td><td>ON</td><td>16 to 31</td></tr></tbody></table> | SW | LED <input checked="" type="checkbox"/> 16 | Indication group | OFF | OFF | 0 to 15 | ON | ON | 16 to 31 | |
| SW | LED <input checked="" type="checkbox"/> 16 | Indication group | | | | | | | | | | |
| OFF | OFF | 0 to 15 | | | | | | | | | | |
| ON | ON | 16 to 31 | | | | | | | | | | |
| 4] | External wiring connector – Caution – <ul style="list-style-type: none">Approx. 120 mm (4.72 in.) of space will be required in the front of the module for the connector and cable. Please choose the installation location (space) accordingly.Use a shielded cable and always use a class D grounding. | Connector for input signals. Special cable with connector is optional. (Refer to chapter 4.31, 4.32.) If separate connector is needed, applicable connector type is below. Manufacturer 1 : Fujitsu Takamisawa Solder type Socket: FCN-361J040-AU Cover: FCN-360C040-E Crimp type Housing: FCN-363J040 Contact: FCN-363J-AU Cover: FCN-360C040-E Crimping tool : FCN-367J040-AU/F Manufacturer 2 : AMP Solder type : 1473381-1 | | | | | | | | | | |

Specification table (transistor output module)



| Item | | Specification | |
|---|-----------|---|---------------------------------|
| Type | | EH-YT32 | EH-YTP32 |
| Output specification | | Transistor output (sink type) | Transistor output (source type) |
| Rated load voltage | | 12/24 V DC (+10%, -15%) | |
| Minimum switching current | | 1 mA | |
| Leak current | | 0.1 mA or less | |
| Maximum load current | 1 circuit | 0.2 A | |
| | 1 common | 6.4 A *1 | |
| Output response time | OFF → ON | 0.3 ms or less | |
| | ON → OFF | 1 ms or less | |
| Number of output points / module | | 32 points / module | |
| Number of output points / common | | 32 points / common (4 common terminals) | |
| Surge removal circuit | | Diode | |
| Fuse *2 | | 10 A/1 common | |
| Insulation system | | Photocoupler insulation | |
| Output display | | LED (green) *3 | |
| Short-circuit protection | | Electronic | |
| External connection | | Connector | |
| Internal current consumption (5 V DC) | | Approx. 90 mA | |
| External power supply *4 (For supplying power to the S terminal) | | 12/24 V DC (+10%, -15%) (maximum 100 mA) | |
| I/O assignment | | Y32 | |

*1: Total current for 4 common terminals. Do not use more than 3A with one common terminal pin. 4 common terminals are connected internally


*2: The module needs to be repaired in case of fuse blown. It is not allowed for users to replace the fuse.

*3: There are 16 points of LED indication. The indication group is switched by toggle switch.

*4: It is necessary to supply 12/24 V DC to the S terminal.

| Terminal layout | | Diagram of internal circuit | | | |
|---|--|-----------------------------|-------------|--|-------------|
|  | | No. | Signal name | No. | Signal name |
| | | 1] | 0 | 21] | 16 |
| | | 2] | 1 | 22] | 17 |
| | | 3] | 2 | 23] | 18 |
| | | 4] | 3 | 24] | 19 |
| | | 5] | 4 | 25] | 20 |
| | | 6] | 5 | 26] | 21 |
| | | 7] | 6 | 27] | 22 |
| | | 8] | 7 | 28] | 23 |
| | | 9] | C | 29] | C |
| | | 10] | S | 30] | S |
| | | 11] | 8 | 31] | 24 |
| | | 12] | 9 | 32] | 25 |
| | | 13] | 10 | 33] | 26 |
| | | 14] | 11 | 34] | 27 |
| | | 15] | 12 | 35] | 28 |
| | | 16] | 13 | 36] | 29 |
| | | 17] | 14 | 37] | 30 |
| | | 18] | 15 | 38] | 31 |
| | | 19] | C | 39] | C |
| | | 20] | S | 40] | S |
| | | | |  | |

4.14 Euro-terminal 32-point Output Module

| | | | | | | | | | | | | |
|---|---------------------------|--|--|--------------------|------------------|-----|---------|---------|----|-----|----------|--|
| <div><p>Name and function of each part</p></div> | | Type | EH-YT32E | | | | | | | | | |
| | | | EH-YTP32E | | | | | | | | | |
| | | Weight | Approx. 0.15 kg (0.33 lb.) | | | | | | | | | |
| | | Dimensions (mm (in.)) | <div><div><div>30</div><div>100</div></div><div><div>104</div></div></div> | | | | | | | | | |
| No. | Name | Function | Remarks | | | | | | | | | |
| 1] | LED cover | This is the cover for the LED that displays the input status and displayed group. When the input signal turns on, the LED for the relevant number lights up. The LED only lights when the module is energized. | | | | | | | | | | |
| 2] | Lock button | When dismantling the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | | | | | | | | | | |
| 3] | LED indication switch | Effective LED group (16 points) is selected by this switch as follows. <table><tr><td>SW</td><td>LED <div>+16</div></td><td>Indication group</td></tr><tr><td>OFF</td><td>Not lit</td><td>0 to 15</td></tr><tr><td>ON</td><td>Lit</td><td>16 to 31</td></tr></table> | SW | LED <div>+16</div> | Indication group | OFF | Not lit | 0 to 15 | ON | Lit | 16 to 31 | |
| SW | LED <div>+16</div> | Indication group | | | | | | | | | | |
| OFF | Not lit | 0 to 15 | | | | | | | | | | |
| ON | Lit | 16 to 31 | | | | | | | | | | |
| 4] | External wiring connector | A connector for input signals. It is attached to the product. Solid wire 0.5...1.0 mm ² Flexible wire 0.5...1.0 mm ² Insulation stripping length 7mm Cable ferrules cannot be used | Applicable connectors (Manufacturer: Weidmuller) <ul style="list-style-type: none">• Type B2L3.5/20AUOR• Pats No. 175736• Poles 20• Color Orange | | | | | | | | | |

Specification table (transistor output module)

| Item | | Specification | |
|--|-----------|--|---------------------------------|
| Type | | EH-YT32E | EH-YTP32E |
| Output specification | | Transistor output (sink type) | Transistor output (source type) |
| Rated load voltage | | 12/24 V DC (+10%, -15%) | |
| Minimum switching current | | 1 mA | |
| Leak current | | 0.1 mA or less | |
| Maximum load current | 1 circuit | 0.2 A | |
| | 1 common | 4.0 A *1 | |
| Output response time | OFF → ON | 0.3 ms or less | |
| | ON → OFF | 1 ms or less | |
| Number of output points / module | | 32 points / module | |
| Number of output points / common | | 8 points / common | |
| Surge removal circuit | | Diode | |
| Fuse *2 | | 10 A/1 common | |
| Insulation system | | Photocoupler insulation | |
| Output display | | LED (green) *3 | |
| Short-circuit protection | | Electronic | |
| External connection | | Spring type connector (removable) | |
| Internal current consumption (5 V DC) | | Approx. 90 mA | |
| External power supply*4 (For supplying power to the S terminal) | | 12/24 V DC (+10%, -15%) (max. 100 mA) | |
| I/O assignment | | Y32 | |


*1: Total current for 4 common terminals. Do not use more than 3A with one common terminal pin.

*2: The module needs to be repaired in case of fuse blown. It is not allowed for uses to replace the fuse.

*3: There are 16 points of LED indication. The indication group is switched by toggle switch.


*4: It is necessary to supply 12/24 V DC to the S terminal.

Terminal layout




| No. | Signal name | No. | Signal name |
|------|-------------|------|-------------|
| (1) | 0 | (21) | 16 |
| (2) | 1 | (22) | 17 |
| (3) | 2 | (23) | 18 |
| (4) | 3 | (24) | 19 |
| (5) | 4 | (25) | 20 |
| (6) | 5 | (26) | 21 |
| (7) | 6 | (27) | 22 |
| (8) | 7 | (28) | 23 |
| (9) | C1 | (29) | C3 |
| (10) | S1 | (30) | S3 |
| (11) | 8 | (31) | 24 |
| (12) | 9 | (32) | 25 |
| (13) | 10 | (33) | 26 |
| (14) | 11 | (34) | 27 |
| (15) | 12 | (35) | 28 |
| (16) | 13 | (36) | 29 |
| (17) | 14 | (37) | 30 |
| (18) | 15 | (38) | 31 |
| (19) | C2 | (39) | C4 |
| (20) | S2 | (40) | S4 |

Diagram of internal circuit



4.15 64-point Output Module

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|---|--|---------------|-------|-------|---------------|-----|-----|---------|---------|---------|----|-----|-----|---------|----------|-----|----|---------|-----|----------|----|----|-----|-----|----------|--|
| <div><div><div>Name and function of each part</div><div></div></div></div> | | Type | EH-YT64 EH-YTP64 | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | Weight | Approx. 0.13 kg (0.29 lb.) | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | Dimensions (mm (in.)) | <div><div><div>30 (1.18)</div><div>100 (3.94)</div></div><div><div>95 (3.74)</div></div></div> | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| No. | Name | Function | Remarks | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1] | LED cover | This is the cover for the LED that displays the output status and displayed group. When the output signal turns on, the LED for the relevant number lights up. The LED only works when the module is energized. | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2] | Lock button | When dismounting the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3] | LED indication switch | Effective LED group (16 points) is selected by these switches as follows. <table><tr><td>SW1</td><td>SW2</td><td>LED16</td><td>LED32</td><td>Display group</td></tr><tr><td>OFF</td><td>OFF</td><td>Not lit</td><td>Not lit</td><td>0 to 15</td></tr><tr><td>ON</td><td>OFF</td><td>Lit</td><td>Not lit</td><td>16 to 31</td></tr><tr><td>OFF</td><td>ON</td><td>Not lit</td><td>Lit</td><td>32 to 47</td></tr><tr><td>ON</td><td>ON</td><td>Lit</td><td>Lit</td><td>48 to 63</td></tr></table> | SW1 | SW2 | LED16 | LED32 | Display group | OFF | OFF | Not lit | Not lit | 0 to 15 | ON | OFF | Lit | Not lit | 16 to 31 | OFF | ON | Not lit | Lit | 32 to 47 | ON | ON | Lit | Lit | 48 to 63 | |
| SW1 | SW2 | LED16 | LED32 | Display group | | | | | | | | | | | | | | | | | | | | | | | | |
| OFF | OFF | Not lit | Not lit | 0 to 15 | | | | | | | | | | | | | | | | | | | | | | | | |
| ON | OFF | Lit | Not lit | 16 to 31 | | | | | | | | | | | | | | | | | | | | | | | | |
| OFF | ON | Not lit | Lit | 32 to 47 | | | | | | | | | | | | | | | | | | | | | | | | |
| ON | ON | Lit | Lit | 48 to 63 | | | | | | | | | | | | | | | | | | | | | | | | |
| 4] | External wiring connector – Caution – <ul style="list-style-type: none">Approx. 120 mm (4.72 in.) of space will be required in the front of the module for the connector and cable. Please choose the installation location (space) accordingly.Use a shielded cable and always use a class D grounding. | Connector for input signals. Special cable with connector is optional. (Refer to chapter 4.31, 4.32.) If separate connector is needed, applicable connector type is below. Manufacturer 1 : Fujitsu Takamisawa Solder type Socket: FCN-361J040-AU Cover: FCN-360C040-E Crimp type Housing: FCN-363J040 Contact: FCN-363J-AU Cover: FCN-360C040-E Crimping tool : FCN-367J040-AU/F Manufacturer 2 : AMP Solder type : 1473381-1 | | | | | | | | | | | | | | | | | | | | | | | | | | |

Specification table (transistor output module)




| Item | | Specification | |
|---|-----------|--|---------------------------------|
| Type | | EH-YT64 | EH-YTP64 |
| Output specification | | Transistor output (sink type) | Transistor output (source type) |
| Rated load voltage | | 12/24 V DC (+10%, -15%) | |
| Minimum switching current | | 1 mA | |
| Leak current | | 0.1 mA or less | |
| Maximum load current | 1 circuit | 0.1 A | |
| | 1 common | 3.2 A | |
| Output response time | OFF → ON | 0.3 ms or less | |
| | ON → OFF | 1 ms or less | |
| Number of output points / module | | 64 points / module | |
| Number of output points / common | | 32 points / common (4 common terminals per group *2) | |
| Surge removal circuit | | Diode | |
| Fuse *1 | | 5 A/1 common | |
| Insulation system | | Photocoupler insulation | |
| Output display | | LED (green) *3 | |
| Short-circuit protection | | Electronic | |
| External connection | | Connector | |
| Internal current consumption (5 V DC) | | Approx. 120 mA | |
| External power supply *4 (For supplying power to the S terminal) | | 12/24 V DC (+10%, -15%) (maximum 100 mA) | |
| I/O assignment | | Y64 | |

*1: The module needs to be repaired in case of fuse blown. It is not allowed for users to replace the fuse.



*2: 2 groups (C1,C2) are separated. 4 common terminals in one group are connected internally.



*3: There are 16 points of LED indication. The indication group is switched by toggle switch.

*4: It is necessary to supply 12/24 V DC to the S terminal.

| Terminal layout | | Diagram of internal circuit | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|--|-------------|------|-------------|-------------|-------------|--|--|-----|-------------|-----|-------------|-----|-------------|-----|-------------|------|----|------|----|-----|---|------|----|------|----|------|----|-----|---|------|----|------|----|------|----|-----|---|------|----|------|----|------|----|-----|---|------|----|------|----|------|----|-----|---|------|----|------|----|------|----|-----|---|------|----|------|----|------|----|-----|---|------|----|------|----|------|----|-----|---|------|----|------|----|------|----|-----|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|---|------|----|------|----|------|----|------|---|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|----|--|
|  | <table><thead><tr><th colspan="4">Left (CN2)</th><th colspan="4">Right (CN1)</th></tr><tr><th>No.</th><th>Signal name</th><th>No.</th><th>Signal name</th><th>No.</th><th>Signal name</th><th>No.</th><th>Signal name</th></tr></thead><tbody><tr><td>(41)</td><td>32</td><td>(61)</td><td>48</td><td>(1)</td><td>0</td><td>(21)</td><td>16</td></tr><tr><td>(42)</td><td>33</td><td>(62)</td><td>49</td><td>(2)</td><td>1</td><td>(22)</td><td>17</td></tr><tr><td>(43)</td><td>34</td><td>(63)</td><td>50</td><td>(3)</td><td>2</td><td>(23)</td><td>18</td></tr><tr><td>(44)</td><td>35</td><td>(64)</td><td>51</td><td>(4)</td><td>3</td><td>(24)</td><td>19</td></tr><tr><td>(45)</td><td>36</td><td>(65)</td><td>52</td><td>(5)</td><td>4</td><td>(25)</td><td>20</td></tr><tr><td>(46)</td><td>37</td><td>(66)</td><td>53</td><td>(6)</td><td>5</td><td>(26)</td><td>21</td></tr><tr><td>(47)</td><td>38</td><td>(67)</td><td>54</td><td>(7)</td><td>6</td><td>(27)</td><td>22</td></tr><tr><td>(48)</td><td>39</td><td>(68)</td><td>55</td><td>(8)</td><td>7</td><td>(28)</td><td>23</td></tr><tr><td>(49)</td><td>C2</td><td>(69)</td><td>C2</td><td>(9)</td><td>C1</td><td>(29)</td><td>C1</td></tr><tr><td>(50)</td><td>S2</td><td>(70)</td><td>S2</td><td>(10)</td><td>S1</td><td>(30)</td><td>S1</td></tr><tr><td>(51)</td><td>40</td><td>(71)</td><td>56</td><td>(11)</td><td>8</td><td>(31)</td><td>24</td></tr><tr><td>(52)</td><td>41</td><td>(72)</td><td>57</td><td>(12)</td><td>9</td><td>(32)</td><td>25</td></tr><tr><td>(53)</td><td>42</td><td>(73)</td><td>58</td><td>(13)</td><td>10</td><td>(33)</td><td>26</td></tr><tr><td>(54)</td><td>43</td><td>(74)</td><td>59</td><td>(14)</td><td>11</td><td>(34)</td><td>27</td></tr><tr><td>(55)</td><td>44</td><td>(75)</td><td>60</td><td>(15)</td><td>12</td><td>(35)</td><td>28</td></tr><tr><td>(56)</td><td>45</td><td>(76)</td><td>61</td><td>(16)</td><td>13</td><td>(36)</td><td>29</td></tr><tr><td>(57)</td><td>46</td><td>(77)</td><td>62</td><td>(17)</td><td>14</td><td>(37)</td><td>30</td></tr><tr><td>(58)</td><td>47</td><td>(78)</td><td>63</td><td>(18)</td><td>15</td><td>(38)</td><td>31</td></tr><tr><td>(59)</td><td>C2</td><td>(79)</td><td>C2</td><td>(19)</td><td>C1</td><td>(39)</td><td>C1</td></tr><tr><td>(60)</td><td>S2</td><td>(80)</td><td>S2</td><td>(20)</td><td>S1</td><td>(40)</td><td>S1</td></tr></tbody></table> | Left (CN2) | | | | Right (CN1) | | | | No. | Signal name | No. | Signal name | No. | Signal name | No. | Signal name | (41) | 32 | (61) | 48 | (1) | 0 | (21) | 16 | (42) | 33 | (62) | 49 | (2) | 1 | (22) | 17 | (43) | 34 | (63) | 50 | (3) | 2 | (23) | 18 | (44) | 35 | (64) | 51 | (4) | 3 | (24) | 19 | (45) | 36 | (65) | 52 | (5) | 4 | (25) | 20 | (46) | 37 | (66) | 53 | (6) | 5 | (26) | 21 | (47) | 38 | (67) | 54 | (7) | 6 | (27) | 22 | (48) | 39 | (68) | 55 | (8) | 7 | (28) | 23 | (49) | C2 | (69) | C2 | (9) | C1 | (29) | C1 | (50) | S2 | (70) | S2 | (10) | S1 | (30) | S1 | (51) | 40 | (71) | 56 | (11) | 8 | (31) | 24 | (52) | 41 | (72) | 57 | (12) | 9 | (32) | 25 | (53) | 42 | (73) | 58 | (13) | 10 | (33) | 26 | (54) | 43 | (74) | 59 | (14) | 11 | (34) | 27 | (55) | 44 | (75) | 60 | (15) | 12 | (35) | 28 | (56) | 45 | (76) | 61 | (16) | 13 | (36) | 29 | (57) | 46 | (77) | 62 | (17) | 14 | (37) | 30 | (58) | 47 | (78) | 63 | (18) | 15 | (38) | 31 | (59) | C2 | (79) | C2 | (19) | C1 | (39) | C1 | (60) | S2 | (80) | S2 | (20) | S1 | (40) | S1 |  |
| | Left (CN2) | | | | Right (CN1) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| No. | Signal name | No. | Signal name | No. | Signal name | No. | Signal name | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (41) | 32 | (61) | 48 | (1) | 0 | (21) | 16 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (42) | 33 | (62) | 49 | (2) | 1 | (22) | 17 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (43) | 34 | (63) | 50 | (3) | 2 | (23) | 18 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (44) | 35 | (64) | 51 | (4) | 3 | (24) | 19 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (45) | 36 | (65) | 52 | (5) | 4 | (25) | 20 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (46) | 37 | (66) | 53 | (6) | 5 | (26) | 21 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (47) | 38 | (67) | 54 | (7) | 6 | (27) | 22 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (48) | 39 | (68) | 55 | (8) | 7 | (28) | 23 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (49) | C2 | (69) | C2 | (9) | C1 | (29) | C1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (50) | S2 | (70) | S2 | (10) | S1 | (30) | S1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (51) | 40 | (71) | 56 | (11) | 8 | (31) | 24 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (52) | 41 | (72) | 57 | (12) | 9 | (32) | 25 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (53) | 42 | (73) | 58 | (13) | 10 | (33) | 26 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (54) | 43 | (74) | 59 | (14) | 11 | (34) | 27 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (55) | 44 | (75) | 60 | (15) | 12 | (35) | 28 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (56) | 45 | (76) | 61 | (16) | 13 | (36) | 29 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (57) | 46 | (77) | 62 | (17) | 14 | (37) | 30 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (58) | 47 | (78) | 63 | (18) | 15 | (38) | 31 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (59) | C2 | (79) | C2 | (19) | C1 | (39) | C1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (60) | S2 | (80) | S2 | (20) | S1 | (40) | S1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | |  | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

4.16 Analog I/O modules


| Name and function of each part  <p>1] Lock button</p> <p>2] I/O cover</p> <p>3] Terminal block</p> | | Type | EH-AX44, EH-AX8* |
|--|----------------|---|---|
| | | | EH-AY22, EH-AY2H, EH-AY4* |
| | | Weight | Approx. 0.18 kg (0.41 lb.) |
| | | Dimensions (mm (in.)) |  |
| No. | Name | Function | Remarks |
| 1] | Lock button | When dismantling the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | |
| 2] | I/O cover | This is the cover attached to the terminal block area. | |
| 3] | Terminal block | This is the terminal block for connecting output signals. The terminal block can be connected or disconnected. | |

| No. | Item | Detailed explanation | Comments |
|--------------------------|------|--|--|
| Explanation of operation | | <p>Analog Input Module</p> <p>The CPU module verifies the status of the installed module and if the I/O assignment information matches that contained in the user program, the input information is received according to the contents of the user program.</p> <p>EH-AX**: Receives analog output signal (voltage or current).</p> <p>Analog Output Module</p> <p>The CPU module verifies the status of the installed module and if the I/O assignment information matches with that contained in the user program, the output information is output according to the contents of the user program.</p> <p>EH-AY**: Outputs analog output signal (voltage or current).</p> | CPU104/208 of HARD REV.00 does not support analog modules. |
| Terminal block | | <p>The screws for the terminal block are M3 screws. Use a crimp terminal that fits the screw diameter. The maximum thickness of the cable should be only up to 0.75 mm². (Use 0.5 mm² cable when two crimp terminals are attached to the same terminal.)</p> <p>The recommended crimp terminal is indicated below.</p> <div style="text-align: center;">  (Recommended) </div> <div style="text-align: center;">  </div> <p>Unit: mm (in.)</p> <p>Care must be exercised when handling the terminal since it may fall off if the screw is loose.</p> | |

*1: The hardware revision of the CPU module was updated to REV.01 in March of 1998. The revision of the CPU module is noted on the specifications plate attached on the side of the unit.


Specification table (analog input module)

| Item | | Specification |
|---------------------------------------|---------------------------------|---|
| Type | | EH-AX44 |
| Input current range (0 to 3 channels) | | 4 to 20 mA |
| Input voltage range (4 to 7 channels) | | 0 to 10 V DC |
| Resolution | | 12 bits |
| Conversion time | | 5 ms or less |
| Overall accuracy | | $\pm 1\%$ or less (of full-scale value) |
| Input impedance | Current input (0 to 3 channels) | Approx. 100 Ω |
| | Voltage input (4 to 7 channels) | Approx. 100 k Ω |
| Insulation | Channel · Internal circuit | Photocoupler insulation |
| | Between channels | No insulation |
| Number of channels | Input current range | 4 channels/module (0 to 3 channels) |
| | Input voltage range | 4 channels/module (4 to 7 channels) |
| External connection | | Removable type screw terminal block (M3) |
| Internal current consumption (5 V DC) | | Approx. 100 mA |
| External power supply | | 24 V DC (+20%, -15%) Approx. 0.15 A (Approx. 0.4 A at power On) |
| External wiring | | 2-core shield wire (20 m (65.62 ft.) or less) |
| I/O assignment | | WX8W |




Specification table (analog voltage input module)

| Item | | Specification | |
|---------------------------------------|----------------------------|---|----------------|
| Type | | EH-AX8V | EH-AX8H |
| Input voltage range | | 0 to 10 V DC | -10 to 10 V DC |
| Resolution | | 12 bits | |
| Conversion time | | 5 ms or less | |
| Overall accuracy | | $\pm 1\%$ or less (of full-scale value) | |
| Input impedance | | Approx. 100 k Ω | |
| Insulation | Channel · Internal circuit | Photocoupler insulation | |
| | Between channels | No insulation | |
| Number of channels | | 8 channels/module (0 to 7 channel) | |
| External connection | | Removable type screw terminal block (M3) | |
| Internal current consumption (5 V DC) | | Approx. 100 mA | |
| External power supply | | 24 V DC (+20%, -15%) Approx. 0.15 A (Approx. 0.4 A at power On) | |
| External wiring | | 2-core shield wire (20 m (65.62 ft.) or less) | |
| I/O assignment | | WX8W | |



Specification table (analog current input module)


| Item | | Specification | |
|---------------------------------------|----------------------------|---|------------|
| Type | | EH-AX8I | EH-AX8IO |
| Input current range | | 4 to 20 mA | 0 to 22 mA |
| Resolution | | 12 bits | |
| Conversion time | | 5 ms or less | |
| Overall accuracy | | $\pm 1\%$ or less (of full-scale value) | |
| Input impedance | | Approx. 100 Ω | |
| Insulation | Channel · Internal circuit | Photocoupler insulation | |
| | Between channels | No insulation | |
| Number of channels | | 8 channels/module (0 to 7 channel) | |
| Weight | | Approx. 0.18 kg (0.4 lb.) | |
| External connection | | Removable type screw terminal block (M3) | |
| Internal current consumption (5 V DC) | | Approx. 100 mA | |
| External power supply | | 24 V DC (+20%, -15%) Approx. 0.15 A (Approx. 0.4 A at power On) | |
| External wiring | | 2-core shield wire (20 m (65.62 ft.) or less) | |
| I/O assignment | | WX8W | |



Specification table (analog output module)

| Item | | Specification | |
|--|----------------------------------|---|----------------|
| Type | | EH-AY22 | EH-AY2H |
| Output voltage range (0 to 1 channel) | | 0 to 10 V DC | -10 to 10 V DC |
| Output current range (2 to 3 channels) | | 4 to 20 mA | — |
| Resolution | | 12 bits | |
| Conversion time | | 5 ms or less | |
| Overall accuracy | | $\pm 1\%$ or less (of full-scale value) | |
| External load resister | Voltage output (0 to 1 channel) | 10 k Ω or more | |
| | Current output (2 to 3 channels) | 0 to 500 Ω | — |
| Insulation | Channel · Internal circuit | Photocoupler insulation | |
| | Between channels | No insulation | |
| Number of channels | Output voltage range *3 | 2 channels/module (0 to 1 channel) | |
| | Output current range *3 | 2 channels/module (2 to 3 channels) | — |
| Weight | | Approx. 0.18 kg (0.4 lb.) | |
| External connection | | Removable type screw terminal block (M3) | |
| Internal current consumption (5 V DC) | | Approx. 100 mA | |
| External power supply | | 24 V DC (+20 %, -15 %) Approx. 0.15 A (Approx. 0.5 A at power On) | |
| External wiring | | 2-core shield wire (20 m (65.62 ft.) or less) | |
| I/O assignment | | WY8W | |

*3: With the EH-AY22, voltage output and current output can be used simultaneously.





*4: Only for the EH-AY22. "NC" for the EH-AY2H.



Specification table (analog voltage output module)

| Item | | Specification | | |
|---------------------------------------|----------------------------|---|----------------|-------------------|
| Type | | EH-AY4V | EH-AY4H | EH-AY4I |
| Input voltage range | | 0 to 10 V DC | -10 to 10 V DC | 4 to 20 mA |
| Resolution | | 12 bits | | |
| Conversion time | | 5 ms or less | | |
| Overall accuracy | | $\pm 1\%$ or less (of full-scale value) | | |
| External load resistor | | 10 k Ω or more | | 0 to 350 Ω |
| Insulation | Channel · Internal circuit | Photocoupler insulation | | |
| | Between channels | No insulation | | |
| Number of channels | | 4 channels/module (0 to 3 channel) | | |
| Weight | | Approx. 0.18 kg (0.4 lb.) | | |
| External connection | | Removable type screw terminal block (M3) | | |
| Internal current consumption (5 V DC) | | Approx. 100 mA | | Approx. 130 mA |
| External power supply | | 24 V DC (+20%, -15%) Approx. 0.15 A (Approx. 0.5 A at power On) | | |
| External wiring | | 2-core shield wire (20 m (65.62 ft.) or less) | | |
| I/O assignment | | WY8W | | |

| Terminal layout | | Diagram of internal circuit | |
|-----------------|--------------|-----------------------------|-------------------------|
| | | | |
| No. | Signal name | | Analog and digital data |
| | AY4V AY4H | AY4I | |
| 1] | V0 + | I0 + | |
| 2] | V1 + | I1 + | |
| 3] | V2 + | I2 + | |
| 4] | V3 + | I3 + | |
| 5] | NC | NC | |
| 6] | NC | NC | |
| 7] | NC | NC | |
| 8] | NC | NC | |
| 9] | 24 V DC + | | |
| 10] | V0 - | I0 - | |
| 11] | V1 - | I1 - | |
| 12] | V2 - | I2 - | |
| 13] | V3 - | I3 - | |
| 14] | NC | NC | |
| 15] | NC | NC | |
| 16] | NC | NC | |
| 17] | NC | NC | |
| 18] | 24 V DC - | | |

4.17 Resistance Temperature Detective Input Module

| <div></div> | | Type | EH-PT4 |
|--|----------------|---|--|
| | | Weight | Approx. 0.18 kg (0.4 lb.) |
| | | Dimensions (mm(in.)) | <div></div> |
| | | | |
| No. | Name | Function | Remarks |
| 1] | Lock button | When dismantling the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | |
| 2] | I/O cover | This is the cover attached to the terminal block area | |
| 3] | Terminal block | This is the terminal block for connecting input signals. The terminal block can be connected or disconnected. | |
| 4] | Switch | This is to set the temperature range. | |



| No. | Item | Detailed explanation | Remarks |
|-----|-----------------------|--|---------|
| | Operation explanation | The module receives input signals from RTD element. The CPU module recognizes the status of the loaded module and when it matches the I/O assignment information included in the user program, input information is received according to the contents of the user program. | |
| | Terminal block | <p>The screws for the terminal block are M3 screws. Use a crimp terminal that fits the screw diameter. The maximum thickness of the cable should be only up to 0.75 mm². (Use 0.5 mm² cable when two crimp terminals are attached to the same terminal.)</p> <p>The recommended crimp terminal is indicated below.</p> <div style="display: flex; align-items: center;">  <div style="margin-left: 10px;">(Recommended)</div> </div> <div style="display: flex; align-items: center;">  <div style="margin-left: 10px;"> <p>Care must be exercised when handling the terminal since it may fall off if the screw is loose.</p> </div> </div> <p style="text-align: center;">Unit: mm (in.)</p> | |

Specification table


| Item | | Specifications |
|---------------------------------------|------------------------------------|--|
| Type | | EH-PT4 |
| Applicable temperature-measuring | | Platinum temperature-measuring resistor Pt 100 (JIS C 1604-1989)/Pt 1000 |
| Temperature conversion data | | Signed 15 bits |
| Accuracy *1 | -20 to 40°C (Pt 100) | $\pm 0.1^{\circ}\text{C}$ @ 25°C ($\pm 0.5^{\circ}\text{C}$ @ 0 to 55°C) |
| | -50 to 400°C (Pt 100) | $\pm 0.6^{\circ}\text{C}$ @ 25°C ($\pm 3^{\circ}\text{C}$ @ 0 to 55°C) |
| | -50 to 400°C (Pt 1000) | $\pm 0.8^{\circ}\text{C}$ @ 25°C ($\pm 6^{\circ}\text{C}$ @ 0 to 55°C) |
| Temperature measuring range | | -20 to + 40°C/-50 to + 400°C (2 mA constant current system) |
| Number of input points | | 4 |
| Conversion time | | Approx. 1 second per 4 values |
| Insulation | Between value and internal circuit | Photocoupler insulation |
| | Between values | No insulation |
| Internal current consumption (5 V DC) | | Approx. 160 mA |
| Externally supplied power | | 24 V DC |
| Unused terminal processing | | The temperature conversion data for one of the four values is H7FFF. |
| External wiring register | | The maximum total resistance of 4 values is 400 Ω |
| External wiring | | Shielded cable |
| Additional function | | Linearization |
| Error detection | | The temperature conversion data at or below -51°C or at or above 410°C is H7FFF. |
| Wire breakage processing | | The temperature conversion data for one of the four values is H7FFF. |
| I/O assignment | | X4W |


*1: The accuracy indicates the value after 10 minutes from the power-up. The value may become slightly higher immediately after the power-up. Also check the temperature-measuring resistor beforehand because it is also subject to error.

*2: Indicates the current terminal wiring in open state. When an open error occurs in the voltage terminal wiring, the data becomes inconsistent.⁷


| Terminal layout | | Diagram of internal circuit | |
|---|--|--|-------------|
|  | | No. | Signal name |
| | | EH-PT4 | |
| | | 1] | b0 |
| | | 2] | B0 |
| | | 3] | b1 |
| | | 4] | B1 |
| | | 5] | b2 |
| | | 6] | B2 |
| | | 7] | b3 |
| | | 8] | B3 |
| | | 9] | 24 V DC + |
| | | 10] | A0 |
| | | 11] | NC |
| | | 12] | A1 |
| | | 13] | NC |
| | | 14] | A2 |
| | | 15] | NC |
| | | 16] | A3 |
| | | 17] | NC |
| | | 18] | 24 V DC - |
| | |  | |

4.18 Counter Module

| Name and function of each part | | Type | EH-CU (2ch) EH-CUE (1ch) |
|---|------------------|--|-----------------------------|
|  | | Weight | Approx. 0.16 kg (0.352 lb.) |
| | | Dimensions (mm(in.)) | |
| | | | |
| No. | Name | Function | Remarks |
| 1] | LED cover | This is the cover for the LED that displays the I/O status. When the I/O signal turns on, the LED for the relevant number lights up. | |
| 2] | Lock button | When dismounting the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | |
| 3] | Wiring connector | 15 × 2 lines 30-pin connector (Note) Common for EH-CU and EH-CUE. Connector (socket) type : HIF3BA-30PA-2.54DS (30 pin, male, HIROSE) Applicable connector (plug) (HIROSE) HIF3BA-30D-2.54C (30 pin, female) HIF3-2226SCC (connector pin) HIF3-TB2226HC (crimping tool) HIF3--30CV (connector cover) | |
| 4] | DIP switches | Performs various initialization settings of the EH-CU and EH-CUE. Turn off the power and remove the module to perform settings. | |
| 5] | Reset switch | This is used when the module generates a hardware error. (Note) After the power is turned on, pressing down the reset switch turns on the "ER" LED. This is normal. | |

| EH-CU | Terminal Layout | No. | CH2 | No. | CH1 | Meaning of signal | |
|---|-----------------|---------------|-------|---------------|-------|-------------------|---|
|  | | 16 | Vin A | 1 | Vin A | Phase A | Connect to a 12 - 24 V DC power supply when using voltage input. |
| | | 17 | A (+) | 2 | A (+) | | Connect to (+) polarity when using differential input. |
| | | 18 | A (-) | 3 | A (-) | | Connect to the open collector signal when using voltage input Connect to (-) polarity when using differential input. |
| | | 19 | Vin B | 4 | Vin B | Phase B | Connect to a 12 - 24 V DC power supply when using voltage input. |
| | | 20 | B (+) | 5 | B (+) | | Connect to (+) polarity when using differential input. |
| | | 21 | B (-) | 6 | B (-) | | Connect to the open collector signal when using voltage input Connect to (-) polarity when using differential input. |
| | | 22 | Vin M | 7 | Vin M | Marker | Connect to a 12 - 24 V DC power supply when using voltage input. |
| | | 23 | M (+) | 8 | M (+) | | Connect to (+) polarity when using differential input. |
| | | 24 | M (-) | 9 | M (-) | | Connect to the open collector signal when using voltage input Connect to (-) polarity when using differential input. |
| | | 25 to 27 N.C. | | 10 to 12 N.C. | | | Do not connect anything. |
| | | 28 | Y2 | 13 | Y0 | Output | Coincidence output. Connect to the other input. |
| | | 29 | Y3 | 14 | Y1 | | Coincidence output. Connect to the other input. |
| | | 30 | Com2 | 15 | Com1 | | (-) common for coincidence output. Commons 1 and 2 are independent. |

Note: The pin number defined in the EH-CU does not correspond to the pin number defined by the connector manufacturer.

| EH-CUE | Terminal Layout | No. | CH2 | No. | CH1 | Meaning of signal | |
|---|-----------------|---------------|------|---------------|-------|-------------------|---|
|  | | 16 | N.C. | 1 | Vin A | Phase A | Connect to a 12 - 24 V DC power supply when using voltage input. |
| | | 17 | N.C. | 2 | A (+) | | Connect to (+) polarity when using differential input. |
| | | 18 | N.C. | 3 | A (-) | | Connect to the open collector signal when using voltage input Connect to (-) polarity when using differential input. |
| | | 19 | N.C. | 4 | Vin B | Phase B | Connect to a 12 - 24 V DC power supply when using voltage input. |
| | | 20 | N.C. | 5 | B (+) | | Connect to (+) polarity when using differential input. |
| | | 21 | N.C. | 6 | B (-) | | Connect to the open collector signal when using voltage input Connect to (-) polarity when using differential input. |
| | | 22 | N.C. | 7 | Vin M | Marker | Connect to a 12 - 24 V DC power supply when using voltage input. |
| | | 23 | N.C. | 8 | M (+) | | Connect to (+) polarity when using differential input. |
| | | 24 | N.C. | 9 | M (-) | | Connect to the open collector signal when using voltage input Connect to (-) polarity when using differential input. |
| | | 25 to 27 N.C. | | 10 to 12 N.C. | | | Do not connect anything. |
| | | 28 | N.C. | 13 | Y0 | Output | Coincidence output. Connect to the other input. |
| | | 29 | N.C. | 14 | Y1 | | Coincidence output. Connect to the other input. |
| | | 30 | N.C. | 15 | Com1 | | (-) common for coincidence output. |

Note: The pin number defined in the EH-CUE does not correspond to the pin number defined by the connector manufacturer.

General specifications

| Item | Specification | |
|--|--|--------|
| Type | EH-CU | EH-CUE |
| Insulation withstand voltage | 250 V DC between I/O signal and FE | |
| Internal current consumption | 5 V 200 mA | |
| Operating ambient temperature/humidity | 0 to 55 degrees, 20 to 90% RH (Non condensing) | |
| Storage ambient temperature/humidity | -10 to 75 degrees, 10 to 90% RH (Non condensing) | |
| I/O assignment | FUN0 | |


Counter specifications

| Item | Specification | |
|--|--|--|
| Type | EH-CU | EH-CUE |
| Maximum number of count | 32 bit (0 to 4, 294, 967, 295) | |
| Maximum frequency | 100 k Hz (25 k Hz when multiple of 4) | |
| Count mode | Select via dip switch settings. (Common to both channels for the EH-CU.) 2 phases; 1 phase (cw/ccw, ck, U/D); 2 phases, multiplication by 4 | |
| Number of channels | 2 channels | 1 channel |
| Differential input current | 4 mA or higher | |
| Differential input voltage | 12 to 24 V DC | |
| | Minimum ON voltage | 10 V DC |
| | Maximum OFF voltage | 4 V DC |
| Insulation method | Photocoupler | |
| Number of input points 3 points x 2 channels | A: A, CW, CK B: B, CCW, U/D M: Marker (z) | Phase difference of each channel (A - B) during 2-phase counting +45° to +125° when up, -45° to -125° when down |
| Minimum counter pulse width | ON: 4 μ s or higher, OFF: 4 μ s or higher | |
| Minimum marker pulse width | 10 μ s or higher (Detected via ON edge) | |
| External wiring method | 30-Pin batch connector for both channels | 30-pin connector |
| External wiring | Wired with twisted pair wires and batch shielded wires | |

Output specifications

| Item | Specification | |
|----------------------------------|---|--|
| Type | EH-CU | EH-CUE |
| Output voltage | 12/24 V DC (30 V DC maximum) | |
| Load current | 20 mA/point maximum | |
| Output method | Open collector output | |
| Minimum load current | 1 mA | |
| Output delay time | ON \rightarrow OFF | 1 ms or less |
| | OFF \rightarrow ON | 1 ms or less |
| Voltage drop when ON | 1.5 V maximum | |
| Number of external output points | 4 points/module External terminal of output destination may be specified for each channel. | 2 points/module |
| | Normal counter | Current value = Set Value 1 or current value > Set Value 1 |
| | Ring counter | Current value = Set Value 2 |
| Leak current | 0.5 mA maximum | |
| Polarity | (-) common within the module | |
| External power supply | 12/24 V DC (30 V DC maximum) | |
| Insulation method | Photocoupler | |

4.19 Single-Axis Pulse Positioning Module

| Name and function of each part | | Type | EH-POS | |
|---|----------------------|--|--|---|
|  | | Weight | Approx. 0.17 kg (0.37 lb.) | |
| | | Dimensions (mm(in.)) | | |
| | | | | |
| No. | Name | Function | Remarks | |
| 1] | Lock button | When dismantling the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | | |
| 2] | Reset switch | Resets the unit when the module is malfunctioning. | | |
| 3] | Positioner connector | Used to connect the positioner | | |
| 4] | I/O connector | Pulse output, external control input connector (20-pin) | Connector on cable: Sumitomo 3M Solder type: 10120-3000VE Case: 10320-52F0-008 (or equivalent) | |
| 5] | Dip switches | Perform initialization settings for the pulse output method (CW/CWW, CK/Direction switching) and output logic (positive/negative logic). Also used to set whether or not external input is used. Turn off the power and remove the module to perform settings. | (Note) Setting dip switches 5 and 6 to ON causes the external RUN input to become invalid (± 0). | |
| | Switch number | ON | OFF | Additional information |
| | 1, 2 | 1 | 2 | |
| | | ON | ON | CW/CCW pulse output (Negative logic) |
| | | ON | OFF | CW/CCW pulse output (Positive logic) |
| | | OFF | ON | Clock pulse/Directional signal output (Negative logic) |
| | | OFF | OFF | Clock pulse/Directional signal output (Positive logic) |
| | 3 | Unused | Unused | |
| | 4 | COIN not input | COIN input | Sets whether or not the positioning complete signal (COIN) is externally input. |
| | 5 | + 0. RUN not input | + 0. input | Sets whether or not the + direction over-run (+O.RUN) is externally input. |
| | 6 | - 0. RUN not input | – 0. input | Sets whether or not the – direction over-run (–O.RUN) is externally input. |

General specifications

| Item | Specification |
|-------------------------------|---|
| Current consumption | 5 V DC, 300 mA, 600 mA (When the positioner is connected) Supply power from the power supply module. |
| Operating ambient temperature | 0 to 55°C (Storage ambient temperature -10 to 75°C) |
| Operating ambient humidity | 20 to 90% RH (no condensation) (Storage ambient humidity 10 to 90% RH (no condensation)) |
| Usage environment | No corrosive gases, no excessive dirt |
| Cooling method | Natural air cooling |
| Weight | Approx. 0.17 kg (0.37 lb.) |
| External dimensions (mm) | 30 (1.18 in.) (W) × 100 (3.94 in.) (H) × 95 (37.4 in.) (D) (170 (6.7 in.) (D) with I/O connector) |
| External power supply | 5 V DC ± 5%, 100 mA (For pulse chain output) 24 V DC, 10 mA/point (For external control input) |

Function specifications



| Item | | Specification |
|------------------------------------|----------------------------------|--|
| Number of control axes | | 1 axis |
| Highest frequency | | 400 k pulse/s |
| Positioning data | Capacity | 256 points |
| | Setting procedures | 1. Sequence program 2. Positioner (Note that the positioner is optional.) |
| Positioning | Method | 1. Absolute system 2. Absolute system + increment system 3. Increment system |
| | Positioning command | 1. Pulse specification 2. μ m specification 3. inch specification 4. degree specification |
| | Speed command | Automatic, manual, home position return 6.25 pulse/s to 400 k pulse/s μ m/s, inch/s, degree/s input function |
| | Speed stage | 10 stages |
| | Acceleration/deceleration system | Trapezoid acceleration/deceleration S-curve acceleration/deceleration (3-stage acceleration/deceleration) |
| | Acceleration/deceleration time | 1 to 65,535 ms |
| | Backlash | 0 to 255 pulse |
| | High/low limit setting | +2,147,483,647 to -2,147,483,648 pulse |
| | Pulse output method | 1. Pulse chain (CW/CCW) 2. Clock + direction signal (CK/direction) (Use dip switches 1 and 2 to select the pulse output method and to switch between positive and negative logic for the selected method.) |
| | Pulse output procedures | 1. Open collector output (Photocoupler insulation) 2. Line driver output (Photocoupler insulation) |
| Home position return function | | 1. Arbitrary origin 2. Low speed origin return 3. High speed origin return 1 4. High speed origin return 2 5. Absolute value encoder home position return |
| Teaching | | Possible |
| Manual (JOG) operation | | Pulse output by manual input signal |
| Operation when the CPU has stopped | | Operation may be performed via I/O setting or using the positioner. |
| I/O allocation | | Word 4W/4W |
| Absolute value encoder input | | Supports the Σ series and ΣII series by Yasukawa Denki and the P series by Sanyo Denki. |

- (Notes) • Stopping the CPU during operation causes the motor to decelerate and come to a stop.
- The maximum travel per single movement is 2,147,483,647 pulses. When an operation was attempted to move beyond the maximum travel, the motor decelerates and stops at the maximum travel position.



I/O interface specifications

| Item | | Specification |
|--------|--|--|
| Output | Pulse chain (CW/CCW) output Clock + direction signal (CK/direction) Pulse output | 1. Open collector output Photocoupler insulation (30 V DC maximum, 30 mA resistive load) 2. Line driver output Photocoupler insulation (5 V DC) |
| | Maximum leakage current | 100 μ A or less |
| | Maximum voltage drop at ON | 0.8 V maximum (at output current 30 mA) |
| Input | Input voltage | 10.8 to 30 V DC |
| | Input impedance | Approx. 2.2 k Ω |
| | Input current | Approx. 10 mA (24 V DC) |
| | Operation voltage | Minimum ON voltage 9 V |
| | | Maximum OFF voltage 3.6 V |
| | Input lag | ON \rightarrow OFF 1 ms or less |
| | | OFF \rightarrow ON 1 ms or less |
| | Polarity | Only the encoder signal input uses the plus common inside the module. Other inputs do not specify polarity. |
| | Insulation method | Photocoupler |



A) Positioner connector (CN1): Conforms to RS-422.

| Terminal layout | No. | Signal | Signal name | Internal ladder diagram |
|--|-----|-----------|------------------|---|
|  | 1] | Do – | Driver output – |  |
| | 2] | Do + | Driver output + | |
| | 3] | Ri – | Receiver input – | |
| | 4] | Ri + | Receiver input + | |
| | 5] | 5 V DC + | + 5 V | |
| | 6] | 0 V | GND | |
| | 7] | 0 V | GND | |
| | 8] | 12 V DC – | -12 V | |


B) I/O connector (CN2)

| Terminal layout | No. | Signal | Signal name | Internal ladder diagram |
|---|-----|-----------|--------------------------------|--|
|  | 1] | 5 V DC + | Pulse output power supply |  |
| | 2] | 0 V | | |
| | 3] | CW | Open collector pulse output | |
| | 4] | CCW | | |
| | 5] | CW + | Line driver pulse output | |
| | 6] | CW – | | |
| | 7] | CCW + | | |
| | 8] | CCW – | | |
| | 9] | C + | Encoder C phase | |
| | 10] | C – | | |
| | 11] | PS – | Encoder location signal | |
| | 12] | PS + | | |
| | 13] | COIN | Positioning complete | |
| | 14] | PROG | Home position LS | |
| | 15] | + 0. RUN | + Over run | |
| | 16] | – 0. RUN | – Over run | |
| | 17] | MODE-SEL | Control mode switch | |
| | 18] | M-CW | Manual CW | |
| | 19] | M-CCW | Manual CCW | |
| | 20] | 24 V DC + | Control power supply | |

4.20 4-Axes Pulse Positioning Module

| <div> <div>Name of Parts</div>  </div> | | Model | EH-POS4 |
|---|------------------|--|---|
| | | Weight | Approx. 0.13 kg (0.29 lb.) |
| | | Dimension(mm) |  |
| | | | |
| No. | Name | Function | Remarks |
| 1] | Lock button | When dismantling the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | |
| 2] | LED cover | This indicates the status of this module. | |
| 3] | Wiring connector | <p>This is connector for pulse output and external control input.</p> <p>Connector for cable:</p> <p>Manufacturer 1 : Fujitsu Takamisawa</p> <p>Solder type</p> <p>Socket: FCN-361J040-AU</p> <p>Cover: FCN-360C040-E</p> <p>Crimp type</p> <p>Housing: FCN-363J040</p> <p>Contact: FCN-363J-AU</p> <p>Cover: FCN-360C040-E</p> <p>Crimping tool : FCN-367J040-AU/F</p> <p>Manufacturer 2 : AMP</p> <p>Solder type : 1473381-1</p> | |

LED display

| Outlook | Name | Signal | Contents | Coler |
|---|------|----------------|---|--------------|
|  | POW | Power source | Lighted when the module is valid | Yellow green |
| | RN* | RUN | Lighted in positioning | Yellow green |
| | SB* | Stand by | Lighted in stand by mode | Yellow green |
| | OR* | Overrun error | Lighted when overrun is occurred | Red |
| | CME | Command error | Lighted when command error is occurred | Red |
| | WDE | Watchdog error | Lighted when Watchdog error is occurred | Red |

Note 1: *=A (Axis A), B (Axis B), C (Axis C), D (Axis D)

Note 2: All of the LED are lighted when power on.

General Specification

| Item | Specification |
|-----------------------|--|
| Consumption current | 5 V DC , 850 mA (supplied from Power module) |
| Operation temperature | 0 to 55 °C |
| Storage temperature | -10 to 75 °C |
| Operation humidity | 20 to 90 % RH (without condensation) |
| Storage humidity | 10 to 90 % RH (without condensation) |
| Operating atmosphere | Free from corrosive gas and dust |
| Cooling | Natural air cooling |
| Weight | Approx. 0.13 k g |
| Dimension | 30(W) x 100(H) x 95(D) (mm) |
| External power source | 24 V DC, approx. 4.3 mA /point (for external input) |



Specification

| Item | | Specification |
|--------------------------------------|------------------------------------|--|
| Number of controlled axes | | 4 |
| Number of interpolation axes | | Linear interpolation : up to 4 axes Circular interpolation : 2 axes |
| Maximum speed | | 1 M pulse/ s |
| Positioning data | Number of positioning points | Maximum 256 points/ axis (storage in the module) |
| | Setting method | 1) Ladder Program 2) Positioning Data Setting tool |
| Positioning | Positioning mode | 1) Absolute mode 2) Absolute and Incremental 3) Incremental |
| | Positioning Unit | 1) Pulse 2) μm 3) inch 4) degree |
| | Speed unit | 1 pulse/ s - 1M pulse/ s (Auto, Manual, Homing) $\mu\text{m/s}$, inch/s , degree/s (selectable by common parameter) |
| | Number of speed stage | Maximum 256 stages (in continuous operation) |
| | Acceleration and Deceleration | Linear S-curve (3 types) |
| | Acceleration and Deceleration time | 1 up to 65 535 ms |
| | Backlash | 0 - 65 535 pulses |
| | Operation range | - 2,147,483,648 up to + 2,147,483,647 pulses - 214,748,364.8 up to + 214,748,364.7 μm - 21,474.83648 up to +21,474.83647 inch - 21,474.83648 up to + 21,474.83647 degree |
| | Pulse train signal | 1) 2 Pulse signal (CW pulse and CCW pulse) 2) Pulse and Direction signal (PLS and SIG) (Selectable by common parameter) |
| Output method | | Line driver |
| Homing | | 1) Free home position 2) Low speed homing 3) High speed homing 1 (Off edge stop) 4) High speed homing 2 (Phase Z input stop) 5) Absolute encoder homing |
| Applied servo amp in absolute homing | | Hitachi AD series |
| Manual operation | | Manual command |
| Teaching function | | Teaching command |
| I/O assignment | | Word 4W/4W |
| Operation on CPU stopping | | Available |

Note: When CPU is turned "RUN" to "STOP" or "STOP" to "RUN", the servo motor stops.

Input / Output Interface



| Item | | | Specification |
|-------------|--|---------------|--|
| Output | Pulse & Sign | | Line driver (SN75158(TI)) |
| | "High" voltage | | Minimum 2.4 V |
| | "Low" voltage | | Maximum 0.4 V |
| Phase input | Phase Z input and Absolute encoder serial signal | | Line driver (input impedance: 220 ohm) |
| Input | Input voltage | | 20.4 up to 28.8 V DC |
| | Input impedance | | Approx. 5.6 k ohm |
| | Input current | | Approx. 4.3 mA (24 V DC) |
| | Operation voltage | "ON" voltage | Minimum 15 V DC |
| | | "OFF" voltage | Maximum 5 V DC |
| | Delay | "ON" to "OFF" | Maximum 1 ms |
| | | "OFF" to "ON" | Maximum 1 ms |
| | Polarity | | No |
| | isolation | | Photo-coupler |

| assignment | Pin assignment and signal | | | | Internal circuit |
|---|---------------------------|--------|------------|--------|---|
|  | left(CN2) | | right(CN1) | |  <p>Same circuit about Axis B, C, D</p> |
| | Axis C | Axis D | Axis A | Axis B | |
| | No. | No. | No. | No. | |
| | (41) | (61) | (1) | (21) | |
| | (42) | (62) | (2) | (22) | |
| | (43) | (63) | (3) | (23) | |
| | (44) | (64) | (4) | (24) | |
| | (45) | (65) | (5) | (25) | |
| | (46) | (66) | (6) | (26) | |
| | (47) | (67) | (7) | (27) | |
| | (48) | (68) | (8) | (28) | |
| | (49) | (69) | (9) | (29) | |
| | (50) | (70) | (10) | (30) | |
| | (51) | (71) | (11) | (31) | |
| | (52) | (72) | (12) | (32) | |
| | (53) | (73) | (13) | (33) | |
| | (54) | (74) | (14) | (34) | |
| | (55) | (75) | (15) | (35) | |
| | (56) | (76) | (16) | (36) | |
| | (57) | (77) | (17) | (37) | |
| | (58) | (78) | (18) | (38) | |
| | (59) | (79) | (19) | (39) | |
| | (60) | (80) | (20) | (40) | |
| | | | | | COM(+24V) |


I/O Signal

| Axis C | Axis D | Axis A | Axis B | I/O | Symbol | Name | Remark |
|-----------|-----------|-----------|-----------|--------|-----------|---------------------------------|---|
| No. | No. | No. | No. | | | | |
| 41 | 61 | 1 | 21 | Output | | | |
| 42 | 62 | 2 | 22 | | CW+ | Pulse train output | Line driver |
| 43 | 63 | 3 | 23 | | CW- | (CW pulse/ PLS) | |
| 44 | 64 | 4 | 24 | | CCW+ | Pulse train output Or direction | |
| 45 | 65 | 5 | 25 | | CCW- | signal (CCW pulse/ SIG) | |
| 46 | 66 | 6 | 26 | | | | |
| 47 | 67 | 7 | 27 | | | | |
| 48 | 68 | 8 | 28 | | | | |
| 49 | 69 | 9 | 29 | Input | Z-(PS-) | Phase Z input | Phase Z output from servo Amp (Absolute encoder serial signal) |
| 50 | 70 | 10 | 30 | | Z+(PS+) | (Absolute encoder signal) | |
| 51 | 71 | 11 | 31 | | SRDY | Servo ready | Ready output from servo AMP |
| 52 | 72 | 12 | 32 | | COIN | In position | Positioning complete signal |
| 53 | 73 | 13 | 33 | | PORG | Origin signal | Origin limit switch |
| 54 | 74 | 14 | 34 | | +ORUN | + Overrun | Overrun for normal direction |
| 55 | 75 | 15 | 35 | | -ORUN | - Overrun | Overrun for reversal direction |
| 56 | 76 | 16 | 36 | | MODSEL | Control mode select | Control mode selective switch In speed and positioning mode |
| 57 | 77 | 17 | 37 | | | | |
| 58 | 78 | 18 | 38 | | | | |
| 59 | 79 | 19 | 39 | | | | |
| 60 | 80 | 20 | 40 | Common | COM(+24V) | Input common | 24 V DC or GND of external power source |

4.21 Ethernet Module


| Name and function of each part | | Type | EH-ETH |
|---|--------------------|---|---|
|  | | Weight | Approx. 0.15 kg (0.33 lb.) |
| | | Dimensions (mm(in.)) | |
| | | |  |
| No. | Name | Function | Remarks |
| 1] | LED cover | This is the cover for the LED that displays the status. | |
| 2] | Dip switch | Sets the operation mode. | |
| 3] | Reset switch | Resets when the module is abnormal. | |
| 4] | Ethernet connector | RJ45 type connector | |
| 5] | Lock button | When dismantling the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | |

Explanation of LED display

| Front diagram | Display | Description of display | ON status | OFF status |
|---|---------|--|---------------------------|----------------------|
|  | POW | Indicates the Ethernet line connection status. | Connected | Not connected |
| | Tx/Rx | Indicates the data transmission and reception status. | Sending or receiving | No data transmission |
| | I. ERR | Indicates Ethernet information setting error. | Error present | No error |
| | ERR | Indicates whether or not a transmission or reception error has occurred. | Error present | No error |
| | STATUS | Indicates whether or not a hardware error has occurred. | Error present (flashes)*1 | No error |

*1: Displays the type of a hardware error by the illumination color and flash count. For details, refer to the Ethernet Module Application Manual (NJI-361(X)).

Operation mode setting

| External view | Bit | | | | | | | | Description |
|---|-------------|-------------|--------------------------------------|---|---|---|-------------|-------------|--|
| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | |
|  | O N | O N | Least significant byte of IP address | | | | | | Sets Ethernet information from the user program |
| | | O F F | | | | | | | Sets Ethernet information using general Web browser. |
| | O F F | * | * | * | * | * | O N | O N | Transmission/reception test mode |
| | | | | | | | | O F F | External loop-back check |
| | | | | | | | O F F | O N | Internal loop-back check |
| | | | | | | | | O F F | Normal operation |

Note: (1) “*” indicates that it is not dependent of the bit status.

(2) When the least significant byte of the IP address is to be set, the switch OFF becomes “0,” and ON becomes “1.”

(3) Do not set all of the least significant bits of the IP address to OFF.

General specifications

| Item | Specification |
|---|--|
| Internal current consumption | 5 V DC, 260 mA |
| Operating ambient temperature, humidity | 0 to 55°C, 20 to 90% RH (no condensation) |
| Storage ambient temperature, humidity | -10 to 75°C, 10 to 90% RH (no condensation) |
| Noise proof feature | <ul style="list-style-type: none"> Noise voltage 1,500 Vpp, noise pulse width 100 nsec, 1 μsec 3,000 V at the electrostatic noise metal exposing section |
| Operating environment | No corrosive gases, no excessive dust |
| Structure | Open wall-mount type |
| Cooling method | Natural air cooling |
| Mounted slot position | Slots 0 to 2 on the basic base: up to two units can be mounted at the same time |
| I/O assignment | COMM |

Performance specifications


| Item | | Specification |
|-------------------------------------|----------------------------|--|
| Communication specification | Ethernet standard | IEEE802.3 standard |
| | Transfer modulation method | Base band |
| | Medium access method | CSMA/CD |
| | Transfer speed | 10 Mbps |
| | Max. length Hub - EH-ETH | 100 (m) |
| Number of ASR connection | | Maximum connection is 6 at once. Maximum data is 1454 bytes / each sending or receiving |
| H-protocol (Taskcode communication) | | 4 connections (max.) |

Functional specifications

| Item | Specification |
|---|---|
| Setup function | <ul style="list-style-type: none"> Select the setup mode using a DIP switch, and perform initial settings such as the IP address, transmission operation specification, transmission/reception area specification using a general-purpose Web browser. The IP address can also be set by programming with a ladder program. |
| Auto Sending/Receiving function, event transmission function | <ul style="list-style-type: none"> Data can be transmitted and received periodically by specifying an internal output signal in a table format. Data can be transmitted and received by signal variation (event) in a ladder program. |
| Task code communication | <ul style="list-style-type: none"> Either TCP/IP or UDP/IP can be specified. H series task code communication can be performed. |
| Test function | <ul style="list-style-type: none"> Internal loop and external loop check functions are supported. One-to-one transmission/reception test function is supported. |



Example of setup function

To create Ethernet information and an auto communication table, the setup page of the general Web browser is used. The following shows the setup tool screen.



Ethernet information setup page using a Web browser

4.22 DeviceNet Master Module

| Name and function of each part | | Type | EH-RMD |
|---|---------------------|---|---|
|  | | Weight | Approx. 0.15 kg (0.33 lb.) |
| | | Dimensions (mm(in.)) |  |
| | | | |
| No. | Name | Function | Remarks |
| 1] | LED cover | This is the cover for the LED that displays the network status and error information. | |
| 2] | Dip switch | Sets the node address and baud rate. | |
| 3] | Reset switch | Resets the module. | |
| 4] | DeviceNet connector | Connects to the network. | |
| 5] | Lock button | When dismantling the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | |

General specifications

| Item | Specification |
|-------------------------------|---|
| Current consumption | 5 V DC, 280 mA |
| Operating ambient temperature | 0 to 55°C (Storage ambient temperature -10 to 75°C) |
| Operating ambient humidity | 20 to 90 % RH (no condensation) (Storage ambient humidity 10 to 90 % RH (no condensation)) |
| Usage environment | No corrosive gases, no excessive dirt |
| Cooling method | Natural air cooling |
| External power supply | 24 V DC \pm 10 % (supplied from communication connector) |

Performance specifications

| Performance specifications | | | | | | |
|----------------------------|------------------------------|---|---------------|--|----------------|--|
| No. | Item | Performance specification | | | | |
| | | LINK mode | | REMOTE mode | | |
| 1 | No. of installed units | 2 units (only on communication slot *) | | 4 units (only on communication slot *) | | |
| 2 | No. of slave-connected units | 63 units | | | | |
| 3 | I/O assignment | LINK | | REMOTE2 | | |
| 4 | Output data | 256 words (WL0-) | | 64 words (WX1000-, WY1000-) | | |
| 5 | Input data | 256 words (WL200-) | | | | |
| 6 | Communication protocol | DeviceNet 2.0 standard | | | | |
| 7 | Supported connections | 1] Poll I/O connection 2] Bit strobe I/O connection 3] Cyclic I/O connection 4] Change of state (COS) I/O connection 5] Explicit message connection | | | | |
| 8 | Connection mode | 1] Multi-drop connection 2] Multi-branch connection using T branch | | | | |
| 9 | Communication speed | 500k/250k/125kbps (set by DIP switches) | | | | |
| 10 | Cable | Dedicated DeviceNet cable | | | | |
| 11 | Communication distance | Communication | Maximum | Each sub-line | Total sub-line | The maximum network length shows the value when a thick trunk cable is used. |
| | | 500 kbps | 100 m or less | 6 m or less | 39 m or less | |
| | | 250 kbps | 250 m or less | 6 m or less | 78 m or less | |
| | | 125 kbps | 500 m or less | 6 m or less | 156 m or less | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

* Refer to chapter 4.7 Base unit.

Note: The followings are recommended communication cables and crimp type terminals for the cables:

Mfg'd by Showa Densen TDN18-**G Trunk cable (thick cable)

TDN24-**G Drop cable (thin cable)

(** indicates the number of m's. However, available lengths are 10/30/50/100/300/500m.)


Mfg'd by Nichifu Trunk cable crimp type terminal TME TC-2-11 (power supply line)

TME TC-1.25-11 (communication line)


Drop cable crimp type terminal TME TC-0.5 (common power supply line/communication line)

Crimp tool NH-32

Node address and communication speed settings

|  NA32 NA16 NA8 NA4 NA2 NA1 DR1 DR0 →ON | Node address | NA1 | NA2 | NA4 | NA8 | NA16 | NA32 |
|--|--------------|-----|-----|-----|-----|------|------|
| 0 | OFF | OFF | OFF | OFF | OFF | OFF | OFF |
| 1 | ON | OFF | OFF | OFF | OFF | OFF | OFF |
| 2 | OFF | ON | OFF | OFF | OFF | OFF | OFF |
| . | | | | | | | |
| . | | | | | | | |
| 62 | OFF | ON | ON | ON | ON | ON | ON |
| 63 | ON | ON | ON | ON | ON | ON | ON |
| Band rate | DR0 | | | DR1 | | | |
| 125 | OFF | | | OFF | | | |
| 250 | ON | | | OFF | | | |
| 500 | OFF | | | ON | | | |
| | ON | | | ON | | | |

4.23 DeviceNet Slave Module

| Name and function of each part | | Type | EH-IOCD |
|---|-------------------------|---|----------------------------|
|  | | Weight | Approx. 0.17 kg (0.37 lb.) |
| | | Dimensions (mm(in.)) | |
| | | | |
| No. | Name | Function | Remarks |
| 1] | LED | This is the cover for the LED that displays the network status and error information. | |
| 2] | Dip switch 1 | Sets the node address and baud rate. | |
| 3] | Reset switch | Resets the module. | |
| 4] | Communication connector | Connects to the network. | |
| 5] | Dip switch 2 | Sets to retain/clear output for the output module on the EH-10CD. | |
| 6] | Lock button | When dismounting the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | |

General specifications

| Item | Specification |
|-------------------------------|---|
| Current consumption | 5 V DC, 320 mA |
| Operating ambient temperature | 0 to 55°C (Storage ambient temperature -10 to 75°C) |
| Operating ambient humidity | 20 to 90% RH (no condensation) (Storage ambient humidity 10 to 90% RH (no condensation)) |
| Usage environment | No corrosive gases, no excessive dirt |
| Cooling method | Natural air cooling |
| External power supply | 24 V DC \pm 10 % (supplied from communication connector) |

Performance specifications

| Performance Specifications | | | | | | |
|----------------------------|------------------------------|---|------------------------|----------------------|-----------------------|--|
| No. | Item | Specification | | | | |
| 1] | No. of installed I/O modules | 16 units/EH-IOCD (Use EH-IOC/H to install 9 or more units.) | | | | |
| 2] | Output data | 256 words | | | | |
| 3] | Input data | 256 words | | | | |
| 4] | Communication protocol | DeviceNet 2.0 standard | | | | |
| 5] | Supported connections | 1] Poll I/O connection 2] Bit Strobe I/O connection 3] Cyclic I/O connection 4] Change of state (COS) I/O connection 5] Explicit message connection | | | | |
| 6] | Connection mode | 1] Multi-drop connection 2] Multi-drop connection using T branch | | | | |
| 7] | Baud rate | 500k/250k/125kbps (switched by DIP switches) | | | | |
| 8] | Cable | Dedicated DeviceNet cable (see Note below) | | | | |
| 9] | Communication distance | Communication speed | Maximum network length | Each sub-line length | Total sub-line length | The maximum network length shows the value when a thick trunk cable is used. |
| | | 500 k bits/s | 100 m or less | 6 m or less | 39 m or less | |
| | | 250 k bits/s | 250 m or less | 6 m or less | 78 m or less | |
| | | 125 k bits/s | 500 m or less | 6 m or less | 156 m or less | |

Note: The following are recommended communication cables and crimp type terminals for the cables:

Mfg'd by Showa Densen TDN18-**G Trunk cable (thick cable)

TDN24-**G Drop cable (thin cable)

(** indicates the number of m's. However, available lengths are 10/30/50/100/300/500m.)


Mfg'd by Nichifu Trunk cable crimp type terminal TME TC-2-11 (power supply line)

TME TC-1.25-11 (communication line)

Drop cable crimp type terminal TME TC-0.5 (common power supply line/communication line)

Crimp tool NH-32


Node address and communication speed settings

| | | | | | | | |
|---|--------------|-----|-----|-----|-----|------|------|
|  | Node address | NA1 | NA2 | NA4 | NA8 | NA16 | NA32 |
| | 0 | OFF | OFF | OFF | OFF | OFF | OFF |
| | 1 | ON | OFF | OFF | OFF | OFF | OFF |
| | 2 | OFF | ON | OFF | OFF | OFF | OFF |
| | . | | | | | | |
| | 62 | OFF | ON | ON | ON | ON | ON |
| | 63 | ON | ON | ON | ON | ON | ON |
| | Band rate | DR0 | | | DR1 | | |
| | 125 | OFF | | | OFF | | |
| | 250 | ON | | | OFF | | |
| | 500 | OFF | | | ON | | |
| | | ON | | | ON | | |

Supported I/O modules.

| Type | Input size (Word) | Output (word) | Type | Input size (Word) | Output (word) |
|------------------------|-------------------|---------------|----------------------|-------------------|---------------|
| EH-XD8/XD16/XDL16 | 1 | 0 | EH-YT64/YTP64 | 0 | 4 |
| EH-XA16/XAH16 | 1 | 0 | EH-AX44/8V/8H/8I/8IO | 8 | 0 |
| EH-XD32(E)/ XDL32(E) | 2 | 0 | EH-AY22/2H/4V/4I | 0 | 8 |
| EH-XD64 | 4 | 0 | EH-PT4 | 4 | 0 |
| EH-YT8/YTP8/YT16/YTP16 | 0 | 1 | EH-POS/4 | 4 | 4 |
| EH-YS4/YR8B/YR12/YR16 | 0 | 1 | EH-CU/CUE | 5 | 3 |
| EH-YT32(E)/ YTP32(E) | 0 | 2 | | | |


4.24 PROFIBUS Master Module

| Name and function of each part | | Type | EH-RMP |
|---|-------------------------|---|---|
|  | | Weight | Approx. 0.13 kg (0.286 lb.) |
| | | Dimensions (mm(in.)) | |
| | | | |
| No. | Name | Function | Remarks |
| 1] | Lock button | When dismantling the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | |
| 2] | LED cover | Displays the communication and other statuses of the module. | |
| 3] | Configuration connector | Used to transfer the configuration data. D-sub 9-pin male | The temperature gets high when connected. Exercise caution when handling the connector. |
| 4] | Reset switch | Resets the unit when the module is malfunctioning. | |
| 5] | Dip switch *1 | Specifies the data transfer mode for the slave when the CPU is in the stop state. | |
| 6] | Terminal end switch | Turns on when this module is at the end of a network. | |
| 7] | Network connector | A connector for connecting to a network. D-sub 9-pin female | The temperature gets high when connected. Exercise caution when handling the connector. |

*1: Prior to setting the DIP switches, remove the module.

When the setting of the DIP switches is complete, paste the attached protective sheet

Explanation of LED display

| Front diagram | Display | Description of display |
|---|---------|--|
|  | RDY | Indicates the hardware abnormality of this module. |
| | RUN | Indicates the communicating status with the slave. |
| | ERR | Indicates an error on the network. |
| | TOKEN | Always lit. |
| | STATUS | Indicates a hardware abnormality, parameter abnormality and other status of this module. |

General specifications

| Item | Specification |
|-------------------------------|--|
| Operating ambient temperature | 0 to 55°C (Storage ambient temperature –10 to 75°C) |
| Operating ambient humidity | 20 to 90 % RH (no condensation), storage ambient humidity 10 to 90 % RH (no condensation) |
| Current consumption | 5 V DC 600 mA |
| Usage environment | No corrosive gases, no excessive dirt |
| Cooling method | Natural air cooling |


Functional specifications

| Item | Specification |
|------------------------------|--|
| No. of installed units | 2 units/CPU (only on communication slot *1) |
| No. of supported slave units | Maximum of 124 units. However, a repeater is required to connect 32 or more units. |
| No. of output words | 256 words |
| No. of input words | 256 words |
| I/O assignment | LINK *2 |
| Band rate: Segment length | 9.6 kbps : 1,200 m 19.2 kbps : 1,200 m 45.45 kbps : 1,200 m 93.75 kbps : 1,200 m 187.5 kbps : 1,000 m 500 kbps : 400 m 1,500 kbps : 200 m 3 Mbps : 100 m 6 Mbps : 100 m 12 Mbps : 100 m |
| Self-diagnostics | System ROM/RAM check Watchdog timer |
| GSD file | File name: Hita1004.gsd Please contact our sales department. |
| Configurator | HMS Fieldbus, configuration software made by AB, is used. Please contact our sales department regarding the purchase. |

*1: Refer to chapter 4.7 Base unit.

*2: Among 1024 words, only 512 words are used. Do not use the remaining area.

4.25 PROFIBUS Slave Module

| Name and function of each part | | Type | EH-IOCP |
|---|---------------------|---|---|
|  | | Weight | Approx. 0.16 kg (0.35 lb.) |
| | | Dimensions (mm(in.)) | |
| | | | |
| No. | Name | Function | Remarks |
| 1] | Lock button | When dismantling the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | |
| 2] | LED | Displays the communication and other statuses of the module. | |
| 3] | Rotary switches | Sets the node address. | |
| 4] | Network connector | A connector for connecting to a network. D-sub 9-pin female | The temperature gets high when connected. Exercise caution when handling the connector. |
| 5] | Dip switch | Specifies the output data for the output module when the network is abnormal. | |
| 6] | Reset switch | Resets the unit when the module is malfunctioning. | |
| 7] | Terminal end switch | Turns on when this module is at the end of a network. | |

General specifications

| Item | Specification |
|-------------------------------|--|
| Operating ambient temperature | 0 to 55°C (Storage ambient temperature -10 to 75°C) |
| Operating ambient humidity | 20 to 90 % RH (no condensation), storage ambient humidity 10 to 90 % RH (no condensation) |
| Current consumption | 5 V DC 600 mA |
| Usage environment | No corrosive gases, no excessive dirt |
| Cooling method | Natural air cooling |

Functional specifications





| Item | Specification |
|------------------------------------|--|
| No. of installed I/O modules | 16 units/EH-IOCP (use EH-IOC to install 9 and more units.) |
| Node address setting range | 1 to 99 |
| Input/output capacity | 208 words |
| Data update time | 5 ms |
| Transmission speed: Segment length | 9.6 kbps : 1,200 m 19.2 kbps : 1,200 m 93.75 kbps : 1,200 m 187.5 kbps : 1,000 m 500 kbps : 400 m 1,500 kbps : 200 m 3 Mbps : 100 m 6 Mbps : 100 m 12 Mbps : 100 m |
| Self-diagnostics | System ROM/RAM check Watchdog timer |
| GSD file | File name: Hita 049.gsd Please contact our sales department. |

Supported I/O modules.

| Type | Input size (Word) | Output (word) | Type | Input size (Word) | Output (word) |
|------------------------|----------------------|------------------|----------------------|----------------------|------------------|
| EH-XD8/XD16/XDL16 | 1 | 0 | EH-YT64/YTP64 | 0 | 4 |
| EH-XA16/XAH16 | 1 | 0 | EH-AX44/8V/8H/8I/8IO | 8 | 0 |
| EH-XD32(E)/ XDL32(E) | 2 | 0 | EH-AY22/2H/4V/4I | 0 | 8 |
| EH-XD64 | 4 | 0 | EH-PT4 | 4 | 0 |
| EH-YT8/YTP8/YT16/YTP16 | 0 | 1 | EH-POS/4 | 4 | 4 |
| EH-YS4/YR8B/YR12/YR16 | 0 | 1 | EH-CU/CUE | 5 | 3 |
| EH-YT32(E)/ YTP32(E) | 0 | 2 | | | |

4.26 CPU Link Module (Coaxial cable)

4.26 CPU Link Module (Coaxial type)

| Name and function of each part | | Type | EH-LNK |
|--|---|--|--|
|  <p>1] Lock button</p> <p>2] LED for Module information display</p> <p>3] Station No. switch (x10)</p> <p>4] Station No. switch (x1)</p> <p>5] Error indication clear switch</p> <p>6] Reset switch</p> <p>7] Coaxial cable connector for send</p> <p>8] Coaxial cable connector for receive</p> | | Weight | Approx. 0.15 kg |
| | | Dimensions (mm) |  |
| No. | Name | Function | Remark |
| 1] | Lock button | When dismantling the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | |
| 2] | LED for Module information display | It is shown that data transmission is carried out. And error information are indicated. | |
| 3] | Station No. switch (x10) | <p>The Link station number is determined by this switch.</p> <p>Setting of this switch becomes valid when the power is ON or reset switch is pushed down on.</p> <p>(Example)</p> <div style="display: flex; align-items: center; justify-content: center;"> <div style="text-align: center;">  x10 -- 1 </div> <div style="font-size: 3em; margin: 0 10px;">}</div> <div style="text-align: center;"> <p>Station No. 18</p> </div> </div> <div style="text-align: center; margin-top: 10px;">  x1 -- 8 </div> | <ul style="list-style-type: none"> - Address range is from No.00 to 63. - When station no. is duplicated, duplicate station No. error occurs. - If No.00 station does not exist in link system, it will not work. |
| 4] | Station No. switch (x1) | | |
| 5] | Error indication clear switch | Contents of display on ERR LED are cleared by this switch. However, the error is indicated again if it has not yet been cancelled. | The ERR LED will be extinguished. The CPU error information will not be cleared. |
| 6] | Reset switch | Hardware reset is made by this switch. Data in WL area is also cleared. | * |
| 7] | Coaxial cable connector for send (TXD) | It sends data to other station. Connect to RXD connector on next station. | |
| 8] | Coaxial cable connector for receive (RXD) | It receives data from other station. Connect to TXD connector on next station. | |

* The CPU module will detect a "Link Module Error (error code: 59H)" when the reset switch is pressed.
Resolve the CPU module error after the link module resumes normal operations when the reset switch has been pressed.

General Specification

| Item | | Specification |
|-----------------------|------------------------|------------------------------|
| General Specification | Operating temperature | 0 to 55°C |
| | Preserving temperature | − 10 to 75°C |
| | Operating humidity | No condensation 20 to 90% RH |
| | Preserving humidity | No condensation 10 to 90% RH |
| | Current consumption | 5V DC Approx. 550 mA |

Functional Specification


| Item | | | Specification |
|-----------------------------|--|------------------|--|
| Functional Specification | No. of connected Link module | | Max. 64 units per Link system |
| | No. of mounted units | | Max. 2 units per CPU (Only on communication slot *1) |
| | No. of Link points | | 1,024 words per Link system (2,048 words per 2 Link systems) *2 |
| | Data delivery system | | Common data area system |
| | Send / Receive distinction on data area allocation | | Parameter setting from peripheral device |
| | Designation of Station No. | | 0 to 63 ; designated by rotary switch |
| | Communication speed | | 1.0 Mbps |
| | Transfer method | | Half – duplex serial transfer, frame synchronization |
| | Communication method | | Token passing |
| | Modulation method | | Base band |
| | Refresh time | | Approx. 390ms in case of 1,024 words communication with 64 stations connected *3 |
| | Error check | | CRC, overrun check, time out, open circuit, parameter error (dual designation of station No., overlapped Link area, etc.) |
| | Self – diagnosis | | System ROM / RAM check, watchdog timer check, transfer loop back check |
| Transfer path Specification | Transfer path form | | Loop type |
| | Cable length | Between stations | Max. 500m |
| | | Total extension | Max. 1,000m |
| | Error station processing | | Bypass system |
| | Recommended cable | | 5D2V with shield or equivalent |
| | Recommended connector | | 413631-1 (made by AMP) or equivalent |

*1 Refer to chapter 4.7 Base unit.


*2 It is not possible to assign retentive area.

*3 This could be longer if other peripheral devices access via Link network.


Display of the LED

| Appearance | Name | Color | Display |
|---|------|-------|--|
|  | TXD | Green | Indicates the status of sending data by blinking. |
| | RXD | Green | Indicates the status of receiving data by blinking. |
| | RUN | Green | Indicates the normal status by turn on. |
| | ERR | Red | Normal state : Turn off Error (data link is possible) : Blinking (blinking in 1 sec intervals) Error (data link is impossible) : Blinking (blinking in 0.5 sec intervals) or Turn on |


(1) In normal state

| Appearance | Status of LED display / Status of Link module |
|---|--|
|  | <p>RUN LED is turned on. LED of TXD / RXD is blinking when data are transmitted or received.</p> <p>Link module do communication with other station.</p> <p>* It becomes the same indication when the warning that a data link is possible occurs.</p> |


(2) In hardware failure (Watchdog timer error, ROM / RAM error)

| Appearance | Status of LED display / Status of Link module |
|---|--|
|  | <p>ERR LED is turned on.</p> <p>Link module do not communication with other station.</p> |

(3) In serious failure (Overlap of station No, Outside of range of station No. etc.)

| Appearance | Status of LED display / Status of Link module |
|--|---|
|  | <p>ERR LED blinking in 0.5 sec intervals.</p> <p>Link module do not communication with other station.</p> |

(4) In Warning (CRC error, Time out error in receiving peripheral data, etc.)

| Appearance | Status of LED display / Status of Link module |
|---|--|
|  | <p>ERR LED blinking in 1 sec intervals.</p> <p>Link module do not communication temporarily with other station.</p> <p>(When the same error frequently occurs, Link module doesn't communicate with other station.)</p> |

Caution

1. The CPU module which can't use EH-LNK.

The list of the CPU which can't use EH-LNK is shown in the following.

| CPU Type | Version |
|-------------------|-------------------------------|
| EH-CPU104 / 208 | Not supported |
| EH-CPU104A / 208A | |
| EH-CPU308 / 316 | |
| EH-CPU308A / 316A | Supported by all the versions |
| EH-CPU448 / 448A | Ver. C3.22 / C4.00 or later |
| EH-CPU516 / 548 | Supported by all the versions |




2. Mount

Mount a CPU link module in either of 0 slot from 2 slot of the basic base. It can't be mounted on the slot except for the above of the basic base and the expansion base.

3. Data link with large H series.

The timing when data are renewed in the large H series and EH-150 is different. EH-150 faces though it is renewed at the timing of I/O Refresh, and a large H series is renewed at the timing when a CPU referred to it. Be careful of the preparation of the program when a large H series is mixed in the link system with EH-150.

4.27 CPU Link Module (Optical type)

| Name and function of each part | | Type | EH-OLNK |
|---|--|---|--|
|  | | Weight | Approx. 0.15 kg |
| | | Dimensions (mm) | |
| | | | |
| No. | Name | Function | Remark |
| 1] | Lock button | When dismantling the module from a base unit, press this button and lift up the module. The module can be fixed firmly by a screw (M4, 10 mm (0.39 in.)). | |
| 2] | Module information display LED | Displays data transmission and receipt, error information and other details. Refer to the section on LED display for further details. | |
| 3] | Station No. setting switch (10-digits) | <p>This switch determines the number of the link station. The setting for this switch is validated when the power supply is switched on or when the reset switch is pressed. The setting range is between 00 and 63. (Ex.) Station No. 18</p> <div style="display: flex; align-items: center;"> <div style="text-align: center;">  10-digits ... 1 </div> <div style="text-align: center;">  1-digits ... 8 </div> <div style="margin-left: 20px;"> <p>} Station No. 18</p> </div> </div> | <ul style="list-style-type: none"> - Address range is from No.00 to 63. - When station no. is duplicated, duplicate station No. error occurs. - If No.00 station does not exist in link system, it will not work. |
| 4] | Station No. setting switch (1-digits) | | |
| 5] | Error display clearance switch | To clear the contents of the ERR LED display (the error will be displayed again if the cause is not resolved.) | The ERR LED will be extinguished. The CPU error information will not be cleared. |
| 6] | Reset switch | Performs the hardware reset procedure. | * |
| 7] | Connector for 5VDC power supply | If the link system needs to work while this module is not powered, supply 5VDC from another power source. | |
| 8] | Receiving optical cable connector (RXD) | To Receive data from other stations. Connect to the next station's TXD by optical cable. | |
| 9] | Transmission optical cable connector (TXD) | To send data to other stations. Connect to the next station's RXD by optical cable. | |

* The CPU module will detect a "Link Module Error (error code: 59H)" when the reset switch is pressed. Resolve the CPU module error after the link module resumes normal operations when the reset switch has been pressed.

General Specification

| Item | | Specification |
|-----------------------|------------------------|------------------------------|
| General Specification | Operating temperature | 0 to 55°C |
| | Preserving temperature | -10 to 75°C |
| | Operating humidity | No condensation 20 to 90% RH |
| | Preserving humidity | No condensation 10 to 90% RH |
| | Current consumption | 5V DC Approx. 550 mA |

Functional Specification


| Item | | | Specification |
|-----------------------------|--|------------------|--|
| Functional Specification | No. of connected Link module | | Max. 64 units per Link system |
| | No. of mounted units | | Max. 2 units per CPU (Only on communication slot *1) |
| | No. of Link points | | 1,024 words per Link system (2,048 words per 2 Link systems) *2 |
| | Data delivery system | | Common data area system |
| | Send / Receive distinction on data area allocation | | Parameter setting from peripheral device |
| | Designation of Station No. | | 0 to 63 ; designated by rotary switch |
| | Communication speed | | 1.0 Mbps |
| | Transfer method | | Half – duplex serial transfer, frame synchronization |
| | Communication method | | Token passing |
| | Modulation method | | Base band |
| | Refresh time | | Approx. 390ms in case of 1,024 words communication with 64 stations connected *3 |
| | Error check | | CRC, overrun check, time out, open circuit, parameter error (dual designation of station No., overlapped Link area, etc.) |
| | Self – diagnosis | | System ROM / RAM check, watchdog timer check, transfer loop back check |
| Transfer path Specification | Transfer path form | | Loop type |
| | Cable length | Between stations | Max. 1,000m |
| | | Total extension | Max. 15,000m |
| | Error station processing | | Bypass system (In case of supply a 5VDC from the outside.) |
| | Recommended Cable and connector | | CA7103-(1)M-(2)L(3)1 JAPAN OPNEXT product (1) Cable length, (2)Cable type, (3) Core number |

*1 Refer to chapter 4.7 Base unit.


*2 It is not possible to assign retentive area.

*3 This could be longer if other peripheral devices access via Link network.


LED indication

| Appearance | Name | Color | Description |
|---|------|-------|--|
|  | TXD | Green | Blinking when data is being transmitted. |
| | RXD | Green | Blinking when data is being received. |
| | RUN | Green | Lighting when the link module is operating normally. |
| | ERR | Red | Normal operations: Off "data link possible" errors: Blinks (1s cycle) "data link not possible" errors: Blinks (0.5s cycle) or lighting |


(1) Normal operations (LED display status and module status)

| Status of LED indication / Status of Link module | |
|---|---|
|  | <p>The RUN LED lights. The TXD and RXD LEDs blink while link data is being transmitted to/from other link modules.</p> <p>The same display will apply when a [data link possible] error occurs.</p> |


(2) Hardware error (Watchdog timer error and ROM/RAM error)

| | |
|---|--|
|  | <div>Status of LED indication / Status of Link module</div> <div>The ERR LED lights. Communications with other link modules will not be performed.</div> |
|---|--|

(3) Configuration error (Station number duplicated or out of the range, etc.)

| | |
|--|---|
|  | <p>Status of LED indication / Status of Link module</p> <p>The ERR LED blinks every 0.5 second. (0.5s ON / 0.5s OFF)</p> <p>Communications with other link modules will not be performed.</p> |
|--|---|

(4) Communication error (transmission errors, peripheral data receiving errors, etc.)

|  | <table><tr><th>Status of LED indication / Status of Link module</th></tr><tr><td>The ERR LED blinks every 1 second. (1s ON / 1s OFF) Communications with other link modules temporarily suspended. (Communications with other link modules will not be performed if the same error occurs frequently.)</td></tr></table> | Status of LED indication / Status of Link module | The ERR LED blinks every 1 second. (1s ON / 1s OFF) Communications with other link modules temporarily suspended. (Communications with other link modules will not be performed if the same error occurs frequently.) |
|---|--|--|---|
| Status of LED indication / Status of Link module | | | |
| The ERR LED blinks every 1 second. (1s ON / 1s OFF) Communications with other link modules temporarily suspended. (Communications with other link modules will not be performed if the same error occurs frequently.) | | | |

Caution

1. Supported CPU modules

The EH-OLNK can be used together with the following types of CPU module.

| CPU Type | Version |
|-------------------|-------------------------------|
| EH-CPU104 / 208 | Not supported |
| EH-CPU104A / 208A | |
| EH-CPU308 / 316 | |
| EH-CPU308A / 316A | Supported by all the versions |
| EH-CPU448 / 448A | Ver. C3.22 / C4.00 or later |
| EH-CPU516 / 548 | Supported by all the versions |


2. Available slot number

Mount the EH-OLNK on slot 0 to 2 of the basic base. The other slots of basic base and all slots of expansion base are not available.

3. Link data with large H series.

Timing of Link data refresh is different between large H series (CPU-xxHa, CPU2-xxH) and EH-150 series. In case of EH-150 series, link data is refreshed at scan end. But in case of H series, when a command is executed, the link data is refreshed directly. Make your program carefully when large H and EH-150 series are mixed in the link system.


4.28 Dummy Module

| Name and function of each part  | | Type | EH-DUM |
|---|-------------|---|-----------------------------|
| | | Weight | Approx. 0.06 kg (0.132 lb.) |
| | | Dimensions (mm(in.)) | |
| | | | |
| No. | Name | Function | Remarks |
| 1] | Lock button | Use when dismantling the unit from base unit. | |

Electronic parts are not mounted on the dummy module.



Use "Empty16" for I/O assignment.

4.29 Expansion Cable



| Name and function of each part  | | Type | EH-CB10 |
|---|------------------------------------|--|----------------------------|
| | | Weight | Approx. 0.24 kg (0.53 lb.) |
| | | Length | 1 m (3.281 ft.) |
| | | | |
| No. | Name | Function | Remarks |
| 1] | Connector for the base unit * | Connect to the connector of the basic base unit. | |
| 2] | Connector for the I/O controller * | Connect to the connector of the I/O controller. | |

* The connectors are represented as the base unit side and I/O controller side for presentation purposes, but either one can be connected to either side.


4.30 Terminal Unit for 32 / 64 points I/O module

| | | | |
|---|---------------------------------|--|--|
| Name and function of each part | | Type | HPX7DS-40V6 |
|  | | Weight | Approx. 0.22 kg |
| | | Dimensions (mm) |  |
| | | | |
| No. | Name | Function | Remark |
| 1] | Terminal block | This is the terminal block for connecting input / output signals. | |
| 2] | Connector | A Connector for 32 / 64 I/O modules. 20 x 2 line, 40 Pin | |
| 3] | Mounting holes | These are used when the terminal unit is attached to a panel. Use M4 x 25mm screws. | |
| 4] | Connector for mounting DIN rail | This is used when the terminal unit is attached to the DIN rail. | |


Terminal configuration

| Terminal | | Connector | |
|---|--|---|--|
|  | |  | |

4.31 Cable for 32 / 64 points module (connector type)

| Name and function of each part | | Type | EH-CBM01W / EH-CBM03W EH-CBM05W / EH-CBM10W |
|---|---|---|--|
|  | | Length | 1 m / 3 m / 5 m / 10 m |
| | | Diameter | AWG# 28 |
| No. | Name | Function | Remark |
| 1] | Connector for I/O module Connector for the terminal unit | Connector to the 32 / 64 I/O module. Connector to the terminal unit. | |
| 2] | Earth terminal | Use a terminal for class D grounding | |


4.32 Cable for 32 / 64 points module (open type)

| Name and function of each part | | Type | EH-CBM01 / EH-CBM03 EH-CBM05 / EH-CBM10 |
|---|---|---|--|
|  | | Length | 1 m / 3 m / 5 m / 10 m |
| | | Diameter | AWG# 28 |
| No. | Name | Function | Remark |
| 1] | Connector for I/O module Connector for the terminal unit | Connector used to connect the 32 / 64 I/O module. Connector used to connect the terminal unit. | |
| 2] | Earth terminal | Use a terminal for class D grounding | |
| 3] | Untie line | Use a wiring for I/O signal from 32 / 64 I/O module or the terminal unit. | |

Cable code for wiring


| Connector Pin No. | Color | Dot (Color) | Connector Pin No. | Color | Dot (Color) |
|----------------------|--------|-------------|----------------------|----------------|-----------------|
| 1 | Orange | ■ (Black) | 21 | Orange | ■ ■ ■ (Black) |
| 2 | Orange | □ (Red) | 22 | Orange | □ □ □ (Red) |
| 3 | Gray | ■ (Black) | 23 | Gray | ■ ■ ■ (Black) |
| 4 | Gray | □ (Red) | 24 | Gray | □ □ □ (Red) |
| 5 | White | ■ (Black) | 25 | White | ■ ■ ■ (Black) |
| 6 | White | □ (Red) | 26 | White | □ □ □ (Red) |
| 7 | Yellow | ■ (Black) | 27 | Yellow | ■ ■ ■ (Black) |
| 8 | Yellow | □ (Red) | 28 | Yellow | □ □ □ (Red) |
| 9 | Pink | ■ (Black) | 29 | Pink | ■ ■ ■ (Black) |
| 10 | Pink | □ (Red) | 30 | Pink | □ □ □ (Red) |
| 11 | Orange | ■ ■ (Black) | 31 | Orange | ■ ■ ■ ■ (Black) |
| 12 | Orange | □ □ (Red) | 32 | Orange | □ □ □ □ (Red) |
| 13 | Gray | ■ ■ (Black) | 33 | Gray | ■ ■ ■ ■ (Black) |
| 14 | Gray | □ □ (Red) | 34 | Gray | □ □ □ □ (Red) |
| 15 | White | ■ ■ (Black) | 35 | White | ■ ■ ■ ■ (Black) |
| 16 | White | □ □ (Red) | 36 | White | □ □ □ □ (Red) |
| 17 | Yellow | ■ ■ (Black) | 37 | Yellow | ■ ■ ■ ■ (Black) |
| 18 | Yellow | □ □ (Red) | 38 | Yellow | □ □ □ □ (Red) |
| 19 | Pink | ■ ■ (Black) | 39 | Pink | ■ ■ ■ ■ (Black) |
| 20 | Pink | □ □ (Red) | 40 | Pink | □ □ □ □ (Red) |
| | | | Earth | Shielded Cable | |

4.33 Conversion Cable for Connecting between CPU and Programmer, etc.

| Name and function of each part | | Type | EH-RS05 |
|--|---------------------------------------|--|-----------------------------|
|  <p>1] Cable connector for peripheral device</p> <p>2] Cable connector for CPU module</p> | | Weight | Approx. 0.07 kg (0.154 lb.) |
| | | Length | 0.5 m (1.64 ft.) |
| No. | Name | Function | Remarks |
| 1] | Cable connector for peripheral device | To be connected to the cable leading to a peripheral device. | |
| 2] | Cable connector for CPU module | To be connected to CPU module port 1 or port 2. | |

When EH-RS05 is used as the cable, connection to peripheral devices may be made similarly to the connector of the H-series CPU for peripheral devices. For connection to peripheral units, it is necessary to set the mode switches. For details, see Chapter 10, "Communication Specifications." (If the settings differ, communication cannot be performed.)

4.34 Cable for Connecting between CPU and PC (IBM-PC/AT Compatible Personal Computer)

| Name and function of each part | | Type | EH-VCB02 |
|---|---------------------------------|---|----------------------------|
|  <p>1] PC (IBM-PC/AT compatible PC) side connector</p> <p>2] CPU module side connector</p> | | Weight | Approx. 0.13 kg (0.29 lb.) |
| | | Length | 2 m (6.56 ft.) |
| No. | Name | Function | Remarks |
| 1] | Connector for peripheral device | To be connected to PC (IBM-PC/AT compatible PC) | |
| 2] | Cable connector for CPU module | To be connected to CPU module port 1 or port 2. | |

If the EH-VCB02 cable is used, the CPU and PC (IBM-PC/AT compatible PC) can directly be connected without a conversion cable. For connection to peripheral units, it is necessary to set the mode switches. For details, see Chapter 10, "Communication Specifications." (If the settings differ, communication cannot be performed.)

4.35 Current consumption

| Name | Type | Current consumption [mA] | Name | Type | Current consumption [mA] |
|---------------------|--------------|--------------------------|----------------------|----------|--------------------------|
| CPU module | EH-CPU104(A) | 400 | Analog module | EH-AX44 | 100 |
| | EH-CPU208(A) | 400 | | EH-AX8V | 100 |
| | EH-CPU308(A) | 400 | | EH-AX8H | 100 |
| | EH-CPU316(A) | 400 | | EH-AX8I | 100 |
| | EH-CPU448(A) | 400 | | EH-AX8IO | 100 |
| | EH-CPU516 | 400 | | EH-AY22 | 100 |
| | EH-CPU548 | 400 | | EH-AY2H | 100 |
| Memory board | EH-MEMP | 30 | | EH-AY4V | 100 |
| | EH-MEMD | 30 | | EH-AY4H | 100 |
| I/O controller | EH-IOC | 30 | | EH-AY4I | 130 |
| | EH-IOCH | 80 | | EH-PT4 | 160 |
| Power supply module | EH-PSA | - | High function module | EH-CU | 310 |
| | EH-PSD | - | | EH-CUE | 310 |
| Base unit | EH-BS3A | 200 | | EH-POS | 300 (600)*1 |
| | EH-BS5A | 200 | | EH-POS4 | 850 |
| | EH-BS8A | 200 | Communication module | EH-LNK | 550 |
| | EH-BS11A | 200 | | EH-OLNK | 550 |
| Input module | EH-XD8 | 30 | | EH-ETH | 260 |
| | EH-XD16 | 50 | | EH-RMD | 280 |
| | EH-XDL16 | 50 | | EH-RMP | 600 |
| | EH-XD32 | 60 | | EH-IOCD | 320 |
| | EH-XD32E | 60 | | EH-IOCP | 600 |
| | EH-XDL32E | 60 | Dummy module | EH-DUM | 0 |
| | EX-XD64 | 80 | | | |
| | EH-XA16 | 50 | | | |
| | EH-XAH16 | 50 | | | |
| Output module | EH-YR8B | 220 | | | |
| | EH-YR12 | 40 | | | |
| | EH-YR16 | 430 | | | |
| | EH-YT8 | 30 | | | |
| | EH-YTP8 | 30 | | | |
| | EH-YT16 | 50 | | | |
| | EH-YTP16 | 50 | | | |
| | EH-YTP16S | 50 | | | |
| | EH-YT32 | 90 | | | |
| | EH-YTP32 | 90 | | | |
| | EH-YT32E | 90 | | | |
| | EH-YTP32E | 90 | | | |
| | EH-YT64 | 120 | | | |
| | EH-YTP64 | 120 | | | |
| | EH-YS4 | 70 | | | |
| | EH-YS16 | 250 | | | |

*1 : Value in brackets is in case positioner connected

Chapter 5 Command Specifications

5.1 Command Classifications

The commands used with the EH-150 are classified as shown in the following table.

Table 5.1 Command classification table

| | Command classification | Description | Type |
|---|--|---|------|
| 1 | Basic commands | Sequence | 21 |
| | | Timer/counter | 11* |
| | | Relational box | 8 |
| 2 | Arithmetic commands | Substitution (array variable) | 1 |
| | | Mathematical operations | 10 |
| | | Logical operations | 3 |
| | | Relational expression | 8 |
| 3 | Application commands | Bit operation | 3 |
| | | Shift/rotate | 8 |
| | | Transfer | 6 |
| | | Negation/Two's complement/Sign | 6 |
| | | Conversion | 5 |
| | | Application: Square root, bit count, swap, FIFO, unit, distribute, I/O conversion | 9 |
| 4 | Control commands | END, JMP, CAL, FOR, NEXT, RTS, RTI, LBL, SB, INT, CEND, CJMP | 12 |
| 5 | High-function module transfer commands | TRNS0, RECV0, TRNS7, RECV7, TRNS8 | 5* |
| 6 | FUN commands | Process stepping, trigonometry, comment, PID and others | 71* |

* The number of commands that can be used is different depending on the CPU module type.

Caution:

WR internal output area is different depending on the type of CPU module.

EH-CPU104(A) : WR000 to WRFFF

EH-CPU208(A) : WR000 to WR1FFF

EH-CPU308(A) : WR000 to WR43FF

EH-CPU316(A) : WR000 to WR57FF

EH-CPU448(A) : WR000 to WRC3FF

EH-CPU516 : WR000 to WR57FF

EH-CPU548 : WR000 to WRC3FF

5.2 List of Commands

[Legend]

Condition code

- DER Data error (special internal output R7F4)
Set to “1” as an error when the I/O number is exceeded or when the BCD was abnormally, etc. When there is no data error, it is set to “0.”
- ERR Error (special internal output R7F3)
Set to “1” when an error is generated when a control command and a special command are executed. The error code is set in WRF015. When there are no errors, the prior condition is maintained.
- SD Shift data (special internal output R7F2)
Performs shift-in of the contents of SD by SHR or SHL command.
- V Over flow (special internal output R7F1)
Indicates that a digit overflow has occurred and the signed data range is exceeded as a result of signed data operations.
- C Carry (special internal output R7F0)
Indicates the contents of digit increase due to addition, digit decrease due to subtraction, and shift-out due to shifting.
- Maintains the prior status.
- 1] Set to “1” when there is an error in operation results. Prior status is maintained if there is no error.
- ↑ Changes according to the operation result.

Processing time

This indicates the command processing time (average value) of the EH-CPU448. Since the processing time of some commands changes depending on the parameter setting and the number of data, refer to the details of the command specifications.

1. Basic commands (sequence commands)

| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μs) | Step | Remarks |
|------------------|-------------|---------------|----------------|----------------------------------|--|---|------|------|------|------|------|-----------------------------|------|----------------------------|
| | | | | | | | DER | ERR | SD | V | C | | | |
| Sequence command | 1 | | LD | Logical operation start | Indicates the commencement of a-contact operation. | X, Y R000 to R7FF L0000 to L3FFF | ● | ● | ● | ● | ● | CPU5** CPU4** CPU***A | 1 | |
| | | | | | | | | | | | | 0.1 | | |
| | | | | | | | | | | | | 1.0 | | |
| | 2 | | LDI | Logical negation operation start | Indicates the commencement of b-contact operation. | L10000 to L13FFF M0000 to M3FFF TD, SS, WDT, MS, TMR, CU, RCU, CT Timer: 0 to 255 Counter: 0 to 511 DIF0 to DIF511 DFN0 to DFN511 | | | | | | 0.1 | | |
| | | | | | | | | | | | | 1.0 | | |
| | 3 | | AND | Logical AND | Indicates a-contact series connection. | | | | | | | 0.1 | | |
| | | | | | | | | | | | | 1.0 | | |
| | 4 | | ANI | Logical NAND | Indicates b-contact series connection. | | | | | | | 0.1 | | |
| | | | | | | | | | | | | 1.0 | | |
| | 5 | | OR | Logical OR | Indicates a-contact parallel connection. | | ● | ● | ● | ● | ● | 7.1 | 2 | |
| | | | | | | | | | | | | 2.1 | | |
| | 6 | | ORI | Logical NOR | Indicates b-contact parallel connection. | | | | | | | 7.1 | | |
| | | | | | | | | | | | | 2.32 | | |
| | 7 | | NOT | Logical NOT | Reverses all operation results up to that point. | None | ● | ● | ● | ● | ● | 0.2 | 2 | |
| | | | | | | | | | | | | 2.14 | | |
| | 8 | | AND DIF | Rising edge detection | Indicates detection of the input rise. | DIF0 to DIF511 (Decimal) | ● | ● | ● | ● | ● | 0.3 | 3 | Number overlap not allowed |
| | | | OR DIF | | | | | | | | | 3.05 | 4 | |
| | | | | | | | | | | | | 7.3 | | |
| | | | | | | | | | | | | 4.05 | | |
| | 9 | | AND DFN | Falling edge detection | Indicates detection of the input fall. | DFN0 to DFN511 (Decimal) | ● | ● | ● | ● | ● | 0.3 | 3 | Number overlap not allowed |
| | | | OR DFN | | | | | | | | | 3.05 | 4 | |
| | | | | | | | | | | | | 7.3 | | |
| | | | | | | | | | | | | 4.05 | | |
| | 10 | | OUT | Coil output | Indicates an output coil. | X, Y R000 to R7FF L0000 to L3FFF L10000 to L13FFF M0000 to M3FFF TD, SS, WDT, MS, TMR, CU, RCU, CTU, CTD, CL Timer: 0 to 255 Counter: 0 to 511 | ● | ● | ● | ● | ● | 0.1 | 1 | |
| | | | | | | | | | | | | 1.04 | | |
| | 11 | | SET | Set coil output | Indicates a set output. | X, Y R000 to R7FF L0000 to L3FFF | ● | ● | ● | ● | ● | 0.1 | 1 | |
| | | | | | | | | | | | | 2.07 | | |
| | 12 | | RES | Reset coil output | Indicates a reset output. | L10000 to L13FFF M0000 to M3FFF | | | | | | 0.1 | | |
| | | | | | | | | | | | | 2.12 | | |
| | 13 | | MCS | Set master control | Indicates a master control set operation. | MCS0 to MCS49 | ● | ● | ● | ● | ● | 0.3 | 3 | Number overlap allowed |
| | | | | | | | | | | | | 3.05 | | |
| | 14 | | MCR | Reset master control | Indicates a master control reset operation. | MCR0 to MCR49 | ● | ● | ● | ● | ● | 0.2 | 2 | Number overlap allowed |
| | | | | | | | | | | | | 2.15 | | |

| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μs) | Step | Remarks |
|------------------|-------------|---------------|----------------|-----------------------------------|--|----------------|------|------|------|------|------|-------------------|------|---------|
| | | | | | | | DER | ERR | SD | V | C | | | |
| Sequence command | 15 | | MPS | Operation result push | Saves the operation result immediately prior. | None | ● | ● | ● | ● | ● | — | 0 | |
| | 16 | | MRD | Operation result read | Reads the saved operation result and continues operation. | | | | | | | | | |
| | 17 | | MPP | Operation result pull | Reads the saved operation result, continues operation and clears the saved result. | | | | | | | | | |
| | 18 | | ANB | Logical block series connection | Indicates series connection between two logical blocks. | None | ● | ● | ● | ● | ● | — | 0 | |
| | 19 | | ORB | Logical block parallel connection | Indicates parallel connection between two logical blocks. | None | | | | | | 7.0 0.95 | 1 | |
| | 20 | | [] | Processing box start and end | Indicates start and end of a process box. | None | ● | ● | ● | ● | ● | 0.3 2.15 | 3 | |
| | 21 | | () | Relational box start and end | Indicates start and end of a comparison box. | None | ● | ● | ● | ● | ● | — | 0 | |

2. Basic commands (timer, counter)

| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μs) | Step | Remarks |
|----------------|-------------|---------------|----------------|-------------------------|--|--|------|------|------|------|------|-------------------|------|----------------------------|
| | | | | | | | DER | ERR | SD | V | C | | | |
| Timer | 22 | | OUT TD | On delay timer | Indicates on delay timer operation. | TD0 to TD255 When 0.01 s, it is possible to use from 0 to 63. | ● | ● | ● | ● | ● | 26.4 28.05 | 5 | Number overlap not allowed |
| | 23 | | OUT SS | Expanded on delay timer | Indicates expanded on delay timer operation. | TM0 to TD2,047 0.01s time base (Fixed) | ● | ● | ● | ● | ● | 15.2 - | 5 | |
| | 24 | | OUT SS | Single shot | Indicates a single shot operation. | SS0 to SS255 0.01s time base for No.0 to 63. | ● | ● | ● | ● | ● | 21.42 23.05 | 5 | |
| | 25 | | OUT MS | Mono stable timer | Indicates a mono stable timer operation. | MS0 to MS255 0.01s time base for No.0 to 63. | ● | ● | ● | ● | ● | 21.4 23.05 | 5 | |
| | 26 | | OUT TMR | Integral timer | Indicates a integral timer operation. | TMR0 to TMR255 0.01s time base for No.0 to 63. | ● | ● | ● | ● | ● | 21.4 23.05 | 5 | |
| | 27 | | OUT WDT | Watchdog timer | Indicates a watchdog timer operation. | WDT0 to WDT255 0.01s time base for No.0 to 63. | ● | ● | ● | ● | ● | 27.6 32.3 | 7 | |
| | 28 | | OUT CU | Counter | Indicates a counter operation. | CU0 to CU511 | ● | ● | ● | ● | ● | 13.4 15.05 | 5 | |
| Counter | 29 | | OUT RCU | Ring counter | Indicates a ring counter operation. | RCU0 to RCU511 | ● | ● | ● | ● | ● | 13.4 15.05 | 5 | |
| | 30 | | OUT CTU | Up of up/down counter | Indicates an up operation of up-down counter. | CTU0 to CTU511 | ● | ● | ● | ● | ● | 13.4 15.05 | 5 | |
| | 31 | | OUT CTD | Down of up/down counter | Indicates a down operation of up-down counter. | CTD0 to CTD511 | ● | ● | ● | ● | ● | 12.2 14.05 | 3 | |
| | 32 | | OUT CL | Counter clear | Indicates a clear operation for CU, RCU, CTU, CTD and WDT. | CL0 to CL511 | ● | ● | ● | ● | ● | 0.1 0.1 | 1 | |

3. Basic commands (relational box)

| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μs) | Step | Remarks |
|----------------|-------------|---------------|--------------------|--------------------------|--|---|------|------|------|------|------|-------------------|------|---|
| | | | | | | | DER | ERR | SD | V | C | | | |
| Relational box | 32 | | LD (s1 == s2) | = Relational box | When s1 = s2: Continuity When s1 ≠ s2: Noncontinuity | [Word] WX, WY, WR, WL, WM, Timer · Counter [Double word] DX, DY, DR, DL, DM Constant | ● | ● | ● | ● | ● | 0.5 | 5 | *1 *2 Upper case: W Lower case: DW |
| | | | | | | | | | | | | 23.45 | 6 | |
| | | | | | | | | | | | | 18.4 | 7 | |
| | | | | | | | | | | | | 26.45 | 8 | |
| | | | AND (s1 == s2) | | | | | | | | | 0.5 | | |
| | | | | | | | | | | | | 23.45 | | |
| | | | | | | | | | | | | 18.4 | | |
| | | | | | | | | | | | | 26.45 | | |
| | | | OR (s1 == s2) | | | | | | | | | 7.5 | | |
| | | | | | | | | | | | | 23.45 | | |
| | | | | | | | | | | | | 25.4 | | |
| | | | | | | | | | | | | 26.45 | | |
| | 33 | | LD (s1 S== s2) | Signed = Relational box | When s1 = s2: Continuity When s1 ≠ s2: Noncontinuity s1 and s2 are compared as signed 32-bit binary. | DX, DY, DR, DL, DM Constant | ● | ● | ● | ● | ● | 18.4 | 5 | *2 |
| | | | | | | | | | | | | 26.45 | 6 | |
| | | | | | | | | | | | | | 7 | |
| | | | | | | | | | | | | 18.4 | 8 | |
| | | | AND (s1 S== s2) | | | | | | | | | 26.45 | | |
| | | | | | | | | | | | | | | |
| | 34 | | LD (s1 <> s2) | <> Relational box | When s1 = s2: Noncontinuity When s1 ≠ s2: Continuity | [Word] WX, WY, WR, WL, WM, Timer · Counter [Double word] DX, DY, DR, DL, DM Constant | ● | ● | ● | ● | ● | 0.5 | 5 | *1 *2 Upper case: W Lower case: DW |
| | | | | | | | | | | | | 23.45 | 6 | |
| | | | | | | | | | | | | 18.4 | 7 | |
| | | | | | | | | | | | | 27.75 | 8 | |
| | | | AND (s1 <> s2) | | | | | | | | | 0.5 | | |
| | | | | | | | | | | | | 23.45 | | |
| | 35 | | LD (s1 S<> s2) | Signed <> Relational box | When s1 = s2: Noncontinuity When s1 ≠ s2: Continuity s1 and s2 are compared as signed 32-bit binary. | DX, DY, DR, DL, DM Constant | ● | ● | ● | ● | ● | 18.4 | 5 | *2 |
| | | | | | | | | | | | | 27.75 | 6 | |
| | | | | | | | | | | | | | 7 | |
| | | | | | | | | | | | | 18.4 | 8 | |
| | | | AND (s1 S<> s2) | | | | | | | | | 27.75 | | |
| | | | | | | | | | | | | | | |
| | | | OR (s1 S<> s2) | | | | | | | | | 25.4 | | |
| | | | | | | | | | | | | 27.75 | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μs) | Step | Remarks |
|----------------|-------------|---------------|--------------------|--------------------------|--|---|------|------|------|------|------|-----------------------------|------|---|
| | | | | | | | DER | ERR | SD | V | C | | | |
| | | | | | | | | | | | | CPU5** CPU4** CPU***A | | |
| Relational box | 36 | | LD (s1 < s2) | < Relational box | When s1 < s2: Continuity When s1 ≥ s2: Noncontinuity | [Word] WX, WY, WR, WL, WM, Timer · Counter [Double word] DX, DY, DR, DL, DM Constant | ● | ● | ● | ● | ● | 0.5 | 5 | *1 *2 Upper case: W Lower case: DW |
| | | | | | | | | | | | | 23.45 | 6 | |
| | | | | | | | | | | | | 19.4 | 7 | |
| | | | | | | | | | | | | 28.75 | 8 | |
| | | | AND (s1 < s2) | | | | | | | | | 0.5 | | |
| | | | | | | | | | | | | 23.45 | | |
| | | | | | | | | | | | | 19.4 | | |
| | | | | | | | | | | | | 28.75 | | |
| | | | OR (s1 < s2) | | | | | | | | | 7.5 | | |
| | | | | | | | | | | | | 23.45 | | |
| | | | | | | | | | | | | 26.5 | | |
| | | | | | | | | | | | | 28.75 | | |
| Relational box | 37 | | LD (s1 S< s2) | Signed < Relational box | When s1 < s2: Continuity When s1 ≥ s2: Noncontinuity s1 and s2 are compared as signed 32-bit binary. | DX, DY, DR, DL, DM Constant | ● | ● | ● | ● | ● | 19.4 | 5 | *2 |
| | | | | | | | | | | | | 24.75 | 6 | |
| | | | | | | | | | | | | | 7 | |
| | | | | | | | | | | | | | 8 | |
| | | | AND (s1 S< s2) | | | | | | | | | 19.4 | | |
| | | | | | | | | | | | | 28.75 | | |
| | | | OR (s1 S< s2) | | | | | | | | | 26.4 | | |
| | | | | | | | | | | | | 28.75 | | |
| | | | | | | | | | | | | | | |
| Relational box | 38 | | LD (s1 <= s2) | <= Relational box | When s1 ≤ s2: Continuity When s1 > s2: Noncontinuity | [Word] WX, WY, WR, WL, WM, Timer · Counter [Double word] DX, DY, DR, DL, DM Constant | ● | ● | ● | ● | ● | 0.5 | 5 | *1 *2 Upper case: W Lower case: DW |
| | | | | | | | | | | | | 23.45 | 6 | |
| | | | | | | | | | | | | 19.4 | 7 | |
| | | | | | | | | | | | | 28.75 | 8 | |
| | | | AND (s1 <= s2) | | | | | | | | | 0.5 | | |
| | | | | | | | | | | | | 23.45 | | |
| | | | | | | | | | | | | 19.4 | | |
| | | | | | | | | | | | | 28.75 | | |
| | | | OR (s1 <= s2) | | | | | | | | | 7.5 | | |
| | | | | | | | | | | | | 23.45 | | |
| | | | | | | | | | | | | 26.5 | | |
| | | | | | | | | | | | | 28.75 | | |
| Relational box | 39 | | LD (s1 S<= s2) | Signed <= Relational box | When s1 ≤ s2: Continuity When s1 > s2: Noncontinuity s1 and s2 are compared as signed 32-bit binary. | DX, DY, DR, DL, DM Constant | ● | ● | ● | ● | ● | 19.4 | 5 | *2 |
| | | | | | | | | | | | | 28.75 | 6 | |
| | | | | | | | | | | | | | 7 | |
| | | | | | | | | | | | | | 8 | |
| | | | AND (s1 S<= s2) | | | | | | | | | 19.4 | | |
| | | | | | | | | | | | | 28.75 | | |
| Relational box | | | OR (s1 S<= s2) | | | | | | | | | 26.4 | | |
| | | | | | | | | | | | | 28.75 | | |
| | | | | | | | | | | | | | | |










4. Arithmetic command



| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μs) | Step | Remarks |
|-------------------------|-------------|---------------|----------------|------------------------|----------------------|--|------|------|------|------|------|-------------------|------|---------------------------------|
| | | | | | | | DER | ERR | SD | V | C | | | |
| Substitution statement | 1 | d=s | | Substitution statement | d ← s | [Bit] d: Y, R, L, M s: X, Y, R, L, M, Constant | ↑ | ● | ● | ● | ● | CPU5** 0.3 | 3 | I/O: I/O |
| | | | | | | | | | | | | 15.6 | | |
| | | | | | | | | | | | | 31 | 4 | I/O: Array |
| | | | | | | | | | | | | 31.9 | | |
| | | | | | | | | | | | | 27 | 4 | Array: I/O |
| | | | | | | | | | | | | 27.9 | | |
| | | | | | | | | | | | | 43 | 5 | Array: Array |
| | | | | | | | | | | | | 40.05 | | |
| | | | | | | [Word] d: WY, WR, WL, WM, Timer · Counter s: WX, WY, WR, WL, WM, Timer · Counter, Constant | ↑ | ● | ● | ● | ● | 0.3 | 3 | I/O: I/O |
| | | | | | | | | | | | | 14.6 | | |
| | | | | | | | | | | | | 27 | 4 | I/O: Array |
| | | | | | | | | | | | | 29.9 | | |
| | | | | | | | | | | | | 25 | 4 | Array: I/O |
| | | | | | | | | | | | | 26.9 | | |
| | | | | | | | | | | | | 39 | 5 | Array: Array |
| | | | | | | | | | | | | 37.9 | | |
| | | | | | | [Double word] d: DY, DR, DL, DM s: DX, DY, DR, DL, DM, Constant * Array variables can be used. | ↑ | ● | ● | ● | ● | 15 | 4 | I/O: I/O |
| | | | | | | | | | | | | 19.9 | | |
| | | | | | | | | | | | | 29 | 4 | I/O: Array |
| | | | | | | | | | | | | 36.55 | | |
| | | | | | | | | | | | | 27 | 5 | Array: I/O |
| | | | | | | | | | | | | 32.55 | | |
| Mathematical operations | 2 | d=s1+s2 | | Binary addition | d ← s1+s2 | [Word] d: WY, WR, WL, WM | ● | ● | ● | ↑ | ↑ | 0.4 | 4 | Upper case: W Lower case: DW |
| | | | | | | | | | | | | 19.9 | | |
| | | | | | | | | | | | | 22 | 6 | |
| | | | | | | | | | | | | 30.5 | | |
| | 3 | d=s1 B+ s2 | | BCD addition | d ← s1+s2 | s1, s2: WX, WY, WR, WL, WM, Timer · Counter, Constant | ↑ | ● | ● | ● | ↑ | 36 | 4 | Upper case: W Lower case: DW |
| | | | | | | | | | | | | 40.9 | | |
| | | | | | | | | | | | | 59 | 6 | |
| | | | | | | | | | | | | 68.5 | | |
| | 4 | d=s1-s2 | | Binary subtraction | d ← s1-s2 | [Double word] d: DY, DR, DL, DM | ● | ● | ● | ↑ | ↑ | 0.4 | 4 | Upper case: W Lower case: DW |
| | | | | | | | | | | | | 19.9 | | |
| | | | | | | | | | | | | 20 | 6 | |
| | | | | | | | | | | | | 30.5 | | |
| | 5 | d=s1 B- s2 | | BCD subtraction | d ← s1-s2 | s1, s2: DX, DY, DR, DL, DM, Constant | ↑ | ● | ● | ● | ↑ | 34 | 4 | Upper case: W Lower case: DW |
| | | | | | | | | | | | | 38.9 | | |
| | | | | | | | | | | | | 54 | 6 | |
| | | | | | | | | | | | | 62.5 | | |

| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μs) | Step | Remarks |
|-------------------------|-------------|--------------------------|------------------------------|---|---|----------------|------|------|------|------|------|-----------------------------|------|---|
| | | | | | | | DER | ERR | SD | V | C | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| Mathematical operations | 6 | $d = s1 \times s2$ | Binary multiplication | $d \leftarrow s1 \times s2$ | [Word] d: WY, WR, WL, WM s1, s2: WX, WY, WR, WL, WM, Timer · Counter, Constant | \uparrow | ● | ● | ● | ● | ● | CPU5** CPU4** CPU***A | 4 | Upper case: W Lower case: DW |
| | | | | | | | | | | | | 30 | | |
| | | | | | | | | | | | | 30.9 | | |
| | | | | | | | | | | | | 39 | | |
| | 7 | $d = s1 B \times s2$ | BCD multiplication | $d \leftarrow s1 \times s2$ | [Double word] d: DY, DR, DL, DM s1, s2: DX, DY, DR, DL, DM, Constant | \uparrow | ● | ● | ● | ● | ● | CPU5** CPU4** CPU***A | 4 | Upper case: W Lower case: DW |
| | | | | | | | | | | | | 63 | | |
| | | | | | | | | | | | | 63.9 | | |
| | | | | | | | | | | | | 132 | | |
| | 8 | $d = s1 S \times s2$ | Signed binary multiplication | $d \leftarrow s1 \times s2$ | [Double word] d: DY, DR, DL, DM s1, s2: DX, DY, DR, DL, DM, Constant | \uparrow | ● | ● | ● | ● | ● | CPU5** CPU4** CPU***A | 6 | |
| | | | | | | | | | | | | 42 | | |
| | | | | | | | | | | | | 47.5 | | |
| | | | | | | | | | | | | 136.5 | | |
| | 9 | $d = s1 / s2$ | Binary division | $d \leftarrow s1 / s2$ WRF016 $\leftarrow s1 \bmod s2$ | [Word] d: WY, WR, WL, WM s1, s2: WX, WY, WR, WL, WM, Timer · Counter, Constant | \uparrow | ● | ● | ● | ● | ● | CPU5** CPU4** CPU***A | 4 | Upper case: W Lower case: DW |
| | | | | | | | | | | | | 28 | | |
| | | | | | | | | | | | | 32.9 | | |
| | | | | | | | | | | | | 32 | | |
| | 10 | $d = s1 B / s2$ | BCD division | $d \leftarrow s1 / s2$ DRF016 $\leftarrow s1 \bmod s2$ | [Double word] d: DY, DR, DL, DM s1, s2: DX, DY, DR, DL, DM, Constant | \uparrow | ● | ● | ● | ● | ● | CPU5** CPU4** CPU***A | 4 | Upper case: W Lower case: DW |
| | | | | | | | | | | | | 41.5 | | |
| | | | | | | | | | | | | 50 | | |
| | | | | | | | | | | | | 54.9 | | |
| | 11 | $d = s1 S / s2$ | Signed binary division | $d \leftarrow s1 / s2$ DRF016 $\leftarrow s1 \bmod s2$ | [Double word] d: DY, DR, DL, DM s1, s2: DX, DY, DR, DL, DM, Constant | \uparrow | ● | ● | ● | ● | ● | CPU5** CPU4** CPU***A | 6 | Lower case: DW |
| | | | | | | | | | | | | 69 | | |
| | | | | | | | | | | | | 77.5 | | |
| | | | | | | | | | | | | 43.5 | | |
| Logical operation | 12 | $d = s1 \text{ OR } s2$ | Logical OR | $d \leftarrow s1 + s2$ | [Bit] d: Y, R, L, M s1, s2: X, Y, R, L, M [Word] d: WY, WR, WL, WM, | ● | ● | ● | ● | ● | ● | CPU5** CPU4** CPU***A | 4 | Upper case: B Middle case: W Lower case: DW |
| | | | | | | | | | | | | 0.4 | | |
| | | | | | | | | | | | | 18.9 | | |
| | | | | | | | | | | | | 0.4 | | |
| | 13 | $d = s1 \text{ AND } s2$ | Logical AND | $d \leftarrow s1 \cdot s2$ | Timer · Counter s1, s2: WX, WY, WR, WL, WM, Timer · Counter, Constant [Double word] | ● | ● | ● | ● | ● | ● | CPU5** CPU4** CPU***A | 4 | Upper case: B Middle case: W Lower case: DW |
| | | | | | | | | | | | | 21.2 | | |
| | | | | | | | | | | | | 18 | | |
| | | | | | | | | | | | | 24.2 | | |
| | 14 | $d = s1 \text{ XOR } s2$ | Exclusive OR | $d \leftarrow s1 + s2$ | d: DY, DR, DL, DM s1, s2: DX, DY, DR, DL, DM, Constant | ● | ● | ● | ● | ● | ● | CPU5** CPU4** CPU***A | 4 | Upper case: B Middle case: W Lower case: DW |
| | | | | | | | | | | | | 0.4 | | |
| | | | | | | | | | | | | 18.9 | | |
| | | | | | | | | | | | | 0.4 | | |

| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μs) | Step | Remarks |
|-----------------------|-------------|---------------|---------------------------------|---|--|----------------|------|------|------|------|------|-------------------|------|----------------|
| | | | | | | | DER | ERR | SD | V | C | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| Relational expression | 15 | d=s1 == s2 | = Relational expression | When s1 = s2, d ← 1 When s1 ≠ s2, d ← 0 | [Word] d: Y, R, L, M s1, s2: WX, WY, WR, WL, WM, Timer · Counter, Constant [Double word] d: Y, R, L, M s1, s2: DX, DY, DR, DL, DM, Constant | ● | ● | ● | ● | ● | | CPU5** | 4 | Upper case: W |
| | | | | | | | | | | | | CPU4** | | |
| | | | | | | | | | | | | CPU***A | | |
| | | | | | | | | | | | | 0.4 | | |
| | 16 | d=s1 S== s2 | Signed = Relational expression | When s1 = s2, d ← 1 When s1 ≠ s2, d ← 0 s1 and s2 are compared as signed 32-bit binary. | [Double word] d: Y, R, L, M s1, s2: DX, DY, DR, DL, DM, Constant | | | | | | | 18.9 | 6 | Lower case: DW |
| | | | | | | | | | | | | 18 | | |
| | | | | | | | | | | | | 26.5 | | |
| | | | | | | | | | | | | 18 | | |
| | 17 | d=s1 <> s2 | <> Relational expression | When s1 = s2, d ← 0 When s1 ≠ s2, d ← 1 | [Word] d: Y, R, L, M s1, s2: WX, WY, WR, WL, WM, Timer · Counter, Constant [Double word] d: Y, R, L, M s1, s2: DX, DY, DR, DL, DM, Constant | ● | ● | ● | ● | ● | | 0.4 | 4 | Upper case: W |
| | | | | | | | | | | | | 18.9 | | |
| | | | | | | | | | | | | 18 | | Lower case: DW |
| | | | | | | | | | | | | 26.5 | | |
| | 18 | d=s1 S<> s2 | Signed <> Relational expression | When s1 = s2, d ← 0 When s1 ≠ s2, d ← 1 s1 and s2 are compared as signed 32-bit binary. | [Double word] d: Y, R, L, M s1, s2: DX, DY, DR, DL, DM, Constant | | | | | | | 18 | 6 | |
| | | | | | | | | | | | | 26.5 | | |
| | | | | | | | | | | | | 18 | | |
| | | | | | | | | | | | | 26.5 | | |
| | 19 | d=s1 < s2 | < Relational expression | When s1 < s2, d ← 1 When s1 ≥ s2, d ← 0 | [Word] d: Y, R, L, M s1, s2: WX, WY, WR, WL, WM, Timer · Counter, Constant [Double word] d: Y, R, L, M s1, s2: DX, DY, DR, DL, DM, Constant | ● | ● | ● | ● | ● | | 0.4 | 4 | Upper case: W |
| | | | | | | | | | | | | 18.9 | | |
| | | | | | | | | | | | | 19 | | Lower case: DW |
| | | | | | | | | | | | | 26.5 | | |
| | 20 | d=s1 S< s2 | Signed < Relational expression | When s1 = s2, d ← 1 When s1 ≠ s2, d ← 0 s1 and s2 are compared as signed 32-bit binary. | [Double word] d: Y, R, L, M s1, s2: DX, DY, DR, DL, DM, Constant | | | | | | | 19 | 6 | |
| | | | | | | | | | | | | 26.5 | | |
| | | | | | | | | | | | | 19 | | |
| | | | | | | | | | | | | 26.5 | | |
| | 21 | d=s1 <= s2 | ≤ Relational expression | When s1 ≤ s2, d ← 1 When s1 > s2, d ← 0 | [Word] d: Y, R, L, M s1, s2: WX, WY, WR, WL, WM, Timer · Counter, Constant [Double word] d: Y, R, L, M s1, s2: DX, DY, DR, DL, DM, Constant | ● | ● | ● | ● | ● | | 0.4 | 4 | Upper case: W |
| | | | | | | | | | | | | 18.9 | | |
| | | | | | | | | | | | | 19 | | Lower case: DW |
| | | | | | | | | | | | | 26.5 | | |
| | 22 | d=s1 S<= s2 | Signed ≤ Relational expression | When s1 ≤ s2, d ← 1 When s1 > s2, d ← 0 s1 and s2 are compared as signed 32-bit binary. | [Double word] d: Y, R, L, M s1, s2: DX, DY, DR, DL, DM, Constant | | | | | | | 19 | 6 | |
| | | | | | | | | | | | | 26.5 | | |
| | | | | | | | | | | | | 19 | | |
| | | | | | | | | | | | | 26.5 | | |

5. Application commands

| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μs) | Step | Remarks |
|----------------|-------------|---------------|----------------|---------------------|---|---|------|------|------|------|------|-------------------|------|---------------------------------|
| | | | | | | | DER | ERR | SD | V | C | | | |
| Bit operations | 1 | BSET(d, n) | | Bit set |  Sets 1 to bit n. | [Word] d: WY, WR, WL, WM, TC n(0-15): WX, WY, WR, WL, WM, TC, Constant [Double word] d: DY, DR, DL, DM n(0-31): WX, WY, WR, WL, WM, TC, Constant | ● | ● | ● | ● | ● | 13 | 3 | Upper case: W Lower case: DW |
| | | | | | | | | | | | | 14.6 | | |
| | | | | | | | | | | | | 15 | | |
| | | | | | | | | | | | | 16.6 | | |
| | 2 | BRES(d, n) | | Bit reset |  Sets 0 to bit n. | | ● | ● | ● | ● | ● | 13 | 3 | Upper case: W Lower case: DW |
| | | | | | | | | | | | | 14.6 | | |
| | | | | | | | | | | | | 15 | | |
| | | | | | | | | | | | | 16.6 | | |
| | 3 | BTS(d, n) | | Bit test |  Acquires the value in bit n to C (R7F0). | | ● | ● | ● | ● | ↑ | 13 | 3 | Upper case: W Lower case: DW |
| | | | | | | | | | | | | 15.6 | | |
| | | | | | | | | | | | | 15 | | |
| | | | | | | | | | | | | 17.6 | | |
| Shift/rotate | 4 | SHR(d, n) | | Shift right |  Shifts right by n bits. | [Word] d: WY, WR, WL, WM, TC n: WX, WY, WR, WL, WM, TC, Constant [Double word] d: DY, DR, DL, DM n: WX, WY, WR, WL, WM, TC, Constant *C: R7F0 SD: R7F2 | ● | ● | ● | ● | ↑ | 17 | 3 | Upper case: W Lower case: DW |
| | | | | | | | | | | | | 18.6 | | |
| | | | | | | | | | | | | 18 | | |
| | | | | | | | | | | | | 20.6 | | |
| | 5 | SHL(d, n) | | Shift left |  Shifts left by n bits. | | ● | ● | ● | ● | ↑ | 16 | 3 | Upper case: W Lower case: DW |
| | | | | | | | | | | | | 18.6 | | |
| | | | | | | | | | | | | 18 | | |
| | | | | | | | | | | | | 20.6 | | |
| | 6 | ROR(d, n) | | Rotate right |  Rotates right by n bits. | | ● | ● | ● | ● | ↑ | 21 | 3 | Upper case: W Lower case: DW |
| | | | | | | | | | | | | 22.6 | | |
| | | | | | | | | | | | | 22 | | |
| | | | | | | | | | | | | 24.6 | | |
| | 7 | ROL(d, n) | | Rotate left |  Rotates left by n bits. | | ● | ● | ● | ● | ↑ | 21 | 3 | Upper case: W Lower case: DW |
| | | | | | | | | | | | | 22.6 | | |
| | | | | | | | | | | | | 22 | | |
| | | | | | | | | | | | | 24.6 | | |
| | 8 | LSR(d, n) | | Logical shift right |  Shifts right by n bits. | | ● | ● | ● | ● | ↑ | 16 | 3 | Upper case: W Lower case: DW |
| | | | | | | | | | | | | 17.6 | | |
| | | | | | | | | | | | | 18 | | |
| | | | | | | | | | | | | 19.6 | | |
| | 9 | LSL(d, n) | | Logical shift left |  Shifts left by n bits. | | ● | ● | ● | ● | ↑ | 16 | 3 | Upper case: W Lower case: DW |
| | | | | | | | | | | | | 17.6 | | |
| | | | | | | | | | | | | 18 | | |
| | | | | | | | | | | | | 19.6 | | |

| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μs) | Step | Remarks |
|------------------------------------|-------------|----------------|----------------|-----------------------|---|---|------|------|------|------|------|----------------------------|------|--------------------------------------|
| | | | | | | | DER | ERR | SD | V | C | | | |
| Shift/rotate | 10 | BSR(d, n) | | BCD shift right |  <p>Shifts BCD to right by n digits.</p> | [Word] d: WY, WR, WL, WM, TC n: WX, WY, WR, WL, WM, TC, Constant | ● | ● | ● | ● | ● | 15 16.6 17 19.6 | 3 | Upper case: W Lower case: DW |
| | 11 | BSL(d, n) | | BCD shift left |  <p>Shifts BCD to left by n digits.</p> | [Double word] d: DY, DR, DL, DM n: WX, WY, WR, WL, WM, TC, constant | ● | ● | ● | ● | ● | 15 16.6 17 19.6 | 3 | Upper case: W Lower case: DW |
| Transfer | 12 | WSHR(d, n) | | Batch shift right | Shifts n bits (or words) starting with I/O number d to the right by 1 bit (or word). | [Bit] d: R, L, M n(0-255): WX, WY, WR, WL, WM, TC, Constant | ↑ | ● | ● | ● | ● | 31 28.9 24 23.26 | 3 | *3 Upper case: B Lower case: W |
| | 13 | WSHL(d, n) | | Batch shift left | Shifts n bits (or words) starting with I/O number d to the left by 1 bit (or word). | [Word] d: WR, WL, WM n(0-255): WX, WY, WR, WL, WM, TC, Constant | ↑ | ● | ● | ● | ● | 31 28.7 25 24.35 | 3 | *3 Upper case: B Lower case: W |
| | 14 | WBSR(d, n) | | Batch BCD shift right | Shifts n digits of BCD starting with I/O number d to the right by 1 digit. | [Word] d: WR, WL, WM n(0-255): WX, WY, WR, WL, WM, TC, Constant | ↑ | ● | ● | ● | ● | 25 24.1 | 3 | *3 |
| | 15 | WBSL(d, n) | | Batch BCD shift left | Shifts n digits of BCD starting with I/O number d to the left by 1 digit. | Constant | ↑ | ● | ● | ● | ● | 25 24.55 | 3 | *3 |
| | 16 | MOV(d, s, n) | | Block transfer | Transfers (copies) n bits (or words) of data starting with I/O number s, to the n bit (or word) range starting with I/O number s. | [Bit] d, s: R, L, M n(0-255): WX, WY, WR, WL, WM, TC, Constant [Word] d, s: WR, WL, WM n(0-255): WX, WY, WR, WL, WM, TC, Constant | ↑ | ● | ● | ● | ● | 87 59.9 83 62.2 | 4 | *3 Upper case: B Lower case: W |
| | 17 | COPY(d, s, n) | | Copy | Copies the bit (or word) data of I/O number s to the n bit (or word) range starting with I/O number d. | [Bit] d: R, L, M s: X, Y, R, L, M, Constant n(0-255): WX, WY, WR, WL, WM, TC, Constant [Word] d: WR, WL, WM s, n(0-255): WX, WY, WR, WL, WM, TC, Constant | ↑ | ● | ● | ● | ● | 43 47.48 93 70.28 | 4 | *3 Upper case: B Lower case: W |
| | 18 | XCG(d1, d2, n) | | Block exchange | Exchanges the n bit (or word) range starting with I/O number d1 and the n bit (or word) range starting with I/O number d2. | [Bit] d1, d2: R, L, M n(0-255): WX, WY, WR, WL, WM, TC, Constant [Word] d: WR, WL, WM n(0-255): WX, WY, WR, WL, WM, TC, Constant | ↑ | ● | ● | ● | ● | 47 44.73 42 41.3 | 4 | *3 Upper case: B Lower case: W |
| Negation / Two's complement / Sign | | | | | | | | | | | | | | |

| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μ s) | Step | Remarks |
|------------------------------------|-------------|---------------|-------------------------|---|---|----------------|---------|------|------|------|-------|--------------------|----------------|----------------|
| | | | | | | | | | | | | CPU5** | | |
| | | | | | | | DER | ERR | SD | V | C | CPU4** | | |
| | | | | | | | CPU***A | | | | | | | |
| Negation / Two's complement / Sign | 19 | NOT(d) | Reverse | Reverses the bit for the I/O number d value. | [Bit] Y, R, L, M [Word] WY, WR, WL, WM [Double word] DY, DR, DL, DM | ● | ● | ● | ● | ● | 13 | 2 | Upper case: B | |
| | | | | | | | | | | | 11.3 | | Middle case: W | |
| | | | | | | | | | | | 11 | | | |
| | | | | | | | | | | | 10.3 | | | |
| | | | | | | | | | | | 13 | | | Lower case: DW |
| | | | | | | | | | | | 12.3 | | | |
| | 20 | NEG(d) | Two's complement | Stores two's complement of the value stored in I/O number d, in d. | [Word] WY, WR, WL, WM [Double word] DY, DR, DL, DM | ● | ● | ● | ● | ● | 12 | 2 | Upper case: W | |
| | | | | | | | | | | | 11.3 | | Lower case: DW | |
| | | | | | | | | | | | 14 | | | |
| | | | | | | | | | | | 13.3 | | | |
| | 21 | ABS(d, s) | Absolute value | Stores the absolute value of s in d, and the sign value of s in carry (R7F0). (0: Positive, 1: Negative) | [Word] d: WY, WR, WL, WM s: WX, WY, WR, WL, WM, TC, Constant [Double word] | ● | ● | ● | ● | ↑ | 13 | 3 | Upper case: W | |
| | | | | | | | | | | | 14.75 | | Lower case: DW | |
| | | | | | | | | | | | 16 | | | |
| | | | | | | | | | | | 20.55 | | | |
| | 22 | SGET(d, s) | Sign addition | If the value of carry (R7F0) is 0, the value is stored in d, and if it is 1, two's complement of the s is stored in d. | d: DY, DR, DL, DM s: DX, DY, DR, DL, DM, Constant | ● | ● | ● | ● | ● | 13 | 3 | Upper case: W | |
| | | | | | | | | | | | 14.75 | | Lower case: DW | |
| | | | | | | | | | | | 16 | | | |
| | | | | | | | | | | | 19.55 | | | |
| | 23 | EXT(d, s) | Sign expansion | Copies the sign bit value of s to all bits in the upper word of d, and stores the value of s in the lower word of d. | d: DY, DR, DL, DM s: WX, WY, WR, WL, WM, TC, Constant | ● | ● | ● | ● | ● | 15 | 3 | | |
| | | | | | | | | | | | 16.75 | | | |
| Conversion | 24 | BCD(d, s) | Binary → BCD conversion | Converts the value of s into BCD and stores it in I/O number d. If there the value of s is erroneous, DER (R7F4) = 1 is set. | [Word] d: WY, WR, WL, WM s: WX, WY, WR, WL, WM, TC, Constant | ↑ | ● | ● | ● | ● | 28 | 3 | Upper case: W | |
| | | | | | | | | | | | 29.75 | | Lower case: DW | |
| | | | | | | | | | | | 31 | | | |
| | | | | | | | | | | | 35.2 | | | |
| | 25 | BIN(d, s) | BCD → Binary conversion | Converts the value of s into binary and stores it in I/O number d. If there the value of s is erroneous, DER (R7F4) = 1 is set. | [Double word] d: DY, DR, DL, DM s: DX, DY, DR, DL, DM, Constant | ↑ | ● | ● | ● | ● | 19 | 3 | Upper case: W | |
| | | | | | | | | | | | 20.75 | | Lower case: DW | |
| | | | | | | | | | | | 27 | | | |
| | | | | | | | | | | | 32.2 | | | |
| | 26 | DECO(d, s, n) | Decode | Decodes the value indicated by the least significant n bits of s, and sets the bit that corresponds to the decoding result of the bit row starting from I/O number d, to 1. | d: R, L, M s: WX, WY, WR, WL, WM, TC, Constant n: Constant(1-8) | ↑ | ● | ● | ● | ● | 38 | 4 | n=1 | |
| | | | | | | | | | | | 37.55 | | | |
| | 27 | ENCO(d, s, n) | Encode | Encodes the bit location in which 1 is set within the bit row, which starts with I/O number s and lasts for the amount of nth power of 2, and stores it in I/O number d. If multiple bits that contain 1 exist, the one with the upper bit locations will be encoded. | d: WY, WR, WL, WM s: R, L, M n: Constant(1-8) | ↑ | ● | ● | ● | ↑ | 38 | 4 | n=1 | |
| | | | | | | | | | | | 41.3 | | | |
| | 28 | SEG(d, s) | 7 segment decode | Coverts the value of s as a 1-digit 4-bit value to a 4-digit 7-segment display code and stores it in d. | d: DY, DR, DL, DM s: WX, WY, WR, WL, WM, TC, Constant | ● | ● | ● | ● | ● | 16 | 3 | | |
| | | | | | | | | | | | 17.75 | | | |

| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μs) | Step | Remarks |
|----------------------|-------------|---------------|----------------|------------------------|--|---|------|------|------|------|------|---------------------------|--------|---------------------------------|
| | | | | | | | DER | ERR | SD | V | C | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| Application commands | 29 | SQR(d, s) | | Square root | Calculates the square root of the value of s (8-digit BCD) and stores it in d (4-digit BCD). | d: WY, WR, WL, WM s: DX, DY, DR, DL, DM, Constant | ↑ | ● | ● | ● | ● | 86 90.2 | 4 | |
| | 30 | BCU(d, s) | | Bit count | Among the contents of s (word, double-word), stores the number of bits that are set to 1 in I/O number d. | [Word] d: WY, WR, WL, WM s: WX, WY, WR, WL, WM, TC, Constant [Double word] d: WY, WR, WL, WM s: DX, DY, DR, DL, DM, Constant | ● | ● | ● | ● | ● | 14 15.75 17 21.2 | 3 4 | Upper case: W Lower case: DW |
| | 31 | SWAP(d) | | Swap | Swaps the upper 8 bits and the lower 8 bits of the value (word) for I/O number d. | d: WY, WR, WL, WM | ● | ● | ● | ● | ● | 12 11.3 | 2 | |
| | 32 | FIFIT(P, n) | | FIFO initialization | Stores the value of n in the FIFO size area (P) and stores 0 in the FIFO used number area (P+1). | P: WR, WL, WM n: Constant(0-255) | ↑ | ● | ● | ● | ● | 24 23.6 | 3 | |
| | 33 | FIFWR(P, s) | | FIFO write | Stores the value of I/O number s in the FIFO write location and adds 1 to the FIFO used number area (P+1). | P: WR, WL, WM s: WX, WY, WR, WL, WM, TC, Constant | ↑ | ● | ● | ● | ● | 25 22.6 | 3 | |
| | 34 | FIFRD(P, d) | | FIFO read | Reads data from the FIFO read location and stores it in d, then shifts the data in the FIFO by one data item and subtracts 1 from the value of the FIFO usage number area (P+1). | P: WR, WL, WM d: WY, WR, WL, WM, TC | ↑ | ● | ● | ● | ● | 157 156.6 | 3 | *4 |
| | 35 | UNIT(d, s, n) | | Unit | Stores the lower 4 bit values of the n words starting with s in the lower 4 bits each of d (word). | d: WY, WR, WL, WM s: WR, WL, WM n: Constant(0-4) | ↑ | ● | ● | ● | ● | 30 31.9 | 4 | |
| | 36 | DIST(d, s, n) | | Distribute | Extracts the value of s (word) in 4 bit units starting with the least significant bits, and sets them in the lower 4 bits of each word starting with I/O number d (word). The upper bits are set to 0. | d: WR, WL, WM s: WX, WY, WR, WL, WM, TC, Constant n: Constant(0-4) | ↑ | ● | ● | ● | ● | 27 29.05 | 4 | |
| | 37 | ADRIO(d, s) | | I/O address conversion | Stores the actual address of the I/O designated by s in d. | [Bit] s: X, Y, R, L, M d: WY, WR, WL, WM [Word] s: WX, WY, WR, WL, WM d: WY, WR, WL, WM | ● | ● | ● | ● | ● | 12 14.6 | 3 | *5 |

6. Control commands

| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μ s) | Step | Remarks |
|------------------|-------------|---------------|----------------|----------------------|---|--|------|------|------|------|------|--------------------|------|----------|
| | | | | | | | DER | ERR | SD | V | C | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| Control commands | 1 | END | | Normal scan end | Indicates the end of a normal scan and re-executes normal scan from the head of the normal scan. | None | ● | ● | ● | ● | ● | 194 194.95 | 1 | |
| | 2 | CEND(s) | | Scan conditional end | Re-executes normal scan from the head of the normal scan when s=1, while the next command is executed when s=0. | s: X, Y, R, L, M | ● | ● | ● | ● | ● | 6 196 202.5 | 2 | *6 *7 |
| | 3 | JMP n | | Unconditional jump | Jumps to LBL n of the same No. n. | n: Constant(0-255) | ● | 1] | ● | ● | ● | 21 22 | 2 | |
| | 4 | CJMP n (s) | | Conditional jump | When s=1, jumps to the LBL n of the same No. n when s=0, executes the next command. | n: Constant(0-255) s: X, Y, R, L, M | ● | 1] | ● | ● | ● | 6 22 26.45 | 3 | *6 *7 |
| | 5 | LBL n | | Label | Indicates the jump destination of JMP or CJMP of the same No. n. | n: Constant(0-255) | ● | ● | ● | ● | ● | 0.1 0.65 | 1 | |
| | 6 | FOR n (s) | | FOR | When s=0, jumps to the location after the NEXT n of the same No. n when s is not 0, executes the next command. | n: Constant(0-49) s: WY, WR, WL, WM | ● | 1] | ● | ● | ● | 29 37 | 3 | |
| | 7 | NEXT n | | NEXT | Subtracts 1 from the s value of the FOR n of the same No. and jumps to FOR n. | n: Constant(0-49) | ● | 1] | ● | ● | ● | 23 25 | 2 | |
| | 8 | CAL n | | Call subroutine | Executes the SB n subroutine of the same No. n. | n: Constant(0-99) | ● | 1] | ● | ● | ● | 19 20 | 2 | |
| | 9 | SB n | | Start subroutine | Indicates the start of No. n subroutine. | n: Constant(0-99) | ● | ● | ● | ● | ● | 0.1 0.65 | 1 | |
| | 10 | RTS | | RETURN SUBROUTIN | Returns from subroutine. | None | ● | ● | ● | ● | ● | 17 16.7 | 1 | |
| | 11 | INT n | | Start interrupt scan | Indicates the start of No. n interrupt scan. | n: Constant(0-2) | ● | ● | ● | ● | ● | 0.1 0.65 | 1 | |
| | 12 | RTI | | RETURN INTERRUPT | Returns from interrupt scan. | None | ● | ● | ● | ● | ● | 8 5 | 1 | |

7. High-function module transfer commands

| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μs) | Step | Remarks |
|--|-------------|---|---|---|---|----------------|------|------|------|------|------|-------------------|------|---------|
| | | | | | | | DER | ERR | SD | V | C | | | |
| | | | | | | | | | | | | CPU5** | | |
| | | | | | | | | | | | | CPU4** | | |
| High-function module transfer commands | 1 | TRNS 0 (d, s, t) | General-purpose port transmission command | Transmits data from the CPU's general-purpose port. | t: R, L, M d: WY(Dummy I/O) s: WR, WL, WM | ↑ | ● | ● | ● | ● | ● | 61 | 5 | |
| | | | | | | | | | | | | 57 | | |
| | 2 | RECV 0 (d, s, t) | General-purpose port receiving command | Receives data at the CPU's general-purpose port. | t: R, L, M d: WX(Dummy I/O) s: WR, WL, WM | ↑ | ● | ● | ● | ● | ● | 61 | 5 | |
| | | | | | | | | | | | | 57 | | |
| | | TRNS 8 (d, s, t) Note.1) Not supported by EH-CPU104(A) | Telecommunication command | Controls the modem with the CPU's ladder program. | t: R, L, M d: WY(Dummy I/O) s: WR, WL, WM | ↑ | ● | ● | ● | ● | ● | 128 | 5 | |
| | | | | | | | | | | | | 68 | | |

8. FUN commands

| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μs) | Step | Remarks |
|----------------|-------------|----------------------------|----------------|----------------------------------|--|----------------|------|------|------|------|------|-------------------|------|---------------------------|
| | | | | | | | DER | ERR | SD | V | C | | | |
| FUN commands | 1 | FUN 0 (s) (PIDIT (s)) | | PID operation initialization | Initializes the area for PID operation. | s: WR | ● | ● | ● | ● | ● | 1,661 2979.9 | 3 | Number of loops = 1 *8 |
| | 2 | FUN 1 (s) (PIDOP (s)) | | PID operation execution control | Performs control for PID operation execution. | | ● | ● | ● | ● | ● | 83 85.4 | 3 | *8 |
| | 3 | FUN 2 (s) (PIDCL (s)) | | PID operation calculation | Executes PID operation. | | ● | ● | ● | ● | ● | 87 91.4 | 3 | Number of loops = 1 *8 |
| | 4 | FUN 4 (s) (IFR (s)) | | Process stepping | Performs the process stepping processing. | s: WR,WL,WM | ↑ | ● | ● | ● | ● | 208 191.4 | 3 | |
| | 5 | FUN 10 (s) (SIN (s)) | | SIN function | Calculates the SIN of the value designated by s and stores the result in s+1, s+2. | | ↑ | ● | ● | ● | ● | 39 40.4 | 3 | |
| | 6 | FUN 11 (s) (COS (s)) | | COS function | Calculates the COS of the value designated by s and stores the result in s+1, s+2. | | ↑ | ● | ● | ● | ● | 40 41.4 | 3 | |
| | 7 | FUN 12 (s) (TAN (s)) | | TAN function | Calculates the TAN of the value designated by s and stores the result in s+1, s+2. | | ↑ | ● | ● | ● | ● | 40 41.4 | 3 | |
| | 8 | FUN 13 (s) (ASIN (s)) | | ARC SIN function | Calculates the ARC SIN of the value designated by s (fractional portion) and s+1 (integer portion), and stores the result in s+2. | | ↑ | ● | ● | ● | ● | 62 63.4 | 3 | |
| | 9 | FUN 14 (s) (ACOS (s)) | | ARC COS function | Calculates the ARC COS of the value designated by s (fractional portion) and s+1 (integer portion), and stores the results in s+2. | | ↑ | ● | ● | ● | ● | 63 64.4 | 3 | |
| | 10 | FUN 15 (s) (ATAN (s)) | | ARC TAN function | Calculates the ARC TAN of the value designated by s (fractional portion) and s+1 (integer portion), and stores the results in s+2. | | ↑ | ● | ● | ● | ● | 41 42.4 | 3 | |
| | 11 | FUN 20 (s) | | Data search | Requested data is searched in assigned I/O table. | | ↑ | ● | ● | ● | ● | 86.2 - | | |
| | 12 | FUN 21 (s) | | Table search | Requested data block is taken from assigned I/O block table, and stored assigned address. | | ↑ | ● | ● | ● | ● | 104.2 - | | |
| | 13 | FUN 22 (s) | | Check code calculation | Check code for sending serial communication message is calculated and created. | | ↑ | ● | ● | ● | ● | 783.2 - | | |
| | 14 | FUN 23 (s) | | Check code verifying | Check code for receiving serial communication message is verified. | | ↑ | ● | ● | ● | ● | 790.2 - | | |
| | 15 | FUN 30 (s) (BINDA (s)) | | BIN → ASCII conversion (16 bits) | Converts 16-bit unsigned binary data to a decimal ASCII code, then stores it. | | ↑ | ● | ● | ● | ● | 140 141.4 | 3 | |
| | 16 | FUN 31 (s) (DBINDA (s)) | | BIN → ASCII conversion (32 bits) | Converts 32-bit unsigned binary data to a decimal ASCII code, then stores it. | | ↑ | ● | ● | ● | ● | 199 200.4 | 3 | |
| | 17 | FUN 32 (s) (BINHA (s)) | | BIN → ASCII conversion (16 bits) | Converts 16-bit unsigned binary data to an ASCII code, then stores it. | | ↑ | ● | ● | ● | ● | 124 125.4 | 3 | |
| | 18 | FUN 33 (s) (DBINHA (s)) | | BIN → ASCII conversion (32 bits) | Converts 32-bit unsigned binary data to an ASCII code, then stores it. | | ↑ | ● | ● | ● | ● | 168 | 3 | |
| | 19 | FUN 34 (s) (BCDDA (s)) | | BIN → ASCII conversion (16 bits) | Converts 16-bit BCD (BCD 4-digit) data to an ASCII code, then stores it. | | ↑ | ● | ● | ● | ● | 112 112.4 | 3 | |

| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μs) | Step | Remarks |
|----------------|-------------|----------------------------|----------------|-------------------------------------|---|----------------|------|------|------|------|------|-------------------|------|---------|
| | | | | | | | DER | ERR | SD | V | C | | | |
| | 20 | FUN 35 (s) (DBCDDA (s)) | | BIN → ASCII conversion (32 bits) | Converts 32-bit BCD (BCD 8-digit) data to an ASCII code, then stores it. | s: WR,WL,WM | ↑ | ● | ● | ● | ● | 171 171.4 | 3 | |
| | 21 | FUN 36 (s) (DABIN (s)) | | ASCII → BIN conversion (16 bits) | Converts unsigned BCD 5-digit data to an ASCII code, then stores it. | | ↑ | ● | ● | ● | ● | 60 61.4 | 3 | |
| | 22 | FUN 37 (s) (DDABIN (s)) | | ASCII → BIN conversion (32 bits) | Converts signed BCD 10-digit data to an ASCII code, then stores it. | | ↑ | ● | ● | ● | ● | 97 98.4 | 3 | |
| | 23 | FUN 38 (s) (HABIN (s)) | | ASCII → BIN conversion (16 bits) | Converts a 4-digit hexadecimal ASCII code to 16-bit binary data, then stores it. | | ↑ | ● | ● | ● | ● | 63 64.4 | 3 | |
| | 24 | FUN 39 (s) (DHABIN (s)) | | ASCII → BIN conversion (32 bits) | Converts a 8-digit hexadecimal ASCII code to 32-bit binary data, then stores it. | | ↑ | ● | ● | ● | ● | 94 94.4 | 3 | |
| | 25 | FUN 40 (s) (DABCD (s)) | | ASCII → BIN conversion (16 bits) | Converts a 4-digit ASCII code to 4-digit BCD data, then stores it. | | ↑ | ● | ● | ● | ● | 64 65.4 | 3 | |
| | 26 | FUN 41 (s) (DDABCD (s)) | | ASCII → BIN conversion (32 bits) | Converts a 8-digit ASCII code to 8-digit BCD data, then stores it. | | ↑ | ● | ● | ● | ● | 93 94.4 | 3 | |
| | 27 | FUN 42 (s) (ASC (s)) | | BIN → ASCII conversion (designated) | Converts binary data to an ASCII code of the designated number of characters, then stores it. | | ↑ | ● | ● | ● | ● | 119 116.4 | 3 | |
| | 28 | FUN 43 (s) (HEX (s)) | | ASCII → BIN conversion (designated) | Converts an ASCII code of the designated number of characters to binary data, then stores it. | | ↑ | ● | ● | ● | ● | 191 188.4 | 3 | |
| | 29 | FUN 44 (s) (SADD (s)) | | Merge character strings | Merges the designated character strings (up to NULL), then stores it in the I/O at the designated position. | | ↑ | ● | ● | ● | ● | 196 184.4 | 3 | |
| | 30 | FUN 45 (s) (SCMP (s)) | | Compare character strings | Compares the designated character strings (up to NULL), then stores the comparison result. | | ↑ | ● | ● | ● | ● | 157 147.4 | 3 | |
| | 31 | FUN 46 (s) (WTOB (s)) | | Word → byte conversion | Divides 16-bit word data, converts it to 8-bit byte data, then stores it. | | ↑ | ● | ● | ● | ● | 115 111.4 | 3 | |
| | 32 | FUN 47 (s) (BTOW (s)) | | Byte → word conversion | Divides 8-bit byte data, merges it into 16-bit word data, then stores it. | | ↑ | ● | ● | ● | ● | 109 104.4 | 3 | |
| FUN commands | 33 | FUN 48 (s) (BSHR (s)) | | Right-shift byte unit | Shifts the designated data string to the right for the number of the designated bytes (8 bits*n). | | ↑ | ● | ● | ● | ● | 81 79.4 | 3 | |
| | 34 | FUN 49 (s) (BSHL (s)) | | Left-shift byte unit | Shifts the designated data string to the left for the number of the designated bytes (8 bits*n). | | ↑ | ● | ● | ● | ● | 85 84.4 | 3 | |
| | 35 | FUN 60 (s) | | Binary square root | Calculates the square root of a 32-byte binary value. | | ↑ | ● | ● | ● | ● | 453 454.4 | 3 | |
| | 36 | FUN 61 (s) | | Dynamic scan pulse | Repeats on and off operations for the number of the designated scans. | | ↑ | ● | ● | ● | ● | 73 70.4 | 3 | |
| | 37 | FUN 80 (s) (ALREF (s)) | | I/O refresh (all points) | Refreshes all external I/O ranges. | | ↑ | ● | ● | ● | ● | 69 41.4 | 3 | |

| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μs) | Step | Remarks |
|----------------|-------------|-----------------------------|----------------|--|---|----------------|------|------|------|------|------|-------------------|------|---------|
| | | | | | | | DER | ERR | SD | V | C | | | |
| FUN commands | 38 | FUN 81 (s) (IOREF (s)) | | I/O refresh (I/O /link designation) | Refreshes only the input range, output range or link range. | s: WR,WL,WM | ↑ | ● | ● | ● | ● | 44 45.4 | 3 | |
| | 39 | FUN 82 (s) (SLREF (s)) | | I/O refresh (any slot) | Refreshes the I/O at the designated slot. | | ↑ | ● | ● | ● | ● | 80 79.4 | 3 | |
| | 40 | FUN 100 (s) (INTW (s)) | | Floating point operation (Real number to integer) | Real number to integer (Word) conversion. | | ↑ | ● | ● | ● | ● | 57 | 3 | *8 |
| | 41 | FUN 101 (s) (INTD (s)) | | Floating point operation (Real number to integer) | Real number to integer (Double word) conversion. | | ↑ | ● | ● | ● | ● | 69 69.4 | 3 | *8 |
| | 42 | FUN 102 (s) (FLOAT (s)) | | Floating point operation (integer to Real number) | Integer (word) to real number conversion. | | ↑ | ● | ● | ● | ● | 43 43.4 | 3 | *8 |
| | 43 | FUN 103 (s) (FLOATD (s)) | | Floating point operation (Integer to real number) | Integer (Double word) to real number conversion. | | ↑ | ● | ● | ● | ● | 47 47.4 | 3 | *8 |
| | 44 | FUN 104 (s) (FADD (s)) | | Floating point operation (addition) | The addition of the real number. | | ↑ | ● | ● | ● | ● | 70 70.4 | 3 | *8 |
| | 45 | FUN 105 (s) (FSUB (s)) | | Floating point operation (subtraction) | The subtraction of the real number. | | ↑ | ● | ● | ● | ● | 70 70.4 | 3 | *8 |
| | 46 | FUN 106 (s) (FMUL (s)) | | Floating point operation (multiplication) | The multiplication of the real number. | | ↑ | ● | ● | ● | ● | 69 70.4 | 3 | *8 |
| | 47 | FUN 107 (s) (FDIV (s)) | | Floating point operation (division) | The division of the real number. | | ↑ | ● | ● | ● | ● | 119 119.4 | 3 | *8 |
| | 48 | FUN 108 (s) (FRAD (s)) | | Floating point operation (radian conversion) | Angle to radian conversion. | | ↑ | ● | ● | ● | ● | 63 64.4 | 3 | *8 |
| | 49 | FUN 109 (s) (FDEG (s)) | | Floating point operation (angle conversion) | Radian to angle conversion. | | ↑ | ● | ● | ● | ● | 63 64.4 | 3 | *8 |
| | 50 | FUN 110 (s) (FSIN (s)) | | Floating point operation (calculate the SIN) | Calculates the SIN of the floating point number. | | ↑ | ● | ● | ● | ● | 282 282.4 | 3 | *8 |
| | 51 | FUN 111 (s) (FCOS (s)) | | Floating point operation (calculate the COS) | Calculates the COS of the floating point number. | | ↑ | ● | ● | ● | ● | 303 304.4 | 3 | *8 |
| | 52 | FUN 112 (s) (FTAN (s)) | | Floating point operation (calculate the TAN) | Calculates the TAN of the floating point number. | | ↑ | ● | ● | ● | ● | 343 341.4 | 3 | *8 |
| | 53 | FUN 113 (s) (FASIN (s)) | | Floating point operation (calculate the ARC SIN) | Calculates the ARC SIN of the floating point number. | | ↑ | ● | ● | ● | ● | 200 200.4 | 3 | *8 |
| | 54 | FUN 114 (s) (FACOS (s)) | | Floating point operation (calculate the ARC COS) | Calculates the ARC COS of the floating point number. | | ↑ | ● | ● | ● | ● | 192 191.4 | 3 | *8 |
| | 55 | FUN 115 (s) (FATAN (s)) | | Floating point operation (calculate the ARC TAN) | Calculates the ARC TAN of the floating point number. | | ↑ | ● | ● | ● | ● | 394 395.4 | 3 | *8 |
| | 56 | FUN 116 (s) (FSQR (s)) | | Floating point operation (calculate the square root) | Calculates the square root of the floating point number. | | ↑ | ● | ● | ● | ● | 481 482.4 | 3 | *8 |
| | 57 | FUN 117 (s) (FEXP (s)) | | Floating point operation (calculate the exponent) | Calculates the exponent of the floating point number. | | ↑ | ● | ● | ● | ● | 329 330.4 | 3 | *8 |
| | 58 | FUN 118 (s) (FLOG (s)) | | Floating point operation (logarithm) | Calculates the logarithm of the floating point number. | | ↑ | ● | ● | ● | ● | 187 187.4 | 3 | *8 |

| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μs) | Step | Remarks |
|----------------|-------------|-----------------------------|----------------|-------------------------------------|---|----------------|------|------|------|------|------|--------------------------|------|---------|
| | | | | | | | DER | ERR | SD | V | C | | | |
| FUN commands | 59 | FUN 120 (s) (INDXD (s)) | | Index setting (argument d) | Sets the argument used as an index in respect to argument d of the MOV and COPY commands. | s: WR,WL,WM | ● | ● | ● | ● | ● | 18 22.4 | 3 | |
| | 60 | FUN 121 (s) (INDXS (s)) | | Index setting (argument s) | Sets the argument used as an index in respect to argument s of the MOV and COPY commands. | | ● | ● | ● | ● | ● | 18 22.4 | 3 | |
| | 61 | FUN 122 (s) (INDXC (s)) | | Index cancel | Cancels the index specification that is set for argument d or s of the MOV and COPY commands. | | ↑ | ● | ● | ● | ● | 18 | 3 | |
| | 62 | FUN 123 (s) (INC (s)) | | Increment (Word I/O) | Add 1 to the number specified with word I/O. | | ● | ● | ● | ● | ● | 29 30.4 | 3 | *9 |
| | 63 | FUN 124 (s) (INCD (s)) | | Increment (Double word I/O) | Add 1 to the number specified with double word I/O. | | ↑ | ● | ● | ● | ● | 42 42.4 | 3 | *9 |
| | 64 | FUN 125 (s) (DEC (s)) | | Decrement (Word I/O) | Subtract 1 from the number specified with word I/O. | | ● | ● | ● | ● | ● | 30 30.4 | 3 | *9 |
| | 65 | FUN 126 (s) (DECD (s)) | | Decrement (Double word I/O) | Subtract 1 from the number specified with double word I/O. | | ↑ | ● | ● | ● | ● | 42 42.4 | 3 | *9 |
| | 65 | FUN 127 (s) (BITTOW (s)) | | Expand bit data to word data | Sets the data equivalent to the number of bits starting from the specified I/O number in the word I/O number. | | ↑ | ● | ● | ● | ● | 139 133.4 | 3 | |
| | 66 | FUN 128 (s) (WTOBIT) | | Expand word data to bit data | Sets the data equivalent to the number of words starting from the specified I/O number in the bit I/O number. | | ↑ | ● | ● | ● | ● | 145 139.4 | 3 | |
| | 66 | FUN 162 (s) | | Explicit message execution | Explicit message sent from EH-RMD to slave units. | | ↑ | ● | ● | ● | ● | 127.2 - | 3 | |
| | 67 | FUN 163 (s) | | Explicit message initial setting | Initial setting for explicit message sending. | | ↑ | ● | ● | ● | ● | 37.2 - | 3 | |
| | 68 | FUN 190 (s) | | Inverter control command | Hitachi inverter SJ300/L300P series controlled via RS-485. | | ↑ | ● | ● | ● | ● | | | |
| | 69 | FUN 200 (s) (XYR/W (s)) | | X/Y area read/write command | Command for reading and writing data using the X and Y areas. | | ↑ | ● | ● | ● | ● | 65 57.4 | 3 | *10 |
| | 70 | FUN 201 (s) (SCR/W (s)) | | Status control read/write command | Command for reading and writing data in the status control area. | | ↑ | ● | ● | ● | ● | 66 | 3 | *10 |
| | 71 | FUN 210 (s) (LOGIT (s)) | | Data logging initialization setting | Initializes the data logging function. | | ↑ | ● | ● | ● | ● | 1,728 2906.4 | 3 | *8 |
| | 72 | FUN 211 (s) (LOGWRT (s)) | | Log data write | Writes the data to the memory board. | | ↑ | ● | ● | ● | ● | 645 526.9 | 3 | *8 |

| Classification | Item number | Ladder symbol | Command symbol | Command name | Process descriptions | I/O types used | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | Process time (μ s) | Step | Remarks |
|----------------|-------------|-----------------------------|----------------|----------------|---|----------------|------|------|------|------|------|--------------------|------|---------|
| | | | | | | | DER | ERR | SD | V | C | | | |
| FUN commands | 73 | FUN 212 (s) (LOGCLR (s)) | | Log data clear | Clears the log data in the memory board. | s: WR,WL,WM | ↑ | ● | ● | ● | ● | 164 79.4 | 3 | *8 |
| | 74 | FUN 213 (s) (LOGRED (s)) | | Log data read | Reads the log data to the specified I/O area. | | ↑ | ● | ● | ● | ● | 268 210.4 | 3 | *8 |
| | 75 | FUN 254 (s) (BOXC (s)) | | BOX comment | Nothing is processed in the CPU. | | ● | ● | ● | ● | ● | 0.3 14.4 | 3 | |
| | 76 | FUN 255 (s) (MEMC (s)) | | Memo comment | Nothing is processed in the CPU. | | ● | ● | ● | ● | ● | 0.3 14.4 | 3 | |

*1 Value in case of word, it is 5 steps for LD (s1□s2) and AND (s1□s2), and 6 steps for OR (s1□s2).

*2 Value in case of D-word for LD (s1□s2) and AND (s1□s2), it is 5 steps when s1 and s2 is I/O and I/O, 6 steps when s1 and s2 is I/O and const. or const. and I/O, and 7 steps when s1 and s2 is const. and const.. For OR (s1□s2), 1 step is added each.

*3 Processing time when n=1.

*4 Value in case of the size of FIFO is n=1.

*5 When condition not fulfilled.

*6 When condition not fulfilled.

*7 When condition fulfilled.

*8: Supported by the EH-CPU308(A)/316(A)/448(A)/516/548.

*9: Supported by the EH-CPU308/316/**A/448/516/548.

*10: Supported by the EH-CPU308A/316A/448(A)/516/548.

*11: Supported by the EH-CPU**A/448/516/548.

*12: Supported by the EH-CPU516/548.

5.3 Command Specification Details





| | |
|--|--|
| (1) Basic commands | |
| (2) Arithmetic commands | |
| (3) Application commands | |
| (4) Control commands | |
| (5) High-function module transfer commands | |
| (6) FUN commands | |

The classification of the processing time column in each command table is shown in the table below:






| Description in the table | Classification |
|--------------------------|--|
| EH-CPU4**/ EH-CPU5** | EH-CPU448/448A/516/548 |
| EH-CPU***A | EH-CPU104A/208A/308A/316A |
| EH-CPU3** | EH-CPU308/316 of ROM Ver. 04 or later |
| Other than left | EH-CPU104/208, and EH-CPU308/316 of ROM Ver. 03 or earlier |

Depending on the CPU model, all of the commands may not be supported. For the commands that are supported by each CPU, see the explanation of each command or Appendix 2, “H-series Command Support Comparison Chart”.

LD
LDI

| Item number | | Basic commands-1, 2 | | | | Name | | Logical operation start (LD, LDI) | | | | | | | | | |
|---|------------|--|-----|-----------------|---------|-----------------------------------|-------|-----------------------------------|------------------------|-------------|-------------------------|-----|-----------------|-------|-----------------------------------|--|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
|  | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | Upper case: LD Lower case: LDI | | |
| | | | | DER | ERR | SD | V | C | Ave | Max | Ave | Max | Ave | Max | | | |
| | | | | ● | ● | ● | ● | ● | | | 1.0 | | | | | | |
| Command format | | | | Number of steps | | | | | 0.1 | ← | 1.1 | ← | 1.3 | 1.5 | | | |
| LD n | | | | Condition | | | Steps | | | | 1.0 | | | | | | |
| LDI n | | | | — | | | 1 | | | | 1.5 | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | |
| n | I/O number | | ○ | ○ | ○ | ○ | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | |
|  | | Starts the a-contact logical operation. Enters the continuity state when input is on. | | | | | | | | | | | | | | | |
|  | | Starts the b-contact logical operation. Enters the continuity state when input is off. | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| ● L and WL become the internal output when link modules are not used. | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
|  | | <div><div>LD</div><div>X00000</div><div>OUT</div><div>Y00100</div></div> <div><div>LDI</div><div>X00001</div><div>OUT</div><div>Y00101</div></div> | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| ● When input X00000 is on, output Y00100 is on; when off, the output is off. | | | | | | | | | | | | | | | | | |
| ● When input X00001 is off, output Y00101 is on; when on, the output is off. | | | | | | | | | | | | | | | | | |

AND n
ANI n

| Item number | | Basic commands-3, 4 | | | | Name | | Contact series connection (AND, ANI) | | | | | | | | | |
|--|------------|---|-----|-----------------|---------|-----------------------------------|-------|--------------------------------------|------------------------|----------------------|-------------------------|-----|-----------------|----------|---------------------------------------|--------|-----|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| <div> </div> | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | Upper case: AND Lower case: ANI | | |
| | | | | DER | ERR | SD | V | C | Ave | Max | Ave | Max | Ave | Max | | | |
| | | | | ● | ● | ● | ● | ● | | | 1.0 | | | | | | |
| Command format | | | | Number of steps | | | | | | 0.1 | ← | | ← | 1.0 | | | 1.2 |
| AND n | | | | Condition | | | Steps | | | | | 1.1 | | | | | |
| ANI n | | | | — | | | 1 | | | | | 1.0 | | | | | |
| | | | | | | | | | | | | 1.3 | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | |
| n | I/O number | | | ○ | ○ | ○ | ○ | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | |
| <div> AND n</div> Obtains AND of the previous operation result and the a-contact operation. | | | | | | | | | | | | | | | | | |
| <div> ANI n</div> Obtains AND of the previous operation result and the b-contact operation. | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| ● L and WL become the internal output when link modules are not used. | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| <div></div> | | <div><div>LD X00002 AND R010 OUT Y00100</div><div>LD X00003 ANI R011 OUT Y00101</div></div> | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| ● When input X00002 and R010 are both on, output Y00100 is on and all others are off. | | | | | | | | | | | | | | | | | |
| ● When input X00003 is on and R011 is off, output Y00101 is on and all others are off. | | | | | | | | | | | | | | | | | |

OR
ORI
n

| Item number | | Basic commands-5, 6 | | | | Name | | Contact parallel connection (OR, ORI) | | | | | | | | | | | | | |
|--|------------|---------------------|--|--|------|---------|-----------------------------------|---------------------------------------|------------------------|----------------------|-------------------------|-------------|-----------------|------------|-----------------------------------|--------|----------|--|-------|--|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | |
| | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | Upper case: OR Lower case: ORI | | | | | | |
| | | | | DER | ERR | SD | V | C | Ave | Max | Ave | Max | Ave | Max | | | | | | | |
| | | | | ● | ● | ● | ● | ● | | | | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | | 7.1 | | ← | | ← | | | 1.3 | | 1.5 | | |
| OR n | | | | Condition | | | Steps | | | | | | | | | | | | | | |
| ORI n | | | | — | | | 2 | | | | | | | | | | | | | | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | | | | Constant | | Other | | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | |
| n | I/O number | | | ○ | ○ | ○ | ○ | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | |
| | | | | Obtains OR of the previous operation result and the a-contact operation. | | | | | | | | | | | | | | | | | |
| | | | | Obtains OR of the previous operation result and the b-contact operation. | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | |
| ● L and WL become the internal output when link modules are not used. | | | | | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | |
| | | | | LD X00000 OR X00001 ORI X00002 OUT Y00105 | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | |
| ● When X00000 is on, X00001 is on, or X00002 is off, the operation is 1 and Y00105 turns on. | | | | | | | | | | | | | | | | | | | | | |



| Item number | Basic commands-7 | | | | | Name | | Negation (NOT) | | | | | | | | | |
|---------------------|------------------|--|-----------------|------|---------|-----------------------------------|------|------------------------|------------|-------------------------|-------------|-----------------|------------|----------|-------|--|--|
| Ladder format | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | |
| | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | | | |
| | | | DER | ERR | SD | V | C | Ave | Max | Ave | Max | Ave | Max | | | | |
| | | | ● | ● | ● | ● | ● | 0.2 | ← | 2.1 | ← | 1.7 | ← | | | | |
| Command format | | | Number of steps | | | | | | | | | | | | | | |
| NOT | | | Condition | | | Steps | | 0.2 | ← | 2.1 | ← | 1.7 | ← | | | | |
| | | | — | | | 2 | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| Function | | ● Reverses the operation result obtained up to that point. | | | | | | | | | | | | | | | |
| Program example | | <div><pre>LD X00010 AND X00011 NOT OUT R100</pre></div> | | | | | | | | | | | | | | | |
| Program description | | <ul style="list-style-type: none">When input X00010 and input X00011 are both on, the operation is 1, but due to , the calculation turns into “0” and R100 turns off.In all other cases, R100 turns on. | | | | | | | | | | | | | | | |

AND DIF n
OR DIF n

| Item number | | Basic commands-8 | | | | Name | | Rising edge detection (AND DIF, OR DIF) | | | | | | | | | |
|---------------------|--------|------------------|---|---|-----------------------------------|-------|------|---|------------------------|-------------|--------------------------|----------|-----------------|-----|---|------------|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | Upper case: AND DIF Lower case: OR DIF | | |
| | | | | DER | ERR | SD | V | C | Ave | Max | Ave | Max | Ave | Max | | | |
| | | | | ● | ● | ● | ● | ● | | | 3.1 | | | | | | |
| Command format | | | | Number of steps | | | | | 0.3 | ← | 3.1 3.1 4.1 3.1 | ← | 2.7 | 2.9 | | | |
| AND DIF n | | | | Condition | | Steps | | | | | | | | | | | |
| OR DIF n | | | | AND DIF n | | 3 | | | | | | | | | | | |
| | | | | OR DIF n | | 4 | | | | | | | | | | | |
| Usable I/O | | X | Y | Bit | | Word | | | | Double word | | Constant | Other | | | | |
| | | | | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | | | DR, DL, DM | |
| n | Number | | | | | | | | | | | | | ○ | 0 to 511 (Decimal) | | |
| Function | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">• Detects the rise of an input signal and retains the operation result for one scan. () indicates the display when the LADDER EDITOR is used. | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">• DIF number may not be overlapped. (However, no error is generated even if overlapped numbers are used.)• DIF cannot use the b contact. | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| | | | | <div>LD X00000</div> <div>AND DIF0</div> <div>OUT R123</div> | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">• Upon rising of X00000 on, R123 turns on for one scan.• If b-contact is used for X00000, operation will be the same as the a-contact DFN operation. | | | | | | | | | | | | | |

| Item number | | Basic commands-9 | | | | Name | | Falling edge detection (AND DFN, OR DFN) | | | | | | | | | |
|--|--------|------------------|-----|-----------------------------------|---------|-----------------------------------|------|--|------------------------|-----|-------------------------|-----|-----------------|----------|---|-------|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | Upper case: AND DFN Lower case: OR DFN | | |
| | | | | DER | ERR | SD | V | C | Ave | Max | Ave | Max | Ave | Max | | | |
| | | | | ● | ● | ● | ● | ● | | | | | | | | | |
| Command format | | | | Number of steps | | | | | 0.3 | ← | 3.1 | ← | 2.7 | 2.9 | | | |
| AND DFN n | | | | Condition | | Steps | | | | | 3.1 | | | | | | |
| OR DFN n | | | | AND DFN n | | 3 | | | | | 4.1 | | | | | | |
| | | | | OR DFN n | | 4 | | | | | 3.1 | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | | Other | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | |
| n | Number | | | | | | | | | | | | | ○ | 0 to 511 (Decimal) | | |
| Function | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">• Detects the fall of an input signal and retains the operation result for one scan. () indicates the display when the LADDER EDITOR is used. | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">• DFN number may not be overlapped. (However, no error is generated even if overlapped numbers are used.)• DFN cannot use the b contact. | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| | | | | LD X00000 AND DFN0 OUT R124 | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">• Upon a fall of X00000, R124 turns on for one scan.• If b-contact is used for X00000, operation will be the same as the a-contact DIF operation. | | | | | | | | | | | | | | | | | |

OUT n

| Item number | | Basic commands-10 | | | | Name | | Coil output (OUT) | | | | | | | | | | | | | |
|---|------------|-------------------|--|--|------|---------|-----------------------------------|-------------------|------------------------|----------------------|-------------------------|-------------|-----------------|------------|----------|--------|--|-----|--|-----|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | |
|  | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | | | | | | |
| | | | | DER | ERR | SD | V | C | Ave | Max | Ave | Max | Ave | Max | | | | | | | |
| | | | | ● | ● | ● | ● | ● | | | | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | | 0.1 | | ← | | 1.0 | | ← | | 1.0 | | 1.7 | |
| OUT n | | | | Condition | | | Steps | | | | | | | | | | | | | | |
| | | | | — | | | 1 | | | | | | | | | | | | | | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | |
| n | I/O number | | | | ○ | ○ | ○ | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">Switches on the coil when the operation result obtained up to that point is “1.”Switches off the coil when the operation result obtained up to that point is “0.” | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">L and WL become the internal output when link modules are not used. | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | |
|  | | | | | | | | | | | | | | | | | | | | | |
| | | | | LD X00000 OUT Y00110 | | | | | | | | | | | | | | | | | |
| | | | | LD X00001 OUT Y00111 OUT Y00112 | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">When input X00000 is on, the operation is “1” and Y00110 turns on.When input X00001 is on, the operation is “1,” and Y00111 and Y00112 turn on. | | | | | | | | | | | | | | | | | |

| Item number | Basic commands-11, 12 | Name | Set/reset coil output (SET, RES) | | | | | | | | | | | |
|---|-----------------------|------|--|------|---------|-----------------------------------|------|------------------------|------------|-------------------------|-----|-----------------|----------|------------------------------------|
| Ladder format | | | Condition code | | | | | Processing time (μs) | | | | | | Remark |
| | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | Upper case: SET Lower case: RES |
| | | | DER | ERR | SD | V | C | Ave | Max | Ave | Max | Ave | Max | |
| | | | ● | ● | ● | ● | ● | | | | | | | |
| Command format | | | Number of steps | | | | | 0.1 | ← | ← | 0.9 | 1.7 | | |
| SET n RES n | | | Condition | | Steps | | | | | | | | | |
| | | | — | | 1 | | | | | | | | | |
| | | | | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | |
| n | I/O number | | | ○ | ○ | | | | | | | | | |
| Function | | | | | | | | | | | | | | |
| | | | Switches on the device when the operation result obtained up to that point is “1.” The device that is switched on will not be switched off even if the operation result is “0.” | | | | | | | | | | | |
| | | | Switches off the device when the operation result obtained up to that point is “1.” () indicates the display when the LADDER EDITOR is used. | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">When a set/reset coil is used on a multi layer coil, it must be set to the highest level or an arbitrary coil must be entered immediately before the set/reset coil. | | | | | | | | | | | | | | |
| <div>Example of OK</div> | | | <div>Example of NG</div> | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | |
| | | | <div>LD X00000 SET R100 LD X00001 RES R100</div> | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">When input X00000 turns on, output R100 turns on. Even if X00000 turns off, R100 remains on.When input X00001 turns on, output R100 turns off. When input X00000 and X00001 both turn on, the one executed later than the other in the program takes priority. | | | | | | | | | | | | | | |

MCS n
MCR n

| Item number | Basic commands-13, 14 | | | | Name | | Set (start)/reset (cancel) master control (MCS, MCR) | | | | | | | | | |
|--|-----------------------|--|--|-----------------|------|---------|--|------|----------------------|------------|-------------|-----|-----------------|------------|------------------------------------|-------------------|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: MCS Lower case: MCR | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | | | Number of steps | | | | | 0.3 | ← | 3.1 | ← | 2.3 | ← | | |
| MCS n MCR n | | | | Condition | | Steps | | | 0.2 | ← | 3.1 | ← | 2.3 | ← | | |
| | | | | MCS n | | 3 | | | | | 2.2 | | | | | |
| | | | | MCR n | | 2 | | | 0.2 | ← | 2.2 | ← | 1.6 | ← | | |
| | | | | Bit | | Word | | | | | Double word | | | | | |
| Usable I/O | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | Constant | Other |
| n | Number | | | | | | | | | | | | | | ○ | 0 to 49 (Decimal) |
| Function | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">Controls the input to the ladder sandwiched by the master control set (MCS n) and reset (MCR n). (An AND operation is performed with respect to each input and MCS.) <p>The master control can be used up to eight layers.</p> <p>() indicates the display when the LADDER EDITOR is used.</p> | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">Always use the master control MCS and MCR in pairs.When a EH-CPU448* (ROM VER. C413 / C331 or older) is used. Insert a double word operation just before a master control instruction. <p>* As for the EH-CPU448 (ROM VER. C414 / C332 or later) , dummy operation doesn't need to add to user program.</p> <p>EX.)</p> <div><p>← Additional ladder</p><p>← Additional ladder</p></div> | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | |
| <div><pre>LD X00000 MCS1 LD X00001 OUT Y00100 MCR1</pre></div> <div><p>← Up to eight layers are allowed.</p></div> | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">When input X00000 is on, the ladders surrounded by MCS and MCR obeys input X00001, and output Y00100 turns on/off.When input X00000 is off, the ladders surrounded by MCS and MCR are independent of input X00001, and output Y00100 turns off. | | | | | | | | | | | | | | | | |







| Item number | Basic commands-15, 16, 17 | Name | | | | | Save/read/clear operation result (Branching of ladder) | | | | | | | | | |
|---|---------------------------|---|-----------------|---------|-----------------------------------|-------|--|----------------------|------------|-------------|-----------------|----------|-------|------------|--|--|
| Ladder format | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| <div><div></div><div></div><div></div></div> <div>Save</div> <div>Read</div> <div>Clear</div> | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | |
| | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | |
| Command format | | | Number of steps | | | | | | | | | | | | | |
| MPS Save | | | Condition | | | Steps | | — | — | — | — | — | — | | | |
| MRD Read | | | — | | | 0 | | | | | | | | | | |
| MPP Clear | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | |
| | | <div><div><div><div>X00100</div><div>R001</div><div>R002</div><div>R003</div><div>R004</div></div><div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div></div></div><div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div></div> | | | | | | | | | | | | | | |


| Item number | Basic commands-18 | | | | | Name | Logical block series connection (ANB) | | | | | | | | | |
|---|-------------------|--|--|------|---------|-----------------------------------|---------------------------------------|----------------------|------------|------------|-------------|-----------------|------------|----------|-------|--|
| Ladder format | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| (See Function column) | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | Number of steps | | | | | — | — | — | — | — | — | | | |
| ANB | | | Condition | | Steps | | | | | | | | | | | |
| | | | — | | 0 | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | |
| | | | <div><div><div><div><div>X00001</div><div>R010</div><div>M0020</div><div>M0021</div><div>Y00110</div></div><div><div>R011</div><div>M0022</div></div></div></div></div> <div><div>LD X00001</div><div>LD R010</div><div>OR R011</div><div>ANB</div><div>LD M0020</div><div>AND M0021</div><div>OR M0022</div><div>ANB</div><div>OUT Y00110</div></div> | | | | | | | | | | | | | |
| This command is used to perform AND operation with respect to the logical operation blocks (dotted line areas). | | | | | | | | | | | | | | | | |

This command is used to perform AND operation with respect to the logical operation blocks (dotted line areas).

| Item number | Basic commands-19 | | | | | Name | Logical block parallel connection (ORB) | | | | | | | | | |
|-----------------------|-------------------|-----|-----------------|---------|-----------------------------------|------|---|----------------------|-----|-------------|-----|-----------------|----------|--------|--|--|
| Ladder format | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| (See Function column) | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | Number of steps | | | | | 7.0 | ← | 1.0 | ← | 0.7 | — | | | |
| ORB | | | Condition | | Steps | | | | | | | | | | | |
| | | | — | | 1 | | 1.0 | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |

This command is used to perform OR operation with respect to the logical operation blocks (dotted line areas).

| Item number | Basic commands-20 | Name | | | | Processing box start and end (PROCESSING BOX) | | | | | | | | | |
|--|-------------------|---|------|---------|-----------------------------------|---|----------------------|------------|-----|-----------------|-----|----------|--------|------------|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
|  | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | | |
| | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | |
| | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | |
| Command format | | Number of steps | | | | | 0.3 | ← | 2.2 | ← | 1.8 | | ← | | |
| [] | | Condition | | | Steps | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">Indicates the start and end of the processing box. | | | | | | | | | | | | | | | |
|  | | <div>LD X00001</div> <div>[</div> <div>WY0010=WX0000</div> <div>]</div> | | | | | | | | | | | | | |
| In the above example, the operation of inside the processing box will be executed when input X00001 is on. | | | | | | | | | | | | | | | |
| Parallel connection of processing box or coil is not allowed. | | | | | | | | | | | | | | | |
| <div><div></div><div>→</div><div></div></div> | | | | | | | | | | | | | | | |
| <div><div>Not allowed</div><div>Allowed</div></div> | | | | | | | | | | | | | | | |
| <div><div></div><div>→</div><div></div></div> | | | | | | | | | | | | | | | |
| <div><div>Not allowed</div><div>Allowed</div></div> | | | | | | | | | | | | | | | |


| Item number | Basic commands-21 | | | | | Name | | Relational box start and end (RELATIONAL BOX) | | | | | | | | | |
|--|-------------------|--|-----|-----------------|---------|-----------------------------------|-------|---|------------|----------------------|-------------|-----|-----------------|----------|-------|--------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
|  | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | — | | — | | — | | — | |
| () | | | | Condition | | | Steps | | | | | | | | | | |
| | | | | — | | | 0 | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">● Indicates the start and end of the relational box. | | | | | | | | | | | | | | | | | |

OUT TD n t s

| Item number | | Basic commands-22 | | | | Name | | On delay timer | | | | | | | | |
|------------------|--------------|---|---|-----------------|-----------------------------------|-------|------|----------------|----------------------|-------------|------------|----------|-----------------|-----------------------|------------|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | | | Number of steps | | | | | 26.4 | ← | 28.1 | ← | 11.5 | 12.0 | | |
| OUT TD n t s | | | | Condition | | Steps | | | | | | | | | | |
| | | | | — | | 5 | | | | | 9.0 | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | | DR, DL, DM | |
| n | Timer number | | | | | | | | | | | | ○ | 0 to 255 (Decimal) | | |
| t | Time base | | | | | | | | | | | | | .01s, .1s, 1s | | |
| s | Set value | | | | | ○ | ○ | ○ | | | | | ○ | 1 to 65,535 (Decimal) | | |
| Function | | <ul style="list-style-type: none">• The progress value is updated when the startup condition is on, and the coil switches on when the progress value is greater than or equal to the set value.• If the startup condition switches off, the progress value is cleared and the coil switches off.• The progress value is set in TC n and does not exceed 65,535 (decimal).• If the progress value is updated while the system is running, the operation will be performed using the new progress value at that point.• If an I/O is set for the set value, the set value can be changed during operation by changing the I/O value, since the set values are updated during each scan. | | | | | | | | | | | | | | |
| Cautionary notes | | <ul style="list-style-type: none">• The .01s time base can only be used for timer numbers 0 to 63 (64 points).• The .1s and 1s time bases can be used for all timer numbers (0 to 255).• A maximum of 256 points can be used for the timers TD, SS, MS, TMR and WDT in total. However, the same area as the counter is used. Timer number and counter number may not be overlapped.• <u>The progress value is updated when the timer command is expected in the EH-CPU***A/448/516/548.</u> Therefore, if a program that does not scan the timer command execution section after the timer is activated is created using the JMP command or master control (MCS), the timer may not turn on correctly. (The timer does not turn on correctly when the time that does not scan the timer command execution section exceeds the time calculated by multiplying the time base by 65,535.) Note that the previous progress value is also retained until the timer command is executed. | | | | | | | | | | | | | | |
| Program example | | <div><pre>LD X00000 OUT TD10 0.01s 12345 LD TD10 OUT R100</pre></div> <ul style="list-style-type: none">• An example of a word I/O being used as the set value for the ladder shown above. <div><pre>LD R7E3 [WR0010=12345] LD X00000 OUT TD10 0.01s WR0010 LD TD10 OUT R100</pre></div> | | | | | | | | | | | | | | |

Program description

[Time chart]









- 1] When input X00000 turns on, TD progress value is updated.
- 2] When input X00000 turns off, the TD progress value is cleared.
- 3] TD10 turns on when progress value \geq set value.
- 4] While X00000 is on, the progress value increases, but will not increase exceeding 65,535.
- 5] When X00000 turns off, TD10 also turns off and the progress value is cleared.

- Example using word I/O as the set value

When RUN is commenced, the set value is set to word I/O.


Or, designate the word I/O for the set value to store in the power failure memory beforehand.

| Item number | | Basic commands-22 | | | | Name | | On delay timer (ON DELAY TIMER) | | | | | | | | | |
|---|--------------|--|---|-----------------|-----------------------------------|-------|------|---------------------------------|----------------------|-------------|------------|----------|-----------------|-----------------------|--------|--|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
|  | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | 26.4 | ← | 28.1 | ← | 11.5 | 12.0 | | | |
| OUT TD n t s | | | | Condition | | Steps | | | | | | | | | | | |
| | | | | — | | 5 | | | | | 9.0 | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | |
| n | Timer number | | | | | | | | | | | | ○ | 0 to 255 (Decimal) | | | |
| t | Time base | | | | | | | | | | | | | .01s, .1s, 1s | | | |
| s | Set value | | | | | ○ | ○ | ○ | | | | | ○ | 1 to 65,535 (Decimal) | | | |
| Function | | <ul style="list-style-type: none">• The progress value is updated when the startup condition is on, and the coil switches on when the progress value is greater than or equal to the set value.• If the startup condition switches off, the progress value is cleared and the coil switches off.• The progress value is set in TV n and does not exceed 65,535 (decimal).• If the progress value is updated while the system is running, the operation will be performed using the new progress value at that point.• If an I/O is set for the set value, the set value can be changed during operation by changing the I/O value, since the set values are updated during each scan. | | | | | | | | | | | | | | | |
| Cautionary notes | | <ul style="list-style-type: none">• Time base is fixed as 0.01s.• Timer TM is supported by LADDER EDITOR for Windows Ver.3.00 or newer. User program including TM does not work with CPU104(A)/208(A)/308(A)/316(A)/448(A) and LADDER EDITOR for Windows Ver.2.** or older.• <u>The progress value is updated when the timer command is expected.</u> Therefore, if a program that does not scan the timer command execution section after the timer is activated is created using the JMP command or master control (MCS), the timer may not turn on correctly. (The timer does not turn on correctly when the time that does not scan the timer command execution section exceeds the time calculated by multiplying the time base by 65,535.) Note that the previous progress value is also retained until the timer command is executed. | | | | | | | | | | | | | | | |
| Program example | | <div><pre>LD X00000 OUT TM10 0.01s 12345 LD TM10 OUT R100</pre></div> <ul style="list-style-type: none">• An example of a word I/O being used as the set value for the ladder shown above. <div><pre>LD R7E3 [WR0010=12345] LD X00000 OUT TM10 0.01s WR0010 LD TM10 OUT R100</pre></div> | | | | | | | | | | | | | | | |
| Please refer to the “TD” for the timing chart. | | | | | | | | | | | | | | | | | |

| Item number | | Basic commands-23 | | | | Name | | Single shot timer | | | | | | | | | | | | | |
|---|--------------|--|--|-----------------|------|---------|-----------------------------------|-------------------|-----------|----------------------|------------|-------------|-----------------|----------|-------|-----------------------|--|------|------------|---|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | |
|  | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | |
| Command format | | | | Number of steps | | | | | | 21.4 | | ← | | 23.1 | | ← | | 12.2 | | ← | |
| OUT SS n t s | | | | Condition | | | Steps | | | | | | | | | | | | | | |
| | | | | — | | | 5 | | | | | | | | | | | | | | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | Constant | Other | | | | | | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | | | | DR, DL, DM | | |
| n | Timer number | | | | | | | | | | | | | | ○ | 0 to 255 (Decimal) | | | | | |
| t | Time base | | | | | | | | | | | | | | | .01s, .1s, 1s | | | | | |
| s | Set value | | | | | | | ○ | ○ | ○ | | | | | ○ | 1 to 65,535 (Decimal) | | | | | |
| Function | | <ul style="list-style-type: none">• Detects the rising edge of the startup condition, starts updating progress values, and switches on the coil.• The coils switches off when the progress value is greater than or equal to the set. If a rising edge is detected while the progress value is less than the set value, the progress value is set to 0 and the counter is reset.• The progress value is set in TC n and does not exceed 65535 (decimal).• If the progress value is updated while the system is running, the operation will be performed using the new progress value at that point.• If an I/O is set for the set value, the set value can be changed during operation by changing the I/O value, since the set values are updated during each scan. | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | <ul style="list-style-type: none">• The .01s time base can only be used for timer numbers 0 to 63 (64 points).• The .1s and 1s time bases can be used for all timer numbers (0 to 255).• A maximum of 256 points can be used for the timers TD, SS, MS, TMR and WDT in total. However, the same area as the counter is used. Timer number and counter number may not be overlapped.• Since the startup condition of a single shot is edge detection, the condition cannot be detected during the first scan after the running is started.• <u>The progress value is updated when the timer command is expected in the EH-CPU***A/448/516/548.</u> Therefore, if a program that does not scan the timer command execution section after the timer is activated is created using the JMP command or master control (MCS), the timer may not turn on correctly. (The timer does not turn on correctly when the time that does not scan the timer command execution section exceeds the time calculated by multiplying the time base by 65,535.) Note that the previous progress value is also retained until the timer command is executed. | | | | | | | | | | | | | | | | | | | |
| Program example | | <div><pre>LD X00001 OUT SS11 0.01s 12567 LD SS11 OUT R101</pre></div> <ul style="list-style-type: none">• An example of a word I/O being used as the set value for the ladder shown above. <div><pre>LD R7E3 [WR0011=12567 LD X00001 OUT SS11 0.01s WR0011 LD SS11 OUT R101]</pre></div> | | | | | | | | | | | | | | | | | | | |




Program description

[Time chart]




- 1] The progress value is updated and SS11 turns on at the rising edge of X00001.
- 2] SS11 turns off when set value \geq progress value. X00001 is turned on at this time, but the single shot startup conditions are ignored because it uses edge trigger.
- 3] SS11 is turned on at the rising edge of X00001 again, and the progress value is updated.
- 4] When the rising edge of X00001 is detected while the progress value does not reach the set value, the single shot timer is triggered again and the progress value returns to 0, then starts increasing. The SS11 remains on.

- Example using word I/O as the set value
When RUN is commenced, the set value is set to word I/O.
Or, designate the word I/O for the set value to store in the power failure memory beforehand.

| Item number | | Basic commands-24 | | | | Name | | Mono stable timer | | | | | | | | | |
|---|--------------|---|--|-----------------|------|---------|-----------------------------------|-------------------|----------------------|-------------|------------|-----|-----------------|-------|--------------------|-----------------------|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
|  | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | 21.4 | ← | 23.1 | ← | 12.2 | ← | | | |
| OUT MS n t s | | | | Condition | | Steps | | | | | | | | | | | |
| | | | | — | | 5 | | | | | | | | | | | |
| Usable I/O | | | | Bit | | | Word | | | Double word | | | Constant | Other | | | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | | | DY | DR, DL, DM | |
| n | Timer number | | | | | | | | | | | | | ○ | 0 to 255 (Decimal) | | |
| t | Time base | | | | | | | | | | | | | | .01s, .1s, 1s | | |
| s | Set value | | | | | | | ○ | ○ | ○ | | | | | ○ | 1 to 65,535 (Decimal) | |
| Function | | <ul style="list-style-type: none">• Detects the rising edge of the startup condition, starts updating progress values, and switches on the coil.• The coil switches off when the progress value is greater than or equal to the set value. The rise of the startup condition is ignored while the MS is on.• The progress value is set in TC n and does not exceed 65,535 (decimal).• If the progress value is updated while the system is running, the operation will be performed using the new progress value at that point.• If an I/O is set for the set value, the set value can be changed during operation by changing the I/O value, since the set values are updated during each scan. | | | | | | | | | | | | | | | |
| Cautionary notes | | <ul style="list-style-type: none">• The .01s time base can only be used for timer numbers 0 to 63 (64 points).• The .1s and 1s time bases can be used for all timer numbers (0 to 255).• A maximum of 256 points can be used for the timers TD, SS, MS, TMR and WDT in total. However, the same area as the counter is used. Timer number and counter number may not be overlapped.• Since the startup condition of the mono stable timer is edge detection, the condition may not be detected during the first scan after the running is started.• <u>The progress value is updated when the timer command is expected in the EH-CPU***A/448/516/548.</u> Therefore, if a program that does not scan the timer command execution section after the timer is activated is created using the JMP command or master control (MCS), the timer may not turn on correctly. (The timer does not turn on correctly when the time that does not scan the timer command execution section exceeds the time calculated by multiplying the time base by 65,535.) Note that the previous progress value is also retained until the timer command is executed. | | | | | | | | | | | | | | | |
| Program example | | <div></div> <div><ul style="list-style-type: none">• An example of a word I/O being used as the set value for the ladder shown above.</div> <div></div> <div><pre>LD X00002 OUT MS12 0.1s 5425 LD MS12 OUT R102 LD R7E3 [WR0012=5425 X00002] LD X00002 OUT MS12 0.1s WR0012 LD MS12 OUT R102</pre></div> | | | | | | | | | | | | | | | |




Program description

[Time chart]




- 1] The progress value is updated and MS12 turns on at the rising edge of X00002.
- 2] MS12 turns off when set value \geq progress value. X00002 is on at this time, but it is ignored since the startup condition for a mono-stable timer is edge trigger.
- 3] MS12 is turned on at the rising edge of X00002 again, and progress value is updated.
- 4] Even if the rising edge of X00002 is detected while the progress value does not reach the set value, the mono-stable timer ignores the rise.

- Example using word I/O as the set value
When RUN is commenced, the set value is set to word I/O.
Or, designate the word I/O for the set value to store in the power failure memory beforehand.

| Item number | | Basic commands-25 | | | | Name | | Integral timer | | | | | | | | | |
|---|--------------|---|---|-----------------|-----------------------------------|------|-------|----------------|-----------|----------------------|------------|------------|-----------------|-----------------------|---|--------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
|  | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | | | | | | | | |
| OUT TMR n t s | | | | Condition | | | Steps | | | 21.4 | ← | 23.1 | ← | 12.2 | ← | | |
| | | | | — | | | 5 | | | | | 9.4 | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| n | Timer number | | | | | | | | | | | | ○ | 0 to 255 (Decimal) | | | |
| t | Time base | | | | | | | | | | | | | .01s, .1s, 1s | | | |
| s | Set value | | | | | ○ | ○ | ○ | | | | | ○ | 1 to 65,535 (Decimal) | | | |
| Function | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">Updates the progress value while the startup condition is on. The progress value is not cleared even if the startup condition switches off, and the update resumes when the condition switches on again.The coil switches on when the progress value is greater than or equal to the set value, and will not turn off until the clear input CL n switches on.The progress value is set in TC n and does not exceed 65,535 (decimal).If the progress value is updated while the system is running, the operation will be performed using the new progress value at that point.If an I/O is set for the set value, the set value can be changed during operation by changing the I/O value, since the set values are updated during each scan. | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">The .01s time base can only be used for timer numbers 0 to 63 (64 points).The .1s and 1s time bases can be used for all timer numbers (0 to 255).A maximum of 256 points can be used for the timers TD, SS, MS, TMR and WDT in total. However, the same area as the counter is used. Timer number and counter number may not be overlapped.While the clear input CL n is on, the turning on of the startup condition is ignored.<u>The progress value is updated when the timer command is expected in the EH-CPU***A/448/516/548.</u> Therefore, if a program that does not scan the timer command execution section after the timer is activated is created using the JMP command or master control (MCS), the timer may not turn on correctly. (The timer does not turn on correctly when the time that does not scan the timer command execution section exceeds the time calculated by multiplying the time base by 65,535.) Note that the previous progress value is also retained until the timer command is executed. | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
|  | | | | | | | | | | | | | | | | | |
| | | LD X00003 OUT TMR13 0.1s 45678 LD TMR13 OUT R103 LD X00004 OUT CL13 | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
|  | | | | | | | | | | | | | | | | | |
| | | LD R7E3 [WR0013=45678] LD X00003 OUT TMR13 0.1s WR0013 LD TMR13 OUT R103 LD X00004 OUT CL13 | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |


Program description

[Time chart]




- 1] The progress value is updated while X00003 is on.
- 2] When X00003 turns off, the update of the progress value is stopped, but the progress value is maintained.
- 3] When X00003 is turned on again, the progress value is re-updated.
- 4] Timer coil TMR13 is turned on while the progress value \geq set value. This state is maintained until the timer clear is turned on.
- 5] When timer clear (CL13) is turned on, the timer coil and progress value are both cleared.
- 6] While timer clear (CL13) is on, the startup condition is ignored.
- 7] The progress value is cleared to 0 when the timer is cleared.


- Example using word I/O as the set value
When RUN is commenced, the set value is set to word I/O.
Or, designate the word I/O for the set value to store in the power failure memory beforehand.
- Timer is cleared by the conditions immediately prior to the execution of the timer coil command.

| Item number | | Basic commands-26 | | | | Name | | | | Watchdog timer | | | | | | | |
|--|--------------|-------------------|---|-----------------|-----------------------------------|------|-------|------------|-----------|----------------------|------------|------------|-----------------|-----------------------|------|--------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
|  | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 27.6 | ← | 32.3 | ← | 14.4 | 15.1 | | |
| OUT WDT n t s1 s2 | | | | Condition | | | Steps | | | | | | | | | | |
| | | | | — | | | 7 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| n | Timer number | | | | | | | | | | | | ○ | 0 to 255 (Decimal) | | | |
| t | Time base | | | | | | | | | | | | | .01s, .1s, 1s | | | |
| s1 | Set value 1 | | | | | ○ | ○ | ○ | | | | | ○ | 1 to 65,535 (Decimal) | | | |
| s2 | Set value 2 | | | | | ○ | ○ | ○ | | | | | ○ | 1 to 65,535 (Decimal) | | | |
| Function | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">Updates the progress value while the startup condition is switched on. The coil will not turn on if the clear input CL n is accessed while set value 1 ≤ progress value < set value 2. The coil switches on if the clear input CL n is accessed while the progress value is less than set value 1 or if set value 2 is less than or equal to the progress value. If the startup condition switches off, everything is cleared.The progress value is set in TC n and does not exceed 65,535 (decimal).If the progress value is updated while the system is running, the operation will be performed using the new progress value at that point.If an I/O is set for the set value, the set value can be changed during operation by changing the I/O value, since the set values are updated during each scan. | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">The .01s time base can only be used for timer numbers 0 to 63 (64 points).The .1s and 1s time bases can be used for all timer numbers (0 to 255).A maximum of 256 points can be used for the timers TD, SS, MS, TMR and WDT in total. However, the same area as the counter is used. Timer number and counter number may not be overlapped.The s1 of the set value must always be less than s2. If s1 is greater than or equal to s2, the coil turns on when the progress value reaches s2.<u>The progress value is updated when the timer command is expected in the EH-CPU***A/448/516/548.</u> Therefore, if a program that does not scan the timer command execution section after the timer is activated is created using the JMP command or master control (MCS), the timer may not turn on correctly. (The timer does not turn on correctly when the time that does not scan the timer command execution section exceeds the time calculated by multiplying the time base by 65,535.) Note that the previous progress value is also retained until the timer command is executed. | | | | | | | | | | | | | | | | | |

Program example




- An example of a word I/O being used as the set value for the ladder shown above.






Program description

[Time chart]




- 1] The progress value is updated while X00004 is on.
- 2] Since watchdog clear (CL14) turned on after the first set value is exceeded and before the second set value is exceeded, it is considered a normal operation, so R104 (WDT14) does not turn on.
- 3] When X00004 turns off, the progress value and WDT coil output are cleared.
- 4] Since the startup condition turned off before the progress value exceeded the first set value, the WDT coil does not turn on, and the progress value is cleared to 0.
- 5] Since the watchdog clear (CL14) turned on before the progress value exceeded the first set value, it is considered an abnormal operation and R104 (WDT14) turns on. The progress value is retained as is.
- 6] Even if the progress value exceeded the second set value, since the watchdog clear (CL14) did not turn on, it is considered an abnormal operation and R104 (SDT14) turns on. The progress value keeps being updated.
- 7] Even if the watchdog clear (CL14) turns on after the WDT coil is turned on after the progress value exceeds the second set value, it is ignored.

- The clear is performed under the conditions set immediately prior to the execution of the WDT coil command.
- Example using word I/O as the set value
When RUN is commenced, the set value is set to word I/O.
Or, designate the word I/O for the set value to store in the power failure memory beforehand.

| Item number | | Basic commands-27 | | | | Name | | Counter | | | | | | | | | |
|---|----------------|-------------------|---|-----------------|---------|-----------------------------------|------|---------|----------------------|-------------|------------|-----|-----------------|-----------------------|--------|------------|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
|  | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | 13.4 | ← | 15.1 | ← | 15.2 | 18.4 | | | |
| OUT CU n s | | | | Condition | | Steps | | | | | | | | | | | |
| | | | | — | | 5 | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | | DR, DL, DM | |
| n | Counter number | | | | | | | | | | | | ○ | 0 to 511 (Decimal) | | | |
| s | Set value | | | | | | ○ | ○ | ○ | | | | ○ | 1 to 65,535 (Decimal) | | | |
| Function | | | | | | | | | | | | | | | | | |
| | | | <ul style="list-style-type: none">• Increments the progress value by 1 each time the rising edge of the startup condition is detected, and switches on the coil when the progress value is greater than or equal to the set value. The coil that is switched on turns off when the counter clear CL n is switched on, and the progress value is cleared to 0.• The progress value is set in TC n and does not exceed 65,535 (decimal).• If the progress value is updated while the system is running, the operation will be performed using the new progress value at that point.• If an I/O is set for the set value, the set value can be changed during operation by changing the I/O value, since the set values are updated during each scan. | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| | | | <ul style="list-style-type: none">• The counter can be used up to 512 points (No. 0 to 511). However, the first 256 points (No. 0 to 255) will use the same area as the timer.• The timer numbers and counter numbers can not overlap.• While the counter clear CL n is on, the rise of startup condition is ignored.• Since the startup condition of the counter is edge detection, the condition can not be detected during the first scan after the operation is started.• If the set value is set to 0, it is regarded as a coil that is always on and controlled by the CL n. | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
|  | | | | | | | | | | | | | | | | | |
| | | | LD X00005 | | | | | | | | | | | | | | |
| | | | OUT CU15 4 | | | | | | | | | | | | | | |
| | | | LD X00006 | | | | | | | | | | | | | | |
| | | | OUT CL15 | | | | | | | | | | | | | | |
|  | | | | | | | | | | | | | | | | | |
| | | | LD R7E3 | | | | | | | | | | | | | | |
| | | | [WR0015=4] | | | | | | | | | | | | | | |
| | | | LD X00005 | | | | | | | | | | | | | | |
| | | | OUT CU15 WR0015 | | | | | | | | | | | | | | |
| | | | <ul style="list-style-type: none">• An example of a word I/O being used as the set value for the ladder shown above. | | | | | | | | | | | | | | |

Program description

[Time chart]






- 1] The progress value (count) is cleared to 0 by the counter clear (CL15). While the counter clear is on, the progress value will not be updated.
- 2] The progress value is updated at the rising edge of X00005.
- 3] Counter coil (CU15) is turned on since set value \geq progress value.
- 4] The count value will not exceed 65,535 (decimal).
- 5] The progress value and counter coil are cleared by counter clear (CL15).
 - The clear is performed under the conditions set immediately prior to the execution of the counter coil command.

- Example using word I/O as the set value


When RUN is commenced, the set value is set to word I/O.

Or, designate the word I/O for the set value to store in the power failure memory beforehand.

| Item number | | Basic commands-28 | | | | Name | | Ring counter | | | | | | | | | |
|---|----------------|-------------------|--|---|------|---------|-----------------------------------|--------------|-----------|----------------------|------------|-------------|-----------------|----------|--------------------|-----------------------|------------|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
|  | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 13.4 | ← | 15.1 | ← | 14.3 | 16.9 | | |
| OUT RCU n s | | | | Condition | | | Steps | | | | | | | | | | |
| | | | | — | | | 5 | | | | | | | | | | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | Constant | Other | | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | | DR, DL, DM |
| n | Counter number | | | | | | | | | | | | | ○ | 0 to 511 (Decimal) | | |
| s | Set value | | | | | | | ○ | ○ | ○ | | | | | ○ | 1 to 65,535 (Decimal) | |
| Function | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">• Increments the progress value by 1 each time the rising edge of the startup condition is detected, and clears the progress value to 0 when the progress value is greater than or equal to the set value. The progress value becomes 0 when the counter clear CL n is switched on, and the coil switches off.• The progress value is set in TC n and does not exceed the set value.• If the progress value is updated while the system is running, the operation will be performed using the new progress value at that point.• If an I/O is set for the set value, the set value can be changed during operation by changing the I/O value, since the set values are updated during each scan. | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">• The counter can be used up to 512 points (No. 0 to 511). However, the first 256 points (No. 0 to 255) will use the same area as the timer.• The timer numbers and counter numbers can not overlap.• While the counter clear CL n is on, the rise of startup condition is ignored.• Since the startup condition of the counter is edge detection, the condition can not be detected during the first scan after the operation is started.• If the set value is set to 0, it is regarded as a coil that is always on and controlled by the CL n. | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| | | | | <div><pre>LD X00006 OUT RCU16 3 LD X00007 OUT CL16 LD RCU16 OUT R106</pre></div> <ul style="list-style-type: none">• An example of a word I/O being used as the set value for the ladder shown above. <div><pre>LD R7E3 [WR0016=3] LD X00006 OUT RCU16 WR0016 LD X00007 OUT CL16 LD RCU16 OUT R106</pre></div> | | | | | | | | | | | | | |

Program description

[Time chart]




- 1] The progress value (count) is updated at the X00006 rising edge.
 - 2] When set value = progress value, the counter coil (RCU16) turns on for one scan and the progress value is cleared.
 - 3] When counter clear (CL16) is turned on, the progress value is cleared. The progress value is not updated while the counter clear is on.
- The clear is performed under the conditions set immediately prior to the execution of the counter coil command.

- Example using word I/O as the set value
When RUN is commenced, the set value is set to word I/O.
Or, designate the word I/O for the set value to store in the power failure memory beforehand.


| Item number | | Basic commands-29, 30 | | | | Name | | Up (CTU n) and down (CTD n) of up/down counter | | | | | | | | | |
|---|----------------|-----------------------|--|-----------------|------|---------|-----------------------------------|--|-----------|----------------------|------------|-------------|-----------------|------------|------------------------------------|-----------------------|-------|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| <div>CTU n s</div> <div>CTD n</div> | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: CTU Lower case: CTD | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 13.4 | ← | 15.1 | ← | 12.5 | | 13.1 | |
| OUT CTU n s | | | | Condition | | | Steps | | | 12.2 | ← | 9.4 | ← | 11.6 | | 11.7 | |
| OUT CTD n | | | | CTU | | | 5 | | | | | 14.1 | | | | | |
| | | | | CTD | | | 3 | | | | | 8.9 | | | | | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | | | Constant | Other |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| n | Counter number | | | | | | | | | | | | | ○ | 0 to 511 (Decimal) | | |
| s | Set value | | | | | | | ○ | ○ | ○ | | | | | ○ | 1 to 65,535 (Decimal) | |
| Function | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">For the UP counter, increments the progress value by 1 each time the rising edge of the startup condition is detected, while it decrements the progress value by 1 for the DOWN counter. The coil switches on when the progress value is greater than or equal to the set value and switches off when the progress value is less than the set value. When the counter clear CL n switches on, the progress value is cleared to 0 and the coil switches off.The progress value is set in TC n, and the value will be in the range of 0 to 65,535 (decimal).If the progress value is updated while the system is running, the operation will be performed using the new progress value at that point.If an I/O is set for the set value, the set value can be changed during operation by changing the I/O value, since the set values are updated during each scan. | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">The counter can be used up to 512 points (No. 0 to 511). However, the first 256 points (No. 0 to 255) will use the same area as the timer.The timer numbers and counter numbers cannot overlap.The numbers for the UP coil and DOWN coil must be the same.While the counter clear CL n is on, the rise of startup condition is ignored.Since the startup condition of the counter is edge detection, the condition may not be detected during the first scan after the operation is started.If the set value is set to 0, it is regarded as a coil that is always on and controlled by the CL n. | | | | | | | | | | | | | | | | | |

OUT CTU n s
OUT CTD n

Program example




- An example of a word I/O being used as the set value for the ladder shown above.



Program description

[Time chart]




- 1] The progress value is up-counted at the rising edge of X00007.
- 2] The counter coil (CT17) is turned on when set value \geq progress value.
- 3] When the up-coil and down-coil startup conditions turn on simultaneously, the progress value does not change.
- 4] The progress value is down-counted at the rising edge of X00008.
- 5] The counter coil turns off when set value $>$ progress value.

- 6] The progress value will never exceed 65,535 (decimal). Also, it will not be below 0.
- 7] When counter clear (CL17) turns on, the progress value and the counter coil are cleared. The progress value is not updated while the counter clear is on.

- The clear is performed under the conditions set immediately prior to the execution of the counter coil command.
- Example using word I/O as the set value

When RUN is commenced, the set value is set to word I/O.

Or, designate the word I/O for the set value to store in the power failure memory beforehand.

| Item number | | Basic commands-31 | | | | Name | | | | Counter clear | | | | | | | | | | | | | |
|---|----------------|-------------------|--|---|------|---------|-----------------------------------|------|-----------|----------------------|------------|-------------|-----------------|----------|--------------------|------------|--|--------|------|--------|------|--------|------|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | | | |
|  | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | |
| Command format | | | | Number of steps | | | | | | 0.1 | ← | 0.1 | ← | 1.0 | | 1.7 | | | | | | | |
| OUT CL n s | | | | Condition | | | Steps | | | | | | | | | | | | | | | | |
| | | | | — | | | 1 | | | | | | | | | | | | | | | | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | Constant | Other | | | | | | | | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | | | | | |
| n | Counter number | | | | | | | | | | | | | ○ | 0 to 511 (Decimal) | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | <div><ul style="list-style-type: none">Clears the TD, SS and MS progress values of the integral timer and switches off the timer coil.In the case of WDT, a time monitor check is performed (see WDT for details).In the case of counters, the progress value is cleared and the counter coil is switched off.The clearing operation is conducted immediately before the counter or timer indicated by the clear coil executes the coil command.</div> <div><div>Example</div><div><table><tr><td>X00000</td><td>CL10</td></tr><tr><td>X00001</td><td>CU10</td></tr><tr><td>X00002</td><td>CL10</td></tr></table><div><div>1) When X00000 is turned on, the CL10 immediately prior to CU10 turns on, and CU10 is cleared.</div><div>2) Even if X00002 turns on, if X00001 is off, the CL10 is turned off by the ladder before CU10 is executed. Therefore, the CU10 will not be cleared.</div></div></div></div> | | | | | | | | | | | | | | X00000 | CL10 | X00001 | CU10 | X00002 | CL10 |
| X00000 | CL10 | | | | | | | | | | | | | | | | | | | | | | |
| X00001 | CU10 | | | | | | | | | | | | | | | | | | | | | | |
| X00002 | CL10 | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | <div><ul style="list-style-type: none">The number same as on the timer or counter must be used.</div> | | | | | | | | | | | | | | | | | | | |

LD (s1 == s2)
AND (s1 == s2)
OR (s1 == s2)

| Item number | | Basic commands-32 | | | | Name | | =Relational box | | | | | | | | | |
|-----------------------|---------------------|--|-----|-----------------|---------|-----------------------------------|------|------------------|----------------------|----------------|--------------|-------|-----------------|----------|---|--|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| (See Function column) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW () indicates the case of OR | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | 0.5 (7.5) | ← (←) | 23.5 51.1 | 91.9 | 76.7 | 185.6 | | | |
| LD (s1 == s2) | | | | Condition | | Steps | | | 15.8 (22.8) | 18.4 (25.4) | 26.5 71.3 | 123.5 | 100.2 | 130.1 | | | |
| AND (s1 == s2) | | | | Word | | (See Cautionary notes) | | | | | | | | | | | |
| OR (s1 == s2) | | | | Double word | | (See Cautionary notes) | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | |
| s1 | Relational number 1 | | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | |
| s2 | Relational number 2 | | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | |
| Function | | | | | | | | | | | | | | | | | |
| [Ladder format] | | <div><div><div></div><div>s1</div><div>==</div><div>s2</div></div><div></div><div><div></div><div>s1</div><div>==</div><div>s2</div></div><div></div><div><div></div><div>s1</div><div>==</div><div>s2</div></div><div></div></div> | | | | | | | | | | | | | | | |
| | | <div><div><div>•</div><div>Compares s1 and s2 as unsigned numbers, and if s1 is equals to s2, it enters the continuity status (on) and if s1 is not equal to s2, enters the noncontinuity status (off).</div></div><div><div><div>•</div><div>When s1 and s2 are words : 0 to 65,535 (decimal) or H0000 to HFFFF (hexadecimal) When s1 and s2 are double words : 0 to 4,294,967,295 (decimal) or H00000000 to HFFFFFFF (hexadecimal)</div></div></div></div> | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| [Number of steps] | | | | | | | | | | | | | | | | | |
| | | Word | | | | Double word | | LD, AND (s1==s2) | | OR (s1==s2) | | | | | | | |
| | | LD (s1 == s2) | | 5 steps | | I/O I/O | | 5 steps | | 6 steps | | | | | | | |
| | | AND (s1 == s2) | | 5 steps | | I/O Constant | | 6 steps | | 7 steps | | | | | | | |
| | | OR (s1 == s2) | | 6 steps | | Constant I/O | | 6 steps | | 7 steps | | | | | | | |
| | | | | | | Constant Constant | | 7 steps | | 8 steps | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| | | <div><div><div></div><div>WR0000</div><div>==</div><div>WR0002</div></div><div></div></div> | | R001 | | LD (WR0000 == WR0002) OUT R001 | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| | | <div><div><div>•</div><div>When WR0000 = WR0002, R001 turns on.</div></div></div> | | | | | | | | | | | | | | | |

LD (s1 S== s2)
AND (s1 S== s2)
OR (s1 S== s2)

| Item number | Basic commands-33 | | | | Name | Signed = Relational box | | | | | | | | | |
|-----------------------|---------------------|--|--|------|------------------------|-----------------------------------|------|----------------------|------------|-------------|-------|-----------------|----------|--------|------------|
| Ladder format | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| (See Function column) | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | |
| | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | |
| | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | | Number of steps | | | | | 18.4 | 25.4 | 26.5 | ← | 76.7 | 130.1 | | |
| LD | (s1 S== s2) | | Condition | | Steps | | | | | | | | | | |
| AND | (s1 S== s2) | | Double word | | (See Cautionary notes) | | | | | | | | | | |
| OR | (s1 S== s2) | | | | | | | | | 71.3 | 123.5 | | | | |
| Usable I/O | | | Bit | | | Word | | | | Double word | | | Constant | Other | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM |
| s1 | Relational number 1 | | | | | | | | | ○ | ○ | ○ | ○ | | |
| s2 | Relational number 2 | | | | | | | | | ○ | ○ | ○ | ○ | | |
| Function | | | | | | | | | | | | | | | |
| [Ladder format] | | | <div><div><div></div><div>s1</div><div>S==</div><div>s2</div></div><div></div><div><div></div><div>s1</div><div>S==</div><div>s2</div></div><div></div><div><div></div><div>s1</div><div>S==</div><div>s2</div></div><div></div></div> <div><div><div></div><div>b31</div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></</div></div> | | | | | | | | | | | | |

LD (s1 <> s2)
AND (s1 <> s2)
OR (s1 <> s2)

| Item number | | Basic commands-34 | | | | Name | | < > Relational box | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-----------------------|---------------------|-------------------|---|-----------------|---------|-----------------------------------|------|--------------------|----------------------|----------------|-----------------|---------|-----------------|---------|---|--|--|--|--|--|--|--|--|-------------|------------------|-------------|---------|---------|---------|--------------|---------|---------|--------------|---------|---------|-------------------|---------|---------|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | | | | | | | | | | | | |
| (See Function column) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW () indicates the case of OR | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | 0.5 (7.5) | ← (←) | 23.5 50.9 | | 91.9 | 100.3 | 185.7 | | | | | | | | | | | | | | | | | | | | | | | |
| LD (s1 < > s2) | | | | Condition | | Steps | | | 15.8 (22.8) | 18.4 (25.4) | 27.85 | | 78.7 | 133.9 | | | | | | | | | | | | | | | | | | | | | | | | |
| AND (s1 < > s2) | | | | Word | | (See Cautionary notes) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| OR (s1 < > s2) | | | | Double word | | (See Cautionary notes) | | | | | 72.3 | 124.3 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | | | | | | | | | | | | | | | | | | | | | |
| s1 | Relational number 1 | | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | | | | | | | | | | | | | | | |
| s2 | Relational number 2 | | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| [Ladder format] | | | <div></div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | <ul style="list-style-type: none">Compares s1 and s2 as unsigned numbers, and if s1 is equals to s2, it enters the noncontinuity status (off) and if s1 is not equal to s2, enters the continuity status (on).When s1 and s2 are words : 0 to 65,535 (decimal) or H0000 to HFFFF (hexadecimal) When s1 and s2 are double words : 0 to 4,294,967,295 (decimal) or H00000000 to HFFFFFFF (hexadecimal) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| [Number of steps] | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | <table><tr><th>Word</th><th></th></tr><tr><td>LD (s1 < > s2)</td><td>5 steps</td></tr><tr><td>AND (s1 < > s2)</td><td>5 steps</td></tr><tr><td>OR (s1 < > s2)</td><td>6 steps</td></tr></table> | | | | Word | | LD (s1 < > s2) | 5 steps | AND (s1 < > s2) | 5 steps | OR (s1 < > s2) | 6 steps | <table><tr><th>Double word</th><th>LD, AND (s1<>s2)</th><th>OR (s1<>s2)</th></tr><tr><td>I/O I/O</td><td>5 steps</td><td>6 steps</td></tr><tr><td>I/O Constant</td><td>6 steps</td><td>7 steps</td></tr><tr><td>Constant I/O</td><td>6 steps</td><td>7 steps</td></tr><tr><td>Constant Constant</td><td>7 steps</td><td>8 steps</td></tr></table> | | | | | | | | | Double word | LD, AND (s1<>s2) | OR (s1<>s2) | I/O I/O | 5 steps | 6 steps | I/O Constant | 6 steps | 7 steps | Constant I/O | 6 steps | 7 steps | Constant Constant | 7 steps | 8 steps |
| Word | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| LD (s1 < > s2) | 5 steps | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| AND (s1 < > s2) | 5 steps | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| OR (s1 < > s2) | 6 steps | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Double word | LD, AND (s1<>s2) | OR (s1<>s2) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| I/O I/O | 5 steps | 6 steps | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| I/O Constant | 6 steps | 7 steps | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Constant I/O | 6 steps | 7 steps | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Constant Constant | 7 steps | 8 steps | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div></div> | | | LD (WR0000 < > WR0002) OUT R003 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | <ul style="list-style-type: none">When WR0000 ≠ WR0002, R003 turns on. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| Item number | | Basic commands-35 | | | | Name | | Signed \diamond Relational box | | | | | | | |
|---|---------------------|----------------------|--|--|------|------------------------|-----------------------------------|----------------------------------|----------------------------|-------------|------------|-----|-----------------|-------|----|
| Ladder format | | | | Condition code | | | | | Processing time (μ s) | | | | Remark | | |
| (See Function column) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | |
| Command format | | | | Number of steps | | | | | 18.4 | 25.4 | 27.8 | ← | 78.7 | 133.9 | |
| LD | | (s1 S \diamond s2) | | Condition | | Steps | | | | | | | | | |
| AND | | (s1 S \diamond s2) | | Double word | | (See Cautionary notes) | | | | | | | | | |
| OR | | (s1 S \diamond s2) | | | | | | | | | | | | | |
| Usable I/O | | | | Bit | | | Word | | | Double word | | | Constant | Other | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | | | DY |
| s1 | Relational number 1 | | | | | | | | | | ○ | ○ | ○ | ○ | |
| s2 | Relational number 2 | | | | | | | | | | ○ | ○ | ○ | ○ | |
| Function | | | | | | | | | | | | | | | |
| [Ladder format] | | | | <div><div><div><div></div><div>s1</div><div>S\diamond</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div>S\diamond</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div>S\diamond</div><div>s2</div></div><div></div></div></div> | | | | | | | | | | | |
| <div><div><div>• Compares s1 and s2 as signed double-word numbers, and if s1 is equals to s2, it enters the noncontinuity status (off) and if s1 is not equal to s2, enters the continuity status (on).</div><div><div>• s1, s2</div><div>– 2,147,483,648 to + 2,147,483,647 (decimal)</div><div>H80000000 to H7FFFFFFF (hexadecimal)</div></div></div></div> | | | | <div><div><div>b31</div><div></div><div>b0</div></div><div><div>— Sign bit: 0 - Positive; 1 - Negative</div></div></div> | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | |
| [Number of steps] | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| </ | | | | | | | | | | | | | | | |

LD (s1 S<> s2)
AND (s1 S<> s2)
OR (s1 S<> s2)

LD (s1 < s2)
AND (s1 < s2)
OR (s1 < s2)

| Item number | | Basic commands-36 | | | | Name | | <Relational box | | | | | | | | | |
|---|---------------------|-------------------|---|-----------------|---------|-----------------------------------|------|-----------------|----------------------|----------------|-------------|-------|-----------------|----------|---|--|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| (See Function column) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW () indicates the case of OR | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format LD (s1 < s2) AND (s1 < s2) OR (s1 < s2) | | | | Number of steps | | | | | 0.5 (7.5) | | 23.5 | | 100.3 | 185.7 | | | |
| | | | | Condition | | Steps | | | | | | | | | | | |
| | | | | Word | | (See Cautionary notes) | | | 16.5 (23.5) | 19.4 (26.4) | 28.8 | | | | | | |
| | | | | Double word | | (See Cautionary notes) | | | | | 74.0 | 126.7 | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | |
| s1 | Relational number 1 | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | |
| s2 | Relational number 2 | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | |
| Function | | | | | | | | | | | | | | | | | |
| [Ladder format] | | | <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> | | | | | | | | | | | | | | |
| | | | <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div><div><div><div></div><div>s1</div><div><</div><div>s2</div></div><div></div></div></div> <div><</div> | | | | | | | | | | | | | | |

5-59

LD (s1 <= s2)
AND (s1 <= s2)
OR (s1 <= s2)

| Item number | | Basic commands-38 | | | | Name | | ≤ Relational box | | | | | | | | | |
|-----------------------|---------------------|---|-----------|-----------------|---------|-----------------------------------|----------|------------------|----------------------|------------|-------------|-------|-----------------|-------|---|------------|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| (See Function column) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW () indicates the case of OR | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | 0.5 | ← | 23.5 | | 100.2 | 185.6 | | | |
| LD | (s1 ≤ s2) | | | Condition | | Steps | | | (7.5) | (←) | 50.9 | 91.9 | | | | | |
| AND | (s1 ≤ s2) | | | Word | | (See Cautionary notes) | | | 16.5 | 19.4 | 28.85 | | | | | | |
| OR | (s1 ≤ s2) | | | Double word | | (See Cautionary notes) | | | (23.5) | (26.4) | 74.0 | 126.7 | | | 80.7 | 136.4 | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | Constant | Other | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | | DR, DL, DM | |
| s1 | Relational number 1 | | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | |
| s2 | Relational number 2 | | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | |
| Function | | | | | | | | | | | | | | | | | |
| [Ladder format] | | | | | | | | | | | | | | | | | |
| • | | Compares s1 and s2 as unsigned numbers, and if s1 is less than or equal to s2, it enters the continuity status (on) and if s1 is greater than s2, it enters the noncontinuity status (off). | | | | | | | | | | | | | | | |
| • | | When s1 and s2 are words : 0 to 65,535 (decimal) or H0000 to HFFFF (hexadecimal) When s1 and s2 are double words : 0 to 4,294,967,295 (decimal) or H00000000 to HFFFFFFF (hexadecimal) | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| [Number of steps] | | | | | | | | | | | | | | | | | |
| | | Word | | | | Double word | | LD, AND (s1≤s2) | | OR (s1≤s2) | | | | | | | |
| | | LD | (s1 ≤ s2) | 5 steps | | I/O | I/O | 5 steps | | 6 steps | | | | | | | |
| | | AND | (s1 ≤ s2) | 5 steps | | I/O | Constant | 6 steps | | 7 steps | | | | | | | |
| | | OR | (s1 ≤ s2) | 6 steps | | Constant | I/O | 6 steps | | 7 steps | | | | | | | |
| | | | | | | Constant | Constant | 7 steps | | 8 steps | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| | | LD (WR0000 ≤ WR0002) OUT R007 | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| • | | When WR0000 ≤ WR0002, R007 turns on. | | | | | | | | | | | | | | | |

| Item number | Basic commands-39 | | | | Name | | Signed ≤ Relational box | | | | | | | | | |
|--|---------------------|-------------|---|------------------------|------------------|-----------------------------------|-------------------------|----------------------|------------|-------------|-----|-----------------|----------|--------|------------|--|
| Ladder format | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| (See Function column) | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | Number of steps | | | | | 19.4 | 26.4 | 28.8 | ← | 81.3 | 137.4 | | | |
| LD | (s1 S≤ s2) | Condition | | Steps | | | | | | | | | | | | |
| AND | (s1 S≤ s2) | Double word | | (See Cautionary notes) | | | | | | | | | | | | |
| OR | (s1 S≤ s2) | | | | | | | | | | | | | | | |
| Usable I/O | | | Bit | | | Word | | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | |
| s1 | Relational number 1 | | | | | | | | | | ○ | ○ | ○ | ○ | | |
| s2 | Relational number 2 | | | | | | | | | | ○ | ○ | ○ | ○ | | |
| Function | | | | | | | | | | | | | | | | |
| [Ladder format] | | | <div><div><div></div><div>s1</div><div>S≤</div><div>s2</div></div><div></div><div><div></div><div>s1</div><div>S≤</div><div>s2</div></div><div></div><div><div></div><div>s1</div><div>S≤</div><div>s2</div></div><div></div></div> | | | | | | | | | | | | | |
| <div><div><div>• Compares s1 and s2 as signed double-word numbers, and if s1 is less than or equal to s2, it enters the continuity status (on) and if s1 is greater than s2, it enters the noncontinuity status (off).</div><div>• s1, s2 – 2,147,483,648 to + 2,147,483,647 (decimal) H80000000 to H7FFFFFFF (hexadecimal)</div></div></div> | | | <div><div><div>b31</div><div></div><div>b0</div></div><div>Sign bit: 0 - Positive; 1 - Negative</div></div> | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | |
| [Number of steps] | | | | | | | | | | | | | | | | |
| | | | Double word | | LD, AND (s1S≤s2) | | | OR (s1S≤s2) | | | | | | | | |
| | | | I/O | I/O | 5 steps | | | 6 steps | | | | | | | | |
| | | | I/O | Constant | 6 steps | | | 7 steps | | | | | | | | |
| | | | Constant | I/O | 6 steps | | | 7 steps | | | | | | | | |
| | | | Constant | Constant | 7 steps | | | 8 steps | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | |
| <div><div><div><div></div><div>DR0000</div><div>S ≤</div><div>DR0002</div></div><div></div><div><div></div><div>R008</div></div></div><div>LD (DR0000 S≤ DR0002) OUT R008</div></div> | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | |
| <div><div><div>• When DR0000 ≤ DR0002, R008 turns on (signed).</div></div></div> | | | | | | | | | | | | | | | | |


| Item number | | Arithmetic commands-1 | | | | Name | | Substitution statement | | | | | | | | | | | | | | | |
|--|--------------------------|-----------------------|----------------------------------|------------------------|-----------------------------------|------|-------|------------------------|-----------------------|----------------------|-------------|------------|-----------------|-------|--|--------|--|--|--|--|--|--|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | | | |
| d = s | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | |
| Command format | | | | Number of steps | | | | | | See following table | | | | | | | | | | | | | |
| d = s | | | | Condition | | | Steps | | | | | | | | | | | | | | | | |
| | | | | (See Cautionary notes) | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | | |
| d | Substitution destination | | | ○ | ○ | | | ○ | ○ | ○ | | ○ | ○ | | | | | | | | | | |
| s | Substitution source | | ○ | ○ | ○ | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | |
| () | Index value | | | | | | ○ | ○ | ○ | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div>• Substitutes the content of s into d.</div><div>• It is possible to use array variables for d and s.</div><div>• When d is a word, the constant is 0 to 65,535 or – 32,768 to + 32,767 (decimal) H0000 to HFFFF or H8000 to H7FFF (hexadecimal)</div></div><div><div>When d is a double word, the constant is 0 to 4,294,967,295 or –2,147,483,648 to +2,147,483,647 (decimal) H00000000 to HFFFFFFF or H80000000 to H7FFFFFFF</div></div></div> | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div>• When using an array variable, DER is set to 1 if the maximum usable I/O number is exceeded, and DER is reset to “0” if it is normal.</div><div>• The combinations of d and s are as follows:</div></div><div><table><tr><td>d</td><td>s</td></tr><tr><td>Bit</td><td>Bit</td></tr><tr><td>Word</td><td>Word</td></tr><tr><td>Double word</td><td>Double word</td></tr></table></div></div> | | | d | s | Bit | Bit | Word | Word | Double word | Double word | | | | | | | | | | | | | |
| | | | d | s | | | | | | | | | | | | | | | | | | | |
| Bit | Bit | | | | | | | | | | | | | | | | | | | | | | |
| Word | Word | | | | | | | | | | | | | | | | | | | | | | |
| Double word | Double word | | | | | | | | | | | | | | | | | | | | | | |
| <div><div>• Step numbers and processing time are as follows:</div></div> | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | |
| Model name | d | s | Number of steps () indicates DW | | | | | | Processing time (μ s) | | | | | | | | | | | | | | |
| EH-CPU448 | I/O | I/O | 3 (4) | | | | | | Bit | Word | Double word | | | | | | | | | | | | |
| | I/O | Array | 4 | | | | | | 0.3 | 0.3 | 15 | | | | | | | | | | | | |
| | Array | I/O | 4 (5) | | | | | | 31 | 27 | 29 | | | | | | | | | | | | |
| | Array | Array | 5 | | | | | | 27 | 25 | 27 | | | | | | | | | | | | |
| Upper case: EH-CPU***A Lower case: EH-CPU3** | I/O | I/O | 3 (4) | | | | | | 43 | 39 | 42 | | | | | | | | | | | | |
| | I/O | I/O | 4 | | | | | | 15.6 | 14.6 | 19.9 | | | | | | | | | | | | |
| | | | | | | | | | 32 | 49 | 69 | | | | | | | | | | | | |
| | I/O | Array | 4 (5) | | | | | | 31.9 | 29.9 | 36.55 | | | | | | | | | | | | |
| | | | | | | | | | 71 | 104 | 144 | | | | | | | | | | | | |
| | Array | I/O | 5 | | | | | | 27.9 | 26.9 | 32.55 | | | | | | | | | | | | |
| | | | | | | | | | 51 | 68 | 92 | | | | | | | | | | | | |
| | Array | Array | 5 | | | | | | 40.05 | 37.9 | 46.55 | | | | | | | | | | | | |
| 86 | | | | | | | | | 119 | 165 | | | | | | | | | | | | | |
| Other than the above | I/O | I/O | 3 (4) | | | | | | 71 | 84 | 69 | | | | | | | | | | | | |
| | I/O | Array | 4 | | | | | | 172 | 250 | 173 | | | | | | | | | | | | |
| | Array | I/O | 4 (5) | | | | | | 101 | 182 | 125 | | | | | | | | | | | | |
| | Arrav | Arrav | 5 | | | | | | 246 | 301 | 225 | | | | | | | | | | | | |

How to use Array variables


An array variable specifies I/O numbers by adding a constant or word I/O (WR, WM and WL) as an index to I/O (R, M, L, WR, WM, WL, TC, DR, DM, DL). Array variables can be used only for commands expressed by substitution formulas.

(1) Expression of array variables

An array variable is expressed by the form $\square a(b)$. $\square a$ is called "I/O of an array variable", and "b" in the parentheses is called "contents of index". When "b" is a constant, " $\square a(b)$ " means " $\square a + b$ ".



(2) Example




(3) Note

An array variables can be used only by the substitution formulas. The way of using it shown in the following can't be done.

$WR10(WR20) = WR100 + 1$
 $R0 = WR10(WR20) < WR30$

Program example



I/O assignment

| | | 0 | 1 | 2 |
|-----|---|----|----|---|
| CPU | X | Y | X | |
| 16 | | 16 | 16 | |
| AVR | | | | |

Program description

- The value of WX0000 is substituted into WR0000 at the rising edge of input X00000.
- The value of WX0000 is substituted into the WR number designated by WR0000 + WM000 at the rising edge of input X00001.
 - When WM000 = H0010, it holds the same meaning as WR0010 = WX0000.
- The word number of the I/O advanced by the amount designated by WR0000 + WM001 due to the I/O assignment is substituted into WR0000 at the rising edge of input X00002.
 - When WM001 = H0010, it holds the same meaning as WR0000 = WR0010.
- The I/O value designated by WR0000 + WM001 at the rising edge of input X00003 is substituted into the I/O of the value designated by WR0000 + WM000.
 Example) When WM000 = H0010 and WM001 = H0015, it holds the same meaning as WR0010 = WR0015.

| Item number | | Arithmetic commands-2 | | | | Name | | Binary addition | | | | | | | | | |
|---|--------------------------|-----------------------|---|-----------------|-----------------------------------|------|-------|-----------------|-----------|----------------------|------------|------------|-----------------|-------|---|---------------------------------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| d = s1 + s2 | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ↑ | ↑ | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 0.4 | ← | 20 | ← | 123 | ← | Upper case: W Lower case: DW | |
| d = s1 + s2 | | | | Condition | | | Steps | | | | | 56 | ← | | | | |
| | | | | Word | | | 4 | | | | | 31 | ← | | | | |
| | | | | Double word | | | 6 | | | | | 80 | ← | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| d | Substitution destination | | | | | | ○ | ○ | ○ | | ○ | ○ | | | | | |
| s1 | Augend | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | |
| s2 | Addend | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div><div></div></div> <div><div></div></div> | | | | | | | | | | | | | | | | | |

| Item number | | Arithmetic commands-3 | | | | Name | | BCD addition | | | | | | | | | | | | | | | | |
|---------------------|--------------------------|-----------------------|---|-----------------|-----------------------------------|------|-------|--------------|-----------|----------------------|------------|------------|-----------------|-------|---------------------------------|--------|----|----|------|------|------|-------------|-------------|-------------|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | |
| d = s1 B+ s2 | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | |
| | | | | ↑ | ● | ● | ● | ↑ | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | | 36 | ← | 41 | ← | 193 | ← | | | | | | | | | |
| d = s1 B+ s2 | | | | Condition | | | Steps | | | | | 82 | ← | | | | | | | | | | | |
| | | | | Word | | | 4 | | | 59 | ← | 69 | ← | 246 | ← | | | | | | | | | |
| | | | | Double word | | | 6 | | | | | 129 | ← | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | | | |
| d | Substitution destination | | | | | | | ○ | ○ | ○ | | ○ | ○ | | | | | | | | | | | |
| s1 | Augend | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | | |
| s2 | Addend | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | <ul style="list-style-type: none">Adds s1 and s2 as BCD data, and stores the result in d as BCD data.The C flag is 1 if there is a digit increase, and 0 if not.The DER flag is 1 if the operation result s1 and s2 are invalid BCD data. In such cases, operation is not performed and the C flag retains the previous state without outputting to d. If the s1 and s2 are valid BCD data, the DER is set to 0.When s1, s2 are words : 0000 to 9999 (BCD)When s1, s2 are double words : 00000000 to 99999999 (BCD) | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | <ul style="list-style-type: none">The combinations of d, s1 and s2 are as follows. <table><tr><td>d</td><td>s1</td><td>s2</td></tr><tr><td>Word</td><td>Word</td><td>Word</td></tr><tr><td>Double word</td><td>Double word</td><td>Double word</td></tr></table> | | | | | | | | | | | | | d | s1 | s2 | Word | Word | Word | Double word | Double word | Double word |
| d | s1 | s2 | | | | | | | | | | | | | | | | | | | | | | |
| Word | Word | Word | | | | | | | | | | | | | | | | | | | | | | |
| Double word | Double word | Double word | | | | | | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | <div><div><div>X00000</div><div>DIF0</div></div><div>WL002 = WL000 B+ WL001</div></div> <div>LD X00000 AND DIF0 [WL002 = WL000 B+ WL001]</div> | | | | | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | <ul style="list-style-type: none">The sum of the values of WL000 and WL001 is substituted into WL002 as BCD data at the rising edge of input X00000. | | | | | | | | | | | | | | | | | | | | | |

d = s1 - s2

| Item number | | Arithmetic commands-4 | | | | Name | | Binary subtraction | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--------------------------|-----------------------|---|-----------------|-----------------------------------|------|-------|--------------------|----------------------|-------------|------------|------------|-----------------|-------|---------------------------------|----|----|----|------|----------|----------|-------------------|-------------|-------------|----------|-------------------|---|----------|----------|----------|---|----------|----------|----------|---|----------|----------|----------|---|----------|----------|----------|---|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| d = s1 - s2 | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | ● | ● | ● | ↑ | ↓ | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | 0.4 | ← | 20 | ← | 121 | ← | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| d = s1 - s2 | | | | Condition | | | Steps | | 20 | ← | 54 | ← | 96 | ← | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | Word | | | 4 | | | | 31 | ← | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | Double word | | | 6 | | 80 | ← | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| d | Substitution destination | | | | | | | ○ | ○ | ○ | | ○ | ○ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s1 | Minuend | | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s2 | Subtrahend | | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div>• Subtracts s2 from s1 as binary data, and substitutes the result into d as binary data.</div><div>• The C flag is 1 if there is a digit decrease, and 0 if not. C = $\overline{s1m} \cdot s2m + s1m \cdot dm + s2m \cdot dm$</div><div>• The V flag is 1 if the operation result is a meaningless signed-binary data, and 0 if it has meaning.</div></div><div><table><tr><th>s1</th><th>s2</th><th>d</th><th>V</th></tr><tr><td>Positive</td><td>Positive</td><td>Positive/Negative</td><td>0</td></tr><tr><td>Negative</td><td>Negative</td><td>Positive/Negative</td><td>0</td></tr><tr><td>Positive</td><td>Negative</td><td>Positive</td><td>0</td></tr><tr><td>Positive</td><td>Negative</td><td>Negative</td><td>1</td></tr><tr><td>Negative</td><td>Positive</td><td>Positive</td><td>1</td></tr><tr><td>Negative</td><td>Positive</td><td>Negative</td><td>0</td></tr></table><div><div><div><div><div></div><div>Most significant bit</div></div><div><div>s1m</div><div></div><div>0</div></div><div>s1</div></div><div><div>-</div><div><div>s2m</div><div></div><div>0</div></div><div>s2</div></div><div><div>C</div><div><div>dm</div><div></div><div>0</div></div><div>d</div></div></div><div>$V = \overline{s1m} \cdot s2m \cdot dm + s1m \cdot \overline{s2m} \cdot \overline{dm}$</div></div></div></div> | | | | | | | | | | | | | | | | s1 | s2 | d | V | Positive | Positive | Positive/Negative | 0 | Negative | Negative | Positive/Negative | 0 | Positive | Negative | Positive | 0 | Positive | Negative | Negative | 1 | Negative | Positive | Positive | 1 | Negative | Positive | Negative | 0 |
| s1 | s2 | d | V | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Positive | Positive | Positive/Negative | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Negative | Negative | Positive/Negative | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Positive | Negative | Positive | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Positive | Negative | Negative | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Negative | Positive | Positive | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Negative | Positive | Negative | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div>• The combinations of d, s1 and s2 are as follows:</div><div><table><tr><th>d</th><th>s1</th><th>s2</th></tr><tr><td>Word</td><td>Word</td><td>Word</td></tr><tr><td>Double word</td><td>Double word</td><td>Double word</td></tr></table></div></div></div> | | | | | | | | | | | | | | | | d | s1 | s2 | Word | Word | Word | Double word | Double word | Double word | | | | | | | | | | | | | | | | | | | |
| d | s1 | s2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Word | Word | Word | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Double word | Double word | Double word | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div><div><div>X00000</div><div></div></div><div><div></div><div></div></div><div><div>WR0002 = WR0000 - WR0001</div><div></div></div></div></div><div><div>LD X00000</div><div>[</div><div>WR0002 = WR0000 - WR0001</div><div>]</div></div></div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div>• When input X00000 is on, the difference between the values in WR0000 and WR0001 is substituted into WR0002.</div></div></div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| Item number | | Arithmetic commands-5 | | | | Name | | BCD subtraction | | | | | | | | | | | | | | | | |
|---------------------|--------------------------|-----------------------|--|--|------|---------|-----------------------------------|-----------------|-----------|----------------------|------------|-------------|-----------------|------------|---------------------------------|--------|----|----|------|------|------|-------------|-------------|-------------|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | |
| d = s1 B- s2 | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | |
| | | | | ↑ | ● | ● | ● | ↑ | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | | 34 | ← | 39 | ← | 193 | ← | | | | | | | | | |
| d = s1 B- s2 | | | | Condition | | | Steps | | | | | 79 | ← | | | | | | | | | | | |
| | | | | Word | | | 4 | | | | | 63 | ← | | | | | | | | | | | |
| | | | | Double word | | | 6 | | | 54 | | ← | 117 | ← | 247 | ← | | | | | | | | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | | | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | |
| d | Substitution destination | | | | | | | | ○ | ○ | ○ | | ○ | ○ | | | | | | | | | | |
| s1 | Minuend | | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | |
| s2 | Subtrahend | | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">Subtracts s2 from s1 as BCD data, and substitutes the result into d as BCD data.The C flag is 1 if there is a digit decrease, and 0 if not.The DER flag is 1 if s1 or s2 is not a valid BCD data. In such cases, operation is not performed and the C flag retains the previous state without outputting to d. If the s1 and s2 are valid BCD data, the DER is set to 0. | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">The combinations of d, s1 and s2 are as follows: <table><tr><td>d</td><td>s1</td><td>s2</td></tr><tr><td>Word</td><td>Word</td><td>Word</td></tr><tr><td>Double word</td><td>Double word</td><td>Double word</td></tr></table> | | | | | | | | | | | | d | s1 | s2 | Word | Word | Word | Double word | Double word | Double word |
| d | s1 | s2 | | | | | | | | | | | | | | | | | | | | | | |
| Word | Word | Word | | | | | | | | | | | | | | | | | | | | | | |
| Double word | Double word | Double word | | | | | | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | <div><div><div>X00000</div><div>└─┘</div></div><div>WR0003 = WR0004 B- WR0005</div></div> <div>LD X00000 [WR0003 = WR0004 B- WR0005]</div> | | | | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">When input X00000 turns on, the difference between the values in WR0004 and WR0005 is substituted into WR0003 as BCD data. | | | | | | | | | | | | | | | | | | | | |

d = s1 x s2

| Item number | | Arithmetic commands-6 | | | | Name | | Binary multiplication | | | | | | | | | | | | | | |
|---------------------|--------------------------|--|---|-----------------|-----------------------------------|------|-------|-----------------------|----------------------|-------------|------------|------------|-----------------|-------|---------------------------------|---|----|----|------|------|------|-------------|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | | | | |
| d = s1 × s2 | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | |
| Command format | | | | Number of steps | | | | | 30 | ← | 31 | ← | 87 | ← | | | | | | | | |
| d = s1 × s2 | | | | Condition | | | Steps | | | | 76 | ← | | | | | | | | | | |
| | | | | Word | | | 4 | | | | 45 | ← | | | | | | | | | | |
| | | | | Double word | | | 6 | | | | 85 | ← | 139 ← | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | |
| d | Substitution destination | | | | | | | ○ | ○ | ○ | | ○ | ○ | | | | | | | | | |
| s1 | Multiplicand | | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | |
| s2 | Multiplier | | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">Multiplies s1 and s2 as binary data, and substitutes the result into d+1 (upper digit) and d (lower digit) in binary.The DER flag is 1 if d+1 has exceeded the usable I/O range (in this case only the lower word is substituted), and 0 when it is not exceeded. | | | | | | | | | | | | | | | | | | | | |
| | | <div><div><div><div>MSB</div><div>0</div></div><div>s1</div></div><div><div><div>MSB</div><div>0</div></div><div>s2</div></div><div><div><div>×</div><div>MSB</div><div>0</div></div><div>d+1</div><div>d</div></div></div> <div><div>Example) WR0012 = WR0010 × WR0011</div><div><div><div>WR0010</div><div>×</div><div>WR0011</div><div>-----</div><div>WR0013</div><div>WR0012</div><div>DR0012</div></div></div></div> <div><div>Example) DR0014 = DR0010 × DR0012</div><div><div><div>WR0011</div><div>WR0010</div><div>-----</div><div>DR0010</div><div>WR0013</div><div>WR0012</div><div>DR0012</div><div>×</div><div>WR0017</div><div>WR0016</div><div>WR0015</div><div>WR0014</div><div>DR0016</div><div>DR0014</div></div></div></div> | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">The combinations of d, s1 and s2 are as follows: | | | | | | | | | | | | | | | | | | | | |
| | | <table><tr><td>d</td><td>s1</td><td>s2</td></tr><tr><td>Word</td><td>Word</td><td>Word</td></tr><tr><td>Double word</td><td>Double word</td><td>Double word</td></tr></table> | | | | | | | | | | | | | | d | s1 | s2 | Word | Word | Word | Double word |
| d | s1 | s2 | | | | | | | | | | | | | | | | | | | | |
| Word | Word | Word | | | | | | | | | | | | | | | | | | | | |
| Double word | Double word | Double word | | | | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">Since the operation results are always substituted into d and d + 1, exercise caution so that the word or double-word at d + 1 is not used as the I/O of others. | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | | |
| | | <div><div><div>X00000</div><div>┌───┐</div><div>WR0002 = WR0000 * WR0001</div></div></div> | | | | | | | | | | | | | | | | | | | | |
| | | <div><div>LD X00000</div><div>[</div><div>WR0002 = WR0000 * WR0001</div><div>]</div></div> | | | | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">When input X00000 turns on, the product of the values in WR0000 and WR0001 is substituted into WR0002. | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | |

| Item number | Arithmetic commands-7 | | | | Name | | BCD multiplication | | | | | | | | | |
|--|--------------------------|-----|-----------------|---------|-----------------------------------|-------|--------------------|----------------------|-----|-------------|-----|-----------------|-------|---------------------------------|--|--|
| Ladder format | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| d = s1 B× s2 | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | |
| | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | ↓ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | Number of steps | | | | | 63 | ← | 64 | ← | 227 | ← | | | |
| d = s1 B× s2 | | | Condition | | | Steps | | 132 | ← | 110 | ← | 323 | ← | | | |
| | | | Word | | | 4 | | | | 137 | ← | | | | | |
| | | | Double word | | | 6 | | | | 203 | ← | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | |
| d | Substitution destination | | | | | | ○ | ○ | ○ | | ○ | ○ | | | | |
| s1 | Multiplicand | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | |
| s2 | Multiplier | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | |
| Function | | | | | | | | | | | | | | | | |
| <div><div><div><div><div><div>MSB</div><div>0</div></div><div><div></div><div></div></div></div><div><div>MSB</div><div>0</div></div><div><div></div><div></div></div></div><div><div>×</div><div></div></div><div><div>MSB</div><div>0</div></div><div><div></div><div>d+1</div></div><div><div></div><div>d</div></div></div></div> <div><div>Example) WR0016 = WR0014 B × WR0015</div><div><div><div>WR0014</div><div>s1</div></div><div><div>WR0015</div><div>s2</div></div><div><div>×</div><div></div></div><div><div>WR0017</div><div>d+1</div></div><div><div>WR0016</div><div>d</div></div></div><div><div>DR0016</div></div></div> <div><div>Example) DR0022 = DR0018 B × DR0020</div><div><div><div><div>WR0019</div><div>WR0018</div></div><div>s1</div></div><div><div>DR0018</div></div><div><div><div>WR0021</div><div>WR0020</div></div><div>s2</div></div><div><div>×</div><div></div></div><div><div>DR0020</div></div><div><div><div>WR0025</div><div>WR0024</div></div><div>d+1</div></div><div><div>WR0023</div><div>WR0022</div></div><div>d</div></div></div> <div><div>DR0024</div><div>DR0022</div></div> | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | |
| <div><div><div><div><div><div>d</div><div>s1</div><div>s2</div></div><div><div>Word</div><div>Word</div><div>Word</div></div><div><div>Double word</div><div>Double word</div><div>Double word</div></div></div></div></div><div><div><div><div><div>Since the operation results are always substituted into d and d + 1, exercise caution so that the word or double-word at d + 1 is not used as the I/O of others.</div></div></div></div></div></div> | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | |
| <div><div><div><div><div>X00000</div><div></div></div><div><div>WR0016 = WR0014 B * WR0015</div></div></div></div><div><div>LD X00000</div><div>[</div><div>WR0016 = WR0014 B * WR0015</div><div>]</div></div></div> | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | |
| <div><div><div><div><div>When input X00000 turns on, the product of the values in WR0014 and WR0015 is substituted into WR0016 as BCD data.</div></div></div></div></div> | | | | | | | | | | | | | | | | |

d = s1 Sx s2

| Item number | | Arithmetic commands-8 | | | | Name | | Signed binary multiplication | | | | | | | | | |
|--|--------------------------|-----------------------|---|-----------------|-----------------------------------|-------|------|------------------------------|----------------------|-------------|------------|------------|-----------------|-------|--------|--|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| d = s1 S × s2 | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ↕ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | 42 | ← | 48 | ← | 143 | ← | | | |
| d = s1 S × s2 | | | | Condition | | Steps | | | | | | | | | | | |
| | | | | Double word | | 6 | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| d | Substitution destination | | | | | | | | | | ○ | ○ | | | | | |
| s1 | Multiplicand | | | | | | | | | ○ | ○ | ○ | ○ | | | | |
| s2 | Multiplier | | | | | | | | | ○ | ○ | ○ | ○ | | | | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div><div><div><div>31</div><div>0</div></div><div><div></div><div></div></div></div><div>s1</div></div><div><div><div>31</div><div>0</div></div><div><div></div><div></div></div></div><div>s2</div></div> <div><div><div>×</div><div>63</div><div>3231</div><div>0</div></div><div><div>↑</div><div>d+1</div><div>d</div></div></div> <div>Sign bit</div> <div><div><div>Example) DR0031 = DR0026 S × DR0028</div><div><div><div><div>WR0027</div><div>WR0026</div></div><div>s1</div></div><div>DR0026</div><div><div><div>WR0029</div><div>WR0028</div></div><div>s2</div></div><div>DR0028</div><div>×</div><div><div><div>WR0034</div><div>WR0033</div></div><div>DR0033</div></div><div><div><div>WR0032</div><div>WR0031</div></div><div>DR0031</div></div></div></div></div> <div>The sign of the operation result is entered in the most significant bit.</div> <div><div>s1, s2</div><div>– 2,147,483,648 to +2,147,483,647 (decimal)</div><div>H80000000 to H7FFFFFFF (hexadecimal)</div></div> | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| <div><div><div>The operation result is always assigned to d and d+1. Be sure not to use word or double word d+1 as the I/O of other functions.</div></div></div> | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| <div><div><div><div><div>X00000</div><div>┌───┴───┐</div><div>DR0031 = DR0026 S * DR0028</div></div></div><div><div>LD</div><div>X00000</div><div>[</div><div>DR0031 = DR0026 S * DR0028</div><div>]</div></div></div></div> | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| <div><div><div>When input X00000 turns on, the product of the values in DR0026 and DR0028 is substituted into DR0031 as signed binary data.</div></div></div> | | | | | | | | | | | | | | | | | |

| Item number | | Arithmetic commands-9 | | | | Name | | Binary division | | | | | | | | | | | | | | | |
|---|--------------------------|-----------------------|---|-----------------|-----------------------------------|------|-------|-----------------|----------------------|-------------|------------|------------|-----------------|-------|---------------------------------|----|----|------|------|------|-------------|-------------|-------------|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | |
| d = s1 / s2 | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | |
| Command format | | | | Number of steps | | | | | 28 | ← | 33 | | 138 | ← | | | | | | | | | |
| d = s1 / s2 | | | | Condition | | | Steps | | | | 72 | ← | | | | | | | | | | | |
| | | | | Word | | | 4 | | | | | | | | | | | | | | | | |
| | | | | Double word | | | 6 | | 32 | ← | 42 | ← | 111 | ← | | | | | | | | | |
| | | | | | | | | | 95 | ← | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | | |
| d | Substitution destination | | | | | | ○ | ○ | ○ | | ○ | ○ | | | | | | | | | | | |
| s1 | Dividend | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | |
| s2 | Divisor | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div><div>• Divides s1 by s2 and substitutes the quotient into d in binary. The remainder is set in the special internal output WRF016 (DRF016 in the case of double word).</div><div>• The DER flag is 1 if s2 is 0 and the operation is not performed. As long as s2 is not 0, the flag is 0 and the operation is performed.</div></div><div><div>Example) WR0042 = WR0040 / WR0041</div><div><div><div><div>WR0042</div><div>...</div><div>WRF016</div></div><div><div>WR0041</div><div>WR0040</div></div></div><div><div><div>WR0044</div><div>WR0043</div></div><div>DR0043</div></div><div><div><div>DR0047</div><div>WR0048</div><div>WR0047</div></div><div>...</div><div><div>WRF017</div><div>WRF016</div></div></div><div><div><div>WR0046</div><div>WR0045</div></div><div>DR0045</div></div></div></div></div></div> | | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div><div>• The combinations of d, s1 and s2 are as follows:</div><div><table><tr><td>d</td><td>s1</td><td>s2</td></tr><tr><td>Word</td><td>Word</td><td>Word</td></tr><tr><td>Double word</td><td>Double word</td><td>Double word</td></tr></table></div></div></div></div> | | | | | | | | | | | | | | | d | s1 | s2 | Word | Word | Word | Double word | Double word | Double word |
| d | s1 | s2 | | | | | | | | | | | | | | | | | | | | | |
| Word | Word | Word | | | | | | | | | | | | | | | | | | | | | |
| Double word | Double word | Double word | | | | | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div><div>X00000</div><div>└──┴──┘</div><div>WR0042 = WR0040 / WR0041</div></div><div><div>LD X00000</div><div>[</div><div>WR0042 = WR0040 / WR0041</div><div>]</div></div></div></div> | | | | | | | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div><div>• When input X00000 turns on, the value in WR0040 is divided by the value in WR0041, then substituted into WR0042. The remainder is substituted into special internal output WRF016.</div></div></div></div> | | | | | | | | | | | | | | | | | | | | | | | |

d = s1 B/ s2

| Item number | | Arithmetic commands-10 | | | | Name | | BCD division | | | | | | | | | | | | | | | | |
|---|--------------------------|------------------------|---|-----------------|-----------------------------------|------|-------|--------------|-----------|----------------------|------------|------------|-----------------|-------|---------------------------------|--------|----|----|------|------|------|-------------|-------------|-------------|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | |
| d = s1 B/ s2 | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | |
| | | | | ↓ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | | 50 | ← | 55 | ← | 236 | | | ← | | | | | | | |
| d = s1 B/ s2 | | | | Condition | | | Steps | | | 69 | ← | 101 | ← | 372 | | | ← | | | | | | | |
| | | | | Words | | | 4 | | | | | 78 | ← | | | | | | | | | | | |
| | | | | Double word | | | 6 | | | | | 141 | ← | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | | | |
| d | Substitution destination | | | | | | ○ | ○ | ○ | | ○ | ○ | | | | | | | | | | | | |
| s1 | Dividend | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | | |
| s2 | Divisor | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div><div>• Divides s1 by s2 as BCD data, and substitutes the quotient into d in BCD. The remainder is set in the special internal output WRF016 (DRF016 in the case of double word).</div><div>• The DER flag is 1 if s1 or s2 is an invalid BCD data or when s2 is 0. In this case the operation is not performed. If both s1 and s2 are valid BCD data and s2 is not 0, the operation is performed.</div></div><div>Example) WR0051 = WR0049 B/ WR0050</div><div><div><div><div>WR0051</div><div>...</div><div>WRF016</div></div><div><div><div>WR0050</div><div>)</div><div>WR0049</div></div></div></div><div><div><div>• When s1, s2 are words : 0000 to 9999 (BCD)</div><div>• When s1, s2 are double words : 00000000 to 99999999 (BCD)</div></div></div></div></div></div> | | | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div><div>• The combinations of d, s1 and s2 are as follows:</div><div><table><tr><td>d</td><td>s1</td><td>s2</td></tr><tr><td>Word</td><td>Word</td><td>Word</td></tr><tr><td>Double word</td><td>Double word</td><td>Double word</td></tr></table></div></div></div></div> | | | | | | | | | | | | | | | | d | s1 | s2 | Word | Word | Word | Double word | Double word | Double word |
| d | s1 | s2 | | | | | | | | | | | | | | | | | | | | | | |
| Word | Word | Word | | | | | | | | | | | | | | | | | | | | | | |
| Double word | Double word | Double word | | | | | | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div><div><div>X00000</div><div><div><div></div><div></div></div></div></div><div>WR0051 = WR0049 B/ WR0050</div></div></div><div><div>LD X00000</div><div>[</div><div>WR0051 = WR0049 B/ WR0050</div><div>]</div></div></div> | | | | | | | | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div><div>• When input X00000 turns on, the value in WR0049 is divided by the value in WR0050, then substituted into WR0051 as BCD data.</div><div>The remainder is substituted into WRF016 as BCD data.</div></div></div></div> | | | | | | | | | | | | | | | | | | | | | | | | |

| Item number | | Arithmetic commands-11 | | | | Name | | Signed binary division | | | | | | | | | |
|---------------------|--------------------------|--|---|-----------------|-----------------------------------|------|-------|------------------------|-----------|----------------------|------------|------------|-----------------|-------|---|--------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| d = s1 S/ s2 | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ↑ | ● | ● | ↑ | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 35 | ← | 44 | ← | 111 | ← | | |
| d = s1 S/ s2 | | | | Condition | | | Steps | | | | | | | | | | |
| | | | | Double word | | | 6 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| d | Substitution destination | | | | | | | | | | ○ | ○ | | | | | |
| s1 | Dividend | | | | | | | | | ○ | ○ | ○ | ○ | | | | |
| s2 | Divisor | | | | | | | | | ○ | ○ | ○ | ○ | | | | |
| Function | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">Divides s1 by s2 as signed binary data, and substitutes the quotient into d in signed binary data. The remainder is set in the special internal output DRF016 signed binary data.The DER flag is 1 if s2 is 0, and the operation is not performed. As long as s2 is not 0, it is 0 and the operation is performed.The V flag is 1 when the quotient is a positive value and exceeds H7FFFFFFF. Otherwise, it is 0. | | | | | | | | | | | | | | | |
| | | Eexample) DR0060 = DR0056 S/ DR0058 | | | | | | | | | | | | | | | |
| | | <div><div><div><div>WR0061</div><div>WR0060</div></div><div>...</div><div><div>WRF017</div><div>WRF016</div></div></div><div>DR0060</div><div><div><div><div>WR0059</div><div>WR0058</div></div><div>DR0058</div></div><div><div><div>WR0057</div><div>WR0056</div></div><div>DR0056</div></div></div></div> | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">s1, s2 – 2,147,483,648 to +2,147,483,647 (decimal) H80000000 to H7FFFFFFF (hexadecimal) | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| | | <div><div><div>X00000</div><div>└─┬─┘</div><div>DR0060 = DR0056 S/ DR0058</div></div><div>LD X00000 [DR0060 = DR0056 S/ DR0058]</div></div> | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">When input X00000 turns on, the value of DR0056 is divided by the value in DR0058, then substituted into DR0060 as signed binary data. The remainder is substituted into special internal output DRF016 as signed binary data. | | | | | | | | | | | | | | | |

d = s1 S/ s2

d = s1 OR s2

| Item number | | Arithmetic commands-12 | | | | Name | | Logical OR | | | | | | | | | | | | | | | | | | | | | |
|---------------------|--------------------------|--|---|-----------------|-----------------------------------|------|-------|------------|------------------------|----------------------|-------------------------|------------|-----------------|-------|---|--------|----|-----|-----|-----|------|------|------|-------------|-------------|-------------|---|---|---|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | | |
| d = s1 OR s2 | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | Upper case: B Middle case: W Lower case: DW | | | | | | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | |
| | | | | ● | ● | ● | ● | ● | 0.4 | ← | 19 | ← | 76 | ← | | | | | | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | | 0.4 | ← | 21 | ← | 89 | | | ← | | | | | | | | | | | | |
| d = s1 OR s2 | | | | Condition | | | Steps | | | 0.4 | ← | 55 | ← | 89 | | | ← | | | | | | | | | | | | |
| | | | | Bit, word | | | 4 | | | 18 | ← | 24 | ← | 78 | | | ← | | | | | | | | | | | | |
| | | | | Double word | | | 6 | | | | | 72 | ← | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | | | | | | | | |
| d | Substitution destination | | ○ | ○ | | | ○ | ○ | ○ | | ○ | ○ | | | | | | | | | | | | | | | | | |
| s1 | Comparand | ○ | ○ | ○ | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | | | | | | | |
| s2 | Relational number | ○ | ○ | ○ | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">Obtains OR of s1 and s2, and substitutes the result into d. | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <table><tr><td>s1</td><td>s2</td><td>d</td></tr><tr><td>0</td><td>0</td><td>0</td></tr><tr><td>0</td><td>1</td><td>1</td></tr><tr><td>1</td><td>0</td><td>1</td></tr><tr><td>1</td><td>1</td><td>1</td></tr></table> | | | | | | | | | | | | | s1 | s2 | d | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 0 | 1 | 1 | 1 | 1 |
| s1 | s2 | d | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 0 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 1 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 0 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 1 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">The combinations of d, s1 and s2 are as follows: | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <table><tr><td>d</td><td>s1</td><td>s2</td></tr><tr><td>Bit</td><td>Bit</td><td>Bit</td></tr><tr><td>Word</td><td>Word</td><td>Word</td></tr><tr><td>Double word</td><td>Double word</td><td>Double word</td></tr></table> | | | | | | | | | | | | | d | s1 | s2 | Bit | Bit | Bit | Word | Word | Word | Double word | Double word | Double word | | | |
| d | s1 | s2 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Bit | Bit | Bit | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Word | Word | Word | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Double word | Double word | Double word | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <div><div><div>X00110</div><div>DIF110</div></div><div></div><div>WR0102= WR0100 OR WR0101</div></div> <div>LD X00110 AND DIF110 [WR0102=WR0100 OR WR0101]</div> | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">At the rising edge of X00110, the OR of WR0100 and WR0101 is set in WR0102. | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <div>WR0100 = H1234 WR0101 = H5678 WR0102 = H567C</div> <div>When ⇒</div> <div>WR0100 = 0001001000110100 WR0101 = 0101011001111000 WR0102 = 0101011001111100</div> | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| Item number | | Arithmetic commands-13 | | | | Name | | Logical AND | | | | | | | | | |
|--|--------------------------|---------------------------|---|---|-----------------------------------|------|-------|-------------|-----------|----------------------|------------|------------|-----------------|-------|---|--------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| d = s1 AND s2 | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: B Middle case: W Lower case: DW | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 0.4 | ← | 19 | ← | 76 | ← | | |
| | | | | | | | | | | | | | | | | | |
| d = s1 AND s2 | | | | Condition | | | Steps | | | 0.4 | ← | 18 | ← | 89 | ← | | |
| | | | | Bit, word | | | 4 | | | 18 | ← | 28 | ← | 79 | ← | | |
| | | | | Double word | | | 6 | | | | | 77 | ← | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| d | Substitution destination | | ○ | ○ | | | ○ | ○ | ○ | | ○ | ○ | | | | | |
| s1 | Comparand | ○ | ○ | ○ | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | |
| s2 | Relational number | ○ | ○ | ○ | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | |
| Function | | | | | | | | | | | | | | | | | |
| ● Obtains AND of s1 and s2, and substitutes the result into d. | | | | | | | | | | | | | | | | | |
| s1 | | s2 | | d | | | | | | | | | | | | | |
| 0 | | 0 | | 0 | | | | | | | | | | | | | |
| 0 | | 1 | | 0 | | | | | | | | | | | | | |
| 1 | | 0 | | 0 | | | | | | | | | | | | | |
| 1 | | 1 | | 1 | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| ● The combinations of d, s1 and s2 are as follows: | | | | | | | | | | | | | | | | | |
| d | | s1 | | s2 | | | | | | | | | | | | | |
| Bit | | Bit | | Bit | | | | | | | | | | | | | |
| Word | | Word | | Word | | | | | | | | | | | | | |
| Double word | | Double word | | Double word | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| X00111 DIF111 | | WR0102= WR0100 AND WR0101 | | LD X00111 AND DIF111 [WR0102=WR0100 AND WR0101] | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| ● At the rising edge of X00111, the AND of WR0100 and WR0101 is set in WR0102. | | | | | | | | | | | | | | | | | |
| WR0100 = H1234 When WR0100 = 0001001000110100 | | | | | | | | | | | | | | | | | |
| WR0101 = H5678 WR0101 = 0101011001111000 | | | | | | | | | | | | | | | | | |
| WR0102 = H1230 WR0102 = 0001001000110000 | | | | | | | | | | | | | | | | | |

d = s1 AND s2

d = s1 XOR s2

| Item number | | Arithmetic commands-14 | | | | Name | | | | Exclusive OR | | | | | | | | | | | | | | | | | | | | |
|---|--------------------------|------------------------|-----|-----------------|---------|-----------------------------------|-------|------|------------|----------------------|-------------|-----|-----------------|----------|---|--------|----|----|-----|-----|-----|------|------|------|-------------|-------------|-------------|---|---|---|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | | | |
| d = s1 XOR s2 | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: B Middle case: W Lower case: DW | | | | | | | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | 0.4 | ← | 19 | ← | 76 | ← | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | 18 | ← | | 89 | | ← | | | | | | | | | | | | | | |
| d = s1 XOR s2 | | | | Condition | | | Steps | | 0.4 | ← | 52 | ← | | | | | | | | | | | | | | | | | | |
| | | | | Bit, word | | | 4 | | 18 | ← | 28 | ← | 79 | ← | | | | | | | | | | | | | | | | |
| | | | | Double word | | | 6 | | | | 76 | ← | | | | | | | | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | | | | | | | | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | | | | | | | | |
| d | Substitution destination | | | | ○ | ○ | | | ○ | ○ | ○ | | | | | | | | | | | | | | | | | | | |
| s1 | Comparand | | | ○ | ○ | ○ | | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | | | | | | | | |
| s2 | Relational number | | | ○ | ○ | ○ | | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div>● Obtains exclusive OR (XOR) of s1 and s2, and substitutes the result into d.</div> <table><tr><td>s1</td><td>s2</td><td>d</td></tr><tr><td>0</td><td>0</td><td>0</td></tr><tr><td>0</td><td>1</td><td>1</td></tr><tr><td>1</td><td>0</td><td>1</td></tr><tr><td>1</td><td>1</td><td>0</td></tr></table> | | | | | | | | | | | | | | | | s1 | s2 | d | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 0 | 1 | 1 | 1 | 0 |
| s1 | s2 | d | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 0 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 1 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 0 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 1 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div>● The combinations of d, s1 and s2 are as follows:</div> <table><tr><td>d</td><td>s1</td><td>s2</td></tr><tr><td>Bit</td><td>Bit</td><td>Bit</td></tr><tr><td>Word</td><td>Word</td><td>Word</td></tr><tr><td>Double word</td><td>Double word</td><td>Double word</td></tr></table> | | | | | | | | | | | | | | | | d | s1 | s2 | Bit | Bit | Bit | Word | Word | Word | Double word | Double word | Double word | | | |
| d | s1 | s2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Bit | Bit | Bit | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Word | Word | Word | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Double word | Double word | Double word | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div>X00112</div><div>DIF112</div><div>WR0102= WR0100 XOR WR0101</div></div><div>LD X00112 AND DIF112 [WR0102=WR0100 XOR WR0101]</div></div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div>● At the rising edge of X00112, the XOR of WR0100 and WR0101 is set in WR0102.</div> <div><div>WR0100 = H1234 WR0101 = H5678 WR0102 = H444C</div><div>When ⇒</div><div>WR0100 = 0001001000110100 WR0101 = 0101011001111000 WR0102 = 0100010001001100</div></div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| Item number | Arithmetic commands-15 | | | | Name | = Relational expression | | | | | | | | | | | | | | | | | |
|---------------------|--------------------------|--|--------------------|---------|-----------------------------------|-------------------------|------|------------|----------------------|-------------|-----|-----------------|----------|---------------------------------|--------|----|----|-----|------|------|-----|-------------|-------------|
| Ladder format | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | |
| d = s1 == s2 | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | | | | | | | | |
| | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | |
| | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | |
| Command format | | | Number of steps | | | | | | 0.4 | ← | 19 | ← | 82 | | 85 | | | | | | | | |
| d = s1 == s2 | | | Condition | | | Steps | | | | | 36 | ← | | | | | | | | | | | |
| | | | s is a word | | | 4 | | | 18 | ← | 27 | ← | 84 | | 85 | | | | | | | | |
| | | | s is a double word | | | 6 | | | | | 44 | ← | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | | |
| d | Substitution destination | | | ○ | ○ | | | | | | | | | | | | | | | | | | |
| s1 | Comparand | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | |
| s2 | Relational number | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | |
| | | ● Substitutes 1 when s1 is equal to s2 and otherwise 0 into d, assuming s1 and s2 as binary data. | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | |
| | | ● The combinations of d, s1 and s2 are as follows: | | | | | | | | | | | | | | | | | | | | | |
| | | <table><tr><td>d</td><td>s1</td><td>s2</td></tr><tr><td>Bit</td><td>Word</td><td>Word</td></tr><tr><td>Bit</td><td>Double word</td><td>Double word</td></tr></table> | | | | | | | | | | | | | d | s1 | s2 | Bit | Word | Word | Bit | Double word | Double word |
| d | s1 | s2 | | | | | | | | | | | | | | | | | | | | | |
| Bit | Word | Word | | | | | | | | | | | | | | | | | | | | | |
| Bit | Double word | Double word | | | | | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | | | |
| | | <div><div><div></div><div>M0000 = WX0000 == WX0001</div></div></div> <div>[M0000 = WX0000 == WX0001]</div> | | | | | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | | | |
| | | ● When WX0000 = WX0001, “1” is set in M0000. Otherwise, M0000 is reset to “0.” | | | | | | | | | | | | | | | | | | | | | |

d = s1 S== s2

| Item number | | Arithmetic commands-16 | | | | Name | | Signed = Relational expression | | | | | | | | | |
|---------------------|--------------------------|------------------------|--|--------------------|---------|-----------------------------------|-------|--------------------------------|------------|----------------------|-------------|-----|-----------------|----------|-------|--------|-----|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| d = s1 S== s2 | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 18 | ← | 27 | ← | 84 | | | 202 |
| d = s1 S== s2 | | | | Condition | | | Steps | | | | | 44 | ← | | | | |
| | | | | s is a double word | | | 6 | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | |
| d | Substitution destination | | | ○ | ○ | | | | | | | | | | | | |
| s1 | Comparand | | | | | | | | | ○ | ○ | ○ | ○ | | | | |
| s2 | Relational number | | | | | | | | | ○ | ○ | ○ | ○ | | | | |
| Function | | | | | | | | | | | | | | | | | |
| | | | <ul style="list-style-type: none">Substitutes 1 when s1 is equal to s2 and otherwise 0 into d, assuming s1 and s2 as signed binary data.s1 and s2 are both signed binary data. When the most significant bit is 0, the value is positive; when the most significant bit is 1, the value is negative. s1, s2 – 2,147,483,648 to +2,147,483,647 (decimal) H80000000 to H7FFFFFFF (hexadecimal) <div><div>b31</div><div>b16 b15</div><div>b0</div><div></div></div> <div>↑ Sign bit: 0 - Positive; 1 - Negative</div> | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| | | | <div><div></div><div>M0000 = DR0000 S== DR0002</div><div></div></div> <div>[M0000 = DR0000 S== DR0002]</div> | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| | | | <ul style="list-style-type: none">When the values of DR0000 and DR0002 are equal, 1 is set in M0000. Otherwise, M0000 is reset to 0. | | | | | | | | | | | | | | |

| Item number | Arithmetic commands-17 | | | | Name | | <> Relational expression | | | | | | | | | | | | | | | | |
|---------------------|--------------------------|--|--------------------|---------|-----------------------------------|-------|--------------------------|------------|----------------------|-------------|-----|-----------------|----------|---------------------------------|--------|----|----|-----|------|------|-----|-------------|-------------|
| Ladder format | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | |
| d = s1 <> s2 | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | | | | | | | | |
| | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | |
| | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | |
| Command format | | | Number of steps | | | | | | 0.4 | ← | 19 | ← | 75 | | 192 | | | | | | | | |
| d = s1 <> s2 | | | Condition | | | Steps | | | 18 | ← | 36 | ← | 84 | | 202 | | | | | | | | |
| | | | s is a word | | | 4 | | | | | 27 | ← | | | | | | | | | | | |
| | | | s is a double Word | | | 6 | | | 43 | ← | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | | Other | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | | |
| d | Substitution destination | | | ○ | ○ | | | | | | | | | | | | | | | | | | |
| s1 | Comparand | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | |
| s2 | Relational number | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | |
| | | ● Substitutes 1 when s1 is not equal to s2 and otherwise 0 into d, assuming s1 and s2 as binary data. | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | |
| | | ● The combinations of d, s1 and s2 are as follows: | | | | | | | | | | | | | | | | | | | | | |
| | | <table><tr><td>d</td><td>s1</td><td>s2</td></tr><tr><td>Bit</td><td>Word</td><td>Word</td></tr><tr><td>Bit</td><td>Double word</td><td>Double word</td></tr></table> | | | | | | | | | | | | | d | s1 | s2 | Bit | Word | Word | Bit | Double word | Double word |
| d | s1 | s2 | | | | | | | | | | | | | | | | | | | | | |
| Bit | Word | Word | | | | | | | | | | | | | | | | | | | | | |
| Bit | Double word | Double word | | | | | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | | | |
| | | <div><div></div><div>Y00000= WR0000 < > WR0001</div></div> <div>[Y00000= WR0000 < > WR0001]</div> | | | | | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | | | |
| | | ● When WR0000 ≠ WR0001, “1” is set in Y00000. Otherwise, Y00000 is reset to “0.” | | | | | | | | | | | | | | | | | | | | | |

d = s1 S<> s2

| Item number | | Arithmetic commands-18 | | | | Name | | Signed <> Relational expression | | | | | | | | | |
|---------------------|--------------------------|------------------------|---|--------------------|---------|-----------------------------------|-------|---------------------------------|------------|----------------------|-------------|-----|-----------------|----------|-------|--------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| d = s1 S<> s2 | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 18 | ← | 27 | ← | 85 | | ← | |
| d = s1 S<> s2 | | | | Condition | | | Steps | | | | | 43 | ← | | | | |
| | | | | s is a double word | | | 6 | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | |
| d | Substitution destination | | | ○ | ○ | | | | | | | | | | | | |
| s1 | Comparand | | | | | | | | | ○ | ○ | ○ | ○ | | | | |
| s2 | Relational number | | | | | | | | | ○ | ○ | ○ | ○ | | | | |
| Function | | | | | | | | | | | | | | | | | |
| | | | <ul style="list-style-type: none">Substitutes 1 when s1 is not equal to s2 and otherwise 0 into d, assuming s1 and s2 as signed binary data.s1 and s2 are both signed binary data. When the most significant bit is 0, the value is positive; when the most significant bit is 1, the value is negative. s1, s2 – 2,147,483,648 to +2,147,483,647 (decimal) H80000000 to H7FFFFFFF (hexadecimal) <div><div>b31</div><div>b16 b15</div><div>b0</div><div></div><div>↑</div><div>Sign bit: 0 - Positive; 1 - Negative</div></div> | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| | | | <div><div></div><div>Y00100 = DR0000 S<> DR0002</div><div></div></div> <div>[Y00100 = DR0000 S<> DR0002]</div> | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| | | | <ul style="list-style-type: none">When the values of DR0000 and DR0002 are not equal, Y00100 is turned on. Otherwise, Y00100 is turned off. | | | | | | | | | | | | | | |

| Item number | | Arithmetic commands-19 | | | | Name | | < Relational expression | | | | | | | | | | | | | | | | |
|---------------------|--------------------------|--|---|--------------------|-----------------------------------|------|-------|-------------------------|-----------|----------------------|------------|------------|-----------------|-------|---------------------------------|--------|----|----|-----|------|------|-----|-------------|-------------|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | |
| d = s1 < s2 | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | | 0.4 | ← | 19 | ← | 76 | ← | | | | | | | | | |
| d = s1 < s2 | | | | Condition | | | Steps | | | | | 36 | ← | | | | | | | | | | | |
| | | | | s is a word | | | 4 | | | | | 27 | ← | | | | | | | | | | | |
| | | | | s is a double word | | | 6 | | | 19 | ← | 44 | ← | 86 | ← | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | | | |
| d | Substitution destination | | | | ○ | ○ | | | | | | | | | | | | | | | | | | |
| s1 | Comparand | | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | |
| s2 | Relational number | | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | |
| | | ● Substitutes 1 when s1 is less than s2 and otherwise 0 into d, assuming s1 and s2 as binary data. | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | | |
| | | ● The combinations of d, s1 and s2 are as follows: | | | | | | | | | | | | | | | | | | | | | | |
| | | <table><tr><td>d</td><td>s1</td><td>s2</td></tr><tr><td>Bit</td><td>Word</td><td>Word</td></tr><tr><td>Bit</td><td>Double word</td><td>Double word</td></tr></table> | | | | | | | | | | | | | | d | s1 | s2 | Bit | Word | Word | Bit | Double word | Double word |
| d | s1 | s2 | | | | | | | | | | | | | | | | | | | | | | |
| Bit | Word | Word | | | | | | | | | | | | | | | | | | | | | | |
| Bit | Double word | Double word | | | | | | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <div><div></div><div>L10000= TC100 < TC101</div><div></div></div> <div>[L10000= TC100 < TC101]</div> | | | | | | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | | | | |
| | | ● When TC100 < TC101, 1 is set in L10000. Otherwise, L10000 is reset to 0. (TC n is the progress value of the no. n timer or counter.) | | | | | | | | | | | | | | | | | | | | | | |

d = s1 S < s2

| Item number | Arithmetic commands-20 | Name | | Signed < Relational expression | | | | | | | | | | | |
|--|--------------------------|------|--------------------|--------------------------------|-----------------------------------|-------|------|------------|----------------------|-------------|-----|-----------------|----------|-------|--------|
| Ladder format | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark |
| d = s1 S< s2 | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | |
| | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | |
| | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | | Number of steps | | | | | | 19 | ← | 27 | ← | 86 | | ← |
| d = s1 S< s2 | | | Condition | | | Steps | | | | | 45 | ← | | | |
| | | | s is a double word | | | 6 | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| d | Substitution destination | | ○ | ○ | | | | | | | | | | | |
| s1 | Comparand | | | | | | | | | ○ | ○ | ○ | ○ | | |
| s2 | Relational number | | | | | | | | | ○ | ○ | ○ | ○ | | |
| Function | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">Substitutes 1 when s1 is less than s2 and otherwise 0 into d, assuming s1 and s2 as signed binary data.s1 and s2 are both signed binary data. When the most significant bit is 0, the value is positive; when the most significant bit is 1, the value is negative. s1, s2 – 2,147,483,648 to +2,147,483,647 (decimal) H80000000 to H7FFFFFFF (hexadecimal)</div> <div><div><div>b31</div><div>b16 b15</div><div>b0</div></div><div><div></div><div></div><div></div></div><div><div>↑</div><div>Sign bit: 0 - Positive; 1 - Negative</div></div></div> | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | |
| <div><div><div></div><div>R100 = DM000 S< DM002</div><div></div></div><div>[R100 = DM000 S< DM002]</div></div> | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">When the value in DM000 is less than the value in DM002, 1 is set in R100. Otherwise, R100 is reset to 0.</div> | | | | | | | | | | | | | | | |

| Item number | | Arithmetic commands-21 | | | | Name | | ≤ Relational expression | | | | | | | | | | | | | | | | |
|---------------------|--------------------------|--|-----|--------------------|---------|-----------------------------------|-------|-------------------------|------------|----------------------|-------------|-----|-----------------|-------|---------------------------------|------------|----|----|-----|------|------|-----|-------------|-------------|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | |
| d = s1 <= s2 | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | | 0.4 | ← | 19 | ← | 76 | ← | | | | | | | | | |
| d = s1 <= s2 | | | | Condition | | | Steps | | | | | 36 | ← | | | | | | | | | | | |
| | | | | s is a word | | | 4 | | | 19 | ← | 27 | ← | 86 | ← | | | | | | | | | |
| | | | | s is a double word | | | 6 | | | | | 45 | ← | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | Constant | Other | | | | | | | | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | | DR, DL, DM | | | | | | | | |
| d | Substitution destination | | | | ○ | ○ | | | | | | | | | | | | | | | | | | |
| s1 | Comparand | | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | |
| s2 | Relational number | | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | |
| | | ● Substitutes 1 when s1 is less than or equal to s2 and otherwise 0 into d, assuming s1 and s2 as binary data. | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | | |
| | | ● The combinations of d, s1 and s2 are as follows: | | | | | | | | | | | | | | | | | | | | | | |
| | | <table><tr><td>d</td><td>s1</td><td>s2</td></tr><tr><td>Bit</td><td>Word</td><td>Word</td></tr><tr><td>Bit</td><td>Double word</td><td>Double word</td></tr></table> | | | | | | | | | | | | | | d | s1 | s2 | Bit | Word | Word | Bit | Double word | Double word |
| d | s1 | s2 | | | | | | | | | | | | | | | | | | | | | | |
| Bit | Word | Word | | | | | | | | | | | | | | | | | | | | | | |
| Bit | Double word | Double word | | | | | | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <div><div>Y00001 = WL3FF <= WL13FF</div><div>[Y00001 = WL3FF <= WL13FF]</div></div> | | | | | | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | | | | |
| | | ● When WL3FF ≤ WL13FF, 1 is set in Y00001. Otherwise, Y00001 is reset to 0. | | | | | | | | | | | | | | | | | | | | | | |

d = s1 S<= s2

| Item number | | Arithmetic commands-22 | | | | Name | | Signed ≤ Relational expression | | | | | | | | | |
|---------------------|--------------------------|------------------------|---|--------------------|---------|-----------------------------------|-------|--------------------------------|------------|----------------------|-------------|-----|-----------------|----------|-------|--------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| d = s1 S<= s2 | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 19 | ← | 27 | ← | 86 | ← | | |
| d = s1 S<= s2 | | | | Condition | | | Steps | | | | | 45 | ← | | | | |
| | | | | s is a double word | | | 6 | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | |
| d | Substitution destination | | | ○ | ○ | | | | | | | | | | | | |
| s1 | Comparand | | | | | | | | | ○ | ○ | ○ | ○ | | | | |
| s2 | Relational number | | | | | | | | | ○ | ○ | ○ | ○ | | | | |
| Function | | | | | | | | | | | | | | | | | |
| | | | <ul style="list-style-type: none">Substitutes 1 when s1 is less than or equal to s2 and otherwise 0 into d, assuming s1 and s2 as signed binary data.s1 and s2 are both signed binary data. When the most significant bit is 0, the value is positive; when the most significant bit is 1, the value is negative. s1, s2 – 2,147,483,648 to +2,147,483,647 (decimal) H80000000 to H7FFFFFFF (hexadecimal) <div><div><div>b31</div><div>b16 b15</div><div>b0</div></div><div><div></div><div></div><div></div></div><div><div>↑</div><div>Sign bit: 0 - Positive; 1 - Negative</div></div></div> | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| | | | <div><div>Y00100 = DL3FE S<= DL13FE</div><div>[Y00100 = DL03FE S<= DL13FE]</div></div> | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| | | | <ul style="list-style-type: none">When the value in DL3FE is less than or equal the value in DL13FE, Y00100 is turned on. Otherwise, Y00100 is turned off. | | | | | | | | | | | | | | |

| Item number | Application commands-1 | Name | | | | Bit set | | | | | | | | | | | |
|---|------------------------|-----------------|------|---------|-----------------------------------|---------|----------------------|------------|------------|-------------|-----------------|------------|---------------------------------|---------------------------------|-------|--|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | |
| BSET (d, n) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | |
| | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | |
| Command format | | Number of steps | | | | | 13 | ← | 15 | ← | 86 | ← | | | | | |
| BSET (d, n) | | Condition | | Steps | | 50 | | | ← | | | | | | | | |
| | | — | | 3 | | 15 | ← | 17 | ← | 66 | ← | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | | Constant | Other | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| d | I/O to be set the bit | | | | | | ○ | ○ | ○ | | ○ | ○ | | | | | |
| n | Bit location to be set | | | | | ○ | ○ | ○ | ○ | | | | ○ | The constant is set in decimal. | | | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div><div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div></div></div></div> | | | | | | | | | | | | | | | | | |

BSET (d, n)

| Item number | | Application commands-2 | | | | Name | | Bit reset | | | | | | | | | |
|--|--------------------------|---|-----|-----------------|---------|-----------------------------------|-------|-----------|------------|----------------------|-------------|-----|-----------------|----------|---------------------------------|--------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| BRES (d, n) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 13 | ← | 15 | ← | 86 | ← | | |
| BRES (d, n) | | | | Condition | | | Steps | | | | | 50 | ← | | | | |
| | | | | — | | | 3 | | | 15 | ← | 17 | ← | 66 | ← | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | |
| d | I/O to be set the bit | | | | | | | ○ | ○ | ○ | | ○ | ○ | | | | |
| n | Bit location to be reset | | | | | | | ○ | ○ | ○ | ○ | | | ○ | The constant is set in decimal. | | |
| Function | | | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">Sets the nth bit in the I/O (word or double word) specified by d to 0.Other bit contents are unaltered.<div><div>d</div><div><div>.....</div><div>n+1</div><div>n</div><div>n-1</div><div>.....</div><div>5</div><div>4</div><div>3</div><div>2</div><div>1</div><div>0</div></div><div><div></div><div></div><div>0</div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div>↑</div><div>Reset to '0'.</div></div></div></div> | | | | | | | | | | | | | | | | | |
| If d is a word : | | Designates the bit location depending on the contents (0 to 15) of the lower 4 bits (b3 to b0) of n (WX, WY, WR, WL, WM, TC). (Upper bits are ignored and considered 0.) The n (constant) can be set to 0 to 15 (decimal). | | | | | | | | | | | | | | | |
| If d is a double word : | | Designates the bit location depending on the contents (0 to 31) of the lower 5 bits (b4 to b0) of n (WX, WY, WR, WL, WM, TC). (Upper bits are ignored and considered 0.) The n (constant) can be set to 0 to 31 (decimal). | | | | | | | | | | | | | | | |

BRES (d, n)


| Item number | | Application commands-3 | | | | Name | | Bit test | | | | | | | | | |
|--|---------------------------|------------------------|--|---|------|---------|-----------------------------------|---|-----------|----------------------|------------|-------------|-----------------|----------|---------------------------------|---------------------------------|---|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| BTS (d, n) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ↓ | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 13 | ← | 16 | ← | 86 | | | ← |
| BTS (d, n) | | | | Condition | | | Steps | | | 15 | ← | 50 | ← | 67 | | | ← |
| | | | | — | | | 3 | | | | | 18 | ← | | | | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | Constant | Other | | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | |
| d | I/O to be tested | | | | | | | | ○ | ○ | ○ | | ○ | ○ | | | |
| n | Bit location to be tested | | | | | | | ○ | ○ | ○ | ○ | | | | ○ | The constant is set in decimal. | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div><div><div>• Checks the contents of the nth bit of the I/O (word or double word) specified by d, and if the result is 1, “1” is set to C (R7F0). If the result is 0, C (R7F0) is reset to “0”.</div><div>• The contents of d remains unaltered.</div></div><div><div><div><div><div>d</div><div><div><div><div>.....</div><div>n+1</div><div>n</div><div>n-1</div><div>.....</div><div>5</div><div>4</div><div>3</div><div>2</div><div>1</div><div>0</div></div></div><div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div>└─</div><div></div><div>C (R7F0)</div></div></div></div></div></div></div></div></div></div> | | | | | | | | | | | | | | | | | |
| | | | | If d is a word : | | | | Designates the bit location depending on the contents (0 to 15) of the lower 4 bits (b3 to b0) of n (WX, WY, WR, WL, WM, TC). (Upper bits are ignored and considered 0.) The n (constant) can be set to 0 to 15 (decimal). | | | | | | | | | |
| If d is a double word : | | | | Designates the bit location depending on the contents (0 to 31) of the lower 5 bits (b4 to b0) of n (WX, WY, WR, WL, WM, TC). (Upper bits are ignored and considered 0.) The n (constant) can be set to 0 to 31 (decimal). | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| <div><div><div>X00200</div><div>DIF200</div><div></div></div><div><div>BSET (DR0100, WX0000)</div><div>BRES (DR0102, WX0000)</div><div>BTS (DR0104, WX0000)</div><div>R000 = R7F0</div></div></div> | | | | <div><div>LD X00200</div><div>AND DIF200</div><div>[</div><div>BSET (DR0100, WX0000)</div><div>BRES (DR0102, WX0000)</div><div>BTS (DR0104, WX0000)</div><div>R000 = R7F0</div><div>]</div></div> | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |

BTS (d, n)


Program description

When WX0000 = H1234 at the rising edge of X00200 (WX0000 = 0001001000110100)
20 (decimal)


If DR0100 = H00000000, DR0102 = HFFFFFFFF and DR0104 = H5555AAAA are set, the 20th bit of DR0100 is set to “1” by the BSET at the rising edge of X00200.





Also, the 20th bit of DR0102 is reset to “0” by BRES.




Also, the 20th bit of DR0104 is checked by BTS.



BTS (d, n)


| Item number | Application commands-4 | Name | | | | Shift right | | | | | | | | | |
|--|------------------------------|-----------------|------|---------|-----------------------------------|-------------|----------------------|------------|------------|-------------|-----------------|------------|---------------------------------|---------------------------------|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| SHR (d, n) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | ● | ● | ● | ● | ↑ | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | Number of steps | | | | | 17 | ← | 19 | ← | 90 | ← | | | |
| SHR (d, n) | | Condition | | | Steps | | 18 | ← | 53 | ← | 71 | ← | | | |
| | | — | | | 3 | | | | 21 | ← | | | | | |
| | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| d | I/O to be shifted | | | | | | ○ | ○ | ○ | | ○ | ○ | | | |
| n | Number of bits to be shifted | | | | | ○ | ○ | ○ | ○ | | | | ○ | The constant is set in decimal. | |
| Function | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">Shifts the contents of d to the right (toward the lower digits) by n bits.Sets n bits of SD (R7F2) contents starting with the most significant bit.Sets the content of the nth bit from the least significant bit in C (R7F0). | | | | | | | | | | | | | | | |
| Before execution | | | | | | | | | | | | | | | |
|  | | | | | | | | | | | | | | | |
| After execution | | | | | | | | | | | | | | | |
|  | | | | | | | | | | | | | | | |
| If d is a word : Designates the shift amount, depending on the contents (0 to 15) of the lower 4 bits (b3 to b0) of n (WX, WY, WR, WL, WM, TC). (Upper bits are ignored and considered 0.) The n (constant) can be set to 0 to 15 (decimal). | | | | | | | | | | | | | | | |
| If d is a double word : Designates the shift amount, depending on the contents (0 to 31) of the lower 5 bits (b4 to b0) of n (WX, WY, WR, WL, WM, TC). (Upper bits are ignored and considered 0.) The n (constant) can be set to 0 to 31 (decimal). | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">If n is equal to 0, the shift is not performed. The previous state is retained in C. | | | | | | | | | | | | | | | |

Program example




Program description

- There exists a conveyor that has 16 stands and is moving to the right.
- Each time the conveyor moves one stand to the right, a pulse input enters X00001.
- There is a sensor on the left end of the conveyor, and when a defective unit is placed on the conveyor, X00000 turns on. X00000 (sensor input) and X00001 (conveyor movement) signals are as follows:



- As the conveyor moves to the right, the data is also shifted one bit at a time, and when data exits to the carry (on the right end of the conveyor), the (Y00100) solenoid valve turns on and rejects the defective unit.



SHR(d,n)


| Item number | Application commands-5 | Name | | | | Shift left | | | | | | | | | |
|---------------------|------------------------------|---|------|---------|-----------------------------------|------------|----------------------|------------|------------|-------------|-----------------|------------|---------------------------------|---------------------------------|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| SHL (d, n) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | ● | ● | ● | ● | ↑ | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | Number of steps | | | | | 16 | ← | 19 | ← | 90 | ← | | | |
| SHL (d, n) | | Condition | | | Steps | | 18 | ← | 54 | ← | 71 | ← | | | |
| | | — | | | 3 | | | | 21 | ← | | 71 | ← | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| d | I/O to be shifted | | | | | | ○ | ○ | ○ | | ○ | ○ | | | |
| n | Number of bits to be shifted | | | | | | ○ | ○ | ○ | ○ | | | ○ | The constant is set in decimal. | |
| Function | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">Shifts the contents of d to the left (toward the upper digits) by n bits.Sets n bits of SD (R7F2) contents starting with the least significant bit.Sets the content of the nth bit from the most significant bit in C (R7F0). <div><div>Before execution</div><div>After execution</div><div><div><div>C (R7F0)</div><div>SD (R7F2)</div></div><div><div>Most significant bit (MSB)</div><div>Least significant bit (LSB)</div></div></div></div> <p>If d is a word : Designates the shift amount, depending on the contents (0 to 15) of the lower 4 bits (b3 to b0) of n (WX, WY, WR, WL, WM, TC). (Upper bits are ignored and considered 0.) The n (constant) can be set to 0 to 15 (decimal).</p> <p>If d is a double word : Designates the shift amount, depending on the contents (0 to 31) of the lower 5 bits (b4 to b0) of n (WX, WY, WR, WL, WM, TC). (Upper bits are ignored and considered 0.) The n (constant) can be set to 0 to 31 (decimal).</p> | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">If n is equal to 0, the shift is not performed. The previous state is retained in C. | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | |
| | | <div><div><div><div>X00000</div><div>X00001 DIF1</div><div>R7F0</div></div><div><div>R7F2</div><div>Y00100</div></div><div>SHL (DR0000 ,1)</div></div><div><pre>LD X00000 OUT R7F2 LD X00001 AND DIF1 [SHL(DR0000,1)] LD R7F0 OUT Y00100</pre></div></div> | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">The R7F2 value of the DR0000 after the shift is determined by the on/off of X00000.The content of DR0000 is shifted to the left when X00001 rises. At this time, the value of R7F2 is set in b0 and the value of b31 (b15 of WR0001) in R7F0.The Y00100 turns on/off depending on the b31 value of DR0000 (b15 of WR0001) prior to the shift. | | | | | | | | | | | | | |

SHL (d, n)

| Item number | | Application commands-6 | | | | Name | | Rotate right | | | | | | | | | |
|---|------------------------------|------------------------|--|-----------------|------|---------|-----------------------------------|--------------|-----------|----------------------|------------|-------------|-----------------|----------|---------------------------------|---------------------------------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| ROR (d, n) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ↕ | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 21 | ← | 23 | ← | 96 | | ← | |
| ROR (d, n) | | | | Condition | | | Steps | | | | | 60 | ← | | | | |
| | | | | — | | | 3 | | | 22 | ← | 25 | ← | 77 | | ← | |
| | | | | | | | | | | | | | | | | | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | Constant | Other | | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | |
| d | I/O to be rotated | | | | | | | | ○ | ○ | ○ | | ○ | ○ | | | |
| n | Number of bits to be rotated | | | | | | | ○ | ○ | ○ | ○ | | | | ○ | The constant is set in decimal. | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div><div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></</div></div></div></div></div> | | | | | | | | | | | | | | | | | |

| Item number | | Application commands-7 | | | | Name | | | | Rotate left | | | | | | | |
|--|------------------------------|------------------------|---|-----------------|-----------------------------------|------|-------|------------|----------------------|-------------|------------|------------|-----------------|---------------------------------|---------------------------------|--|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| ROL (d, n) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ↑ | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | 21 | ← | 23 | ← | 95 | ← | | | |
| ROL (d, n) | | | | Condition | | | Steps | | 22 | ← | 59 | ← | 77 | ← | | | |
| | | | | — | | | 3 | | | | 76 | ← | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| d | I/O to be rotated | | | | | | ○ | ○ | ○ | | ○ | ○ | | | | | |
| n | Number of bits to be rotated | | | | | ○ | ○ | ○ | ○ | | | | ○ | The constant is set in decimal. | | | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div><div><div></div></div></div><div><div><div></div></div><div><div></div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div> <div><div><</div></div> | | | | | | | | | | | | | | | | | |


Program example



Program description

- When X00001 rises, the 64 bit data is shifted one bit at a time.
The open area after the shift is filled with “0.”

Overall movement



ROL (d, n)

| Item number | | Application commands-8 | | | | Name | | Logical shift right | | | | | | | | | |
|----------------|------------------------------|---|---|-----------------|-----------------------------------|------|-------|---------------------|----------------------|-------------|------------|------------|-----------------|---------------------------------|---------------------------------|--|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ↓ | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | 16 | ← | 18 | ← | 89 | ← | Upper case: W Lower case: DW | | |
| LSR (d, n) | | | | Condition | | | Steps | | | | 53 | ← | | ← | | | |
| | | | | — | | | 3 | | 18 | ← | 20 | ← | 71 | ← | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| d | I/O to be shifted | | | | | | ○ | ○ | ○ | | ○ | ○ | | | | | |
| n | Number of bits to be shifted | | | | | ○ | ○ | ○ | ○ | | | | ○ | The constant is set in decimal. | | | |
| Function | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">Shifts the contents of d to the right (toward the lower digits) by n bits.“0” is set from the most significant bit to the nth bit.The content of the nth bit from the least significant bit is set in C (R7F0). <div><div>Before execution</div><div><div><div>d</div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></</div></div></div></div> | | | | | | | | | | | | | | | |

LSR (d, n)

LSL (d, n)

| Item number | | Application commands-9 | | | | Name | | Logical shift left | | | | | | | | | |
|--|------------------------------|------------------------|--|-----------------|------|---------|-----------------------------------|--------------------|-----------|----------------------|------------|-------------|-----------------|----------|---------------------------------|---------------------------------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| LSL (d, n) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ↓ | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 16 | ← | 18 | ← | 89 | | ← | |
| LSL (d, n) | | | | Condition | | | Steps | | | | | 53 | ← | | | | |
| | | | | — | | | 3 | | | 18 | ← | 20 | ← | 71 | | ← | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | Constant | Other | | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | |
| d | I/O to be shifted | | | | | | | | ○ | ○ | ○ | | ○ | ○ | | | |
| n | Number of bits to be shifted | | | | | | | | ○ | ○ | ○ | ○ | | | ○ | The constant is set in decimal. | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div><div>• Shifts the contents of d to the left (toward the upper digits) by n bits.</div><div>• 0 is set from the least significant bit to the nth bit.</div><div>• The content of the nth bit from the most significant bit is set in C (R7F0).</div></div><div><div>Before execution</div><div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div></div></div></div> | | | | | | | | | | | | | | | | | |

| Item number | | Application commands-10 | | | | Name | | BCD shift right | | | | | | | | | |
|---|--------------------------------|-------------------------|--|---|------|---------|-----------------------------------|-----------------|-----------|----------------------|------------|-------------|-----------------|----------|---------------------------------|---------------------------------|---|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| BSR (d, n) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 15 | ← | 17 | ← | 88 | ← | | |
| BSR (d, n) | | | | Condition | | | Steps | | | 17 | ← | 52 | ← | 70 | ← | | |
| | | | | — | | | 3 | | | | | 20 | ← | | | 70 | ← |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | Constant | Other | | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | |
| d | I/O to be shifted | | | | | | | | ○ | ○ | ○ | | ○ | ○ | | | |
| n | Number of digits to be shifted | | | | | | | ○ | ○ | ○ | ○ | | | | ○ | The constant is set in decimal. | |
| Function | | | | | | | | | | | | | | | | | |
| <div>• Shifts the contents of d to the right (toward the lower digits) by n digits (1 digit is equivalent to 4 bits).</div> <div>• 0 is set from the most significant bit to the nth digit.</div> <div>• The digits from least significant bit to the nth digit are discarded.</div> <div><div>Before execution</div><div>After execution</div><div><div>0</div>→<div>0000</div>←<div>0000</div></div><div>MSB</div><div>LSB</div><div>Discarded</div></div> <div>If d is a word : Designates the shift amount, depending on the contents (0 to 3) of the lower 2 bits (b1, b0) of n (WX, WY, WR, WL, WM, TC). (Upper bits are ignored and considered “0”). The n (constant) can be set to 0 to 3 (decimal).</div> <div>If d is a double word : Designates the shift amount, depending on the contents (0 to 7) of the lower 3 bits (b2 to b0) of n (WX, WY, WR, WL, WM, TC). (Upper bits are ignored and considered “0”). The n (constant) can be set to 0 to 7 (decimal).</div> | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| <div>• If n is equal to 0, the shift is not performed.</div> | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| <div><div>X00001</div><div>DIF1</div><div>BSR (WR0000 ,1)</div></div> | | | | <div>LD X00001</div> <div>AND DIF1</div> <div>[</div> <div>BSR (WR0000 ,1)</div> <div>]</div> | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| <div>• When X00001 rises, the content of WR0000 is regarded as BCD code and shifted to the right by four bits. At this time, the values in the lower 4 bits (b3 to b0) are deleted and “0000” is set in the upper four bits (b15 to b12).</div> <div><div>H 1 2 3 ④</div><div>0001 0010 0011 0100</div><div>Before the shift</div><div>→</div><div>H ① 1 2 3</div><div>0000 0001 0010 0011</div><div>After the shift</div><div>Deleted</div><div>Set to "0"</div></div> | | | | | | | | | | | | | | | | | |

BSL (d, n)

| Item number | Application commands-11 | Name | | | | BCD shift left | | | | | | | | | |
|-------------------------|--------------------------------|--|------|---------|-----------------------------------|----------------|----------------------|------------|------------|-------------|-----------------|----------|---------------------------------|-------|---|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| BSL (d, n) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | Number of steps | | | | | 15 | ← | 17 | ← | 88 | ← | | | |
| BSL (d, n) | | Condition | | | Steps | | 17 | ← | 52 | ← | 70 | ← | | | |
| | | — | | | 3 | | | | 20 | ← | | | | 69 | ← |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | DR, DL, DM | | |
| d | I/O to be shifted | | | | | | ○ | ○ | ○ | | ○ | ○ | | | |
| n | Number of digits to be shifted | | | | | ○ | ○ | ○ | ○ | | | ○ | The constant is set in decimal. | | |
| Function | | | | | | | | | | | | | | | |
| Function | | <div><ul style="list-style-type: none">Shifts the contents of d to the left (toward the upper digits) by n digits (1 digit is equivalent to 4 bits).0 is set from the least significant bit to the nth digit.The digits from the most significant bit to the nth digit are discarded.<div><div>Before execution</div><div>After execution</div><div>Discarded</div><div>Most significant bit (MSB)</div><div>Least significant bit (LSB)</div></div></div> | | | | | | | | | | | | | |
| If d is a word : | | Designates the shift amount, depending on the contents (0 to 3) of the lower 2 bits (b1, b0) of n (WX, WY, WR, WL, WM, TC). (Upper bits are ignored and considered “0”). The n (constant) can be set to 0 to 3 (decimal). | | | | | | | | | | | | | |
| If d is a double word : | | Designates the shift amount, depending on the contents (0 to 7) of the lower 3 bits (b2 to b0) of n (WX, WY, WR, WL, WM, TC). (Upper bits are ignored and considered “0”). The n (constant) can be set to 0 to 7 (decimal). | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | |
| Cautionary notes | | <ul style="list-style-type: none">If n is equal to 0, the shift is not performed. | | | | | | | | | | | | | |
| Program example | | <div><div><div>X00001</div><div>DIF1</div><div>BSL (WR0000 ,1)</div></div><div><div>LD X00001</div><div>AND DIF1</div><div>[BSL (WR0000 ,1)</div><div>]</div></div></div> | | | | | | | | | | | | | |
| Program description | | <div><ul style="list-style-type: none">When X00001 rises, the content of WR0000 is regarded as BCD code and shifted to the left by four bits. At this time, the data of the lower 4 bits are deleted and “0000” is set in the upper four bits.<div><div>Before the shift</div><div>After the shift</div></div></div> | | | | | | | | | | | | | |

| Item number | | Application commands-12 | | | | Name | | Batch shift right (SHIFT RIGHT BLOCK) | | | | | | |
|--|--------------------------------------|-------------------------|-----|-----------------|---------|-----------------------------------|-------|---------------------------------------|----------------------|--------------------------|-----------------|--------------------------------|-------|---------------------------------|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | Remark | | |
| WSHR (d, n) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | EH-CPU***A | Other than left | Upper case: B Lower case: W | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | EH-CPU3** | | | | |
| | | | | ⇕ | ● | ● | ● | ● | Ave | Ave | Ave | | | |
| Command format | | | | Number of steps | | | | | 31.3+0.08n | Note.1(margin) | 45.1+0.08n | | | |
| WSHR (d, n) | | | | Condition | | | Steps | | | 54.6+0.09n | | | | |
| | | | | — | | | 3 | | 23.1+0.08n | 22.5+0.76n 64.6+0.75n | 57+0.8n | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | Constant | Other | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | | | DY |
| d | Head I/O to be shifted | | | | | ○ | | | ○ | | | | | |
| n | Number of bits (words) to be shifted | | | | | | | ○ | ○ | ○ | ○ | | ○ | The constant is set in decimal. |
| Function | | | | | | | | | | | | | | |
| <div><div><div>• Shifts n bits (words) between d and d + n – 1 to the right (toward smaller I/O number) by one bit (word).</div><div>• 0 (H0000) is set to the d + n – 1 bit (word).</div><div>• The content of d is discarded.</div></div><div><div><div>Before execution</div><div>After execution</div></div><div><div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div></div></div></div></div> | | | | | | | | | | | | | | |

Note.1: 28.9+1.32*(n/16)

| Item number | | Application commands-13 | | | | Name | | Batch shift left (SHIFT LEFT BLOCK) | | | | | | |
|----------------|--------------------------------------|---|---|-----------------|-----------------------------------|-------|------|-------------------------------------|----------------------|--------------------------|-----------------|--------------------------------|--------|---------------------------------|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | Remark | |
| WSHL (d, n) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | EH-CPU***A | Other than left | Upper case: B Lower case: W | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | EH-CPU3** | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Ave | Ave | | | |
| Command format | | | | Number of steps | | | | | 30.7+0.11n | Note.1(margin) | 43.3+0.11n | | | |
| WSHL (d, n) | | | | Condition | | Steps | | | | 55.0+0.11n | | | | |
| | | | | — | | 3 | | | 24.1+0.75n | 23.6+0.75n 64.6+0.75n | 58+0.75n | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM |
| d | Head I/O to be shifted | | | | | ○ | | | ○ | | | | | |
| n | Number of bits (words) to be shifted | | | | | | ○ | ○ | ○ | ○ | | | ○ | The constant is set in decimal. |
| Function | | | | | | | | | | | | | | |
| | | <div><div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></</div></div></div></div> | | | | | | | | | | | | |

Note.1: 28.7+1.60*(n/16)

| Item number | | Application commands-14 | | | | Name | | Batch shift right (BCD SHIFT RIGHT BLOCK) | | | | | | | |
|---|-------------------------------|-------------------------|---|---------|-----------------------------------|-----------------|------|---|-------|-------------|----------------------|------------|-----------------|---------------------------------|-----------|
| Ladder format | | | | | | Condition code | | | | | Processing time (μs) | | | Remark | |
| WBSR (d, n) | | | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | EH-CPU***A | Other than left | | |
| | | | | | | DER | ERR | SD | V | C | EH-CPU5** | EH-CPU3** | | | |
| | | | | | | ↑ | ● | ● | ● | ● | Ave | Ave | Ave | | |
| Command format | | | | | | Number of steps | | | | | 23.6+1.3n | | | | 57.5+1.3n |
| WBSR (d, n) | | | | | | Condition | | | Steps | | | | | | |
| | | | | | | — | | | 3 | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| d | Head I/O to be shifted | | | | | | | ○ | | | | | | | |
| n | Number of words to be shifted | | | | | ○ | ○ | ○ | ○ | | | | ○ | The constant is set in decimal. | |
| Function | | | | | | | | | | | | | | | |
| <div><div><div>• Shifts n words between d and d + n – 1 to the right (toward smaller I/O number) by one digit (1 digit is equivalent to 4 bits) as BCD data.</div><div>• 0 is set to the most significant digit of d + n – 1.</div><div>• The content of the least significant digit of d is discarded.</div></div><div><div><div>Before execution</div><div><div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div></div></div></div></div></div> | | | | | | | | | | | | | | | |

| Item number | | Application commands-15 | | | | Name | Batch shift left (BCD SHIFT LEFT BLOCK) | | | | | | | | | |
|--|-------------------------------|-------------------------|------|---------|-----------------------------------|------|---|------------|-------------|-----------------|-----------|--------|---------------------------------|------------|--|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | Remark | | | | |
| WBSL (d, n) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | EH-CPU***A | | Other than left | | | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | EH-CPU3** | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Ave | | Ave | | | | | | |
| Command format | | Number of steps | | | | | 23.8+1.4n | | 23.2+1.35n | | 57.5+1.4n | | | | | |
| WBSL (d, n) | | Condition | | | Steps | | | | 64.6+1.4n | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | Double word | | Constant | Other | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | | | DY | DR, DL, DM | | |
| d | Head I/O to be shifted | | | | | | | ○ | | | | | | | | |
| n | Number of words to be shifted | | | | | ○ | ○ | ○ | ○ | | | ○ | The constant is set in decimal. | | | |
| Function | | | | | | | | | | | | | | | | |
| <div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></</div></div></div> | | | | | | | | | | | | | | | | |

| Item number | Application commands-16 | Name | | | | Block transfer (MOVE) | | | | | | | | |
|---------------|--|--|------|---------|-----------------------------------|-----------------------|----------------------|----------------|--------------------|--------------------------------|----|----------|--------------------|---------------------------------|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | Remark | | | | |
| MOV (d, s, n) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | EH-CPU***A | Other than left | | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | EH-CPU3** | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Ave | Ave | | | | | |
| Command forma | | Number of steps | | | | | 172+112a | Note.1(margin) | 245+164a | Upper case: B Lower case: W | | | | |
| MOV (d, s, n) | | Condition | | | Steps | | a:Quotient of n/32 | 260+165a | a:Quotient of n/32 | | | | | |
| | | — | | | 4 | | 148+80b | Note.2(margin) | 264+91b | | | | b:Quotient of n/64 | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM |
| d | Transfer destination head I/O | | | ○ | | | | ○ | | | | | | |
| s | Transfer source head I/O | | | ○ | | | | ○ | | | | | | |
| n | Number of bits (words) to be transferred | | | | | ○ | ○ | ○ | ○ | | | | ○ | The constant is set in decimal. |
| Function | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">Transfers n bits (words) between s and s + n – 1 to d + n – 1.The values between s and s + n – 1 are retained. However, if the transfer source and transfer destination ranges overlap, the transferred values will be used. | | | | | | | | | | | | |
| | | <div><div>Before execution</div><div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></</div></div></div></div> | | | | | | | | | | | | |

Note.1 : 57.33+112a(a:Quotient of n/32)+2.9b(b: Remainder of n/32)

59.9+112a(a: Quotient of n/32)+3b

With no specification of an index.

Those of an index with specification.

Note.2 : 58.3+80a(a:Quotient of n/64)+2.2b(b: (Remainder of n/64) / Quotient of 2)


62.2+80a(a: Quotient of n/64)+2.2b(b: (Remainder of n/64) / Quotient of 2)

With no specification of an index.

Those of an index with specification.

Program example



- The data in the first link area (WL020 to WL05F) is transferred to the second link area (WL1000 to WL103F).



```
LD    R001
AND   DIF0
[
MOV   (WL1000,WL020,64)
]
LD    R7F4
SET   Y00100
```

Program description

- 64 words of data are transferred from link system 1 of the first link to link system 2 of the second link. WL020 to WL05F and WL1000 to WL103F are used as the respective transfer areas.



MOV (d,s,n)

| Item number | Application commands-17 | Name | | | | Copy | | | | | | | |
|---|-------------------------------------|-----------------|------|---------|-----------------------------------|------|----------------------|----------------|--------------------|--------------------------------|----|----------|---------------------------------|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | Remark | | | |
| COPY (d, s, n) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | EH-CPU***A | Other than left | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | EH-CPU3** | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Ave | Ave | | | | |
| Command format | | Number of steps | | | | | 97+64a | Note.1(margin) | 124+95a | Upper case: B Lower case: W | | | |
| COPY (d, s, n) | | Condition | | Steps | | | a:Quotient of n/32 | 137+95a | a:Quotient of n/32 | | | | |
| | | — | | 4 | | | b:Quotient of n/64 | Note.2(margin) | 174+46b | b:Quotient of n/64 | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | |
| d | Copy destination head I/O | | | ○ | | | | ○ | | | | | |
| s | Copy source head I/O | ○ | ○ | ○ | | ○ | ○ | ○ | ○ | | | ○ | |
| n | Number of bits (words) to be copied | | | | | ○ | ○ | ○ | ○ | | | ○ | The constant is set in decimal. |
| Function | | | | | | | | | | | | | |
| <div><div><div><div></div><div>s</div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></</div></div></div></div> | | | | | | | | | | | | | |

Note.1 : 45.48+63.0a(a:Quotient of n/32)+1.6b(b: Remainder of n/32) d,s is at the time of R. Without index specification.

46.75+2.14a(a: Quotient of n/16) d,s is at the times other than R. Without index specification.

47.48+63.0a(a:Quotient of n/32)+1.6b(b: Remainder of n/32) d,s is at the time of R. With index specification.

34.85+2.14a(a: Quotient of n/16) d,s is at the times other than R. With index specification.

65.98+61.0a(a:Quotient of n/32)+1.6b(b: Remainder of n/32) d,s is at the time of R. Without index specification.

67.28+2.20a(a: Quotient of n/16) d,s is at the times other than R. Without index specification.

69.98+61.0a(a:Quotient of n/32)+1.6b(b: Remainder of n/32) d,s is at the time of R. With index specification.

70.28+2.20a(a: Quotient of n/16)+3b d,s is at the times other than R. With index specification.

Note.2 : 37.68+1080a(a:Quotient of n/2)

39.68+0.80a(a: Quotient of n/2)

56.24+0.81a(a:Quotient of n/2)

60.24+0.81a(a: Quotient of n/2)

* Please refer to FUN 120-123 about index specification.

Copy source : Constant


Copy source : I/O

Copy source : Constant

Copy source : I/O

Program example


The default value (H2020) is set in the range of WR0100 to WR01FE.



Program description

WR0100 to WR01FE is considered as the communication data area and is filled with space codes (H20) as the default value during the first scan after RUN commencement.

R7E3: The first scan ON after RUN



| Item number | | Application commands-18 | | | | Name | | Block exchange (EXCHANGE) | | | | | | | | | |
|--|--|-------------------------|--|-----------------|------|---------|-----------------------------------|---------------------------|-----------|---|-----------------|-------------|--------------------------------|---------------------------------|-------|------------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | Remark | | | |
| XCG (d1, d2, n) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | EH-CPU***A | Other than left | | Upper case: B Lower case: W | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | EH-CPU3** | | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Ave | Ave | | | | | | |
| Command format | | | | Number of steps | | | | | | 44.1+2.5n | | 42.2+2.53n | | 76.0+3.1n | | | |
| XCG (d1, d2, n) | | | | Condition | | | Steps | | | 89.9+3.1n | | | | | | | |
| | | | | — | | | 4 | | | 40.1+1.4n | | 39.9+1.4n | | | | 116+1.9n | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | Constant | Other | | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | |
| d1 | Block exchange (EXCHANGE) | | | | | ○ | | | ○ | | | | | | | | |
| d2 | Exchange source head I/O | | | | | ○ | | | ○ | | | | | | | | |
| n | Number of bits (words) to be exchanged | | | | | | ○ | ○ | ○ | ○ | | | ○ | The constant is set in decimal. | | | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div><div>• Exchanges the contents of the n bits from d1 to d1 + n - 1 and the contents between d2 and d2 + n - 1.</div><div>• Bits are exchanged with bits and words are exchanged with words.</div></div><div><div><div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div></div><div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div></div><div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div></div> <div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div></div> <div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div> <div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div> <div><div>If n is a word: The contents (0 to 255) of the lower 8 bits (b7 to b0) of n (WX, WY, WR, WL, WM, TC) are set to the number of bits (words) to be exchanged.</div><div>If n is a constant: 0 to 255 (decimal) can be designated for the number of bits (words) to be exchanged.</div></div> | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| <div><div><div>• Use this command so that d1 + n - 1 and d2 + n - 1 do not exceed the I/O range *. If the I/O range is exceeded, DER is equal to “1” and the exchange is performed up to the maximum range with respect to the smaller number of bits (words) specified in d1 and d2.</div><div>* For I/O ranges, refer to the P3-6 and P3-7 performance specification table.</div><div>• If n is equal to 0, the block exchange is not performed and DER (R7F4) will be “0”.</div></div></div> | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| <div><div><div>X00001</div><div>DIF1</div></div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div><div><div>XCG (WL000, WL1000, 255)</div></div></div> | | | | | | | | | | <div><div>LD X00001</div><div>AND DIF1</div><div>[</div><div>XCG (WL000, WL1000, 255)</div><div>]</div></div> | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| <div><div><div><div>• When X00001 rises, the contents of WL000 to WL0FE are exchanged with the contents of WL1000 to WL10FE.</div></div><div><div><div><div><div>WL000</div><div>H0000</div><div>⋮</div><div>H0000</div></div><div>WL0FE</div></div><div>WL000</div><div>HFFFF</div><div>⋮</div><div>HFFFF</div></div><div>WL0FE</div></div><div><div><div>WL1000</div><div>HFFFF</div><div>⋮</div><div>HFFFF</div></div><div>WL10FE</div></div><div>WL1000</div><div>H0000</div><div>⋮</div><div>H0000</div></div><div>WL10FE</div></div> <div><div>Before execution</div><div>After execution</div></div> | | | | | | | | | | | | | | | | | |

| Item number | | Application commands-19 | | | | Name | | NOT | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--------------------|-------------------------|-----|---|---------|-----------------------------------|------|--------------|----------------------|--|-------------|-----|-----------------|----------|---------------------------------|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| NOT (d) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | 11 | ← | 10 | ← | 80 | ← | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| NOT (d) | | | | Condition | | Steps | | | | | 45 | ← | | ← | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | — | | 2 | | | 13 | ← | 12 | ← | 61 | ← | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| d | I/O to be reversed | | | | ○ | ○ | | ○ | ○ | | ○ | ○ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ● Reverses the contents of d. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Before execution | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | <table><tr><td>1</td><td>1</td><td>1</td><td>1</td><td>0</td><td>0</td><td>0</td><td>0</td><td>1</td><td>1</td><td>1</td><td>1</td><td>0</td><td>0</td><td>0</td><td>0</td></tr></table> | | | | | | | | | | | | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | | | | | | | | | | | | | | | | |
| 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| After execution | | | | <table><tr><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td></tr><tr><td>0</td><td>0</td><td>0</td><td>0</td><td>1</td><td>1</td><td>1</td><td>1</td><td>0</td><td>0</td><td>0</td><td>0</td><td>1</td><td>1</td><td>1</td><td>1</td></tr></table> | | | | | | | | | | | | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 |
| ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ● Use edge trigger as the startup condition for this command. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table><tr><td colspan="2">R000</td><td colspan="2">DIF0</td><td colspan="2">NOT (WR0000)</td></tr></table> | | | | R000 | | DIF0 | | NOT (WR0000) | | <pre>LD R000 AND DIF0 [NOT WR0000]</pre> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| R000 | | DIF0 | | NOT (WR0000) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ● When R000 rises, the content of WR0000 is reversed. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Example) If WR0000 is H1234, WR0000 = HEDCB after the command is executed; WR0000 = H1234 when executed again | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

NOT (d)

| Item number | Application commands-20 | Name | | Two's complement (NEGATE) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---------------------|-------------------------|---|------|---------------------------|-----------------------------------|------|------------------------|------------|-------------------------|-------------|-----------------|----------|---------------------------------|------------|---|------|------|--------------|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|---|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| NEG (d) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | Upper case: W Lower case: DW | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | DER | ERR | SD | V | C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Command format | | Number of steps | | | | | 12 | ← | 11 | ← | 80 | ← | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| NEG (d) | | Condition | | | Steps | | | | 45 | ← | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | — | | | 2 | | | | 13 | ← | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | 62 | ← | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| d | I/O to take complement | | | | | | ○ | ○ | | | ○ | ○ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">Calculates two's complements of d (Reverses each bit contained in d and adds 1. However, C (R7F0) remains unchanged). | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Before execution | | <table><tr><td>1</td><td>1</td><td>0</td><td>0</td><td>1</td><td>1</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>1</td><td>1</td><td>0</td><td>1</td><td>0</td></tr><tr><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td><td>↓</td></tr><tr><td>0</td><td>0</td><td>1</td><td>1</td><td>0</td><td>0</td><td>1</td><td>1</td><td>1</td><td>1</td><td>1</td><td>0</td><td>0</td><td>1</td><td>0</td><td>1</td></tr><tr><td colspan="15"></td><td>1</td></tr></table> | | | | | | | | | | | | | | 1 | 1 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 1 | 0 | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | 0 | 0 | 1 | 1 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 1 | 0 | 1 | | | | | | | | | | | | | | | | 1 |
| 1 | 1 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 1 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | ↓ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 0 | 1 | 1 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 1 | 0 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| After execution | | <table><tr><td>0</td><td>0</td><td>1</td><td>1</td><td>0</td><td>0</td><td>1</td><td>1</td><td>1</td><td>1</td><td>1</td><td>0</td><td>0</td><td>1</td><td>1</td><td>0</td></tr></table> | | | | | | | | | | | | | | | 0 | 0 | 1 | 1 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 1 | 1 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 0 | 1 | 1 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 1 | 1 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">Use edge trigger as the startup condition for this command. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <table><tr><td>R000</td><td>DIF0</td><td>NEG (WR0000)</td></tr></table> <div>LD R000 AND DIF0 [NEG WR0000]</div> | | | | | | | | | | | | | | R000 | DIF0 | NEG (WR0000) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| R000 | DIF0 | NEG (WR0000) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">When R000 rises, 2's complement of the content of WR0000 is obtained. <div>Example) If WR0000 is H1234, WR0000 = HEDCC after the command is executed; WR0000 = H1234 when executed again</div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

NEG (d)

ABS (d, s)

| Item number | | Application commands-21 | | | | Name | | Absolute value | | | | | | | | | |
|--|------------------------------------|-------------------------|-----|-----------------|---------|-----------------------------------|-------|----------------|----------------------|-------------|------------|-----|-----------------|-------|---------------------------------|------------|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| ABS (d, s) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ↑ | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | 13 | ← | 15 | ← | 85 | ← | | | |
| ABS (d, s) | | | | Condition | | | Steps | | 13 | ← | 50 | ← | 85 | ← | | | |
| | | | | Word | | | 3 | | | | 21 | | | | | | |
| | | | | Double word | | | 4 | | 16 | ← | 70 | ← | 71 | ← | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | | DR, DL, DM | |
| d | I/O after absolute value is taken | | | | | | | ○ | ○ | | | ○ | ○ | | | | |
| s | I/O before absolute value is taken | | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | | | | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div><div>• Given s is signed, set the absolute value of s in d.</div><div>• If s is positive or 0: The content of s is set to d. C (R7F0) is set to “0”.</div><div>• If s is negative: Two’s complements of the contents of s are set in d. C (R7F0) is set to “1”.</div><div>• Perform with d and s as both words or both double words.</div></div><div><div>Example)</div><div><div><div><div><div></div><div>R000</div><div>DIF0</div></div><div></div><div>ABS(WR0000, WX0000)</div></div></div><div><div>(When the value of WX is positive or 0)</div><div>WX0000 = H4C1A</div><div><div><div><div>WX0000</div><div>s</div><div>01001100000011010</div><div>0</div><div>R7F0</div></div><div>↓</div><div><div><div>WR0000</div><div>d</div><div>01001100000011010</div><div>0</div></div></div></div><div><div>(When the value of WX is negative)</div><div>WX0000 = HCC1A</div><div><div><div><div>WX0000</div><div>s</div><div>11001100000011010</div><div>0</div><div>R7F0</div></div><div>↓</div><div><div><div>001100110011001100110011</div><div>+</div><div>001100110011001100110</div><div>1</div><div>WR0000</div><div>d</div></div></div></div></div></div></div></div></div></div></div> | | | | | | | | | | | | | | | | | |
| <div><div><div>• When s is a word: 0 to 32,767 (decimal) correspond to H0000 to H7FFF (hexadecimal). -32,768 to -1(decimal) correspond to H8000 to HFFFF (hexadecimal).</div><div>• When s is a double word: 0 to 2,147,483,647 (decimal) correspond to H00000000 to H7FFFFFFF (hexadecimal). -2,147,483,648 to -1 (decimal) correspond to H80000000 to HFFFFFFF (hexadecimal).</div></div></div> | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| <div><div>• Use edge trigger as the startup condition for this command.</div></div> | | | | | | | | | | | | | | | | | |

| Item number | | Application commands-22 | | | | Name | | Sign addition (SIGN GET) | | | | | | | | | |
|---|------------------------------------|-------------------------|---|-----------------|-----------------------------------|------|-------|--------------------------|----------------------|-----|------------|----------|-----------------|------------|---------------------------------|--|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| SGET (d, s) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | 13 | ← | 15 | ← | 85 | ← | | | |
| SGET (d, s) | | | | Condition | | | Steps | | 16 | ← | 20 | ← | 70 | ← | | | |
| | | | | Word | | | 3 | | | | 69 | ← | | | | | |
| | | | | Double word | | | 4 | | | | | ← | | | | | |
| Usable I/O | | Bit | | | | Word | | | Double word | | | Constant | Other | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | |
| d | I/O after absolute value is taken | | | | | | | ○ | ○ | | | ○ | ○ | | | | |
| s | I/O before absolute value is taken | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div><div><div></div><div></div><div></div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></</div></div></div> | | | | | | | | | | | | | | | | | |

EXT (d, s)

| Item number | Application commands-23 | Name | | Sign expansion (EXTEND) | | | | | | | | | | | |
|---------------------|---------------------------|---|------|-------------------------|-----------------------------------|------|----------------------|------------|------------|-------------|-----------------|----------|--------|------------|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| EXT (d, s) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | Number of steps | | | | | 15 | ← | 17 | ← | 66 | ← | | | |
| EXT (d, s) | | Condition | | | Steps | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | |
| d | I/O after sign expansion | | | | | | | | | | ○ | ○ | | | |
| s | I/O before sign expansion | | | | | ○ | ○ | ○ | ○ | | | | ○ | | |
| Function | | | | | | | | | | | | | | | |
| | | <div><ul style="list-style-type: none">The sign bit (MSB) of s is extended to the upper word of d.The lower word of d is set to the contents of s.</div> <div></div> | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | |
| | | <div></div> <div><pre>LD R000 [EXT (DR0100, WX0000)]</pre></div> | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | |
| | | <div><ul style="list-style-type: none">When R000 is turned on, the content of WX0000 is extended to DR0100.<div><div>When WX0000 is positive or 0 Example) WX0000 = H7FFF (+32767) ↓ DR0100 = H00007FFF (+32767)</div><div>When WX0000 is negative Example) WX0000 = H8000 (– 32768) ↓ DR0100 = HFFFF8000 (– 32768)</div></div></div> | | | | | | | | | | | | | |



| Item number | Application commands-24 | | | | Name | | Binary → BCD conversion | | | | | | | | | |
|----------------|-----------------------------|--|--|------|---------|-----------------------------------|-------------------------|------------------------|------------|-------------------------|-------------|-----------------|----------|---------------------------------|-------|------------|
| Ladder format | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| BCD (d, s) | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | Upper case: W Lower case: DW | | |
| | | | DER | ERR | SD | V | C | | | | | | | | | |
| | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | Number of steps | | | | | 28 | ← | 30 | ← | 139 | ← | | | |
| BCD (d, s) | | | Condition | | | Steps | | 31 | ← | 66 | ← | 191 | ← | | | |
| | | | Word | | | 3 | | | | 35 | | | | | | |
| | | | Double word | | | 4 | | | | 86 | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | Constant | | Other | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | | DR, DL, DM |
| d | I/O after conversion (BCD) | | | | | | | ○ | ○ | | | ○ | ○ | | | |
| s | I/O before conversion (BIN) | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | |
| Function | | | | | | | | | | | | | | | | |
| | | | <div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div></div><div></div></div><div><div></div><div></div></div></</div></div></div> | | | | | | | | | | | | | |

BIN (d, s)

| Item number | | Application commands-25 | | | | Name | | BCD → Binary conversion | | | | | | | | | |
|---|-----------------------------|-------------------------|-----|-----------------|---------|-----------------------------------|-------|-------------------------|------------|----------------------|-------------|-----|-----------------|----------|---------------------------------|--------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| BIN (d, s) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: W Lower case: DW | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ↕ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 19 | ← | 21 | ← | 92 | 93 | | |
| BIN (d, s) | | | | Condition | | | Steps | | | 27 | ← | 32 | ← | 83 | 201 | | |
| | | | | Word | | | 3 | | | | | 57 | | | | | |
| | | | | Double word | | | 4 | | | | | 83 | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | |
| d | I/O after conversion (BIN) | | | | | | | ○ | ○ | | | ○ | ○ | | | | |
| s | I/O before conversion (BCD) | | | | | | | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div></div><div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><</div></div></div> | | | | | | | | | | | | | | | | | |

5-115

| Item number | | Application commands-27 | | | | Name | | | | Encode | | | | |
|--|------------------------------|-------------------------|---|-----------------|-----------------------------------|------|-------|------------|-----------|-----------------------|-------------------------|--|------------------------|-------|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | Remark | |
| ENCO (d, s, n) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | EH-CPU***A | Other than left | Upper case: Bit position of less than higher 16 bits Lower case: Other than the above | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | EH-CPU3** | | | | |
| | | | | ↑ | ● | ● | ● | ↑ | Ave | Ave | Ave | | | |
| Command format | | | | Number of steps | | | | | | 33+1.4×2 ⁿ | 39.9+1.4×2 ⁿ | | 84+1.6×2 ⁿ | |
| ENCO (d, s, n) | | | | Condition | | | Steps | | | 84+1.6×2 ⁿ | 67.9+0.2×2 ⁿ | | 170+0.2×2 ⁿ | |
| | | | | — | | | 4 | | | 84+0.1×2 ⁿ | 170+0.2×2 ⁿ | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | |
| d | Decode destination head I/O | | | | | | | ○ | ○ | | | | | |
| s | Word I/O to be encoded | | | | ○ | | | | | | | | | |
| n | Number of bits to be encoded | | | | | | | | | | | ○ | 1 to 8 (decimal) | |
| Function | | | | | | | | | | | | | | |
| <div><div><div><div><div><div></div><div>s+2ⁿ-1</div></div><div><div></div><div></div></div><div><div></div><div>s+B</div></div><div><div></div><div></div></div><div><div></div><div>s</div></div><div><div></div><div></div></div></div><div><div>0</div><div></div><div>1</div><div></div><div>0</div><div>0</div><div></div></div><div>2ⁿ</div></div><div><div><div><div></div><div>b15</div></div><div><div></div><div>b7</div></div><div><div></div><div>b0</div></div></div><div><div></div><div></div><div>H0B</div></div><div>n bits (1 to 8)</div></div></div></div> | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | |
| <div><div><div><div><div><div></div><div>s+2ⁿ-1</div></div><div><div></div><div></div></div><div><div></div><div>s</div></div><div><div></div><div></div></div></div><div><div>0</div><div></div><div>1</div><div></div><div>0</div><div>0</div><div></div></div><div>2ⁿ</div></div><div><div><div><div></div><div>b15</div></div><div><div></div><div>b7</div></div><div><div></div><div>b0</div></div></div><div><div></div><div></div><div>H0B</div></div><div>n bits (1 to 8)</div></div></div></div> | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | |
| <div><div><div><div><div><div></div><div>X00001</div></div><div><div></div><div>DIF1</div></div></div><div><div></div><div>ENCO (WR0000, R000, 4)</div></div></div></div><div><div>LD X00001</div><div>AND DIF1</div><div>[</div><div>ENCO (WR0000, R000, 4)</div><div>]</div></div></div> | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | |
| <div><div><div><div><div><div></div><div>s+2ⁿ-1</div></div><div><div></div><div></div></div><div><div></div><div>s+B</div></div><div><div></div><div></div></div><div><div></div><div>s</div></div><div><div></div><div></div></div></div><div><div>0</div><div></div><div>1</div><div></div><div>0</div><div>0</div><div></div></div><div>2ⁿ</div></div><div><div><div><div></div><div>b15</div></div><div><div></div><div>b7</div></div><div><div></div><div>b0</div></div></div><div><div></div><div></div><div>H0B</div></div><div>n bits (1 to 8)</div></div></div></div> | | | | | | | | | | | | | | |

| Item number | | Application commands-28 | | | | Name | | 7 segment decode | | | | | | | | | | | | | |
|--|-----------------------------|-------------------------|---|---|------|-------------|-----------------------------------|------------------|------------------------|----------------------|------------------------|-------------|-----------------|-------------------|---|--------|--|----|--|------------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | |
| SEG (d, s) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU**A EH-CPU3** | | Other than left | | | | | | | | |
| | | | | DER | ERR | SD | V | C | | | | | | | | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | |
| Command format | | | | Number of steps | | | | | | 16 | | ← | | 68 ----- 68 | | ← | | 94 | | 98 | |
| SEG (d, s) | | | | Condition | | | Steps | | | | | | | | | | | | | | |
| | | | | — | | | 3 | | | | | | | | | | | | | | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | Constant | | Other | | | | | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | | | | | DR, DL, DM | |
| d | Decode destination head I/O | | | | | | | | | | | ○ | ○ | | | | | | | | |
| s | Decode contents | | | | | | | ○ | ○ | ○ | ○ | | | | ○ | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">The result of the content conversion of s as 1-digit 4-bit data into 4-digit 7-segment display code is output to d. | | | | | | | | | | | | | | | | | |
| <div></div> | | | | Input data (4 bits) | | Output data | | | | | | | | Display | | | | | | | |
| | | | | | | g | f | e | d | c | b | a | | | | | | | | | |
| | | | | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | | | | | | | |
| | | | | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 1 | 1 | | | | | | | |
| | | | | 2 | 0 | 1 | 0 | 1 | 1 | 0 | 1 | 1 | 2 | 2 | | | | | | | |
| | | | | 3 | 0 | 1 | 0 | 0 | 1 | 1 | 1 | 1 | 3 | 3 | | | | | | | |
| | | | | 4 | 0 | 1 | 1 | 0 | 0 | 1 | 1 | 0 | 4 | 4 | | | | | | | |
| | | | | 5 | 0 | 1 | 1 | 0 | 1 | 1 | 0 | 1 | 5 | 5 | | | | | | | |
| | | | | 6 | 0 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | 6 | 6 | | | | | | | |
| | | | | 7 | 0 | 0 | 1 | 0 | 0 | 1 | 1 | 1 | 7 | 7 | | | | | | | |
| | | | | 8 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 8 | 8 | | | | | | | |
| | | | | 9 | 0 | 1 | 1 | 0 | 1 | 1 | 1 | 1 | 9 | 9 | | | | | | | |
| | | | | A | 0 | 1 | 1 | 1 | 0 | 1 | 1 | 1 | A | A | | | | | | | |
| | | | | B | 0 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | B | B | | | | | | | |
| | | | | C | 0 | 0 | 1 | 1 | 1 | 0 | 0 | 1 | C | C | | | | | | | |
| | | | | D | 0 | 1 | 0 | 1 | 1 | 1 | 1 | 0 | D | D | | | | | | | |
| | | | | E | 0 | 1 | 1 | 1 | 1 | 0 | 0 | 1 | E | E | | | | | | | |
| F | 0 | 1 | 1 | 1 | 0 | 0 | 0 | 1 | F | F | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | |
| <div></div> | | | | <div>LD X00000 AND DIF0 [SEG (DR0002, WR0000)]</div> | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">Upon the rising of X00000, the content of WR0000 is converted to an 8-bit 4-digit 7 segment LED display data. (The most significant bit of the eight bits in each digit is always “0.”) | | | | | | | | | | | | | | | | | |

SQR (d, s)

| Item number | | Application commands-29 | | | | Name | | Square root | | | | | | | | | |
|----------------|------------------------|-------------------------|--|--|------|---------|-----------------------------------|-------------|-----------|----------------------|------------|-------------|-----------------|------------|----------|--------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| SQR (d, s) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 86 | ← | 90 | ← | 107 | | 108 | |
| SQR (d, s) | | | | Condition | | | Steps | | | | | | | | | | |
| | | | | — | | | 4 | | | | | | | | | | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| d | Square Root (BCD) | | | | | | | ○ | ○ | | | | | | | | |
| s | Take square root (BCD) | | | | | | | | | | ○ | ○ | ○ | ○ | | | |
| Function | | | | | | | | | | | | | | | | | |
| | | | | <div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></div><div><div></div></</div></div> | | | | | | | | | | | | | |

BCU (d, s)


| Item number | Application commands-31 | | | | | Name | | Swap | | | | | | | | | |
|---------------------|-------------------------|--|-----|--|---------|-----------------------------------|------|------|----------------------|-------------|------------|-----|-----------------|-------|------------|--|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| SWAP (d) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | 12 | ← | 11 | ← | 81 | 198 | | | |
| SWAP (d) | | | | Condition — | | Steps | | 45 | | | ← | | | | | | |
| | | | | | | 2 | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | |
| d | I/O to be exchanged | | | | | | | ○ | ○ | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">Switches the upper 8 bits and lower 8 bits contained in d. <div><div>(Before execution) d</div><div><div>0001110101101101</div><div></div><div>0110110100011101</div></div><div>(After execution) d</div></div> | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">Use edge trigger as the startup condition for this command. | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| | | | | <div><div><div>X00000</div><div>DIF0</div></div><div>SWAP (WR0010)</div></div> <div><div>LD X00000</div><div>AND DIF0</div><div>[</div><div>SWAP (WR0010)</div><div>]</div></div> | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">Upon rising of X00000, the upper 8 bits and lower 8 bits of WR0010 are swapped and stored in WR0010. <div><div>WR0010</div><div>H1234</div><div>Before execution</div></div> <div><div>WR0010</div><div>H3412</div><div>After execution</div></div> <div>Note)</div> <div>When there is no rising edge of DIF0, it is executed during each scan, so the upper and lower bits of WR0010 are swapped in each scan.</div> | | | | | | | | | | | | | |

FIFIT (P, n)

| Item number | Application commands-33 | Name | | | | FIFO write | | | | | | | | | |
|---|----------------------------|------|-----------------|---------|-----------------------------------|------------|------|----------------------|-----|-------------|-----|-----------------|----------|--------|--|
| Ladder format | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FIFWR (P, s) | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | |
| | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | |
| | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | | Number of steps | | | | | 25 | ← | 23 | ← | 72 | 189 | | |
| FIFWR (P, s) | | | Condition | | Steps | | | | | 67 | ← | | | | |
| | | | — | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| P | Head I/O of FIFO | | | | | | | ○ | | | | | | | |
| s | Data to be written to FIFO | | | | | ○ | ○ | ○ | ○ | | | | ○ | | |
| Function | | | | | | | | | | | | | | | |
| <div><div><div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><</div></div></div></div> | | | | | | | | | | | | | | | |

| Item number | | Application commands-34 | | | | Name | | | | FIFO read | | | | | | | | | |
|--|-------------------------------|-------------------------|--|-----|---|-----------------|-----------------------------------|------|-------|------------|----------------------|-------------|------------|------------|-----------------|-------|--------|--|--|
| Ladder format | | | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| FIFRD (P, d) | | | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | | | Number of steps | | | | | 157 | 285 | 157 | 285 | 141 | 258 | | | |
| FIFRD (P, d) | | | | | | Condition | | | Steps | | | | 232 | 360 | | | | | |
| | | | | | | — | | | 3 | | | | | | | | | | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| P | FIFO head I/O | | | | | | | | | | ○ | | | | | | | | |
| d | I/O that stores the read data | | | | | | | | | | ○ | ○ | ○ | | | | ○ | | |
| Function | | | | | | | | | | | | | | | | | | | |
| <div><div><div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div></div></div></div> | | | | | | | | | | | | | | | | | | | |


Program example



```
LD    R7E3
[
FIFIT (WR0000, 10)
]
LD    X00000
AND   DIF0
[
FIFWR (WR0000, HFF)
]
LD    X00001
AND   DIF1
[
FIFRD (WR0000, WL000)
]
```


Program description

- The FIFO buffer is set at WR0002 through WR000B during the first scan after RUN execution
- HFF is stored when X00000 rises.
- HFF is read to WL000 when X00001 rises.



| Item number | | Application commands-35 | | | | Name | | | | Unit | | | | | | | | | |
|--|------------------------------------|-------------------------|--|-----|---|-----------------|-----------------------------------|-------|------|------------|----------------------|-------------|------------|----------|-----------------|------------|--------|--|--|
| Ladder format | | | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| UNIT (d, s, n) | | | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | | | Number of steps | | | | | 30 | ← | 32 | ← | 149 | 267 | | | |
| UNIT (d, s, n) | | | | | | Condition | | Steps | | | | | | | | | | | |
| | | | | | | — | | 4 | | | | | | | | | | | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | Constant | Other | | | | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | |
| d | Unity result write destination I/O | | | | | | | | | ○ | ○ | | | | | | | | |
| s | Unity destination head I/O | | | | | | | | | | ○ | | | | | | | | |
| n | Numbers of words to be united | | | | | | | | | | | | | ○ | n=0 to 4 | | | | |
| Function | | | | | | | | | | | | | | | | | | | |
| <div><div><div><div><div></div><div></div><div></div><div></div></div><div>When n=4</div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>s</div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>s+1</div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>s+2</div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>s+3</div></div></div><div>Ignored</div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>4 bits</div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>B1</div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>B2</div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>B3</div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>B4</div></div></div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>Upper digits</div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>B4</div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>B3</div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>B2</div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>B1</div></div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>Lower digits</div></div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>When n is 0 : B1 to B4 of d are 0</div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>When n is 1 : B2 to B4 of d are 0</div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>When n is 2 : B3 to B4 of d are 0</div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>When n is 3 : B4 of d is 0</div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div> | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | |
| <div><div><div><div></div><div></div><div></div><div></div></div><div>When n=0, DER = “0” and 0 will be set in the write destination I/O.</div></div><div><div><div><div></div><div></div><div></div><div></div></div><div>When n>5, nothing is executed.</div></div></div></div> | | | | | | | | | | | | | | | | | | | |


Program example



```
LD X00001
AND DIF0
[
UNIT (WY0010, WR0000, 4)
]
```

Program description


A 4-digit BCD input display device is connected to the WY0010, and each digit displays WR0000 to WR0003 data independently. (Only the lower four bits are considered valid data for WR0000 to WR0003.)



UNIT (d, s, n)

| Item number | | Application commands-36 | | | | Name | | Distribute | | | | | | | | | |
|--|--|-------------------------|---|-----------------|-----------------------------------|------|-------|------------|-----------|----------------------|------------|------------|-----------------|-------|----------|--------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| DIST (d, s, n) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ↕ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 27 | ← | 29 | ← | 80 | 198 | | |
| DIST (d, s, n) | | | | Condition | | | Steps | | | | | | | | | | |
| | | | | — | | | 4 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| d | Distribution result write destination head I/O | | | | | | | | ○ | | | | | | | | |
| s | I/O to be distributed | | | | | | ○ | ○ | ○ | ○ | | | | ○ | | | |
| n | Number of words to be distributed | | | | | | | | | | | | | ○ | n=0 to 4 | | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div><div><div></div><div></div><div></div><div></div></div><div>When n = 4:</div><div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></</div></div></div></div> | | | | | | | | | | | | | | | | | |


Program example



```
LD X00001
AND DIF0
[
DIST (WR0000, WX0010, 4)
]
```

Program description

A 4-bit 4-digit Digit switch is connected to the WX0010, and the data for each digit is stored in WR0000 to WR0003 as independent data.



DIST (d, s, n)

| Item number | | Application commands-37 | | | | Name | | I/O address conversion | | | | | | | | | |
|---------------------|---------------------|--|-----|-----------------|---------|-----------------------------------|-------|------------------------|------------------------|----------------------|-------------------------|----------|-----------------|----------|---|--------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| ADRIO (d, s) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | Upper case: B Lower case: W | | |
| | | | | DER | ERR | SD | V | C | | | | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | | | | | 145 | 262 | | |
| ADRIO (d, s) | | | | Condition | | | Steps | | | | | | | | | | |
| | | | | — | | | 3 | | | 12 | ← | 15 49 | ← | 84 | 202 | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | |
| d | Conversion address | | | | | | | ○ | ○ | | | | | | | | |
| s | I/O to be converted | | | ○* | ○* | ○ | | ○* | ○* | ○ | | | | | *The EH-CPU104A/208A/308A/316A/448 can not be used. | | |
| Function | | | | | | | | | | | | | | | | | |
| | | ● Obtains the actual address of the I/O designated by s, and sets the result in d. | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| | | ● In the EH-104A/208a/308A/316A/448, ADRIO command External I/O(X,Y,WX,WY) . (Please see chapter 0 0.2.7 ADRIO Command, to) | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| | | <div><div><div>X00200 DIF0</div><div><div></div><div></div><div></div></div><div>ADRIO(WR0100,WR0000)</div></div><div></div><div>LD X00200 AND DIF0 [ADRIO (WR0100, WR0000)]</div></div> | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| | | ● Upon X00200 rise, the actual address of WR0000 (H3C00) is set in WR0100. After command execution, WR0100 becomes H3C00. | | | | | | | | | | | | | | | |

ADRIO (d, s)

| Item number | Control commands-1 | | | | Name | | Normal scan end | | | | | | | | | | |
|---|--------------------|-------------------------|-----|-----------------|---------|-----------------------------------|-----------------|--|------------|----------------------|-------------|-----|-----------------|-------|------------|--------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| END | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 194 | 214 | 184 | 195 | 285 | 304 | | |
| END | | | | Condition | | | Steps | | | | | 311 | 320 | | | | |
| | | | | — | | | 1 | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | Constant | Other | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">Indicates the end of a normal scan program. (The execution of this command returns to the beginning of the program, and a normal scan is executed.)This command is not necessary when there are no subroutine programs or interrupt scan programs.If there is a subroutine program or interrupting program, write this command at the end of the normal scan program.This command is used only once in a program. Do not use any startup conditions. | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">The END command is checked prior to the execution, and if there is an error, the following error codes are set in the special internal output WRF001. Also, the CPU error code “34” is set to special internal output WRF000. | | | | | | | | | | | | | | | | | |
| CPU error code | | Special internal output | | | | Error code | | Error description | | | | | | | | | |
| 34 | | WRF001 | | | | H0010 | | There is no END command. | | | | | | | | | |
| | | | | | | H0022 | | There are two or more END commands. | | | | | | | | | |
| | | | | | | H0032 | | A startup condition is used for the END command. | | | | | | | | | |
| Instruction for use | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |

END

| Item number | | Control commands-2 | | | | Name | | Scan conditional end | | | | | | | | | |
|--|--------------------|-------------------------|--|-----------------|------|------------|-----------------------------------|--|-----------|----------------------|------------|-------------|-----------------|------------|---|-----------------------------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| CEND (s) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: Conditions do not meet Lower case: Conditions meet | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 6 | ← | | | 12 | ← | Lower case: Conditions meet | |
| CEND (s) | | | | Condition | | | Steps | | | | | 13 | ← | | | | |
| | | | | — | | | 2 | | | 196 | 216 | 193 | 203 | 164 | 315 | | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| s | Scan end condition | | | ○ | ○ | ○ | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div></div><div><div></div><div></div><div></div><div></div></div></div> <ul style="list-style-type: none">If the scan end condition (s) is on, the execution of this command returns to the head of the scan program and executes the program.If (s) is off, the next command is executed.This command can only be used in normal scan programs, and can be used as many times as desired.This command can specify a startup condition. In this case, if the startup condition and (s) are both on, this command is executed. | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| <div><div></div><div><div></div><div></div><div></div><div></div></div></div> <ul style="list-style-type: none">The CEND command is checked prior to the execution, and if there is an error, the following error codes are set in the special internal output WRF001. Also, the CPU error code “34” is set to special internal output WRF000. | | | | | | | | | | | | | | | | | |
| CPU error code | | Special internal output | | | | Error code | | Error description | | | | | | | | | |
| 34 | | WRF001 | | | | H0023 | | The CEND command exists after the END command. | | | | | | | | | |
| Instruction for use | | | | | | | | | | | | | | | | | |
| <div><div></div><div><div></div><div></div><div></div><div></div></div></div> | | | | | | | | | | | | | | | | | |

| Item number | | Control commands-3 | | | | Name | | Unconditional jump (JUMP) | | | | | | | | | | | | | |
|---------------------|-------------|--------------------|--|-------------------------|---------|-----------------------------------|-------|--|------------|----------------------|-------------|-----|-----------------|----------|-------|--------------------|--|----|--|-----|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | |
| JMP n | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | |
| | | | | ● | 1] | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | |
| Command format | | | | Number of steps | | | | | | 21 | | 45 | | 21 | | 22 | | 77 | | 104 | |
| JMP n | | | | Condition | | | Steps | | | | | | | 28 | | 57 | | | | | |
| | | | | — | | | 2 | | | | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | |
| n | Code number | | | | | | | | | | | | | | ○ | 0 to 255 (Decimal) | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | |
| | | | <ul style="list-style-type: none">• If the startup condition of JMP n switches on, the control jumps the program from this command to the LBL n of the same code number. Always use JMP n and LBL n in pairs.• If the startup condition is not met, the next command will be executed.• If setting this command in conjunction with other commands in the same arithmetic-operation box, set this command at the end.• The JMP n command is valid only within the same program. (A jump to a subroutine or interrupt scan cannot be performed from a normal scan, nor vice versa.)• Nesting of JMP n commands is possible, but caution must be exercised so that an overload error does not occur. | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | |
| | | | <ul style="list-style-type: none">• This command is checked prior to the execution, and if there is an error, the following error codes are set in the special internal outputs R7F3 and WRF015. In this case, jump is not performed and the next command will be executed. | | | | | | | | | | | | | | | | | | |
| | | | | Special internal output | | Error code | | Error description | | | | | | | | | | | | | |
| R7F3=1 | | WRF015 | | | | H0015 | | There is no LBL n. | | | | | | | | | | | | | |
| | | | | | | H0040 | | A jump is attempted to a different program area. | | | | | | | | | | | | | |
| Instruction for use | | | | | | | | | | | | | | | | | | | | | |
| | | | <div><div><div><div><div></div><div>JMP n</div></div><div>Program</div></div><div><div><div></div><div>LBL n</div></div><div>Program</div></div></div><div></div></div> <ul style="list-style-type: none">• When the startup condition turns on, it jumps to LBL n.• If there is a timer within the program it jumped to, the progress value is updated, but since commands are not executed, output will not turn on even if the ON conditions are met. | | | | | | | | | | | | | | | | | | |


JMP n

| Item number | | Control commands-4 | | | | Name | | Conditional jump | | | | | | | | | |
|---|----------------|--------------------|--|-----------------|------|---------|-----------------------------------|------------------|-----------|----------------------|------------|-------------|-----------------|----------|---|------------|-----|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| CJMP n (s) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Upper case: Conditions do not meet Lower case: Conditions meet | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ● | 1] | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 6 | ← | | | 14 | ← | | |
| CJMP n (s) | | | | Condition | | | Steps | | | | | | | | | | |
| | | | | — | | | 3 | | | 22 | 46 | 25 | 26 | 31 | 60 | 59 | 105 |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | Constant | Other | | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | |
| n | Code number | | | | | | | | | | | | | ○ | 0 to 255 (Decimal) | | |
| s | Jump condition | | | ○ | ○ | ○ | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div><div><div><div><div></div></div></div></div></div></div></div></div> | | | | | | | | | | | | | | | | | |

CJMP n (s)


Syntax of JMP, CJMP

- 1) LBL n with the same code number as the code number n of the JMP command is required.




- If JMP 1 is executed when there is no LBL 1 an LBL undefined error
JMP 1 will do nothing and execute the processing of program

- 6) An overlap of JMP commands with the same code number is valid.




- 2) Jump is not permitted to outside the area in which the JMP command resides.



- When the JMP 1 command is executed, since LBL 1 is not in the normal scan area, a "jump outside the area" error will be generated. The JMP 1 command will do nothing and execute the next processing of program.
- JMP 2 to JMP 7 similar processing.

- 7) A startup condition can be programmed with respect to JMP commands.



- If a jump is performed from JMP 0 to LBL 0, programs B and C will not be executed.

- 8) The CJMP command also follows the same syntax as 1) through 7).

Note 1: When a JMP command jumps to LBL, the status of each I/O between JMP and LBL is retained.

However, the timer progress value will be updated.

In case of EH-104A/208A/308A/316A/448, when you use JMP command at the time of Timer starting, please keep in mind that the progress value is updated at time of Timer command execution.


(Please see each Timer commands, to)

- 3) Code number n of the JMP command and the LBL n with the same code number may not be overlapped.




- In the pre-operation process, the label commands ① and ② have 5 as the code numbers, so a duplicate definition error will occur.


- 4) Nesting of JMP commands is allowed.



- 5) The JMP command can jump to a location before the command itself.




- JMP 0 will jump to LBL 0, which is a location before the JMP command.
- When input X00000 turns on, the loop between LBL 0 and JMP 0 is escaped by jumping from CJMP1 (X00000) to LBL 1.
- If there is no command as CJMP 1 (X00000) to escape from the loop, the loop from LBL 0 to JMP 0 will continue endlessly.



- If X00000 turns on after X00001 turns on, the progress value of TD0 will be updated even if a jump is performed from JMP 1 to LBL 1. If X00000 remains on, TD0 will not turn on even if its progress value exceeds 100.

Note 2: If the JMP command is used in conjunction with the MCS or MCR command, the following actions will result, so exercise caution when programming.



- When JMP 2 does not jump, Y00100 will turn on when X00001 and X00002 are both on.
- When JMP 2 does jump, if X00000 is on, Y00100 will follow the on/off of X00002 regardless of the on/off of X00001.

Note 3: Do not create a circuit that jumps to outside from between MCS and MCR.

LBL n

| Item number | | Control commands-5 | | | | Name | | Label | | | | | | | | | | | | | | | |
|---------------------|-------------------------|--------------------|-----------------------------|--|---------|-----------------------------------|------|-------|----------------------|-------------|------------|----------|-----------------|--------------------|----|----------------|-------------------------|------------|-------------------|----|--------|-------|-----------------------------|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | Remark | | | | | | | | | | |
| LBL n | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | |
| Command format | | | | Number of steps | | | | | 0.05 | ← | 0.65 | ← | 1.3 | ← | | | | | | | | | |
| LBL n | | | | Condition | | Steps | | | | | | | | | | | | | | | | | |
| | | | | — | | 1 | | | | | | | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | Constant | Other | | | | | | | | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | | | | DY | DR, DL, DM | | | | | | | |
| n | Code number | | | | | | | | | | | | ○ | 0 to 255 (Decimal) | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">This command indicates the destination of the jump when the JMP n or CJMP n command is executed (n is always used in pairs).The n in the LBL n cannot be used multiple times in the same program.This command alone does not do anything.Even if a startup condition is used for LBL n, it will be ignored. | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">This command is checked prior to execution, and when there is an error, the following error code is set in the special internal output WRF001. Also, the CPU error code “34” is set to special internal output WRF000. | | | | | | | | | | | | | | | | | | | |
| | | | | <table><tr><th>CPU error code</th><th>Special internal output</th><th>Error code</th><th>Error description</th></tr><tr><td>34</td><td>WRF001</td><td>H0001</td><td>Duplicate definition of LBL</td></tr></table> | | | | | | | | | | | | CPU error code | Special internal output | Error code | Error description | 34 | WRF001 | H0001 | Duplicate definition of LBL |
| CPU error code | Special internal output | Error code | Error description | | | | | | | | | | | | | | | | | | | | |
| 34 | WRF001 | H0001 | Duplicate definition of LBL | | | | | | | | | | | | | | | | | | | | |
| Instruction for use | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | <div><div><div>R100 └─┐</div><div>JMP 0</div><div>WR0000 = WR0000 + 1</div><div>LBL 0</div></div><div><div>R100 └─┐</div><div>JMP 1</div><div>WR0000 = WR0000 - 1</div><div>LBL 1</div></div></div> <div>(00001) (00002) (00003) (00004) (00005) (00006)</div> | | | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">When R100 is on, JMP 0 will be executed but JMP 1 will not be executed. Therefore, the content of WR0000 will decrement by one during each scan.When R100 is off, JMP 0 will not be executed but JMP 1 will be executed. Therefore, the content of WR0000 will increment by one during each scan. | | | | | | | | | | | | | | | | | | | |


| Item number | | Control commands-6 | | | | Name | | FOR | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--------------------------|--------------------|-----------------------------|-----------------|---------|-----------------------------------|-------|------|------------|----------------------|-------------|-----|-----------------|----------|-------------------|----------------|-------------------------|------------|-------------------|----|--------|-------|-----------------------------|-------------------------|--|------------|-------------------|--------|--------|-------|----------------|-------|-------------------|-------|---------------------|-------|---------------------------|-------|----------------------|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | | | | | | | | | | | | |
| FOR n (s) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | ● | 1] | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | | 29 | 49 | 27 | 37 | 90 | 102 | | | | | | | | | | | | | | | | | | | | | | | | |
| FOR n (s) | | | | Condition | | | Steps | | | | | 84 | 102 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | — | | | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | | | | | | | | | | | | | | | | | |
| n | Code number | | | | | | | | | | | | | ○ | 0 to 49 (Decimal) | | | | | | | | | | | | | | | | | | | | | | | | |
| s | Number of times repeated | | | | | | | ○ | ○ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div></div><div><ul style="list-style-type: none">Jumps from the NEXT n of the same code number to this command.If the number of times repeated (s) is greater than 0, the command following the FOR n (s) is executed.If the number of times repeated (s) is equal to 0, it jumps to the command following the NEXT n.Use FOR n (s) and NEXT n in pairs. Also, place the NEXT n after FOR n.The FOR n (s) may not be used multiple times.Use the FOR n (s) and NEXT n in the same program area. (It is not allowed to include FOR n (s) in the normal scan and NEXT n in the subroutine area.)The FOR n (s) to NEXT n nesting can be made up to 5 levels.</div></div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div></div><div><ul style="list-style-type: none">This command is checked prior to execution, and when there is an error, the following error code is set in the special internal output WRF001. Also, the CPU error code “34” is set to special internal output WRF000.</div></div> <table><tr><th>CPU error code</th><th>Special internal output</th><th>Error code</th><th>Error description</th></tr><tr><td>34</td><td>WRF001</td><td>H0002</td><td>Duplicate definition of FOR</td></tr></table> <div><div></div><div><ul style="list-style-type: none">If an error is generated during the execution of the command, an error code will be set in the special internal outputs R7F3 and WRF015, and the following program will be executed.</div></div> <table><tr><th colspan="2">Special internal output</th><th>Error code</th><th>Error description</th></tr><tr><td rowspan="5">R7F3=1</td><td rowspan="5">WRF015</td><td>H0017</td><td>NEXT undefined</td></tr><tr><td>H0043</td><td>FOR to NEXT error</td></tr><tr><td>H0044</td><td>Area error for NEXT</td></tr><tr><td>H0045</td><td>FOR to NEXT nesting error</td></tr><tr><td>H0046</td><td>FOR nesting overflow</td></tr></table> | | | | | | | | | | | | | | | | CPU error code | Special internal output | Error code | Error description | 34 | WRF001 | H0002 | Duplicate definition of FOR | Special internal output | | Error code | Error description | R7F3=1 | WRF015 | H0017 | NEXT undefined | H0043 | FOR to NEXT error | H0044 | Area error for NEXT | H0045 | FOR to NEXT nesting error | H0046 | FOR nesting overflow |
| CPU error code | Special internal output | Error code | Error description | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 34 | WRF001 | H0002 | Duplicate definition of FOR | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Special internal output | | Error code | Error description | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| R7F3=1 | WRF015 | H0017 | NEXT undefined | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | H0043 | FOR to NEXT error | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | H0044 | Area error for NEXT | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | H0045 | FOR to NEXT nesting error | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | H0046 | FOR nesting overflow | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Instruction for use | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| For the command to use this, refer to NEXT n. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| Item number | | Control commands-7 | | | | Name | | NEXT | | | | | | | | | | | | | | | | | | | | | | | | |
|-------------------------|-------------------------|---|------------------------------|-----------------|---------|-----------------------------------|------|------|----------------------|-------------|------------|-----|-----------------|-------|-------------------|----------------|-------------------------|------------|-------------------|----|--------|-------|------------------------------|-------------------------|------------|-------------------|--------|--------|-------|---------------|-------|----------------------|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | | | | | | |
| NEXT n | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | | | | | | | | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | | | | | | | | | |
| | | | | ● | 1] | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | 23 | ← | 25 63 | ← | 76 | ← | | | | | | | | | | | | | | | | | | |
| NEXT n | | | | Condition | | Steps | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | — | | 2 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | | | | | | | | | | | | | | | | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | | | | | | | | | | | | | | | |
| n | Code number | | | | | | | | | | | | | ○ | 0 to 49 (Decimal) | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">Subtracts 1 from the number of times repeated (s) for the FORn(s) command of the same code number, then jumps to FORn(s). | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">This command is checked prior to execution, and when there is an error, the following error code is set in the special internal output WRF001. Also, the CPU error code “34” is set to special internal output WRF000. <table><tr><th>CPU error code</th><th>Special internal output</th><th>Error code</th><th>Error description</th></tr><tr><td>34</td><td>WRF001</td><td>H0003</td><td>Duplicate definition of NEXT</td></tr></table> <ul style="list-style-type: none">If an error is generated during the execution of the command, an error code will be set in the special internal outputs R7F3 and WRF015, and the following program will be executed. <table><tr><th>Special internal output</th><th>Error code</th><th>Error description</th></tr><tr><td rowspan="2">R7F3=1</td><td rowspan="2">WRF015</td><td>H0016</td><td>FOR undefined</td></tr><tr><td>H0046</td><td>FOR nesting overflow</td></tr></table> | | | | | | | | | | | | | | CPU error code | Special internal output | Error code | Error description | 34 | WRF001 | H0003 | Duplicate definition of NEXT | Special internal output | Error code | Error description | R7F3=1 | WRF015 | H0016 | FOR undefined | H0046 | FOR nesting overflow |
| CPU error code | Special internal output | Error code | Error description | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 34 | WRF001 | H0003 | Duplicate definition of NEXT | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Special internal output | Error code | Error description | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| R7F3=1 | WRF015 | H0016 | FOR undefined | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | H0046 | FOR nesting overflow | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Instruction for use | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <div><div><div>R000 DIF0</div><div>— — —</div></div><div>When WR0000>0</div><div>When WR0000=0</div><div>To the next program</div><div><div>WR0000=512</div><div>WR0001=0</div><div>FOR 0(WR0000)</div><div>TC0(WR0001)=0</div><div>WR0001=WR0001+1</div><div>NEXT 0</div></div></div> <ul style="list-style-type: none">When R000 is turned on, the progress value (TC n) of the timer or counter is cleared with 0 for 512 points.Once the FOR to NEXT is begun, the command keeps executing until (s) is 0.FOR0 (WR0000) performs commands after TC0 (WR0001) = 0 while WR0000>0, subtracts 1 from WR0000 at NEXT0, then jumps to FOR0 (WR0000).FOR0 (WR0000) jumps to the next command within the current box upon WR0000 = 0. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |


NEXT n

Syntax of FOR to NEXT


- 1] A NEXT command with the same code number as the code number n of the FOR command is required after the FOR command.




- 2] An overlap of FOR and NEXT commands with the same code number n is not allowed.




- 3] FOR and NEXT must be within the same area.




- 4] Use FOR to NEXT as a nest.




- 5] It is possible to escape from a FOR to NEXT loop using a jump command.




- 6] FOR to NEXT may be nested up to 5 levels. When a subroutine is included, the FOR to NEXT within the subroutine is counted.



- 7] Do not include a startup condition between FOR and NEXT. If a startup condition is required, create a circuit as shown below:



- 8] The number of repeats may be modified within the program.



- When R005 is off
Program B is executed after program A is repeated 20 times.
- When R005 is on
The repeat counter WR0010 changes to 1, and since the NEXT 1 processing subtracts 1 from it, the content of WR0010 becomes 0. Therefore, the repeating of program A is terminated and program B is executed.

| Item number | Control commands-8 | Name | | | | Call subroutine | | | | | | | | | | | | | | | | | |
|-------------------------|--------------------|--|-------------------|---------|-----------------------------------|-----------------|----------------------|------------|------------|-------------|-----------------|----------|-------------------|-------------------------|--|------------|-------------------|--------|--------|-------|--------------|-------|---------------|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | |
| CAL n | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | | | | | | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | | |
| | | ● | 1] | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | |
| Command format | | Number of steps | | | | | 19 | ← | 20 | ← | 43 | ← | | | | | | | | | | | |
| CAL n | | Condition | | | Steps | | | | | | | | | | | | | | | | | | |
| | | — | | | 2 | | | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | | | | | | | |
| n | Code number | | | | | | | | | | | ○ | 0 to 99 (Decimal) | | | | | | | | | | |
| Function | | <ul style="list-style-type: none">• If the startup condition of CAL n is on, this commands executes the subroutine program (the program sandwiched by SB n and RTS) of the same code number.• If the startup condition is off, the next program is executed.• Up to 5 levels of CAL (nesting) for another subroutine can be performed within a subroutine.• It is possible to call a subroutine from within an interrupt scan program. | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | <ul style="list-style-type: none">• If an error is generated during the execution of the command, an error code will be set in the special internal outputs R7F3 and WRF015, and the following program will be executed. <table><tr><th colspan="2">Special internal output</th><th>Error code</th><th>Error description</th></tr><tr><td rowspan="2">R7F3=1</td><td rowspan="2">WRF015</td><td>H0013</td><td>SB undefined</td></tr><tr><td>H0041</td><td>Nesting error</td></tr></table> | | | | | | | | | | | | Special internal output | | Error code | Error description | R7F3=1 | WRF015 | H0013 | SB undefined | H0041 | Nesting error |
| Special internal output | | Error code | Error description | | | | | | | | | | | | | | | | | | | | |
| R7F3=1 | WRF015 | H0013 | SB undefined | | | | | | | | | | | | | | | | | | | | |
| | | H0041 | Nesting error | | | | | | | | | | | | | | | | | | | | |
| Instruction for use | | <div><div><div>R000</div><div>Other program</div><div>END</div><div>SB n</div><div>Subroutine program</div><div>RTS</div></div><div><div>R000 turns ON</div><div>R000 tur OFF</div></div><div><ul style="list-style-type: none">• When R000 is on, a subroutine program is executed by CAL n. After the execution, the program is re-executed from the code following the CAL n.• When R000 is off, the subroutine program is not executed, and the next program is executed.</div></div> | | | | | | | | | | | | | | | | | | | | | |

CAL n

| Item number | | Control commands-9 | | | | Name | | Start subroutine program | | | | | | | | | | | | | | | | | |
|---------------------|-------------------------|--------------------|----------------------------|---|---------|-----------------------------------|------|--------------------------|------------------------|-------------|-------------------------|----------|-----------------|-------------------|----|----------------|-------------------------|------------|-------------------|----|--------|-------|----------------------------|-------|--------------|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | Remark | | | | | | | | | | | | |
| SB n | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | | | | | | | | | | | | | | | | | |
| | | | | ● | 1] | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | 0.05 | ← | 0.65 0.65 | ← | 1.3 | ← | | | | | | | | | | | |
| SB n | | | | Condition | | Steps | | | | | | | | | | | | | | | | | | | |
| | | | | — | | 1 | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | Constant | Other | | | | | | | | | | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | | | | DY | DR, DL, DM | | | | | | | | | |
| n | Code number | | | | | | | | | | | | ○ | 0 to 99 (Decimal) | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">• This command indicates the start of a subroutine program (processing is not performed).• The n in the SB n cannot be used multiple times in the same program.• Even if a startup condition is used for SB n, it will be ignored.• Always use SB n and RTS in pairs.• Code the SB n to RTS subroutine program after the END command. | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | <ul style="list-style-type: none">• This command is checked prior to execution, and when there is an error, the following error code is set in the special internal output WRF001. Also, the CPU error code “34” is set to special internal output WRF000. | | | | | | | | | | | | | | | | | | | | | |
| | | | | <table><tr><th>CPU error code</th><th>Special internal output</th><th>Error code</th><th>Error description</th></tr><tr><td rowspan="2">34</td><td rowspan="2">WRF001</td><td>H0004</td><td>Duplicate definition of SB</td></tr><tr><td>H0013</td><td>SB undefined</td></tr></table> | | | | | | | | | | | | CPU error code | Special internal output | Error code | Error description | 34 | WRF001 | H0004 | Duplicate definition of SB | H0013 | SB undefined |
| CPU error code | Special internal output | Error code | Error description | | | | | | | | | | | | | | | | | | | | | | |
| 34 | WRF001 | H0004 | Duplicate definition of SB | | | | | | | | | | | | | | | | | | | | | | |
| | | H0013 | SB undefined | | | | | | | | | | | | | | | | | | | | | | |
| Instruction for use | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | <div><div><div>END</div><div>SB 0</div><div>Subroutine 0 program</div><div>SB 1</div><div>Subroutine 0.1 program</div><div>RTS</div></div><div>SB 0 SB 1</div></div> <ul style="list-style-type: none">• When CAL 0 is executed, SB 0 to RTS is executed as a subroutine.• When CAL 1 is executed, SB 1 to RTS is executed as a subroutine. | | | | | | | | | | | | | | | | | | | | | |

| Item number | Control commands-10 | | | | | Name | | End of subroutine program (RETURN SUBROUTINE) | | | | | | | | | |
|--|---------------------|-------------------------|-----------------|------|---------|-----------------------------------|-----------------------------|---|----------------------|-------------------------|-------------|-----------------|----------|-------|------------|--|--|
| Ladder format | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | |
| RTS | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | | | |
| | | | DER | ERR | SD | V | C | | | | | | | | | | |
| | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | |
| Command format | | | Number of steps | | | | | | 17 | ← | 21 | ← | 38 | ← | | | |
| RTS | | | Condition | | | Steps | | | | | | | | | | | |
| | | | — | | | 1 | | | | | 16.7 | ← | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | Constant | Other | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div></div><div><ul style="list-style-type: none">This command declares the end of a subroutine program.When this command is executed, the program is resumed starting from the line following the CAL n command that called the subroutine.Do not set a startup condition for this command.</div></div> | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| <div><div></div><div><ul style="list-style-type: none">This command is checked prior to execution, and when there is an error, the following error code is set in the special internal output WRF001. Also, the CPU error code “34” is set to special internal output WRF000.</div></div> | | | | | | | | | | | | | | | | | |
| CPU error code | | Special internal output | | | | Error code | | Error description | | | | | | | | | |
| 34 | WRF001 | | | | H0011 | | RTS undefined | | | | | | | | | | |
| | | | | | H0020 | | RTS area error | | | | | | | | | | |
| | | | | | H0030 | | RTS startup condition error | | | | | | | | | | |
| Instruction for use | | | | | | | | | | | | | | | | | |
| <div><div><div><div><div>R000</div><div></div></div><div><div></div><div></div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><</div></div> | | | | | | | | | | | | | | | | | |


| Item number | | Control commands-11 | | | | Name | | Start interrupt scan program (INTERRUPT) | | | | | | | | | | | | | | | | | |
|---|-------------------------|---------------------|-----------------------------|-----------------|---------|-----------------------------------|-------|--|------------|----------------------|-------------|------|-----------------|----------|------------------|----------------|-------------------------|------------|-------------------|----|--------|-------|-----------------------------|-------|---------------|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | |
| INT n | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | | 0.05 | ← | 0.65 | ← | 1.3 | ← | | | | | | | | | | |
| INT n | | | | Condition | | | Steps | | | | | | | | | | | | | | | | | | |
| | | | | — | | | 1 | | | | | | | | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | | | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | | | |
| n | Interrupt priority | | | | | | | | | | | | | ○ | 0 to 2 (Decimal) | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">This command declares the start of an interrupt scan program.n=0 to 2 indicates a periodical interrupt scan.It is set to the 10 ms periodic scan when n=0, 20 ms periodic scan when n=1, and 40 ms periodic interrupt scan when n=2.The smaller the number n, the higher the interrupt priority.Always use INT n and RTI in pairs.Even if a startup condition is used for INT n, it will be ignored.Code the INT n to RTI subroutine program after the END command.The n in INT n cannot be used multiple times within the same program.</div> | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">This command is checked prior to execution, and when there is an error, the following error code is set in the special internal output WRF001. Also, the CPU error code “34” is set to special internal output WRF000.</div> <table><tr><th>CPU error code</th><th>Special internal output</th><th>Error code</th><th>Error description</th></tr><tr><td rowspan="2">34</td><td rowspan="2">WRF001</td><td>H0005</td><td>Duplicate definition of INT</td></tr><tr><td>H0014</td><td>INT undefined</td></tr></table> <div><ul style="list-style-type: none"><u>The progress value is updated when the timer command is expected in the EH-CPU448.</u> Therefore, if a program that does not scan the timer command execution section after the timer is activated is created using the interrupt scan, the timer may not turn on correctly. (The timer does not turn on correctly when the time that does not scan the timer command execution section exceeds the time calculated by multiplying the time base by 65,535.) Note that the previous progress value is also retained until the timer command is executed.</div> | | | | | | | | | | | | | | | | CPU error code | Special internal output | Error code | Error description | 34 | WRF001 | H0005 | Duplicate definition of INT | H0014 | INT undefined |
| CPU error code | Special internal output | Error code | Error description | | | | | | | | | | | | | | | | | | | | | | |
| 34 | WRF001 | H0005 | Duplicate definition of INT | | | | | | | | | | | | | | | | | | | | | | |
| | | H0014 | INT undefined | | | | | | | | | | | | | | | | | | | | | | |
| Instruction for use | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div><div>END</div><div>INT 0</div><div>10 ms interrupt scan program</div><div>RTI</div></div><div>⇕ INT 0 scar</div></div><div><ul style="list-style-type: none">The program between INT0 and RTI is started and executed every 10 ms.</div></div> | | | | | | | | | | | | | | | | | | | | | | | | | |

| Item number | Control commands-12 | | | | Name | | End interrupt scan program (RETURN INTERRUPT) | | | | | | | | | | | | | | | | | | | | |
|---------------------|-------------------------|---|-----------------------------|------|---------|-----------------------------------|---|------------------------|----------------------|-------------------------|-----|-----------------|----------|-------|------------|----------------|-------------------------|------------|-------------------|----|--------|-------|---------------|-------|----------------|-------|-----------------------------|
| Ladder format | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | |
| RTI | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | | | | | | | | | | | | | |
| | | | DER | ERR | SD | V | C | | | | | | | | | | | | | | | | | | | | |
| | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | |
| Command format | | | Number of steps | | | | | | 8 | ← | 5 | ← | 22 | ← | | | | | | | | | | | | | |
| RTI | | | Condition | | | Steps | | | | | | | | | | | | | | | | | | | | | |
| | | | — | | | 1 | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | | | | | | | | | | | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">• This command declares the end of an interrupt scan program.• When this program is executed, the processing is returned to the program that was executing before the interrupt scan was performed.• Do not set a startup condition for this command. | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">• This command is checked prior to execution, and when there is an error, the following error code is set in the special internal output WRF001. Also, the CPU error code “34” is set to special internal output WRF000. | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <table><tr><th>CPU error code</th><th>Special internal output</th><th>Error code</th><th>Error description</th></tr><tr><td rowspan="3">34</td><td rowspan="3">WRF001</td><td>H0012</td><td>RTI undefined</td></tr><tr><td>H0021</td><td>RTI area error</td></tr><tr><td>H0031</td><td>RTI startup condition error</td></tr></table> | | | | | | | | | | | | | | CPU error code | Special internal output | Error code | Error description | 34 | WRF001 | H0012 | RTI undefined | H0021 | RTI area error | H0031 | RTI startup condition error |
| CPU error code | Special internal output | Error code | Error description | | | | | | | | | | | | | | | | | | | | | | | | |
| 34 | WRF001 | H0012 | RTI undefined | | | | | | | | | | | | | | | | | | | | | | | | |
| | | H0021 | RTI area error | | | | | | | | | | | | | | | | | | | | | | | | |
| | | H0031 | RTI startup condition error | | | | | | | | | | | | | | | | | | | | | | | | |
| Instruction for use | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <div><div><div><div><div></div><div>INT 0</div></div><div><div>X00000</div><div>→</div><div>I</div></div><div><div>WR0000=0</div><div>R000=0</div></div><div><div>X00000</div><div>→</div><div>I</div></div><div><div>WR0000=WR0000+1</div></div><div><div>WM000</div><div><=</div><div>WR0000</div></div><div><div>R000</div><div>○</div></div><div>SET</div><div>RTI</div></div></div><ul style="list-style-type: none">• A 0.01s timer is created using 10 ms interval interrupts.• WM000 is used for the set value, WR0000 for the progress value and R000 for the timer coil.• When X00000 is off, the progress value and timer coil are cleared.• When X00000 is on, the progress value increments by 1 every 10 ms.• The timer coil is turned on upon WM000<=WR0000.</div> | | | | | | | | | | | | | | | | | | | | | | | | | |


RTI

Syntax of SB n, RTS, INT n and RTI

- 1] A subroutine can be programmed between a normal scan and interrupt scan, between two interrupt scans, or after the final interrupt scan.




- 2] Program the subroutine start (SB n) and subroutine end (RTS) commands without specifying startup conditions.




- The RTS startup condition error will occur during operation pre-processing.


- 3] Program the interrupt scan start (INT n) and scan complete (RTI) commands without specifying startup conditions.




- 4] The same subroutine can be called from a normal scan, interrupt scan or subroutine.




- 5] It is also possible to program a subroutine with multiple entry points and one exit.




- 6] It is also possible to program an interrupt scan with many entry points and one exit.



- 7] Nesting of subroutines is allowed up to 5 levels.




Program head
END




- (1) As shown to the left, the subroutine program order and nesting order have no relationship.

| Item number | | Transfer commands-1 | | | | Name | | General-purpose port transmission command | | | | | | | | | | | | | | | | | | | | | | | |
|---|---------------------------------------|---------------------|--|-----------------|------|---------|-----------------------------------|---|-----------|----------------------|------------|-------------|-----------------|------------|----------|--------|--|-----|--------------------|--|--|---|--|--|--|--|--|--|--|--|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | | | | |
| TRNS 0 (d, s, t) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | | | | | | | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | | | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | | 61 | | 589 | | 57 | | 571 | | 168 | | 1,301 | | | | | | | | | | | |
| TRNS 0 (d, s, t) | | | | Condition | | | Steps | | | | | | | 142 | | 1,465 | | | | | | | | | | | | | | | |
| | | | | — | | | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | | | | | | | | | | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | | | | | | | | |
| d | Module loading location | | | | | | | ○ | | | | | | | | | | | | | | | | | | | | | | | |
| s | Head of parameter area | | | | | | | | ○ | | | | | | | | | | s uses up to s+14. | | | | | | | | | | | | |
| t | Head of communication control bit | | | | | ○ | | | | | | | | | | | | | t uses up to t+11. | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (1) This is a communication command for general-purpose serial ports used in the CPU ladder program. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (2) The WY to which an arbitrary I/O is assigned is set in d. (Since this is used as a dummy, it is possible to set open n points to a slot that does not actually exist.) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (3) s is used to set the head I/O number of the parameter area, in which various communication parameters (head and size of communication data area, timeout value, receiving data length, transmission code and transmission parameter) are set. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (4) t is used to set the head I/O number of the communication control bit area, in which the start of communication, control bits for initial settings and the determination as to whether or not the communication ended properly are stored. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (5) The TRNS 0 command is a command to perform reception after transmission. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| (6) Area description of s | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s | 1] Return code | | | | | | | | | | | | | | | | | | | 1] Return code: | | Set in the lower 8 bits of the execution result of the TRNS 0 command as follows: | | | | | | | | | |
| s+1 | 2] System area | | | | | | | | | | | | | | | | | | | | | Normal completion → 0 | | | | | | | | | |
| | (Cannot be used by the user) | | | | | | | | | | | | | | | | | | | | | Abnormal completion → ≠ 0 | | | | | | | | | |
| s+3 | 3] Timeout time | | | | | | | | | | | | | | | | | | | 2] System area: | | Used by the system processing of the TRNS 0 command when the command is executed. | | | | | | | | | |
| s+4 | 4] Head I/O of transmitting data area | | | | | | | | | | | | | | | | | | | | | <u>This area may not be used by the user.</u> | | | | | | | | | |
| s+6 | 5] Size of transmitting data area | | | | | | | | | | | | | | | | | | | <div>⚠ Don't set some value in this area by the program, the force set, and so on. A serious failure occurs in the CPU, and a movement is suspended.</div> | | | | | | | | | | | |
| s+7 | 6] Head I/O of receiving data area | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+9 | 7] Size of receiving data area | | | | | | | | | | | | | | | | | | | 3] Timeout time: | | Designates the timeout time from the start of TRNS 0 command execution to completion, as follows: | | | | | | | | | |
| s+10 | 8] Receiving data length | | | | | | | | | | | | | | | | | | | | | 0: Timeout check is not performed. | | | | | | | | | |
| s+11 | 9] Start code | | | | | | | | | | | | | | | | | | | | | ≠ 0: × 10ms timeout check is performed (The maximum possible set value is HFFFF.). | | | | | | | | | |
| s+12 | 10] End code | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+13 | 11] Transmission speed | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+14 | 12] Transmission format | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div></div> : User write-prohibited area | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div></div> : User setting area | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |


- 4] Head I/O of transmitting data area:
When transmitted by the TRNS 0 command, designates the type and number of the head I/O of the area in which transmitting data is stored.



- 5] Size of transmitting data area:
The size of the transmitting data area is designated in word units.
- 6] Head I/O of receiving data area:
Designates the type and number of the head I/O of the area in which the response data, with respect to the command or data transmitted, is stored (the area composition is the same as the transmitting data area).
- 7] Size of receiving data area:
The size of the receiving data area is designated in word units.
- 8]^{*1} Receiving data length:
Receiving data length is designated in byte units. However, do not exceed the maximum value (256 bytes) or the receiving data area. If either is exceeded, DER is equal to "1" and ends abnormally.
- 9]^{*1} Start code:
Designates the receiving start code.



- 10]^{*1} End code:
Designates the receiving end code.



- 11] Transmission speed:
Designates the transmission speed.

| Baud rate | Set value |
|-----------|-----------|
| 19200 bps | H0006 |
| 9600 bps | H0005 |
| 4800 bps | H0004 |
| 2400 bps | H0003 |
| 1200 bps | H0002 |
| 600 bps | H0001 |
| 300 bps | H0000 |

TRNS 0 (d, s, t)

12] Transmission format:


Designates the transmission format.

| Transmission code | Set value |
|----------------------------|-----------|
| 7-bit even parity, 2 stops | H0000 |
| 7-bit odd parity, 2 stops | H0001 |
| 7-bit even parity, 1 stop | H0002 |
| 7-bit odd parity, 1 stop | H0003 |
| 8-bit no parity, 2 stops | H0004 |
| 8-bit no parity, 1 stop | H0005 |
| 8-bit even parity, 1 stop | H0006 |
| 8-bit odd parity, 1 stop | H0007 |


*1 The following four types of data communication methods can be designated depending on the settings of 8] through 10].

(a) Designation by the start code and receiving data length *2

(i) Receiving data structure




(ii) Parameter settings




(b) Designation by the start and end codes *2

(i) Receiving data structure




(ii) Parameter settings




(c) Designation by the end code

(i) Receiving data structure




*2 When receiving data by specifying a start code, the receive buffer may overflow if data with a different start code is sent from the connected device. If this occurs, the data reception will not be executed. Make sure the specified start code is the same as the one used at the connected device.

(ii) Parameter settings




(d) Designation by receiving data length

(i) Receiving data structure




(ii) Parameter settings



Priority order among start code, end code and receiving data length

| | | | | |
|------------|---|--|------------------------------------|--|
| Start code | 0 | 1 | 0 | 1 |
| End code | 0 | 0 | 1 | 1 |
| Action | Receives according to the receiving data length | Received according to the start code and receiving data length | Receives according to the end code | Receives according to the codes (data length is ignored) |

(7) Description of area t



- 1] Communication execution:
This bit is set to "1" when the communication is performed using the TRNS 0 command. After communication is completed, the TRNS 0 command resets the area to "0."
- 2] Normal completion:
This bit is set to "1" when communication started by the TRNS 0 command ends normally. Also, the TRNS 0 command resets this bit to "0" when communication is commenced.
- 3] Abnormal completion:
This bit is set to "1" when communication started by the TRNS 0 command ends abnormally. Also, the TRNS 0 command resets this bit to "0" when communication is commenced.
- 4] Initialization request:
This bit is set to "1" when the TRNS 0 command is initialized. If an initialization request is issued during transmission, communication is terminated forcibly.
- 5] Initialization end:
This bit is set to "1" when the initialization of the TRNS 0 command is completed normally. At this time, 4] initialization request is reset to 0."
- 6] Continuation:
This bit is set to "1" when receiving data immediately after transmission is complete. After the communication, the TRNS 0 command resets this bit to "0."
- 7] Parity error:
This bit is set to "1" when a parity error occurs during communication.
- 8] Framing error:
This bit is set to "1" when a framing error occurs during communication.
- 9] Overrun error:
This bit is set to "1" when an overrun error occurs during communication.
- 10] Timeout:
This bit is set to "1" when a communication times out.
- 11] Input buffer full:
This bit is set to "1" when the receiving buffer is full.
- 12] Conflict error:
This bit is set to "1" when multiple TRANS 0 commands are started simultaneously in the user program, or when a TRANS 0 command and a RECV 0 command are started simultaneously. This forces the communication to terminate.

The TRNS 0 command resets 7] through 12] to "0" during initialization or when the TRNS 0 command is started.

Supplement

- When the CPU receives data from a connected device after reception in your system, if reception is executed with the RECV 0 command after the completion of transmission with the TRNS 0 command, the reception data may not completely be received depending on the timing.
In such systems, it is recommended that you set 6] Continuation bit to “1” and specify the reception mode after transmission.

(8) Description of the transmitting data area

This is the area to store the data to be transmitted by the TRNS 0 command. Set the data to be transmitted according to the following structure:

1] When even number of bytes are transmitted

| Number of bytes to be transmitted (N) | |
|---------------------------------------|----------|
| 1st byte | 2nd byte |
| 3rd byte | 4th byte |
| 5th byte | 6th byte |
| 7th byte | 8th byte |
| to | |
| N-1th byte | Nth byte |

2] When odd number of bytes are transmitted

| Number of bytes to be transmitted (N) | |
|---------------------------------------|----------------|
| 1st byte | 2nd byte |
| 3rd byte | 4th byte |
| 5th byte | 6th byte |
| 7th byte | 8th byte |
| to | |
| N-2th byte | N-1th byte |
| Nth byte | (Invalid data) |

Transmitting data area

(9) Description of the receiving data area

This is the area to store the response with respect to the data transmitted by the TRNS 0 command. The received data is set according to the following structure:

1] When even number of bytes are received

| Number of bytes to be received (N) | |
|------------------------------------|----------|
| 1st byte | 2nd byte |
| 3rd byte | 4th byte |
| 5th byte | 6th byte |
| 7th byte | 8th byte |
| to | |
| N-1th byte | Nth byte |

2] When odd number of bytes are received


| Number of bytes to be received (N) | |
|------------------------------------|----------------|
| 1st byte | 2nd byte |
| 3rd byte | 4th byte |
| 5th byte | 6th byte |
| 7th byte | 8th byte |
| to | |
| N-2th byte | N-1th byte |
| Nth byte | (Invalid data) |

Receiving data area s

Cautionary notes

- The TRNS 0 command initializes the internal work area with one scan ON.
If there are startup conditions before the TRNS 0 command, the system software may not be able to execute initialization processing normally. Therefore, do not specify startup conditions.
- Set 1] Communication execution bit of the TRNS 0 command at the second scan or later.
- Use this command so that s+14 and t+11 do not exceed the I/O range*. If the I/O range is exceeded, DER is equal to “1” and communication will not be executed.
* For I/O ranges, refer to the P3-6 and P3-7 performance specification table.
- When there is an error in the parameters set by s to , there may be cases in which the CPU module error “52” is set in special internal output WRF000.
- A CPU turns on an ER signal at the following timing.
 - When communication practice was accepted normally.
- A CPU turns off an ER signal at the following timing.
 - When an initials requirement was turned on during the communication. (But, an ER signal is still on in the case after communication is completed.)
 - When a CPU did STOP during the communication and RUN was done after that. (But, an ER signal is still on in the case after communication is completed.)
 - When time out occurred during the communication.
 - When a s/t parameter was rewritten during the communication and it became a range error.

Program example



R7E3 : 1st scan ON
Timeout = 0

Reserve area for data sending :
16 words from WR0

Reserve area for data receiving :
256 words from WR100

Data receiving definition
Start code : H02, End code : H0D

Communication speed : 19.2k bps
Format : 7 bits, even, 2 stop

Sent data : 9 bytes
Inverter (SJ300/L300P) command
FWD RUN for station No.18
02 31 38 30 30 31 33 38 0D
(STX 18 00 1 38 CR) [38=BCC]

When the switch is ON, execution bit R0 is ON, and
data is sent out from CPU port.

R5 enables data receiving from the other device.

Description

This is a sample program for communication with Hitachi inverter (SJ300/L300P).
TRNS 0 parameter and sent data are configured at 1st scan by R7E3 contact.
When the switch is ON, execution bit R0 is ON, and CPU starts sending data.
After sending, CPU gets ready to receive response data from inverter, which is stored in WR100-.

Caution

- Parameter WX10 of RECV 0 is sample value in case of input module is mounted on slot 1. Set right parameter according to your I/O configuration. (If input module is on slot 3, this should be WX30.)
- Dip switch must be general purpose port setting (2-OFF, 5-OFF).


TRNS 0 (d, s, t)

TRNS/RECV command return code list

| Return code | Name | Description | Corrective action |
|-------------|--|---|---|
| H00 | Normal completion | Transmitting and receiving completed normally. | — |
| H10 | Module error *1 | Watchdog timer error | Check the module loading, then restart power or replace the module. |
| H21 | Range check error | The last entry in parameters s and t exceed the I/O range. | Set each parameter area in the valid range. |
| H22 | Transmitting area setting error | The head of the transmitting area is not set correctly. | Set the head of the receiving area in the valid range. |
| H23 | Transmitting area range error | The last entry in the transmitting area exceeds the I/O range. | Set the transmitting area in the valid range. |
| H24 | Receiving area setting error | The head of the receiving area is not set correctly. | Set the head of the receiving area in the valid range. |
| H25 | Receiving area range error | The last entry in the receiving area exceeds the I/O range. | Set the receiving area in the valid range. |
| H26 | Transmitting data length setting error | The transmitting data length is set exceeding the transmitting area length. | Perform setting so that the transmitting data length is within the transmitting area. |
| H27 | Receiving data length setting error | The receiving data length is set exceeding the receiving area length. | Perform setting so that the receiving data length is within the receiving area. |
| H28 | Area overlap error *2 | There is an overlapped area for parameters s and t, transmitting area and receiving area. | Set each area so there is no overlap. |
| H30 | Timeout *1 | The communication processing did not complete within the set time frame. | Increase the set value or review the processing contents. |
| H40 | Receiving area full *3 | Receiving data has been stored to the maximum capacity of the receiving area and there is no more open space. | Increase the receiving area. |
| H41 | Parity error *4 | Parity error has occurred during the communication processing. | Verify the transmission path, data format, etc. of the general-purpose port. |
| H42 | Framing error *4 | Framing error has occurred during the communication processing. | |
| H43 | Overrun error | Overrun error has occurred during the communication processing. | |
| H44 | Conflict error | TRNS 0/RECV 0 has been started at two or more locations simultaneously. | Change the setting so that it does not startup at two or more locations simultaneously. |
| H45 | Parameter error | The settings for TRNS 0/RECV 0 baud rate, transmission code, etc. are invalid. | Set the valid value. |
| H46 | Port designation error | TRNS 0 or RECV 0 was started when a general-purpose port was not designated. | Check port settings. |
| H55 | Line disconnection | No carrier is set during call origination | Check line connection |
| H80 | Module specific error | The high-function module detected an error. | Refer to the user's manual of each module. |

*1 Since the I/F designations of various high-function modules are identical from the stand point of the TRNS or RECV command, it is not possible to determine if the intended type is used. Therefore, no error indicating that the command and the module are mismatched is returned. However, when communication cannot be established due to discrepancy in the register configuration or the handshake bit location, a timeout error (if timeout has been designated) or a module error is returned as the error code.

*2 The return code for an area overlap error is H28, but when there is an area overlap as shown below, the return code may not be displayed as H28, so exercise caution.



If the head area of s and the t area are overlapped, H28 is set in the head area of s, but the abnormal completion bit is set to "1" at the same time, making the value appear as H21.


*3 It is set for the amount of the receiving area size (maximum 256 bytes).

*4 While receiving, the receiving data is not guaranteed.


| Item number | Transfer commands-2 | Name | | | | General-purpose port receiving command | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---------------------------------------|-----------------|------|---------|-----------------------------------|--|----------------------|------------|------------|-------------|-----------------|----------|---------------|------------|----------------|-----|----------------|--|------------------------------|-----|-----------------|-----|---------------------------------------|-----|-----------------------------------|-----|------------------------------------|-----|--------------------------------|------|--------------------------|------|---------------|------|--------------|------|------------------------|------|-------------------------|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | |
| RECV 0 (d, s, t) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Command format | | Number of steps | | | | | 61 | 365 | 57 | 579 | 171 | 1,305 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| RECV 0 (d, s, t) | | Condition | | | Steps | | | | 142 | 1,479 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | — | | | 5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | | | | | | | | | | | | | | | | | | | | | | | |
| d | Module loading location | | | | | ○ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s | Head of parameter area | | | | | | | ○ | | | | | up to s + 14. | | | | | | | | | | | | | | | | | | | | | | | | | | |
| t | Head of communication control bit | | | ○ | | | | | | | | | up to t + 11. | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div>(1) This is a communication command for general-purpose serial ports used in the CPU ladder program.</div><div>(2) A WX to which an arbitrary I/O is assigned is set in d.</div><div>(3) s is used to set the head I/O number of the parameter area, in which various communication parameters (head and size of transmitting and receiving data area, timeout value, receiving data length, transmission code and transmission parameter) are set.</div><div>(4) t is used to set the head I/O number of the communication control bit area, in which the start of communication, control bits for initial settings and the determination as to whether or not the communication ended properly are stored.</div><div>(5) The RECV 0 command is a command to perform reception after transmission.</div><div>(6) Area description of s.</div></div><div><table><tr><td>s</td><td>1] Return code</td></tr><tr><td>s+1</td><td>2] System area</td></tr><tr><td></td><td>(Cannot be used by the user)</td></tr><tr><td>s+3</td><td>3] Timeout time</td></tr><tr><td>s+4</td><td>4] Head I/O of transmitting data area</td></tr><tr><td>s+6</td><td>5] Size of transmitting data area</td></tr><tr><td>s+7</td><td>6] Head I/O of receiving data area</td></tr><tr><td>s+9</td><td>7] Size of receiving data area</td></tr><tr><td>s+10</td><td>8] Receiving data length</td></tr><tr><td>s+11</td><td>9] Start code</td></tr><tr><td>s+12</td><td>10] End code</td></tr><tr><td>s+13</td><td>11] Transmission speed</td></tr><tr><td>s+14</td><td>12] Transmission format</td></tr></table><div><div></div> : User write-prohibited area</div><div><div></div> : User setting area</div></div><div><div><div><div>1] Return code:</div><div>Set in the lower 8 bits of the execution result of the RECV 0 command as follows:</div><div>Normal completion → 0</div><div>Abnormal completion → ≠ 0</div></div><div><div>2] System area:</div><div>Used by the system processing of the RECV 0 command when the command is executed.</div><div><u>This area may not be used by the user.</u></div></div><div><div><div>⚠ Don't set some value in this area by the program, the force set, and so on. A serious failure occurs in the CPU, and a movement is suspended.</div></div><div><div>3] Timeout time:</div><div>Designates the timeout time from the start of RECV 0 command execution to completion, as follows:</div><div>0: Timeout check is not performed.</div><div>≠ 0: × 10 ms timeout check is performed (The maximum possible set value is HFFFF.).</div></div></div></div></div></div> | | | | | | | | | | | | | | s | 1] Return code | s+1 | 2] System area | | (Cannot be used by the user) | s+3 | 3] Timeout time | s+4 | 4] Head I/O of transmitting data area | s+6 | 5] Size of transmitting data area | s+7 | 6] Head I/O of receiving data area | s+9 | 7] Size of receiving data area | s+10 | 8] Receiving data length | s+11 | 9] Start code | s+12 | 10] End code | s+13 | 11] Transmission speed | s+14 | 12] Transmission format |
| s | 1] Return code | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+1 | 2] System area | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | (Cannot be used by the user) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+3 | 3] Timeout time | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+4 | 4] Head I/O of transmitting data area | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+6 | 5] Size of transmitting data area | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+7 | 6] Head I/O of receiving data area | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+9 | 7] Size of receiving data area | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+10 | 8] Receiving data length | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+11 | 9] Start code | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+12 | 10] End code | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+13 | 11] Transmission speed | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+14 | 12] Transmission format | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

RECV 0 (d, s, t)


- 4] Head I/O of transmitting data area:
When transmitted by the RECV 0 command, designates the type and number of the head I/O of the area in which transmitting data is stored.



- 5] Size of transmitting data area:
The size of the transmitting data area is designated in word units.
- 6] Head I/O of receiving data area:
Designates the type and number of the head I/O of the area in which receiving data is stored (the area composition is the same as the transmitting data area).
- 7] Size of receiving data area:
The size of the receiving data area is designated in word units.
- 8] Receiving data length:
Receiving data length is designated in byte units. However, do not exceed the maximum value (256 bytes) or the receiving data area. If either is exceeded, DER is equal to "1" and ends abnormally.
- 9] Start code:
Designates the receiving start code. *1



- 10] End code:
Designates the receiving end code.




- 11] Transmission speed:
Designates the transmission speed.
See the TRNS 0.
- 12] Transmission format:
Designates the transmission format.
See the TRNS 0.

Designate 4] and 5] when transmitting after receiving by the RECV 0 command.

*1 When receiving data by specifying a start code, the receive buffer may overflow if data with a different start code is sent from the connected device. If this occurs, the data reception will not be executed. Make sure the specified start code is the same as the one used at the connected device.

RECV 0 (d, s, t)

(7) Area description of t



- 1] Communication execution:
This bit is set to “1” when the communication is performed using the RECV 0 command. After communication is completed, the RECV 0 command resets the area to “0.”
- 2] Normal completion:
This bit is set to “1” when communication started by the RECV 0 command ends normally. Also, the RECV 0 command resets this bit to “0” when communication is commenced.
- 3] Abnormal completion:
This bit is set to “0” when communication started by the RECV 0 command ends abnormally. Also, the RECV 0 command resets this bit to “0” when communication is commenced.
- 4] Initialisation request:
This bit is set to “1” when the RECV 0 command is initialised. If an initialisation request is issued during transmission, communication is terminated forcibly.
- 5] Initialisation end:
This bit is set to “1” when the initialisation of the RECV 0 command is completed normally. At this time, 4] initialisation request is reset to “0.”
- 6] Continuation:
This bit is set to “1” when transmitting after receiving is complete. After the communication, the RECV 0 command resets this bit to “0.”
- 7] Parity error:
This bit is set to “1” when a party error occurs during communication.
- 8] Framing error:
This bit is set to “1” when a framing error occurs during communication.
- 9] Overrun error:
This bit is set to “1” when an overrun error occurs during communication.
- 10] Timeout:
This bit is set to “1” when a communication times out.
- 11] Input buffer full:
This bit is set to “1” when the receiving buffer is full.
- 12] Conflict error:
This bit is set to “1” when multiple RECV 0 commands are started simultaneously in the user program. This forces the communication to terminate.

The RECV 0 command resets 7] through 12] to “0” during initialisation or when the TRNS 0 command is started.

(8) Description of the transmission and receiving data area

See the TRNS 0.


Supplement

- If the CPU transmits data from a connected device after reception in your system, it is recommended that you set 6] Continuation bit to “1” and specify the transmission mode after reception.

Cautionary notes

- The RECV 0 command initializes the internal work area with one scan ON.
If there are startup conditions before the RECV 0 command, the system software may not be able to execute initialization processing normally. Therefore, do not specify startup conditions.
- Set 1] Communication execution bit of the RECV 0 command at the second scan or later.
- Use this command so that s+14 and t+11 do not exceed the I/O range*. If the I/O range is exceeded, DER is equal to “1” and communication will not be executed.
* For I/O ranges, refer to the P3-6 and P3-7 performance specification table.
- When the parameters set for s and after are abnormal, there may be cases when “52” is indicated on the CPU module error display.

Program example



Description

RECV 0 parameter and sent data are configured at 1st scan by R7E3 contact.
When the switch is ON, execution bit R0 is ON, and CPU gets ready to receive data receiving.
Data ACK01CR (0630310D) is sent back from CPU after data receiving.

Caution

- Parameter WX10 of RECV 0 is sample value in case of input module is mounted on slot 1. Set right parameter according to your I/O configuration. (If input module is on slot 3, this should be WX30.)
- Dip switch must be general purpose port setting (2-OFF, 5-OFF).


| Item number | | Transfer commands-5 | | | | Name | | Telecommunication command † | | | | | | | | | |
|--|-----------------------------------|---------------------|---|-----------------|-----------------------------------|-------|------|-----------------------------|----------------------|-------------|------------|------------|-----------------|-------|--------------------|--|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| TRNS 8 (d, s, t) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | 128 | 602 | 68 | 532 | | | | | |
| TRNS 8 (d, s, t) | | | | Condition | | Steps | | | | | 153 | 1,100 | | | | | |
| | | | | — | | 5 | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| d | Module loading location | | | | | | ○ | | | | | | | | | | |
| s | Head of parameter area | | | | | | | ○ | | | | | | | s uses up to s+10. | | |
| t | Head of communication control bit | | | | ○ | | | | | | | | | | t uses up to t+13 | | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div><div>(1) This is a communication command for controlling the modem that is used by the CPU's ladder program.</div><div>(2) Set the WY to which an arbitrary I/O is assigned in d. (Since this is used as a dummy, it is possible to set open n points to a slot that does not actually exist in I/O assignments.)</div><div>(3) For s, set the head I/O number of the parameter area in which various communication parameters (control type, head and size of transmission data area, transmission code and transmission parameter) are specified.</div><div>(4) For t, set the head I/O number of the communication control bit area in which the start of communication, control bits for initial settings and the result as to whether or not the communication ended properly are stored.</div><div>(5) Description of area s</div></div><div><div><div><div>s</div><div>1] Return code</div></div><div><div>s + 1</div><div>2] System area</div><div>(Cannot be used by the user)</div></div><div><div>s + 3</div><div>3] Control type</div></div><div><div>s + 4</div><div>4] Head I/O of transmission</div><div>data area</div></div><div><div>s + 6</div><div>5] Size of transmission data area</div></div><div><div>s + 7</div><div>6] Dial interval</div></div><div><div>s + 8</div><div>7] Non-response monitor time</div></div><div><div>s + 9</div><div>8] Modem-PLC transmission speed</div></div><div><div>s + 10</div><div>9] Transmission format</div></div></div><div><div><div></div>: User write-prohibited area</div><div><div></div>: User setting area</div></div><div><div>1] Return code: The execution result of the TRNS 8 command is set in the lower 8 bits as follows: Normal completion → 0 Abnormal completion → ≠ 0</div><div>2] System area: Used for system communication of the TRNS 8 command when the TRNS 8 command is executed. <u>This area cannot be used by the user.</u><div><div>⚠ Don't set some value in this area by the program, the force set, and so on. A serious failure occurs in the CPU, and a movement is suspended.</div></div></div><div>3] Control type: Specify the control type of the TRNS 8 command.<div>1: Dedicated/general switch request 2: General/dedicated switch request 3: TEL origination request 4: TEL disconnection request 5: Line connection check</div></div></div></div></div> | | | | | | | | | | | | | | | | | |

†: Supported by EH-CPU ***A/448/516/548 only.

TRNS 8 (d, s, t)

Function

- 4] Head I/O of the transmission data area:
Set the command to be sent to the modem with the TRNS 8 command. Specify the initialization command if initialization is required when a dedicated/general switch request is made, the type and number of the head I/O of the area in which the originating telephone number is stored.



- 5] Transmission data area size:
Specify the size of the transmission data area in units of words.
- 6] Dial interval:
Set the dial wait time for the second and subsequent dialing.
=0: 5 sec.
≠0: Waits until the next dial with a time of x1s.
- 7] Non-response monitor time:
Specify the timeout time after a command is issued to the modem.
=0: 10 sec.
≠0: Times out with a time of 1s.
- 8] Modem-PLC transmission speed:
Specify the transmission speed between the modem and PLC.


| Baud rate | Setting value |
|------------|---------------|
| 115.2 kbps | H0009 |
| 57.6 kbps | H0008 |
| 38.4 kbps | H0007 |
| 19.2 kbps | H0006 |
| 9600 bps | H0005 |
| 4800 bps | H0004 |
| 2400 bps | H0003 |
| 1200 bps | H0002 |
| 600 bps | H0001 |
| 300 bps | H0000 |

- 9] Transmission format:
Specify the transmission format.

| Transmission code | Set value |
|----------------------------|-----------|
| 7-bit even parity, 2 stops | H0000 |
| 7-bit odd parity, 2 stops | H0001 |
| 7-bit even parity, 1 stop | H0002 |
| 7-bit odd parity, 1 stop | H0003 |
| 8-bit no parity, 2 stops | H0004 |
| 8-bit no parity, 1 stop | H0005 |
| 8-bit even parity, 1 stop | H0006 |
| 8-bit odd parity, 1 stop | H0007 |

Function

(6) Description of area t



- 1] Communication execution:
This bit is set to “1” when the communication is performed using the TRNS 8 command. After communication is completed, the TRNS 8 command resets the area to “0.”
- 2] Normal completion:
This bit is set to “1” when communication started by the TRNS 8 command ends normally. Also, the TRNS 8 command resets this bit to “0” when communication is commenced.
- 3] Abnormal completion:
This bit is set to “1” when communication started by the TRNS 8 command ends abnormally. Also, the TRNS 8 command resets this bit to “0” when communication is started.
- 4] Being connected (2 bits):
Sets the line status. When an originating call is being connected, “01” is set. When a incoming call is being connected, “10” is set. If nothing is connected, “00” is set. The TRNS 8 command resets this bit to “00” when communication is starts. This bit is set when communication is completed normally.
- 5] Dial busy:
This bit is set to “1” when dial busy is detected after call origination.
- 6] Line busy:
This bit is set to “1” when line busy is detected after call origination.
- 7] Received:
This bit is set to “1” when a call is received when a switch request or originating request is made.
- 8] No response:
This bit is set to “1” when there is no response after dedicated/general switching.
- 9] Parity error:
This bit is set to “1” when a party error occurs.
- 10] Framing error:
This bit is set to “1” when a framing error occurs.
- 11] Overrun error:
This bit is set to “1” when an overrun error occurs.
- 12] Dedicated port being connected
This bit is set to “1” when the dedicated port is being connected after a switch request is made.
- 13] Contension error:
This bit is set to “1” when multiple TRANS 8 commands are started simultaneously by the user program, or when the TRANS 0 and RECV 0 commands are started simultaneously. This forces the communication to terminate.
The TRNS 8 command resets 5] through 13] to “0” when the TRNS 8 command is started.

Function

(7) Description of the transmission data area

This area stores the data to be transmitted to the modem with the TRNS 8 command, and is used for the initialization command and call origination. Set the data to be transmitted according to the following format:

| 1] When even number of bytes are transmitted | | 2] When odd number of bytes are transmitted | | Transmission data area size |
|--|----------|---|----------------|-----------------------------|
| Number of bytes to be transmitted (N) | | Number of bytes to be transmitted (N) | | |
| 1st byte | 2nd byte | 1st byte | 2nd byte | |
| 3rd byte | 4th byte | 3rd byte | 4th byte | |
| 5th byte | 6th byte | 5th byte | 6th byte | |
| 7th byte | 8th byte | 7th byte | 8th byte | |
| : | | : | | |
| N-1th byte | Nth byte | N-2th byte | N-1th byte | |
| | | Nth byte | (Invalid data) | |
| | | | | |

(i) When the initialization command is required during dedicated/general switch request

Specify the initialization command excluding the head AT.

(Example) Initialization command: To send ATE0Q0V0 & CI &SI to the modem

| H000C | |
|---------|---------|
| H45 (E) | H30 (O) |
| H51 (Q) | H30 (O) |
| H56 (V) | H30 (O) |
| H26 (&) | H43 (C) |
| H31 (1) | H26 (&) |
| H53 (S) | H31 (1) |

Set the following values when the modem is initialized*:

Result code: Output
Display format of result code: Numeric format
Echo back: None
DR signal: Always on
CD signal control: Follows the carrier of the opposite modem
ER signal control: Disconnects the line by switching from on to off

* The model may not operate normally if it is used with settings other than above. Be sure to set the model correctly by referring to the instruction manual of your modem.

(ii) When the initialization command is not required during dedicated/general switch request

Only AT can be sent by setting the transmission size to zero.

| H0000 | |
|-------|--|
| | |
| | |
| | |
| | |
| | |
| | |

Function

(iii) For call origination

Specify the telephone numbers to be dialed for call origination. Multiple numbers may be specified by delimiting each number with a space (H20). If two consecutive spaces are entered, it is considered that no telephone numbers are present thereafter. If a space is entered at the beginning, no call origination will be performed.

To redial the same telephone number, specify the same telephone number for the number of times to be called.


To redial different telephone numbers, specify different telephone numbers.

(Example) To dial TEL 03-1111-2222 three times

| H0020 | |
|--------|--------|
| H30(0) | H33(3) |
| H31(1) | H31(1) |
| H31(1) | H31(1) |
| H32(2) | H32(2) |
| H32(2) | H32(2) |
| H20() | H30(0) |
| H33(3) | H31(1) |
| H31(1) | H31(1) |
| H31(1) | H32(2) |
| H32(2) | H32(2) |
| H32(2) | H20() |
| H30(0) | H33(3) |
| H31(1) | H31(1) |
| H31(1) | H31(1) |
| H32(2) | H32(2) |
| H32(2) | H32(2) |


Notes

- Use this command so that s+10 and t+13 do not exceed the I/O range*. If the I/O range is exceeded, DER is equal to "1" and communication will not be executed.
* For the I/O ranges, see the EH-CPU448 Performance Specifications Table on page 3.
- Control type
 - 1] Dedicated/general switch request
Switches communication from the dedicated port communication to the general port communication. When the switching is completed normally, the general port is enabled. If an error occurs, the switching will not be performed. If the initialization command is required for the modem, the initialization command can be specified. If it is not required, set the transmission size to zero. This can be executed only when the line is being disconnected.
 - 2] General/dedicated switch request
Switches communication from the general port communication to the dedicated port communication. If this switching is done while the line is being connected, the transmission speed and transmission format specified for the general port must match those for the dedicated port.
 - 3] Call origination request
Performs a call origination to the specified telephone number.
 - 4] Call disconnection request
Performs a call disconnection. Both the dedicated port and general port can be disconnected. When the disconnection is completed normally, the dedicated port is enabled.
 - 5] Line connection check
Checks the line connection status.




TRNS 8 (d, s, t)

Dedicated port being connected Line check Part 1




Dedicated port being connected Line check Part 2



TRANS 8 (d, s, t)

Dedicated port being connected Call origination



Call termination (ring reception) check is not performed before the AT command is issued.
It may result in either normal completion or abnormal completion (line busy, termination detected, no response). In case of abnormal completion, retry the operation.
When changed from RUN to STOP:
The port mode is set to the dedicated port.
If a modem is connected using the general port, the line will be placed in the disconnected status.
If the port is the dedicated port, no status change will occur.

TRNS 8 (d, s, t)

Error code

TRNS 8 error code list


Types of errors: 1] Dedicated/general port switch request, 2] General/dedicated port switch request, 3] Call origination request, 4] Call disconnection request, 5] Line connection check

| Return code | Error name | Description | Type of error |
|-------------|--|---|------------------------|
| 21h | Range check error | The s parameter and/or t parameter exceeded the I/O range. | 1], 2], 3], 4], 5] |
| 22h | Transmission area setting error | The starting address setting of the transmission area is incorrect. | 1], 2] |
| 23h | Transmission area range error | The transmission area exceeded the I/O range. | 1], 2] |
| 26h | Transmission data length error | The transmission data length is longer than the transmission area. | 1], 2] |
| 28h | Area overlap | The s parameter, t parameter and transmission area are overlapped. | 1], 2], 3], 4], 5] |
| 41h | Parity error | A parity error occurred during result reception. | 1], 2] |
| 42h | Framing error | A framing error occurred during result reception. | 1], 2] |
| 43h | Overrun error | An overrun error occurred during result reception. | 1], 2] |
| 44h | Contention error | More than one TRNS 8 command were started simultaneously. The TRNS 8 command was started with the TRNS 0 command simultaneously. The TRNS 8 command was started with the RECV 0 command simultaneously. | 1], 2], 3], 4], 5] |
| 45h | Parameter error | The setting values of the baud rate, transmission format and control type are incorrect. | 1], when abnormal type |
| 46h | Port specification error | The DIP switches are not set for modem connection. | 1], 2], 3], 4], 5] |
| 50h | Dial busy | Busy during call origination | 2] |
| 51h | Line busy | Line busy during call origination | 2] |
| 52h | Termination detected | When switching or during call origination | 1], 2] |
| 53h | No response | The no-response time has reached without the response of the AT command. | 1] |
| 54h | Dedicated port is being connected | Being connected to the dedicated port during switch request. | 1] |
| 55h | Line disconnection | No carrier is set during call origination. | 2] |
| 56h | Abnormal modem response | Response from the modem is abnormal. | 1], 2] |
| 57h | Abnormal port mode | The port mode was set to the dedicated port during origination. | 2] |
| 58h | Telephone number setting error | The telephone number set in the transmission data area started with a space. The number of data to be sent was zero during origination. | 2] |
| 59h | Cannot switch from general to dedicated port | Switching to the dedicated port did not complete normally. | 5] |

| Program description | | |
|--|---|---|
| <div>R7E3</div> <div>1 scan ON after RUN</div> | <div>WR3 = 1 WR4 = HA WR5 = H10 WR6 = 10 WR7 = 0 WR8 = 10 WR9 = 6 WRA = 2</div> | 0001 To switch dedicated port to general purpose port, and to initialize. Data area : WR10 Data size : 10 words |
| <div>R7E3</div> <div>1 scan ON after RUN</div> | <div>WR10 = 15 WR11 = H4530 WR12 = H5130 WR13 = H5630 WR14 = H2643 WR15 = H3126 WR16 = H5330 WR17 = H2644 WR18 = H3200</div> | 0002 Initializing AT command "E0Q0V0&C1&S0&D2" |
| <div>R7E3</div> <div>1 scan ON after RUN</div> | <div>WR23 = 3 WR24 = HA WR25 = H30 WR26 = 20 WR27 = 10 WR28 = 0 WR29 = 0 WR2A = 0</div> | 0003 To dial Data area : WR30 Data size : 20 words |
| <div>R7E3</div> <div>1 scan ON after RUN</div> | <div>WR30 = 12 WR31 = H3034 WR32 = H3734 WR33 = H3933 WR34 = H3837 WR35 = H3139</div> | 0004 Dialing number "0474938719" |
| <div>R7E3</div> <div>1 scan ON after RUN</div> | <div>WM3 = 0 WM4 = HC WM5 = H10 WM6 = 6 WM7 = HC WM8 = H20 WM9 = 10 WMA = 7 WMB = 0 WMC = 0 WMD = 6 WME = 2</div> | 0005 General purpose port command TRNS 0 Sent area : WM10 Received : WM20 |
| <div>R7E3</div> <div>1 scan ON after RUN</div> | <div>WM10 = 10 WM11 = H3132 WM12 = H3334 WM13 = H3536 WM14 = H3738 WM15 = H3930 WM16 = H3132</div> | 0006 Sent data "123456789" |

TRNS 8 (d, s, t)

Program description



TRNS 8 (d, s, t)

| Item number | Fun commands-1 | Name | | PID Initialization † | | | | | | | | | | |
|---|-------------------|-----------------|------|----------------------|-----------------------------------|------|------------------------|------------|-------------------------|-------------|-----------------|------------|----------|---------|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 0 (s) * (PIDIT (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU3**A EH-CPU3** | | Other than left | | | |
| | | DER | ERR | SD | V | C | | | | | | | | |
| | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | Number of steps | | | | | 1,661 | 3,154 | 2980 | 5718 | 4,421 | 8,493 | | |
| FUN 0 (s) * (PIDIT (s)) | | Condition | | | Steps | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | |
| s | PID control table | | | | | | | ○ | | | | | | WR only |
| Function | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">The FUN 0 (s) initializes the area in which the initialization set data required for PID operation is stored.The (s) in the FUN 0 (s) is used to specify the head number of WR of the PID management table.If there is an error in the contents specified in the PID control table, an error code will be set in error code 0 of the PID control table and initialization will not be performed.Once initialization is successfully completed (FUN 0 normal completion (“1”) in the PID management table), re-executing the FUN 0 will generate an error. <p>* () indicates the display when the LADDER EDITOR is used.</p> | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">If difficulty arises when the area used by the PID operation is cleared upon operation start or recovering from a power failure, please specify the power failure memory. | | | | | | | | | | | | | | |

†: Supported by EH-CPU 308(A)/316(A)/448(A)/516/548 only.

| Item number | Fun commands-2 | Name | | | | PID operation control † | | | | | | | | | | | | Remark |
|--|-------------------|-----------------|------|---------|-----------------------------------|-------------------------|------------------------|------------|-------------------------|-------------|-----------------|------------|-----------------|---------|--------|--|--|--------|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Other than left | | Remark | | | |
| FUN 1 (s) * (PIDOP (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU3**A EH-CPU3** | | Other than left | | | | | | | |
| | | DER | ERR | SD | V | C | Ave | Max | Ave | Max | Ave | Max | | | | | | |
| | | ● | ● | ● | ● | ● | | | | | | | | | | | | |
| Command format | | Number of steps | | | | | 83 | 140 | 85 | 130 | 131 | 216 | | | | | | |
| FUN 1 (s) * (PIDOP (s)) | | Condition | | | Steps | | | | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | |
| s | PID control table | | | | | | | ○ | | | | | | WR only | | | | |
| Function | | | | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">The FUN 1 (s) determines the loop in which the operation is performed after reading the PID Execution flag from the bit table area of the loop and the PID Constant Change flag.Set (s) in the FUN 1 (s) as the head number of the PID control table. If set differently, an error will be generated and an error code will be set to error codes 0 and 1 of the PID control table, resulting in the FUN 1 not being executed.Program the FUN 1 (s) so that it is executed once during the 20 ms periodic scanning.<p>* () indicates the display when the LADDER EDITOR is used.</p></div> | | | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU 308(A)/316(A)/448(A)/516/548 only.

| Item number | Fun commands-3 | Name | | PID calculation process [†] | | | | | | | | | | | | Remark |
|-----------------------------|----------------|-----------------|------|--------------------------------------|-----------------------------------|------|------------------------|------------|-------------------------|-------------|-----------------|------------|----------|-------|---------|--------|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | | | | |
| FUN 2 (s) * (PIDCL (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU3**A EH-CPU3** | | Other than left | | | | | |
| | | DER | ERR | SD | V | C | | | | | | | | | | |
| | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | |
| Command format | | Number of steps | | | | | 87 | ← | 91 | ← | 183 | — | | | | |
| FUN 2 (s) * (PIDCL (s)) | | Condition | | | Steps | | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | |
| s | Word table | | | | | | | ○ | | | | | | | WR only | |
| Function | | | | | | | | | | | | | | | | |

- The sampling time set in the word table for each loop determines whether or not PID calculation is performed.
- The FUN 2 (s) turns ON the PID Calculation In Progress flag of the loop that is being calculated.
- Set all of the head number of WR of the word table for each PID loop of the FUN 2 (s).
- The FUN 2 (s) will check for the output upper limit and low limit values, set value bit pattern, and range of the output value bit pattern for each loop. If an error is generated, the FUN 2 Error flag of the loop bit table will turn ON and an error code is set to error code 2 of the PID control table. The FUN 2 will be executed even if an error is generated.
- Program the FUN 2 (s) so that it is executed during the 20 ms periodic scanning.

* () indicates the display when the LADDER EDITOR is used.

[†]: Supported by EH-CPU 308(A)/316(A)/448(A)/516/548 only.

(1) PID control table (In the case of FUN 0 (WRxxxx))

(a) Structure of PID management table (1)

Sets the header number of the WR used as the PID control table in s of FUN 0 (s). The PID control table is comprised of 2], 3], 4] and 5], and the size of the table increases by the number of loops 3]. Make sure that the maximum number of the WR is not exceeded. Otherwise, error code H0004 will be written in error code 0 2].

| Address | Contents | Details | Remarks |
|-------------|--|--|---------|
| xxxx | Error code 0 *1 (Read) | <ul style="list-style-type: none"> Sets the error code generated by FUN 0 processing or some part of FUN 1 processing. If no error is present, the prior status is maintained. | 2] |
| xxxx + 1 | Error code 1 *1 (Read) | <ul style="list-style-type: none"> Sets the error code generated by FUN 1 processing. If no error is present, the prior status is maintained. | |
| xxxx + 2 | Error code 2 *1 (Read) | <ul style="list-style-type: none"> Sets the error code generated by FUN 2 processing. If no error is present, the prior status is maintained. | |
| xxxx + 3 | FUN 0 Normal completion 1 (Read) | <ul style="list-style-type: none"> Sets H0001 when FUN 0 (PID initialization) is executed normally. If an error is generated, the value will be H0000, and an error code will be set in error code 0. | 5] |
| xxxx + 4 | Number of loops (Write) *2 | <ul style="list-style-type: none"> Sets the number of loops used in a range between 1 and 64. If the value is 0, H0002 is written in error code 0, and the PID will not be processed. (Even if the FUN 1 and FUN 2 are programmed, PID will not be processed.) | 3] |
| xxxx + 5 | Head address of the WR of the word table for loop 1 (Write) *2 | <ul style="list-style-type: none"> 48 words are used per loop for PID constant input and for PID internal calculations. If the maximum WR number is exceeded, error code XX05 will be written in error code 0. | 4] |
| xxxx + 6 | Head address of the WR of the word table for loop 2 (Write) *2 | <ul style="list-style-type: none"> 48 words are used per loop for PID constant input and for PID internal calculations. If the maximum WR number is exceeded, error code XX05 will be written in error code 0. | |
| xxxx + 7 | Head address of the WR of the word table for loop 3 (Write) *2 | <ul style="list-style-type: none"> 48 words are used per loop for PID constant input and for PID internal calculations. If the maximum WR number is exceeded, error code XX05 will be written in error code 0. | |
| • • • | • • • | • • • | |
| xxxx + 44 | Head address of the WR of the word table for loop 64 (Write)*2 | <ul style="list-style-type: none"> 48 words are used per loop for PID constant input and for PID internal calculations. If the maximum WR number is exceeded, error code XX05 will be written in error code 0. | |

*1 Error codes are expressed as a four-digit hexadecimal value. For more information, see the Error Code Details.

*2 The (Write) in the above table indicates the areas where the user enters data using a program. (It is also possible to read data.)


(b) Word table and bit table for each loop

(If the content of xxxx+5 in (a) is ADRIO (xxxx+5, yyyy))


| Address | Contents | Specifications | Notes | Remarks |
|----------------------------|---|--|---|---------|
| yyyy | ADRIO (yyyy, zzzz) zzzz is the header number of the bit internal output. | Sets the header address of the bit table. | Uses 16 bits per loop. Set the actual address of the header number using the ADRIO command so the last suffix of the bit internal output is not exceeded. | 11] |
| yyyy + 1 | Sampling time TZ | When 1 to 200 ($\times 20$ ms) analog I/O is installed in a basic base or extended base. | <ul style="list-style-type: none"> Set a multiple of the minimum set value. The minimum set value is the value set to the number of loops 3]. | 12] |
| yyyy + 2 | Proportional gain KP | - 1,000 to +1,000 | Corresponds to -10.00 to +10.00. | 13] |
| yyyy + 3 | Integral content Ti/TZ | 1 to 32,767 | Value is set to $Ti / (\text{Sampling time} \times 20 \text{ ms})$ | 14] |
| yyyy + 4 | Derivative constant TD/TZ | 1 to 32,767 | Value is set to $Ti / (\text{Sampling time} \times 20 \text{ ms})$ | 15] |
| yyyy + 5 | Derivative delay constant Tn/TZ | 1 to 32,767 | Value is set to $Ti / (\text{Sampling time} \times 20 \text{ ms})$ | 16] |
| yyyy + 6 | Output upper limit value UL | - 32,767 to 32,767 | The following condition must be met. $LL \leq \text{INIT} \leq \text{UL}$ | 17] |
| yyyy + 7 | Output low limit value LL | - 32,767 to 32,767 | | 18] |
| yyyy + 8 | Initial value INIT | - 32,767 to 32,767 | | 19] |
| yyyy + 9 | Set value I/O number (Write) | Set the actual address of the word number of the I/O for which the set value is set. | | 20] |
| yyyy + A | Measured Value I/O number (Write) | Set the actual address of the word number of the I/O for which the measured value is set. | | 21] |
| yyyy + B | Output value I/O Number (Write) | Set the actual address of the word number of the I/O that outputs the PID calculation results. | | 22] |
| yyyy + C | Set value bit pattern (Write) | Determine the method that is used to convert the set value to the 16-bit data in which the PID operation is performed. See *1 below and use a value between H0001 and H0004. | | 23] |
| yyyy + D | Measured value bit pattern (Write) | Determine the method that is used to convert the data read from the measured value I/O number 21] to the 16-bit data. (See the set value bit pattern 23].) | | 24] |
| yyyy + E | Output value bit pattern (Write) | <ul style="list-style-type: none"> Write to the output value I/O number 22] after converting the results of the FUN 2 process or PID calculation according to the output value bit pattern 25]. Use a value between H0001 and H0004 in *2 depending on the type of output I/O. | | 25] |
| yyyy + F ↓ yyyy + 2F | PID calculation area (Cannot be used by the user) | Do not use this in user programs because this is used by FUN 0, FUN 1, and FUN 2 processing. | | 26] |

*1:


H0001: 8-bit → 16-bit



H0002: 12-bit unsigned → 16-bit




H0003: 12-bit signed → expand the sign to 16-bit



H0004: Do not convert

*2 :


H0001: 16-bit → 8-bit



If values are H0FFF through H7FFF before conversion, the values are converted to H00FF.

If values are H8000 through HFFFF before conversion, the values are converted to H0000.


H0002: 16-bit → 12-bit



If values are H0FFF through H7FFF before conversion, the values are converted to H00FF.

If values are H8000 through HFFFF before conversion, the values are converted to H0000.

H0003: 16-bit signed → 12-bit signed



If values are H0FFF through H7FFF before conversion, the values are converted to H07FF.

If values are H8000 through HF000 before conversion, the values are converted to H0800.

H0004: Do not convert


FUN0(S)
FUN1(S)
FUN2(S)

(c) Details of word tables used for each loop

| Address | PID management table | Details | Remarks |
|----------|--|--|---------|
| zzzz | Execution flag (Write) | <ul style="list-style-type: none"> When the Execution flag starts up (0 → 1), the PID constant at that time is checked and the PID calculation value is initialized. If successful, the PID RUN flag 58] is set to "1." If there is an error, the PID RUN flag 58] is set to "0" and PID calculation will not be performed. PID calculation is performed while the Execution flag = 1. When the Execution flag = 0, the PID calculation will end and the output will become "0." | 50] |
| zzzz + 1 | Non-bumpless flag (Write) | 0 : Perform Bumpless processing 1 : Perform non-bumpless processing | 51] |
| zzzz + 2 | PID constant change flag (Write) | <ul style="list-style-type: none"> When the PID Constant Change flag is turned from OFF → ON, the PID constant that is used for the PID calculation is read again, and this value is used to perform calculations. After the PID constant change is complete, this flag must be turned OFF by the user. If there is an error in the PID constant (PID Constant OK = 0), the PID calculation value based on the previous PID constant will be used and the operation will continue. | 52] |
| zzzz + 3 | S flag (Write) | When the S flag is set to "1", it reverts the output value to its initial value. It performs the following output depending on the relationship between Output Upper Limit Value 17], Output Lower Limit Value 18], and Initial Values 19]. Output Lower Limit Value 18] > Output Upper Limit Value 17]No output Output Lower Limit Value 18] ≤ Initial Value 19] ≤ Output Upper Limit Value 17] ...Outputs Initial Values 19] Output Lower Limit Value 18] ≤ Output Upper Limit Value 17] ≤ Initial Values 19] ... ≤ Outputs Output Upper Limit Value 17] Initial Values 19] ≤ Output Lower Limit Value 18] ≤ Output Upper Limit Value 17] ... Outputs Output Lower Limit Value 18] The S flag takes priority over the R Flag. | 53] |
| zzzz + 4 | R flag (Write) | When the R flag is set to "1", it clears the output value to 0. | 54] |
| zzzz + 5 | D-FREI flag (Write) | "0": Calculate PID without performing integrals or derivatives. "1": Calculate PID using integrals or derivatives. | 55] |
| zzzz + 6 | Unused | | |
| zzzz + 7 | Unused | | |
| zzzz + 8 | PID RUN flag (Read) | <ul style="list-style-type: none"> When the FUN 1 detects the startup of the Execution flag 50], 12] through 16] and 20] through 22] will be checked for logical validity and the result will be set to the PID RUN flag 58]. 1 : Valid 0 : Invalid If the Execution flag 50] startup is detected by the FUN 1 when the PID RUN flag 58] = 1, PID RUN 58] becomes 0 and the PID process will end. | 58] |
| zzzz + 9 | PID calculation in progress flag (Read) | <ul style="list-style-type: none"> Sets the PID Calculation in Progress flag 59] in the loop in which the FUN 2 calculates the PID to "1," and sets all PID Calculation in Progress flags in other loops to "0." | 59] |
| zzzz + A | PID constant OK flag (Read) | <ul style="list-style-type: none"> When the FUN 1 detects the startup of the PID Constant Change flag 52], the PID constants 12] through 16] will be checked for logical validity and the result will be set in the PID Constant OK Flag 60]. | 60] |
| zzzz + B | Upper limit over flag (Read) | <ul style="list-style-type: none"> If the PID output value calculated by the FUN 2 is greater than the output upper limit UL 17], the Upper Limit Over flag 61] will be set to "1." | 61] |
| zzzz + C | Lower limit over flag (Read) | <ul style="list-style-type: none"> If the PID output value calculated by the FUN 2 is greater than the output lower limit LL 18], the Lower Limit Over flag 62] will be set to "1." | 62] |
| zzzz + D | FUN 2 error flag (Read) | When there is an error in the output upper limit value 17], output lower limit value 18], or in any of the bit patterns 23] through 25] during FUN 2 processing, the FUN 2 Error 63] will be set to "1." The cause of the error is set in error code 2 2]. PID calculation will still be executed even if an error is generated. If there is no error, the FUN 2 Error flag 63] = 0. Nothing will be set to error code 2 2]. | 63] |
| zzzz + E | Unused | | |
| zzzz + F | Unused | | |

(2) PID operation execution format

(Example 1) Using two loops with both loops set as $TZ = 2 (\times 20 \text{ ms})$




PID Operation Execution Control (2 loops)

(Example 2) Using three loops set as follows:

Loop1: $TZ = 3 (\times 20 \text{ ms})$

Loop2: $TZ = 6 (\times 20 \text{ ms})$

Loop3: $TZ = 12 (\times 20 \text{ ms})$




PID Operation Execution Control (3 loops)

(3) PID operation timing chart

(a) Timing chart example 1

The following timing chart shows the operation of the PID RUN flag, PID constant OK flag, PID calculation in progress flag, FUN 0, FUN 1, and FUN 2 when the execution flag and PID constant change flag is turned from ON to OFF in a single loop.



Description of timing chart example 1


- 1] This is ignored since FUN 0 is not executed properly even when the execution flag, 2] and 3] of the PID constant change flag are turned on.
- 4] No process will be performed even if FUN 1 is executed because there was an error in the PID related table during FUN 0 processing.
- 5] 6] FUN 1 processing will be started because the FUN 0 processing ended normally. 7] FUN2 will not perform PID calculations because the execution flag is off.
- 8] 9] FUN 1 will detect turning on of the execution flag and will check the PID constant. Since it is normal, the PID constant will be calculated and the PIDRUN flag will be turned on.
- 10] The PID calculation of FUN 2 will not be performed on the first scan, so it will start with 11] FUN 2.
- 11] FUN 2 will turn the PID calculation in progress flag before calculating the PID. 12] FUN 1 will turn off the PID calculation in progress flag.
- 13] 14] FUN 1 checks the PID constant when the PID constant change flag is turned on. Since it is normal, the PID constant OK flag is turned on and the PID constant will be changed.
- 15] Since PID calculations are not performed in FUN 2, PID calculations will be performed from 16] FUN 2 according to the PID constant after it has been changed.
- 17] When the PID constant change flag was turned on, 18] FUN 1 checked the PID constant. An error was detected, so the PID constant OK flag is turned off. The PID constant flag will not be changed.
- 19] FUN 0 will be ignored when re-executed during PID operation.
- 20] Since 21] FUN 1 detected turning off of the execution flag, the PIDRUN flag will be turned off and the output will be set to 0.
- 21] Since 23] FUN 1 detected turning on of the PID constant change flag when the execution flag was off, the PID constant will be checked. Since it is valid, the PID constant will be changed and the PID constant OK flag will be turned on.
- 24] Since 25] FUN 1 detected turning on of the PID constant change flag when the execution flag was off, the PID constant will be checked. Since there was an error, the PID constant OK flag will be turned OFF.
- 26] 27] FUN 1 will detect turning on of the execution flag and check the PID constant. Since an error was detected, the PIDRUN flag will be turned off.
- 28] Since 29] FUN 1 detected turning on of both the execution flag and the 32] PID constant change flag simultaneously, turning on of the 32] PID constant change flag will be ignored. 29] FUN 1 checks the PID constant, and since it is normal, the PIDRUN flag will be turned on. PID calculation will be started from 33] FUN 2.
- 30] 31] If the execution flag turns from on to off in a timing such that the cyclic interrupt cannot detect it, it will be ignored.

(b) Timing chart example 2

The following is an operation timing chart in respect to the S flag and R flag (bumpless).


S flag.....Sets the output value to the initial value.

R flag.....Sets the output value to 0.



(c) Timing chart example 3


Bumpless and non-bumpless



FUN 0(S)
FUN 1(S)
FUN 2(S)

(4) PID command error code details

- Error codes are shown using a 4-digit hexadecimal value.



Shows the loop number.

In the case of H00, it is an error that has no relation to loop numbers.

In the case of H01 through H04, there is an error in the loop shown in the loop number.

(a) Error code 0

The error codes generated in FUN 0 processing and some parts of FUN 1 processing are set in error code 0.

If there is no error, the previous status will be maintained.

| Error code | Contents and cause | Corrective action | Remarks |
|----------------|---|--|---|
| 0001 | The FUN 0 was executed again after the FUN 0 had been successfully completed. | Do not execute the FUN 0 after it has been executed successfully. | "FUN 0 normal completion 5]" maintains the previous value. |
| 0002 | The number of loops 3] is 0. | Set the number of loops 3] to a value between the range of 1 to 64. | |
| 0003 | The number of loops 3] exceeds 65. | Set the number of loops 3] to a value between the range of 1 to 64. | |
| 0004 | The PID control table exceeds the maximum number of WR. | Change the head of PID management table or the number of loops 3] so that the maximum number of WR is not exceeded. | The size of the PID management table will change. If the number of loops 3] exceeds the suffix of the I/O, "FUN 0 normal completion 5]" will maintain the previous value. |
| xx05 | The word table of loop xx exceeds the maximum number of WR. | Set the number in the WR for the loop 4] again. | The size of the bit table is 16 bits per loop. |
| xx06 | The bit table of loop xx exceeds the maximum number of R. | Set the bit number for R 11] again. | The size of the bit table is 16 bits per loop. |
| xx07 | The output upper limit value 17] in loop xx is outside of range. | Set the output upper limit value 17] to a value between -32,767 and 32,767. | |
| xx08 | The output lower limit value 18] in loop xx is outside of range. | Set the output lower limit value 18] to a value between -32,767 and 32,767. | |
| xx09 | The initial value 19] in loop xx is outside of range. | Set the initial value 19] to a value between -32,767 and 32,767. | |
| xx0A | There is an error in the size relationship between the output upper limit value 17], output lower limit value 18], and initial value 19]. | Perform settings so that the output lower limit value 18] (initial value 19] (output upper limit value 17] is met. | |
| xx0B | The set value bit pattern 23] in loop xx is outside of range. | Set the set value bit pattern 23] to a value between 1 and 4. | |
| xx0C | The measured value bit pattern 24] in loop xx is outside of range. | Set the measured value bit pattern 24] to a value between 1 and 4. | |
| xx0D | The output value bit pattern 25] in loop xx is outside of range. | Set the output value bit pattern 25] to a value between 1 and 4. | |
| 0020 (Note) | The FUN 1 is being executed when the FUN 0 is not successfully completed. | Do not run the FUN 1 until the FUN 0 is successfully executed. | Set to the error code 0 specified by the (S) in the FUN 1 (S). |
| 0021 (Note) | The S in the FUN 1 (S) is different from the S in the FUN 0 (S) of the PID management table. | Set the same WR for the S in the FUN 1(S) and the S in the FUN 0 (S). | Set to the error code 0 specified by the (S) in the FUN 1 (S). |

(Note) Error codes 0020 and 0021 will over-write the errors generated previously (0001 to XX0D). Therefore, execute the FUN 1 after verifying that the FUN 0 is successfully executed.

(b) Error code 1

The error code generated in the FUN 1 process is set in error code 1. If there is no error, the previous condition is maintained.


| Error code | Contents and cause | Corrective action | Remarks |
|------------|--|---|--|
| 0020 | The FUN 1 is being executed when the FUN 0 is not successfully completed. | Do not run the FUN 1 until the FUN 0 is successfully executed. | Set to the error code 0 specified by the (S) in the FUN 1 (S). |
| 0021 | The S in the FUN 1 (S) is different from the S in the FUN 0 (S) of the PID management table 1]. | Set the same WR number for the S in the FUN 1(S) and the S in the FUN 0 (S). | Set to the error code 0 specified by the (S) in the FUN 1 (S). |
| xx22 | There is an error in the set value I/O number 20] in loop xx. | Set the set value I/O number 20] using the ADRIO command. | These are errors that may be generated when the Execution flag starts up. |
| xx23 | There is an error in the measured value I/O number 21] in loop xx. | Set the measured value I/O number 21] using the ADRIO command. | |
| xx24 | There is an error in the output value I/O number 22] in loop xx. | Set the output value I/O number 22] using the ADRIO command. | |
| xx25 | The sampling time 12] of loop xx is out of range. | Set the sampling time 12] to a value within the range of 1 to 200. | These are errors that may be generated when the Execution flag starts up or when the PID Constant Change flag starts up. |
| xx26 | The sampling time 12] of loop xx is not a multiple of the number of loops 3]. | Set the sampling time 12] so that it becomes a multiple of the number of loops 3]. | |
| xx27 | The proportional gain 13] of loop xx is out of range. | Set the proportional gain 13] to a value within the range of -1,000 to 1,000. | |
| xx28 | The integral constant 14] of loop xx is out of range. | Set the integral constant 14] to a value within the range of 1 to 32,767. | |
| xx29 | The derivative constant 15] of loop xx is out of range. | Set the derivative constant 15] to a value within the range of 1 to 32,767. | |
| xx2A | The derivative delay constant 16] of loop xx is out of range. | Set the derivative delay constant 16] to a value within the range of 1 to 32,767. | There is a possibility that this error is generated when the S flag 53] is turned ON while the PID RUN flag 58] is OFF. |
| xx30 | There is an error in the size relationship between the output lower limit value 18] and output upper limit value 17] in loop xx. | Set the values so that the output lower limit value 18] \leq output upper limit value 17] is satisfied. | |
| xx31 | There is an error in the output value I/O number 22] in loop xx. | Set the output value I/O number 22] using the ADRIO command. | |
| xx32 | The output value bit pattern 25] in loop xx is outside of range. | Set the output value bit pattern 25] to a value between 1 and 4. | There is a possibility that these errors are generated when the S flag 53] or R flag 54] is turned on while the PID RUN flag 58] is OFF. |

(c) Error code 2

| Error code | Contents and cause | Corrective action | Remarks |
|------------|--|---|---|
| 0040 | | | |
| xx41 | The set value bit pattern 23] in loop xx is outside of range. | Set the set value bit pattern 23] to a value between 1 and 4. | When the bit pattern is outside of range, the process will continue based on "4. Do not convert." |
| xx42 | The measured value bit pattern 24] in loop xx is outside of range. | Set the set value bit pattern 24] to a value between 1 and 4. | |
| xx43 | The output value bit pattern 25] in loop xx is outside of range. | Set the output value bit pattern 25] to a value between 1 and 4. | |
| xx44 | There is an error in the size relationship between the output lower limit value 18] and output upper limit value 17] in loop xx. | Set the values so that the output lower limit value 18] \leq output upper limit value 17] is satisfied. | If there is a size relationship error, the process will continue but there will be no output. |


Program example

This program is an example comprised of three loops. This program also rewrites the PID constant every time the CPU starts a RUN process.




FUN 0 (\$)
FUN 1 (\$)
FUN 2 (\$)

Program example




FUN0(S)
FUN1(S)
FUN2(S)

Program example




FUN 0 (S)
FUN 1 (S)
FUN 2 (S)

Program example



The program on this page can also be as shown below.




* Please take note that INT2 is used for the EH-CPU448 and EnhanceCPU.

| Item number | | Fun commands-4 | | | | Name | | Process stepping | | | | | | | | | | |
|---|---|----------------|--|-----|---|-----------------|-----------------------------------|------------------|-------|------------|----------------------|-------------|------------|------------|-----------------|----------------------------|--------|--|
| Ladder format | | | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 4 (s) * (IFR (s)) | | | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | |
| | | | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | |
| | | | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | | | | | Number of steps | | | | | 208 | ← | 191 | ← | 398 | ← | | |
| FUN 4 (s) * (IFR (s)) | | | | | | Condition | | | Steps | | | | 370 | | | | | |
| | | | | | | — | | | 3 | | | | | | | | | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | | Constant | Other | | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | |
| s | Argument | | | | | | | | | ○ | | | | | | s uses up to s+3. | | |
| | | | | | | | | | | | | | | | | s+3 is used by the system. | | |
| Function | | | | | | | | | | | | | | | | | | |
| s | Previous process condition I/O number | | | | | | | | | | | | | | | | | |
| s+1 | Process set I/O number | | | | | | | | | | | | | | | | | |
| s+2 | Next process (clear condition) I/O number | | | | | | | | | | | | | | | | | |
| s+3 | Used by the system | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">When the I/O designated by s (previous process) switches on, the s+1 (process set) switches on and the state is retained. (The previous process condition is triggered by edge.)When the I/O designated by s+2 (next process) switches on, the s+1 (process set) is switched off. (The next process is triggered by level.)When s (previous process) and s+2 (next process) are both on, the s+2 (next process) has the priority.The user should designate output for each process, if necessary. <p>* () indicates the display when the LADDER EDITOR is used.</p> | | | | | | | | | | | | | | | | | | |

FUN 4 (s)


Program example



FUN 4 (s)

Cautionary notes

- Set the actual R, L and M address for the parameters s through s+2 using the ADRIO command.
- If the areas designated by s to s+2 overlap, if s+1, s+2 or s+3 falls out of range, DER will be equal to “1” and the command will not be processed.
- Do not designate the same I/O for arguments of different processes, since the action of the current process is levelled by the previous process.
- Each process requires at least one scan time.



t: One scan time is necessary

- In the program example described previously, the external I/O (X, Y) are used as switch signals of a process; thus, the time for performing I/O refresh (i.e., at least one scan period) is required for each process.

| Item number | | Fun commands-5 | | Name | | SIN function | | | | | | | | | |
|--|----------|----------------|-----|-----------------|---------------|--|------|------|------------------------|-------------|-------------------------|-----|-----------------|-------------------|------------------|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | Remark | |
| FUN 10 (s) * (SIN (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | |
| | | | | DER | ERR | SD | V | C | | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | |
| Command format | | | | Number of steps | | | | | 39 | ← | 40 ----- 87 | ← | 105 | ← | |
| FUN 10 (s) * (SIN (s)) | | | | Condition | | Steps | | | | | | | | | |
| | | | | — | | 3 | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM |
| s | Argument | | | | | | | | ○ | | | | | s uses up to s+2. | |
| Function | | | | | | | | | | | | | | | |
| <div><div><div><div>s+2</div><div>15</div><div>0</div><div>Integer portion</div></div><div><div>s+1</div><div>15</div><div>0</div><div>Fractional portion</div></div></div><div>← SIN</div><div><div>s</div><div>15</div><div>0</div><div>0 to 360°</div></div></div> <div><div><div><div>•</div><div>Calculates the SIN value using the unsigned binary value designated using s as the argument, and sets the integer and fractional portions of the result in s+2 and s+1, respectively.</div></div><div><div>•</div><div>The SIN value is indicated in a binary value, and negative values are indicated in two’s complements.</div></div><div><div>•</div><div>If the calculation is performed normally, DER is equal to “0.”</div></div><div><div>•</div><div>The fractional data is the value obtained by multiplying the actual value by 65,535.</div></div></div><div>* () indicates the display when the LADDER EDITOR is used.</div></div> | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | |
| <div><div><div><div>•</div><div>The argument is given in degrees in the range 0 ≤ s ≤ 360. Any other value will equal DER to “1” and the operation will not be performed.</div></div><div><div>•</div><div>If s+1 and s+2 exceed the maximum value for the I/O number, DER is equal to “1” and the operation will not be performed.</div></div></div></div> | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | |
| <div><div><div><div><div>X00100 DIF0</div><div><div>WR0100 = 40</div><div>FUN 10 (WR0100)</div></div></div></div><div><div>LD X00100</div><div>AND DIF0</div><div>[</div><div>WR0100 = 40</div><div>FUN 10 (WR0100)</div><div>]</div></div></div></div> | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | |
| <div><div><div><div>•</div><div>An angle of 40° is set in WR0100.</div></div><div><div>•</div><div>SIN operation is performed at the leading edge of X00100, and the fractional portion of the result is set in WR0101 and the whole number portion is set in WR0102 as binary values.</div></div></div><div>Execution results: WR0102=H0000, WR0101=HA48E, WR0100=H0028</div></div> | | | | | | | | | | | | | | | |

| Item number | | Fun commands-6 | | Name | | COS function | | | | | | | | | | |
|---|----------|----------------|-----|-----------------|---------|-----------------------------------|-------|------|------------------------|-------------|-------------------------|-----|-----------------|-------------------|------------|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 11 (s) * (COS (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | |
| | | | | DER | ERR | SD | V | C | | | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | | | Number of steps | | | | | 40 | ← | 41 88 | ← | 108 | ← | | |
| FUN 11 (s) * (COS (s)) | | | | Condition | | | Steps | | | | | | | | | |
| | | | | — | | | 3 | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | |
| s | Argument | | | | | | | | ○ | | | | | s uses up to s+2. | | |
| Function | | | | | | | | | | | | | | | | |
| <div><div><div><div>s+2</div><div>15</div><div>0</div></div><div><div>s+1</div><div>15</div><div>0</div></div></div><div><div>Integer portion</div><div>Fractional portion</div></div><div>← COS</div><div><div>s</div><div>15</div><div>0</div></div><div><div>0 to 360°</div></div></div> | | | | | | | | | | | | | | | | |
| <div><div><div><div><div>•</div><div>Calculates the COS value using the unsigned binary value designated by s as the argument, and sets the integer and fractional portions of the result in s+2 and s+1, respectively.</div></div><div><div>•</div><div>The COS value is indicated in a binary value, and negative values are indicated in two's complements.</div></div><div><div>•</div><div>If the calculation is performed normally, DER is equal to “0.”</div></div><div><div>•</div><div>The fractional data is the value obtained by multiplying the actual value by 65,535.</div></div></div><div><div>* () indicates the display when the LADDER EDITOR is used.</div></div></div></div> | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | |
| <div><div><div><div><div>•</div><div>The argument is given in degrees in the range $0 \leq s \leq 360$. Any other value will equal DER to “1” and the operation will not be performed.</div></div><div><div>•</div><div>If s+1 and s+2 exceed the maximum value for the I/O number, DER is equal to “1” and the operation will not be performed.</div></div></div></div></div> | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | |
| <div><div><div><div><div><div>X00101 DIF1</div><div><div><div>WR0110 = 110</div><div>FUN 11 (WR0110)</div></div></div></div></div></div><div><div>LD X00101</div><div>AND DIF1</div><div>[</div><div>WR0110 = 110</div><div>FUN 11 (WR0110)</div><div>]</div></div></div></div> | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | |
| <div><div><div><div><div>•</div><div>An angle of 110° is set in WR0110.</div></div><div><div>•</div><div>COS operation is performed at the leading edge of X00101, and the fractional portion of the result is set in WR0111 and the whole number portion is set in WR0112 as binary values.</div></div></div><div>Execution results: WR0112=HFFFF, WR0111=HA871, WR0110=H006E</div></div></div> | | | | | | | | | | | | | | | | |

| Item number | | Fun commands-7 | | Name | | TAN function | | | | | | | | | |
|---|----------|----------------|-----|-----------------|---------|-----------------------------------|------|------|------------------------|-------------|-------------------------|-----|-----------------|-------------------|------------|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark |
| FUN 12 (s) * (TAN (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | |
| | | | | DER | ERR | SD | V | C | | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | |
| Command format | | | | Number of steps | | | | | 40 | ← | 41 88 | ← | 109 | ← | |
| FUN 12 (s) * (TAN (s)) | | | | Condition | | Steps | | | | | | | | | |
| | | | | — | | 3 | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM |
| s | Argument | | | | | | | | ○ | | | | | s uses up to s+2. | |
| Function | | | | | | | | | | | | | | | |
| <div><div><div><div>s+2</div><div>15</div><div>Integer portion</div></div><div><div>s+1</div><div>0 15</div><div>Fractional portion</div></div></div><div>← TAN</div><div><div>s</div><div>15 0</div><div>0 to 360°</div></div></div> <div><ul style="list-style-type: none">Calculates the TAN value using the unsigned binary value designated by s as the argument, and sets the integer and fractional portions of the result in s+2 and s+1, respectively.The TAN value is indicated in a binary value, and negative values are indicated in two’s complements.If the calculation is performed normally, DER is equal to “0.”The fractional data is the value obtained by multiplying the actual value by 65,535.<p>* () indicates the display when the LADDER EDITOR is used.</p></div> | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">The argument is given in degrees in the $0 \leq s \leq 360$. When s is equal to 90 or s is equal to 270, H7FFF and HFFFF are set for s+2 and s+1, respectively. If s falls outside the range, DER is equal to “1” and the operation will not be performed.If s+1 and s+2 exceed the maximum value for the I/O number, DER is equal to “1” and the operation will not be performed.</div> | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | |
| <div><div><div><div>X00102 DIF2</div><div><div>WR0105 = 45</div><div>FUN 12 (WR0105)</div></div></div></div><div><div>LD X00102</div><div>AND DIF2</div><div>[</div><div>WR0105 = 45</div><div>FUN 12 (WR0105)</div><div>]</div></div></div> | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">An angle of 45° is set in WR0105.TAN operation is performed at the leading edge of X00102, and the fractional portion of the result is set in WR0106 and the whole number portion is set in WR0107 as binary values.<p>Execution results: WR0107=H0001, WR0106=H0000, WR0105=H002D</p></div> | | | | | | | | | | | | | | | |

| Item number | | Fun commands-8 | | | Name | | ARC SIN function | | | | | | | | | |
|--|-------------------------------|----------------|---|---|-----------------|-----------------------------------|------------------|-------|------------|----------------------|-------------|------------|------------|-----------------|-------------------|--|
| Ladder format | | | | | Condition code | | | | | Processing time (μs) | | | | | Remark | |
| FUN 13 (s) * (ASIN (s)) | | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | |
| | | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | |
| | | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | |
| Command format | | | | | Number of steps | | | | | 62 | ← | 63 | ← | 174 | ← | |
| FUN 13 (s) * (ASIN (s)) | | | | | Condition | | | Steps | | | | | | | | |
| | | | | | — | | | 3 | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| s | Argument (fractional portion) | | | | | | | | ○ | | | | | | s uses up to s+2. | |
| s+1 | Argument (integer portion) | | | | | | | | ○ | | | | | | | |
| Function | | | | | | | | | | | | | | | | |
| <div><div><div>15</div><div>s+2</div><div>0</div><div>0 to 90, 180 to 270</div></div><div>← SIN⁻¹</div><div><div>15</div><div>s+1</div><div>0</div><div>Integer portion</div></div><div><div>15</div><div>s</div><div>0</div><div>Fractional portion</div></div></div> <div><ul style="list-style-type: none">Calculates the SIN⁻¹ value using the unsigned binary value designated by s (fractional portion) and s+1 (integer portion) as the argument, and outputs s+2.The SIN⁻¹ value is described in degrees in the range of 0 to 90 and 180 to 270.If the calculation is completed normally, DER is equal to “0.”The fractional data is the value obtained by multiplying the actual value by 65,535.<p>* () indicates the display when the LADDER EDITOR is used.</p></div> | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">When the argument s+1.s > 1, DER is equal to “1” and operation will not be performed.When s+1 and s+2 exceed the maximum value for the I/O number, DER is equal to “1” and operation will not be performed.</div> | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | |
| <div><div><div>X00103 DIF3</div><div>DR0010 = H0000A48E FUN 13 (WR0010)</div></div></div> | | | <div><div>LD X00103 AND DIF3 [DR0010 = H0000A48E FUN 13 (WR0010)]</div></div> | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">Set data in DR0010 (WR0010, WR0011).SIN⁻¹ operation is performs at the leading edge of X00103, and the result is set in WR0012 as a binary value. Execution results: WR0012=H0028, WR0011=H0000, WR0010=HA48E</div> | | | | | | | | | | | | | | | | |

| Item number | | Fun commands-9 | | Name | | ARC COS function | | | | | | | | | | |
|---|-------------------------------|----------------|-----|-----------------|---------|-----------------------------------|-------|------|----------------------|-------------|------------|-----|-----------------|-------------------|------------|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 14 (s) * (ACOS (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | | | Number of steps | | | | | 63 | ← | 64 | ← | 177 | ← | | |
| FUN 14 (s) * (ACOS (s)) | | | | Condition | | | Steps | | | | | | | | | |
| | | | | — | | | 3 | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | |
| s | Argument (fractional portion) | | | | | | | | ○ | | | | | s uses up to s+2. | | |
| s+1 | Argument (integer portion) | | | | | | | | ○ | | | | | | | |
| Function | | | | | | | | | | | | | | | | |
| <div><div><div>s+2</div><div>150</div><div>0 to 180°</div></div><div>← COS⁻¹</div><div><div>s+1</div><div>150</div><div>Integer portion</div></div><div><div>s</div><div>150</div><div>Fractional portion</div></div></div> <div><ul style="list-style-type: none">Calculates the COS⁻¹ value using the unsigned binary value designated by s (fractional portion) and s+1 (integer portion) as the argument, and outputs s+2.The COS⁻¹ value is described in degrees in the range of 0 to 180.If the calculation is completed normally, DER is equal to “0.”The fractional data is the value obtained by multiplying the actual value by 65,535.<p>* () indicates the display when the LADDER EDITOR is used.</p></div> | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">When the argument s+1.s > 1, DER is equal to “1” and operation will not be performed.When s+1 and s+2 exceed the maximum value for the I/O number, DER is equal to “1” and operation will not be performed.</div> | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | |
| <div><div><div>X00104 DIF4</div><div>DR0024 = HFFFA871 FUN 14 (WR0024)</div></div><div><pre>LD X00104 AND DIF4 [DR0024 = HFFFA871 FUN 14 (WR0024)]</pre></div></div> | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">Set data in DR0024 (WR0024, WR0025).COS⁻¹ operation is performs at the leading edge of X00104, and the result is set in WR0026 as a binary value.<p>Execution results: WR0026=H006E, WR0025=HFFFF, WR0024=HA871</p></div> | | | | | | | | | | | | | | | | |

| Item number | | Fun commands-10 | | Name | | ARC TAN function | | | | | | | | | |
|--|-------------------------------|-----------------|---|-----------------|-----------------------------------|------------------|-------|------------|------------------------|-------------|-------------------------|------------|-----------------|-------------------|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | Remark | |
| FUN 15 (s) * (ATAN (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | |
| | | | | DER | ERR | SD | V | C | | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | | Max | | Ave | | |
| Command format | | | | Number of steps | | | | | 41 | ← | 42 91 | ← | 194 | ← | |
| FUN 15 (s) * (ATAN (s)) | | | | Condition | | | Steps | | | | | | | | |
| | | | | — | | | 3 | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| s | Argument (fractional portion) | | | | | | | ○ | | | | | | s uses up to s+2. | |
| s+1 | Argument (integer portion) | | | | | | | ○ | | | | | | | |
| Function | | | | | | | | | | | | | | | |
| <div><div><div>15s+20</div><div>0 to 180°</div></div><div>← TAN⁻¹</div><div><div>15s+1015s0</div><div>Integer portionFractional portion</div></div></div> | | | | | | | | | | | | | | | |
| <div><div><div><div>•</div><div>Calculates the TAN⁻¹ value using the unsigned binary value designated by s (fractional portion) and s+1 (integer portion) as the argument, and outputs s+2.</div></div><div><div><div>•</div><div>The TAN⁻¹ value is described in degrees in the range of 0 to 90 and 180 to 270.</div></div><div><div>•</div><div>If the calculation is completed normally, DER is equal to “0.”</div></div><div><div>•</div><div>The fractional data is the value obtained by multiplying the actual value by 65,535.</div></div></div><div><div>* () indicates the display when the LADDER EDITOR is used.</div></div></div></div> | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | |
| <div><div><div><div>•</div><div>When s+1 and s+2 exceed the maximum value for the I/O number, DER is equal to “1” and operation will not be performed.</div></div></div></div> | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | |
| <div><div><div><div><div>X00105 DIF5</div><div></div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><</div></div></div> | | | | | | | | | | | | | | | |

| Item number | Fun commands-11 | Name | Data search † | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-----------------------------|---------------------------|--|---------------|---------|-----------------------------------|------|----------------------|------------|--|----|----|----------|-------|--------------------------|--|--|-----|--|----------------|-----------|-----|--|----------------|-----------|-----|--|----------------|-----------|-----|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | Remark | | | | | | | | | | | | | | | | | | | | | |
| FUN 20 (s) * (DSRCH (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU5** | | The test condition is that searched data is 2 out of 10 words table. | | | | | | | | | | | | | | | | | | | | | |
| | | DER | ERR | SD | V | C | | | | | | | | | | | | | | | | | | | | | | | | |
| | | ↓ | ● | ● | ● | ● | Ave | Max | | | | | | | | | | | | | | | | | | | | | | |
| Command format | | Number of steps | | | | | 86.2 | 86.2 | | | | | | | | | | | | | | | | | | | | | | |
| FUN 20 (s) * (DSRCH (s)) | | Condition | | Steps | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | — | | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | Double word | | | Constant | Other | | | | | | | | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | | | | | | | | | | | | | | |
| s | Search data | | | | | | | ○ | | | | | | | | | | | | | | | | | | | | | | |
| s+1 | Top I/O No. of data table | | | | | | | ○ | | | | | | The real address is set. | | | | | | | | | | | | | | | | |
| s+2 | No. of search words | | | | | | | ○ | | | | | | s to s+4 are used. | | | | | | | | | | | | | | | | |
| Function | | <div><div><div><div>s</div><div>Search data (d)</div></div><div><div>s+1</div><div>Top I/O No. (a)</div></div><div><div>s+2</div><div>No. of search words (m)</div></div><div><div>s+3</div><div>Data position (i)</div></div><div><div>s+4</div><div>Quantity (n)</div></div></div><div><div>s to s+2 : Parameter</div><div>s+3, s+4 : Result</div></div><div><div><div>↑</div><div>a</div></div><div><div>↓</div><div>a+m-1</div></div><div><div>↕</div><div>m words</div></div></div><div><div>Data table</div><table><tr><td></td><td></td></tr><tr><td>...</td><td></td></tr><tr><td>Matched data d</td><td>1st data1</td></tr><tr><td>...</td><td></td></tr><tr><td>Matched data d</td><td>2st data1</td></tr><tr><td>...</td><td></td></tr><tr><td>Matched data d</td><td>3st data1</td></tr><tr><td>...</td><td></td></tr></table></div><div><ul style="list-style-type: none">Data specified in "s" will be searched in data specified in "s+1" and "s+2". If data is searched, the relative address from the top I/O and the quantity will be stored in "s+3" and "s+4".When no matched data is found, 0 is set in "s+3"Address in "s+1" is specified by ADRIO command.If operation is performed properly, DER = 0.</div><div>*Command name in () is indications of the ladder editor.</div></div> | | | | | | | | | | | | | | | ... | | Matched data d | 1st data1 | ... | | Matched data d | 2st data1 | ... | | Matched data d | 3st data1 | ... | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ... | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Matched data d | 1st data1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ... | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Matched data d | 2st data1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ... | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Matched data d | 3st data1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ... | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | <ul style="list-style-type: none">Address in "s+1" is specified to WR, WL or WM by ADRIO command., otherwise nothing executed with DER="1".If specified areas by "s" to "s+4" are over lapped, nothing executed with DER="1".If specified addresses in "s+1" and "s+2" do not exist in CPU, nothing executed with DER="1". | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program example | | <div><div><div>X00200</div><div>DIF10</div></div><div><div>WR0100 = H1010</div><div>ADRIO(WR0101 , WM0000)</div><div>WR0102 = H0100</div><div>FUN20 (WR0100)</div></div><div><div>LD X00200</div><div>AND DIF10</div><div>[</div><div>WR0100 = H1010</div><div>ADRIO (WR0101,WM0000)</div><div>WR0102 = H0100</div><div>FUN20 (WR0100)</div><div>]</div></div></div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program description | | <ul style="list-style-type: none">Data H1010 is searched for among 256 word of WM0000.Relative address and data quantity will be stored in WR103 and WR104. | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU 516/548 only.

| Item number | Fun commands-12 | Name | Table search [†] | | | | | | | | | | | |
|--|---|--|---------------------------|---------|-----------------------------------|------|----------------------|------------|---|-------------|----|------------|----------|--------------------------|
| Ladder format | | Condition code | | | | | Processing time (μs) | | Remark | | | | | |
| FUN 21 (s) * (TSRCH (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU5** | | The test condition is that searched data block is 1 block, 2 words in 10 th block. | | | | | |
| | | DER | ERR | SD | V | C | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | | | | | | |
| Command format | | Number of steps | | | | | 104.2 | 104.2 | | | | | | |
| FUN 21 (s) * (TSRCH (s)) | | Condition | | Steps | | | | | | | | | | |
| | | — | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | |
| s | Data table top I/O No. | | | | | | | ○ | | | | | | The real address is set. |
| s+1 | Length of one No. | | | | | | | ○ | | | | | | s to s+3 are used. |
| s+2 | Search block No. | | | | | | | ○ | | | | | | |
| s+3 | Fetch table top I/O No. | | | | | | | ○ | | | | | | The real address is set. |
| Function | | | | | | | | | | | | | | |
| s | Data table top I/O No (real address) (a1) | a1 | | | | | | | | | | | | |
| s+1 | Length of one block (m) | a1+m-1 | | | | | | | | | | | | |
| s+2 | Search block No. (n) | a+m | | | | | | | | | | | | |
| s+3 | Fetch table top I/O (real address) (a2) | a1+2m- | | | | | | | | | | | | |
| | | a1+(n-1)*m | | | | | | | | | | | | |
| | | a1+n*(m-1) | | | | | | | | | | | | |
| <ul style="list-style-type: none">• Data will be searched (taken) in data table specified in "s" and "s+1", and stored in the address specified in "s+3".• Addresses in "s+1" and "s+3" are specified by ADRIO command.• If operation is performed properly, DER = 0. <p>*Command name in () is indications of the ladder editor.</p> | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">• Addresses in "s+1" and "s+3" are specified to WR, WL or WM by ADRIO command, otherwise nothing executed with DER="1".• If specified areas by "s" and "s+3" are over lapped, nothing executed with DER="1".• If specified addresses in "s" or "s+3" does not exist in CPU, nothing executed with DER="1". | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | |
| | | <div>ADRIO(WR0110 , WM0000) WR0111 = 2 WR0112 = 10 ADRIO(WR0113 , WM0100) FUN21 (WR0110)</div> <div>LD X00201 AND DIF11 [WR0100 = H1010 ADRIO (WR0110,WM0000) WR0111 = 2 WR0112 = 10 ADRIO (WR0113,WM0100) FUN21 (WR0110)]</div> | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">• 10th data block will be taken out of data table from WM0000, which consist of 2 word block each, and stoed in WM0100. | | | | | | | | | | | | | | |

[†]: Supported by the EH-CPU 516/548 only.

| Item number | FUN command-13 | Name | | Check code calculation† | | | | | | | | | | | | | | | | | | | | | | | |
|----------------|-----------------------------------|---|------|-------------------------|-----------------------------------|------|-----------------|-------------|-----------|---|--------|----|----------|------------|------------------------------|-----|-----------------------------------|-----|----------------------|-----|-------------------------|-----|-----------------|-----|------------------------|-----|---------------------------|
| Ladder format | | Condition code | | | | | Processing time | | | | Remark | | | | | | | | | | | | | | | | |
| FUN 22 (s) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU5** | | Other CPU | | | | | | | | | | | | | | | | | | |
| | | DER | ERR | SD | V | C | Ave. | Max. | - | - | | | | | | | | | | | | | | | | | |
| | | ↕ | ● | ● | ● | ● | 783.2 | ← | - | - | | | | | | | | | | | | | | | | | |
| Command format | | Number of steps | | | | | | | | | | | | | | | | | | | | | | | | | |
| FUN 22 (s) | | Condition | | | Steps | | | | | | | | | | | | | | | | | | | | | | |
| | | - | | | 3 | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | Word | | | Double word | | | Others | | | | | | | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | | | DX | DY | DR, DL, DM | | | | | | | | | | | | | |
| s | Starting I/O | | | | | | | ○ | | | | | s to s+6 | | | | | | | | | | | | | | |
| Function | | <div><ul style="list-style-type: none">• This command creates check code to be attached to serial communication message frame.• Calculation type is specified in the parameter "s".• Byte format (high or low byte) is specified in the parameter "s+1".• Data address and data length are specified in "s+2", "s+3" and "s+4".• Result data address is specified in "s+5" and "s+6".</div> <div><div><div>FUN 22 (s)</div><table><tr><td>s</td><td>[0] Calculation type setting</td></tr><tr><td>s+1</td><td>[1] Byte format (data and result)</td></tr><tr><td>s+2</td><td>[2] I/O type of data</td></tr><tr><td>s+3</td><td>[3] I/O address of data</td></tr><tr><td>s+4</td><td>[4] Data length</td></tr><tr><td>s+5</td><td>[5] I/O type of result</td></tr><tr><td>s+6</td><td>[6] I/O address of result</td></tr></table></div><div><div>Data to be calculated</div><div>Result (check code)</div><div>Data length (Word / Byte)</div></div></div> | | | | | | | | | | | | s | [0] Calculation type setting | s+1 | [1] Byte format (data and result) | s+2 | [2] I/O type of data | s+3 | [3] I/O address of data | s+4 | [4] Data length | s+5 | [5] I/O type of result | s+6 | [6] I/O address of result |
| s | [0] Calculation type setting | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+1 | [1] Byte format (data and result) | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+2 | [2] I/O type of data | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+3 | [3] I/O address of data | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+4 | [4] Data length | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+5 | [5] I/O type of result | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+6 | [6] I/O address of result | | | | | | | | | | | | | | | | | | | | | | | | | | |

†: Supported by the EH-CPU 516/548 only.

Function


[0] Calculation type setting

Calculation type to be selected from 7 types as follwos.

| Setting | Calculation type | Result (Check code) | |
|---------|----------------------------|---------------------|------------------------------------|
| H0000 | (B1) + (B2) + ... +(Bn) | Byte | (ex. 12) |
| H0001 | (B1) + (B2) + ... +(Bn) | Word | Normal (ex.1234) |
| H0002 | (B1) + (B2) + ... +(Bn) | Word | Byte swapped (ex.3412) |
| H0003 | (B1) + (B2) + ... +(Bn) | Word | ASCII converted, normal (ex.3132) |
| H0004 | (B1) + (B2) + ... +(Bn) | Word | ASCII converted, swapped (ex.3231) |
| H0005 | (W1) + (W2) + ... +(Wn) | Word | Normal (ex. 1234) |
| H0006 | (W1) + (W2) + ... +(Wn) | Word | Swapped (ex. 3412) |
| H0010 | { (B1)xor(B2)} xor·xor(Bn) | Byte | (ex. 12) |
| H0011 | { (B1)xor(B2)} xor·xor(Bn) | Word | ASCII converted, normal (ex. 3132) |
| H0012 | { (B1)xor(B2)} xor·xor(Bn) | Word | ASCII converted, swapped (ex.3231) |
| H0013 | { (W1)xor(W2)} xor·xor(Wn) | Word | Normal (ex. 1234) |
| H0014 | { (W1)xor(W2)} xor·xor(Wn) | Word | Swapped (ex. 3412) |
| Others | DATA Error (DER ON) | | |

[1] Byte format (data and result) :

Calculation starting byte position and result storing position are specified as below in case of byte oriented calculation.



H00xx : Calculation starts from high byte
H01xx : Calculation starts from low byte
Others : DATA Error (DER ON)

Setting value : H00xx

| | | |
|---|-----|----|
| B | B1 | B2 |
| | B3 | B4 |
| | ... | |

| | |
|---|-----|
| W | W1 |
| | W2 |
| | ... |

Setting value : H01xx

| | | |
|---|-----|----|
| B | — | B1 |
| | B2 | B3 |
| | ... | |

| | | |
|---|------|------|
| W | — | W1_h |
| | W1_l | W2_h |
| | W2_l | ... |

Hxx00 : Data storing starts from high byte
Hxx01 : Data storing starts from low byte *
Others : Data Error (DER ON)
* If result is WORD, L-byte is stored in H-byte position of the next word as below.

Setting value : Hxx00

| | | |
|---|-----|---|
| B | [1] | - |
|---|-----|---|

| | |
|---|-----|
| W | [1] |
|---|-----|

Setting value : Hxx01

| | | |
|---|---|-----|
| B | - | [1] |
|---|---|-----|

| | | |
|---|-----|-----|
| W | - | [1] |
| | [1] | - |

- : Existing data
[1] : Result

Function

[2] I/O type of data :

Type WR:H000A, WL:H000B, WM:H000C

[3] I/O address of data:

I/O address H0000 - HFFFF

[4] Data length :

Byte data : unit is byte (H0000 - HFFFF)

Word data : unit is word (H0000 - HFFFF)

[5] I/O type of result

Type WR:H000A, WL:H000B, WM:H000C

[6] I/O address of result:

I/O address H0000 - HFFFF

Sample program

<Sent data frame> Check code = XOR for each byte and ASCII conversion

| STX | Data [0101000500] | C.C. | CR |
|------|------------------------|-------|------|
| (02) | (30313031303030353030) | (?) | (0D) |

<Sent data area>

| | | |
|-----|-----|-----|
| WM0 | 0 2 | 3 0 |
| WM1 | 3 1 | 3 0 |
| WM2 | 3 1 | 3 0 |
| WM3 | 3 0 | 3 0 |
| WM4 | 3 5 | 3 0 |
| WM5 | 3 0 | ? ? |
| WM6 | ? ? | 0 D |


<Sample program>

WR0 = H0011 [1]
WR1 = H0101 [2]
WR2 = H000C } [3]
WR3 = H0000 }
WR4 = 10 [4]
WR5 = H000C } [5]
WR6 = H0005 }
FUN 22 (WR0)

- [1] Calculation type setting (Byte, ASCII, normal) : H0011
- [2] Calculation starts from L-byte
Data storing from L-byte : (H0101)
- [3] Data address : WM0 (H000C, H0000)
- [4] Data length : 10 bytes
- [5] Result address : WM5 (H000C, H0005)

<Result>

| | | |
|-----|-----|-----|
| WM0 | 0 2 | 3 0 |
| WM1 | 3 1 | 3 0 |
| WM2 | 3 1 | 3 0 |
| WM3 | 3 0 | 3 0 |
| WM4 | 3 5 | 3 0 |
| WM5 | 3 0 | 3 0 |
| WM6 | 3 5 | 0 D |



| Item number | FUN command-14 | Name | | Check code verifying [†] | | | | | | | | | | |
|----------------|----------------|---|------|-----------------------------------|-----------------------------------|-------|-----------|------------|-----------|-----------------|----|--|----------|------------|
| Ladder format | | Condition code | | | | | | | | Processing time | | | | Remark |
| FUN 23 (s) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU5** | | Other CPU | | | | | |
| | | DER | ERR | SD | V | C | Ave. | Max. | - | - | | | | |
| | | ↕ | ● | ● | ● | ● | 790.2 | ← | - | - | | | | |
| Command format | | Number of steps | | | | | | | | | | | | |
| FUN 23 (s) | | Conditon | | | | Steps | | | | | | | | |
| | | - | | | | 3 | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Others | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | W X | W Y | WR, WL, WM | TC | DX | DY | | | DR, DL, DM |
| s | Starting I/O | | | | | | | ○ | | | | | s to s+9 | |
| Function | | <div><ul style="list-style-type: none">• This command verifies check code attached in received message frame.• Calculation type is specified in the parameter "s".• Byte format (high or low byte) is specified in the parameter "s+1".• Data address and data length are specified in "s+2", "s+3" and "s+4".• Check code specified in "s+5" and "s+6" is compared with calculated check code, and result is stored in the address specified in "s+7".</div> | | | | | | | | | | | | |
| s | [0] | Calculation type setting | | | | | | | | | | | | |
| s+1 | [1] | Byte format (data) | | | | | | | | | | | | |
| s+2 | [2] | I/O type of data | | | | | | | | | | | | |
| s+3 | [3] | I/O address of data | | | | | | | | | | | | |
| s+4 | [4] | Data length | | | | | | | | | | | | |
| s+5 | [5] | I/O type of check code | | | | | | | | | | | | |
| s+6 | [6] | I/O address of check code | | | | | | | | | | | | |
| s+7 | [7] | Verified result | | | | | | | | | | | | |
| s+8 | [8] | Calculation result | | | | | | | | | | | | |
| s+9 | [9] | Calculation result | | | | | | | | | | | | |

[†]: Supported by the EH-CPU 516/548 only.

Function

[0] Calculation type setting :

Calculation type to be selected from 7 types as follows.

| Value | Calculation type | Result (Check code) | |
|--------|---|---------------------|------------------------------------|
| H0000 | $(B1) + (B2) + \dots + (Bn)$ | Byte | (ex. 12) |
| H0001 | $(B1) + (B2) + \dots + (Bn)$ | Word | Normal (ex.1234) |
| H0002 | $(B1) + (B2) + \dots + (Bn)$ | Word | Byte swapped (ex.3412) |
| H0003 | $(B1) + (B2) + \dots + (Bn)$ | Byte | ASCII converted, normal (ex.3132) |
| H0004 | $(B1) + (B2) + \dots + (Bn)$ | Byte | ASCII converted, swapped (ex.3231) |
| H0005 | $(W1) + (W2) + \dots + (Wn)$ | Word | Normal (ex. 1234) |
| H0006 | $(W1) + (W2) + \dots + (Wn)$ | Word | Swapped (ex. 3412) |
| H0010 | $\{ (B1) \text{ xor } (B2) \} \text{ xor } \dots \text{ xor } (Bn)$ | Byte | (ex. 12) |
| H0011 | $\{ (B1) \text{ xor } (B2) \} \text{ xor } \dots \text{ xor } (Bn)$ | Byte | ASCII converted, normal (ex. 3132) |
| H0012 | $\{ (B1) \text{ xor } (B2) \} \text{ xor } \dots \text{ xor } (Bn)$ | Byte | ASCII converted, swapped (ex.3231) |
| H0013 | $\{ (W1) \text{ xor } (W2) \} \text{ xor } \dots \text{ xor } (Wn)$ | Word | Normal (ex. 1234) |
| H0014 | $\{ (W1) \text{ xor } (W2) \} \text{ xor } \dots \text{ xor } (Wn)$ | Word | Swapped (ex. 3412) |
| Others | DATA Error (DER ON) | | |

[1] Byte format :

Verification starting byte position is specified as below in case of byte oriented calculation.

| Starting Word | Byte type | | Word type | | Word type | |
|---------------|-----------|------|-----------|------|-----------|--------|
| | (B1) | (B2) | (B1) | (B2) | (W1_H) | (W1_L) |
| +1 | (B3) | (B4) | (B2) | (B3) | (W2_H) | (W2_L) |
| +2 | (B5) | (B6) | (B4) | (B5) | (W3_H) | (W3_L) |
| | ... | ... | ... | ... | ... | ... |
| | ... | ... | ... | ... | ... | ... |
| +(m-1) | (Bn-1) | (Bn) | (Bn) | | (Wn_H) | (Wn_L) |

H : High byte
L : Low byte
Wn : Wn_H Wn_L

<High byte>

Verification starting byte

<Low byte>

Check code starting byte

H00xx : Verification starts from high byte

H01xx : Verification starts from low byte

Others : DATA Error (DER ON)

Setting value : H00xx

| | | |
|---|-----|----|
| B | B1 | B2 |
| | B3 | B4 |
| | ... | |

| | |
|---|-----|
| W | W1 |
| | W2 |
| | ... |

Setting value : H01xx

| | | |
|---|-----|----|
| B | — | B1 |
| | B2 | B3 |
| | ... | |

| | | |
|---|------|------|
| W | — | W1_h |
| | W1_l | W2_h |
| | W2_l | ... |

Hxx00 : Check code starts from high byte

Hxx01 : Check code starts from low byte *

Others : Data Error (DER ON)

* If check code is WORD, L-byte is taken in H-byte position of the next word as below.

Setting value : Hxx00

| | | |
|---|-----|---|
| B | [1] | - |
|---|-----|---|

| | |
|---|-----|
| W | [1] |
|---|-----|

Setting value : Hxx01

| | | |
|---|---|-----|
| B | - | [1] |
|---|---|-----|

| | | |
|---|-----|-----|
| W | - | [1] |
| | [1] | - |

- : Existing data

[1] : Result

| |
|---|
| Function |
| [2] I/O type of data : Type WR:H000A, WL:H000B, WM:H000C |
| [3] I/O address of data : I/O address H0000 - HFFFF |
| [4] Data length Byte data : unit is byte (H0000 - HFFFF) Word data : unit is word (H0000 - HFFFF) |
| [5] I/O type of check code : Type WR:H000A, WL:H000B, WM:H000C |
| [6] I/O address of check code I/O address H0000 - HFFFF |
| [7] Verifying result : OK - H8000, NG - H80FF |
| [8] [9] Calculation result : Calculated value is stored in this area. If existing check code is separated in 2 words, calculated value is also stored in 2 words separately. |

| | | | | | | | | | | | | | | | | | | | | | |
|---|-------------|-------|-------------|-------|-------------|---------|-------------|----------|-------|-------------|---------|-------------|----------------|-----|-----|-------|-----|-----|-------|-----|-----|
| Sample program | | | | | | | | | | | | | | | | | | | | | |
| <Received data frame> Check code = Sum for each byte and ASCII conversion | | | | | | | | | | | | | | | | | | | | | |
| <table><tr><td>WR100</td><td>0 2</td><td>3 0</td></tr><tr><td>WR101</td><td>3 1</td><td>3 0</td></tr><tr><td>WR102</td><td>3 1</td><td>3 0</td></tr><tr><td>WR103</td><td>3 0</td><td>3 0</td></tr><tr><td>WR104</td><td>3 5</td><td>3 0</td></tr><tr><td>WR105</td><td>3 0</td><td>4 5</td></tr><tr><td>WR106</td><td>3 7</td><td>0 D</td></tr></table> | WR100 | 0 2 | 3 0 | WR101 | 3 1 | 3 0 | WR102 | 3 1 | 3 0 | WR103 | 3 0 | 3 0 | WR104 | 3 5 | 3 0 | WR105 | 3 0 | 4 5 | WR106 | 3 7 | 0 D |
| WR100 | 0 2 | 3 0 | | | | | | | | | | | | | | | | | | | |
| WR101 | 3 1 | 3 0 | | | | | | | | | | | | | | | | | | | |
| WR102 | 3 1 | 3 0 | | | | | | | | | | | | | | | | | | | |
| WR103 | 3 0 | 3 0 | | | | | | | | | | | | | | | | | | | |
| WR104 | 3 5 | 3 0 | | | | | | | | | | | | | | | | | | | |
| WR105 | 3 0 | 4 5 | | | | | | | | | | | | | | | | | | | |
| WR106 | 3 7 | 0 D | | | | | | | | | | | | | | | | | | | |
| <Sample program> | | | | | | | | | | | | | | | | | | | | | |
| <table><tr><td>WM0 = H0003</td><td>[1]</td></tr><tr><td>WM1 = H0101</td><td>[2]</td></tr><tr><td>WM2 = H000A</td><td rowspan="2">} [3]</td></tr><tr><td>WM3 = H0100</td></tr><tr><td>WM4 = 10</td><td>[4]</td></tr><tr><td>WM5 = H000A</td><td rowspan="2">} [5]</td></tr><tr><td>WM6 = H0105</td></tr><tr><td colspan="2">FUN 23 (WM0)</td></tr></table> | WM0 = H0003 | [1] | WM1 = H0101 | [2] | WM2 = H000A | } [3] | WM3 = H0100 | WM4 = 10 | [4] | WM5 = H000A | } [5] | WM6 = H0105 | FUN 23 (WM0) | | | | | | | | |
| WM0 = H0003 | [1] | | | | | | | | | | | | | | | | | | | | |
| WM1 = H0101 | [2] | | | | | | | | | | | | | | | | | | | | |
| WM2 = H000A | } [3] | | | | | | | | | | | | | | | | | | | | |
| WM3 = H0100 | | | | | | | | | | | | | | | | | | | | | |
| WM4 = 10 | [4] | | | | | | | | | | | | | | | | | | | | |
| WM5 = H000A | } [5] | | | | | | | | | | | | | | | | | | | | |
| WM6 = H0105 | | | | | | | | | | | | | | | | | | | | | |
| FUN 23 (WM0) | | | | | | | | | | | | | | | | | | | | | |
| [1] Calculation type setting (Byte, ASCII, normal) :H0003 | | | | | | | | | | | | | | | | | | | | | |
| [2] Verification starts from L-byte Check code starts from L-byte : H0101 | | | | | | | | | | | | | | | | | | | | | |
| [3] Data address : WR100 (H000A, H0100) | | | | | | | | | | | | | | | | | | | | | |
| [4] Data length : 10 bytes | | | | | | | | | | | | | | | | | | | | | |
| [5] Check code address : WR105 (H000A, H00105) | | | | | | | | | | | | | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | |
|---|------|-----|-----|------|-----|-----|------|-----|-----|------|-----|-----|------|-----|-----|------|-----|-----|------|-----|-----|
| <Result> | | | | | | | | | | | | | | | | | | | | | |
| <table><tr><td>WR10</td><td>0 2</td><td>3 0</td></tr><tr><td>WR11</td><td>3 1</td><td>3 0</td></tr><tr><td>WR12</td><td>3 1</td><td>3 0</td></tr><tr><td>WR13</td><td>3 0</td><td>3 0</td></tr><tr><td>WR14</td><td>3 5</td><td>3 0</td></tr><tr><td>WR15</td><td>3 0</td><td>4 5</td></tr><tr><td>WR16</td><td>3 7</td><td>0 D</td></tr></table> <div><div>31 30 31 30 30 30 35 30 30</div><div>30+31+30+31+30+30+30+35+30+30</div><div>= H 0 1 E 7 ⇒ E7</div><div>↓ ASCII</div><div>45 37</div></div> | WR10 | 0 2 | 3 0 | WR11 | 3 1 | 3 0 | WR12 | 3 1 | 3 0 | WR13 | 3 0 | 3 0 | WR14 | 3 5 | 3 0 | WR15 | 3 0 | 4 5 | WR16 | 3 7 | 0 D |
| WR10 | 0 2 | 3 0 | | | | | | | | | | | | | | | | | | | |
| WR11 | 3 1 | 3 0 | | | | | | | | | | | | | | | | | | | |
| WR12 | 3 1 | 3 0 | | | | | | | | | | | | | | | | | | | |
| WR13 | 3 0 | 3 0 | | | | | | | | | | | | | | | | | | | |
| WR14 | 3 5 | 3 0 | | | | | | | | | | | | | | | | | | | |
| WR15 | 3 0 | 4 5 | | | | | | | | | | | | | | | | | | | |
| WR16 | 3 7 | 0 D | | | | | | | | | | | | | | | | | | | |
| Verifying OK (WM7=H8000) as right value. (WM7=H80FF in case of wrong value) | | | | | | | | | | | | | | | | | | | | | |

| Item number | Fun commands-15 | Name | | Conversion from 16-bit unsigned binary to decimal ASCII data † (BINARY TO DECIMAL ASCII) | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|----------------------------|---|-----------------|---|-----------------------------------|------|------------------------|------------|-------------------------|-------------|-----------------|----------|--------|------------------|----|----|---|-------|-----------------|--|-----------------|-------|-----------------|--|-----------------|-------|-----------------|--|------|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | | | | | |
| FUN 30 (s) * (BINDA (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | | | | | | | | | | | | | | | | |
| | | DER | ERR | SD | V | C | | | | | | | | | | | | | | | | | | | | | | | |
| | | ↕ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | | | |
| Command format | | Number of steps | | | | | 140 | ← | 141 | ← | | | | | | | | | | | | | | | | | | | |
| FUN 30 (s) * (BINDA (s)) | | Condition | | | Steps | | | | | | | | | | | | | | | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | | | | | | | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | | | | | | | | | | | | | |
| s | Argument (conversion data) | | | | | | | ○ | | | | | | s uses up to s+3 | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div>16-bit unsigned binary data</div><div><div>s</div><div>0 to 65535</div></div><div>10ⁿ: ASCII code in the 10ⁿ place</div></div><div><div>Decimal ASCII data</div><table><tr><td></td><td>15</td><td>87</td><td>0</td></tr><tr><td>s + 1</td><td>10⁴</td><td></td><td>10³</td></tr><tr><td>s + 2</td><td>10²</td><td></td><td>10¹</td></tr><tr><td>s + 3</td><td>10⁰</td><td></td><td>NULL</td></tr></table></div><div><ul style="list-style-type: none">The 16-bit unsigned binary data specified by argument s is converted to 5-digit decimal ASCII code and the result is stored in s + 1 to s + 3.Leading zeros of the conversion result are suppressed and these digits are replaced by H20 (space).The remaining digits after converting to ASCII are replaced by NULL, which indicates the end of a string.If the operation is performed normally, DER is set to “0.”<p>* () indicates the display when the LADDER EDITOR is used.</p></div></div> | | | | | | | | | | | | | | | 15 | 87 | 0 | s + 1 | 10 ⁴ | | 10 ³ | s + 2 | 10 ² | | 10 ¹ | s + 3 | 10 ⁰ | | NULL |
| | 15 | 87 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 1 | 10 ⁴ | | 10 ³ | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 2 | 10 ² | | 10 ¹ | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 3 | 10 ⁰ | | NULL | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | <ul style="list-style-type: none">If s + 1 to s + 3 exceed the maximum I/O number, DER is set to “1” and no operation is performed. | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program example | | <div><div><div><div>X00300</div><div>DIF30</div></div><div><div>WR0000 = 12345</div><div>FUN 30 (WR0000)</div></div></div><div><div>LD X00300</div><div>AND DIF30</div><div>[</div><div>WR0000 = 12345</div><div>FUN 30 (WR0000)</div><div>]</div></div></div> | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program description | | <ul style="list-style-type: none">The binary data 12345 stored in WR0000 is converted to ASCII data.The conversion result is stored in WR0001 to 3. <p>Execution results: WR0000=12345 (H3039), WR0001=H3132, WR0002=H3334, WR0003=H3500</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

FUN 30 (s)

| Item number | Fun commands-16 | Name | | Conversion from 32-bit signed binary to decimal ASCII data † (DOUBLE BINARY TO DECIMAL ASCII) | | | | | | | | | | |
|---|-------------------|---|------|--|-----------------------------------|------|------------------------|------------|-------------------------|-------------|-----------------|----------|-------|-------------------|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | Remark | | |
| FUN 31 (s) * (DBINDA (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | |
| | | DER | ERR | SD | V | C | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | Number of steps | | | | | 199 | ← | 200 | ← | | | | |
| FUN 31 (s) * (DBINDA (s)) | | Condition | | | Steps | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM |
| s | Argument (lower) | | | | | | | ○ | | | | | | -2,147,483,648 to |
| s | Argument (higher) | | | | | | | ○ | | | | | | 2,147,483,647 |
| Function | | | | | | | | | | | | | | |
| <div><div><div>32-bit signed binary data</div><div><div>s</div><div>Lower 16-bit</div></div><div><div>s + 1</div><div>Higher 16-bit</div></div></div><div><div>Signs</div><div>Plus: H20 (space)</div><div>Minus: H2D ("‑")</div><div>10ⁿ: ASCII code in the 10ⁿ place</div></div></div> <div><div><div>Decimal ASCII data</div><div><div>15</div><div>87</div><div>0</div></div><div><div>s + 2</div><div>Sign</div><div>10⁹</div></div><div><div>s + 3</div><div>10⁸</div><div>10⁷</div></div><div><div>s + 4</div><div>10⁶</div><div>10⁵</div></div><div><div>s + 5</div><div>10⁴</div><div>10³</div></div><div><div>s + 6</div><div>10²</div><div>10¹</div></div><div><div>s + 7</div><div>10⁰</div><div>NULL</div></div></div></div> <div><div><div>The 32-bit signed binary data specified by arguments s (lower) and s + 1 (higher) is converted to 10-digit decimal ASCII code and the result is stored in s + 2 to s + 7.</div><div>If the sign is a plus, it is indicated by H20 (space), and by H2D ("‑") if it is a minus.</div><div>Leading zeros of the conversion result are suppressed and these digits are replaced by H20 (space).</div><div>The remaining digits after converting to ASCII are replaced by NULL, which indicates the end of a string.</div><div>If the operation is performed normally, DER is set to "0."</div></div><div>* () indicates the display when the LADDER EDITOR is used.</div></div> | | | | | | | | | | | | | | |
| Cautionary notes | | <div><div>If s + 1 to s + 7 exceed the maximum I/O number, DER is set to "1" and no operation is performed.</div></div> | | | | | | | | | | | | |
| Program example | | <div><div><div><div>X00301</div><div>DIF31</div></div><div><div>DR0010 = -1234567</div><div>FUN 31 (WR0010)</div></div></div><div><div>LD X00301</div><div>AND DIF31</div><div>[</div><div>DR0010 = -1234567</div><div>FUN 31 (WR0010)</div><div>]</div></div></div> | | | | | | | | | | | | |
| Program description | | <div><div><div>The binary data -1234567 stored in WR0000 (WR0010, WR0011) is converted to ASCII data.</div><div>The conversion result is stored in WR0012 to WR0017.</div></div><div>Execution results: DR0010=-1234567 (HFFED2979), WR0012=H2020, WR0013=H2020, WR0014=H3132, WR0015=H3334, WR0016=H3536, WR0017=H3700</div></div> | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

| Item number | Fun commands-17 | Name | | Conversion from 16-bit binary to hexadecimal ASCII data [†] (BINARY TO HEXA ASCII) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|----------------------------|--|------|--|-----------------------------------|------|------------------------|------------|-------------------------|-------------|-----------------|------------|----------|------------------|--|----|---|---|---|-------|-----------------|--|--|-----------------|-------|-----------------|--|--|-----------------|-------|------|--|--|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | | | | | | | | | | |
| FUN 32 (s) * (BINHA (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | | | | | | | | | | | | | | | | | | | | | |
| | | DER | ERR | SD | V | C | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | | | | | | | | |
| Command format | | Number of steps | | | | | 124 | ← | 125 | ← | | | | | | | | | | | | | | | | | | | | | | | | |
| FUN 32 (s) * (BINHA (s)) | | Condition | | | Steps | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | | | | | | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | | | | | | | | | | | | | |
| s | Argument (conversion data) | | | | | | | ○ | | | | | | s uses up to s+3 | | | | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div>16-bit unsigned binary data</div><div><div>s</div><div>H0 to HFFFF</div></div><div>16ⁿ: ASCII code in the 16ⁿ place</div></div><div><div>Hexadecimal ASCII data</div><table><tr><td></td><td>15</td><td>8</td><td>7</td><td>0</td></tr><tr><td>s + 1</td><td>16³</td><td></td><td></td><td>16²</td></tr><tr><td>s + 2</td><td>16¹</td><td></td><td></td><td>16⁰</td></tr><tr><td>s + 3</td><td colspan="4">NULL</td></tr></table></div><div><ul style="list-style-type: none">The 16-bit unsigned binary data specified by argument s is converted to 4-digit hexadecimal ASCII code and the result is stored in s + 1 to s + 3.Leading zeros of the conversion result are not suppressed.NULL after ASCII data indicates the end of a string.If the operation is performed normally, DER is set to “0.”<p>* () indicates the display when the LADDER EDITOR is used.</p></div></div> | | | | | | | | | | | | | | | | 15 | 8 | 7 | 0 | s + 1 | 16 ³ | | | 16 ² | s + 2 | 16 ¹ | | | 16 ⁰ | s + 3 | NULL | | | |
| | 15 | 8 | 7 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 1 | 16 ³ | | | 16 ² | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 2 | 16 ¹ | | | 16 ⁰ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 3 | NULL | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | <ul style="list-style-type: none">If s + 1 to s + 3 exceed the maximum I/O number, DER is set to “1” and no operation is performed. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program example | | <div><div><div>X00302</div><div>DIF32</div></div><div><div>WR0020 = H1234</div><div>FUN 32 (WR0020)</div></div></div> <div><div>LD X00302</div><div>AND DIF32</div><div>[</div><div>WR0020 = H1234</div><div>FUN 32 (WR0020)</div><div>]</div></div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program description | | <ul style="list-style-type: none">The binary data H1234 stored in WR0020 is converted to ASCII data.The conversion result is stored in WR0021 to WR0023. <p>Execution results: WR0020=H1234, WR0021=H3132, WR0022=H3334, WR0023=H0000</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

| Item number | Fun commands-18 | Name | Conversion from 32-bit binary to hexadecimal ASCII data † (DOUBLE BINARY TO HEXA ASCII) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|-------------------|--|--|---------|-----------------------------------|-------|------|------------------------|-----|-------------------------|-----|-----------------|----------|---|---------------------|--|---|--|--|--|--|--|--|--|--|--|--|--|--|-----------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|---------------------|--|---|--|--|--|--|--|--|--|--|--|--|--|--|
| Ladder format | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| FUN 33 (s) * (DBINHA (s)) | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | DER | ERR | SD | V | C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Command format | | | Number of steps | | | | | 168 | ← | 169 | ← | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| FUN 33 (s) * (DBINHA (s)) | | | Condition | | | Steps | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | — | | | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s | Argument (lower) | | | | | | | ○ | | | | | | H00000000 to HFFFFFFF s uses up to s+6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 1 | Argument (higher) | | | | | | | ○ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div>32-bit unsigned binary data</div><div><div>s</div><div>Lower 16-bit</div></div><div><div>s + 1</div><div>Higher 16-bit</div></div></div><div><div>16ⁿ: ASCII code in the 16ⁿ place</div></div><div><div>Hexadecimal ASCII data</div><div><div>15</div><div>8</div><div>7</div><div>0</div></div><div><div>s + 2</div><div>16⁷</div><div>16⁶</div></div><div><div>s + 3</div><div>16⁵</div><div>16⁴</div></div><div><div>s + 4</div><div>16³</div><div>16²</div></div><div><div>s + 5</div><div>16¹</div><div>16⁰</div></div><div><div>s + 6</div><div>NULL</div></div></div></div> <div><div><div><div>•</div><div>The 32-bit signed binary data specified by arguments s (lower) and s + 1 (higher) is converted to an 8-digit hexadecimal ASCII code and the result is stored in s + 2 to s + 6.</div></div><div><div>•</div><div>Leading zeros of the conversion result are not suppressed.</div></div><div><div>•</div><div>NULL after ASCII data indicates the end of a string.</div></div><div><div>•</div><div>If the operation is performed normally, DER is set to “0.”</div></div><div><div>•</div><div>* () indicates the display when the LADDER EDITOR is used.</div></div></div></div> <tr><td colspan="2">Cautionary notes</td><td colspan="13"><div><div><div>•</div><div>If s + 1 to s + 6 exceed the maximum I/O number, DER is set to “1” and no operation is performed.</div></div></div></td></tr> <tr><td colspan="2">Program example</td><td colspan="13"><div><div><div><div><div>X00303</div><div>DIF33</div></div><div><div>DR0030 = H001289AB</div><div>FUN 33 (WR0030)</div></div></div><div><div>LD X00303</div><div>AND DIF33</div><div>[</div><div>DR0030 = H001289AB</div><div>FUN 33 (WR0030)</div><div>]</div></div></div></div><tr><td colspan="2">Program description</td><td colspan="13"><div><div><div><div>•</div><div>The binary data H001289AB stored in DR0030 (WR0030, WR0031) is converted to ASCII data.</div></div><div><div>•</div><div>The conversion result is stored in WR0032 to WR0036.</div></div></div><div>Execution results: DR0030=H001289AB, WR0032=H3030, WR0033=H3132, WR0034=H3839, WR0035=H4142, WR0036=H0000</div></div></td></tr></td></tr> | | | | | | | | | | | | | | | Cautionary notes | | <div><div><div>•</div><div>If s + 1 to s + 6 exceed the maximum I/O number, DER is set to “1” and no operation is performed.</div></div></div> | | | | | | | | | | | | | Program example | | <div><div><div><div><div>X00303</div><div>DIF33</div></div><div><div>DR0030 = H001289AB</div><div>FUN 33 (WR0030)</div></div></div><div><div>LD X00303</div><div>AND DIF33</div><div>[</div><div>DR0030 = H001289AB</div><div>FUN 33 (WR0030)</div><div>]</div></div></div></div> <tr><td colspan="2">Program description</td><td colspan="13"><div><div><div><div>•</div><div>The binary data H001289AB stored in DR0030 (WR0030, WR0031) is converted to ASCII data.</div></div><div><div>•</div><div>The conversion result is stored in WR0032 to WR0036.</div></div></div><div>Execution results: DR0030=H001289AB, WR0032=H3030, WR0033=H3132, WR0034=H3839, WR0035=H4142, WR0036=H0000</div></div></td></tr> | | | | | | | | | | | | | Program description | | <div><div><div><div>•</div><div>The binary data H001289AB stored in DR0030 (WR0030, WR0031) is converted to ASCII data.</div></div><div><div>•</div><div>The conversion result is stored in WR0032 to WR0036.</div></div></div><div>Execution results: DR0030=H001289AB, WR0032=H3030, WR0033=H3132, WR0034=H3839, WR0035=H4142, WR0036=H0000</div></div> | | | | | | | | | | | | |
| Cautionary notes | | <div><div><div>•</div><div>If s + 1 to s + 6 exceed the maximum I/O number, DER is set to “1” and no operation is performed.</div></div></div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program example | | <div><div><div><div><div>X00303</div><div>DIF33</div></div><div><div>DR0030 = H001289AB</div><div>FUN 33 (WR0030)</div></div></div><div><div>LD X00303</div><div>AND DIF33</div><div>[</div><div>DR0030 = H001289AB</div><div>FUN 33 (WR0030)</div><div>]</div></div></div></div> <tr><td colspan="2">Program description</td><td colspan="13"><div><div><div><div>•</div><div>The binary data H001289AB stored in DR0030 (WR0030, WR0031) is converted to ASCII data.</div></div><div><div>•</div><div>The conversion result is stored in WR0032 to WR0036.</div></div></div><div>Execution results: DR0030=H001289AB, WR0032=H3030, WR0033=H3132, WR0034=H3839, WR0035=H4142, WR0036=H0000</div></div></td></tr> | | | | | | | | | | | | | Program description | | <div><div><div><div>•</div><div>The binary data H001289AB stored in DR0030 (WR0030, WR0031) is converted to ASCII data.</div></div><div><div>•</div><div>The conversion result is stored in WR0032 to WR0036.</div></div></div><div>Execution results: DR0030=H001289AB, WR0032=H3030, WR0033=H3132, WR0034=H3839, WR0035=H4142, WR0036=H0000</div></div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program description | | <div><div><div><div>•</div><div>The binary data H001289AB stored in DR0030 (WR0030, WR0031) is converted to ASCII data.</div></div><div><div>•</div><div>The conversion result is stored in WR0032 to WR0036.</div></div></div><div>Execution results: DR0030=H001289AB, WR0032=H3030, WR0033=H3132, WR0034=H3839, WR0035=H4142, WR0036=H0000</div></div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

| Item number | Fun commands-19 | Name | | Conversion from 16-bit BCD to decimal ASCII data † (BCD TO DECIMAL ASCII) | | | | | | | | | | | | | | | | | | | |
|--|----------------------------|---|-----------------|--|-----------------------------------|------|------------------------|------------|-------------------------|-------------|-----------------|----------|--------|------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|------|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | |
| FUN 34 (s) * (BCDDA (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | | | | | | | | | | |
| | | DER | ERR | SD | V | C | | | | | | | | | | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | |
| Command format | | Number of steps | | | | | 112 | ← | 112 | ← | | | | | | | | | | | | | |
| FUN 34 (s) * (BCDDA (s)) | | Condition | | | Steps | | | | | | | | | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | | | | | | | |
| s | Argument (conversion data) | | | | | | | ○ | | | | | | s uses up to s+3 | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div>16-bit BCD data</div><div><div>1512117430</div><div>s<table><tr><td>10³</td><td>10²</td><td>10¹</td><td>10⁰</td></tr></table></div><div>10ⁿ: BCD code in the 10ⁿ place</div></div><div><div>Decimal ASCII data</div><div><div>15870</div><div>s + 1<table><tr><td>10³</td><td>10²</td></tr></table></div><div>s + 2<table><tr><td>10¹</td><td>10⁰</td></tr></table></div><div>s + 3<table><tr><td>NULL</td></tr></table></div><div>10^m: ASCII code in the 10^m place</div></div><div><ul style="list-style-type: none">The 16-bit BCD data specified by argument s is converted to a 4-digit decimal ASCII code and the result is stored in s + 1 to s + 3.Leading zeros of the conversion result are suppressed and these digits are replaced by H20 (space)NULL after ASCII data indicates the end of a string.If the operation is performed normally, DER is set to “0.”<p>* () indicates the display when the LADDER EDITOR is used.</p></div></div></div></div> | | | | | | | | | | | | | | | 10 ³ | 10 ² | 10 ¹ | 10 ⁰ | 10 ³ | 10 ² | 10 ¹ | 10 ⁰ | NULL |
| 10 ³ | 10 ² | 10 ¹ | 10 ⁰ | | | | | | | | | | | | | | | | | | | | |
| 10 ³ | 10 ² | | | | | | | | | | | | | | | | | | | | | | |
| 10 ¹ | 10 ⁰ | | | | | | | | | | | | | | | | | | | | | | |
| NULL | | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | <ul style="list-style-type: none">If s is other than BCD data, DER is set to “1” and no operation is performed.If s + 1 to s + 3 exceed the maximum I/O number, DER is set to “1” and no operation is performed. | | | | | | | | | | | | | | | | | | | | | |
| Program example | | <div><div><div>X00304DIF34</div><div><div>WR0030 = H0123</div><div>FUN 34 (WR0030)</div></div></div><div><div>LD X00304</div><div>AND DIF34</div><div>[</div><div>WR0030 = H0123</div><div>FUN 34 (WR0030)</div><div>]</div></div></div> | | | | | | | | | | | | | | | | | | | | | |
| Program description | | <ul style="list-style-type: none">The BCD data H0123 stored in WR0030 is converted to ASCII data.The conversion result is stored in WR0031 to WR0033. <p>Execution results: WR0030=H0123, WR0031=H2031, WR0032=H3233, WR0033=H0000</p> | | | | | | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

| Item number | Fun commands-20 | Name | | Conversion from 32-bit BCD to decimal ASCII data † (DOUBLE BCD TO DECIMAL ASCII) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|-------------------|-----------------|-----------------|---|-----------------------------------|------|------------------------|------------|-------------------------|-------------|-----------------|------------|----------|------------------|--|----|----|----|--|---|--|---|---|--|---|---|-----------------|-----------------|-----------------|-----------------|--|--|--|--|--|--|-------|-----------------|-----------------|-----------------|-----------------|--|--|--|--|--|--|--|----|--|---|---|--|---|-------|-----------------|--|-----------------|--|--|--|-------|-----------------|--|-----------------|--|--|--|-------|-----------------|--|-----------------|--|--|--|-------|-----------------|--|-----------------|--|--|--|-------|------|--|--|--|--|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| FUN 35 (s) * (DBCDDA (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | DER | ERR | SD | V | C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Command format | | Number of steps | | | | | 171 | ← | 171 | ← | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| FUN 35 (s) * (DBCDDA (s)) | | Condition | | | Steps | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s | Argument (lower) | | | | | | | ○ | | | | | | s is BCD data. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+1 | Argument (higher) | | | | | | | ○ | | | | | | s uses up to s+6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div>32-bit BCD data</div><table><tr><td></td><td>15</td><td>12</td><td>11</td><td></td><td>7</td><td></td><td>4</td><td>3</td><td></td><td>0</td></tr><tr><td>s</td><td>10³</td><td>10²</td><td>10¹</td><td>10⁰</td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>s + 1</td><td>10⁷</td><td>10⁶</td><td>10⁵</td><td>10⁴</td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table><p>10ⁿ: BCD code in the 10ⁿ place</p></div><div><div>Decimal ASCII data</div><table><tr><td></td><td>15</td><td></td><td>8</td><td>7</td><td></td><td>0</td></tr><tr><td>s + 2</td><td>10⁷</td><td></td><td>10⁶</td><td></td><td></td><td></td></tr><tr><td>s + 3</td><td>10⁵</td><td></td><td>10⁴</td><td></td><td></td><td></td></tr><tr><td>s + 4</td><td>10³</td><td></td><td>10²</td><td></td><td></td><td></td></tr><tr><td>s + 5</td><td>10¹</td><td></td><td>10⁰</td><td></td><td></td><td></td></tr><tr><td>s + 6</td><td colspan="6">NULL</td></tr></table><p>10^m: ASCII code in the 10^m place</p></div></div> <div><div><div><div></div><div>X00305</div><div>DIF35</div></div><div></div><div>DR0040 = H00120567 FUN 35 (WR0040)</div><div></div></div><div>LD X00305 AND DIF35 [DR0040 = H00120567 FUN 35 (WR0040)]</div></div> <div><div>Cautionary notes</div><div><div>If s, s + 1 is other than BCD data, DER is set to “1” and no operation is performed.</div><div>If s + 1 to s + 6 exceed the maximum I/O number, DER is set to “1” and no operation is performed.</div></div></div> <div><div>Program example</div><div></div></div> <div><div>Program description</div><div><div>The BCD data H00120567 stored in DR0040 (WR0040, WR0041) is converted to ASCII data.</div><div>The conversion result is stored in WR0042 to WR0046.</div><div>Execution results: DR0040=H00120567, WR0042=H2020, WR0043=H3132, WR0044=H3035, WR0045=H3637, WR0046=H0000</div></div></div> | | | | | | | | | | | | | | | | 15 | 12 | 11 | | 7 | | 4 | 3 | | 0 | s | 10 ³ | 10 ² | 10 ¹ | 10 ⁰ | | | | | | | s + 1 | 10 ⁷ | 10 ⁶ | 10 ⁵ | 10 ⁴ | | | | | | | | 15 | | 8 | 7 | | 0 | s + 2 | 10 ⁷ | | 10 ⁶ | | | | s + 3 | 10 ⁵ | | 10 ⁴ | | | | s + 4 | 10 ³ | | 10 ² | | | | s + 5 | 10 ¹ | | 10 ⁰ | | | | s + 6 | NULL | | | | | |
| | 15 | 12 | 11 | | 7 | | 4 | 3 | | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s | 10 ³ | 10 ² | 10 ¹ | 10 ⁰ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 1 | 10 ⁷ | 10 ⁶ | 10 ⁵ | 10 ⁴ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 15 | | 8 | 7 | | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 2 | 10 ⁷ | | 10 ⁶ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 3 | 10 ⁵ | | 10 ⁴ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 4 | 10 ³ | | 10 ² | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 5 | 10 ¹ | | 10 ⁰ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 6 | NULL | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

| Item number | Fun commands-21 | Name | | Conversion from 5-digit unsigned decimal ASCII to 16-bit binary data [†] (DECIMAL ASCII TO BINARY) | | | | | | | | | |
|--|-------------------|--|------|--|-----------------------------------|------|------------------------|------------|-------------------------|-------------|-----------------|----------|---|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | Remark | |
| FUN 36 (s) * (DABIN (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | |
| | | DER | ERR | SD | V | C | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | |
| Command format | | Number of steps | | | | | 60 | ← | 61 | ← | | | |
| FUN 36 (s) * (DABIN (s)) | | Condition | | | Steps | | | | | | | | |
| | | — | | | 3 | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | |
| s | Argument (higher) | | | | | | | ○ | | | | | s to s + 2 will have combinations of H00, H20, and H 30 to H39. s uses up to s + 3 |
| s+1 | Argument (middle) | | | | | | | ○ | | | | | |
| s+2 | Argument (lower) | | | | | | | ○ | | | | | |
| Function | | | | | | | | | | | | | |
| <div><div>Unsigned decimal ASCII data</div><div><div>s</div><div>10⁴</div><div>10³</div><div>s + 1</div><div>10²</div><div>10¹</div><div>s + 2</div><div>10⁰</div><div>H00</div></div><div>10ⁿ: ASCII code in the 10ⁿ place</div></div> <div><div>16-bit binary data</div><div><div>s + 3</div><div>0 to 65535</div></div></div> | | | | | | | | | | | | | |
| <div><div><div><div>• The 5-digit unsigned decimal ASCII data specified by arguments s (upper), s + 1 (middle), and s + 2 (lower) is converted to 16-bit binary data and the result is stored in s + 3.</div><div>• Higher digit's H00 and H20 (NULL and space) are processed as H30 ("0"). (Leading-zero-suppressed digit)</div><div>• If the operation is performed normally, DER is set to "0."</div></div><div>* () indicates the display when the LADDER EDITOR is used.</div></div></div> | | | | | | | | | | | | | |
| Cautionary notes | | <div><div><div><div>• If the 5-digit ASCII code stored in s to s + 2 is other than H30 to H39 (0 to 9), DER is set to "1" and no operation is performed. However, this does not apply to H00 and H20 (NULL and space) of leading-zero-suppressed digits.</div><div>• If s + 1 to s + 3 exceed the maximum I/O number, DER is set to "1" and no operation is performed.</div><div>• If a data value is 65,536 or higher, DER is set to "1" and no operation is performed.</div></div></div></div> | | | | | | | | | | | |
| Program example | | <div><div><div><div><div>X00306</div><div>DIF36</div></div><div></div></div><div><div>WR0050 = H3132</div><div>WR0051 = H3334</div><div>WR0052 = H3500</div><div>FUN 36 (WR0050)</div></div></div><div><div>LD X00306</div><div>AND DIF36</div><div>[</div><div>WR0050 = H3132</div><div>WR0051 = H3334</div><div>WR0052 = H3500</div><div>FUN 36 (WR0050)</div><div>]</div></div></div> | | | | | | | | | | | |
| Program description | | <div><div><div><div>• The ASCII data "1," "2," "3," "4," "5" stored in WR0050 to WR0052 is converted to binary data.</div><div>• The conversion result is stored in WR0053.</div></div><div>Execution results: WR0050=H3132, WR0051=H3334, WR0052=H3500, WR0053=12345 (H3039)</div></div></div> | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.


| Item number | Fun commands-22 | Name | | Conversion from 10-digit signed decimal ASCII to 32-bit binary data □ (DOUBLE DECIMAL ASCII TO BINARY) | | | | | | | | | | | |
|--|-----------------------|-----------------|------|---|-----------------------------------|------|------------------------|------------|-------------------------|-------------|-----------------|------------|----------|--|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| FUN 37 (s) * (DDABIN (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | | |
| | | DER | ERR | SD | V | C | | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | Number of steps | | | | | 97 | ← | 98 | ← | | | | | |
| FUN 37 (s) * (DDABIN (s)) | | Condition | | | Steps | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| s | Argument (ASCII code) | | | | | | | ○ | | | | | | Sign is H20 or H2D, and other digits are combinations of H00, H20, and H30 to H39. s uses up to s + 7 | |
| ~ | ~ | | | | | | | ~ | | | | | | | |
| s+5 | Argument (ASCII code) | | | | | | | ○ | | | | | | | |
| Function | | | | | | | | | | | | | | | |
| <div><div><div>Signed decimal ASCII data</div><div><div><div><div>15</div><div>8</div><div>7</div><div>0</div></div><div><div>s</div><div>s + 1</div><div>s + 2</div><div>s + 3</div><div>s + 4</div><div>s + 5</div></div><div><div>Sign</div><div>10⁸</div><div>10⁶</div><div>10⁴</div><div>10²</div><div>10⁰</div></div><div><div>10⁹</div><div>10⁷</div><div>10⁵</div><div>10³</div><div>10¹</div><div>H00</div></div></div></div><div><div>32-bit signed binary data</div><div><div><div>s + 6</div><div>s + 7</div></div><div><div>Lower 16-bit</div><div>Higher 16-bit</div></div><div><div>Signs</div><div>Plus: H20 (space)</div><div>Minus: H2D (“-”)</div><div>10ⁿ: ASCII code in the 10ⁿ place</div></div></div></div></div></div> | | | | | | | | | | | | | | | |
| <div><div><div><div><div><div>•</div><div>The 10-digit signed decimal ASCII data specified by arguments s to s + 6 is converted to 32-bit binary data and the result is stored in s + 7 (higher) and s + 6 (lower).</div></div></div><div><div><div>•</div><div>Arguments will be combinations of H00, H20, H30 to H39, and H2D (“-”).</div></div></div><div><div><div>•</div><div>Higher digit’s H00 and H20 (NULL and space) are processed as H30 (“0”). (Leading-zero-suppressed digit)</div></div></div><div><div><div>•</div><div>If the operation is performed normally, DER is set to “0.”</div></div></div><div><div><div>•</div><div>Signed data must be in the range from –2,147,483,648 to 2,147,483,647.</div></div></div></div><div><div><div>*</div><div>() indicates the display when the LADDER EDITOR is used.</div></div></div></div></div> | | | | | | | | | | | | | | | |

†: Supported by EH-CPU ***A/448/516/548 only.

Cautionary notes

- If the sign is other than H20 and H2D, and other digits are other than H30 to H39 (0 to 9), DER is set to “1” and no operation is performed. However, this does not apply to H00 and H20 (NULL and space) of leading-zero-suppressed digits.
- If data is outside the range from –2,147,483,648 to 2,147,483,647, DER is set to “1” and no operation is performed.
- If s + 1 to s + 7 exceed the maximum I/O number, DER is set to “1” and no operation is performed.

Program example



Program description

- The ASCII data “-,” “2,” “1,” “4,” “7,” “4,” “8,” “3,” “6,” “4,” “8” stored in WR0060 to WR0065 is converted to binary data.
- The conversion result is stored in WR0067 (higher) and WR0066 (lower).

Execution results: WR0060=H2D32, WR0061=H3134, WR0062=H3734, WR0063=H3833, WR0064=H3634,
WR0065=H3800, DR0060=-2147483648(H80000000)

| Item number | Fun commands-23 | Name | | Conversion from 4-digit hexadecimal ASCII to 16-bit binary data † (HEXA ASCII TO BINARY) | | | | | | | | | | |
|---|-------------------------|-----------------|------|---|-----------------------------------|------|------------------------|------------|-------------------------|-------------|-----------------|------------|----------|---|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 38 (s) * (HABIN (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | |
| | | DER | ERR | SD | V | C | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | Number of steps | | | | | 63 | ← | 64 | ← | | | | |
| FUN 38 (s) * (HABIN (s)) | | Condition | | | Steps | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | |
| s | Argument (higher ASCII) | | | | | | | ○ | | | | | | Combination of H00, H20, H30 to H39 and H41 to 46 |
| s+1 | Argument (lower ASCII) | | | | | | | ○ | | | | | | s uses up to s + 2 |
| Function | | | | | | | | | | | | | | |
| <div><div><div>Hexadecimal ASCII data</div><div><div><div>15870</div><div><div>s</div><div>s + 1</div></div><div><div>16³</div><div>16²</div><div>16¹</div><div>16⁰</div></div></div><div>16ⁿ: ASCII code in the 16ⁿ place</div></div><div><div>16-bit binary data</div><div><div>s + 2</div><div>H0 to HFFFF</div></div></div></div></div> | | | | | | | | | | | | | | |
| <div><div><div><div><div><div></div></div></div><div><div><div></div></div></div><div><div><div></div></div></div><div><div><div></div></div></div></div><div><div>LD X00308</div><div>AND DIF38</div><div>[</div><div>WR0070 = H3132</div><div>WR0071 = H4142</div><div>FUN 38 (WR0070)</div><div>]</div></div></div></div> | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | |
| <div><div><div><div><div></div></div></div><div><div><div></div></div></div><div><div><div></div></div></div><div><div><div></div></div></div></div><div><div>If the 4-digit ASCII code stored in s to s + 1 is other than H30 to H39, H41 to H46 (0 to 9 and A to F), DER is set to “1” and no operation is performed. However, this does not apply to H00 and H20 (NULL and space) of leading-zero-suppressed digits.</div><div>If s + 1 to s + 2 exceed the maximum I/O number, DER is set to “1” and no operation is performed.</div></div></div> | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | |
| <div><div><div><div><div></div></div></div><div><div><div></div></div></div><div><div><div></div></div></div><div><div><div></div></div></div></div><div><div>LD X00308</div><div>AND DIF38</div><div>[</div><div>WR0070 = H3132</div><div>WR0071 = H4142</div><div>FUN 38 (WR0070)</div><div>]</div></div></div> | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | |
| <div><div><div><div><div></div></div></div><div><div><div></div></div></div><div><div><div></div></div></div><div><div><div></div></div></div></div><div><div>The ASCII data “1,” “2,” “A,” “B” stored in WR0070, WR0071 is converted to binary data.</div><div>The conversion result is stored in WR0072.</div><div>Execution results: WR0070=H3132, WR0071=H4142, WR0072=H12AB</div></div></div> | | | | | | | | | | | | | | |

| Item number | Fun commands-24 | Name | | Conversion of 8-digit hexadecimal ASCII to 32-bit binary data † (DOUBLE HEXA ASCII TO BINARY) | | | | | | | | | | |
|---|-----------------------|-----------------|------|--|-----------------------------------|------|------------------------|------------|-------------------------|-------------|-----------------|------------|----------|---|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 39 (s) * (DHABIN (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | |
| | | DER | ERR | SD | V | C | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | Number of steps | | | | | 94 | ← | 94 | ← | | | | |
| FUN 39 (s) * (DHABIN (s)) | | Condition | | | Steps | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | |
| s | Argument (ASCII data) | | | | | | | ○ | | | | | | Combination of H00, H20, H30 to H39 and H41 to 45 s uses up to s + 5 |
| ~ | ~ | | | | | | | ~ | | | | | | |
| s | Argument (ASCII data) | | | | | | | ○ | | | | | | |
| Function | | | | | | | | | | | | | | |
| <div><div><div>Hexadecimal ASCII data</div><div><div><div>15870</div><div><div>s16⁷</div><div>16⁶</div></div><div><div>s + 116⁵</div><div>16⁴</div></div><div><div>s + 216³</div><div>16²</div></div><div><div>s + 316¹</div><div>16⁰</div></div></div><div>16ⁿ: ASCII code in the 16ⁿ place</div></div><div><div>32-bit binary data</div><div><div><div>s + 4Lower 16-bit</div><div>s + 5Higher 16-bit</div></div><div>H00000000 to HFFFFFFF</div></div></div></div></div> | | | | | | | | | | | | | | |
| <div><div><div><div><div><div></div><div></div><div></div><div></div></div><div>X00309 DIF39</div></div><div><div><div>WR0080 = H4645</div><div>WR0081 = H4443</div><div>WR0082 = H4241</div><div>WR0083 = H3938</div><div>FUN 39 (WR0080)</div></div></div></div><div><div>LD X00309</div><div>AND DIF39</div><div>[</div><div><div>WR0080 = H4645</div><div>WR0081 = H4443</div><div>WR0082 = H4241</div><div>WR0083 = H3938</div><div>FUN 39 (WR0080)</div></div><div>]</div></div></div></div> | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | |
| <div><div><div><div><div></div><div></div><div></div><div></div></div><div>The ASCII data “F,” “E,” “D,” “C,” “B,” “A,” “9,” “8” stored in WR0080 to WR0083 is converted to binary data.</div><div>The conversion result is stored in WR0084 and WR0085.</div></div><div>Execution results: WR0080=H4645, WR0081=H4443, WR0082=H4241, WR0083=H3938, DR0084=HFEDCBA98</div></div></div> | | | | | | | | | | | | | | |

†: Supported by EH-CPU ***A/448/516/548 only.

| Item number | Fun commands-25 | Name | Conversion from 4-digit decimal ASCII to 16-bit BCD data † (DECIMAL ASCII TO BCD) | | | | | | | | | | | | | | | | | | |
|--|---|--|--|-----------------|-----------------------------------|--|------------------------|------------|-------------------------|-------------|-----------------|----------|-------|--|--|--|--|-----------------|-----------------|-----------------|-----------------|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | Remark | | | | | | | | | |
| FUN 40 (s) * (DABCD (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | | | | | | | | |
| | | DER | ERR | SD | V | C | | | | | | | | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | |
| Command format | | Number of steps | | | | | 64 | ← | 65 | ← | | | | | | | | | | | |
| FUN 40 (s) * (DABCD (s)) | | Condition | | | Steps | | | | | | | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | | | | | |
| s | Argument (ASCII data) | | | | | | | ○ | | | | | | Combination of H00, H20 and H30 to H39 s uses up to s + 2 | | | | | | | |
| s+1 | Argument (ASCII data) | | | | | | | ○ | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | |
| Decimal ASCII data | | 16-bit unsigned BCD data | | | | | | | | | | | | | | | | | | | |
| s | <table><tr><td>10³</td><td>10²</td></tr><tr><td>10¹</td><td>10⁰</td></tr></table> | 10 ³ | 10 ² | 10 ¹ | 10 ⁰ | <table><tr><td>10³</td><td>10²</td><td>10¹</td><td>10⁰</td></tr></table> | | | | | | | | | | | | 10 ³ | 10 ² | 10 ¹ | 10 ⁰ |
| 10 ³ | 10 ² | | | | | | | | | | | | | | | | | | | | |
| 10 ¹ | 10 ⁰ | | | | | | | | | | | | | | | | | | | | |
| 10 ³ | 10 ² | 10 ¹ | 10 ⁰ | | | | | | | | | | | | | | | | | | |
| s + 1 | | | | | | | | | | | | | | | | | | | | | |
| 10 ^m : ASCII code in the 10 ^m place | | 10 ⁿ : BCD code in the 10 ⁿ place | | | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">The 4-digit decimal ASCII data specified by arguments s to s + 1 is converted to 16-bit BCD data and the result is stored in s + 2.Higher digit's H00 and H20 (NULL and space) are processed as H30 ("0"). (Leading-zero-suppressed digit)Arguments will be combinations of H30 to H39 (0 to 9).If the operation is performed normally, DER is set to "0." <p>* () indicates the display when the LADDER EDITOR is used.</p> | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | <ul style="list-style-type: none">If the 4-digit ASCII code stored in s to s + 1 is other than H30 to H39 (0 to 9), DER is set to "1" and no operation is performed. However, this does not apply to H00 and H20 (NULL and space) of leading-zero-suppressed digits.If s + 1 to s + 2 exceed the maximum I/O number, DER is set to "1" and no operation is performed. | | | | | | | | | | | | | | | | | | | |
| Program example | | <div><div><div>X00400 DIF40</div><div><div>WR0090 = H2020</div><div>WR0091 = H3031</div><div>FUN 40 (WR0090)</div></div></div><div><div>LD X00400</div><div>AND DIF40</div><div>[</div><div>WR0090 = H2020</div><div>WR0091 = H3031</div><div>FUN 40 (WR0090)</div><div>]</div></div></div> | | | | | | | | | | | | | | | | | | | |
| Program description | | <ul style="list-style-type: none">The ASCII data "□" "□" "0," "1," stored in WR0090 and WR0091 is converted to 16-bit BCD data.The conversion result is stored in WR0092. ("□"=H20) <p>Execution results: WR0090=H2020, WR0091=H3031, WR0092=H0001</p> | | | | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

| Item number | | Fun commands-26 | | Name | | Conversion from 8-digit decimal ASCII to 32-bit BCD data † (DOUBLE DECIMAL ASCII TO BCD) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|-----------------------|--|-----------------|-----------------|-----------------------------------|---|-----------------|------------|------------------------|-----|-------------------------|----------|-----------------|------------|--|----|---|---|---|---|-----------------|--|-----------------|--|-------|-----------------|--|-----------------|--|-------|-----------------|--|-----------------|--|-------|-----------------|--|-----------------|--|--|----|----|----|---|---|---|---|---|-------|-----------------|--|-----------------|--|-----------------|--|-----------------|--|-------|-----------------|--|-----------------|--|-----------------|--|-----------------|--|------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|-----------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|---------------------|--|---|--|--|--|--|--|--|--|--|--|--|--|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| FUN 41 (s) * (DDABCD (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | 93 | ← | 94 | ← | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| FUN 41 (s) * (DDABCD (s)) | | | | Condition | | | Steps | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | — | | | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | Double word | | | Constant | Other | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s | Argument (ASCII code) | | | | | | | | ○ | | | | | | Combination of H00, H20 and H30 to H39 s uses up to s + 5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ~ | ~ | | | | | | | | ~ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 3 | Argument (ASCII code) | | | | | | | | ○ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div>Decimal ASCII data</div><table><tr><td></td><td>15</td><td>8</td><td>7</td><td>0</td></tr><tr><td>s</td><td colspan="2">10⁷</td><td colspan="2">10⁶</td></tr><tr><td>s + 1</td><td colspan="2">10⁵</td><td colspan="2">10⁴</td></tr><tr><td>s + 2</td><td colspan="2">10³</td><td colspan="2">10²</td></tr><tr><td>s + 3</td><td colspan="2">10¹</td><td colspan="2">10⁰</td></tr></table></div><div><div>32-bit BCD data</div><table><tr><td></td><td>15</td><td>12</td><td>11</td><td>8</td><td>7</td><td>4</td><td>3</td><td>0</td></tr><tr><td>s + 4</td><td colspan="2">10³</td><td colspan="2">10²</td><td colspan="2">10¹</td><td colspan="2">10⁰</td></tr><tr><td>s + 5</td><td colspan="2">10⁷</td><td colspan="2">10⁶</td><td colspan="2">10⁵</td><td colspan="2">10⁴</td></tr></table><div>10ⁿ: BCD code in the 10ⁿ place</div></div></div> <div><div>10^m: ASCII code in the 10^m place</div><div><div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div></div><div><div>The 8-digit decimal ASCII data specified by arguments s to s + 1 is converted to 32-bit BCD data and the result is stored in s + 4 (lower), s + 5 (higher).</div><div>Higher digit's H00 and H20 (NULL and space) are processed as H30 ("0"). (Leading-zero-suppressed digit)</div><div>Arguments will be combinations of H30 to H39 (0 to 9).</div><div>If the operation is performed normally, DER is set to "0."</div></div><div>* () indicates the display when the LADDER EDITOR is used.</div></div></div> <tr><td colspan="2">Cautionary notes</td><td colspan="13"><div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div></div><div><div>If the 8-digit ASCII code stored in s to s + 3 is other than H30 to H39 (0 to 9), DER is set to "1" and no operation is performed. However, this does not apply to H00 and H20 (NULL and space) of leading-zero-suppressed digits.</div><div>If s + 1 to s + 5 exceed the maximum I/O number, DER is set to "1" and no operation is performed.</div></div></td></tr> <tr><td colspan="2">Program example</td><td colspan="13"><div><div><div><div>X00401</div><div>DIF41</div></div><div><div>WR00A0 = H3938</div><div>WR00A1 = H3736</div><div>WR00A2 = H3534</div><div>WR00A3 = H3332</div><div>FUN 41 (WR00A0)</div></div></div><div><div>LD X00401</div><div>AND DIF41</div><div>[</div><div>WR00A0 = H3938</div><div>WR00A1 = H3736</div><div>WR00A2 = H3534</div><div>WR00A3 = H3332</div><div>FUN 41 (WR00A0)</div><div>]</div></div></div></td></tr> <tr><td colspan="2">Program description</td><td colspan="13"><div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div></div><div><div>The ASCII data "9," "8," "7," "6," "5," "4," "3," "2" stored in WR00A0 to WR00A3 is converted to 32-bit BCD data.</div><div>The conversion result is stored in WR00A4, WR00A5.</div></div><div>Execution results: WR00A0=H3938, WR00A1=H3736, WR00A2=H3534, WR00A3=H3332, DR00A4=H98765432</div></td></tr> | | | | | | | | | | | | | | | | 15 | 8 | 7 | 0 | s | 10 ⁷ | | 10 ⁶ | | s + 1 | 10 ⁵ | | 10 ⁴ | | s + 2 | 10 ³ | | 10 ² | | s + 3 | 10 ¹ | | 10 ⁰ | | | 15 | 12 | 11 | 8 | 7 | 4 | 3 | 0 | s + 4 | 10 ³ | | 10 ² | | 10 ¹ | | 10 ⁰ | | s + 5 | 10 ⁷ | | 10 ⁶ | | 10 ⁵ | | 10 ⁴ | | Cautionary notes | | <div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div></div> <div><div>If the 8-digit ASCII code stored in s to s + 3 is other than H30 to H39 (0 to 9), DER is set to "1" and no operation is performed. However, this does not apply to H00 and H20 (NULL and space) of leading-zero-suppressed digits.</div><div>If s + 1 to s + 5 exceed the maximum I/O number, DER is set to "1" and no operation is performed.</div></div> | | | | | | | | | | | | | Program example | | <div><div><div><div>X00401</div><div>DIF41</div></div><div><div>WR00A0 = H3938</div><div>WR00A1 = H3736</div><div>WR00A2 = H3534</div><div>WR00A3 = H3332</div><div>FUN 41 (WR00A0)</div></div></div><div><div>LD X00401</div><div>AND DIF41</div><div>[</div><div>WR00A0 = H3938</div><div>WR00A1 = H3736</div><div>WR00A2 = H3534</div><div>WR00A3 = H3332</div><div>FUN 41 (WR00A0)</div><div>]</div></div></div> | | | | | | | | | | | | | Program description | | <div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div></div> <div><div>The ASCII data "9," "8," "7," "6," "5," "4," "3," "2" stored in WR00A0 to WR00A3 is converted to 32-bit BCD data.</div><div>The conversion result is stored in WR00A4, WR00A5.</div></div> <div>Execution results: WR00A0=H3938, WR00A1=H3736, WR00A2=H3534, WR00A3=H3332, DR00A4=H98765432</div> | | | | | | | | | | | | |
| | 15 | 8 | 7 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s | 10 ⁷ | | 10 ⁶ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 1 | 10 ⁵ | | 10 ⁴ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 2 | 10 ³ | | 10 ² | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 3 | 10 ¹ | | 10 ⁰ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 15 | 12 | 11 | 8 | 7 | 4 | 3 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 4 | 10 ³ | | 10 ² | | 10 ¹ | | 10 ⁰ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s + 5 | 10 ⁷ | | 10 ⁶ | | 10 ⁵ | | 10 ⁴ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cautionary notes | | <div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div></div> <div><div>If the 8-digit ASCII code stored in s to s + 3 is other than H30 to H39 (0 to 9), DER is set to "1" and no operation is performed. However, this does not apply to H00 and H20 (NULL and space) of leading-zero-suppressed digits.</div><div>If s + 1 to s + 5 exceed the maximum I/O number, DER is set to "1" and no operation is performed.</div></div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program example | | <div><div><div><div>X00401</div><div>DIF41</div></div><div><div>WR00A0 = H3938</div><div>WR00A1 = H3736</div><div>WR00A2 = H3534</div><div>WR00A3 = H3332</div><div>FUN 41 (WR00A0)</div></div></div><div><div>LD X00401</div><div>AND DIF41</div><div>[</div><div>WR00A0 = H3938</div><div>WR00A1 = H3736</div><div>WR00A2 = H3534</div><div>WR00A3 = H3332</div><div>FUN 41 (WR00A0)</div><div>]</div></div></div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program description | | <div><div><div></div><div></div><div></div><div></div></div><div><div></div><div></div><div></div><div></div></div></div> <div><div>The ASCII data "9," "8," "7," "6," "5," "4," "3," "2" stored in WR00A0 to WR00A3 is converted to 32-bit BCD data.</div><div>The conversion result is stored in WR00A4, WR00A5.</div></div> <div>Execution results: WR00A0=H3938, WR00A1=H3736, WR00A2=H3534, WR00A3=H3332, DR00A4=H98765432</div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.


| Item number | Fun commands-27 | Name | Conversion from hexadecimal binary to hexadecimal ASCII data † (BINARY TO ASCII) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|----------------------------|-------------------------------------|---|---|---------|-----------------------------------|--------|------------------------|------------|-------------------------|-------------|-----------------|----------|-------------------|-----------------------|----|----|----|---|---|---|---|---|----|--|----|--|----|--|----|--|--|--|--|--|--|--|--|--|------|--|------|--|----|--|--------|--|----|---|---|---|----|--|----|--|----|--|----|--|--|--|--|--|------|--|------|--|----|--|-----|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| FUN 42 (s) * (ASC (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | 10 char. conv. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | DER | ERR | SD | V | C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | ↓ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Command format | | Number of steps | | | | | 119 | ← | 116 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| FUN 42 (s) * (ASC (s)) | | Condition | | | Steps | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s | No. of converted characters | | | | | | | ○ | | | | | | s uses up to s+2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+1 | Binary data head I/O No. | | | | | | | ○ | | | | | | Actual address is set | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+2 | ASCII head I/O No. after conversion | | | | | | | ○ | | | | | | Actual address is set | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <div><div><div>s</div><div>No. of conversions n</div></div><div><div>s + 1</div><div>Binary data head a1</div></div><div><div>s + 2</div><div>ASCII data head a2</div></div></div> <div><div><div>a1</div><div>$a1 + \left\lceil \frac{n-1}{4} \right\rceil$</div></div><div><div>a2</div><div>a2 + 1</div><div>$a2 + \left\lceil \frac{n-3}{2} \right\rceil$</div><div>$a2 + \left\lceil \frac{n-1}{2} \right\rceil$</div></div></div> <div><div>Binary data table</div><table><tr><td>15</td><td>12</td><td>11</td><td>8</td><td>7</td><td>4</td><td>3</td><td>0</td></tr><tr><td>d1</td><td></td><td>d2</td><td></td><td>d3</td><td></td><td>d4</td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>dn-2</td><td></td><td>dn-1</td><td></td><td>dn</td><td></td><td>dn + 1</td><td></td></tr></table><div><div>ASCII data table</div><table><tr><td>15</td><td>8</td><td>7</td><td>0</td></tr><tr><td>d1</td><td></td><td>d2</td><td></td></tr><tr><td>d3</td><td></td><td>d4</td><td></td></tr><tr><td></td><td></td><td></td><td></td></tr><tr><td>dn-2</td><td></td><td>dn-1</td><td></td></tr><tr><td>dn</td><td></td><td>H20</td><td></td></tr></table></div></div> <div><ul style="list-style-type: none">The number of hexadecimal data characters specified by argument s is converted to hexadecimal ASCII codes beginning from the head I/O specified by argument s + 1, and the results are stored in addresses beginning from the head I/O specified by s + 2.If the number of characters is odd, the lower 8 bits of the data at the output destination will be H20 (space).Use the ADRIO command to set the actual addresses in the head I/Os of s + 1 and s + 2.If the operation is performed normally, DER is set to “0.”<p>* () indicates the display when the LADDER EDITOR is used.</p></div> | | | | | | | | | | | | | 15 | 12 | 11 | 8 | 7 | 4 | 3 | 0 | d1 | | d2 | | d3 | | d4 | | | | | | | | | | dn-2 | | dn-1 | | dn | | dn + 1 | | 15 | 8 | 7 | 0 | d1 | | d2 | | d3 | | d4 | | | | | | dn-2 | | dn-1 | | dn | | H20 | |
| 15 | 12 | 11 | 8 | 7 | 4 | 3 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| d1 | | d2 | | d3 | | d4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dn-2 | | dn-1 | | dn | | dn + 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 15 | 8 | 7 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| d1 | | d2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| d3 | | d4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dn-2 | | dn-1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dn | | H20 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

Cautionary notes

- The ADRIO command should be used to set the actual addresses in s + 1 and s + 2. If not, DER is set to “1” and no operation is performed.
- If s to s + 2 and the areas specified by them overlap, DER is set to “1” and no operation is performed.
- If s to s + 2 and the areas specified by s + 1 and s + 2 exceed the maximum I/O number, DER is set to “1” and no operation is performed.

Program example



Program description

- 1) The result is stored in the data table from WR0100 by special internal output R7E3 (single scan ON after RUN start).
- 2) At a rising edge of X00402, the hexadecimal binary data is converted to hexadecimal ASCII data, and the converted data is stored from WM000.

Execution results: WR0100 = H1234
WR0101 = H5678
WR0102 = H9ABC
WR0103 = HDEF0

➡

WM000=H3132, WM001=H3334
WM002=H3536, WM003=H3738
WM004=H3941, WM005=H4243
WM006=H4445, WM007=H4620 (“20” is a space.)


| Item number | | Fun commands-28 | | Name | | Conversion from hexadecimal ASCII to hexadecimal binary data † (ASCII TO BINARY) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|-------------------------------------|-----------------|--------|-----------------|---------------|---|-------|------|------------------------|-------------|-------------------------|----------|-----------------|-----------------------|-------------------|------------------|---|---|---|----|--|--|----|----|--|--|----|--|--|--|--|------|--|--|------|----|--|--|--------|----|----|----|---|---|---|---|---|----|--|----|--|----|--|--|----|--|--|--|--|--|--|--|--|------|--|------|--|----|--|--|-----|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| FUN 43 (s) * (HEX (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | 10 char. conv. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | ↕ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | 191 | ← | 188 | ← | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| FUN 43 (s) * (HEX) (s)) | | | | Condition | | | Steps | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | — | | | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | Constant | Other | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | | | DY | | DR, DL, DM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s | No. of converted characters | | | | | | | ○ | | | | | | s uses up to s+2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+1 | ASCII head I/O No. | | | | | | | ○ | | | | | | Actual address is set | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s+2 | Binary conversion data head I/O No. | | | | | | | ○ | | | | | | Actual address is set | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div>s</div><div>No. of conversions n</div></div><div><div>s + 1</div><div>ASCII data head a1</div></div><div><div>s + 2</div><div>Binary data head a2</div></div></div> <div><div><div>a1</div><div>a1 + 1</div><div>$a1 + \left[\frac{n-3}{2}\right]$</div><div>$a1 + \left[\frac{n-1}{2}\right]$</div></div><div><div>ASCII data table</div><table><tr><td>15</td><td>8</td><td>7</td><td>0</td></tr><tr><td>d1</td><td></td><td></td><td>d2</td></tr><tr><td>d3</td><td></td><td></td><td>d4</td></tr><tr><td></td><td></td><td></td><td></td></tr><tr><td>dn-2</td><td></td><td></td><td>dn-1</td></tr><tr><td>dn</td><td></td><td></td><td>dn + 1</td></tr></table></div><div><div><div>a2</div><div>$a2 + \left[\frac{n-1}{4}\right]$</div></div><div><div>Binary data table</div><table><tr><td>15</td><td>12</td><td>11</td><td>8</td><td>7</td><td>4</td><td>3</td><td>0</td></tr><tr><td>d1</td><td></td><td>d2</td><td></td><td>d3</td><td></td><td></td><td>d4</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>dn-2</td><td></td><td>dn-1</td><td></td><td>dn</td><td></td><td></td><td>H00</td></tr></table></div></div></div> <div><ul style="list-style-type: none">The number of hexadecimal ASCII code characters specified by argument s is converted to binary data beginning from the head of the hexadecimal ASCII code specified by argument s + 1, and the results are stored in addresses beginning from the head I/O specified by s + 2.If the number of characters is odd, the lower 4 bits of the data at the output destination will be “0.”Use the ADRIO command to store the actual addresses of the head I/Os at s + 1 and s + 2.Higher digit’s H00 and H20 (NULL and space) are processed as H30 (“0”). (Leading-zero-suppressed digit)If the operation is performed normally, DER is set to “0.”<p>* () indicates the display when the LADDER EDITOR is used.</p></div> | | | | | | | | | | | | | | | | 15 | 8 | 7 | 0 | d1 | | | d2 | d3 | | | d4 | | | | | dn-2 | | | dn-1 | dn | | | dn + 1 | 15 | 12 | 11 | 8 | 7 | 4 | 3 | 0 | d1 | | d2 | | d3 | | | d4 | | | | | | | | | dn-2 | | dn-1 | | dn | | | H00 |
| 15 | 8 | 7 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| d1 | | | d2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| d3 | | | d4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dn-2 | | | dn-1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dn | | | dn + 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 15 | 12 | 11 | 8 | 7 | 4 | 3 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| d1 | | d2 | | d3 | | | d4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| dn-2 | | dn-1 | | dn | | | H00 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

†: Supported by EH-CPU ***A/448/516/548 only.

Cautionary notes

- The ADRIO command should be used to set the actual addresses in s + 1 and s + 2. If not, DER is set to “1” and no operation is performed.
- If s to s + 2 and the areas specified by them overlap, DER is set to “1” and no operation is performed.
- If s to s + 2 and the areas specified by s + 1 and s + 2 exceed the maximum I/O number, DER is set to “1” and no operation is performed.

Program example



Program description

- 1) The result is stored in the data table from WR0100 by special internal output R7E3 (single scan ON after RUN start).
- 2) At a rising edge of X00403, the hexadecimal ASCII data is converted to hexadecimal binary data, and the converted data is stored from WM0100.

Execution results: WM000=H3031, WM001=H3233
WM002=H3435, WM003=H3637
WM004=H3839, WM005=H4142
WM006=H4344, WM007=H4546

➡

WR0100=H0123
WR0101=H4567
WR0102=H89AB
WR0103=HCDE0

FUN 43 (s)


| Item number | Fun commands-29 | Name | | | | Merge strings † | | | | | | | | | | | |
|--|--|-----------------|------|---------|-----------------------------------|-----------------|----------------------|------------|------------|-------------|-----------------|----------|--|------------|--|--|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | |
| FUN 44 (s) * (SADD (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | 10 char. + 10 char. ↓ 20 char. | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | |
| Command format | | Number of steps | | | | | 196 | ← | 184 | ← | | | | | | | |
| FUN 44 (s) * (SADD (s)) | | Condition | | | Steps | | | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | |
| s | String 1 head I/O No. | | | | | | | ○ | | | | | Actual addresses are set in s to s + 2 | | | | |
| s+1 | String 2 head I/O No. | | | | | | | ○ | | | | | | | | | |
| s+2 | Merged character string's head I/O No. | | | | | | | ○ | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div><div>sString 1 head I/O No. a1</div><div>s + 1String 2 head I/O No. a2</div><div>s + 2Merged character string's head I/O No. a3</div></div><div><div>Character string 1</div><div>15870</div><div>d11d12</div><div>⋮</div><div>d1nNULL</div></div><div><div>Character string 2</div><div>15870</div><div>d21d22</div><div>⋮</div><div>d2m-1d2m</div><div>NULL</div></div><div><div>+</div></div><div><div>a3</div><div>15870</div><div>d11d12</div><div>⋮</div><div>d1n-2d1n-1</div><div>d1nd21</div><div>d22d23</div><div>⋮</div><div>d2mNULL</div></div></div> | | | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">• The string that begins from the head I/O specified by argument s is merged with the string that begins from the head I/O specified by argument s + 1, and the result is stored in the head I/O area specified by s + 2.• The character strings to be merged end before a NULL (H00).• A NULL will be set after the merged character string.• Use the ADRIO command to store the actual addresses of the head I/Os at s and s + 2.• If the operation is performed normally, DER is set to "0."<div>* () indicates the display when the LADDER EDITOR is used.</div></div> | | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

Cautionary notes

- The ADRIO command should be used to set the actual addresses in s to s + 2. If not, DER is set to “1” and no operation is performed.
- If s to s + 2 and the areas specified by them overlap, DER is set to “1” and no operation is performed.
- If s to s + 2 and the areas specified by s + 1 and s + 2 exceed the maximum I/O number, DER is set to “1” and no operation is performed.

Program example



Program description

- 1) Sets the first character string from WM010 and the second character string from WM020 using special internal output R7E3 (single scan ON after RUN start).
- 2) At a rising edge of X00404, character strings are merged and output to WM030 and succeeding areas.

Execution results:

| | | |
|-------------|-------------|-------------|
| WM010=H4849 | WM020=H4E48 | WM030=H4849 |
| WM011=H5441 | WM021=H534E | WM031=H5441 |
| WM012=H4348 | WM022=H5249 | WM032=H4348 |
| WM013=H4900 | WM023=H4E53 | WM033=H494E |
| | WM024=H0000 | WM034=H4853 |
| | | WM035=H4E52 |
| | | WM036=H494E |
| | | WM037=H5300 |

FUN 44 (s)


| Item number | Fun commands-30 | Name | | Compare character strings † | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|-----------------------|-----------------|------|-----------------------------|-----------------------------------|------|----------------------|------------|------------|-------------|-----------------|----------|--|------------|----|----|----|--------------------------------|---|---|---|----------------------------|---|---|---|--------------------------|---|---|---|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | | | | | |
| FUN 45 (s) * (SCMP (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Comparison between 10 char. and 10 char. | | | | | | | | | | | | | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | | | | | | | | |
| | | ↕ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | | | |
| Command format | | Number of steps | | | | | 157 | ← | 147 | ← | | | | | | | | | | | | | | | | | | | |
| FUN 45 (s) * (SCMP (s)) | | Condition | | | Steps | | | | | | | | | | | | | | | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | | | | | | | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | | | | | | | | | | | | | |
| s | String 1 head I/O No. | | | | | | | ○ | | | | | Actual addresses are set in s to s + 1 s uses up to s + 2 | | | | | | | | | | | | | | | | |
| s+1 | String 2 head I/O No. | | | | | | | ○ | | | | | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div><div><div>String 1 head I/O No. a1</div><div>String 2 head I/O No. a2</div></div></div><div><div>Character string 1</div><div><div><div>15870</div><div><div>d11</div><div>d12</div><div>⋮</div><div>d1n</div><div>NULL</div></div></div><div>Character string 2</div><div><div><div>15870</div><div><div>d21</div><div>d22</div><div>⋮</div><div>d2m</div><div>NULL</div></div></div></div><div>Comparison</div><div>↓</div><div>Result</div><div><div><div>15210</div><div><div>s + 2</div><div><div>F2</div><div>F1</div><div>F0</div></div></div></div><table><tr><td></td><td>F2</td><td>F1</td><td>F0</td></tr><tr><td>Unmatched number of characters</td><td>1</td><td>0</td><td>0</td></tr><tr><td>Unmatched character string</td><td>0</td><td>1</td><td>0</td></tr><tr><td>Matched character string</td><td>0</td><td>0</td><td>1</td></tr></table></div></div></div></div></div> | | | | | | | | | | | | | | | F2 | F1 | F0 | Unmatched number of characters | 1 | 0 | 0 | Unmatched character string | 0 | 1 | 0 | Matched character string | 0 | 0 | 1 |
| | F2 | F1 | F0 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Unmatched number of characters | 1 | 0 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Unmatched character string | 0 | 1 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Matched character string | 0 | 0 | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">The character string that begins from the head I/O specified by argument s and the character string that begins from the head I/O specified by argument s + 1 are compared, and the result is stored in s + 2.The character strings to be compared end before a NULL (H00).The numbers of characters in the strings are compared first. If the numbers do not match, bit 2 is set to “1.” If the numbers of characters match, the strings themselves are compared. If they do not match, bit 1 is set to “1.” If both the numbers of characters and strings match, bit 0 is set to “1.”Use the ADRIO command to set the actual addresses in the head I/Os of s and s + 1.If the operation is performed normally, DER is set to “0.” <p>* () indicates the display when the LADDER EDITOR is used.</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

Cautionary notes

- The ADRIO command should be used to set the actual addresses in s and s + 1. If not, DER is set to “1” and no operation is performed.
- If s to s + 2 and the areas specified by them overlap, DER is set to “1” and no operation is performed.
- If s to s + 2 and the areas specified by s and s + 1 exceed the maximum I/O number, DER is set to “1” and no operation is performed.

Program example



Program description

- 1) The compared data is stored in WM000 and succeeding areas by special internal output R7E3 (single scan ON after RUN start).
- 2) At a rising edge of R100, the data beginning from WM000 and the data beginning from WM010 are compared.
- 3) Depending on the comparison result, Y00000 to Y00002 turn on.

FUN 45 (s)

| Item number | Fun commands-31 | Name | | Conversion from word units to byte units [†] | | | | | | | | | | | | | | | | | | | | | | | |
|-----------------------------|-----------------------------------|--|------|---|-----------------------------------|------|----------------------|------------|------------|-------------|-----------------|----------|---|------------------|--|---|--|--|--|--|--|--|--|--|--|--|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | | | | | | | | | | | |
| FUN 46 (s) * (WTOB (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | 5 words to 10 bytes (word) | | | | | | | | | | | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | | | | | | |
| | | ↓ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | |
| Command format | | Number of steps | | | | | 115 | ← | 111 | ← | | | | | | | | | | | | | | | | | |
| FUN 46 (s) * (WTOB (s)) | | Condition | | | Steps | | | | | | | | | | | | | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | | | | | | | | | | | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | | | | | | | | | | | |
| s | Word data head I/O No. | | | | | | | ○ | | | | | Actual addresses are set in s and s + 1 s uses up to s + 2 | | | | | | | | | | | | | | |
| s+1 | Byte conversion data head I/O No. | | | | | | | ○ | | | | | | | | | | | | | | | | | | | |
| s+2 | No. of converted bytes | | | | | | | ○ | | | | | | | | | | | | | | | | | | | |
| Function | | <div><div><div>s</div><div>Word-unit data head I/O No. a1</div></div><div><div>s + 1</div><div>Converted byte-unit data head I/O No. a2</div></div><div><div>s + 2</div><div>No. n of converted bytes</div></div></div> <div><div>Word unit data</div><div><div>15870</div><div>d1d2</div><div>⋮</div><div>dn dn + 1</div></div></div> <div><div>Byte unit data</div><div><div>15870</div><div>00n d1</div><div>00n d2</div><div>⋮</div><div>00n dn-1</div><div>00n dn</div></div></div> <div><div>a1</div><div>a2</div><div>a2 + 1</div><div>a2 + n-2</div><div>a2 + n-1</div></div> <div><div>n</div></div> <tr><td colspan="2">Cautionary notes</td><td colspan="12"><div><div><div><div>•</div><div>The word character string data of the head I/O specified by argument s is divided into byte units for the number of bytes specified by argument s + 2, and the result is stored in the head I/O area specified by s + 1.</div></div><div><div>•</div><div>Use the ADRIO command to set the actual addresses in the head I/Os of s to s + 1.</div></div><div><div>•</div><div>The higher byte of the divided data is set to H00.</div></div><div><div>•</div><div>If the operation is performed normally, DER is set to “0.”</div></div><div><div>*</div><div>() indicates the display when the LADDER EDITOR is used.</div></div></div></div><div><div><div><div>•</div><div>The ADRIO command should be used to set the actual addresses in s and s + 1. If not, DER is set to “1” and no operation is performed.</div></div><div><div>•</div><div>If s to s + 2 and the areas specified by them overlap, DER is set to “1” and no operation is performed.</div></div><div><div>•</div><div>If s to s + 2 and the areas specified by s and s + 1 exceed the maximum I/O number, DER is set to “1” and no operation is performed.</div></div></div></div></td></tr> | | | | | | | | | | | | Cautionary notes | | <div><div><div><div>•</div><div>The word character string data of the head I/O specified by argument s is divided into byte units for the number of bytes specified by argument s + 2, and the result is stored in the head I/O area specified by s + 1.</div></div><div><div>•</div><div>Use the ADRIO command to set the actual addresses in the head I/Os of s to s + 1.</div></div><div><div>•</div><div>The higher byte of the divided data is set to H00.</div></div><div><div>•</div><div>If the operation is performed normally, DER is set to “0.”</div></div><div><div>*</div><div>() indicates the display when the LADDER EDITOR is used.</div></div></div></div> <div><div><div><div>•</div><div>The ADRIO command should be used to set the actual addresses in s and s + 1. If not, DER is set to “1” and no operation is performed.</div></div><div><div>•</div><div>If s to s + 2 and the areas specified by them overlap, DER is set to “1” and no operation is performed.</div></div><div><div>•</div><div>If s to s + 2 and the areas specified by s and s + 1 exceed the maximum I/O number, DER is set to “1” and no operation is performed.</div></div></div></div> | | | | | | | | | | | |
| Cautionary notes | | <div><div><div><div>•</div><div>The word character string data of the head I/O specified by argument s is divided into byte units for the number of bytes specified by argument s + 2, and the result is stored in the head I/O area specified by s + 1.</div></div><div><div>•</div><div>Use the ADRIO command to set the actual addresses in the head I/Os of s to s + 1.</div></div><div><div>•</div><div>The higher byte of the divided data is set to H00.</div></div><div><div>•</div><div>If the operation is performed normally, DER is set to “0.”</div></div><div><div>*</div><div>() indicates the display when the LADDER EDITOR is used.</div></div></div></div> <div><div><div><div>•</div><div>The ADRIO command should be used to set the actual addresses in s and s + 1. If not, DER is set to “1” and no operation is performed.</div></div><div><div>•</div><div>If s to s + 2 and the areas specified by them overlap, DER is set to “1” and no operation is performed.</div></div><div><div>•</div><div>If s to s + 2 and the areas specified by s and s + 1 exceed the maximum I/O number, DER is set to “1” and no operation is performed.</div></div></div></div> | | | | | | | | | | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.


| Item number | Fun commands-32 | Name | Conversion from byte units to word units [†] | | | | | | | | | | |
|-----------------------------|-----------------------------|---|---|---------|-----------------------------------|------|----------------------|------------|------------|-------------|-----------------|----------|---|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark |
| FUN 47 (s) * (BTOW (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | 10 bytes (word) to 5 words |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | |
| Command format | | Number of steps | | | | | 109 | ← | 104 | ← | | | |
| FUN 47 (s) * (BTOW (s)) | | Condition | | | Steps | | | | | | | | |
| | | — | | | 3 | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | |
| s | Byte-unit data head I/O No. | | | | | | | ○ | | | | | Actual addresses are set in s and s + 1 s uses up to s + 2 |
| s+1 | Word-unit data head I/O No. | | | | | | | ○ | | | | | |
| s+2 | No. of converted bytes | | | | | | | ○ | | | | | |
| Function | | <div><div><div><div>s</div><div>Byte-unit data head I/O No. a1</div></div><div><div>s + 1</div><div>Converted word-unit data head I/O No. a2</div></div><div><div>s + 2</div><div>No. n of converted bytes</div></div></div><div><div>Byte unit data</div><div><div><div>15870</div><div><div><div>a1</div><div>a1 + 1</div><div>a1 + n - 2</div><div>a1 + n - 1</div></div><div><div>d1</div><div>d2</div><div>⋮</div><div>dn - 1</div><div>dn</div></div></div></div></div><div><div>Word unit data</div><div><div><div>15870</div><div><div><div>a2</div><div>a2 + 1</div><div>a2 + $\left[\frac{n - 3}{2}\right]$</div><div>a2 + $\left[\frac{n - 1}{2}\right]$</div></div><div><div>d1</div><div>d2</div><div>d3</div><div>d4</div><div>⋮</div><div>dn - 2</div><div>dn - 1</div><div>dn</div><div>H00</div></div></div></div></div></div></div></div> | | | | | | | | | | | |
| Cautionary notes | | <div><div><div><div>A byte data string is combined into word units beginning from the head I/O specified by argument s for the number of bytes specified by argument s + 2, and the result is stored in the head I/O area specified by s + 1.</div><div>The higher byte of the byte unit data is ignored.</div><div>If the number of converted bytes is odd, the lower 8 bits at the end of the output destination is set to H00.</div><div>Use the ADRIO command to set the actual addresses in the head I/Os of s and s + 1.</div></div><div><div>* () indicates the display when the LADDER EDITOR is used.</div></div></div></div> | | | | | | | | | | | |
| Cautionary notes | | <div><div><div><div>The ADRIO command should be used to set the actual addresses in s and s + 1. If not, DER is set to “1” and no operation is performed.</div><div>If s to s + 2 and the areas specified by them overlap, DER is set to “1” and no operation is performed.</div><div>If s to s + 2 and the areas specified by s to s + 2 exceed the maximum I/O number, DER is set to “1” and no operation is performed.</div></div></div></div> | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

| Item number | Fun commands-33 | Name | Byte right shift † | | | | | | | | | | |
|-----------------------------|-------------------------|---|--------------------|---------------|--|------|----------------------|------------------|-------------|-----|---|-------|---|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark |
| FUN 48 (s) * (BSHR (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | Shift 10 char. by 1 byte |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | |
| | | ↓ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | |
| Command format | | Number of steps | | | | | 81 | ← | 79 | ← | <div></div> <div></div> <div></div> <div></div> | | |
| FUN 48 (s) * (BSHR (s)) | | Condition | | | Steps | | | | | | | | |
| | | — | | | 3 | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | Double word | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | | | DY |
| s | No. of shifted bytes | | | | | | | ○ | | | | | Address is set in s + 1. s uses up to s + 1. |
| s+1 | Shift data head I/O No. | | | | | | | ○ | | | | | |
| Function | | <div><div><div><div>No. n of shifted bytes</div><div>Shift data head I/O No. a</div></div><div><div>Before shift</div><div>After shift</div></div><div><div>Before conversion</div><div>After conversion</div></div></div><div><div>For even bytes</div><div>For odd bytes</div></div></div> | | | | | | | | | | | |
| Cautionary notes | | <div><div><div><div><div>The data given by the number of bytes specified by argument s is shifted one byte to the right, beginning from the head I/O specified by argument s + 1.</div><div>An H00 is inserted in an area that became empty after the shift. Note that the data after the specified number of bytes is lost by the shift operation.</div><div>Use the ADRIO command to set the actual addresses in the head I/Os of s + 1.</div><div>If the operation is performed normally, DER is set to “0.”</div></div><div>* () indicates the display when the LADDER EDITOR is used.</div></div></div></div> | | | | | | | | | | | |
| Cautionary notes | | <div><div><div><div><div>The ADRIO command should be used to set the actual addresses in s + 1. If not, DER is set to “1” and no operation is performed.</div><div>If s and s + 1 and the areas specified by them overlap, DER is set to “1” and no operation is performed.</div><div>If s + 1 and the areas specified by s and s + 1 exceed the maximum I/O number, DER is set to “1” and no operation is performed.</div></div></div></div></div> | | | | | | | | | | | |

†: Supported by EH-CPU ***A/448/516/548 only.


Program example



| Item number | Fun commands-34 | Name | | | | Byte left shift † | | | | | | | | | | | |
|-----------------------------|-------------------------|--|------|---------|-----------------------------------|-------------------|----------------------|------------|------------|-------------|-----------------|----------|---|--|------------|--|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | |
| FUN 49 (s) * (BSHL (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | 10 char. | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | |
| | | ↕ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | |
| Command format | | Number of steps | | | | | 85 | ← | 84 | ← | | | | | | | |
| FUN 49 (s) * (BSHL (s)) | | Condition | | | Steps | | | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | | DR, DL, DM | | |
| s | No. of shifted bytes | | | | | | | ○ | | | | | Actual address is set s uses up to s + 1. | | | | |
| s+1 | Shift data head I/O No. | | | | | | | ○ | | | | | | | | | |
| Function | | <div><div><div><div><div>No. n of shifted bytes</div><div>Shift data head I/O No. a</div></div><div><div>Before shift</div><div>After shift</div></div><div><div>Before conversion</div><div>After conversion</div></div></div><div><div>For even bytes</div><div>For odd bytes</div></div></div><div><div>Lost</div><div></div></div></div> <div><ul style="list-style-type: none">The data given by the number of bytes specified by argument s is shifted one byte to the left, beginning from the head I/O specified by argument s + 1,.An H00 is inserted in an area that became empty after the shift. Note that the head data is lost by the shift operation.Use the ADRIO command to set the actual addresses in the head I/Os of s + 1.If the operation is performed normally, DER is set to "0."<div><div>* () indicates the display when the LADDER EDITOR is used.</div></div></div> | | | | | | | | | | | | | | | |
| Cautionary notes | | <div><ul style="list-style-type: none">The ADRIO command should be used to set the actual addresses in s + 1. If not, DER is set to "1" and no operation is performed.If s and s + 1 and the areas specified by them overlap, DER is set to "1" and no operation is performed.If s + 1 and the areas specified by s and s + 1 exceed the maximum I/O number, DER is set to "1" and no operation is performed.</div> | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

Program example



Program description

Five bytes of data with control code is stored in WM100 and succeeding areas. The control code is deleted from this data so that it becomes a data string containing only data.
Execution results:

| | | | | | | |
|-------|-----|-----|--|-------|-----|-----|
| WM100 | H02 | "T" | | WM100 | "T" | "E" |
| WM101 | "E" | "X" | | WM101 | "X" | "T" |
| WM102 | "T" | | | WM102 | H00 | |

| Item number | Fun commands-35 | Name | Binary square root † | | | | | | | | | | | |
|--|-------------------|-----------------|----------------------|---------|-----------------------------------|------|----------------------|------------|------------|-------------|-----------------|----------|------------------|------------|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 60 (s) * (BSQR (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | Number of steps | | | | | 453 | ← | 454 | ← | | | | |
| FUN 60 (s) * (BSQR (s)) | | Condition | | | Steps | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM |
| s | Argument (lower) | | | | | | | ○ | | | | | | |
| s+2 | Argument (higher) | | | | | | | ○ | | | | | s uses up to s+2 | |
| Function | | | | | | | | | | | | | | |
| <div><div><div>150</div><div>Square root</div><div>s + 2</div></div><div>←</div><div><div>3216150</div><div>HigherLower</div><div>s + 1s</div></div></div> <ul style="list-style-type: none">The square root of the 32-bit binary value specified by arguments s (lower) and s + 1 (higher) is calculated and stored in s + 2.If the operation is performed normally, DER is set to “0.” <p>* () indicates the display when the LADDER EDITOR is used.</p> | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">If s + 1 to s + 2 exceed the maximum I/O number, DER is set to “1” and no operation is performed. | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | |
| <div><div><div>X00600DIF60</div><div>DR0100 = H12345678 FUN 60 (WR0100)</div></div><div><div>LD X00600 AND DIF60 [WR0000 = H12345678 FUN 60 (WR0100)]</div></div></div> | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">Stores the 32-bit binary value H12345678 in WR0100 and WR0101.The conversion result is stored in WR0102. <p>Execution results: DR0100=H12345678, WR0102=H4444(17476)</p> | | | | | | | | | | | | | | |

†: Supported by EH-CPU ***A/448/516/548 only.

| Item number | | Fun commands-36 | | Name | | Dynamic scan pulse command † | | | | | | | | | |
|-----------------------------|-----------------------|-----------------|---|-----------------|-----------------------------------|------------------------------|-------|------------|----------------------|-------------|------------|------------|-----------------|----------------------------|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | Remark | |
| FUN 61 (s) * (PGEN (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | |
| Command format | | | | Number of steps | | | | | 73 | ← | 70 | ← | | | |
| FUN 61 (s) * (PGEN (s)) | | | | Condition | | | Steps | | | | | | | | |
| | | | | — | | | 3 | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| s | No. of ON scan pulse | | | | | | | ○ | | | | | | | |
| s+1 | No. of OFF scan pulse | | | | | | | ○ | | | | | | | |
| s+2 | Pulse output I/O | | | | ○ | | | | | | | | | Actual address is set | |
| s+3 | System area | | | | | | | | | | | | | Cannot be used by the user | |
| s+4 | | | | | | | | | | | | | | | |


Function

Table

| | |
|-------|-------------------------|
| s | n1 of ON scan pulse |
| s + 1 | n2 of OFF scan pulse |
| s + 2 | Pulse output I/O No. a |
| s + 3 | ON scan progress value |
| s + 4 | OFF scan progress value |

Relationship between number of scans and pulse activation

| Number of scans | | Pulse activation |
|-----------------|--------|--|
| n1 | n2 | |
| n1 = 0 | n2 = 0 | Pulse output turns OFF. |
| | n2 ≥ 1 | |
| n1 ≥ 1 | n2 = 0 | Pulse output turns ON. |
| | n2 ≥ 1 | Pulse output turns ON for n1 scans and turns OFF for n2 scans. |



- The following operation is repeated: Turns ON the bit internal output specified by argument s + 2 for the number of scans specified by argument s and turns it OFF for the number of scans specified by argument s + 1.
- If this command is executed several times within one scan, the internal bit output turns ON and OFF according to the number of executions.
- If both s and s + 1 are 0, the output stays OFF.
- If the startup condition turns OFF, the output as well as the progress values in s + 3 and s + 4 are retained.
- Both s + 3 and s + 4 should be cleared at initialization; otherwise the pulse width of the first cycle may change.
- Use the ADRIO command to store an actual address in the pulse output I/O. ADRIO (s + 2, bit internal output)
- If the operation is performed normally, DER is set to "0."

* () indicates the display when the LADDER EDITOR is used.

[†]: Supported by EH-CPU ***A/448/516/548 only.

Cautionary notes

- The pulse activation may at most be delayed by one scan in relation to the pulse output startup condition. Note that if the startup condition changes from ON to OFF then to ON, the pulse width of that part may change by \pm one scan.
- Use the ADRIO command to store an actual address in the pulse output I/O of $s + 2$. If not, an error will occur and no operation will be performed
- If $s + 1$ to $s + 4$ and the areas specified by $s + 2$ exceed the maximum I/O number, DER is set to “1” and no operation is performed.

| Item number | | Fun commands-37 | | Name | | I/O refresh (All points) | | | | | | | | | | |
|---|------------------|-----------------|-----|-----------------|---------|-----------------------------------|------|------|------------------------|-------------|-------------------------|-----|-----------------|-------|------------|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 80 (s) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | |
| | | | | DER | ERR | SD | V | C | | | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | | | Number of steps | | | | | 69 | ← | 41 156 | ← | 162 | ← | | |
| FUN 80 (s) | | | | Condition | | Steps | | | | | | | | | | |
| | | | | — | | 3 | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | |
| s | Argument (dummy) | | | | | | | | ○ | | | | | | | |
| Function | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">This command performs I/O refresh of all data in the external I/Os (including link area) in the middle of a scan. | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">This command performs I/O refresh of all external I/Os (including link area). If refresh of certain area is to be performed, use FUN81 or FUN82.If the argument s exceeds the maximum I/O number, DER is equal to “1” and the command will not be processed.Assign argument s as a one-word dummy. The I/O specified by argument s (WR, WL, WM) will not be affected. | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | |
| <div></div> | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | |
| <div></div> | | | | | | | | | | | | | | | | |

FUN 80 (s)

| Item number | Fun commands-38 | Name | | | | I/O refresh (Input/output designation) | | | | | | | | | |
|---------------------|-----------------|---|------|---------|-----------------------------------|--|----------------------|------------|------------|-------------|-----------------|------------|----------|-------|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| FUN 81 (s) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | Number of steps | | | | | 44 | ← | 45 | ← | 104 | ← | | | |
| FUN 81 (s) | | Condition | | | Steps | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| s | Type | | | | | | | ○ | | | | | | | |
| Function | | | | | | | | | | | | | | | |
| s | Input type | H00: Input refresh (including remote) H01: Output refresh (including remote) H02: Link refresh • Depending on the I/O type of the area specified by s, refresh is performed with respect to I/O modules only, output modules only or link area only. • Refresh is performed by each slot assignment according to the I/O assignment. • If the refresh processing is completed normally, DER is set to “0.” | | | | | | | | | | | | | |
| Cautionary notes | | • If the I/O type is other than H00, H01 or H02, DER is equal to “1” and the command will not be processed. • If the argument s exceeds the maximum I/O number, DER is set to “1” and the command will not be processed. | | | | | | | | | | | | | |
| Program example | | <div><div><div><div>R000</div><div>DIF0</div></div><div><div></div><div></div></div><div>WR0004 = 0 FUN 81 (WR0004)</div></div><div><div>R001</div><div>DIF1</div></div><div><div></div><div></div></div><div>WR0004 = 1 FUN 81 (WR0004)</div></div> <div><pre>LD R000 AND DIF0 [WR0004 = 0 FUN 81 (WR0004)] LD R001 AND DIF1 [WR0004 = 1 FUN 81 (WR0004)]</pre></div> | | | | | | | | | | | | | |
| Program description | | • Upon rising of R000, the input module is refreshed. • Upon rising of R001, the output module is refreshed. | | | | | | | | | | | | | |

| Item number | | Fun commands-39 | | Name | | I/O Refresh (slot) | | | | | | | | | | |
|---------------------|----------------------|--|---|-----------------|-----------------------------------|--------------------|------|------------|----------------------|-------------|------------|------------|-----------------|------------------------------|--------|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 82 (s) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | | | Number of steps | | | | | 80 | ← | 79 | ← | 201 | ← | | |
| FUN 82 (s) | | | | Condition | | Steps | | | | | | | | | | |
| | | | | — | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | |
| s | Number of slot | | | | | | | ○ | | | | | | | | |
| s+1 and beyond | Slot location number | | | | | | | ○ | | | | | | Designate the slot location. | | |
| Function | | | | | | | | | | | | | | | | |
| | | <div><div><div>s</div><div>Number of slot</div></div><div><div>s+1</div><div>Refresh slot number</div></div><div><div>s+2</div><div>Refresh slot number</div></div><div><div>:</div><div>:</div></div><div><div>.</div><div>:</div></div><div><div>s+n</div><div>Refresh slot number</div></div></div> <div><div>n ≤ 64</div><div>Refresh slot number is designated by unit and slot number.</div></div> | | | | | | | | | | | | | | |
| | | <div><div><div><div><div>R000</div><div>DIF0</div></div><div></div></div><div><div>WR0000 = H0002</div><div>WR0001 = H0000</div><div>WR0002 = H0012</div><div>FUN 82 (WR0000)</div></div></div><div><div>LD R000</div><div>AND DIF0</div><div>[</div><div>WR0000 = H0002</div><div>WR0001 = H0000</div><div>WR0002 = H0012</div><div>FUN 82 (WR0000)</div><div>]</div></div></div> | | | | | | | | | | | | | | |
| Program description | | <div><div><div><div><div></div><div></div></div><div></div></div><div><div>Upon rising of R000, the two slots designated after WR0001 (unit 0, slot 0) and (unit 1, slot 2) are refreshed.</div></div></div></div> | | | | | | | | | | | | | | |

Cautionary notes

- Set the unit number (0 to 1) and slot number (0 to 7) after s+1. Setting any other value will equal DER to “1” and that slot will not be processed.
- If there is no I/O assignment to the designated slot, DER is equal to “1” and that slot will not be processed.
- If the number of s+n points exceeds the maximum I/O number, DER is equal to “1” and no processing is performed.
- If the number of points exceeds 64, DER is set to 1 and the points exceeding 64 will not be processed (refresh will be performed for up to 64 points).

Slot location number

The slot locations are designated using the unit number and slot number.

The unit number and slot number are set as follows in one word units:

| | | | | |
|--------|--------|-------------|-------------|----|
| b15 | b12 | b7 | b3 | b0 |
| 0 to 0 | 0 to 0 | Unit number | Slot number | |

| Name | Floating-point operation (FUN100 to FUN118) cautionary notes |
|------|--|
|------|--|

The following describes some points of caution related to all the FUN commands (FUN100 to FUN 118) for performing floating-point operation. Data for the floating-point commands uses single-precision floating points conforming to IEEE754. The internal representation of IEEE754's single-precision floating-point numbers is explained below.

- Internal representation format of floating point

Single-precision floating-point numbers are expressed as 32-bit data in the following format.

| Contents | Sign bit (S) | Exponent part (E) | Mantissa part (M) |
|------------|-----------------|---------------------------------|--------------------------------|
| Bit number | b ₃₁ | b ₃₀ b ₂₃ | b ₂₂ b ₀ |

The 32-bit data in the above table corresponds to internal outputs in the following manner. Examples of representation of internal output I/O numbers when WR100, WR101, and DR100 are used are shown in parentheses..

| Word | Upper word (WR101) | Lower word (WR100) |
|-------------|--------------------------------|--------------------------------|
| Bit number | b ₁₅ b ₀ | b ₁₅ b ₀ |
| Double word | Double word (DR100) | |
| Bit number | b ₃₁ | b ₀ |

(1) Sign Bit

| Sign bit (S) | Contents |
|--------------|-----------------|
| 0 | Real number |
| 1 | Negative number |

(2) Exponent Part

| Exponent part (E) | Two's exponential value (E') |
|-------------------|------------------------------|
| FF | Indicates overflow value. |
| FE | 127 |
| ↓ | ↓ |
| 80 | 1 |
| 7F | 0 |
| 7E | -1 |
| ↓ | ↓ |
| 01 | -126 |
| 00 | Treated as 0. |

(3) Mantissa Part

| Mantissa part (M) | The value of mantissa part (M') |
|-------------------|---------------------------------|
| 7FFFFFFF | (1.11 ... 11) ₂ |
| 7FFFFFFE | (1.11 ... 10) ₂ |
| ↓ | ↓ |
| 1 | (1.00 ... 01) ₂ |
| 0 | (1.00 ... 00) ₂ |

1 in the integer portion of M' in the above table does not appear in the format.

(4) Mathematical Expression

The floating-point number (F) can be expressed with the following formula using the sign bit (S), exponent part (E), and mantissa part (M) listed above.

$$(F) = (-1)^S \times (1 + M \times 2^{-23}) \times 2^{E-7FH} = (-1)^S \times M' \times 2^E$$

- Range that can be expressed by floating-point numbers

| Hexadecimal Expression | | Floating Point Expression | Remark |
|------------------------|------------|-----------------------------------|---|
| Higher word | Lower word | | |
| H7F7F | HFFFF | +3.402823 ... × 10 ³⁸ | Maximum value |
| H0080 | H0000 | +1.175494 ... × 10 ⁻³⁸ | The minimum absolute value of a positive number |
| ↓ | ↓ | ↓ | The value in this range is treated as 0. |
| H8080 | H0000 | -1.175494 ... × 10 ⁻³⁸ | The minimum absolute value of a negative number |
| HFF7F | HFFF | -3.402823 ... × 10 ³⁸ | Minimum value |

- Example of setting in interval outputs

| Interval output | | Sign bit | Exponent part | Mantissa part | Floating point |
|-----------------|------------|----------|---------------|---------------|---|
| Higher word | Lower word | | | | |
| H3F80 | H0000 | 0 | 7F | 0 | (1.00 ... 00) ₂ × 2 ^{7FH-7FH} = 1.0 |
| H4128 | H0000 | 0 | 82 | 28 | (1.0101000 ... 0) ₂ × 2 ^{82H-7FH} = 10.5 |
| HBF00 | H0000 | 1 | 7E | 0 | (-1) × (1.00 ... 00) ₂ × 2 ^{7EH-7FH} = -0.5 |
| H3F00 | H0000 | 0 | 7E | 0 | (1.00 ... 00) ₂ × 2 ^{7EH-7FH} = 0.5 |

| Item number | | Fun commands-40 | | Name | | Floating Point Operation † (Real to Integer (Word) Conversion) | | | | | | | | | | | |
|---|----------|-----------------|---|-----------------|-----------------------------------|--|-------|------------|-----------|----------------------|------------|------------|-----------------|-------|------------------|--------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 100 (s) * (INTW (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 57 | ← | 58 | ← | 107 | ← | | |
| FUN 100 (s) * (INTW (s)) | | | | Condition | | | Steps | | | | | | | | | | |
| | | | | — | | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| s | Argument | | | | | | | | ○ | | | | | | s uses up to s+2 | | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div><div>s+2</div><div>150</div><div>Integer portion</div></div><div>← INTW</div><div><div>s+1</div><div>150</div><div>Real number portion</div></div><div><div>s</div><div>150</div><div>Real number portion</div></div></div> <div><ul style="list-style-type: none">Converts the real number specified by arguments s and s+1 to integer word data, then sets the result in s+2.If the calculation is completed normally, DER is equal to “0.”The floating point format conforms to IEEE754.<p>* () indicates the display when the LADDER EDITOR is used.</p></div> | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">When the resulting integer value of the conversion of the real number specified in s and s+1 falls outside the range of −32,768 to 32,767, DER is set to "1" and s+2 does not change.If s to s+2 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed.</div> | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| <div><div><div>X00200</div><div>└─┬─┘</div></div><div>DR0100 = H46FFFE00 FUN100 (WR0100)</div><div>LD X00200 [DR0100 = H46FFFE00 FUN 100 (WR0100)]</div></div> | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">At a rising edge of X0200, the real number specified in DR0100 (WR0100, WR0101) is converted to an integer and the result is set in WR0102.<p>Internal output setting : WR0101 = H46FF, WR0100 = HFE00</p><p>Operation result : WR0102 = H7FFF</p></div> | | | | | | | | | | | | | | | | | |

†: Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

| Item number | Fun commands-41 | Name | | | | Floating Point Operation † (Real to Integer (Double Word) Conversion) | | | | | | | | | |
|---|-----------------|--|------|---------|-----------------------------------|---|------------------------|------------|-------------------------|-------------|-----------------|------------|----------|------------------|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| FUN 101 (s) * (INTD (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU3**A EH-CPU3** | | Other than left | | | | |
| | | DER | ERR | SD | V | C | | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | Number of steps | | | | | 69 | ← | 69 | ← | 123 | ← | | | |
| FUN 101 (s) * (INTD (s)) | | Condition | | | Steps | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| s | Argument | | | | | | | ○ | | | | | | s uses up to s+3 | |
| Function | | | | | | | | | | | | | | | |
| <div><div><div><div>s+3</div><div>15</div><div>Integer portion</div></div><div><div>s+2</div><div>0</div><div>Integer portion</div></div><div>← INTD</div><div><div>s+1</div><div>15</div><div>Real number portion</div></div><div><div>s</div><div>0</div><div>Real number portion</div></div></div></div> | | | | | | | | | | | | | | | |
| <div><div><div>• Converts the real number specified by arguments s and s+1 to double word data, then sets the result in s+2 and s+3.</div><div>• If the calculation is completed normally, DER is equal to “0.”</div><div>• The floating point format conforms to IEEE754.</div></div><div>* () indicates the display when the LADDER EDITOR is used.</div></div> | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | |
| <div><div><div>• When the resulting integer value of the conversion of the real number specified in s and s+1 falls outside the range of −2,147,483,648 to 2,147,483,647, DER is set to "1," and s+2 and s+3 do not change.</div><div>• If s to s+3 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed.</div></div></div> | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | |
| <div><div><div>X00200</div><div>└─┴─┘</div></div><div><div>DR0100 = H4EFFFFFFF</div><div>FUN101 (WR0100)</div></div></div> | | <div><div>LD X00200</div><div>[</div><div>DR0100 = H4EFFFFFFF</div><div>FUN 101 (WR0100)</div><div>]</div></div> | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | |
| <div><div><div>• At a rising edge of X0200, the real number specified in DR0100 (WR0100, WR0101) is converted to an integer and the result is set in DR0102 (WR0102, WR0103).</div></div><div>Internal output setting : WR0101 = H4EFF, WR0100 = HFFFF</div><div>Operation result : WR0103 = H7FFF, WR0102 = HFF80</div></div> | | | | | | | | | | | | | | | |

†: Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

| Item number | | Fun commands-42 | | Name | | Floating Point Operation † (Integer (Word) to Real Number Conversion) | | | | | | | | | |
|---|----------|--|-----|-----------------|---------|---|-------|------|----------------------|-------------|------------|-----|-----------------|------------------|------------|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | Remark | |
| FUN 102 (s) * (FLOAT (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU3**A | | Other than left | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | |
| Command format | | | | Number of steps | | | | | 42 | ← | 43 | | 93 | ← | |
| FUN 102 (s) * (FLOAT (s)) | | | | Condition | | | Steps | | | | | | | | |
| | | | | — | | | 3 | | | | 89 | ← | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM |
| s | Argument | | | | | | | | O | | | | | s uses up to s+2 | |
| Function | | | | | | | | | | | | | | | |
| <div><div><div>15s+2015s+10</div><div>Real number portionReal number portion</div></div><div>← FLOAT</div><div><div>15s0</div><div>Integer portion</div></div></div> <ul style="list-style-type: none">Converts the integer word data s to a real number, then sets the result in s+1 and s+2.If the calculation is completed normally, DER is equal to “0.”The floating point format conforms to IEEE754. <p>* () indicates the display when the LADDER EDITOR is used.</p> | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">An integer value in the range of −32,768 to 32,767 can be set for s and s+1.If s to s+2 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed. | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | |
| <div><div>X00200</div><div><div>WR0100 = H7FFF</div><div>FUN102 (WR0100)</div></div></div> | | <div><div>LDX00200</div><div>[</div><div>DR0100 = H7FFF</div><div>FUN 102 (WR0100)</div><div>]</div></div> | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">At a rising edge of X0200, the integer specified in WR0100 is converted to a real number and the result is set in DR0101 (WR0101, WR0102). <p>Internal output setting : WR0100 = H7FFF</p> <p>Operation result : WR0102 = H46FF, WR0101 = HFE00</p> | | | | | | | | | | | | | | | |

†: Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

| Item number | | Fun commands-43 | | Name | | Floating Point Operation † (Integer (Double Word) to Real Number Conversion) | | | | | | | | | | |
|---|----------|-----------------|-----|-----------------|---------|--|-------|------|----------------------|-------------|------------|-----|-----------------|------------------|------------|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 103 (s) * (FLOATD (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU3**A | | Other than left | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | | | Number of steps | | | | | 47 | ← | 47 | ← | 99 | ← | | |
| FUN 103 (s) * (FLOATD (s)) | | | | Condition | | | Steps | | | | | | | | | |
| | | | | — | | | 3 | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | |
| s | Argument | | | | | | | | ○ | | | | | s uses up to s+3 | | |
| Function | | | | | | | | | | | | | | | | |
| <div><div><div>15s+3015s+20</div><div>Real number portionReal number portion</div></div><div>← FLOATD</div><div><div>15s+1015s0</div><div>Integer portionInteger portion</div></div></div> <ul style="list-style-type: none">Converts the integer double word data s and s+1 to a real number, then sets the result s+2 and s+3.If the calculation is completed normally, DER is equal to “0.”The floating point format conforms to IEEE754. <p>* () indicates the display when the LADDER EDITOR is used.</p> | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">An integer value in the range of −2,147,483,648 to 2,147,483,647 can be set for s and s+1.If s to s+3 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed. | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | |
| <div><div><div>X00200</div><div>DR0100 = H00020001 FUN103 (WR0100)</div></div><div>LD X00200 [DR0100 = H00020001 FUN 103 (WR0100)]</div></div> | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">At a rising edge of X0200, the integer specified in DR0100 (WR0100, WR0101) is converted to a real number and the result is set in DR0102 (WR0102, WR0103). <p>Internal output setting: WR0101 = H0002, WR0100 = H0001</p> <p>Operation result: WR0103 = H4800, WR0102 = H0040</p> | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

FUN 103 (s)

| Item number | | Fun commands-44 | | Name | | Floating Point Operation [†] (Addition) | | | | | | | | | | |
|---|----------|---|---|-----------------|-----------------------------------|--|------|------------|----------------------|-------------|------------|------------|-----------------|------------------|--------|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 104 (s) * (FADD (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU3**A | | Other than left | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | | | Number of steps | | | | | 70 | ← | 70 | ← | 125 | ← | | |
| FUN 104 (s) * (FADD (s)) | | | | Condition | | Steps | | | | | | | | | | |
| | | | | — | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | |
| s | Argument | | | | | | | | ○ | | | | | s uses up to s+5 | | |
| Function | | | | | | | | | | | | | | | | |
| <div><div><div>15s+5015s+40</div><div>Real number portionReal number portion</div></div><div>← FADD</div><div><div>15s+1015s0</div><div>Real number portionReal number portion</div></div><div>+</div><div><div>15s+3015s+20</div><div>Real number portionReal number portion</div></div></div> | | | | | | | | | | | | | | | | |
| <div><div><div><div>• Adds the real number (s+2, s+3) to the real number (s, s+1), then sets the result in (s+4, s+5).</div><div>• If the calculation is completed normally, DER is equal to “0.”</div><div>• The floating point format conforms to IEEE754.</div></div><div>* () indicates the display when the LADDER EDITOR is used.</div></div></div> | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | |
| <div><div><div><div>• When the operation result is not within the range of −1e+37 to 1e+37, DER is set to "1."</div><div>• If s to s+5 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed.</div></div></div></div> | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | |
| <div><div><div>X00200DIF0</div><div></div><div>DR0100 = H42C90000 DE0102 = H43488000 FUN104 (WR0100)</div></div></div> | | <div><div>LDX00200 ANDDIF0 [DR0100 = H42C90000 DR0102 = H43488000 FUN 104 (WR0100)]</div></div> | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | |
| <div><div><div><div>• At a rising edge of X0200, the real number specified in DR0100 (WR0100, WR0101) is added to the real number specified in DR0102 (WR0102, WR0103), and the result is set in DR0104 (WR0104, WR0105).</div><div>Internal output setting :WR0101 = H42C9, WR0100 = H0000 WR0103 = H4348, WR0102 = H8000</div><div>Operation result :WR0105 = H4396, WR0104 = H8000</div></div></div></div> | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

| Item number | Fun commands-45 | Name | | Floating Point Operation † (Subtraction) | | | | | | | | | | | | | |
|------------------------------|-----------------|--|------|--|-----------------------------------|------|-----------|----------------------|------------|-------------|-----------------|------------|----------|------------------|--|---|--|
| Ladder format | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | | | |
| FUN 105 (s) * (FSUB (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU3**A | | Other than left | | | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | |
| Command format | | Number of steps | | | | | | 70 | ← | 70 | | ← | | 125 | | ← | |
| FUN 105 (s) * (FSUB (s)) | | Condition | | | Steps | | | | | 121 | | ← | | | | | |
| | | — | | | 3 | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| s | Argument | | | | | | | O | | | | | | s uses up to s+5 | | | |
| Function | | | | | | | | | | | | | | | | | |
| | | <div><div><div>15s+5015s+40</div><div>Real number portionReal number portion</div></div><div>← FSUB</div><div><div>15s+1015s0</div><div>Real number portionReal number portion</div></div><div>—</div><div><div>15s+3015s+20</div><div>Real number portionReal number portion</div></div></div> <div><ul style="list-style-type: none">Subtracts the real number (s+2, s+3) from the real number (s, s+1), then sets the result in (s+4, s+5).If the calculation is completed normally, DER is equal to “0.”The floating point format conforms to IEEE754.<p>* () indicates the display when the LADDER EDITOR is used.</p></div> | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">When the operation result is not within the range of −1e+37 to 1e+37, DER is set to "1."If s to s+5 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed. | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| | | <div><div><div>X00200DIF0</div><div></div><div>DR0100 = H43488000 DE0102 = H42C90000 FUN105 (WR0100)</div></div><div>LD X00200 AND DIF0 [DR0100 = H43488000 DR0102 = H42C90000 FUN 105 (WR0100)]</div></div> | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">At a rising edge of X0200, the real number specified in DR0102 (WR0102, WR0103) is subtracted from the real number specified in DR0100 (WR0100, WR0101), and the result is set in DR0104 (WR0104, WR0105). <p>Internal output setting : WR0101 = H4348, WR0100 = H8000 WR0103 = H42C9, WR0102 = H0000</p> <p>Operation result : WR0105 = H42C8, WR0104 = H0000</p> | | | | | | | | | | | | | | | |

† : Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

| Item number | Fun commands-46 | Name | | Floating Point Operation [†] (Multiplication) | | | | | | | | | | | |
|--|-----------------|--|------|--|-----------------------------------|------|------------------------|------------|-------------------------|-------------|-----------------|------------|----------|------------------|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| FUN 106 (s) * (FMUL (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU3**A EH-CPU3** | | Other than left | | | | |
| | | DER | ERR | SD | V | C | | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | Number of steps | | | | | 69 | ← | 70 | ← | 125 | ← | | | |
| FUN 106 (s) * (FMUL (s)) | | Condition | | | Steps | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| s | Argument | | | | | | | ○ | | | | | | s uses up to s+5 | |
| Function | | | | | | | | | | | | | | | |
| <div><div><div>15s+5015s+40</div><div>Real number portionReal number portion</div></div><div>← FMUL</div><div><div>15s+1015s0</div><div>Real number portionReal number portion</div></div><div>×</div><div><div>15s+3015s+20</div><div>Real number portionReal number portion</div></div></div> | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">Multiplies the real number (s, s+1) with the real number (s+2, s+3), then sets the result in (s+4, s+5).If the calculation is completed normally, DER is equal to “0.”The floating point format conforms to IEEE754. <p>* () indicates the display when the LADDER EDITOR is used.</p> | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">When the operation result is not within the range of −1e+37 to 1e+37, DER is set to "1."If s to s+5 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed. | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | |
| <div><div>X00200DIF0</div><div>DR0100 = H43488000 DE0102 = H42C90000 FUN106 (WR0100)</div></div> | | <div>LDX00200 ANDDIF0 [DR0100 = H43488000 DR0102 = H42C90000 FUN 106 (WR0100)]</div> | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">At a rising edge of X0200, the real number specified in DR0100 (WR0100, WR0101) is multiplied by the real number specified in DR0102 (WR0102, WR0103), and the result is set in DR0104 (WR0104, WR0105). <p>Internal output setting : WR0101 = H4348, WR0100 = H8000 WR0103 = H42C9, WR0102 = H0000</p> <p>Operation result : WR0105 = H469D, WR0104 = H6C80</p> | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

| Item number | | Fun commands-47 | | Name | | Floating Point Operation † (Division) | | | | | | | | | | |
|---|----------|-----------------|-----|-----------------|---------------|--|------|------|------------------------|-------------|-------------------------|-----|-----------------|------------------|------------------|---|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 107 (s) * (FDIV (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU3**A EH-CPU3** | | Other than left | | | |
| | | | | DER | ERR | SD | V | C | | | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | | | Number of steps | | | | | 119 | ← | 119 | ← | 174 | ← | | |
| FUN 107 (s) * (FDIV (s)) | | | | Condition | | Steps | | | | | | | | | | |
| | | | | — | | 3 | | | | | | | | | 171 | ← |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | |
| s | Argument | | | | | | | | ○ | | | | | s uses up to s+5 | | |
| Function | | | | | | | | | | | | | | | | |
| <div><div><div><div>15s+5015s+40</div><div>Real number portionReal number portion</div></div><div>← FDIV</div><div><div>15s+1015s0</div><div>Real number portionReal number portion</div></div><div>/</div><div><div>15s+3015s+20</div><div>Real number portionReal number portion</div></div></div></div> <div><ul style="list-style-type: none">Divides real number (s, s+1) by real number (s+2, s+3), then sets the result in (s+4, s+5).If the calculation is completed normally, DER is equal to “0.”The floating point format conforms to IEEE754.<p>* () indicates the display when the LADDER EDITOR is used.</p></div> | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">When the operation result is not within the range of −1e+37 to 1e+37, DER is set to "1."If s to s+5 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed. | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | |
| <div><div><div><div>X00200DIF0</div><div></div><div>DR0100 = H43488000 DE0102 = H42C88000 FUN107 (WR0100)</div></div><div></div><div><div>LDX00200 ANDDIF0 [DR0100 = H43488000 DR0102 = H42C88000 FUN 107 (WR0100)]</div></div></div></div> | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">At a rising edge of X0200, the real number specified in DR0100 (WR0100, WR0101) is divided by the real number specified in DR0102 (WR0102, WR0103), and the result is set in DR0104 (WR0104, WR0105). <p>Internal output setting : WR0101 = H4348, WR0100 = H8000 WR0103 = H42C8, WR0102 = H8000</p> <p>Operation result : WR0105 = H4000, WR0104 = H0000</p> | | | | | | | | | | | | | | | | |

†: Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

| Item number | Fun commands-48 | Name | | Floating Point Operation † (Angle to Radian Conversion) | | | | | | | | | | | |
|--|-----------------|--|------|---|-----------------------------------|------|----------------------|------------|------------|-------------|-----------------|------------|----------|------------------|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| FUN 108 (s) * (FRAD (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU3**A | | Other than left | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | Number of steps | | | | | 63 | ← | 64 | ← | 117 | ← | | | |
| FUN 108 (s) * (FRAD (s)) | | Condition | | | Steps | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| s | Argument | | | | | | | ○ | | | | | | s uses up to s+3 | |
| Function | | | | | | | | | | | | | | | |
| <div><div><div>15s+3015s+20</div><div>Real number portionReal number portion</div></div><div>← FRAD</div><div><div>15s+1015s0</div><div>Real number portionReal number portion</div></div></div> <div><div>degrees × π180 = radian</div><div><ul style="list-style-type: none">Converts the angle units of the real number value specified in s and s+1 as the arguments to radian units, the sets the result the result in s+2 and s+3.If the calculation is completed normally, DER is equal to “0.”The floating point format conforms to IEEE754.</div><div>* () indicates the display when the LADDER EDITOR is used.</div></div> | | | | | | | | | | | | | | | |
| Cautionary notes | | <div><ul style="list-style-type: none">When the operation result is not within the range of −1e+37 to 1e+37, DER is set to "1."If s to s+3 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed.</div> | | | | | | | | | | | | | |
| Program example | | <div><div><div>X00200</div><div>DR0100 = H42C80000 FUN108 (WR0100)</div></div><div><div>LD X00200</div><div>[</div><div>DR0100 = H42C80000</div><div>FUN 108 (WR0100)</div><div>]</div></div></div> | | | | | | | | | | | | | |
| Program description | | <div><ul style="list-style-type: none">At a rising edge of X0200, the real number specified in DR0100 (WR0100, WR0101) is converted to a radian and the result is set in DR0102 (WR0102, WR0103).<div>Internal output setting : WR0101 = H42C8, WR0100 = H0000</div><div>Operation result : WR0103 = H3FDF, WR0102 = H66F3</div></div> | | | | | | | | | | | | | |

[†]: Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

| Item number | | Fun commands-49 | | Name | | Floating Point Operation † (Radian to Angle Conversion) | | | | | | | | | | |
|--|----------|--|---|-----------------|-----------------------------------|---|------|------------|------------------------|-------------|-------------------------|------------|-----------------|------------------|--------|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 109 (s) * (FDEG (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU3**A EH-CPU3** | | Other than left | | | |
| | | | | DER | ERR | SD | V | C | | | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | | | Number of steps | | | | | 63 | ← | 64 | ← | 117 | ← | | |
| FUN 109 (s) * (FDEG (s)) | | | | Condition | | Steps | | | | | | | | | | |
| | | | | — | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | |
| s | Argument | | | | | | | | ○ | | | | | s uses up to s+3 | | |
| Function | | | | | | | | | | | | | | | | |
| <div><div><div>15s+3015s+20</div><div>Real number portionReal number portion</div></div><div>← FDEG</div><div><div>15s+1015s0</div><div>Real number portionReal number portion</div></div></div> <div><div>radian × 180π = degrees</div><div>degrees</div></div> <div><div>• Converts the radian units of the real number value specified in s and s+1 as the arguments to angle units, then sets the result in s+2 and s+3.</div><div>• If the calculation is completed normally, DER is equal to “0.”</div><div>• The floating point format conforms to IEEE754.</div><div>* () indicates the display when the LADDER EDITOR is used.</div></div> | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | |
| <div><div>• When the operation result is not within the range of −1e+37 to 1e+37, DER is set to "1."</div><div>• If s to s+3 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed.</div></div> | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | |
| <div><div><div>X00200DIF0</div><div></div></div><div>DR0100 = H3FDF66F3 FUN109 (WR0100)</div></div> | | <div><div>LD X00200</div><div>AND DIF0</div><div>[</div><div>DR0100 = H3FDF66F3</div><div>FUN 109 (WR0100)</div><div>]</div></div> | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | |
| <div><div>• At a rising edge of X0200, the real number specified in DR0100 (WR0100, WR0101) is converted to an angle and the result is set in DR0102 (WR0102, WR0103).</div><div>Internal output setting : WR0101 = H3FDF, WR0100 = H66F3</div><div>Operation result : WR0103 = H42C8, WR0102 = H0000</div></div> | | | | | | | | | | | | | | | | |

†: Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

| Item number | | Fun commands-50 | | Name | | Floating Point Operation † (SIN) | | | | | | | | | |
|--|----------|-----------------|-----|-----------------|---------|-----------------------------------|-------|------|------------------------|-------------|-------------------------|-----|-----------------|------------------|------------|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | Remark | |
| FUN 110 (s) * (FSIN (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU3**A EH-CPU3** | | Other than left | | |
| | | | | DER | ERR | SD | V | C | | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | |
| Command format | | | | Number of steps | | | | | 281 | ← | 282 | ← | 358 | ← | |
| FUN 110 (s) * (FSIN (s)) | | | | Condition | | | Steps | | | | | | | | |
| | | | | — | | | 3 | | | | | | | | 354 |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM |
| s | Argument | | | | | | | | ○ | | | | | s uses up to s+3 | |
| Function | | | | | | | | | | | | | | | |
| <div><div><div>15s+3015s+20</div><div>Real number portionReal number portion</div></div><div>← FSIN</div><div><div>15s+1015s0</div><div>Real number portionReal number portion</div></div></div> <div><ul style="list-style-type: none">Calculates the sine value of the real number value in radian units specified in s and s+1 as the arguments, then sets the result in s+2 and s+3.If the calculation is completed normally, DER is equal to “0.”The floating point format conforms to IEEE754.<p>* () indicates the display when the LADDER EDITOR is used.</p></div> | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">When the operation result is not within the range of −1e+37 to 1e+37, DER is set to "1."If s to s+3 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed.When the value of s, s+1 is greater than 1.414847550405688000e+16, the sine value cannot be calculated, thus DER is set to "1."When the value of s, s+1 is greater than 2.981568260000000000e+08, a result is obtained but the accuracy decreases, so DER is set to "1."</div> | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | |
| <div><div><div><div>X00200DIF0</div><div></div><div></div></div><div>DR0100 = H3F060A92 FUN110 (WR0100)</div></div><div><div>LDX00200 ANDDIF0 [DR0100 = H3F060A92 FUN110 (WR0100)]</div></div></div> | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">At a rising edge of X0200, the SIN of the real number specified in DR0100 (WR0100, WR0101) is calculated and the result is set in DR0102 (WR0102, WR0103).<p>Internal output setting : WR0101 = H3F06, WR0100 = H0A92</p><p>Operation result : WR0103 = H3F00, WR0102 = H0000</p></div> | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

| Item number | Fun commands-51 | Name | | Floating Point Operation † (COS) | | | | | | | | | | | |
|---|-----------------|-----------------|------|----------------------------------|-----------------------------------|------|----------------------|------------|------------|-------------|-----------------|------------|----------|------------------|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| FUN 111 (s) * (FCOS (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU3**A | | Other than left | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | Number of steps | | | | | 303 | ← | 304 | ← | 383 | ← | | | |
| FUN 111 (s) * (FCOS (s)) | | Condition | | | Steps | | | | 380 | ← | | | | | |
| | | — | | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| s | Argument | | | | | | | ○ | | | | | | s uses up to s+3 | |
| Function | | | | | | | | | | | | | | | |
| <div><div><div>15s+3015s+20</div><div>Real number portionReal number portion</div></div><div>← FCOS</div><div><div>15s+1015s0</div><div>Real number portionReal number portion</div></div></div> | | | | | | | | | | | | | | | |
| <div><div><div>• Calculates the cosine value of the real number value in radian units specified in s and s+1 as the arguments, the sets the result in s+2 and s+3.</div><div>• If the calculation is completed normally, DER is equal to “0.”</div><div>• The floating point format conforms to IEEE754.</div></div><div>* () indicates the display when the LADDER EDITOR is used.</div></div> | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | |
| <div><div><div>• When the operation result is not within the range of −1e+37 to 1e+37, DER is set to "1."</div><div>• If s to s+3 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed.</div><div>• When the value of s, s+1 is greater than 1.414847550405688000e+16, the cosine value cannot be calculated and DER is set to "1."</div><div>• When the value of s, s+1 is greater than 2.981568260000000000e+08, a result is obtained but the accuracy decreases, so DER is set to "1."</div></div></div> | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | |
| <div><div><div><div>X00200DIF0</div><div></div><div>DR0100 = H3F060A92 FUN111 (WR0100)</div></div></div><div><div>LD X00200 AND DIF0 [DR0100 = H3F060A92 FUN 111 (WR0100)]</div></div></div> | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | |
| <div><div><div>• At a rising edge of X0200, the cosine value of the real number specified in DR0100 (WR0100, WR0101) is calculated and the result is set in DR0102 (WR0102, WR0103).</div></div><div>Internal output setting : WR0101 = H3F06, WR0100 = H0A92</div><div>Operation result : WR0103 = H3F5D, WR0102 = HB3D7</div></div> | | | | | | | | | | | | | | | |

†: Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

| Item number | | Fun commands-52 | | Name | | Floating Point Operation [†] (TAN) | | | | | | | | | | |
|--|----------|-----------------|-----|-----------------|---------|---|-------|------|------------------------|-----|-------------------------|-----|-----------------|------------------|------------|---|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 112 (s) * (FTAN (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU3**A EH-CPU3** | | Other than left | | | |
| | | | | DER | ERR | SD | V | C | | | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | | | Number of steps | | | | | 343 | ← | 341 | ← | 417 | ← | | |
| FUN 112 (s) * (FTAN (s)) | | | | Condition | | | Steps | | | | | | | | | |
| | | | | — | | | 3 | | | | | | | | 414 | ← |
| Usable I/O | | | Bit | | | | Word | | | | Double word | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | |
| s | Argument | | | | | | | | ○ | | | | | s uses up to s+3 | | |
| Function | | | | | | | | | | | | | | | | |
| <div><div><div>15s+3015s+20</div><div>Real number portionReal number portion</div></div><div>← FTAN</div><div><div>15s+1015s0</div><div>Real number portionReal number portion</div></div></div> <div><ul style="list-style-type: none">Calculates the tangent value of the real number value in radian units specified in s and s+1 as the arguments, the sets the result in s+2 and s+3.If the calculation is completed normally, DER is equal to “0.”The floating point format conforms to IEEE754.<p>* () indicates the display when the LADDER EDITOR is used.</p></div> | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">When the operation result is not within the range of −1e+37 to 1e+37, DER is set to "1."If s to s+3 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed.When the value of s, s+1 is greater than 1.414847550405688000e+16/2, the tangent value cannot be calculated and DER is set to "1."When the value of s, s+1 is greater than 2.981568260000000000e+08/2, a result is obtained but the accuracy decreases, so DER is set to "1."</div> | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | |
| <div><div><div><div>X00200DIF0</div><div></div></div><div></div><div><div>DR0100 = H3F060A92</div><div>FUN112 (WR0100)</div></div></div><div><pre>LD X00200 AND DIF0 [DR0100 = H3F060A92 FUN 112 (WR0100)]</pre></div></div> | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">At a rising edge of X0200, the tangent value of the real number specified in DR0100 (WR0100, WR0101) is calculated and the result is set in DR0102 (WR0102, WR0103).<p>Internal output setting : WR0101 = H3F06, WR0100 = H0A92</p><p>Operation result : WR0103 = H3F13, WR0102 = HCD3A</p></div> | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

| Item number | | Fun commands-53 | | Name | | Floating Point Operation † (ARC SIN) | | | | | | | | | | |
|--|----------|-----------------|-----|-----------------|---------|--------------------------------------|-------|------|------------------------|-------------|-------------------------|-----|-----------------|------------------|------------|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 113 (s) * (FASIN (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU3**A EH-CPU3** | | Other than left | | | |
| | | | | DER | ERR | SD | V | C | | | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | | | Number of steps | | | | | 200 | ← | 200 | ← | 278 | ← | | |
| FUN 113 (s) * (FASIN (s)) | | | | Condition | | | Steps | | | | 275 | ← | | | | |
| | | | | — | | | 3 | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | |
| s | Argument | | | | | | | | O | | | | | s uses up to s+3 | | |
| Function | | | | | | | | | | | | | | | | |
| <div><div><div>15s+3015s+20</div><div>Real number portionReal number portion</div></div><div>← FASIN</div><div><div>15s+1015s0</div><div>Real number portionReal number portion</div></div></div> <div><div><div>• Calculates the SIN⁻¹ value of the real number value specified in s and s+1 as the arguments, and sets the result in radian units in s+2 and s+3.</div><div>• If the calculation is completed normally, DER is equal to “0.”</div><div>• The floating point format conforms to IEEE754.</div></div><div>* () indicates the display when the LADDER EDITOR is used.</div></div> | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | |
| <div><div><div>• When the operation result is not within the range of −1e+37 to 1e+37, DER is set to "1."</div><div>• If s to s+3 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed.</div><div>• When the value of s, s+1 is greater than 1, DER is set to "1."</div></div></div> | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | |
| <div><div><div><div>X00200DIF0</div><div></div></div><div></div><div>DR0100 = H3F800000 FUN113 (WR0100)</div></div><div><div>LD X00200 AND DIF0 [DR0100 = H3F800000 FUN 113 (WR0100)]</div></div></div> | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | |
| <div><div><div>• At a rising edge of X0200, the SIN⁻¹ value of the real number specified in DR0100 (WR0100, WR0101) is calculated and the result is set in DR0102 (WR0102, WR0103).</div><div>Internal output setting : WR0101 = H3F80, WR0100 = H0000</div><div>Operation result : WR0103 = H3FC9, WR0102 = H0FDB</div></div></div> | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

| Item number | | Fun commands-54 | | Name | | Floating Point Operation [†] (ARC COS) | | | | | | | | | |
|--|----------|-----------------|-----|-----------------|---------|---|-------|------|----------------------|-------------|------------|-----|-----------------|------------------|------------|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | Remark | |
| FUN 114 (s) * (FACOS (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU3**A | | Other than left | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | |
| Command format | | | | Number of steps | | | | | 191 | ← | 191 | ← | 269 | ← | |
| FUN 114 (s) * (FACOS (s)) | | | | Condition | | | Steps | | | | 266 | ← | | | |
| | | | | — | | | 3 | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM |
| s | Argument | | | | | | | | O | | | | | s uses up to s+3 | |
| Function | | | | | | | | | | | | | | | |
| <div><div><div>15s+3015s+20</div><div>Real number portionReal number portion← FACOS</div></div><div><div>15s+1015s0</div><div>Real number portionReal number portion</div></div></div> <div><div>• Calculates the COS⁻¹ value of the real number value specified in s and s+1 as the arguments, and sets the result in radian units in s+2 and s+3.</div><div>• If the calculation is completed normally, DER is equal to “0.”</div><div>• The floating point format conforms to IEEE754.</div><div>* () indicates the display when the LADDER EDITOR is used.</div></div> | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | |
| <div><div>• When the operation result is not within the range of −1e+37 to 1e+37, DER is set to "1."</div><div>• If s to s+3 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed.</div><div>• When the value of s, s+1 is greater than 1, DER is set to "1."</div></div> | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | |
| <div><div><div><div>X00200DIF0</div><div><div></div><div></div><div></div></div><div>DR0100 = H3F800000 FUN114 (WR0100)</div></div></div><div><div>LDX00200</div><div>ANDDIF0</div><div>[</div><div>DR0100 = H3F800000</div><div>FUN 114 (WR0100)</div><div>]</div></div></div> | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | |
| <div><div>• At a rising edge of X0200, the COS⁻¹ value of the real number specified in DR0100 (WR0100, WR0101) is calculated and the result is set in DR0102 (WR0102, WR0103).</div><div>Internal output setting : WR0101 = H3F80, WR0100 = H0000</div><div>Operation result : WR0103 = H0000, WR0102 = H0000</div></div> | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

| Item number | | Fun commands-55 | | Name | | Floating Point Operation † (ARC TAN) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|----------|-----------------|-----|-----------------|---------|--------------------------------------|------|------|----------------------|-------------|------------|-----|-----------------|------------------|------------|---------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|---------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|---------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|---|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| FUN 115 (s) * (FATAN (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU3**A | | Other than left | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Command format | | | | Number of steps | | | | | 394 | ← | 395 | ← | 466 | ← | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| FUN 115 (s) * (FATAN (s)) | | | | Condition | | Steps | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | — | | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| s | Argument | | | | | | | | ○ | | | | | s uses up to s+3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div>15s+3015s+20</div><div>Real number portionReal number portion</div></div><div>← FATAN</div><div><div>15s+1015s0</div><div>Real number portionReal number portion</div></div></div> <div><div><div><div>• Calculates the TAN⁻¹ value of the real number value specified in s and s+1 as the arguments, and sets the result in radian units in s+2 and s+3.</div><div>• If the calculation is completed normally, DER is equal to “0.”</div><div>• The floating point format conforms to IEEE754.</div></div><div>* () indicates the display when the LADDER EDITOR is used.</div></div></div> <tr><td colspan="2">Cautionary notes</td><td colspan="14"></td></tr> <tr><td colspan="16"><div><div><div><div>• When the operation result is not within the range of −1e+37 to 1e+37, DER is set to "1."</div><div>• If s to s+3 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed.</div></div></div></div><tr><td colspan="2">Program example</td><td colspan="14"></td></tr><tr><td colspan="16"><div><div><div><div><div>X00200DIF0</div><div></div><div></div><div></div><div></div></div><div></div><div>DR0100 = HC0000000 FUN115 (WR0100)</div></div></div><div><div>LD X00200 AND DIF0 [DR0100 = HC0000000 FUN 115 (WR0100)]</div></div></div><tr><td colspan="2">Program description</td><td colspan="14"></td></tr><tr><td colspan="16"><div><div><div><div><div>• At a rising edge of X0200, the TAN⁻¹ value of the real number specified in DR0100 (WR0100, WR0101) is calculated and the result is set in DR0102 (WR0102, WR0103).</div><div>Internal output setting : WR0101 = HC000, WR0100 = H0000</div><div>Operation result : WR0103 = HBF8D, WR0102 = HB70D</div></div></div></div></div></td></tr></td></tr></td></tr> | | | | | | | | | | | | | | | | Cautionary notes | | | | | | | | | | | | | | | | <div><div><div><div>• When the operation result is not within the range of −1e+37 to 1e+37, DER is set to "1."</div><div>• If s to s+3 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed.</div></div></div></div> <tr><td colspan="2">Program example</td><td colspan="14"></td></tr> <tr><td colspan="16"><div><div><div><div><div>X00200DIF0</div><div></div><div></div><div></div><div></div></div><div></div><div>DR0100 = HC0000000 FUN115 (WR0100)</div></div></div><div><div>LD X00200 AND DIF0 [DR0100 = HC0000000 FUN 115 (WR0100)]</div></div></div><tr><td colspan="2">Program description</td><td colspan="14"></td></tr><tr><td colspan="16"><div><div><div><div><div>• At a rising edge of X0200, the TAN⁻¹ value of the real number specified in DR0100 (WR0100, WR0101) is calculated and the result is set in DR0102 (WR0102, WR0103).</div><div>Internal output setting : WR0101 = HC000, WR0100 = H0000</div><div>Operation result : WR0103 = HBF8D, WR0102 = HB70D</div></div></div></div></div></td></tr></td></tr> | | | | | | | | | | | | | | | | Program example | | | | | | | | | | | | | | | | <div><div><div><div><div>X00200DIF0</div><div></div><div></div><div></div><div></div></div><div></div><div>DR0100 = HC0000000 FUN115 (WR0100)</div></div></div><div><div>LD X00200 AND DIF0 [DR0100 = HC0000000 FUN 115 (WR0100)]</div></div></div> <tr><td colspan="2">Program description</td><td colspan="14"></td></tr> <tr><td colspan="16"><div><div><div><div><div>• At a rising edge of X0200, the TAN⁻¹ value of the real number specified in DR0100 (WR0100, WR0101) is calculated and the result is set in DR0102 (WR0102, WR0103).</div><div>Internal output setting : WR0101 = HC000, WR0100 = H0000</div><div>Operation result : WR0103 = HBF8D, WR0102 = HB70D</div></div></div></div></div></td></tr> | | | | | | | | | | | | | | | | Program description | | | | | | | | | | | | | | | | <div><div><div><div><div>• At a rising edge of X0200, the TAN⁻¹ value of the real number specified in DR0100 (WR0100, WR0101) is calculated and the result is set in DR0102 (WR0102, WR0103).</div><div>Internal output setting : WR0101 = HC000, WR0100 = H0000</div><div>Operation result : WR0103 = HBF8D, WR0102 = HB70D</div></div></div></div></div> | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div><div>• When the operation result is not within the range of −1e+37 to 1e+37, DER is set to "1."</div><div>• If s to s+3 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed.</div></div></div></div> <tr><td colspan="2">Program example</td><td colspan="14"></td></tr> <tr><td colspan="16"><div><div><div><div><div>X00200DIF0</div><div></div><div></div><div></div><div></div></div><div></div><div>DR0100 = HC0000000 FUN115 (WR0100)</div></div></div><div><div>LD X00200 AND DIF0 [DR0100 = HC0000000 FUN 115 (WR0100)]</div></div></div><tr><td colspan="2">Program description</td><td colspan="14"></td></tr><tr><td colspan="16"><div><div><div><div><div>• At a rising edge of X0200, the TAN⁻¹ value of the real number specified in DR0100 (WR0100, WR0101) is calculated and the result is set in DR0102 (WR0102, WR0103).</div><div>Internal output setting : WR0101 = HC000, WR0100 = H0000</div><div>Operation result : WR0103 = HBF8D, WR0102 = HB70D</div></div></div></div></div></td></tr></td></tr> | | | | | | | | | | | | | | | | Program example | | | | | | | | | | | | | | | | <div><div><div><div><div>X00200DIF0</div><div></div><div></div><div></div><div></div></div><div></div><div>DR0100 = HC0000000 FUN115 (WR0100)</div></div></div><div><div>LD X00200 AND DIF0 [DR0100 = HC0000000 FUN 115 (WR0100)]</div></div></div> <tr><td colspan="2">Program description</td><td colspan="14"></td></tr> <tr><td colspan="16"><div><div><div><div><div>• At a rising edge of X0200, the TAN⁻¹ value of the real number specified in DR0100 (WR0100, WR0101) is calculated and the result is set in DR0102 (WR0102, WR0103).</div><div>Internal output setting : WR0101 = HC000, WR0100 = H0000</div><div>Operation result : WR0103 = HBF8D, WR0102 = HB70D</div></div></div></div></div></td></tr> | | | | | | | | | | | | | | | | Program description | | | | | | | | | | | | | | | | <div><div><div><div><div>• At a rising edge of X0200, the TAN⁻¹ value of the real number specified in DR0100 (WR0100, WR0101) is calculated and the result is set in DR0102 (WR0102, WR0103).</div><div>Internal output setting : WR0101 = HC000, WR0100 = H0000</div><div>Operation result : WR0103 = HBF8D, WR0102 = HB70D</div></div></div></div></div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div><div><div>X00200DIF0</div><div></div><div></div><div></div><div></div></div><div></div><div>DR0100 = HC0000000 FUN115 (WR0100)</div></div></div><div><div>LD X00200 AND DIF0 [DR0100 = HC0000000 FUN 115 (WR0100)]</div></div></div> <tr><td colspan="2">Program description</td><td colspan="14"></td></tr> <tr><td colspan="16"><div><div><div><div><div>• At a rising edge of X0200, the TAN⁻¹ value of the real number specified in DR0100 (WR0100, WR0101) is calculated and the result is set in DR0102 (WR0102, WR0103).</div><div>Internal output setting : WR0101 = HC000, WR0100 = H0000</div><div>Operation result : WR0103 = HBF8D, WR0102 = HB70D</div></div></div></div></div></td></tr> | | | | | | | | | | | | | | | | Program description | | | | | | | | | | | | | | | | <div><div><div><div><div>• At a rising edge of X0200, the TAN⁻¹ value of the real number specified in DR0100 (WR0100, WR0101) is calculated and the result is set in DR0102 (WR0102, WR0103).</div><div>Internal output setting : WR0101 = HC000, WR0100 = H0000</div><div>Operation result : WR0103 = HBF8D, WR0102 = HB70D</div></div></div></div></div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <div><div><div><div><div>• At a rising edge of X0200, the TAN⁻¹ value of the real number specified in DR0100 (WR0100, WR0101) is calculated and the result is set in DR0102 (WR0102, WR0103).</div><div>Internal output setting : WR0101 = HC000, WR0100 = H0000</div><div>Operation result : WR0103 = HBF8D, WR0102 = HB70D</div></div></div></div></div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

FUN 115 (s)

| Item number | Fun commands-56 | Name | | Floating Point Operation [†] (Square Root) | | | | | | | | | | | |
|---|-----------------|--|------|---|-----------------------------------|------|----------------------|------------|------------|-------------|-----------------|------------|----------|------------------|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| FUN 116 (s) * (FSQR (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU3**A | | Other than left | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | Number of steps | | | | | 481 | ← | 482 | ← | 556 | ← | | | |
| FUN 116 (s) * (FSQR (s)) | | Condition | | | Steps | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| s | Argument | | | | | | | ○ | | | | | | s uses up to s+3 | |
| Function | | | | | | | | | | | | | | | |
| <div><div><div>15s+3015s+20</div><div>Real number portionReal number portion</div></div><div>← FSQR</div><div><div>15s+1015s0</div><div>Real number portionReal number portion</div></div></div> <div><div><div>• Calculates the square root using the real number value specified in s and s+1 as the arguments, the sets the result in s+2 and s+3.</div><div>• If the calculation is completed normally, DER is equal to “0.”</div><div>• The floating point format conforms to IEEE754.</div></div><div>* () indicates the display when the LADDER EDITOR is used.</div></div> | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | |
| <div><div><div>• When the operation result is not within the range of −1e+37 to 1e+37, DER is set to "1."</div><div>• If s to s+3 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed.</div><div>• When the value of s, s+1 is lower than 0, the value cannot be calculated and DER is set to "1."</div></div></div> | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | |
| <div><div><div>X00200DIF0</div><div>DR0100 = H40000000 FUN116 (WR0100)</div></div></div> | | <div><div>LDX00200 ANDDIF0 [DR0100 = H40000000 FUN 116 (WR0100)]</div></div> | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | |
| <div><div><div><div>• At a rising edge of X0200, the square root of the real number specified in DR0100 (WR0100, WR0101) is calculated and the result is set in DR0102 (WR0102, WR0103).</div><div>Internal output setting :WR0101 = H4000, WR0100 = H0000</div><div>Operation result :WR0103 = H3FB5, WR0102 = H04F3</div></div></div></div> | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

| Item number | Fun commands-57 | Name | | Floating Point Operation † (Exponent) | | | | | | | | | | | |
|--|-----------------|---|------|---------------------------------------|-----------------------------------|------|----------------------|------------|------------|-------------|-----------------|------------|----------|------------------|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| FUN 117 (s) * (FEXP (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU3**A | | Other than left | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | ↓ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | Number of steps | | | | | 329 | ← | 330 | ← | 399 | ← | | | |
| FUN 117 (s) * (FEXP (s)) | | Condition | | | Steps | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| s | Argument | | | | | | | ○ | | | | | | s uses up to s+3 | |
| Function | | | | | | | | | | | | | | | |
| <div><div><div>15s+3015s+20</div><div>Real number portionReal number portion← FEXP</div></div><div><div>15s+1015s0</div><div>Real number portionReal number portion</div></div></div> <ul style="list-style-type: none">Performs an exponent operation using the real number value specified in s and s+1 as the arguments, the sets the result in s+2 and s+3.An exponent operation is performed using 2.71828 as the base (e).If the calculation is completed normally, DER is equal to “0.”The floating point format conforms to IEEE754. <p>* () indicates the display when the LADDER EDITOR is used.</p> | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">When the operation result is not within the range of −1e+37 to 1e+37, DER is set to "1."If s to s+3 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed.Calculation cannot be performed when the value of s, s+1 is lower than −7.0839639e+02. In this case, DER is set to "1." | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | |
| | | <div><div><div>X00200DIF0</div><div></div><div>DR0100 = H40000000 FUN117 (WR0100)</div></div><div><pre>LD X00200 AND DIF0 [DR0100 = H40000000 FUN 117 (WR0100)]</pre></div></div> | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">At a rising edge of X0200, an exponent operation of the real number specified in DR0100 (WR0100, WR0101) is performed and the result is set in DR0102 (WR0102, WR0103). <p>Internal output setting : WR0101 = H4000, WR0100 = H0000</p> <p>Operation result : WR0103 = H40EC, WR0102 = H7326</p> | | | | | | | | | | | | | | | |

†: Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

| Item number | Fun commands-58 | Name | | | | Floating Point Operation † (Natural Logarithm) | | | | | | | | | | | |
|---|-----------------|-----------------|------|---------|-----------------------------------|--|----------------------|------------|------------|-------------|-----------------|------------|----------|------------------|--|--|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | |
| FUN 118 (s) * (FLOG (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU3**A | | Other than left | | | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | |
| Command format | | Number of steps | | | | | 187 | ← | 187 | ← | 257 | ← | | | | | |
| FUN 118 (s) * (FLOG (s)) | | Condition | | | Steps | | | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| s | Argument | | | | | | | ○ | | | | | | s uses up to s+3 | | | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div><div>15s+3015s+20</div><div>Real number portionReal number portion</div></div><div>← FLOG</div><div><div>15s+1015s0</div><div>Real number portionReal number portion</div></div></div> <div><ul style="list-style-type: none">Performs a logarithm operation for the real number value specified by arguments s and s+1 using the natural logarithm (e) as the base, then sets the result in s+2 and s+3.If the calculation is completed normally, DER is equal to “0.”The floating point format conforms to IEEE754.<p>* () indicates the display when the LADDER EDITOR is used.</p></div> | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">When the operation result is not within the range of −1e+37 to 1e+37, DER is set to "1."If s to s+3 exceeds the maximum value of the I/O number, DER is set to "1" and no operation is performed.Calculation cannot be performed when the value of s, s+1 is lower than or equal to 0. In this case, DER is set to "1."</div> | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| <div><div><div><div>X00200DIF0</div><div></div></div><div></div><div>DR0100 = H3F000000 FUN118 (WR0100)</div></div><div><pre>LD X00200 AND DIF0 [DR0100 = H3F000000 FUN 118 (WR0100)]</pre></div></div> | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| <div><ul style="list-style-type: none">At a rising edge of X0200, the logarithm operation of the real number specified in DR0100 (WR0100, WR0101) is performed and the result is set in DR0102 (WR0102, WR0103).<p>Internal output setting : WR0101 = H3F00, WR0100 = H0000</p><p>Operation result : WR0103 = HBF31, WR0102 = H7218</p></div> | | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU 308(A)/316(A)/448/516/548 only.

| Item number | | Fun commands-59 | | Name | | Index setting [†] (argument d) | | | | | | | | | | |
|--|---------------|---|-----|-----------------|---------|---|-------|------|------------------------|-------------|-------------------------|-----|-----------------|-------|----------------|--|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 120 (s) * (INDXD (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | |
| | | | | DER | ERR | SD | V | C | | | | | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | | | Number of steps | | | | | 18 | ← | 22 | ← | | | | |
| FUN 120 (s) * (INDXD (s)) | | | | Condition | | | Steps | | | | | | | | | |
| | | | | — | | | 3 | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DN, DM | |
| s | Index I/O No. | | | | | | | | ○ | | | | | | | |
| Function | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">Sets the argument used as an index in respect to argument d of the MOV and COPY commands. | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">The I/O value specified in the Index Area will be initialized to “0.”Index qualification will be performed to both the MOV and COPY commands.This does not check for duplicate index numbers. | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | |
| <div><div><div>X00200</div><div>├──┤</div><div>FUN 120 (WR0100)</div></div><div><div>X00200</div><div>├──┤</div><div>COPY(WR0200, H2020, 255) FUN 123 (WR0100)</div></div></div> <div><div>Sets the WR0100 as an index in respect to argument d.</div><div>Performs copy processing after the index (WR0100) is added in respect to argument d of the COPY command (WR0200). After the COPY command is executed, the index will be updated (+1) (FUN 123).</div></div> | | | | | | | | | | | | | | | | |


[†]: Supported by EH-CPU ***A/448/516/548 only.

| Item number | Fun commands-60 | Name | | | | Index setting [†] (argument s) | | | | | | | | | |
|-------------------------------|-----------------|---|------|---------|-----------------------------------|---|------------------------|------------|-------------------------|-------------|-----------------|----------------|----------|-------|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| FUN 121 (s) * (INDXS (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | | |
| | | DER | ERR | SD | V | C | | | | | | | | | |
| | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | Number of steps | | | | | 18 | ← | 22 | ← | | | | | |
| FUN 121 (s) * (INDXS (s)) | | Condition | | | Steps | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DN, DM | | | |
| s | Index I/O No. | | | | | | | ○ | | | | | | | |
| Function | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">Sets the argument used as an index in respect to argument s of the MOV and COPY commands. | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">The I/O value specified in the Index Area will be initialized to “0.”Index qualification will be performed to both the MOV and COPY commands.This does not check for duplicate index numbers. | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | |
| | | <div><div><div>X00200</div><div></div><div>FUN 120 (WR0100) FUN 121 (WR0101)</div></div><div><div>X00200</div><div></div><div>COPY(WR0200, WM100, 255) FUN 123 (WR0100) FUN 123 (WR0101)</div></div></div> <div><div>Sets WR0100 as an index in respect to argument d and sets WR0101 as an index in respect to argument s.</div><div>Adds an index (WR0100) in respect to argument d (WR0200) of the COPY command. Then adds an index (WR0101) in respect to argument s (WM100). After the COPY command is executed, the index will be updated (+1) (FUN 123).</div></div> | | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

| Item number | Fun commands-61 | Name | | Index cancel † | | | | | | | | | | |
|-------------------------------|-----------------|--|------|----------------|-----------------------------------|------|----------------------|------------|------------|-------------|-----------------|----------------|----------|-------|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 122 (s) * (INDXC (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | Number of steps | | | | | 18 | ← | 21 | ← | | | | |
| FUN 122 (s) * (INDXC (s)) | | Condition | | | Steps | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DN, DM | | |
| s | Index I/O No. | | | | | | | ○ | | | | | | |
| Function | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">• Cancels the index specification that is set for argument d or s of the MOV and COPY commands.• Sets the I/O number specified by FUN 120 or FUN 121 to s. | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">• Cancels the index specification for argument d or s in respect to both the MOV and COPY commands.• If the I/O number set in s is not specified as an index, DER will be equal to “1” and no processing will be performed. | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | |
| | | <div><div><div>X00200</div><div><div></div><div></div></div></div><div>FUN 122 (WR0100)</div><div>Cancels the index specification with which WR0100 is set as an index.</div></div> | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

| Item number | Fun commands-62 | Name | | | | Increment [†] (INC) | | | | | | | | | | | |
|--|-----------------|---|------|---------|-----------------------------------|---|----------------------|------------|------------|-------------|-----------------|------------|----------|-------|--|--|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | |
| FUN 123 (s) * (INC (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | |
| | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | |
| Command format | | Number of steps | | | | | 29 | ← | 30 | ← | 77 | ← | | | | | |
| FUN 123 (s) * (INC (s)) | | Condition | | | Steps | | | | 74 | ← | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| s | Argument | | | | | | | ○ | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">Increments the word I/O specified in WR, WL, WM by 1 (+1). <p>* () indicates the display when the LADDER EDITOR is used.</p> | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">When FFFFH is increased by 1 (+1), the result will be 0000H. | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| | |  | | | | <pre>LD X00200 AND DIF0 [WR0100 = H0000] LD X00200 AND DIF1 [FUN 123 (WR0100)]</pre> | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">At a rising edge of X0200, the WR0100 is incremented by 1 (+1). <p>Internal output setting : WR0100 = H0000</p> <p>Operation result : WR0100 = H0001</p> | | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

| Item number | | Fun commands-63 | | Name | | Double Word Increment [†] (INCD) | | | | | | | | | |
|---|----------|-----------------|-----|-----------------|---------|---|------|------|------------------------|-------------|-------------------------|-----|-----------------|------------------|------------|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | Remark | |
| FUN 124 (s) * (INCD (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | |
| | | | | DER | ERR | SD | V | C | | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | |
| Command format | | | | Number of steps | | | | | 42 | ← | 42 | ← | 94 | ← | |
| FUN 124 (s) * (INCD (s)) | | | | Condition | | Steps | | | | | | | | | |
| | | | | — | | 3 | | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM |
| s | Argument | | | | | | | | ○ | | | | | s uses up to s+1 | |
| Function | | | | | | | | | | | | | | | |
| <div>• Replaces the specified I/O in WR, WL or WM with the double word I/O in DR, DL or DM, and increments the double word I/O by 1 (+1).</div> <div>* () indicates the display when the LADDER EDITOR is used.</div> | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | |
| <div>• When the area specified by s exceeds the maximum value of I/O number, DER is set to "1" and no operation is performed.</div> <div>• When FFFFFFFFH is increased by 1 (+1), the result will be 00000000H.</div> | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | |
| <div><div><div>X00200DIF0</div><div>DR0100 = H00000000</div></div><div><div>X00200DIF1</div><div>FUN 124 (WR0100)</div></div></div> <div><div>LDX00200ANDDIF0[DR0100 = H00000000]</div><div>LDX00200ANDDIF1[FUN 124 (WR0100)]</div></div> | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | |
| <div>• At a rising edge of X0200, the DR0100 is incremented by 1 (+1).</div> <div>Internal output setting : DR0100 = H00000000</div> <div>Operation result : DR0100 = H00000001</div> | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

FUN 124 (s)

| Item number | Fun commands-64 | Name | | | | Decrement [†] (DEC) | | | | | | | | | | | |
|-----------------------------|-----------------|--|------|---------|-----------------------------------|------------------------------|----------------------|------------|------------|-------------|-----------------|------------|--------|----------|-------|--|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | |
| FUN 125 (s) * (DEC (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | |
| | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | |
| Command format | | Number of steps | | | | | 30 | ← | 30 | ← | 77 | ← | | | | | |
| FUN 125 (s) * (DEC (s)) | | Condition | | | Steps | | | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | | Constant | Other | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| s | Argument | | | | | | | ○ | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">Decrements the word I/O specified in WR, WL or WM by 1 (−1). <p>* () indicates the display when the LADDER EDITOR is used.</p> | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">When 0000H is decreased by 1 (−1), the result will be FFFFH. | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| | | <div><div><div>X00200DIF0</div><div>— — —</div><div>WR0100 = HFFFF</div></div><div><div>X00200DIF1</div><div>— — —</div><div>FUN 125 (WR0100)</div></div></div> <div><pre>LD X00200 AND DIF0 [WR0100 = HFFFF] LD X00200 AND DIF1 [FUN 125 (WR0100)]</pre></div> | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">At a rising edge of X0200, the WR0100 is decremented by 1 (−1). <p>Internal output setting : WR0100 = HFFFF</p> <p>Operation result : WR0100 = HFFFE</p> | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

| Item number | | Fun commands-65 | | Name | | Double Word Decrement [†] (DECD) | | | | | | | | | | | |
|---|----------|-----------------|--|-----------------|------|---|-----------------------------------|------|-----------|----------------------|------------|-------------|-----------------|------------|------------------|--------|--|
| Ladder format | | | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 126 (s) * (DECD (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | | | Number of steps | | | | | | 41 | ← | 42 | ← | 94 | ← | | |
| FUN 126 (s) * (DECD (s)) | | | | Condition | | | Steps | | | | | 91 | ← | | | | |
| | | | | — | | | 3 | | | | | | | | | | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| s | Argument | | | | | | | | ○ | | | | | | s uses up to s+1 | | |
| Function | | | | | | | | | | | | | | | | | |
| <div>• Replaces the specified I/O in WR, WL or WM with the double word I/O in DR, DL or DM, and decrements the double word I/O by 1 (–1).</div> <div>* () indicates the display when the LADDER EDITOR is used.</div> | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| <div>• When the area specified by s exceeds the maximum value of I/O number, DER is set to "1" and no operation is performed.</div> <div>• When 00000000H is decreased by 1 (–1), the result will be FFFFFFFFH.</div> | | | | | | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | | | | |
| <div><div><div><div>X00200</div><div>DIF0</div><div></div></div><div>DR0100 = HFFFFFFF</div></div><div><div><div>X00200</div><div>DIF1</div><div></div></div><div>FUN 126 (WR0100)</div></div></div> <div><div>LD X00200</div><div>AND DIF0</div><div>[</div><div>WR0100 = HFFFFFFF</div><div>]</div><div>LD X00200</div><div>AND DIF1</div><div>[</div><div>FUN 126 (WR0100)</div><div>]</div></div> | | | | | | | | | | | | | | | | | |
| Program description | | | | | | | | | | | | | | | | | |
| <div>• At a rising edge of X0200, the DR0100 is decremented by 1 (–1).</div> <div>Internal output setting : DR0100 = HFFFFFFF</div> <div>Operation result : DR0100 = HFFFFFFFE</div> | | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

| Item number | Fun commands-66 | Name | | Expand bit data to word data [†] | | | | | | | | | | |
|--------------------------------|--------------------|---|------|---|-----------------------------------|------|------------------------|------------|-------------------------|-------------|-----------------|----------|--------|------------------------------------|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 127 (s) * (BITTOW (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | |
| | | DER | ERR | SD | V | C | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | Number of steps | | | | | 139 | ← | 133 | ← | | | | |
| FUN 127 (s) * (BITTOW (s)) | | Condition | | | Steps | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DN, DM |
| s | Bit header I/O No. | | | | | | | ○ | | | | | | Specify with actual address (Note) |
| s+1 | No. of bits | | | | | | | ○ | | | | | | 0 to 16 |
| s+2 | Word I/O No. | | | | | | | ○ | | | | | | Specify with actual address (Note) |
| Function | | | | | | | | | | | | | | |
| | | <div><div><div>s</div><div>s+1</div><div>s+2</div></div><div><div>Bit header I/O No.</div><div>No. of bits</div><div>Word I/O No.</div></div><div><div><div><div>b15</div><div>~</div><div>b4</div><div>b3</div><div>b2</div><div>b1</div><div>b0</div></div><div><div>0</div><div>~</div><div>0</div><div>d</div><div>c</div><div>b</div><div>a</div></div></div><div><div><div><div>↑</div><div>↑</div><div>↑</div><div>↑</div></div><div><div>a</div><div>b</div><div>c</div><div>d</div></div></div></div></div></div> | | | | | | | | | | | | |
| Cautionary notes | | <div><div><div><div><div>•</div><div>Set the actual I/O addresses using the ADRIO command for the s and s + 2 parameters. If the actual addresses are not specified, DER will be equal to “1” and no processing will be performed.</div></div><div><div>•</div><div>If s through s + 2 or the areas specified by them overlap, DER will be equal to “1” and no processing will be performed.</div></div><div><div>•</div><div>If s through s + 2 exceed the maximum value of the I/O number, DER will be equal to “1” and no processing will be performed..</div></div><div><div>•</div><div>If the areas specified by s through s + 2 exceed the maximum I/O number, the data will be expanded within the specified area range, but DER will be equal to “1”.</div></div><div><div>•</div><div>If the number of bits (s + 1) exceeds 16, DER will be equal to “1” and no processing will be performed.</div></div><div><div>•</div><div>If the number of bits (s + 1) is 0, no processing will be performed. DER will be equal to “1”.</div></div></div></div></div> | | | | | | | | | | | | |
| Program example | | | | | | | | | | | | | | |
| | | <div><div><div><div>X00200</div><div> </div><div> </div></div><div><div>ADRIO (WR0100, M0000)</div><div>WR0101 = H0004</div><div>ADRIO (WR0102, WR0200)</div><div>FUN 127 (WR0100)</div></div><div><div>Sets the bit data of M0000 through M0003 starting with the lower level bits of WR0200 in sequence. All other bits will be set to “0”.</div></div></div></div> | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

| Item number | Fun commands-67 | Name | | Compress word data to bit data (DeviceNet) [†] | | | | | | | | | | |
|--------------------------------|--------------------|---|------|---|-----------------------------------|------|------------------------|------------|-------------------------|-------------|-----------------|----------|--------|------------------------------------|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 128 (s) * (WTOBIT (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU***A EH-CPU3** | | Other than left | | | |
| | | DER | ERR | SD | V | C | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | |
| Command format | | Number of steps | | | | | 145 | ← | 139 | ← | | | | |
| FUN 128 (s) * (WTOBIT (s)) | | Condition | | | Steps | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DN, DM |
| s | Word I/O No. | | | | | | | ○ | | | | | | Specify with actual address (Note) |
| s+1 | No. of bits | | | | | | | ○ | | | | | | 0 to 16 |
| s+2 | Bit header I/O No. | | | | | | | ○ | | | | | | Specify with actual address (Note) |
| Function | | | | | | | | | | | | | | |
| | | <div><div><div>• Sets the specified number of bits (s + 1), from the lowest bit of the I/O (s) specified by the word I/O number, in the area starting with the specified header I/O number (s + 2).</div><div><div><div><div>s</div><div>Word I/O No.</div></div><div><div>s+1</div><div>No. of bits</div></div><div><div>s+2</div><div>Bit header I/O No.</div></div></div><div><div><div>b15</div><div>~</div><div>b5</div><div>b4</div><div>b3</div><div>b2</div><div>b1</div><div>b0</div></div><div><div>p</div><div>~</div><div>f</div><div>e</div><div>d</div><div>c</div><div>b</div><div>a</div></div></div><div><div><div>a</div><div>b</div><div>c</div><div>d</div></div><div><div>←</div><div>←</div><div>←</div><div>←</div></div></div></div></div></div> | | | | | | | | | | | | |
| Cautionary notes | | <div><div><div><div>• Set the actual I/O addresses using the ADRIO command for the s and s + 2 parameters. If the actual addresses are not specified, DER will be equal to “1” and no processing will be performed.</div><div>• If s through s + 2 or the areas specified by them overlap, DER will be equal to “1” and no processing will be performed.</div><div>• If s through s + 2 exceed the maximum value of the I/O number, DER will be equal to “1” and no processing will be performed..</div><div>• If the areas specified by s through s + 2 exceed the maximum I/O number, the data will be expanded within the specified area range, but DER will be equal to “1”.</div><div>• If the number of bits (s + 1) exceeds 16, DER will be equal to “1” and no processing will be performed.</div><div>• If the number of bits (s + 1) is 0, no processing will be performed. DER will be equal to “1”.</div></div></div></div> | | | | | | | | | | | | |
| Program example | | <div><div><div><div>X00200</div><div> </div></div><div><div>ADRIO (WR0100, WR0200) WR0101 = H0004 ADRIO (WR0102, M0000) FUN 128 (WR0100)</div></div></div><div><div>Expands the lower four bits of WR0200 to the range from M0000 through M0003.</div></div></div> | | | | | | | | | | | | |

[†]: Supported by EH-CPU ***A/448/516/548 only.

| Item number | Fun commands-68 | Name | | Explicit message execution [†] | | | | | | | | | | |
|--|-----------------|-----------------|------|---|----------------|-------|-----------|------------|-----|----------------------|----|------------|----------|-------|
| Ladder format | | Condition code | | | | | | | | Processing time (μs) | | | Remark | |
| FUN 162 (S) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU5** | | | | | | | |
| | | DER | ERR | SD | V | C | Ave | Max | | | | | | |
| | | ↕ | ● | ● | ● | ● | 127 | | 388 | | | | | |
| Command format | | Number of steps | | | | | | | | | | | | |
| FUN 162 (S) | | Condition | | | | Steps | | | | | | | | |
| | | — | | | | 3 | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other |
| | | X | Y | R, L, M | TD, SS, CU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | |
| s | Argument | | | | | | | ○ | | | | | | |
| Function | | | | | | | | | | | | | | |
| <div>• This is to execute explicit command for EH-RMD module.</div> <div>• Put this command without any contact together with FUN 163 command.</div> | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

†: Supported by EH-CPU 516/548 only.

| Item number | Fun commands-69 | Name | | Explicit message configuration (DeviceNet) † | | | | | | | | | |
|---|--|-----------------|------|--|----------------|------|-------------------------------------|--|-------------|----|----------|-------|------------------|
| Ladder format | | Condition code | | | | | | Processing time (μs) | | | Remark | | |
| FUN 163 (s) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU5** | | | | | | |
| | | DER | ERR | SD | V | C | Ave | Max | | | | | |
| | | ↕ | ● | ● | ● | ● | 37 | 150 | | | | | |
| Command format | | Number of steps | | | | | | | | | | | |
| FUN 163 (s) | | Condition | | | Steps | | | | | | | | |
| | | — | | | 3 | | | | | | | | |
| Usable I/O | | Bit | | | Word | | | | Double word | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, CU, CT | WX | WY | WR, WL, WM | TC | DX | | | DY |
| s | Argument | | | | | | | O | | | | | s uses up to s+5 |
| Function | | | | | | | | | | | | | |
| <div>• Flag table and sending/receiving area address for explicit message are configured in this command.</div> <div>• Since 4 times of EH-RMD can be used in case of remote assignment, this command has parameter area for 4 modules.</div> | | | | | | | | | | | | | |
| S parameter | | | | | | | | | | | | | |
| +0 | [0] Number of EH-RMD modules | | | | | | 1 st EH-RMD | [0] Number of EH-RMD modules. Maximum is 4. | | | | | |
| +1 | [1] Slot No. for 1 st EH-RMD | | | | | | | [1] Slot number for 1 st EH-RMD (0 to 7) | | | | | |
| +2 | [2] Control flag address [ADRIO command] | | | | | | | [2] Control flag address configured by ADRIO command. (Possible I/O type : R, L and M.) | | | | | |
| +3 | [3] Sending area address [ADRIO command] | | | | | | | [3] Sending area address configured by ADRIO command. (Possible I/O type : WR, WL and WM) | | | | | |
| +4 | [4] Receiving area address [ADRIO command] | | | | | | | [4] Receiving area address configured by ADRIO command. (Possible I/O type : WR, WL and WM) | | | | | |
| +5 | [5] Sending error code | | | | | | | [5] Sending error code set by CPU | | | | | |
| +6 | [6] Receiving error code | | | | | | [6] Receiving error code set by CPU | | | | | | |
| +7 | [1] Slot No. for 2 nd EH-RMD | | | | | | 4 th EH-RMD | | | | | | |
| - | - | | | | | | | | | | | | |
| +H13 | [1] Slot No. for 4 th EH-RMD | | | | | | | | | | | | |
| +H14 | [2] Control flag address [ADRIO command] | | | | | | | | | | | | |
| +H15 | [3] Sending area address [ADRIO command] | | | | | | | | | | | | |
| +H16 | [4] Receiving area address [ADRIO command] | | | | | | | | | | | | |
| +H17 | [5] Sending error code | | | | | | | | | | | | |
| +H18 | [6] Receiving error code | | | | | | | | | | | | |
| Caution | | | | | | | | | | | | | |
| <div>• Parameter tables are addressed by ADRIO command for [2] to [4].</div> <div>• If I/O address of "s" does not exist in CPU, the command is not executed with DER=1.</div> <div>• Be careful to map each table since area overlapping is not checked by system.</div> | | | | | | | | | | | | | |

[†]: Supported by EH-CPU 516/548 only.

Control flag details

| | |
|----|-----------------------|
| +0 | [0] Send data flag |
| +1 | [1] Initializing flag |

[0] Send data flag :

Set 1 by user program to send explicit message. This flag is cleared after communication completed.

[1] Initializing flag :

Set 1 by user program to initialize the FUN command or to clear timeout. Received message is cleared as well.

Sending area details

| | | |
|----|-------------------------------|-----------------|
| +0 | Size | |
| +1 | Service | MACID |
| +2 | Class | |
| +3 | Instance | |
| +4 | Service data 1 | Service data 0 |
| | Max. 64 byte for service data | |
| | Service data 63 | Service data 62 |

Size :

Service data (sending area from s+4 to s+n) size with byte unit


*) If the byte size is odd number, the last byte is stored in lower byte.

Sending error code

| |
|------------|
| Error code |
|------------|

| Error code | Name | Remarks |
|------------|-------------------|--|
| 0001H | Timeout error | Detected by EH-RMD (timeout 3 sec.) |
| 0002H | Data size error | Detected by EH-RMD |
| 0003H | Mail box error | Detected by EH-RMD |
| 0101H | Timeout error | Detected by CPU (timeout 5 sec.) |
| 0202H | Range error | Data size exceeds configured sending area. |
| 0203H | Slot number error | Slot number must be 0 to 7. |
| 0204H | No module error | EH-RMD is not mounted on configured slot. |

Receiving area details



Size :
 Service data (receiving area from s+4 to s+n) size with byte unit
 *) If the byte size is odd number, the last byte is stored in lower byte.

Receiving error

| |
|------------|
| Error code |
|------------|

| Error code | Description | Remarks |
|------------|---|---|
| 0000H | Command message sending ready | |
| 0001H | Command message sending completed properly. | |
| 0002H | Message being sent. | |
| 0004H | Node off line error | Detected by EH-RMD |
| 0005H | DeviceNet port off line | Detected by EH-RMD |
| 0006H | Invalid Txid | Detected by EH-RMD |
| 0007H | Txid duplicated | Detected by EH-RMD |
| 0009H | sending/receiving buffer full | Detected by EH-RMD |
| 000CH | Response data size over | Detected by EH-RMD |
| 000EH | Size error | Detected by EH-RMD |
| 000FH | Response time out error | Detected by EH-RMD (Timeout : 3 sec.) |
| 0101H | Time out error | CPU←→EH-RMD timeout 5 sec. |
| 0102H | Receiving time out error | Timeout 5 sec. |
| 0201H | Txid unmatched | |
| 0202H | Area range error | Receiving data is out of receiving range *1 |

*1) Data withing the range is kept.

| Item number | Fun commands-70 | Name | Inverter control command † | | | | | | | | | | | |
|----------------|------------------|-----------------|----------------------------|---------|----------------|------|----------------------|------------|--------|-------------|----|----------|-------|------------------|
| Ladder format | | Condition code | | | | | Processing time (μs) | | Remark | | | | | |
| FUN 190 (S) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU5** | | | | | | | |
| | | DER | ERR | SD | V | C | Ave | Max | | | | | | |
| | | ↕ | ● | ● | ● | ● | 136.4 | 2736.4 | | | | | | |
| Command format | | Number of steps | | | | | | | | | | | | |
| FUN 190 (S) | | Condition | | | Steps | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, CU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM |
| s | Argument | | | | | | | ○ | | | | | | s uses up to s+5 |
| g | Control bit area | | | ○ | | | | | | | | | | g uses up to g+3 |
| h | Command area | | | | | | | ○ | | | | ○ | | h uses up to h+3 |
| i | Response area | | | | | | | ○ | | | | ○ | | i uses up to i+3 |
| Function | | | | | | | | | | | | | | |

(1) This command is to control Hitachi inverter (SJ300/L300P/SJH300/HFC-VAN3 series) through CPU port 1.

(2) Configure communication port 1 as a RS-485 . (dip switch 5 Off, port type in WRF036)
(Please see Chapter 4 System Equipment 4.2 CPU Module, Chapter13 System Internal Outputs 13.2 Word Special Internal Output Area)

(3) Configure s parameters to control inverter as below.

(4) s parameter table

S-parameter

| | |
|-----|---|
| s | 1] Starting address of Control bit area [ADRIO (s , g)] |
| s+1 | 2] Starting address of Command area [ADRIO (s+1 , h)] |
| s+2 | 3] Starting address of Response area [ADRIO (s+2 , i)] |
| s+3 | 4] Timeout |
| s+4 | 5] Communication speed |
| s+5 | 6] Communication format |

(s: WR , WL , WM)

Control bit area

| | |
|-----|--------------------------|
| g | 7] Send command |
| g+1 | 8] Comm. completed |
| g+2 | 9] Initialize |
| g+3 | 10] Initialize completed |

(g: R , L , M)

Command area

| | | |
|-----|------------------|-------------|
| h | 11] Node address | 12] Command |
| H+1 | { h+1 | 13] Data |
| | h+2 | |
| | h+3 | |
| H+3 | { h+3 | 13] Data |
| | h+4 | |

(h: WR , WL , WM / H: DR , DL , DM)

Response area

| | | |
|------|----------------|----------|
| i | 14] Error code | |
| I+1 | { i+1 | 15] Data |
| | i+2 | |
| | i+3 | |
| I+3 | { i+3 | 15] Data |
| | i+4 | |
| | i+5 | |
| I+66 | { i+66 | 15] Data |
| | i+67 | |

(i: WR , WL , WM / I: DR , DL , DM)

Communication parameter

FUN 190 (s)

†: Supported by CPU516/548.

Function

1] Starting address of control bit area : Assign control bit area by ADRIO command*¹.

2] Starting address of command area: Assign inverter command area by ADRIO command*¹.

3] Starting address of response: Assign response area by ADRIO command*¹.

*¹ Refer to the Chapter 5 Command Specifications, 5.3 Command Specification Details (3) Application command for ADRIO command.

4] Timeout: The timeout from the execution of FUN190 command to the command completion.

= 0: Timeout is not checked

≠ 0: ×10ms timeout check (The maximum possible set value is HFFFF)

5] Communication speed: Configure as same speed as inverter's.

| • Baud rate | • Set value |
|-------------|-------------|
| • 2400 bps | • H0000 |
| • 4800 bps | • H0001 |
| • 9600 bps | • H0002 |
| • 19200 bps | • H0003 |

6] Transmission format: Configure as same format as inverter's.

| Transmission code | Set value |
|---------------------------|-----------|
| 7 bit even parity 2 stops | H0000 |
| 7 bit odd parity 2 stops | H0001 |
| 7 bit even parity 1 stop | H0002 |
| 7 bit odd parity 1 stop | H0003 |
| 8 bit no parity 2 stops | H0004 |
| 8 bit no parity 1 stop | H0005 |
| 8 bit even parity 1 stop | H0006 |
| 8 bit odd parity 1 stop | H0007 |

(5) Control bit area

Set 1 in user program to send command or initialize the command.

7] Send command: Set 1 to send command to inverter in user program.

CPU sets 0 automatically when the operation completed.

8] Communication completed : CPU sets 1 automatically when the operation completed

When 7] Send command bit or 9] Initialize bit is set, it is cleared by CPU.

9] Initialize: Set 1 to initialize the FUN 190 command in user program.

CPU sets 0 automatically when the operation completed.

10] Initialize completed: CPU sets 0 automatically when the operation initialized.

When 7] Send command bit or 9] Initialize bit is set, it is cleared by CPU.

(6) Command area

Configure Node address number and command according to below description.

11] Node address: Set Node address number of inverter from 01 up to 32(all BCD data). Node address number FF (at BCD data)^{*2} is for broadcast sending, which is supported only by commands 00, 01, 02, 07, 08, 0A, and 0B^{*3}. Inverters do not reply to this broadcast command.

*² If configured Node address number does not exist, no error will be detected. Use timeout instead.

*³ If Node address number FF is used with command, which does not support FF, error message given in “ (7)Response area 14] Error code”.

Function

12] Command list of inverter


| Command | Description | Broadcast |
|---------|--|-----------|
| 00 | Forward / Reverse / Stop command | ✓ |
| 01 | Setting of frequency in standard profile | ✓ |
| 02 | Setting of intelligent terminal state | ✓ |
| 03 | Read all monitor data (back read) | |
| 04 | Read inverter status | |
| 05 | Read trip history | |
| 06 | Read a single parameter value | |
| 07 | Write a single parameter value | ✓ |
| 08 | Set inverter parameters to default values | ✓ |
| 09 | Verifies that the requested setting can be written to EEPROM | |
| 0A | Writes a parameter value to EEPROM | ✓ |
| 0B | Requests the recalculation of internal constant | ✓ |

13] Data : The setting value set as an inverter by each command is input.

(7) Response area

The response from inverter is stored in this area.

14] Error code : If FUN 190 command is not completed correctly, error code is given in the following format.



[1] Node address : Inverter Node address number of communication error is given in BCD format.

(Node address No.24 → H24) When PLC detects errors, Node address is displayed on "HEE".

[2] Error code: Detected by either inverter error or PLC error .

Error code list

| Inverter error | | PLC error | |
|----------------|-------------------------------------|------------|--------------------------------|
| Error code | Description | Error code | Description |
| | Parity error | | Parity error |
| H02 | Check sum error | H22 | Framing error |
| H03 | Framing error | H23 | Overrun error |
| H04 | Overrun error | H24 | Timeout |
| H05 | Protocol error | H25 | Receiving buffer overrun error |
| H06 | ASCII code error | H26 | Sum check error |
| H07 | Receive buffer overrun error | H27 | Protocol error ^{*4} |
| H08 | Receive time-out error | H28 | ASCII code error |
| H11 | Abnormal command code/value error | H29 | Node address error |
| H13 | Execution impossible error | H30 | Command unusual error |
| H16 | Abnormal parameter code/value error | H31 | Conflict error ^{*5} |
| | | H32 | Port designation error |
| | | H33 | Command area range error |
| | | H34 | Response area range error |
| | | H35 | Overlap error |
| | | H36 | Node address unmatched |

*4 No [CR] is detected in right position.

*5 This error is detected when FUN190 is executed while TRNS0 or RECV0 command is operated. In this case, FUN190 command will be terminated.


15] Data : The response data is stored in the following format depending on 03,04,05,06,09 command.

(8) Command area/ Response area by each command.


(a) Command area



(a) Command area



(a) Command area



| [FW] | [CF1] | [CF2] | (Input Data) |
|------|-------|-------|--------------|
|------|-------|-------|--------------|

$$H00000000000000000001 + H00000000000000000004 + H00000000000000000008 = H0000000000000000000D$$

Input Data



No response normally. If operation does not work properly, error code is given as shown in “14] Error code”.

Function

(iv) Command 03: Read all monitor data

(a) Command area

| | | |
|---|------------------|-----|
| h | 11] Node address | H03 |
|---|------------------|-----|

(b) Response area

No response normally. If operation does not work properly, error code is given as shown in "14] Error code".

| | | | |
|-----------|--|-------------|---------------------------------------|
| i | 14] Error code | i+13 | [10] Electric power $\times 10^{*12}$ |
| I+1 { i+1 | [1] Output frequency $\times 100^{*7}$ | i+14 | [11] Reserved |
| i+2 | | I+15 { i+15 | [12] Run Mode time |
| i+3 | [2] Output current $\times 10$ | i+16 | |
| i+4 | [3] Direction of rotation | I+17 { i+17 | [13] Power ON time |
| I+5 { i+5 | [4] PID feedback ^{*8} | i+18 | |
| i+6 | | | |
| i+7 | [5] Intelligent input | | |
| i+8 | [6] Intelligent output | | |
| I+9 { i+9 | [7] Frequency converting $\times 100$ | | |
| i+10 | | | |
| i+11 | [8] Output torque $\times 10^{*11}$ | | |
| i+12 | [9] Output voltage $\times 10$ | | |

[1] Output frequency^{*7}: (value $\times 100$)

^{*7} As for SJH300 / HFC-VAH3 Series, the value of output frequency $\times 10$ is displayed.

[2] Output current : The value of output current $\times 10$ of an Inverter is displayed.

[3] The rotation direction:

0 : Stop, 1 : FWD, 2 REV

[4] PID feedback monitor^{*8}: (value $\times 100$)

^{*8} Not supported by SJH300 / HFC-VAH3 Series. ("H0" is displayed)

[5] Intelligent input monitor:

| Terminal | Monitor Item | Set value |
|-----------------|---------------|-----------|
| [FW] | Forward input | H0100 |
| 1 | Input 1 | H0001 |
| 2 | Input 2 | H0002 |
| 3 | Input 3 | H0004 |
| 4 | Input 4 | H0008 |
| 5 | Input 5 | H0010 |
| 6 ^{*9} | Input 6 | H0020 |
| 7 ^{*9} | Input 7 | H0040 |
| 8 ^{*9} | Input 8 | H0080 |

^{*9} Not supported by L300P Series.

[6] Intelligent output monitor

| Terminal | Monitor Item | Set value |
|-------------------|--------------|-----------|
| AL | Alarm relay | H0020 |
| 11 | Output 1 | H0001 |
| 12 | Output 2 | H0002 |
| 13 ^{*10} | Output 3 | H0004 |
| 14 ^{*10} | Output 4 | H0008 |
| 15 ^{*10} | Output 5 | H0010 |

^{*10} Not supported by L300P Series..


Function

- [7] Frequency conversion monitor: (value × 100)
[8] Output torque^{*11}:
 *11 Not supported by SJH300 / HFC-VAH3 Series. ("H0" is displayed)
[9] Output voltage monitor: (value × 10)
[10] Electric power monitor^{*12}: (value × 10)
 *12 Not supported by HFC-VAH3 Series. ("H0" is displayed)
[11] Reserve: (always 0)
[12] RUN time monitor:
[13] Power ON time monitor:

(V) Command 04: Read inverter status
(a) Command area

| | | |
|---|------------------|-----|
| h | 11] Node address | H04 |
|---|------------------|-----|

(b) Response area
If operation does not work properly, error code is given as shown in "14] Error code".



Status A code

| code | Status |
|------|--------------------|
| H00 | Initial state |
| H01 | - |
| H02 | On Stopping |
| H03 | On Running |
| H04 | On Free-run stop |
| H05 | On Jog |
| H06 | On Dynamic braking |
| H07 | On Retry |
| H08 | On TRIP |
| H09 | On Under-voltage |


Status B code

| code | Status |
|------|-------------|
| | |
| H01 | On Running |
| H02 | On Tripping |

Status C code

| code | Status |
|------|----------------------|
| | - |
| H01 | Stop |
| H02 | Deceleration speed |
| H03 | Constant speed |
| H04 | Acceleration speed |
| H05 | Forward |
| H06 | Reverse |
| H07 | Reverse from forward |
| H08 | Forward from reverse |
| H09 | Forward start |
| H10 | Reverse start |


Example) Status A: On Running + Status B: On Running + Status C: Forward
(03) (01) (05)



(Vi) Command 05: Read trip history

| | | |
|---|------------------|-----|
| h | 11] Node address | H05 |
|---|------------------|-----|

No response normally. If operation does not work properly, error code is given as shown in “14] Error code”.




[1] Total count : The total accumulated number of trips

[2] Trip factor^{*14}:

*14 Please refer to inverter manual for further information.

[3] Inverter Status:



Status A: Status at inverter trip.

Status B: Trip factor detected by gate array.

Status C: Detailed status at inverter trip.

Function

Status A code

| Code | Condition |
|------|------------------|
| H00 | Initial status |
| H01 | - |
| H02 | On Stopping |
| H03 | On Running |
| H04 | On Free-Run Stop |
| H05 | On Jog |
| H06 | On Dynamic |
| H07 | On retry |
| H08 | On Trip |
| H09 | On Under-Voltage |

Status B code

| Bit | Condition |
|------|------------------------|
| bit0 | Option earth fault |
| bit1 | IGBT error U phase |
| bit2 | Undervoltage |
| bit3 | Overvoltage protection |
| bit4 | Abnormal temperature |
| bit5 | IGBT error W phase |
| bit6 | IGBT error Vphase |
| bit7 | Gate array error |

Status C code


| Code | Condition |
|------|------------------------|
| | On Reset |
| H01 | On Stopping |
| H02 | On Decelerating |
| H03 | On Constant speed |
| H04 | On Accelerating |
| H05 | On Running 0Hz |
| H06 | On Starting |
| H07 | On Dynamic Braking |
| H08 | On overload protection |

Example) Inverter trip by abnormal temperature and Overvoltage protection during acceleration of Running (Trip history 1)

Status A : On Running (03)

Status B : Abnormal temperature (bit4) ,and Overvoltage protection (bit3)

Status C : On Accelerating (04)



*15 "H00" is displayed on a Reserve.

*16 Trip factor (status B) is given as 8 bits format data. "1" is set in corresponding bit.

[4] Output frequency: (value × 10)

[5] Accumulate Run time :


[6] Output current: (value × 10)

[7] Output DC voltage: (value × 10)

[8] Power ON time:

(vii) Command 06: Read a single parameter value

(a) Command area




Example) "PID proportional gain": A072

Input parameter h+1 : H2072

Function

(b) Response area

When FUN 190 command does an unusual end, Error code is displayed on “14] Error code”.




15] Data:

Example 1) Parameter of the 1st acceleration time (F002)

and a response is 30.00s

I+1 : 3000 = 30 × 100 [3000 (DEC) = BB8 (HEX)] *17




*17 10 or 100 times value is given depending on each command. Refer to inverter manual for further information..

Please refer to inverter manual for further information.

Example 2) When the parameter of the 02 start (A111) is read by command

and a response is -200%


I+1 : -200 × 100 = -20000 [-20000 (DEC) = FFFB1E0 (HEX)] *17,*18



*18 The data of the parameter of A111~ A114 is given as two's complement.


(viii) Command 07: Write a single parameter value

(a) Command area



Example 1.) "Acceleration (F002)" → h+1 : H1002


30.00 sec. → H+2 : 3000 (30×100) *19 [3000 (DEC) = BB8 (HEX)]



*19 Set 10 or 100 times value depending on each command. Refer to inverter manual for further information

Function

Example 2.) 02-L input active range start frequency (A111) → h+1 : H2111
 -200 % → -20000 (-200×100) (Two's complement) ^{*20} → H+2 : HFFFFB1E0
 [-20000 (DEC) = FFFFB1E0 (HEX)] ^{*20}



^{*20} Negative value is given by two's complement

(b) Response area

No response normally. If operation does not work properly, error code is given as shown in “14] Error code”.

(ix) Command 08: Set inverter parameters to default values

(a) Command area

| | | |
|---|------------------|-----|
| h | 11] Node address | H08 |
|---|------------------|-----|

(b) Response area

No response normally. If operation does not work properly, error code is given as shown in “14] Error code”.

(X) Command 09: Verifies that the requested setting can be written to EEPROM

(a) Command area

| | | |
|---|------------------|-----|
| h | 11] Node address | H09 |
|---|------------------|-----|

(b) Response area

No response normally. If operation does not work properly, error code is given as shown in “14] Error code”.

| | |
|-----|----------------|
| i | 14] Error code |
| i+1 | 15] Data |

15] Data: The result checked by Command 09 is displayed.

Check result code

| Code | Condition |
|------|--------------------|
| H00 | Save is impossible |
| H01 | Save is possible |

(Xi) Command 0A: Writes a parameter value to EEPROM

(a) Command area

| | | |
|---|------------------|-----|
| h | 11] Node address | H0A |
|---|------------------|-----|

(b) Response area

No response normally. If operation does not work properly, error code is given as shown in “14] Error code”.

(Xii) Command 0B: Requests the recalculation of internal constant

(a) Command area

| | | |
|---|------------------|-----|
| h | 11] Node address | H0B |
|---|------------------|-----|

(b) Response area

No response normally. If operation does not work properly, error code is given as shown in “14] Error code”.

Cautionary notes


- FUN190 cannot carry out multiplex execution. When multiplex execution is carried out, FUN190 is not performed normally.
- Supported inverters are Hitachi SJ300/L300P/SJH300/HFC-VAN3 series.
- Refer to the inverter manuals for further information.
- Be sure to configure the RS-485 communication port of inverter side.
- Configure each parameter within the I/O range, otherwise this command does not work. In this case, error code 52 is stored in WRF000, and DER bit is set.

Occupied words for each command

| Command | Command data | Response data |
|---------|--------------|---------------|
| 00 | 2 words | 1 words |
| 01 | 3 words | 1 words |
| 02 | 5 words | 1 words |
| 03 | 1 word | 19 words |
| 04 | 1 word | 3 words |
| 05 | 1 word | 68 words |
| 06 | 2 words | 3 words |
| 07 | 4 words | 1 words |
| 08 | 1 word | 1 words |
| 09 | 1 word | 2 words |
| 0A | 1 word | 1 words |
| 0B | 1 word | 1 words |

- When the parameter set as s-parameter is unusual, error code 52 is stored in WRF000, and DER bit is set.
- When the PLC communication port is not set as RS-485, error code 52 is stored in WRF000, and DER bit is set.

Program example



(00001)
ADRIO(WM0 ,R0) ← Control bit area specification (R0~)
ADRIO(WM1 ,WR100) ← Instruction input area specification (WR100~)
ADRIO(WM2 ,WR200) ← Response storing area specification (WR200~)
WM3= H0000 ← Timeout time (Timeout is not checked)
WM4 = H0003 ← Communication access speed (19200bps)
WM5 = H0002 ← Transmission format
 (7bit even parity 1 stop)
WR100 = H0200 ← Node address / Forward command
 (No.2 / Forward,Reverse,Stop command)
WR101 = H0001 ← Command Code (Forward command)

(00002)
FUN190(WM0) ← Start Inverter control command

(00003)
Start sending data

FUN 190 (s)

Program description

- When the switch 1 is ON, inverter No.2 starts operation in forward direction.

| Item number | Fun commands-64 | Name | | | | Extended X/Y area read/write command † | | | | | | | | | | | |
|--|--------------------------|-----------------|------|---------|-----------------------------------|--|------------------------|------------|-------------------------|-------------|-----------------|------------|----------|------------------|--|--|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | |
| FUN 200 (s) * (XYR/W (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU3**A EH-CPU3** | | Other than left | | | | | | |
| | | DER | ERR | SD | V | C | | | | | | | | | | | |
| | | ↕ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | |
| Command format | | Number of steps | | | | | 65 | 337 | 57 | 217 | | | | | | | |
| FUN 200 (s) * (XYR/W (s)) | | Condition | | | Steps | | | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| s | Header of parameter area | | | | | | | ○ | | | | | | s uses up to s+7 | | | |
| Function | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">• This command reads and writes data between the CPU and a module using the extended X and Y areas.• The maximum read and write data sizes are determined by the number of module's I/O assignment points. For details on using this command, refer to the applicable module manual.• By specifying the control type, the read/write method by performing or not performing handshaking with the module can be selected. However, in order to use the read/write method by performing handshaking, the module side must support handshaking. For more details, refer to the applicable module manual.• s sets the head I/O number of the parameter area that sets various data read/write parameters. <p>* The values displayed inside parenthesis () show the display when LADDER EDITOR is used.</p> | | | | | | | | | | | | | | | | | |
| <div><div><div>Extended X area</div><div><div></div><div></div><div></div><div></div><div></div><div></div></div></div><div><div>Extended Y area</div><div><div></div><div></div><div></div><div></div><div></div><div></div></div></div><div><div>WR, WL, and WM areas</div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div></div><div><div>Read</div><div>Read</div><div>Write</div></div></div> | | | | | | | | | | | | | | | | | |

†: Supported by EH-CPU 308(A)/316(A)/448(A)/516/548 only.

Description of S parameter area

| | |
|-----|---|
| s+0 | 1] Error code |
| s+1 | 2] System area |
| s+2 | (not available to user) |
| s+3 | 3] Control type |
| s+4 | 4] Header of target area |
| s+5 | 5] Read/write control bit I/O No. |
| s+6 | 6] Transfer source (destination) header I/O No. |
| s+7 | 7] Size |

[1] Error code:

The result of FUN 200 command execution is set.

Normal end → = 0

Abnormal end → ≠ 0

[2] System area:

This is used by the system processes of the FUN 200 command when the FUN 200 command is executed. This area cannot be used by the user.

[3] Control type

Specifies the control type.

H0001: Read request from the X area (with handshaking)

H0002: Read request from the X area (without handshaking)

H0003: Write request to the Y area (with handshaking)

H0004: Forced write request to the Y area (without handshaking)

H0005: Forced read request from the Y area (without handshaking)

[4] Header of target area:

| | | | |
|----------|----------|---------------|----|
| b15 | b11 | b7 | b0 |
| Unit No. | Slot No. | Word location | |

Sets the unit number (0 to 7)

Sets the slot number (0 to 7)

Sets the word location (from 0) *1

[5] Read/write control bit I/O number:

Sets the actual addresses of R, L, and M in the read/write control bit I/O number using the ADRIO command.

[6] Transfer source (destination) header I/O number:

Sets the actual addresses of WR, WL, and WM in the transfer source (destination) header I/O number using the ADRIO command.

[7] Size:

Sets the size to be read or written (from 1) in word units. *1

Description of read/write control bit table

| | |
|----|----------------------|
| +0 | 1] Execute flag |
| +1 | 2] Normal end flag |
| +2 | 3] Abnormal end flag |

* Description of borders

| |
|----------------------------|
| User setting area |
| User write prohibited area |

1] Execution flag:

Set to "1" using a user program when performing read or write operation using the FUN 200 command. When the read or write operation is complete, the FUN 200 command resets this to "0".

2] Normal end flag:

Set to "1" when read or write operation by the FUN 200 command is normally completed. When read or write operation is started, the FUN 200 command resets this to "0".

3] Abnormal end flag:

Set to "1" when read or write operation by the FUN 200 command is abnormally completed. When read or write operation is started, the FUN 200 command resets this to "0".

*1 The ranges in which the word location and size can be specified will differ depending on assignment. The equation for calculating the ranges of the word location and size is as follows.

$$\text{Size} = 3Fh - \text{Number of input points} - \text{Number of output points}$$

(Example) If assignment is 4W/4W,

$$3Fh - 4 - 4 = 37h$$

The word location range is 00h through 36h.

The size range is 0001h through 0037h.

Cautionary notes


- When an error is generated, an error code is set, DER will be equal to “1,” and no processing will be performed.
- If the specified size is 0, the process will end normally with performing anything.
- Execute using only normal scan without entering any startup conditions.

For more information on the error codes that can be set, see the Error Code Details.

Program example

In this program example, a program performs information settings on the Ethernet module (EH-ETH) by writing to the Y area. After the information is set normally, the program reads the information settings of the Ethernet module (EH-ETH) by reading the X area.

(1) EH-ETH installation



The EH-ETH is installed in the “0” slot of the basic base.
Therefore, the I/O assignment of the EH-ETH will be WX0000, WY0001.

(2) Internal output assignments

A sample program will be created using the assignments shown below. Change the I/O number, etc. according to the application in an actual usage.

| I/O | NO. | Usage |
|-----|--------------------|--|
| WR | 0000 to 0007 | FUN 200 command (Y area writing) Parameter area (S to S + 7) |
| M | 0000 to 0002 | FUN 200 command (Y area writing) Control bit table |
| WM | 100 to 117 | Transfer source data area (24 words) |
| WR | 0010 to 0017 | FUN 200 command (X area reading) Parameter area (S to S + 7) |
| M | 0010 to 0012 | FUN 200 command (X area reading) Control bit table |
| WM | 120 to 137 | Transfer source data area (24 words) |
| R | 100 101 | Execution request (FUN 200 execution Y area writing) Execution request (FUN 200 execution X area reading) |

Program example


(3) Data passed from the CPU to the EH-ETH

Using the following program example, the data to be set in the transfer source data area that will be passed from the CPU to the EH-ETH is described.

For more details, see the EH-ETH manual.

| I/O NO. | Data | Description | Remark |
|---------|-------|---|------------------|
| WM100 | HC000 | Higher IP address | 192.000 |
| WM101 | H0000 | Lower IP address | 000.000 |
| WM102 | HFFFF | Higher subnet mask address | 255.255 |
| WM103 | HFF00 | Lower subnet mask address | 255.000 |
| WM104 | HC000 | Higher IP address for sending and receiving tests | 192.000 |
| WM105 | H00FF | Lower IP address for sending and receiving tests | 000.255 |
| WM106 | H0FA0 | Port number for sending and receiving tests | 4000 |
| WM107 | H0000 | Higher gateway address 1 | 000.000 |
| WM108 | H0000 | Lower gateway address 1 | 000.000 |
| WM109 | H0000 | Higher gateway address 2 | 000.000 |
| WM10A | H0000 | Lower gateway address 2 | 000.000 |
| WM10B | H0000 | Higher gateway address 3 | 000.000 |
| WM10C | H0000 | Lower gateway address 3 | 000.000 |
| WM10D | H0000 | Higher gateway address 4 | 000.000 |
| WM10E | H0000 | Lower gateway address 4 | 000.000 |
| WM10F | H0BBC | Task code 1 port number | 3004 |
| WM110 | H0001 | Task code 1 communication protocol | TCP/IP |
| WM111 | H0BBD | Task code 2 port number | 3005 |
| WM112 | H0001 | Task code 2 communication protocol | TCP/IP |
| WM113 | H0BBE | Task code 3 port number | 3006 |
| WM114 | H0001 | Task code 3 communication protocol | TCP/IP |
| WM115 | H0BBF | Task code 4 port number | 3007 |
| WM116 | H0001 | Task code 4 communication protocol | TCP/IP |
| WM117 | H0000 | Task code timeout | No timeout check |

Program example



Perform parameter area initialization settings with 1 scan execution on.
Write request to the Y area
Set M0000 in the read control bit I/O number from unit number 0, slot number 0, word location word 0.
Set WM100 in the transfer source header I/O number.
Set the read size to 24 words.

Read request from the X area
Set M0010 in the read control bit I/O number from unit number 0, slot number 0, word location word 0.
Set WM120 in the transfer source header I/O number.
Set the read size to 24 words.

Start reading when the execution flag M0000 turns on
Contact point R100 turns off when the normal end flag M0001 turns on.
Contact point R101 turns on when the normal end flag M0001 turns on.
Contact point R100 turns off when the abnormal end flag M0002 turns on.

After writing to the Y area is completed normally, start reading from the X area.

Start reading when the execution flag M0010 turns on.

Contact point R101 turns on when the normal end flag M0011 turns on.

Contact point R101 turns off when the abnormal end flag M0012 turns on.

FUN 200 (s)

| Item number | Fun commands-65 | Name | | | | Status control read/write command † | | | | | | | | | |
|---|--------------------------|-----------------|------|---------|-----------------------------------|-------------------------------------|------------------------|------------|-------------------------|-------------|-----------------|------------|----------|------------------|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| FUN 201 (s) * (SCR/W (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU3**A EH-CPU3** | | Other than left | | | | |
| | | DER | ERR | SD | V | C | | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | Number of steps | | | | | 66 | 338 | 58 | 218 | | | | | |
| FUN 201 (s) * (SCR/W (s)) | | Condition | | | Steps | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| s | Header of parameter area | | | | | | | ○ | | | | | | s uses up to s+7 | |
| Function | | | | | | | | | | | | | | | |
| <div><div><div><div><div></div><div></div><div></div><div></div><div></div><div></div></div><div>Control area</div></div><div><div><div></div><div></div><div></div><div></div><div></div><div></div></div><div>Status area</div></div></div><div><div>Read</div><div>Read</div><div>Write</div></div><div><div>WR, WL, and WM areas</div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div></div></div> | | | | | | | | | | | | | | | |
| <div><div><div><div><div></div><div></div><div></div><div></div><div></div><div></div></div><div>Control area</div></div><div><div><div></div><div></div><div></div><div></div><div></div><div></div></div><div>Status area</div></div></div><div><div>Read</div><div>Read</div><div>Write</div></div><div><div>WR, WL, and WM areas</div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div></div></div> | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU 308(A)/316(A)/448(A)516/548 only.

Description of S parameter area

| | |
|-----|---|
| s+0 | 1] Error code |
| s+1 | 2] System area |
| s+2 | (not available to user) |
| s+3 | 3] Control type |
| s+4 | 4] Header of target area |
| s+5 | 5] Read/write control bit I/O No. |
| s+6 | 6] Transfer source (destination) header I/O No. |
| s+7 | 7] Size |

[1] Error code:

The result of FUN 201 command execution is set.

Normal end → = 0

Abnormal end → ≠ 0

[2] System area:

This is used by the system processes of the FUN 201 command when the FUN 201 command is executed. This area cannot be used by the user.

[3] Control type

Specifies the control type.

H0001: Read request from the status area (with handshaking)

H0002: Read request from the status area (without handshaking)

H0003: Write request to the control area (with handshaking)

H0004: Forced write request to the control area (without handshaking)

H0005: Forced read request from the control area (without handshaking)

HA55A: Software reset

[4] Header of target area:

| | | | |
|----------|----------|---------------|----|
| b15 | b11 | b7 | b0 |
| Unit No. | Slot No. | Word location | |

Sets the unit number (0 to 7)

Sets the slot number (0 to 7)

Sets the word location (from 0) *1

[5] Read/write control bit I/O number:

Sets the actual addresses of R, L, and M in the read/write control bit I/O number using the ADRIO command.

[6] Transfer source (destination) header I/O number:

Sets the actual addresses of WR, WL, and WM in the transfer source (destination) header I/O number using the ADRIO command.

[7] Size:

Sets the size to be read or written (from 1) in word units. *1

Description of read/write control bit table

| | |
|----|----------------------|
| +0 | 1] Execute flag |
| +1 | 2] Normal end flag |
| +2 | 3] Abnormal end flag |

* Description of borders

| |
|----------------------------|
| User setting area |
| User write prohibited area |

1] Execution flag:

Set to "1" using a user program when performing read or write operation using the FUN 201 command. When the read or write operation is complete, the FUN 201 command resets this to "0".

2] Normal end flag:

Set to "1" when read or write operation by the FUN 201 command is normally completed. When read or write operation is started, the FUN 201 command resets this to "0".

3] Abnormal end flag:

Set to "1" when read or write operation by the FUN 201 command is abnormally completed. When read or write operation is started, the FUN 201 command resets this to "0".

*1

- When performing read or write operation by controlling handshaking (when the control type is H001 or H003)
The ranges that can be specified for the word location and size are different for each module. Refer to the applicable module manual.
- When performing forced read or forced write operation
The word location range will be 00h to 3Dh.
The size range will be 0001h to 003Eh.

Cautionary notes


- When an error is generated, an error code is set, DER will be equal to “1,” and no processing will be performed.
- If the specified size is 0, the process will end normally with performing anything.
- Execute using only normal scan without entering any startup conditions.

For more information on the error codes that can be set, see the Error Code Details.

Program example

The following is an example of a program that sets the transmission information of the Ethernet module (EH-ETH) by writing to the control area. Another example of a program that reads the communication status and error information of the Ethernet module (EH-ETH) by reading the status area is also shown.

(1) EH-ETH installation



The EH-ETH is installed in the “0” slot of the basic base.
Therefore, the I/O assignment of the EH-ETH will be
WX0000, WY0001.

(2) Internal output assignments


A sample program will be created using the assignments shown below. Change the I/O number, etc. according to the application in an actual usage.

| I/O | NO. | Usage |
|-----|--------------------|--|
| WR | 0000 to 0007 | FUN 201 command (control area writing) Parameter area (S to S + 7) |
| M | 0000 to 0002 | FUN 201 command (control area writing) Control bit table |
| WM | 100 to 108 | Transfer source data area (9 words) |
| WR | 0010 to 0017 | FUN 201 command (status area reading) Parameter area (S to S + 7) |
| M | 0010 to 0012 | FUN 201 command (status area reading) Control bit table |
| WM | 120 to 12D | Transfer source data area (13 words) |
| R | 100 101 | Execution request (FUN 201 execution control area writing) Execution request (FUN 201 execution status area reading) |

Program example

(3) Data passed from the CPU to the EH-ETH
Using the following program example, the data to be set in the transfer source data area that will be passed from the CPU to the EH-ETH is described.
For more details, see the EH-ETH manual.

| I/O NO. | Data | Description | Remark |
|---------|-------|--------------------------------|--------|
| WM100 | H000F | Module control register | |
| WM101 | H0000 | Connection open/close request | |
| WM102 | H003F | Dedicated transmission control | |
| WM103 | H003F | Automatic transmission control | |
| WM104 | H003F | Dedicated reception control | |
| WM105 | H003F | Automatic reception control | |
| WM106 | H3F3F | Error clear 1 control | |
| WM107 | H3F3F | Error clear 2 control | |
| WM108 | H3F3F | Error clear 3 control | |



Perform parameter area initialization settings with 1 scan execution on.
Write request to the control area
Set M0000 in the read control bit I/O number from unit number 0, slot number 0, word location word 0.
Set WM100 in the transfer source header I/O number.
Set the read size to 9 words.

Read request from the status area
Set M0010 in the read control bit I/O number from unit number 0, slot number 0, word location word 0.
Set WM120 in the transfer source header I/O number.
Set the read size to 13 words.

Start reading when the execution flag M0000 turns on
Contact point R100 turns off when the normal end flag M0001 turns on.
Contact point R101 turns on when the normal end flag M0001 turns on.
Contact point R100 turns off when the abnormal end flag M0002 turns on.

After writing to the control area is completed normally, start reading from the status area.

Start reading when the execution flag M0010 turns on.

Contact point R101 turns on when the normal end flag M0011 turns on.

Contact point R101 turns off when the abnormal end flag M0012 turns on.

FUN 201 (S)

Error code details

FUN200/FUN201 command error code list

| Return code | Name | Description | Corrective action |
|-------------|---|---|--|
| 0000 | Normal end | Read/write operation ended normally. | |
| 0002 | S parameter area range error | Argument s has exceeded the maximum word I/O number. | Change the header I/O number of argument s. |
| 0004 | Control bit table range error | The control bit table has exceeded the maximum bit I/O number. | Change the bit header I/O number of the control bit table. |
| 0006 | Control type setting error | The control type setting is incorrect. | Set the correct value for the control type. |
| 0008 | Target area header setting error | The header setting of the target area is incorrect. | Set the unit number within a range of 0 to 7, set the slot number within a range of 0 to 7, and set the word location within the proper range. |
| 000A | Target area range error*1 | The target area header word location + size – 1 has exceeded the last word location. | Set the target area within the correct range. |
| 000C | Transfer source (destination) header I/O number range error | The transfer source (destination) header I/O number has exceeded the maximum word I/O number. | Change the transfer source (destination) header word I/O number. |
| 000D | Transfer source (destination) area range error*1 | The transfer source (destination) header I/O + size – 1 has exceeded the maximum word I/O number. | Change the transfer source (destination) area within the correct range. |
| 000E | Overlap error | The area for argument s and the area specified by argument s overlap. | Perform settings so the area for argument s and the area specified by argument s do not overlap. |
| 0010 | No assignment | There is no assignment in the specified unit and slot. | Perform assignment. |
| 0020 | Installation error | A module that supports handshaking is not installed. | Change the control type to forced read operation or forced write operation. |
| 0022 | Non-existent read or write area | There is no area in which read or write operation can be performed while controlling handshaking. | Change the control type to forced read operation or forced write operation. |
| 0030 | Timeout*2 | No response from the module. | Check the attachment to the CPU basic base and restart. Or exchange the module. |
| 0040 | Conflict error | Read or write operation was simultaneously attempted to the same target area, or the module was reset while reading or writing. | Do not startup simultaneously or change the target area. |

*1 An error will be generated, but the read/write processing will be performed within the specified range.

*2 1] A timeout will be generated if a response is not received within 100 ms after handshake is controlled and read/write operation is started.

A timeout will be generated if a response is not received within 5 s after software reset is started.

2] Note that processing new is not received during timeout detection.

Please perform the next processing after checking an abnormal end flag and a normal end flag.

| Item number | Fun commands-66 | Name | | Data logging initialization setting [†] | | | | | | | | | | | |
|-------------------------------|-------------------------------|---|------|--|-----------------------------------|------|------------------------|----------------------|-------------------------|-------------|-----------------|------------|----------|--------|--|
| Ladder format | | Condition code | | | | | | Processing time (μs) | | | | | | Remark | |
| FUN 210 (s) * (LOGIT (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** EH-CPU5** | | EH-CPU3**A EH-CPU3** | | Other than left | | | | |
| | | DER | ERR | SD | V | C | | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | Number of steps | | | | | | 1,728 | 3,121 | 2906 | 5492 | 6,163 | 11,663 | | |
| FUN 210 (s) * (LOGIT (s)) | | Condition | | | Steps | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| s | Data logging management table | | | | | | | ○ | | | | | | | |
| Function | | | | | | | | | | | | | | | |
| | | <div><div><div><div></div><div>Initializes the data logging function (common area).</div></div><div><div></div><div>The initialization settings will be used to check and initialize the parameters for log data write and log data clear processes.</div></div><div><div></div><div>Always perform the initialization setting once during operation.</div></div></div><div><div>*</div><div>() indicates the display when the LADDER EDITOR is used.</div></div><div>For the details of the data logging management table, see “Management table details.”</div><div>For the error codes that are set, see “Error code details.”</div></div> | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | |
| | | <div><div><div><div></div><div>If an error is generated, an error code will be set to <u>the error code in the data logging management table</u>, and DER will be set to “1.” In this case, initialization setting will not be performed.</div></div><div><div></div><div>An error will be generated if initialization is performed again after the initialization setting has already been performed once (initialization of the data logging management table has been successfully completed).</div></div><div><div></div><div>An error will be generated if the argument S (data logging management table) exceeds the maximum value for the I/O number.</div></div><div><div></div><div>An error will be generated if there is an error in the verification process of items that have been specified for initialization in (S+3).</div></div></div></div> | | | | | | | | | | | | | |

[†]: Supported by EH-CPU 308(A)/316(A)/448(A)516/548 only.


Program example

The following shows a sample program that performs initial settings for data logging.
This program initializes the log write parameter table and log clear parameter bit table.

Assigning internal outputs

This sample program is created using the following assignments. In actual cases, change the I/O numbers and other items according to the application.

| I/O | No. | Usage | Remarks |
|-----|--------------|---|---------------------------------------|
| WR | 0100 to 0105 | FUN 210 command Data logging management table (s to s+5) | See the data logging management table |
| WR | 0400 to 0404 | Log information table | See the log information table |
| WM | 0100 to 0105 | Log write parameter table | See the log write parameter table |
| R | 0100 to 0103 | Log write control bit table | See the log write control bit table |
| WR | 0200 to 023F | Log data group 1 | This I/O content is logged |
| WR | 0300 to 033F | Log data group 2 | This I/O content is logged |
| R | 0200 to 0202 | Log clear parameter bit table | See the log clear parameter bit table |



Setting of actual address for log information table.
Initialization of log write parameter table and log clear
parameter bit table.
Setting of actual address for log write parameter table.
Setting of actual address for log clear parameter bit table.
Execution of initial setting for data logging.

Program example

1. This program performs the initial settings of the log information table, log write table and log clear parameter bit table when a single scan execution (R7E3) is on.

Management table
overview

See “Management table details” for detailed description.

(a) Logging management table (6 words)

| | |
|-------|---|
| s + 0 | 1) Error codes |
| s + 1 | 2) Initialization result |
| s + 2 | 3) Logging information table I/O number |
| s + 3 | 4) Initialization specification |
| s + 4 | 5) Log write parameter I/O number |
| s + 5 | 6) Log clear parameter I/O number |

(b) Logging information table (5 words)

| | |
|-----|--------------------------------|
| + 0 | Number of logs allowed (Lower) |
| + 1 | Number of logs allowed (Upper) |
| + 2 | Log size (words/log) |
| + 3 | Number of logs (Lower) |
| + 4 | Number of logs (Upper) |

Exists when initialization specification (S+3) for log write is enabled.

(c) Log write parameter table (2 + MAX (128 *2) words)

| | |
|---------------|----------------------------------|
| + 0 | Log write control bit I/O Number |
| + 1 | Number of log groups (n) MAX 128 |
| + 2 | Log groups 1 head I/O number |
| + 3 | Log groups 1 size |
| + 4 | Log groups 2 head I/O number |
| + 5 | Log groups 2 size |
| | — |
| | — |
| + (n + 2) + 0 | Log groups n head I/O number |
| + (n + 2) + 1 | Log groups n size |

(d) Log write control bit table (4 bits)

| | |
|-----|--------------------------|
| + 0 | EXECUTE flag |
| + 1 | RUN flag |
| + 2 | WRITE flag |
| + 3 | ABNORMAL COMPLETION flag |

MAX
(128 *2) words

Exists when initialization specification (S+3) for log clear is enabled.

(e) Log clear parameter bit table (3 bits)

| | |
|-----|--------------------------|
| + 0 | EXECUTE flag |
| + 1 | RUN flag |
| + 2 | ABNORMAL COMPLETION flag |

* Description of cells

| |
|----------------------------------|
| Area set by the user |
| Area where the user cannot write |

Management table details

(a) Explanation of data logging management table (1/2)

1] Data logging management table

| | | |
|-------|--------------------------------------|----|
| S | Error code | 2] |
| S + 1 | Initialization result | 3] |
| S + 2 | Logging information table I/O number | 4] |
| S + 3 | Initialization specifications | 5] |
| S + 4 | Log write parameter I/O number | 6] |
| S + 5 | Log clear parameter I/O number | 7] |

1] Data logging management table

1. Set in the FUN 210 (S) the word head I/O number used as the data logging management table.
2. The data logging management table consists of 2) through 7) and the size is 6 words. Make sure the maximum value for the word head I/O number is not exceeded.
If the maximum value is exceeded, H0002 will be set to the error code.

2] Error code (Read)

Sets the error code generated in the FUN 210 process.

3] Initialization result (Read/Common area)

Sets the initialization result, and whether or not execution is allowed.

| | | | |
|----|---|---|---|
| 15 | 8 | 7 | 0 |
| d | c | b | a |

- a. (b0 to b3) Whether or not re-initialization is allowed is set.
0 : Allowed
Other than 0 : Not allowed
- b. (b4 to b7) Whether or not execution of the FUN 211 (Log Data Write) is allowed is set.
0 : Not allowed
Other than 0 : Allowed
- c. (b8 to b11) Whether or not execution of the FUN 212 (Log Data Clear) is allowed is set.
0 : Not allowed
Other than 0 : Allowed
- d. (b12 to b15) Whether or not execution of the FUN 213 (Log Data Read) is allowed is set.
0 : Not allowed
Other than 0 : Allowed

* If recovery is not possible by use of commands, b0 to b3 will become other than 0 and b4 to b15 will become 0.

4] Logging information table I/O number (Write/Common area)

Sets the word head I/O number that stores the current logging information data.

See “(b) Explanation of logging information word table.”

5] Initialization specifications (Write)

Sets the parameter table used.

| | | | |
|----|---|---|---|
| 15 | 8 | 7 | 0 |
| d | c | b | a |

- a. (b0 to b3) Open (Unused)
- b. (b4 to b7) Initialization of log write parameter table
0 : Not initialized
Other than 0 : Initialized
- c. (b8 to b11) Initialization of log clear parameter table
Other than 0 : Initialized
- d. (b12 to b15) Open (Unused)

Management table
details

- (a) Explanation of data logging management table (2/2)
- 6] Log write parameter I/O number (Write)
Sets the word head I/O number used in the FUN 211 (Log Data Write) process.
When the write Function is not used, set H0000 as a dummy argument.
See “(c) Explanation of log write parameter word table.”
- 7] Log clear parameter I/O number (Write)
Sets the bit head I/O number of the parameter used in the FUN 212 (Log Data Clear) process.
When the clear function is not used, set H0000 as a dummy argument.
See “(e) Explanation of log clear parameter bit tables.”

Management table
details

(b) Explanation of log information word table

1] Log information word table

| | | | |
|-----|------------------------|-------------|----|
| + 0 | Number of logs allowed | : lower (R) | 2] |
| + 1 | Number of logs allowed | : upper (R) | |
| + 2 | Log size (words/log) | (R) | 3] |
| + 3 | Number of logs | : lower (R) | 4] |
| + 4 | Number of logs | : upper (R) | |

(R) Read word

1] Log information word table

1. Set the actual address (WR, WL, WM) of the word head I/O number that is used as the table into the data logging management table 4) using the ADRIO command.
2. The table consists of 2) through 4), and the size is 5 words. Make sure the maximum value for the word I/O number is not exceeded. If the maximum value is exceeded, H0003 will be set to the error code in the data logging management table.

2] Number of logs allowed

1. Indicates the number of logs currently allowed.
2. The value calculated by the formula shown below is set.

$$\text{Number of logs allowed} = 384 \text{ k } (393216) \text{ words} \div 3) \text{ Log size}$$
 (*) Round off below the decimal point.

3] Log size (words/log)

Indicates the number of words (Total number of words of respective log groups) per data groups written for a single log.

4] Number of logs

The number of logs that have been written at present is set. The number does not include the log whose data is currently being written. The count is increased by 1 when all data for that log has been written.

Management table details

(c) Explanation of log write parameter word table

1] Log write parameter word table

| | | |
|---------------|----------------------------------|----|
| + 0 | Log write control bit I/O number | 2) |
| + 1 | Log groups quantity (n) | 3) |
| + 2 | Log groups 1 head I/O number | 4) |
| + 3 | Log groups 1 size | |
| + 4 | Log groups 2 head I/O number | |
| + 5 | Log groups 2 size | |
| • | • | |
| • | • | |
| + (n × 2) + 0 | Log groups n head I/O number | |
| + (n × 2) + 1 | Log groups n size | |

1] Log write parameter word table

1. Set the actual address (WR, WL, WM) of the word head I/O number that is used as the table into the data log management table 6) using the ADRIO command.
2. The table consists of 2) through 4), and the size increases depending on the log groups quantity 3). Make sure the maximum value for the word head I/O number is not exceeded. If the maximum value is exceeded, H0005 will be set to the error code in the data logging management table.

2] Log write control bit I/O number

Set the bit I/O number used in FUN 211 control.
See (d), "Explanation of log write control bit table."

3] Log groups quantity

Set the number of logging groups in the range between 1 and 128.
If the specified value exceeds the allowable range, H0004 will be set to the error code in the data logging management table. If this error occurs, data logging will not be performed.

4] Log selection

Select the elements that comprise a single logging.

1. Head I/O number 1 to n ... Set each number using the ADRIO command by making sure the maximum value for the word head I/O number (WR, WL, WM, WX), from which the data will be logged, is not exceeded.
2. Size Set the range for the number of words logged from the word head I/O number.
3. If the maximum I/O number is exceeded, Hxx08 will be set to the error code in the data logging management table. If this error occurs, data logging will not be performed.
4. If the specified size is not between 1 and 128, H0007 will be set to the error code in the data logging management table. If this error occurs, data logging will not be performed.
5. The total size (number of words) of the selected data items must be in the range between 1 and 128 words. If the above range is exceeded, H0009 will be set to the error code in the data logging management table. If this error occurs, data logging will not be performed.

Management table
details

(d) Explanation of log write control bit table

1] Log write control bit table

| | | | |
|-----|--------------------------|-----|----|
| + 0 | EXECUTE flag | (W) | 2) |
| + 1 | RUN flag | (R) | 3) |
| + 2 | WRITE flag | (R) | 4) |
| + 3 | ABNORMAL COMPLETION flag | (R) | 5) |

(W) Set and read bit

(R) Read bit

1] Log write control bit table

1. Set the actual address (R, L, M) of the bit head I/O number that is used as the table into the log write parameter table 2) using the ADRIO command.
2. The table consists of 2) through 5), and the size is 4 bits. Make sure the maximum value for the bit I/O number is not exceeded. If the maximum value is exceeded, H0006 will be set to the error code in the data logging management table.

2] EXECUTE flag

1. When the EXECUTE flag rises (0 → 1), the system waits for the start of data logging.
2. If the execution ready state is achieved normally, the RUN flag 3) becomes 1. If there is an error, the RUN flag 3) becomes 0.
3. Logging is performed while the EXECUTE flag is 1.

3] RUN flag

1. When the FUN 211 detects the rise of the EXECUTE flag 2), it checks if execution is allowed and sets the result.
1 : Check result is normal. Data logging is started.
0 : Check result is abnormal. Data logging is not performed. The EXECUTE flag 2) becomes 0 and the cause of error is set to the FUN 211 (log data write) error code.
2. When the FUN 211 detects the fall of the EXECUTE flag 2) while the RUN flag is 1, and if the WRITE flag 4) is 1 (data is being written), the RUN flag will become 0 when the write is completed and the data logging will end.

4] WRITE flag

This flag indicates whether or not the data that has been stored temporarily via the FUN 211 is currently being written.

- 1 : Data write is being executed.
0 : Data write is yet to be executed.

5] ABNORMAL COMPLETION flag

This flag indicates whether or not the FUN 211 (data logging write) has been executed normally.

- 1 : Abnormal completion. The cause of error is set to the FUN 211 (log data write) error code.
0 : Normal completion. Indicates a state where no error has been generated.

Management table details

(e) Explanation of log clear parameter bit table

1] Log clear parameter bit table

| | | | |
|-----|--------------------------|-----|----|
| + 0 | EXECUTE flag | (W) | 2) |
| + 1 | RUN flag | (R) | 3) |
| + 2 | ABNORMAL COMPLETION flag | (R) | 4) |

(W) Set and read bit

(R) Read bit

1] Log clear parameter bit table

1. Set the actual address (R, L, M) of the bit head I/O number that is used as the table into the data log management table 7) using the ADRIO command.
2. The table consists of 2) through 4), and the size is 3 bits. Make sure the maximum value for the bit I/O number is not exceeded. If the maximum value is exceeded, H000A will be set to the error code in the data logging management table.

2] EXECUTE flag

1. When the EXECUTE flag rises (0 → 1), the system waits for the start of log data clear.
2. If the execution ready state is achieved normally, the RUN flag 3) becomes 1. If there is an error, the RUN flag 3) becomes 0.

3] RUN flag

1. When the FUN 212 detects the rise of the EXECUTE flag 2), it checks if execution is allowed and sets the result.
1 : Check result is normal. Log data clear is started.
0 : Check result is abnormal. Log data clear is not performed. The EXECUTE flag 2) becomes 0 and the cause of error is set to the FUN 212 (log data clear) error code.
2. When the clear is completed, both the RUN flag and EXECUTE flag 2) become 0. If the FUN 212 detects the fall of the EXECUTE flag 2) while the RUN flag is 1 (data is being cleared), the RUN flag will become 0 when the clear is completed and the log data clear will end.

4] ABNORMAL COMPLETION flag


This flag indicates whether or not the FUN 212 (log data clear) has been executed normally.

- 1 : Abnormal completion. The cause of error is set to the FUN 212 (log data clear) error code.
0 : Normal completion. Indicates a state where no error has been generated.

Error code details

(a) Explanation of log function error code

Each error code is expressed as a four-digit hexadecimal number.



The last 2 digits indicate the cause of error.

These digits indicate the log groups number.

If H00, it indicates that this error is not related to the log groups number.

If between H01 and H80, it indicates that there is an error regarding the log groups number.

In the error code list, the error codes in which the first 2 digits are indicated by ×× have a log groups number between H01 and H80 in place of ××. Numbers in brackets and ○ used in the table below indicate the corresponding numbers in “Management table details.”

| Error code | Check point/output destination | | | | Description and cause | Corrective action |
|------------|--------------------------------|---------|---------|------|--|---|
| | Initial | Write | Clear | Read | | |
| 0001 | ○ | × | × | × | The FUN 210 was executed again after its re-initialization had become disabled. | Modify the program so that the FUN 210 will not be executed after its initialization is completed. |
| 0002 | ○ | ○ *3 | ○ *3 | ○ | The argument S exceeds the maximum value for the word I/O number. | Change the head I/O number of the argument S. |
| 0003 | ○ | × | × | × | The log information table (a) 4) exceeds the maximum value for the word I/O number. | Change the head word I/O number (a) 4). |
| 0004 | ○ *1 | × | × | × | The log groups quantity (c) 3) exceeds the range between 1 and 128. | Set the log groups quantity (c) 3) in the range between 1 and 128. |
| 0005 | ○ *1 | × | × | × | The log write parameter table (a) 6) exceeds the maximum value for the word I/O number. | Change the head word I/O number (a) 6)/ log groups quantity (c) 3). |
| 0006 | ○ *1 | × | × | × | The log write control bit table (c) 2) exceeds the maximum value for the bit I/O number. | Change the head bit I/O number (c) 2). |
| ××07 | ○ *1 | × | × | × | Groups size (c) 4) number ×× exceeds the range between 1 and 128. | Set the groups size (c) 4) corresponding to ×× in the range between 1 and 128. |
| ××08 | ○ *1 | × | × | × | Logging groups (c) 4) number XX exceeds the maximum value for the word I/O number. | Change the head word I/O number (c) 4)/ groups size (c) 4) corresponding to XX. |
| 0009 | ○ *1 | × | × | × | The total size of the log groups exceeds the range between 1 and 128. | Set the total size of the log groups so it falls in the range between 1 and 128. |
| 000A | ○ *2 | × | × | × | The log clear parameter table (a) 7) exceeds the maximum value for the bit I/O number. | Change the head bit I/O number (a) 7). |
| 000B | × | ○ | ○ | ○ | A FUN was executed although its execution was not allowed (3) initialization result was “execution not allowed”). | Execute the FUN after confirming that the initialization result has become “execution allowed.” |
| 000C | × | × | × | ○ | The specified file address does not exist. | Set the file address between H0000 and HFFFF (lower) or H0000 and H0005 (upper). |
| 000D | × | × | × | ○ | The acquisition source area exceeds the maximum value for the word I/O number. | Change the head I/O number or size of the acquisition source. |
| 000E | ○ | × | × | ○ | The area of the argument S and the area specified by the argument S are overlapping. | Set the area of the argument S so it does not overlap with the area specified by the argument S. |
| 000F | × | × | × | ○ | There is no log data in the specified file address. | Calculate the value of file address again by referring to the log information table (a) 4). |
| 0010 | ○ | ○ | × | × | The size of the single log that was previously written to the memory board is different from the total size of the log groups. | Modify the program according to the previous log size. Or, execute the FUN 212 command to clear the data, then execute again. |
| 0011 | × | × | × | ○ | The read size exceeds 128. | Set the read size in the range between 1 and 128. |

Error code details

| Error code | Check point/output destination | | | | Description and cause | Corrective action |
|------------|--------------------------------|-------|-------|------|--|---|
| | Initial | Write | Clear | Read | | |
| 0012 | × | ○ | × | × | The log data area became full and no new log data could be added. | To recover this error, read the current data using the FUN 213 command, then clear the data using the FUN 212 command. When the data has been cleared, execute again. |
| 0020 | ○ | ○ | ○ | ○ | No memory board is installed, or the memory board does not support the logging function. | Set a memory board that supports the logging function. |
| 0021 | × | ○ | ○ | × | Operation was attempted in the write-prohibited mode. | Change the dip switch setting to the write-enable mode. |
| 0022 | ○ | ○ | ○ | × | Hardware error was detected in the memory board. | The memory board may be damaged. Replace the memory board. |
| 0023 | ○ | ○ | × | × | The previous logging has failed. | To recover this error, execute the FUN 212 command to clear the data, then execute again. |
| 0024 | × | ○ | ○ | ○ | Operation was attempted in a mode other than the data logging mode. | Change the dip switch setting to the data logging mode. |

* Initial: FUN 210 (initial setting)

Write: FUN 211 (write)

Clear: FUN 212 (clear)

Read: FUN 213 (read)

*1: When the initialization of log write is specified.

*2: When the initialization of log clear is specified.

*3: Cannot be output.

| Item number | Fun commands-67 | Name | | | | Log data write † | | | | | | | | | | | |
|--------------------------------|-----------------|--|------|---------|-----------------------------------|------------------|----------------------|------------|------------|-------------|-----------------|------------|----------|-------|--|--|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | |
| FUN 211 (s) * (LOGWRT (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU3**A | | Other than left | | | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | |
| Command format | | Number of steps | | | | | 645 | 1,188 | 527 | 959 | 973 | 1,535 | | | | | |
| FUN 211 (s) * (LOGWRT (s)) | | Condition | | | Steps | | | | 1,025 | 1,587 | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| s | Error code | | | | | | | ○ | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">This command is used to log (i.e., write to the memory board) the items specified by the FUN 210 (initial setting for data logging).* () indicates the display when the LADDER EDITOR is used.For the data logging management table, see “Management table details.”For the error codes to be set, see “Error code details.” | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| | | <ul style="list-style-type: none">If an error occurs, an error code is set and DER becomes equal to “1.” If this happens, the log data write will not be performed.If this command is executed when <u>the initialization result in the data logging management table</u> corresponding to the FUN 210 (initial setting for data logging) is “execution not allowed,” an error will occur.An error will occur if the argument S exceeds the maximum value for the I/O number.Do not set a startup condition for this command. Execute it during normal scans only.An error will occur if the dip switch setting on the memory board specifies write prohibited or any mode other than the data logging mode.If the memory board is currently in use for other processing, DER becomes equal to “0” and R7F7 becomes equal to “1.” If this happens, the processing will not be performed. | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU 308(A)/316(A)/448(A)/516/548 only.

Program example


The following shows a sample program that writes into the logging area a total of 128 words including WR200 through WR23F (64 words) and WR300 through WR33F (64 words) at intervals of 10 minutes after ON of X00000 (the start bit), together with date data (year/month, day/hour, minute/second) and sequence number.

Assigning internal outputs

The sample program is created using the following assignments. In actual cases, change the I/O numbers and other items according to the application.

| I/O | No. | Usage | Remarks |
|-----|--------------|---|---|
| WR | 0100 to 0105 | FUN 210 command Data logging management table (s to S+5) | See the data logging management table |
| WR | 0400 to 0404 | Log information table | See the log information table |
| WM | 100 to 105 | Log write parameter table | See the log write parameter table |
| R | 100 to 103 | Log write control bit table | See the log write control bit table |
| WR | 0200 to 023F | Log data groups 1 | This data is logged |
| WR | 0300 to 033F | Log data groups 2 | This data is logged |
| DR | 0204 | Sequence number | Increments by 1 after each logging |
| WR | 0405 | Save area for initialization result | Only the result of the FUN 211 is set |
| R | 0 | Save bit for initialization result | If ON, it indicates normal completion (execution allowed) |
| X | 0 | Log start bit | Logging interval (10 minutes) monitoring start bit |
| TD | 10 | 10 minute monitoring timer | Turns on when 10 minutes have elapsed |
| WR | 0000 | FUN 211 command error code (s) | The error code that has been generated as a result of the log data write is set |

Program example



Create a write parameter in WM0100 that logs 128 words (64 words from WR200 and 64 words from WR300) upon turning ON of single scan execution. Clears the sequence number to 0.

Specify initial setting so that the specified item (WM0100) is logged in WR0100 upon turning ON of single scan execution. Sets the initialization result in R000 after the initial setting.

1S 600 (Turns ON when 10 minutes have elapsed)
The progress value is updated while the start bit is ON but only when both the initial setting and logging have been completed normally.

Logging is started when TD10 is turned ON (when 10 minutes have elapsed).

Date data (year/month, day/hour, minute/second) and sequence number are appended to the head of log data (WR200 to WR205) when the logging execution flag is turned ON (R100 OFF → ON).

Executes the logging.

| Item number | Fun commands-68 | Name | | | | Log data clear [†] | | | | | | | | | | | |
|---|-----------------|-----------------|------|---------|-----------------------------------|-----------------------------|----------------------|------------|------------|-------------|-----------------|------------|----------|-------|--|--|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | | | |
| FUN 212 (s) * (LOGCLR (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU3**A | | Other than left | | | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | | | |
| Command format | | Number of steps | | | | | 163 | 164 | 79 | 79 | 391 | ← | | | | | |
| FUN 212 (s) * (LOGCLR (s)) | | Condition | | | Steps | | | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | | Constant | Other | | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | | | |
| s | Error code | | | | | | | ○ | | | | | | | | | |
| Function | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">This command is used to forcibly erase (clear) the logged data in the memory board. <p>* () indicates the display when the LADDER EDITOR is used.</p> <p>For the data logging management table, see “Management table details.”</p> <p>For the error codes to be set, see “Error code details.”</p> | | | | | | | | | | | | | | | | | |
| Cautionary notes | | | | | | | | | | | | | | | | | |
| <ul style="list-style-type: none">If an error occurs, an error code is set and DER becomes equal to “1”. If this happens, the log data clear will not be performed.If this command is executed when <u>the initialization result in the data logging management table</u> corresponding to the FUN 210 (initial setting for data logging) is “execution not allowed,” an error will occur.An error will occur if the argument S exceeds the maximum value for the I/O number.Do not set a startup condition for this command. Execute it during normal scans only.An error will occur if the dip switch setting on the memory board specifies write prohibited or any mode other than the data logging mode.If the memory board is currently in use for other processing, DER becomes equal to “0” and R7F7 becomes equal to “1.” If this happens, the processing will not be performed. | | | | | | | | | | | | | | | | | |

[†]: Supported by EH-CPU 308(A)/316(A)/448(A)516/548 only.


Program example

The following shows a sample program that performs initial setting for logging area clear and then clears the logging area.

Assigning internal outputs

The sample program is created using the following assignments. In actual cases, change the I/O numbers and other items according to the application.

| I/O | No. | Usage | Remarks |
|-----|--------------|---|---|
| WR | 0100 to 0105 | FUN 210 command Data logging management table (s to S+5) | See the data logging management table |
| WR | 0400 to 0404 | Log information table | See the log information table |
| R | 200 to 202 | Log clear parameter bit table | See the log clear parameter bit table |
| WR | 0405 | Save area for initialization result | Only the result of the FUN 212 is set |
| R | 000 | Save bit for initialization result | If ON, it indicates normal completion (execution allowed) |
| X | 00001 | Clear start bit | Logging clear start bit |
| WR | 0000 | FUN 212 command error code (s) | The error code that has been generated as a result of the log data clear is set |



Setting of actual address for log information table.
Initialization specification for log clear.
No specification for log write parameter table.
Setting of actual address for log clear parameter bit table.
Execution of initial setting for data logging.
Acquisition of initialization result.
Creation of initialization result bit.

Program description

The log area is cleared when X00001 (the clear start bit) is turned ON after the initial setting for log area clear has been executed upon turning ON of single scan execution (R7E3) and completed normally.

| Item number | Fun commands-69 | Name | | Log data read [†] | | | | | | | | | | | |
|--------------------------------|-----------------|-----------------|------|----------------------------|-----------------------------------|------|----------------------|------------|------------|-------------|-----------------|----------|--------|------------|--|
| Ladder format | | Condition code | | | | | Processing time (μs) | | | | | | Remark | | |
| FUN 213 (s) * (LOGRED (s)) | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU3**A | | Other than left | | | | |
| | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | | | |
| | | ↑ | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | | | |
| Command format | | Number of steps | | | | | 268 | 357 | 210 | 299 | 560 | 645 | | | |
| FUN 213 (s) * (LOGRED (s)) | | Condition | | | Steps | | | | | | | | | | |
| | | — | | | 3 | | | | | | | | | | |
| Usable I/O | | Bit | | | | Word | | | | Double word | | Constant | Other | | |
| | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM | |
| s | Argument | | | | | | | ○ | | | | | | | |
| Function | | | | | | | | | | | | | | | |

The logged data in the memory board is transferred to the specified I/O number area by the amount of data corresponding to the number of words being specified by the source log data address (word position from the head of log data).

s

Error code

s + 1

Source log data address (lower)

s + 2

Source log data address (upper)

s + 3

Destination head I/O number

s + 4

Size (1 to 128 words)

Log data (memory board)

Transfer area

The range of log data address is shown below.

Lower address : 0 to FFFFH

Upper address : 0 to 0005H

- The valid maximum log data address is calculated by the formula shown below :
(Log size in the log information table × Number of logs) – 1
- When the log data read is completed normally, DER becomes equal to “0.”
- If the specified size is 0, nothing will be done and the process will complete normally.
- For the S+3 parameter, set the actual address (WR, WL, WM) using the ADRIO command.

* () indicates the display when the LADDER EDITOR is used.

For the data logging management table, see “Management table details.”

For the error codes to be set, see “Error code details.”

[†]: Supported by EH-CPU 308(A)/316(A)/448(A)516/548 only.

Cautionary notes

- If an error occurs, an error code is set and DER becomes equal to “1”. If this happens, the log data read will not be performed.
- If this command is executed when the initialization result in the data logging management table corresponding to the FUN 210 (initial setting for data logging) is “execution not allowed,” an error will occur.
- An error will occur if the specified log data address does not exist.
- If the specified log data does not exist, an error will occur after the read.
- An error will occur if the area specified by the argument S or S+3 exceeds the maximum value for the I/O number.
- An error will occur if the area specified by the argument S and the one specified by S+3 overlap.
- An error will occur if the dip switch setting on the memory board specifies any mode other than the data logging mode.
- If the memory board is currently in use for other processing, DER becomes equal to “0” and R7F7 becomes equal to “1.” If this happens, the processing will not be performed.


Program example

The following shows a sample program that performs initial setting for log data read and then reads the logged data.

Assigning internal outputs

The sample program is created using the following assignments. In actual cases, change the I/O numbers and other items according to the application.

| I/O | No. | Usage | Remarks |
|-----|--------------|---|--|
| WR | 0100 to 0105 | FUN 210 command Data logging management table (s to S+5) | See the data logging management table |
| WR | 0400 to 0404 | Data logging information table | See the log information table |
| WR | 0405 | Save area for initialization result | Only the result of the FUN 213 is set |
| R | 000 | Save bit for initialization result | If ON, it indicates normal completion (execution allowed) |
| X | 00002 | Read start bit | Logging read start bit |
| WR | 0300 to 0304 | FUN 213 command parameter area (s to S+4) | |
| WM | 0100 to 0104 | Log data transfer area | The data that has been read is set |




Program description

Of the three logs of data that have been written, with each log consisting of 5 words, the content of the third log (in the memory board) is transferred to the destination (WM100) by the amount of data specified for a single log (5 words), with X00002 (the read start bit) ON.

Program example

The following shows an example of a program that starts logging at every 10 minutes after X0 turns ON, reads the first and last log data when X0 is OFF, and then clears the log data.



Setting of actual address for logging information table
Initializes the log write parameter table and log clear parameter table.
Log write parameter table not specified
Log clear parameter bit table not specified
Data logging initialization setting executed

Specify initial setting so that the specified item (WM0100) is logged/cleared in WR0100 upon turning ON of single scan execution.
Sets the initialization result in R000 after the initial setting.

1S 600 (Turns ON when 10 minutes have elapsed)
The progress value is updated while the start bit is ON but only when both the initial setting and logging have been completed normally.

Logging is started when the TD10 (10 min has elapsed) is ON.

Date data (year/month, day/hour, minute/second) and sequence number are appended to the head of log data (WR200 to WR205) when the logging execution flag is turned ON (R100 OFF → ON).

FUN 213 (S)



| Item number | | Fun commands-70 | | | | Name | | BOX comment | | | | | | | | | |
|---|---------------------------|-----------------|--|-----|---|-----------------|-----------------------------------|-------------|-------|------------|----------------------|-------------|------------|------------|-----------------|--------|--|
| Ladder format | | | | | | Condition code | | | | | Processing time (μs) | | | | | Remark | |
| FUN 254 (s) * (BOXC (s)) | | | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | |
| | | | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | |
| | | | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | |
| Command format | | | | | | Number of steps | | | | | 0.15 | ← | 14 | ← | 20 | ← | |
| FUN 254 (s) * (BOXC (s)) | | | | | | Condition | | | Steps | | | | | | | | |
| | | | | | | — | | | 3 | | | | 14 | | | | |
| Usable I/O | | | | Bit | | | | Word | | | | Double word | | | Constant | Other | |
| | | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | DR, DL, DM | | | |
| s | Argument (dummy constant) | | | | | | | | | ○ | | | | | | | |
| Function | | | | | | | | | | | | | | | | | |
| <div><div></div><div>This command does not perform any operations. It is used to print comments on the right side of the calculation box in conjunction with the LADDER EDITOR.</div><div>A comment can contain a maximum of 32 characters.</div><div>* () indicates the display when the LADDER EDITOR is used.</div></div> | | | | | | | | | | | | | | | | | |

| Item number | | Fun commands-71 | | Name | | Memo comment | | | | | | | | | |
|--|---------------------------|-----------------|-----|-----------------|---------|-----------------------------------|-------|------|----------------------|-------------|------------|-----|-----------------|--------|------------|
| Ladder format | | | | Condition code | | | | | Processing time (μs) | | | | | Remark | |
| FUN 255 (s) * (MEMC (s)) | | | | R7F4 | R7F3 | R7F2 | R7F1 | R7F0 | EH-CPU4** | | EH-CPU***A | | Other than left | | |
| | | | | DER | ERR | SD | V | C | EH-CPU5** | | EH-CPU3** | | | | |
| | | | | ● | ● | ● | ● | ● | Ave | Max | Ave | Max | Ave | Max | |
| Command format | | | | Number of steps | | | | | 0.15 | ← | 14.4 | ← | 20 | ← | |
| FUN 255 (s) * (MEMC (s)) | | | | Condition | | | Steps | | | | 14.4 | | | | |
| | | | | — | | | 3 | | | | | | | | |
| Usable I/O | | | Bit | | | | Word | | | Double word | | | Constant | Other | |
| | | | X | Y | R, L, M | TD, SS, WDT, MS, TMR, CU, RCU, CT | WX | WY | WR, WL, WM | TC | DX | DY | | | DR, DL, DM |
| s | Argument (dummy constant) | | | | | | | ○ | | | | | | | |
| Function | | | | | | | | | | | | | | | |
| <div><div><div><div><div></div><div>This command does not perform any operations. It is used to print comments on the right side of the calculation box in conjunction with the LADDER EDITOR.</div></div><div><div></div><div>A comment can contain a maximum of one screen (66 characters × 16 lines).</div></div></div><div><div></div><div>* () indicates the display when the LADDER EDITOR is used.</div></div></div></div> | | | | | | | | | | | | | | | |

Chapter 6 I/O Specifications

Classification of I/O that can be used with the EH-150 as well as the I/O points are indicated in Table 6.1.

Table 6.1 Usable I/O classification and points

| Function | | Symbol | Size | 10 / 16 | Name | CPU104 /104A | CPU208 /208A | CPU308 /308A | CPU316 /316A | CPU448 /448A | CPU516 | CPU548 | | | | | | | |
|-----------------|-----------------|--------|------|---------|---------------------------------|--|-----------------|--------------|--------------|--------------|--------------|-----------------|-----------------|--|--|--|--|-----------------------------|--|
| External I/O | External I/O | X | B | 10* | Bit external input | 512 points ** | 1,024 points ** | | | | | 2,112 points ** | 3,520 points ** | | | | | | |
| | | Y | B | 10* | Bit external output | | | | | | | | | | | | | | |
| | | WX | W | 16 | Word external input | 8 words | 16 words | | | | | | | | | | | | |
| | | WY | W | 16 | Word external output | | | | | | | | | | | | | | |
| | | DX | D | 16 | Double word ex. input | | | | | | | | | | | | | | |
| | | DY | D | 16 | Double word ex. output | | | | | | | | | | | | | | |
| | Remote I/O | X | B | 10* | Bit remote ex. input | - | | | | | 4,096 points | | | | | | | | |
| | | Y | B | 10* | Bit remote ex. output | | | | | | | | | | | | | | |
| | | WX | W | 16 | Word remote ex. input | - | | | | | 256 words | | | | | | | | |
| | | WY | W | 16 | Word remote ex. output | | | | | | | | | | | | | | |
| | | DX | D | 16 | Double word remote ex. in. | | | | | | | | | | | | | | |
| | | DY | D | 16 | Double word remote ex. out. | | | | | | | | | | | | | | |
| CPU link area | | L | B | 16 | Bit link area 1 | 16,384 points | | | | | | | | | | | | | |
| | | WL | W | 16 | Word link area 1 | | | | | | | | 1,024 words | | | | | | |
| | | DL | D | 16 | Double word link area 1 | 16,384 points | | | | | | | | | | | | | |
| | | L | B | 16 | Bit link area 2 | | | | | | | | 1,024 words | | | | | | |
| | | WL | W | 16 | Word link area 2 | | | | | | | | | | | | | | |
| | | DL | D | 16 | Double word link area 2 | | | | | | | | | | | | | | |
| Internal output | Bit | R | B | 16 | Bit internal output | 1,984 points | | | | | | | | | | | | | |
| | | R | B | 16 | Bit special internal output | | | | | | | | 64 points | | | | | | |
| | Word | WR | W | 16 | Word internal output | 4,096 words | 8,192 words | 17,408 words | 22,528 words | 50,176 words | 22,528 words | 50,176 words | | | | | | | |
| | | DR | D | 16 | D. word internal output | | | | | | | | | | | | | | |
| | | WR | W | 16 | Word special internal output | 512 words | | | | | | | | | | | | | |
| | | DR | D | 16 | D. word special internal output | | | | | | | | | | | | | | |
| | Shared bit/word | M | B | 16 | Bit internal output | 16,384 points | | | | | | | | | | | | | |
| | | WM | W | 16 | Word internal output | | | | | | | | 1,024 words | | | | | | |
| | | DM | D | 16 | D. word internal output | | | | | | | | | | | | | | |
| Others | Edge detection | DIF | B | 10 | Rise edge | 512 points | | | | | | | | | | | | | |
| | | DFN | B | 10 | Fall edge | | | | | | | | 512 points | | | | | | |
| | Master control | MCS | B | 10 | Master control set | 50 points | | | | | | | | | | | | | |
| | | MCR | B | 10 | Master control reset | | | | | | | | | | | | | | |
| | Timer, Counter | TD | B | 10 | On delay timer | Timer 256 points (0.01 s timer has only 0 to 63) * The same No. cannot be used to timer, counter. * TM is available with only EH-CPU448. Counter 512 points (The same area as timer is used up to 256 points) * The same No. cannot be used to timer, counter. | | | | | | | | | | | | | |
| | | SS | B | 10 | Single-shot timer | | | | | | | | | | | | | | |
| | | WDT | B | 10 | Watchdog timer | | | | | | | | | | | | | | |
| | | MS | B | 10 | Monostable timer | | | | | | | | | | | | | | |
| | | TMR | B | 10 | Accumulative timer | | | | | | | | | | | | | | |
| | | CU | B | 10 | Up counter | | | | | | | | | | | | | | |
| | | RCU | B | 10 | Ring counter | | | | | | | | | | | | | | |
| | | CTU | B | 10 | Up-down counter up input | | | | | | | | | | | | | | |
| | | CTD | B | 10 | Up-down counter down input | | | | | | | | | | | | | | |
| | | CT | B | 10 | Up-down counter down output | | | | | | | | | | | | | | |
| | | CL | B | 10 | Progress value clear | | | | | | | | | | | | | | |
| | | TC | W | 10 | Timer/counter accumulator | | | | | | | | | | | | | | |
| | | TM | B | 10 | On delay timer | | | | | | | | - | | | | | 2,048 points 0.01s fixed | |
| | | TV | W | 10 | Timer accumulator | | | | | | | | | | | | | | |

* The lower 2 digits of external bit X,Y are decimal (0-95) however, next digit (slot number) is hexa-decimal format (0-A).

See table 6.3 for further information.

** In case 64 points module used.

6.1 External I/O

When operation start is performed for the EH-150, the user program is executed (scanned) after the input refresh processing (receiving external input data) is performed. Operations are performed according to the contents of the user program, and the next input refresh processing and output refresh processing (operation results are reflected in the external output) are performed. After that, the next user program is executed (scanned). This series of operations is continually repeated until operation is stopped or until something occurs where operation can no longer continue. When operation is stopped or if something occurs so that operation can no longer continue, the CPU performs an output refresh with all output data as off data and stops operation, regardless of the execution status for the user program. Diagram outlining this series of operations is indicated in Figure 6.1 below.




Figure 6.1 Overview of user program execution and refresh processing

The user programs are executed in order, usually from the program at the beginning of the scan area to the end of the program or until the END command. After that, I/O data is refreshed prior to the execution of the next user program. As shown above, external I/O data is updated in group in the refresh processing after the user program is executed. If it is necessary to update (refresh) the I/O data while the user program is being executed, use the refresh command (FUN80 to FUN82).

When designing the system, take into account the above refresh operation from when the input data is received and operated on until output data is obtained.

The next section explains the assignment of external I/O. The external I/O numbers for the EH-150 system are expressed with the following rules.

Table 6.2 List of external I/O classification and data type


| Classification | I/O classification | Data type | Remarks |
|----------------|--------------------|---------------------------|---|
| X | External input | Bit type | Corresponds to the signal of each terminal block. |
| WX | | Word type (16-bit) | Data in the range 0 to 15 is batch processed. 16-bit synchronicity guaranteed. |
| DX | | Double word type (32-bit) | Two word data are batch expressed. 32-bit synchronicity is not guaranteed. |
| Y | External output | Bit type | Corresponds to the signal of each terminal block. |
| WY | | Word type (16-bit) | Data in the range 0 to 15 is batch processed. 16-bit synchronicity guaranteed. |
| DY | | Double word type (32-bit) | Two word data are batch expressed. 32-bit synchronicity is not guaranteed. |

Table 6.3 List of I/O number rules for external I/O

| Data type | Numbering rule | Example |
|-------------------------------|----------------|--|
| Bit type (basic/expansion) | | <p>Digital output EH-YT16 Y200-Y215</p> <p>Digital input EH-XD16 X0-X15</p> <p>Analog output EH-AY4V WY30-WY33</p> |
| Word type | | |
| Double word type | | <p>Digital output EH-YR16 Y1100-Y1115</p> <p>Analog output EH-AX8V WX120-WX127</p> |

The external I/O word type is a collection of 16 points, and double word type is a collection of 32 points of the relevant bit type.

(Example) Relationship between DX10, WX10 and X100 to X115 is,




6.2 Internal Output

Memory in the CPU module is available as the area for internal outputs. There are three areas: bit dedicated area (R), word dedicated area (WR), and bit/word common area (M/WM).


Table 6.4 List of I/O number rules for external I/O

| Data type | Numbering rule | Example |
|----------------------|--|---------------------------------|
| Bit dedicated type | <p>R </p> <p>Normal area H000 to H7BF Special area H7C0 to H7FF Both are expressed by hexadecimal</p> | R0 R105 R23C R7E7 |
| Word dedicated type | <p><Word></p> <p>WR </p> <p>Normal area H0000 to Special area HF000 to Both are expressed by hexadecimal</p> | WR0 WR11 WR1234 WRF004 |
| | <p><Double word></p> <p>DR </p> <p>Normal area H0000 to Special area HF000 to Both are expressed by hexadecimals. Expresses WR for 2 words in continuatio</p> | DR0 DR11 DR1234 DRF004 |
| Bit/word common type | <p><Bit></p> <p>M </p> <p>H0000 to</p> | M0 M11 M1234 |
| | <p><Word></p> <p>WM </p> <p>H000 to</p> <p>M120F M1200</p> <p>WM120</p> | WM0 WM11 WM123 |
| | <p><Double word></p> <p>DM </p> <p>H0000 to Expressed by hexadecimals. Expresses DM for 2 words in continuatio</p> | DM0 DM11 DM234 |

- Internal output R and WR, DR are completely separate areas. Bit-based operations cannot be performed in WR. (Example) Relationship between R100 and WR10, DR10



- Since internal output M, WM and DM share the same area, bit-based operations are allowed. (Example) Relationship between M100 and WM10, DM10



6.3 Virtual remote I/O for internal output

Virtual remote I/O area (WY1000-) is available by assigning "Remote2" at empty slot in basic base as follows.

- (1) Assign "Remote2" at empty slot in basic base.
- (2) Assign any of "Empty 16/32/64/128" at I/O configuration table of slave station. Then virtual area is kept according to this setting points.
- (3) Select "RUN" at operation mode of I/O assignment unmatched in your programming software.
- (4) Y, WY, DY can be used as WM according to the table below.

[例] 割付の例

| Basic unit | | Remote master 1 | |
|------------|----------------|-----------------|------------------------------|
| 0 | X16 | Empty 64 | Y10000-Y10063, WY1000-WY1004 |
| 1 | X16 | Empty 64 | Y10100-Y10163, WY1000-WY1014 |
| 2 | X16 | Empty 64 | Y10200-Y10263, WY1000-WY1024 |
| 3 | Y16 | Empty 64 | Y10300-Y10363, WY1000-WY1034 |
| 4 | Y16 | Empty 64 | Y10400-Y10463, WY1000-WY1044 |
| 5 | Y16 | Empty 64 | Y10500-Y10563, WY1000-WY1054 |
| 6 | X8W | Empty 64 | Y10600-Y10663, WY1000-WY1064 |
| 7 | Y8W | Empty 64 | Y10700-Y10763, WY1000-WY1074 |
| 8 | Remote2 | | |
| 9 | | | |
| A | | | |

*1: It is possible to assign "Empty 128" however, bit access is up to Y95 while word access is 8 words.

*2 :Use Y,WY,DY. Input X,WX, DX are not available.

Basic specification

| | |
|--------------------|--|
| I/O points | 1,024 points (64 words) / remote master 4 remote master / CPU (basic base) Total 4,095 points (256 words) |
| Remote I/O address | Remote master 1 : Y10000- / WY1000- Remote master 2 : Y20000- / WY2000- Remote master 3 : Y30000- / WY3000- Remote master 4 : Y40000- / WY4000- |
| Supported CPU | CPU516/548 |

MEMO

Chapter 7 Programming

7.1 Memory Capacity

The specifications for the user program in EH-150 are given in Table 7.1.

Table 7.1 User program specifications

| No. | Item | | CPU104(A) | CPU208(A) | CPU308(A) | CPU316(A) CPU516 | CPU448(A) CPU548 |
|-----|----------------------|-------------|---|-------------|-------------|---------------------|---------------------|
| 1 | Program capacity | | 3.5 k steps | 7.6 k steps | 7.6 k steps | 15.7 k steps | 48.5 k steps |
| 2 | Command size | | 32 bits/1 step | | | | |
| 3 | Memory specification | SRAM | Backup is possible by installing the battery | | | | |
| | | FLASH | Backup is possible by using FLASH memory | | | | |
| 4 | Programming language | | H-series ladder/command language | | | | |
| 5 | Program creation | | Created with H-series programming device | | | | |
| 6 | Program modification | During STOP | Can be done as desired by using the programming device. | | | | |
| | | During RUN | Can be done by using the modification during RUN operation (except control commands). Control commands can be changed with special operations. *1 (When a change is made during RUN, control operation stops while the program is being modified.). | | | | |
| 7 | Program protection | | The program cannot be changed unless with a WRITE occupancy. (Occupancy is automatically controlled by the programming device). | | | | |
| 8 | Password | | A password can be set using the programming device (the program cannot be displayed when setting the password. The program can be downloaded to the programming device). | | | | |
| 9 | Check function | | A sum check function for the program is always running. An address check with the I/O assignment table is done at the time RUN begins. | | | | |
| 10 | Program name | | The program name is set using the programming device and is stored together with the program. | | | | |

*1: Refer to the peripheral device manual for details.

Note:

- Comment data that has been created with peripheral device is not stored in the CPU.
- Save the user program to a separate floppy disk or other media, in case a mishap should occur.

7.2 Programming Method

The following methods are allowed for creating the user program.

Table 7.2 Programming methods

| No. | Programming device used | Operation concept | Remarks |
|-----|--|--|--|
| 1 | Personal computer software (LADDER EDITOR, etc.) | [For off-line / on-line operation] The I/O assignment table created, program to be created is input, and transferred to the EH-150 CPU. | <ul style="list-style-type: none"> • When each EH-150 module is loaded to the base unit, the I/O assignment information can be read. • Initialize the EH-150 CPU when using it for the first time after it is unpacked or when a battery error occurs. |
| 2 | Dedicated programming console (GPCL01H, etc.) | [For direct operation] As the programs are input one by one, the program input to the CPU is directly written to the CPU, each time. | |
| 3 | Portable graphic programmer (PGM-GPH) (Do not use an option box.) | As the programs are input one by one, the program input to the CPU is directly written to the CPU, each time. | |
| 4 | Ccommand language programmer (PGM-CHH) | | |

The system configuration and procedure for creating a user program when using personal computer software are indicated below. It is necessary to take note that cables, etc. differ depending on the personal computer and the software used.

Table 7.3 System configuration when using a personal computer





| No. | Personal computer software used | DOS/V PC | PC9800 series personal computer |
|-----|---|--|---|
| 1 | LADDER EDITOR (Windows® version) | DOS/V PC (Windows®95/NT) | PC9800 series personal computer (Windows®95/NT) |
| | | Specify H-302. Specify EH-150 after version 2.0.*2 | |
| | | Specify RAM-04H (4 k memory). | |
| | | Specify RAM-08H (8 k memory). | |
| | | Specify RAM-08H (8 k memory). | |
| | | Specify RAM-16H (16 k memory). | |
| | | Specify RAM-48H (48 k memory).*2 | |
| | | EH-RS05 | EH-RS05 |
| | | WVCB02H | WPCB02H |
| | | EH-VCB02 | |
| 2 | LADDER EDITOR (DOS version) | DOS/V PC (MS-DOS®) | PC9800 series personal computer (MS-DOS®) |
| | | Specify H-302. | |
| | | Specify RAM-04H (4 k memory). | |
| | | Specify RAM-08H (8 k memory). | |
| | | Specify RAM-08H (8 k memory). | |
| | | Specify RAM-16H (16 k memory). | |
| | | Specify RAM-48H (48 k memory). | |
| | | EH-VCB02 | |
| | | EH-RS05 | PCCB02H |
| | | | |
| | Mode setting switch *1 (Serial port 1 setting) | SW 1 2 3 4 5 6 7 8 Toggle | SW 1 2 3 4 5 6 7 8 Toggle |
| | | Sta- OFF — — — — — OFF OFF — | Sta- OFF — — — — — OFF OFF — |
| | | — — — — — ON ON — — — | — — — — — ON ON — — — |
| | | — — — — — — — — — | — — — — — — — — — |
| | | — — — — — — — — — | — — — — — — — — — |
| | | — — — — — — — — — | — — — — — — — — — |
| | | — — — — — — — — — | — — — — — — — — — |
| | | — — — — — — — — — | — — — — — — — — — |
| | | — — — — — — — — — | — — — — — — — — — |
| | | — — — — — — — — — | — — — — — — — — — |
| | Mode setting switch *1 (Serial port 2 setting) | SW 1 2 3 4 5 6 7 8 Toggle | SW 1 2 3 4 5 6 7 8 Toggle |
| | | Sta- OFF — — — — — OFF OFF OFF | Sta- OFF — — — — — OFF OFF OFF |
| | | — — — — — — — — — | — — — — — — — — — |
| | | — — — — — — — — — | — — — — — — — — — |
| | | — — — — — — — — — | — — — — — — — — — |
| | | — — — — — — — — — | — — — — — — — — — |
| | | — — — — — — — — — | — — — — — — — — — |
| | | — — — — — — — — — | — — — — — — — — — |
| | | — — — — — — — — — | — — — — — — — — — |
| | | — — — — — — — — — | — — — — — — — — — |

*1 Restart the power supply after the mode setting switch has been adjusted. The settings that are made while the power is on will not be effective until the power is restarted.

*2 When using the EH-CPU448(A)/548, please use the LADDER EDITOR for Windows® Ver. 2.13 and later. When using before Ver 2.12, please specify H-302. (Memory setting is RAM-48H)

Note: Refer to the manual that comes with each software on how to install the software (LADDER EDITOR).



Table 7.4 List of procedures for creating a program

| Item | Create new program | Modify | Test operation, adjustment | |
|-----------------------------|---|--|---|--|
| | Off-line | Off-line | On-line | On-direct |
| Operation procedure summary |  |  |  |  |
| Circumstance | When creating a new program | When modifying a program | When transferring a program to the CPU for the first time | When modifying a program during test operation |
| Point | A program can be created without having the actual EH-150. | When using a program that was used in another H-series, specify H-302 as the CPU type. | When performing CPU error check, make sure the I/O assignment matches the loaded module. (The match can be forced using the loading read function). | Match the personal computer and the contents of CPU memory to enter the on-direct mode. Afterwards, the modification will be reflected in both the computer memory and CPU memory. |

*1: For LADDER EDITOR for DOS version and LADDER EDITOR 1.xx for Windows ®.

Specify EH-150 after LADDER EDITOR 2.xx for Windows ®. When you will set the 48k to the Memory setting, please use after LADDER EDITOR 2.13 for Windows®.

Table 7.5 System configuration when using the programmer

| Item | Portable graphic programmer (PGM-GPH) | Command language programmer (PGM-CHH) |
|-------------------------|---|---|
| System configuration |  |  |
| Cable (EH-150 side) | EH-RS05 | EH-RS05 |
| Cable (programmer side) | PGCB02H | PGCB02H |

Note: 1. Do not use the option box (model: PGMIF1H) for the portable graphic programmer. Because of the large current consumption, the EH-150 system may go down.

Also, use a cable of 2 m (6.56 ft.) in length (model: PGCB02H) on the programmer side to connect a programmer. If a 5 m (16.4 ft.) cable (model: PGCB05H) is used, the programmer operation may become unstable.

2. The programmer can only be connected to serial port 2. For more information on setting modes, see Table 10.6.

With the EH-150, the user program is controlled in ladder units and as shown with Figure 7.1, 1 ladder can describe 9 contacts (a-type contact or b-type contact) and 7 coils.




Figure 7.1 Max. size of one ladder

Or, one relational box can be described using the width of 3 contacts. The relational box can be thought of as an a-type contact that turns on when the conditions in the box are satisfied (Figure 7.2).




Figure 7.2 Using comparison box

In addition, if return symbols are used, a ladder containing up to 57 contacts and one coil can be input within seven lines. (Figure 7.3)





Figure 7.3 Example of using return symbols

A processing box can be placed in the coil position. Processing commands, application commands, control commands, transfer command and FUN commands can be described in a processing box. A maximum of 19 commands can be described in one processing box. The processing box is executed when the condition in the contact section that is connected directly before it, is satisfied and not executed if the condition is unsatisfied.

Refer to “Chapter 5 Command Specifications” for details on each command.



A maximum of 4 contacts can be described in one line

Figure 7.4 Using a processing box

Note: For the LADDER EDITOR for Windows®, the processing box can be displayed in 1 contact point width, so a ladder of 9 contact and 1 processing box can be input.

For details, refer to the user's manual for the LADDER EDITOR for Windows®.

MEMO

Chapter 8 PLC Operation

The EH-150 can switch its operation status and stop status through various types of operations. This feature is shown in Figure 8.1.




Figure 8.1 Diagram of status transition between operation and stop

The EH-150 can be operated or stopped under the conditions as shown in Figure 8.1. If an error is detected during operation or stop, output is shut off, an error is displayed and the EH-150 stops. Error includes serious failure, medium failure, minor failure and warning. The operation status for each failure is shown in Table 8.1.

Table 8.1 Description of each failure and operation status

| Classification | Description | Run/Stop |
|-----------------|---|--|
| Serious failure | This indicates there is a serious, unrecoverable error, such as power failure, microcomputer error, system ROM error, system RAM error, system bus error, etc. | Stop |
| Medium failure | This indicates there is an error such as data memory abnormal, system program abnormal, user memory abnormal, user memory size error, grammatical assemble error, etc., which will cause a malfunction if operation is continued. | Stop |
| Minor failure | These are errors such as I/O information verify error, remote abnormal, overload error, excessively assigned I/O points. The operation can continue when there is a continue operation setting in the user program. | Stop (continued operation is possible if specified) |
| Warning | These are abnormal such as a transfer error, where it is possible to continue the operation. | Operation continues |




Note

If CPU type is 448(A)/516/548, "RUN continue" can not be specified at scan time error for cyclic scan. Make your program of periodical scan carefully so that scan time error is not detected.

8.1 RUN Start

When the EH-150 switches to operation status, the user program is executed in sequence from the head. The user program consists of a normal scan program and periodic scan program. In addition to these programs, there is a subroutine area defined as a subroutine.

Table 8.2 Program classification

| No. | Program classification | Description | Expression |
|-----|------------------------|--|--|
| 1 | Normal scan program | This is the program that is normally executed. When the program has been executed to the END command, execution starts again from the head. Overload error monitoring is performed according to the overload check time set by the user. Monitoring is from the top of the program until the END command. If it is designated to continue during overload, the operation continues. |  |
| 2 | Cyclic scan program | This program is executed periodically at intervals of 5 ms, 10 ms, 20 ms, or 40 ms *. Each execution cycle time becomes the overload error monitoring time. If it is specified to continue during overload, the operation is terminated in the middle. If CPU type is 448(A)/516/548, "RUN continue" can not be specified at scan time error for cyclic scan. Make your program of periodical scan carefully so that scan time error is not detected. | <p>Described in the area after the END command.</p>  |
| 3 | Subroutine | This is a program called out by the CALL command. | <p>Described in the area after the END command</p>  |

* Cyclic scan time depends on CPU types

| | CPU104/208/308/316 | CPU***A/448/516/548 |
|-------|--------------------|---------------------|
| INT 0 | 10 ms | 5 ms |
| INT 1 | 20 ms | 10 ms |
| INT 2 | 40 ms | 20 ms |
| INT 3 | - | 40 ms |

8.1.1 Scan operation

Each program is executed in the order of the priority shown in Figure 8.2. Each program is executed while monitoring the execution time of each program area. If the monitored time exceeds the prescribed time, this causes an overload error and operation stops. When continued operation has been specified, operation continues.

The timing for scan execution is shown in Figure 8.2. System processing is performed at set periods (every 5 ms), followed by communication system processing. The maximum execution time of communication system processing *1 equals the duration of time until the next periodic system processing is started. If the communication system processing ends before the maximum execution time is up, execution of scan processing is started upon completion of the communication system processing. When the next periodic processing is performed, scanning is performed until the next periodic processing is performed.

*1: Communication system processing is executed every 10 ms.




Figure 8.2 Relationship between system processing and scanning

As shown in Figure 8.3, scan processing is done while periodic scanning is performed. Periodic scanning is processed at the point when switching to normal scan. Periodic scans are performed at intervals of every 5 ms, 10 ms, 20 ms, or 40 ms. (5 ms periodic scan is supported only for the EH-CPU***A/448/516/548.) In terms of priority of execution, 5 ms scans have the highest priority. Use the refresh command when you wish to perform data processing for the external I/O (X,Y) during the periodic scan.

Update of timer progress value is performed as part of system processing. (For the EH-CPU***A/448/516/548, it is performed when each timer command is executed.)




Figure 8.3 Scan execution timing

8.1.2 Setting System Processing Time (EH-CPU***A/448/516/548)

System processing time can be assigned from 1 to 8 ms out of 10 ms for EH-CPU***A/448/516/548. It is thus possible to select the optimal system processing time according to the purpose of control.

(1) Operation and application

Figure 8.4 shows the scan operation when the system processing time is set to 3 ms. In this figure, the system operation time corresponds to “periodical system processing” + “communication system processing.” And you can set up time to assign this processing as a parameter.




Figure 8.4 Scan operation when the system processing time is set to 3 ms

Because the scan processing time for executing user programs can be made longer, the operation processing efficiency per unit time can be improved.

(2) Setup method

Set the system processing time in special internal output WRF038.




Figure 8.5 Special internal output for setting the system processing time

Enter a value from 1 to 8 in 1-digit BCD format representing the user setting time. If a value outside this range is selected, the system sets the value which can be used with the system. Furthermore, the processing time of the system currently in operation, which is set in the lower eight bits of the current system processing time field, can be checked by monitoring WRF038 with a peripheral unit. This setting range changes as shown in the following table due to the existence of 5ms periodical scan (INT0).

Table 8.3 The correspondence of the user setting value and the actual system processing time

| Setting value(*1) | H0 | H0 | H0 | H0 | H0 | H0 | H0 | H0 | H0 | H0 | Remark |
|--|----|----|----|----|----|----|----|----|----|----|--|
| INT0(5ms periodical scan) Not exist | H2 | H1 | H2 | H3 | H4 | H5 | H6 | H7 | H8 | H8 | The part of __ shows the value changed forcibly with the system. |
| INT0(5ms periodical scan) Exist | H2 | H1 | H2 | H3 | H2 | H2 | H2 | H2 | H2 | H2 | |

*1: Setting value is the lower digit BCD format of an upper 8 bits of WRF038. The value of an upper digit BCD format is ignored.

Ex.1): In order to set the system processing time to 3 ms, enter H0300 in WRF038.

Ex.2): If H10 is set as the user setting time, the value of an upper digit BCD format is ignored. Therefore, a system is judged H0 to be set up, and system set to 3 ms the system operation time. It is indicated with H1002 when WRF038 is seen at this time.

This setting becomes valid immediately after setting.

The existence of 5 ms periodical scan (INT0) is confirmed with the system at the time of the RUN start. System processing time is changed forcibly when INT0 is contained in the program and user setting time is beyond H4. (Table 8.3 reference.)

(3) Precautions

Please make a program referring to “8.1.6 (4) Cautions when using 5 ms periodical scan “ when you use the 5 ms periodical scan (INT0), which is supported only by the EH-CPU***A/448/516/548.

8.1.3 Setting System Processing Time (EH-CPU308/316)

NOTE:

This function is available only for EH-CPU308/316.
EH-CPU***A/448/516/548 is not applied.

The system processing time of the EH-CPU308/316* can be fixed at 5 ms. By fixing the system processing time, the normal scan time will not fluctuate and it is executed for 5 ms in 5 ms cycles.

* The EH-CPU308/316 of ROM Version 03 or earlier do not support this function.

(1) Operation and application

Figure 8.6 shows the scan operation when the system processing time is fixed. In this figure, the system operation time corresponds to “periodical system processing” + “communication system processing,” thus it is possible to set this parameter.

Conventionally, the operation shifts to normal scan processing when the system processing is finished. If, however, the system processing time is fixed, the normal scan does not start until 5 ms have elapsed, even if the system processing is finished.




Figure 8.6 System processing time (fixed at 5 ms)

The scan processing time for executing user programs can be fixed. Use this function if it is not desirable to allow the normal scan time to fluctuate.

(2) Setup method

Set the system processing time in special internal output WRF038.

| | | | | |
|--------|-------------------|---|---|--------------------------|
| Bit: | 15 | 8 | 7 | 0 |
| WRF038 | User setting time | | | Current operation status |

Figure 8.7 Special internal output for setting the system processing time

Enter H*5 as the user setting time. When the setting is completed, H05 is set in the current operation status field. If a value other than H*5 is set in the user setting time field, the setting value is stored in the user setting time field but H00 is stored in the current operation status field, and the system processing time becomes variable as usual.

Example: In order to fix the system processing time, enter H0500 in WRF038. If WRF038 is monitored at this point, it can be observed that H0505 is set.

If a value other than H*5, e.g. H0300, is set as the system processing time, the system processing time becomes variable and the value that can be monitored in WRF038 is H0300.

This setting becomes valid immediately after setting.

8.1.4 Normal Scan

(1) Definition and operation

The normal scan refers to the calculations and execution of the ladder/instruction language program (or the programs written in Pro-H) until the END scan processing caused by the END instruction (excluding interrupt programs). The time required for one scan, from the beginning of a normal scan program to the END scan processing, is called the normal scan time.




Figure 8.8 Operation of normal scan

(2) Causes of congestion errors at normal scan

Congestion errors may occur at normal scan because of the following two possible reasons. In particular when using a periodical scan program together, care must be taken to create the program in such a way that the total scan time does not exceed the congestion check time.

(a) When only a normal scan program is used

The scan time exceeded the congestion check time because the time required for one scan was too long.




Figure 8.9 Congestion error at normal scan (a)

(b) When both a normal scan program and a periodical scan program are used

The congestion check time was exceeded because the periodical scan program was executed and the normal scan time became longer. (Figure 8.10 shows an example of operation by CPUs other than the EH-CPU104A/208A/308A/316A/448.)




Figure 8.10 Congestion error at normal scan (b)

(3) Continuation of operation after a congestion error occurred

When the special internal output R7C0, which specifies whether the operation should continue after a congestion error occurred, is turned on, the normal scan executes the scan until the end regardless of the congestion check time, and after executing the END scan processing, executes the normal scan from the beginning again.




Figure 8.11 Operation when operation continuation at congestion error is set

However, note that this setting does not stop the execution of the scan when a congestion error occurred even when an infinite loop is formed within the normal scan by the JMP instruction.

8.1.5 Periodical Scan (In case of the EH-CPU104/208/308/316)

(1) Definition and operation

This scan executes operations of interrupt programs (periodical scan programs) while the CPU is operating with a cycle time specified by the user (10 ms, 20 ms or 40 ms). For the EH-CPU***A/448/516/548, 5 ms periodical scan has newly been added. The details about the periodical scan of the EH-CPU***A/448/516/548 are explained in Section 8.1.6. This section explains about the EH-CPU104/208/308/316.

Enter the periodical scan program to be executed between instructions INT0 and RT1 if it should be started up with a 10 ms cycle time, and between INT1 and RT1 if it should be started up with a 20 ms cycle time.

The periodical system processing is executed every 10 ms regardless of whether or not there is a periodical scan program.




Figure 8.12 Operation of periodical scan (in case of INT1)

(2) Causes of congestion errors at periodical scan

If there are periodical scans at every 10 ms as well as scans at every 20 ms or 40 ms, a congestion error occurs and the scan is stopped if the periodical scan at 10 ms is started up again before all the periodical scans are completed (i.e., the periodical system processing at INT0 to INT2 does not end within 10 ms).




Figure 8.13 Congestion error at periodical scan (10 ms)

Similarly, when executing with a periodical scan at every 20 ms or with a combination of periodical scans at every 20 ms and 40 ms, a congestion error occurs if the periodical scan at 20 ms is started up again before all the periodical scans are completed (i.e., the periodical system processing at INT1 to INT2 does not end within 20 ms). Finally, when using a periodical scan at every 40 ms, a congestion error occurs if the periodical scan at 40 ms is started up again before all the periodical scans are completed (i.e., the periodical system processing at INT2 does not end within 40 ms).

(3) Continuation of operation after a congestion error

If a congestion error occurs when the special internal output bit R7C1, which specifies whether the operation should continue after a congestion error, is turned on, the execution of the periodical scan is stopped and the periodical scan is executed from the beginning again. If the operation continuation specification for the normal scan is Off when this happens, the scan stops as a congestion error at a normal scan. If the operation continuation specification for the normal scan is On, only the periodical scan continues to be executed in the event of a periodical congestion error. Care must be taken because the normal scan is not executed under this condition.




Figure 8.14 Operation when operation continuation at congestion error is set

8.1.6 Periodical Scan (In case of EH-CPU***A/448/516/548)

(1) Definition and operation

In addition to the conventional periodical scan, a “5 ms periodical scan” is now available in the EH-CPU***A/448/516/548. The basic operations, such as normal operation and operations at congestion errors, are the same as the operations available at the periodic scan described in Section 8.1.5.

Table 8.4 Interrupt labels and cycles time

| No. | Interrupt label | Startup cycle | |
|-----|-----------------|--------------------|---------------------------|
| | | EH-CPU***A/516/548 | EH-CPU104/208/ 308/316 |
| 1 | INT0 | Every 5 ms | Every 10 ms |
| 2 | INT1 | Every 10 ms | Every 20 ms |
| 3 | INT2 | Every 20 ms | Every 40 ms |
| 4 | INT3 | Every 40 ms | - |

(2) Causes of congestion errors at periodical scan

In the same way as in CPUs other than the EH-CPU104A/208A308A/316A/448, a congestion error occurs when the execution time of the periodic scan exceeds the minimum cycle (time) of periodical program steps used in the program.

Ex. 1) If all the interrupt labels, INT0 to INT3, are used

Since the minimum cycle of the periodical scans being used is 5 ms, a congestion error occurs if the total scan time of each periodical scan exceeds 3 ms. Refer to (4) for INT0 specially.

Ex. 2) When INT2 and INT3 are used

Since the minimum cycle of the periodical scans being used is 20 ms, a congestion error occurs if the total scan time of each periodical scan exceeds 20 ms.

(3) Continuation of operation after the occurrence of a congestion error

The CPU except for EH-CPU448(A)/516/548 can continue operation even if a congestion error occurs in periodical scan when special internal output “R7C1” is turned on. But, even if this setting is done, operation isn't continued with EH-CPU448(A)/516/548. Please make a periodical scan program so that a congestion error may not occur in periodical scanning.

And, when the time to assign it to the system processing is lengthened, the time that is assigned to periodical scan becomes short. Therefore carry out the change of the system processing time after you do enough confirmation.

Note) When the congestion error occurs in the CPU except EH-CPU448, the periodical scan program aborts on the way.

When the next period scan begins, it executes again from the beginning of the period scan program.

Therefore, please modify the period scan program to finish in period scan, because the period scan program of the congestion error occurrence since then isn't executed

(4) Cautions when using 5 ms periodical scan

The congestion check time of 5 ms periodical scan (INT0) is the time when system processing time, the completion processing time of periodical scanning, trance/receiving processing time of the communication, and so on were deducted from 5 ms. The allowable time when 5 ms periodical scan (INT0) can be carried out in the table 8.5 is shown. Please make a program to be in time when the value that the processing time of each command was summed up shows it in the table.

Table 8.5 Standard of 5 ms periodical scan executive time

| Setting value | System processing time | Equation | INT0 Allowable time |
|---------------|------------------------|--|---------------------|
| H0 | H2 (0 to 3 ms) | $(5 \text{ ms} - 3 \text{ ms} - 0.5 \text{ ms}) \times 60\%$ | 0.9 ms |
| H1 | H1 (0 to 2 ms) | $(5 \text{ ms} - 2 \text{ ms} - 0.5 \text{ ms}) \times 60\%$ | 1.5 ms |
| H2 | H2 (0 to 3 ms) | $(5 \text{ ms} - 3 \text{ ms} - 0.5 \text{ ms}) \times 60\%$ | 0.9 ms |
| H3 | H3 (0 to 4 ms) | $(5 \text{ ms} - 4 \text{ ms} - 0.5 \text{ ms}) \times 60\%$ | 0.3 ms |
| H4 to H9 | H2 (0 to 3 ms) | $(5 \text{ ms} - 3 \text{ ms} - 0.5 \text{ ms}) \times 60\%$ | 0.9 ms |

8.2 Online Change in RUN

The user program can be modified during operation while retaining the output status as is. This is called the "online change in RUN" function. Modifying the user program requires programming software specifically for this or a programmer. Refer to the individual manuals on how to do this.

Online change in RUN cannot be done in the following situations. Perform this operation after completing the conditions.

Table 8.4 Conditions for performing online change in RUN

| No | Conditions under which online change in RUN cannot be done | Specific situation | How to satisfy the conditions |
|----|--|--|---|
| 1 | When READ-occupying | Other programming device is connected. | Change other programming devices to off-line. |
| 2 | | When a personal computer or panel, etc. is connected and monitoring is being done. | Change the personal computer or panel to off-line. (When monitoring, it is convenient to use the occupancy unnecessary task code.) |
| 3 | END command is not executed. | A program that runs in an endless loop is being executed. | Correct the program so that it does not run in an endless loop. |
| 4 | Trying to modify a program that contains control commands. | Doing an online change in RUN for a ladder containing a control command may cause operation to stop depending on the type of the program modification error. | An explanation of how to do an online change in RUN for a ladder that contains a control command is given in the programming software manual. |
| 5 | A password has been set. | A program protected by a password cannot be modified. | Perform the revision after having the system supervisor remove the password. |

(When the CPU is stopped, the modification is executed without displaying a message confirming online change in RUN.)

8.2.1 Cautionary Items for Changing Programs in RUN

The system operation of EH-CPU***A/448/516/548 is slightly different from EH-CPU104/208/308/316. The following describes cautionary items for changing programs in RUN when using EH-CPU***A/448/516/548.

(1) Updating the timer elapsed value

The timer elapsed value of EH-CPU104A/208A/308A/316A/448 is calculated by comparing with the previous elapsed value when the timer coil command is executed. The execution of a user program halts temporarily when it is changed in RUN. Therefore, the timer elapsed value will not be updated when the CPU is in the HALT state.

Reference: The timer elapsed values of EH-CPU104/208/308/316 are updated periodically. Therefore, these timer elapsed values are updated even in the HALT state.

(2) Transferring changed programs to the FLASH memory

EH-CPU***A/448/516/548 loads the programs that have been changed in RUN to the FLASH memory after the change in RUN display on the peripheral unit goes off. If the CPU power is turned off while a changed program is being transferred to the FLASH memory, that program may be damaged.

To prevent this, the special internal output R7EF which indicates that programs are being transferred to the FLASH memory (turns on while programs are being transferred to the FLASH memory) has been added. Before turning off the CPU power, be sure that this special internal output R7EF is off, or wait for about two minutes after the change in RUN operation.

The EH-150 operation when the user program is changed in RUN is shown below.




Figure 8.15 Internal processing for an online change in RUN

8.2.2 HALT time

When performing online change in RUN, the program to be written to the CPU is checked if there are no errors, then the CPU is halted temporarily (RUN → HALT).

The program of the modified area is written to the CPU while it is halted, and the CPU is set to operate (HALT → RUN) again.

At this time, the approximate time the CPU is halted will be obtained in the equation below (it is not necessarily the maximum value).


$$\begin{aligned}
 \text{HALT time (ms)} &= 45 \times \text{Program capacity (ks)} + 20 \text{ (EH-CPU104//208)} \\
 &= 38 \times \text{Program capacity (ks)} + 10 \text{ (EH-CPU308/316)} \\
 &= 18 \times \text{Program capacity (ks)} + 15 \text{ (EH-CPU104A-316A)} \\
 &= 29 \times \text{Program capacity (ks)} + 10 \text{ (EH-CPU516)} \\
 &= 29 \times \text{Program capacity (ks)} + 60 \text{ (EH-CPU448(A)/548)}
 \end{aligned}$$

An example of a calculation of the HALT time using the above equation is shown below.

| Program size (k step) | HALT time (ms) | | | | |
|--------------------------|----------------|------------|--------------|--------|---------------|
| | CPU104/208 | CPU308/316 | CPU104A-316A | CPU516 | CPU448(A)/548 |
| 4 | 200 | 162 | 87 | 126 | 176 |
| 8 | 380 | 314 | 159 | 242 | 292 |
| 16 | - | 618 | 303 | 474 | 524 |
| 48 | - | - | - | - | 1,452 |

8.3 Instantaneous Power Failure

What happens when the power supply to the EH-150 shuts off, is shown below.



(1) Powering on

The EH-150 starts operations after a maximum of 3.5 seconds have elapsed after power-up. If the power for input module is not completely started when the operation is commenced, the input that is supposed to be on will be received as OFF and operation proceeds, so make sure that the power for I/O module is completely started before operation is commenced.

Note: When expansion unit used, turn on the power supply of the expansion side, or turn on the power for the basic side and expansion side at the same time. If the basic side is powered up first, an error will occur.

(2) Instantaneous power failure actions

(a) When 100 V AC is supplied

Operation continues if power failure time is 10 ms or less.

(b) When 200 V AC is supplied

Operation continues if power failure time is 20 ms or less.

Note: Since EH-150 detects power failure by voltage level of internal 5VDC, the power failure resistance time depends on mounted module configuration. For this reason, only expansion unit can be reset due to instantaneous power failure. If this is not accepted, connect the AC power of PLC to AC input module and use it as interlock.

Note: Power for input should be supplied as long as CPU is running. If the power for PLC and AC input module is the same source, CPU can recognize input data as OFF at instantaneous power failure.

Note: If power failure time is more than the above resistance time, CPU will be reset and all data will be cleared.

8.4 Operation Parameter

The settings of "parameters," which are required to perform tasks such as creating programs, transferring programs to the CPU, are performed. The setting contents are explained below.

| Item | Function | Description | When to use the function | | | | | | | | | | | | |
|-------------|----------------------|---|---|----------------|-------------------------|----------------------|-------------|---------|---------|---------|-----|-------------------|-------------|---------|---|
| 1 | Password | <ul style="list-style-type: none">○ Register a password to a program in the four-digit hexadecimal format. The program with a password will not allow program operation nor changes unless the correct password is entered, so please exercise caution. <u>Caution: The user will not be able to reset the password when it is forgotten, so exercise sufficient caution when using a password.</u> Password is not set at the time of shipment. | Use when protecting the confidentiality of the program. | | | | | | | | | | | | |
| 2 | CPU type | <ul style="list-style-type: none">○ Set the CPU name used to perform programming. For EH-150, set to the following: Set H-302 with the EH-150. However, set EH-150 with the LADDER EDITOR (Windows ® version) Ver 2.0 or later. | Always perform these settings when programming. | | | | | | | | | | | | |
| 3 | Memory assignment | <ul style="list-style-type: none">○ Set the memory capacity. For EH-150, set to the following:<table border="1"><tr><td>CPU</td><td>EH-CPU104/104A</td><td>EH-CPU208(A) /308(A)</td><td>EH-CPU316(A) /516</td></tr><tr><td>Memory type</td><td>RAM-04H</td><td>RAM-08H</td><td>RAM-16H</td></tr></table><table border="1"><tr><td>CPU</td><td>EH-CPU448 /548</td></tr><tr><td>Memory type</td><td>RAM-48H</td></tr></table> Set the “CPU type” of Item 2 to H-302 for EH-CPU448. However in case of LADDER EDITOR for Windows® Ver. 2.13 and later , set the EH-150. | CPU | EH-CPU104/104A | EH-CPU208(A) /308(A) | EH-CPU316(A) /516 | Memory type | RAM-04H | RAM-08H | RAM-16H | CPU | EH-CPU448 /548 | Memory type | RAM-48H | Always perform these settings when programming. |
| CPU | EH-CPU104/104A | EH-CPU208(A) /308(A) | EH-CPU316(A) /516 | | | | | | | | | | | | |
| Memory type | RAM-04H | RAM-08H | RAM-16H | | | | | | | | | | | | |
| CPU | EH-CPU448 /548 | | | | | | | | | | | | | | |
| Memory type | RAM-48H | | | | | | | | | | | | | | |
| 4 | Operation parameters | <ul style="list-style-type: none">○ Operation control Perform these settings when controlling the operation and stopping using a specific I/O. If this is not set, operation will commence automatically when the RUN switch is set to "RUN."○ Overload check time Set this when you wish to stop the CPU operation when the set maximum processing time for a normal scan is exceeded. When the setting is not made, this is automatically set to initial value 100 ms.○ Operation mode at abnormal occurrence Set this when you wish to continue the CPU operation when the error generated by the CPU is minor. However, do not use this when not debugging. | Set according to the user's operation purposes. | | | | | | | | | | | | |
| 5 | I/O assignment | <ul style="list-style-type: none">○ This sets the I/O assignment information of the CPU. It is recommended to use the EH-150's convenient I/O assignment copy function. | Always perform these settings when programming. | | | | | | | | | | | | |
| 6 | Program name | Set the program name using a maximum of 16 kana or alphanumeric characters. The set program names can be written into the CPU along with the program, which will make the program verification and maintenance works easier. | Set this when easy program verification and maintenance are desired. | | | | | | | | | | | | |
| 7 | Power failure memory | This sets the range in which the data in a specified area in the CPU is to be stored upon CPU power off or when commencing RUN. Settings for R, WR, WM, TD, DIF, DFN are possible. | Set this when there is data you wish to maintain when operation is stopped. The special internal output data is unconditionally saved for power failure by I/O number. | | | | | | | | | | | | |

8.5 Test Operation

(1) Verification of interlock

Verify the performance of the interlock in preparation for unexpected accidents.

Create ladders such as an emergency stop ladder, protective ladder and interlock ladder outside the program controller. With regard to the relay output module, however, do not control the relay drive power supply to interlock with external loads.

(2) Operation without load

Before actually operating the loads in the system, test the program only and verify its operation.

Always perform this if there is any possibility of damaging the other party's equipment due to unexpected occurrences caused by program errors or other problems.

(3) Operation using actual loads

Supply power to the external input and external output to verify the actions.

MEMO

Chapter 9 PLC Installation, Loading, Wiring

9.1 Installation

(1) Installation location and environment

- (a) When installing the EH-150, use the module within the [3.3 general specification] environment.
- (b) Mount the PLC onto a metal plate.
- (c) Install the PLC in a suitable enclosure such as a cabinet that opens with a key, tool, etc.

(2) Installing the base unit

(a) Precautions when installing the base unit

- 1] When installing the base unit, fix it securely with screws in 4 places (M4, length 20 mm (0.79 in.) or more) or DIN rail.
- 2] To keep the unit within the ambient temperature range when using,
 - a) Allow ample space for air circulation. (50 mm (1.97 in.) or more at top and bottom, 10 mm (0.39 in.) or more to the left and right)
 - b) Avoid installing the unit directly above equipment that generates a lot of heat (heater, transformer, large-capacity resistance, etc.)
 - c) When the ambient temperature reaches more than 55 °C, install a fan or cooler to lower the temperature to below 55 °C.
- 3] Avoid mounting inside a panel where high-voltage equipment is installed.
- 4] Install 200 mm (7.87 in.) or more away from high-voltage lines or power lines.
- 5] Avoid upside down, vertical or horizontal mounting.




Figure 9.1 Installation space




Figure 9.2 External dimensions


Dimensional table

| Base | L1 (Outer dimensions) | L2 (Mounted dimensions) |
|----------|-----------------------|-------------------------|
| 3 slots | 222.5 (8.76) | 207 (8.15) |
| 5 slots | 282.5 (11.12) | 267 (10.51) |
| 8 slots | 372.5 (14.67) | 357 (14.06) |
| 11 slots | 462.5 (18.21) | 447 (17.60) |

Unit: mm (in.)

(b) Mounting to a DIN rail


Attaching to a DIN rail



- 1] Hook the claw fixed at the bottom of the base unit, to the DIN rail.
- 2] Press the base unit into the DIN rail until it clicks.


Note: After installation, check to make sure the base unit is securely fixed.

Fixing the unit



Secure the unit by installing DIN rail fixing brackets from both sides. (The product may go out of place if not secured with the fixing brackets.)


Removing the unit from the DIN rail



- 1] While lowering the DIN rail fixing mounting lever toward the bottom, raise the base upward to remove.

9.2 Loading the Module

(1) Installing




- 1] Hook the bottom part of the module to the hole in the base.
- 2] Press in the upper side of the module until it clicks.

Note 1: After loading the module, check to make sure it does not come out.

Note 2: Load the power module at the leftmost side of the base unit.

Note 3: Load the CPU module and I/O controller to the left of the power module.

(2) Removing



- 1] Push in the lock button.
- 2] With the lock button pushed in, pull the top of the module toward the front.
- 3] Raise it toward the top and pull it out.

Note: For the power module, pull it out while pushing down the two lock buttons.

9.3 Wiring

(1) Separation of the power system

For the power supply, there is power for the EH-150 PLC unit/power for the I/O signals/power for general equipment. These power supplies should be wired from separate systems as much as possible.

When these power supplies are supplied from one main power source, separate the wiring with a transformer or similar device, so that each power supply is a separate system.




Figure 9.3 Example of power system diagram

(2) Regarding fail safe

1] Construct an interlock circuit outside the PLC.

When the PLC power supply is turned on or off, the lag time and difference in startup time between the PLC unit power and the external power (particularly DC power supply) for the PLC I/O module signals, may temporarily cause the I/O not to operate normally.

Do not control the power for the EH-YR12 relays to have it perform an interlock with the external load, etc. The relays may turn on even when power is not being supplied by an aluminum electrolytic condenser inside the module to drive the relays.

Also, it is plausible that a fault in the external power supply or a failure in the PLC unit will lead to abnormal actions. To prevent such actions from causing abnormal operation of the entire system, and from the viewpoint of creating a fail-safe mechanism, construct ladders such as an emergency stop circuit, the protect circuit, and the interlock circuit, for the sections that lead to a mechanical breakdown or accident from abnormal operation outside the PLC.

2] Install a lightning arrester

To prevent damage to equipment as a result of being struck by lightning, it is recommended that a lightning arrester be set up for each PLC power supply ladder.

The EH-150 detects power failures from a voltage drop of the internal 5 V DC power supply. For this reason, when the load in the unit's internal 5 V DC is light, the 5 V DC is retained for a long time and operations may continue for more than 100 ms. Therefore, when using the AC input module, an off delay timer for coordinating with the internal 5 V DC is necessary since the AC input signal turns off more quickly than the internal 5 V DC.

(3) Wiring to the power module





Figure 9.4 Wiring power diagram

- (a) For power supply wiring, use a cable of 2 mm² (0.0031 in.) or more to prevent a voltage drop from occurring.
- (b) The function ground terminal (FE terminal) should use cable of 2 mm² (0.0031 in.²) or more and Class D grounding (100 Ω or less). The appropriate distance for ground cable is within 20 m (65.62 ft.).
 - 1] Shared with instrumentation panel, relay panel grounding
 - 2] Avoid joint grounding with equipment that can generate noise such as high-frequency heating furnace, large power panel (several kW or more), thyristor exchanger, electric welders, etc.
 - 3] Be sure to connect a noise filter (NF) to the power cable.
- (c) The terminal screw is an M3. When wiring, tighten screws within a torque range of 0.49 to 0.78 N·m.
- (d) Use the same power supply system for the basic and expansion units.

(4) Wiring cable for I/O signals



Screws for all terminals are M3.

Tighten within a torque range of 0.49 to 0.78 N·m.


When using a crimp terminal, use one with an outer diameter of 6 mm (0.24 in.) or less.

Use only up to two crimp terminals in the same terminal. Avoid clamping down more than three at the same time.

Use a cable thickness of maximum 0.75 mm^2 (0.0011 in^2). (Use a 0.5 mm^2 (0.00075 in^2) cable when adding two crimp terminals in the same terminal).

Note: When corresponding to CE marking EMC command is necessary, use shielded cable for the relay output module.

Attaching the terminal block



- 1] Align the tip of the terminal block mounting screws to the screw section of the I/O cover insertion fittings.
- 2] Push in the top of the terminal block until the I/O cover claw section locks with a click.
- 3] While holding down the upper part of the terminal block, tighten the terminal block mounting screws.
- 4] Pull on the top of the terminal block to make sure that it is locked and cannot come out.

Note: If the terminal block is removed, always reinstall it following the instructions above.

(5) Input wiring for the input module





Figure 9.5 Input wiring

(a) DC input module


- 1] When all input terminals (X0, X1, ...) and the common terminal (C) are loaded with 24 V DC, inputs change to ON, and approximately 6.9 mA of current in the case of the EH-XD8, and approximately 4mA in the case of the EH-XD16, flow to the external input contacts.
- 2] For sensors such as a proximity switch or photoelectric switch, current output type (transistor open collector) can be directly connected. For voltage-output-type sensors, connect them to the input terminal after first going through the transistor.
- 3] Measures to prevent faulty contact in a strong electric contact



The current that flows to a contact when external contacts are closed is approximately 6.9 mA for the EH-XD8, and approximately 4 mA for the EH-XD16. If the use of a strong electric contact cannot be avoided, add resistance as shown in the diagram at left and supply sufficient current to the contact to prevent a faulty contact.

- 4] Max. cable length is 30 m (98.43 ft.)

(b) 32/64-point DC input module (Based on CE marking)




Caution

- 1] Wire only the signal line through the shielded cable. Cable shield should be grounded.
- 2] Do not wire the common line with signal lines in shielded cable. Be sure to wire it independently and separately from the power line, I/O lines or power supply line.
- 3] Power supply should be installed at common terminal of input module as close as possible.


(c) AC input module

In case of AC input module, input voltage may exist if input wiring is long although no device drives. This phenomenon is caused from leakage current due to floating capacitance between lines.



The countermeasures are [1] or [2] as follows. This voltage due to electrostatic coupling must be half of max. OFF voltage or less.

- [1] To install dummy resistor in parallel so that impedance of input module is lower.
- [2] To replace power supply at drive (external device) side.




(6) Output wiring for the output module

| Item | Relay output (EH-YR12) | Relay output (EH-YR16) | Transistor output (sink type) (EH-YT16, EH-YT8) | Transistor output (source type) (EH-YTP16, EH-YTP16S, EH-YTP8) |
|-----------------|---------------------------|---------------------------|---|---|
| External wiring | | | | |

Figure 9.6 Output wiring

(a) Wiring for the relay output module

1] Life of relay contacts



Life of the contact is also in squared reverse proportion to the current, so be aware that interrupting rush current or directly driving the condenser load will drastically reduce the life of the relay.

When switching is done with high frequency, use a transistor output module.

2] Surge killer

For inductive load, connect a surge killer (condenser 0.1 μ F, + resistance of around 100 Ω) in parallel to the load. Also, for DC load, connect a flywheel diode.

3] Fuse

A fuse is not built into this module. Install a 6 A fuse in the common to prevent the external wiring from burning out.

4] Power supply for driving the relays

If a 24 V DC power supply is connected to drive the relays, take care with respect to the polarity when connecting. There is a risk that the internal circuit will be damaged if the wiring is done incorrectly. Also, do not perform an interlock, etc. to the external load with the power supply for driving the relays.

(b) Wiring for the transistor output module

5] Flywheel diode

For inductive load, connect a flywheel diode in parallel.

6] S and C terminals

Always connect an S terminal and C (common) terminal. If the module is used without connecting these terminals, the internal flywheel diode does not function and there is a risk that the module will malfunction or breakdown.

7] Fuse

A fuse is inserted in the common to prevent the external wiring from burning out, but this does not protect transistor elements. Therefore, when the external load is shorted, these elements are destroyed, so exercise caution. If the external load shorts, please contact us for repair.

Also, if the fuse blows, there will be no output even if the LED lights up. (The fuse out lamp for the module at this time as well as a CPU module error will not be displayed.)

Note: If the fuse is melted or blown, do not supply power to the module after changing the fuse without eliminating the source of the problem. Damage escalation, smoke, etc., may otherwise result.

(8) Wiring to the module terminal




Figure 9.7 Example of wiring

MEMO

Chapter 10 Communication Specifications

10.1 Features

The EH-150 has two communication ports. Supported function of each port is shown in the below table.

10.1.1 Communication port functions

| Port type | | RS-232C | | | RS-422/485 | | | | |
|-------------------|--------------|----------------------------------|-------------|----------------------|--------------------------|---------------|---------|---------|----------------------|
| | | Dedicated port * | | General purpose port | Dedicated port * | | | | General purpose port |
| | | | | | | | | | |
| | | | | | | | | | |
| Procedure 1 | | Procedure 2 | Procedure 1 | | Procedure 2 | | | | |
| | | | Std. (1:1) | St. No. (1:N) | Std. (1:1) | St. No. (1:N) | | | |
| Connected devices | | PC, Programmer, Modem, HMI, etc. | PC etc. | PC etc. | PC, Programmer, HMI etc. | PC etc. | PC etc. | PC etc. | PC etc. |
| Port 1 | CPU104/208 | ✓ | - | ✓ | - | - | - | - | - |
| | CPU104A/208A | ✓ | ✓ | ✓ | - | - | - | - | - |
| | CPU308/316 | ✓ | - | ✓ | - | - | - | - | ✓ |
| | CPU308A/316A | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | CPU448/448A | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | CPU516/548 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Port 2 | All CPU | ✓ | - | - | - | - | - | - | - |

* Dedicated port = Programming port for PC, HMI, SCADA.

10.1.2 Port 1 setup method

Set the mode setting switch, power up again and set the special internal output values according to table below.

(1) General port setup

In case of general purpose port, with using the TRNS 0 and RECV 0 commands in a user program, set the interface according to the table below. After the setting, the system overwrites the following values, and switches the interface type. If user set value is out of the possible range, the system will not accept. Be sure to check the safety of the unit to be connected before setting.

Table 10.2 General purpose port setting for port 1

| mode SW | | WRF036 | | | | Interface |
|---------|-----|-------------------------------------|------------------|------------------------------------|------------------|-----------|
| | | Built-in termination resistor OFF * | | Built-in termination resistor ON * | | |
| 2 | 5 | Use set value | System set value | Use set value | System set value | |
| OFF | OFF | H0003 | H0002 | - | - | RS-232C |
| | | H0005 | H0004 | H0015 | H0014 | RS-422 |
| | | H0009 | H0008 | H0019 | H0018 | RS-485 |

* If the built-in termination resistor is set ON, built-in 100Ω resistor will be connected between lines (between receiver lines in case of RS-422). So no external termination is necessary.

(2) Dedicated port mode setup (Not supported by EH-CPU104(A))

When a modem is used, configure the following setup:

Table 10.3 Modem settings of port 1

| Mode SW | | WRF037 | | | Contents of setting | |
|---------|-----|----------------|---------------------|-------------------------------------|---------------------|----------------------------------|
| 2 | 5 | User set value | System set value *1 | Value displayed after power restart | Interface | Control procedure |
| ON | OFF | H8000 | H0000 | H0000 | RS-232C | Transmission control procedure 1 |
| | | HC000 | H4000 | H4000 | | Transmission control procedure 2 |

(3) Dedicated port setup

If the port 1 of EH-***A/448/516/548 is used as a dedicated port, configure the following setup.

Table 10.4 Dedicated port settings of port 1(EH-CPU***A/448/516/548)

| No. | Mode SW | | WRF037 | | | Contents of setting | |
|-----|---------|----|----------------|---------------------|-------------------------------------|--------------------------------------|---|
| | 2 | 5 | User set value | System set value *2 | Value displayed after power restart | Interface | Control procedure |
| 1 | - | ON | H8000 | H0000 | H0000 | RS-232C *1 | Transmission control procedure 1 |
| 2 | | | HC000 | H4000 | H4000 | | Transmission control procedure 2 |
| 3 | | | H8100 | H0100 | H0500 | RS-422 (Built-in termination OFF) *3 | Transmission control procedure 1 |
| 4 | | | HC100 | H4100 | H4500 | | Transmission control procedure 2 |
| 5 | | | HA1** | H21** | H25** | | Transmission control procedure 1 with station No. |
| 6 | | | HE1** | H61** | H65** | | Transmission control procedure 2 with station No. |
| 7 | | | H8200 | H0200 | H0A00 | RS-485 (Built-in termination OFF) *3 | Transmission control procedure 1 |
| 8 | | | HA2** | H22** | H2A** | | Transmission control procedure 1 with station No. |
| 9 | | | HE2** | H62** | H6A** | | Transmission control procedure 2 with station No. |
| | | | H9100 | H1100 | H1500 | RS-422 (Built-in termination ON) *3 | Transmission control procedure 1 |
| | | | HD100 | H5100 | H5500 | | Transmission control procedure 2 |
| | | | HB1** | H31** | H35** | | Transmission control procedure 1 with station No. |
| | | | HF1** | H71** | H75** | | Transmission control procedure 2 with station No. |
| | | | H9200 | H1200 | H1A00 | RS-485 (Built-in termination ON) *3 | Transmission control procedure 1 |
| | | | HB2** | H32** | H3A** | | Transmission control procedure 1 with station No. |
| | | | HF2** | H72** | H7A** | | Transmission control procedure 2 with station No. |

**: This means station number in 1:N communication. Set *3 a 2-digit BCD value from 00 to 31. If a value outside this range is specified as a station number, the specified value will be displayed, but the system will operate using a BCD value of 31.

*1 EH-CPU104A/208A supports only No.1 and 2 (RS232C only).

*2 The current interface status is displayed by b11 and b10 of WRF037. For this reason, other values may be displayed as system set values depending on previous setting. Please refer to chapter 13 for further information about WRF037.

*3 If the built-in termination resistor is set ON, built-in 100Ω resistor will be connected between lines (between receiver lines in case of RS-422). So no external termination is necessary.

10.2 Dedicated Port

The specification of dedicated port is shown in table 10.5.

By the dedicated port, CPU can be programmed or monitored by peripheral devices or PC or HMI. In addition, supervisor system or special sytem can be connected as well by making communication software.

Be sure to check cables and setting switches carefully beforehand.

Table 10.5 Specifications for a dedicated port

| Item | Specification | | | | |
|---------------------------------------|---|-----|----------------------------|------------------|--|
| Transmission speed | 4,800 bps, 9,600 bps, 19,200 bps, 38,400 bps Configured by setting switch. | | | | |
| | Port 1 | | | Port 2 *1 | |
| | SW3 | SW4 | Transmission speed setting | SW6 | Transmission speed setting |
| | ON | ON | 4,800 bps | ON | PHL = Low: 9,600 bps PHL = High: 38,400 bps |
| | OFF | ON | 9,600 bps | | |
| | ON | OFF | 19,200 bps | OFF | PHL = Low: 4,800 bps PHL = High: 19,200 bps |
| | OFF | OFF | 38,400 bps | | |
| Interface*2 | RS-232C | | RS-422 | RS-485 | RS-232C |
| Max cable length | 15 m | | 500 m | 500 m | 15 m |
| Connection mode (max connected units) | 1 : 1 | | 1 : N (32 units) | 1 : N (32 units) | 1 : 1 |
| Communication system | Half duplex | | | | |
| Synchronization system | Start-stop synchronization | | | | |
| Startup system | One-sided startup using the host side command | | | | |
| Transmission system | Serial transmission (bit serial transmission) | | | | |
| Transmission code | ASCII | | | | |
| Transmission code configuration | ASCII: 7-bit data, 1 start, 1 stop, even number parity | | | | |
| Transmission code outgoing sequence | Sent out from the lowest bit in character units | | | | |
| Error control | Vertical parity check, sum check, overrun check, framing check | | | | |
| Transmission unit | Message unit (variable length) | | | | |
| Maximum message length | 503 bytes*3 (including control characters) | | | | |
| Control procedure | H-series dedicated procedure (high protocol) Standard procedure 1 (transmission control procedure 1), simplified procedure (transmission control procedure 2)*4 | | | | |
| Connector used | CPU side: TM5RJ3-88 8-pin modular connector (Hirose) Partner side: Comparable to TM10P-88P (Hirose) | | | | |

*1 When the PHL switch is set high, +12 V DC is supplied from the connector pin 4 of port 2.

*2 RS-422/485 is supported by EH-CPU308A/316A/448(A)/516/548 only.

*3 When H series' dedicated procedure with station number is used in the EH-CPU308A/316A/448(A)/516/548, the maximum message length will be 505 bytes (including control character).

*4 Transmission control procedure 2 are supported by the EH-CPU***A/448/516/548 only.




Figure 10.1 Circuit diagram and pin numbers for port 1

Table 10.6 List of port 1 signals

| Pin No. | Signal abbreviation | Direction | | Meaning |
|---------|---------------------|-----------|------|--|
| | | CPU | Host | |
| 1] | SG1 | ←→ | ←→ | Ground for signal |
| 2] | CD1 | ← | → | Notification signal during carrier received |
| 3] | ER1 | → | → | Communication enabled signal When this signal is high level, communication is possible. |
| 4] | ER2 | → | → | Outputs High |
| 5] | SD1 | → | → | Data sent by the CPU |
| 6] | RD1 | ← | ← | Data received by the CPU |
| 7] | DR1 | ← | → | Peripheral units connected signal When this signal is high level, indicates that dedicated peripherals are connected. |
| 8] | RS1 | → | → | Transmission request signal When this signal is high level, indicates that the CPU can receive data. |




Figure 10.2 Circuit diagram and pin numbers for port 2

Table 10.7 List of port 2 signals

| Pin No. | Signal abbreviation | Direction | | Meaning |
|---------|---------------------|-----------|------|--|
| | | CPU | Host | |
| 1] | SG2 | ←→ | ←→ | Signal ground |
| 2] | PV5 | → | → | 5 V DC is supplied. |
| 3] | NV12 | → | → | -12 V DC is supplied. |
| 4] | PHL2 / PV12 | ← | → | Peripheral units connected signal/+12 V DC output. Indicates that a dedicated peripheral is connected. (when the switching switch is off). 12 V DC is supplied. (when the switching switch is on). |
| 5] | SD2 | → | → | Data sent by the CPU |
| 6] | RD2 | ← | ← | Data received by the CPU |
| 7] | DR2 | ← | → | Receive enabled signal When this signal is high level, indicates that connected devices can receive data. |
| 8] | RS2 | → | → | Transmission request signal When this signal is high level, indicates that the CPU can receive data. |

10.3 General Purpose Port

Port 1 can be used as a general-purpose port. In this case, user program must be prepared with using serial communication command TRNS 0 and RECV 0. The specifications of general purpose port is given in Table 10.8 below.

Be sure to check the connecting cables and setting switches carefully beforehand. Refer to P4-6 for setting switch.

Table 10.8 Specifications for a general-purpose port

| Item | Specification | | |
|---------------------------------------|---|--------------------|--------------------|
| Transmission speed | 300, 600, 1,200, 2,400, 4,800, 9,600, 19,200 bps | | |
| Communication system | Half duplex | | |
| Synchronization system | Start-stop synchronization | | |
| Startup system | One-sided startup using the host side command | | |
| Transmission system | Serial transmission (bit serial transmission) | | |
| Transmission code | User defined | | |
| Transmission code configuration | User setting: (1 start, 7 or 8 bit data, NON or EVEN or ODD parity, 1 or 2 stop) | | |
| Transmission code outgoing sequence | Sent out from the lowest bit in character units | | |
| Error control | Vertical parity check, overrun check, framing check | | |
| Transmission unit | Message unit (variable length) | | |
| Maximum message length | CPU104/208/308/316 : 256 bytes (including control characters) CPU***A/448/516/548 : 1,024 bytes (including control characters) | | |
| Interface * | RS-232C | RS-422 | RS-485 |
| Maximum cable length | 15 m (49.2 ft.) | 500 m (1640.5 ft.) | 500 m (1640.5 ft.) |
| Connection mode (max connected units) | 1 : 1 | 1 : N (32 units) | 1 : N (32 units) |
| Control procedure | No procedure | | |
| Control code | User defined | | |
| Connector used | CPU side: TM5RJ3-88 8-pin modular connector (Hirose) Partner side: Comparable to TM10P-88P (Hirose) | | |

* EH-CPU 104(A)/208(A) supports only RS-232C.

TRNS0, RECV0 commands specifications

Transmission speed set value (For other specification details, refer to the item in the list of instructions.)

| Baud rate | Set value |
|------------|-----------|
| 19,200 bps | H0006 |
| 9,600 bps | H0005 |
| 4,800 bps | H0004 |
| 2,400 bps | H0003 |
| 1,200 bps | H0002 |
| 600 bps | H0001 |
| 300 bps | H0000 |

10.3.1 RS-232C interface




Figure 10.3 Circuit diagram and pin numbers

Table 10.9 List of port 1 signals

| Pin No. | Signal abbreviation | Direction | | Meaning |
|---------|---------------------|-----------|------|--|
| | | CPU | Host | |
| 1] | SG1 | ←→ | ←→ | Ground for signal |
| 2] | CD1 | ← | — | Notification signal during carrier received |
| 3] | ER1 | — | → | Transmission enabled signal When this signal is high level, communication is possible. |
| 4] | ER2 | — | → | Outputs High. |
| 5] | SD1 | — | → | Data sent by the CPU |
| 6] | RD1 | ← | — | Data received by the CPU |
| 7] | DR1 | ← | — | Reception request signal When this signal is high level, indicates that dedicated the host can send data. Connect it to RTS signal on the host. |
| 8] | RS1 | — | → | Transmission request signal When this signal is high level, indicates that the CPU can receive data. Connect it to CTS on the host. |

10.3.2 RS-422/485 interface




Figure 10.4 Circuit diagram and pin numbers

Table 10.10 List of port 1 signal

| Pin No. | Signal abbreviation | Direction | | Meaning |
|---------|---------------------|-----------|------|----------------------------|
| | | CPU | Host | |
| 1] | SG1 | ←→ | ←→ | Signal ground |
| 2] | CD1 | ← | — | Not used. Do not connect. |
| 3] | ER1 | — | → | Not used. Do not connect. |
| 4] | TX | — | → | Data sent by the CPU + |
| 5] | TXN | — | → | Data sent by the CPU – |
| 6] | RXN | ← | — | Data received by the CPU – |
| 7] | RX | ← | — | Data received by the CPU + |
| 8] | RS1 | — | → | Not used. Do not connect. |




Figure 10.5 RS-422 signal connection diagram

If used as RS-485 interface, connect pin numbers 4] and 7], and 5] and 6], externally.




Figure 10.6 RS-485 signal connection diagram

10.3.3 1: N communication (RS-485)

(1) Precautions

When performing 1 to N communication using RS-485, do so in polling/selecting mode. When creating a ladder program, observe the following precautions.

- 1] Perform communication by making sure the master station and slave station are using the same start code.
- 2] At the master station, send a request by specifying the station number of the slave station.
- 3] At the slave station, send a response only when the request received from the master station is addressed to the own station. Set the station so that it will reset the mode and wait for the next request in the event it received a request addressed to other station.
- 4] At the master station, send a new request after at least 20 ms (t_p in figure below) has elapsed from the time it completed receiving the last response from the slave station.
- 5] At the slave station, send a response after at least 20 ms (t_s in figure below) has elapsed from the time it completed receiving the request from the master station.

Figure 10.7 shows an example of 1 to N transmission sequence. This example shows a sequence in which the master station sends a series of requests to slave stations 1 to 3, with each slave station sending a response to the received request.

In Figure 10.7, a plateau expressed in solid line indicates that the station received a transmission addressed to the own station. Similarly, a plateau expressed in dotted line indicates that the station received a transmission addressed to other station.




Figure 10.7 1:N transmission and reception sequence

(2) Sample Program

The following shows a sample program that performs communication between one master station and three slave stations using RS-485.

1] Mounting the module

(a) Master station side

| | | 0 | 1 |
|--------------|------------|---|-----------------|
| Power supply | CPU module | | 16-point output |

Mount the 16-point output module in slot "1" of the basic base.

(b) Slave station side

| | | 0 | 1 |
|--------------|------------|----------------|-----------------|
| Power supply | CPU module | 16-point input | 16-point output |

Mount the 16-point input module in slot "0" of the basic base and mount the 16-point output module in slot "1" of the basic base.

2] Assigning internal outputs

The sample program is created using the following assignments. In actual cases, change the I/O numbers and other items according to the application.

(a) Assigning internal outputs on the master station side

| I/O | No. | Usage |
|-----|--------------|--|
| WM | 100 to 10E | TRNS 0 instruction Parameter area (s to s+14) |
| R | 000 to 00B | TRNS 0 instruction Communication control bit area (t to t+11) |
| | 100 | Transmission data setting completion flag |
| WR | 0000 to 001F | Transmission data area (32-word) |
| | 0100 to 011F | Reception data area (32-word) |
| | 4000 | Station number of target slave station |
| | 4001 | Number of slave stations |
| WL | 001 to 003 | Reception data storage area |

(b) Assigning internal outputs on the slave station side

| I/O | No. | Usage |
|-----|--------------|--|
| WM | 0000 to 000E | RECV 0 instruction Parameter area (s to s+14) |
| | 200 to 21F | Transmission data area (32-word) |
| | 300 to 31F | Reception data area (32-word) |
| WR | 0000 to 000E | TRNS 0 instruction Parameter area (s to s+14) |
| | 0200 to 021F | Transmission data area (32-word) |
| | 0300 to 031F | Reception data area (32-word) |
| | 4000 | Station number of communicating slave station |
| | 4001 | Own station number |
| WL | 001 to 003 | Reception data storage area |

3] Transmission format

The following shows the formats that are used when transmitting data between the master station and slave station.

(a) Request format from the master station to slave station (a maximum of 3 bytes)

| Start code | Slave station number | End code |
|------------|----------------------|----------|
| 02H | 1 to 3 | 0DH |

(b) Response format from the slave station to master station (a maximum of 5 bytes)

| Start code | Own station number | Data | | End code |
|------------|--------------------|-------|-------|----------|
| 02H | 1 to 3 | Any * | Any * | 0DH |

*: Any data can be set except for the end code (0DH). The slave station number is set in this sample program.


4] Reception result on the master station side

When the transmissions between slave stations 1 to 3 have completed successfully, the corresponding data are set in the WL area of the master station as shown below. In this sample program, the slave stations set their own station number as part of the data.


| Address | Set value | Contents |
|---------|-----------|---|
| WL0001 | 0001H | The data received from slave station 1. |
| WL0002 | 0002H | The data received from slave station 2. |
| WL0003 | 0003H | The data received from slave station 3. |


5] Program

(a) Program on the master station side (with three slave stations)



(b) Program on the slave station side (slave station number 2)






10.4 Modem Control Function

All CPU except CPU104(A) is equipped with a modem control function. The modem control function can be controlled using task codes.

To use this function, the mode setting switch must be set. For setting switches, refer to P4-6.

Connecting the two operating modems may be difficult if there is a large difference between them in communication speeds. Match to eliminate any difference in communication speeds.

10.4.1 Configuration



10.4.2 Connection specifications

| Item | Specification |
|-------------------------------------|---|
| Transmission speed | 2,400 bps, 4,800 bps, 9,600 bps, 19,200 bps, 38,400 bps * Communication speed between the modem and PLC depends on the setting for the special internal output WRF01A. |
| Communication system | Full duplex (communication program is half-duplex control) |
| Synchronization system | Start-stop synchronization |
| Transmission system | Serial transmission (bit serial transmission) |
| Transmission code | ASCII code |
| Transmission code configuration | <p>Start bit (1-bit) Parity bit (1-bit)</p> <p>Stop bit (1-bit)</p> <p>2⁰ 2¹ 2⁶ P</p> <p>Data (7-bit) (Even parity)</p> |
| Transmission code outgoing sequence | Sent out from the lowest bit (2 ⁰) in character units |
| Error detection | Vertical parity check, overrun check, framing check |
| Interface | Conforms to RS-232C |
| Control procedure | H-series dedicated procedure (high protocol) |
| Startup system | One-sided startup using the host side command |

* Since ER signal cannot be controlled, be sure to use command or another I/O to disconnect line.

Table 10.11 List of port 1 signals when a modem is connected

| Pin No. | Signal abbreviation | Direction | | Meaning |
|---------|---------------------|-----------|-------|--|
| | | CPU | Modem | |
| 1] | SG1 | ← | — | Signal ground |
| 2] | CD1 | ← | — | Carrier receive in-progress notification signal Connected to CD in the modem. |
| 3] | ER1 | — | → | Communication enabled signal of the terminal |
| 4] | ER2 | — | → | Unused |
| 5] | SD1 | — | → | Data sent by the CPU Connected to SD in the modem. |
| 6] | RD1 | ← | — | Data received by the CPU Connected to RD in the modem. |
| 7] | DR1 | ← | — | Communication enabled signal of the modem Connected to DR in the modem. |
| 8] | RS1 | — | → | Transmission request signal Connected to RS in the modem. |




Figure 10.8 Cable connection between a modem (25 pin socket) and port 1

10.4.3 Additional task code

The existing task codes are supported, and ladder disconnection processing is supported as an additional function. The specification is the same as the current post communication (destination processing, ladder disconnection processing), except for the NCU control.

Line disconnection task code

Line disconnection request

| |
|-----|
| H1C |
|-----|

Response (normal response only)

| | |
|-----|-----|
| H00 | H1C |
|-----|-----|

10.4.4 AT commands

In AT commands, an instruction sent to the modem from the host is called a "command" and the character string in response to the "command" returned to the host from the modem is called a "result code".

AT commands always begin with the character string "AT" and a return code is input at the end of the command. However, A/ is excluded. The command that follows after the "AT" can have multiple inputs in a single line.

(1) Format

1] AT command format

| | | | |
|---|---|---|----|
| A | T | command parameter command parameter | CR |
|---|---|---|----|

2] Result code format

| | | | | |
|----|----|--------------------|----|----|
| CR | LF | result code (word) | CR | LF |
|----|----|--------------------|----|----|

| | |
|----------------------|----|
| Result code (number) | CR |
|----------------------|----|

(2) List of commands (extract)

1] AT commands

| Command | Function overview | | Example |
|----------------------|---|---|-------------------------|
| AT | Automatically recognizes data format | | — |
| A/ | Re-executes the response directly preceding | | — |
| ATDmm | Dial | | ATD12345678 |
| ATHn | Line ON/OFF | 0: On hook (disconnect) 1: Off hook | ATH0 ATH1 |
| ATPn | Pulse setting | 0, 1: 10 pps 2: 20 pps | ATP0, ATP1 ATP2 |
| ATT | Tone setting | | ATT |
| ATS _n = X | Sets S register value | | ATS0 = 0 |
| ATVn | Result code display format | 0: Number 1: Word | ATV0 ATV1 |
| AT&Cn | CD signal control | 0: Always on 1: Depends on the carrier of counter-party modem | AT&C0 AT&C1 |
| AT&Dn | ER signal control | 0: Always on 2: Turning from on to off during communication disconnects line 3: Turning from on to off resets the software | AT&D0 AT&D2 AT&D3 |
| AT&Sn | DR signal | 0: Always on 1: Depends on sequence 2: Depends on CD signal | AT&S0 AT&S1 AT&S2 |
| AT&Rn | RI (CI) signal control | 0: Turns on from calling start until communication begins 1: Turns on from calling start until communication ends 2: Turns on/off in synchronization with the call signal | AT&R0 AT&R1 AT&R2 |

2] S register

| S register | Set value | Function |
|------------|--------------------------------------|--|
| S0 | 0 no automatic reception 1 to 255 | Setting for automatic reception/reception ring count |
| S2 | 0 to 127 (43 [+]) | Escape code setting |
| S3 | 0 to 127 (13 [CR]) | CR code setting |
| S4 | 0 to 127 (10 [LF]) | LF code setting |


3] Result codes

| Number format | Word format | Meaning |
|---------------|---------------|-----------------------|
| 0 | OK | Normal execution |
| 1 | CONNECT | Connection complete |
| 2 | RING | Reception detected |
| 3 | NO CARRIER | Line disconnected |
| 4 | ERROR | Command error |
| 5 | CONNECT 1200 | 1,200 bps connection |
| 6 | NO DIAL TONE | Cannot hear dial tone |
| 7 | BUSY | Busy signal detected |
| 8 | NO ANSWER | No tone heard |
| 10 | CONNECT 2400 | 2,400 bps connection |
| 11 | CONNECT 4800 | 4,800 bps connection |
| 12 | CONNECT 9600 | 9,600 bps connection |
| 13 | CONNECT 14400 | 14,400 bps connection |

(3) Sequence

An example of a communication sequence using the Omron-made modem ME3314A is given below.

(a) Reception sequence



- 1] The PLC generates the AT command that performs the initial setting of the modem.
- 2] If initial setting is OK, the modem returns "0."
- 3] When the PLC is in reception wait status and detects the result code "2" three times, it connects the modem.

(b) Disconnect sequence



The PLC disconnects the line when the result code "3" is returned.


Note 1: Since the modem initial setup sets only minimal items from the PLC side, connect a personal computer and perform necessary settings before making the connection. (Set the DR signal to always on.)

Note 2: The CPU version showed by Table 10.12 support time out setting at special internal output (WRF03B). The default setting is “no time out”. Refer to the “Chapter 13 Special Internal Outputs” for details.

Table 10.12 CPU version

| CPU type | CPU516/548 | CPU448 | CPU316A | CPU308A | CPU208A |
|---------------------------------|------------|--------|---------|---------|---------|
| ROM version (WRF050, WRF051) | All | C416 | B205 | A205 | B105 |

Note: the time out of the former CPU version of Table 10.12 is fixed 20ms EH-CPU104/104A do not support modem control function.



Note

Special internal outputs(WRF01A,WRF03B,WRF03C) about modem connection are maintained by the battery during power failuer.It is not necessary to set up every time the power is turned ON. However, when a battery error occurs, please re-set up.
















10.5 Port and Peripheral Unit Connection

Tables 10.13 and 10.14 show the settings of the mode setting switches and the connecting cables to connect a peripheral unit to ports 1 and 2 of the EH-150, respectively.

Table 10.13 Settings of the mode setting switches for connecting peripheral units

| Condition | | A | B | C | D | E | F |
|---------------|--------|--------------------------------------|-------------------------------------|--------------------------------|---|---------------------------------------|--------------------------------------|
| PORT | SW | Windows® LADDER EDITOR (DOS/V) | Windows® LADDER EDITOR (PC98) | DOS LADDER EDITOR (PC98) | DOS LADDER EDITOR (AT compatible) | LADDER EDITOR For GPCL / HILDRL | Programmer (PGM-GPH) (PGM-CHH) |
| 1 | 8 | OFF | OFF | OFF | OFF | Cannot connect | Cannot connect |
| | 7 | OFF | OFF | OFF | OFF | | |
| | 6 | — | — | — | — | | |
| | 5 | ON | ON | ON | ON | | |
| | 4 | OFF | OFF | ON | ON | | |
| | 3 | ON | ON | ON | ON | | |
| | 2 | — | — | — | — | | |
| | 1 | OFF | OFF | OFF | OFF | | |
| | Toggle | — | — | — | — | | |
| 2 | 8 | OFF | OFF | OFF | OFF | OFF | OFF |
| | 7 | OFF | OFF | OFF | OFF | OFF | OFF |
| | 6 | OFF | OFF | OFF | OFF | OFF | OFF |
| | 5 | — | — | — | — | — | — |
| | 4 | — | — | — | — | — | — |
| | 3 | — | — | — | — | — | — |
| | 2 | — | — | — | — | — | — |
| | 1 | OFF | OFF | OFF | OFF | OFF | OFF |
| | Toggle | ON | ON | OFF | OFF | OFF | ON |
| Software type | | HLW-PC3 | HLW-PC3 | HL-PC3 | HL-AT3E | HL-GPCL HILDRL | (Built-in programmer) |
| Cable type | | WVCB02H + EH-RS05 | WPCB02H + EH-RS05 | PCCB02H + EH-RS05 | EH-VCB02 | GPCB02H + EH-RS05 | PGCB02H + EH-RS05 |
| | | EH-VCB02 | | | | | |

Table 10.14 Peripheral unit connection configuration

| Peripheral unit | Cable | |
|--|--|--|
| GPCL01H (LADDER EDITOR, HI-Ladder)  | GPCB02H  | EH-RS05  |
| LADDER EDITOR  | PCCB02H  | EH-RS05  |
| LADDER EDITOR for Windows®  | WPCB02H  WVCB02H  | EH-RS05  |
| | EH-VCB02  | |
| Pro-H  | WVCB02H  | EH-RS05  |
| | EH-VCB02  | |

10.6 Connection method for RS-422/485 communication

Communication can be performed with an interface of RS-422/485 at the port 1 of the EH-150. Using the H series' dedicated control procedure (high protocol) or general port commands (TRNS 0 and RECV 0), communication of 1:N stations can be performed. Figures 10.9 and 10.10 show examples when a connection is made for 1:N stations at the port 1. Note that, for the connection for communication in 1:1 mode, only the first EH-150 in these figures is connected.




Figure 10.9 Connection for 1:n station communication by RS-422




Figure 10.10 Connection for 1:n station communication by RS-485

Chapter 11 Real Time Clock and Memory Board

11.1 Real Time Clock Function

The EH-CPU208/308/316/448 includes a function that manages the time and date of PLC data. The clock function can be operated with either special internal output or a task code.

Clock data is retained by battery power. Note that the battery is not connected when the module is shipped. When using the clock function, connect the battery and set the clock data.

Clock function is not supported by EH-CPU104(A).

11.1.1 Operation using a special internal output

(1) Reading clock data

By turning the read request (R7F8) on, the clock data at the time of the request is stored in the read value area (WRF01B to WRF01F).

(2) Clock data setting

The clock data setting is done by first set the data to store in the set value area (WRF01B to WRF01F), and then turning on the setting request (R7F9). At this time, if there is an error in the set value, the setting data error (R7FB) turns on. When the setting request (R7F9) turns off and the setting data error (R7FB) is off, setting is complete.

(3) Clock data ± 30 seconds adjustment

By turning on the ± 30 second adjustment request (R7FA), the seconds value will be set as follows depending on the value at this time.

- When the digit for seconds is 00 to 29: the digit becomes 00
- When the digit for seconds is 30 to 59: the time becomes +1 minute and the digit for seconds becomes 00.

(4) Defining special internal output

- Operation bit

| Item | I/O number | Name | Function |
|------|------------|---|---|
| 1 | R7F8 | Request to read calendar and clock data | Calendar and clock data is read out to WRF01B-F01F. |
| 2 | R7F9 | Request to write calendar and clock data | Calendar and clock data in WRF01B-F01F is written to the current data in WRF00B-F00F. |
| 3 | R7FA | Clock ± 30 seconds adjustment request | Sets the second digits of the RTC to 00. |
| 4 | R7FB | Calendar and clock setting data error | Turns on when the setting data is abnormal. |

- Current data monitor area : Current data of the clock given always (all BCD data).

| Item | I/O number | Name | Description |
|------|------------|-----------------|-----------------------------|
| 1 | WRF00B | Year | 4-digit year [yyyy] |
| 2 | WRF00C | Month/day | [mmdd] |
| 3 | WRF00D | Day of the week | 0 to 6 : Sunday to Saturday |
| 4 | WRF00E | Hour | [hhmm] (24-hour system). |
| 5 | WRF00F | Seconds | [00ss] |

- Reading/writing area : Clock data to be read or written (all BCD data).

| Item | I/O number | Name | Description |
|------|------------|-----------------|-----------------------------|
| 1 | WRF01B | Year | 4-digit year [yyyy] |
| 2 | WRF01C | Month/day | [mmdd] |
| 3 | WRF01D | Day of the week | 0 to 6 : Sunday to Saturday |
| 4 | WRF01E | Hour | [hhmm] (24-hour system). |
| 5 | WRF01F | Seconds | [00ss] |

Note 1: Day of the week data is as follows (3 upper digits are always 000):

0 - Sunday, 1 - Monday, 2 - Tuesday, 3- Wednesday, 4- Thursday, 5- Friday, 6 - Saturday

11.1.2 Operation using task codes

The following can be performed with the clock setting and reading task codes.

- Read clock data
- Set clock data
- Clock data ± 30 seconds adjustment

Refer to the task code list (Appendix 3) for more detail on task codes.

11.2 Memory Board Function

The EH-CPU308(A)/316(A)/448/516/548 have the program transfer function for transferring and comparing programs between the CPU and either the EH-MEMP or EH-MEMD memory board, and the data logging function via the FUN command from user programs using the EH-MEMD memory board. Table 11.1 shows the DIP switch settings of the EH-MEMP and EH-MEMD memory boards for switching to each mode.

* The EH-CPU104/104A/208/208A do not support the memory board function.

Table 11.1 Operation modes settings with dip switch of memory board

| Function | SW4 | SW3 | SW2 | SW1 | Operation details | Remarks |
|------------------|-----|-----|---------|-----|---|---------|
| Program transfer | | | | | Starts up in the normal operating mode (Invalid memory board) | |
| | | | | ON | From memory board to CPU (Program transfer) | |
| | | | ON | | From CPU to memory board (Program transfer) | |
| | | | ON | ON | Between memory board and CPU (Check program) | |
| | | ON | | | Starts up in the normal operating mode (Invalid memory board) | * |
| | | ON | | ON | From memory board to CPU (Program transfer) | * |
| | | ON | ON | | Dip switch setting error | * |
| | | ON | ON | ON | Between memory board and CPU (Check program) | * |
| Data logging | ON | | Invalid | | Starts up in the normal mode (Data logging command can be executed) | |
| | ON | ON | Invalid | | Starts up in the normal mode (Data logging command can be executed) | * |

*: If the SW3 is ON, writing to the memory board is prohibited.

In the case of program transfer mode, the dip switch setting becomes effective only after turning on the power. In the case of data logging mode, SW3 becomes effective in real time. (However, if the setting is changed while a command is being executed, the new setting becomes effective upon execution of the next command.)

11.2.1 Program transfer function

The EH-CPU308/308A/316/316A/448 have the program transfer function for transferring and comparing programs between the CPU and either the EH-MEMP or EH-MEMD memory board by setting the DIP switches of the memory board in advance and turning on the power. Since the CPU starts up in a special mode, the CPU will not switch to the RUN mode in this case. Table 11.2 shows the operation modes that can be executed between each CPU model and the EH-MEMP/EH-MEMD memory board. As shown in Table 11.2, the maximum program size that can be transferred to the EH-MEMD memory board is 16 k steps. Thus, to transfer a program of larger than 16 k steps and a maximum of 48 k steps in the EH-CPU448, use the EH-MEMP memory board.

Table 11.2 EH-MEMP/MEMD function

| Item | EH-MEMP | EH-MEMD |
|---------------------------------|----------------|----------------|
| User program size | Max. 48 k step | Max. 16 k step |
| Data memory size | - | 384 k words |
| Program copy (CPU→MEMP/D) | ✓ | ✓ |
| Program copy (CPU←MEMP/D) | ✓ | ✓ |
| Program verify (CPU←→MEMP/D) | ✓ | ✓ |
| Data logging | - | ✓ |

Table 11.3 shows the LED displays when an error occurs during the execution of the program transfer function.

Table 11.3 CPU LED indications in the program transfer mode

| Operation mode | Memory board → CPU | | Memory board ← CPU | | Memory board = CPU | |
|--------------------------------------|--------------------|-----|--------------------|-----|--------------------|-----|
| | RUN | ERR | RUN | ERR | RUN | ERR |
| Dip switch setting error | — | — | ● | ◐ | — | — |
| Sum error in memory board | ● | ○ | — | — | ● | ○ |
| Sum error in CPU memory | — | — | ◐ | ○ | ◐ | ○ |
| Memory size error | ◐*1 | ◐*1 | — | — | — | — |
| Transfer and checking in progress | ◐ | ● | ◐ | ● | ◐ | ● |
| FLASH error (inside memory board) *4 | — | — | ○ | ◐ | — | — |
| Unmatched check result | ● | ◐ | ● | ◐ | ● | ◐ |
| Normal completion | ○→● | ● | ○→● | ● | ○→● | ● |

○: ON ●: OFF ◐: Flashing (1 s ON, 1 s OFF) ◑: Flashing (500 ms ON, 500 ms OFF)

◒: Flashing (250 ms ON, 250 ms OFF) ○→●: 3 s OFF after ON

*1: RUN and LED of ERR flash at the same time

*2: Erase error and write error of FLASH

11.2.2 Logging Function

The EH-CPU 308(A)/316(A)/448(A)/516/548 provides the function for log data using the EH-MEMD.

* This function cannot be used with the EH-MEMP.

(1) Log commands

There are four types of log commands, as shown below.

| | |
|-------------------------------|----------------------------------|
| FUN 210 (s) * (LOGIT (s)) | Initial setting for data logging |
| FUN 211 (s) * (LOGWRT (s)) | Log data write |
| FUN 212 (s) * (LOGCLR (s)) | Log data clear |
| FUN 213 (s) * (LOGRED (s)) | Log data read |

* () indicates the display when the LADDER EDITOR is used.

(2) Overview of logging function

The logging function is used to transfer a group of specified data groups (word internal output/external input) to the log data area (memory board) as a single log, or read a group of data stored in the log data area.


Use example:

1] FUN 210 (Initial setting for data logging)

Sets a total of 8 words from three groups of the log data including WR0000 through WR0002 (3 words), WX0000 and WX0001 (2 words), and WM0000 through WM0002 (3 words), as a data for a single log.


2] FUN 211 (log data write)

Writes to the log data area (memory board) the log data for a single log specified in the initial setting in 1].



3] FUN 213 (log data read)

Reads to the specified destination after WR0003 the contents of the log data area written in 2] by the amount of data for a single log (8 words) starting from the head of the log data area.



4] FUN 212 (log data clear)

Clears the contents of the log data area in the memory board.

(3) Applicable log area

The table below shows the I/O areas that can be used for logging and their allowable ranges.

| | Symbol | Allowable range | | |
|----------------------|--------|------------------|----------------|----------------|
| | | EH-CPU308/308A | EH-CPU316/316A | EH-CPU448 |
| Word external input | WX | 16 words | | Cannot be used |
| CPU link area 1 | WL | WL0 to WL3FF | | |
| CPU link area 2 | WL | WL1000 to WL13FF | | |
| Word internal output | WR | WR0 to WR43FF | WR0 to WR57FF | WR0 to WRC3FF |
| | WM | WM0 to WM3FFF | | |

* If an area outside the corresponding range is specified, the DER (R7F4) bit is turned ON and the processing will not be performed.

(4) Log data size and write interval

- Size of log data area
384 K (393,216) words
- Size of log data
Data between 1 and 128 words can be specified for a single log.
- Write interval
The table below shows the number of words in a single log and the corresponding logging interval.


| | Minimum | Intermediate | Maximum |
|-----------------------------|----------------|---------------------|-------------------|
| Log data size (words/log) | 1 word per log | n words per log | 128 words per log |
| Minimum write interval (ms) | Approx. 10 ms | Approx. (5n + 5) ms | Approx. 645 ms |

* In the above table, n indicates an integer between 1 and 128.

No new data can be logged in between the write intervals (ms) shown above.

(5) Log write (FUN 211) time chart

The diagram below shows the relationship between the log write control bit table (EXECUTE flag, RUN flag, WRITE flag, ABNORMAL COMPLETION flag) and the execution of the FUN 211 (log write).



The EXECUTE flag rises 1]. However, since the initialization result indicates that execution of the FUN 211 is not allowed, the FUN 211 turns on 2] the ABNORMAL COMPLETION flag 3].

A log write parameter error is found during the processing of the FUN 210 4]. As a result, the initialization result does not indicate that execution of the FUN 211 is allowed.

The write parameters are correctly set 5]. As a result, the initialization result indicates that execution of the FUN 211 is allowed 6].

The FUN 211 detects 8] the rise of the EXECUTE flag 7] and checks if the execution is allowed. Since the check result is normal, the RUN flag is turned on 9] and the log data is stored temporarily. When all data has been stored, the WRITE flag is turned on 10] and the log data is written to the memory board (starting of write).

When the writing of data for the first log is completed 11], the RUN flag and WRITE flag are turned off 12].


Since the EXECUTE flag is still on, writing of the second log is started 13].

The FUN 211 detects 14] the fall of the EXECUTE flag 15]. However, the processing continues since the writing of data for the second log is not completed yet.

When the writing of data for the second log is completed 16], the RUN flag and WRITE flag are turned off 17].

(6) Log clear (FUN 212) time chart

The diagram below shows the relationship between the log clear parameter bit table (EXECUTE flag, RUN flag, ABNORMAL COMPLETION flag) and the execution of the FUN 211 (log clear).



The EXECUTE flag rises 1]. However, since the initialization result indicates that execution of the FUN 211 is not allowed, the FUN 211 turns on 2] the ABNORMAL COMPLETION flag 3].

A log clear parameter error is found during the processing of the FUN 210 4]. As a result, the initialization result does not indicate that execution of the FUN 211 is allowed.

The log clear parameters are correctly set 5]. As a result, the initialization result indicates that execution of the FUN 211 is allowed 6].

The FUN 212 detects 8] the rise of the EXECUTE flag 7] and checks if the execution is allowed. Since the check result is normal, the RUN flag is turned on 9] and the log data is cleared.

When the log data clear is completed 11], the EXECUTE flag 12] and the RUN flag 13] are turned off.

The FUN 212 detects 15] the rise of the EXECUTE flag 14] and starts the second data clear.

The FUN 212 detects 16] the fall of the EXECUTE flag 17]. However, since the second data clear is not completed yet, the processing continues.

When the second data clear is completed, the FUN 212 turns off 18] the RUN flag 19].

(7) Log error details

When started in the logging mode, the system checks the log data upon power ON. If the system detects an error during the check, it sets to the special internal output R7FE or WRF07F an applicable error code from among the following error codes, and then executes the program shown below. At the same time, the CPU error code "A0" is set to the special internal output WRF000. The table below shows the description of each error.

| CPU error code | Special internal output | | Error code | Description of error |
|----------------|-------------------------|--------|----------------|--|
| A0 | R7FE = 1 | WRF07F | H0001 | Different memory board from the one previously installed |
| | | | H0002 to H0009 | Invalid log data |
| | | | H00FF | Memory board cannot be accessed |

(8) Corrective actions to be taken upon detection of log error

When the system detects any of the log errors described in (7), take appropriate actions as shown below.

When H0001 occurred:

Reinstall the memory board previously installed, and restart the system.

If a new memory board is installed, clear the log data using the log data clear command (FUN 212).

When any of the errors between H0002 and H0009 occurred:

Clear the log data using the log data clear command (FUN 212), and then restart the system.

When H00FF occurred:

Check if the memory board is properly installed, and then restart the system. If the error persists, there may be a hardware error in the memory board.

MEMO

Chapter 12 Error Code List

12.1 Error Codes

The table below indicates the self-diagnostic error codes. (Refer to Chapter 15 Troubleshooting for corrective action.) Error codes are output as a hexadecimal to the special internal output WRF000. (This special internal output is saved during a power failure, and is retained even when the cause of the error disappears. Also, when more than one error is generated, the one that is classified with the greatest severity is stored.)

Note: LED example

○ : ON ● : OFF ◐ : Flashing (1 s ON, 1 s OFF) ◑ : Flashing (500 ms ON, 500 ms OFF) ◒ : Flashing (250 ms ON, 250 ms OFF)

| Error code | Error name [detection timing] | Classifi- cation | Nature of error | RUN LED | ERR LED | Ope- ration | Related special internal output | |
|------------|--|---------------------|---|------------|------------|----------------|------------------------------------|--------|
| | | | | | | | Bit | Word |
| 11 | System ROM error [when power turns on] | Serious failure | The system ROM has a sum error or cannot be read | ● | ○ | Stops | R7DB | — |
| 12 | System RAM error [when power turns on] | Serious failure | System RAM cannot be read and written properly | ● | ○ | Stops | R7DB | — |
| 13 | Micro processor error [always checking] | Serious failure | Address error interrupt, undefined command interrupt occurred in the micro computer | ● | ○ | Stops | R7C8 | — |
| 15 | System bus time out error [when bus is accessed] | Serious failure | Micro computer detects a system bus time out | ● | ○ | Stops | R7D8 | — |
| 16 | System program abnormal [always checking] | Serious failure | System program in FLASH memory has a sum error | ● | ○ | Stops | R7C8 | — |
| — | Power off Power error [always checking] | Serious failure | No power supply from the power module | ● | ● | Stops | — | — |
| — | Microcomputer overload error [Constantly checked] | Serious failure | The watchdog timer detected a microcomputer overload because the microcomputer did not operate according to program (the microcomputer is not functioning correctly). | —*1 | ○ | Stops | — | — |
| 22 | Sequence processor error | Medium failure | The microcomputer detected a sequence processor did not operate. (the sequence processor is not functioning correctly). | ● | ○ | Stops | R7DB | — |
| 23 | Undefined code [check during operation] | Medium failure | Unknown code is found by microprocessor. | ◐ | ○ | Stops | R7C9 | — |
| 27 | Data memory error [when power ON, at initialization] | Medium failure | Data memory cannot be read/written properly. | ● | ○ | Stops | — | — |
| 31 | User memory abnormal [when power turns on, when RUN starts, when parameters are changed, at initialization] | Medium failure | A sum error is detected in user memory or RUNNING memory | ◐ | ○ | Stops | R7CA | — |
| 33 | User memory size error [when RUN starts] | Medium failure | User program capacity set by the parameter is larger than actual user memory capacity | ◐ | ○ | Stops | R7CC | — |
| 34 | Grammar/assemble error [when RUN starts, online change in RUN] | Medium failure | There is a grammar error in the user program | ◑ | ○ | Stops | R7D4 | WRF001 |
| 41 | I/O information verify error [always checking] | Minor failure | I/O assignment information and actual loading of module do not match | ◑ | ○ | Stops *2 | R7CD | WRF002 |

*1: Condition prior to error occurrence is restored. (If operation was in progress, the RUN LED turns ON; if operation was stopped, the RUN LED turns off)

*2: Depending on the run parameter setting, operation can continue even when an abnormal occurs.

| Error code | Error name [detection timing] | Classification | Nature of error | RUN LED | ERR LED | Operation | Related special internal output | |
|------------|--|----------------|---|---------|---------|-----------|---------------------------------|----------------------------------|
| | | | | | | | Bit | Word |
| 43 | Remote abnormal [always checking] | Minor failure | <ul style="list-style-type: none"> I/O assignment verify mismatch occurs in the remote slave station module Communication error occurs between the remote master station module and CPU There is an error in the remote master station module, and transmission to the slave station has stopped | | | Stops *2 | R7D0 | WRF006 WRF080 to WRF0DF |
| 44 | Overload error (Normal scan) [during operation] | Minor failure | Execution time for normal scan exceeded the overload check time set by the parameter | | | Stops *2 | R7D1 | — |
| 45 | Overload error (periodic scan) [periodic processing] | Minor failure | Execution time for periodic scan exceeded the execution period | | | Stops *2 | R7D2 | — |
| 47 | I/O assignment points over [when power turns on, when RUN starts, during RUN, when parameters changed] | Minor failure | Slot number exceeds the possible range. | | | Stops *2 | R7D6 | — |
| 51 | I/O module abnormal [always checking] | Warning | <ul style="list-style-type: none"> High function module, communication module faults out | — *1 | | Runs | R7D5 | WRF005 WRF080 to WRF0DF |
| 52 | I/O transmission error [when high function module is transmitting, when transfer command is being executed] | Warning | <ul style="list-style-type: none"> Error occurs during high function module transmission TRNS, RECV command parameter error | — *1 | | Runs | — | — |
| 53 | I/O inappropriate assignment [check during operation] | Warning | Assignment of communication module is incorrect | — *1 | | Runs | — | — |
| 54 | Communication module abnormal [always checking] | Warning | Communication module hardware abnormal | — *1 | | Runs | R7D7 | WRF004 |
| 55 | Communication module transmission error [when a peripheral device is connected to the communication module] | Warning | Error occurred during transmission to the communication module | — *1 | | Runs | R7D7 | WRF004 |
| 57 | Communication module I/O assignment over [always checking] | Warning | The number of communication module assignments exceeds the maximum | — *1 | | Runs | R7DD | — |
| 58 | Communication module I/O verify error [always checking] | Warning | <ul style="list-style-type: none"> Mismatch between communication module assignment information and module loading Communication module hardware error | — *1 | | Runs | R7CE | WRF003 |
| 59 | Link module abnormal [always checking] | Warning | <ul style="list-style-type: none"> Link module hardware abnormal Link parameter abnormal | — *1 | | Runs | R7DE | WRF007 WRF0E0 to WRF19F |
| 61 | Port 2 transmission error (parity) [when transmitting] | Warning | Parity error detected during transmission | — *1 | | Runs | — | — |
| 62 | Port 2 transmission error (framing/overflow) [when transmitting] | Warning | Framing error or overrun error detected during transmission | — *1 | | Runs | — | — |
| 63 | Port 2 transmission error (time out) [when transmitting] | Warning | Time out error detected during transmission | — *1 | | Runs | — | — |

*1: Condition prior to error occurrence is restored. (If operation was in progress, the RUN LED turns ON; if operation was stopped, the RUN LED turns off)

*2: Depending on the run parameter setting, operation can continue even when an abnormal occurs.

| Error code | Error name [detection timing] | Classification | Nature of error | RUN | ERR | Operation | Related special internal output | |
|------------|--|----------------|--|------|---|-----------|---------------------------------|--------|
| | | | | LED | LED | | Bit | Word |
| 64 | Port 2 transmission error (protocol error) [when transmitting] | Warning | Protocol (transmission procedure) error detected during transmission | — *1 |  | Runs | — | — |
| 65 | Port 2 transmission error (BCC error) [when transmitting] | Warning | Sum error detected during transmission | — *1 |  | Runs | — | — |
| 67 | Port 1 transmission error (parity) [when transmitting] | Warning | Parity error detected during transmission | — *1 |  | Runs | — | — |
| 68 | Port 1 transmission error (framing/overflow) [when transmitting] | Warning | Framing error or overrun error detected during transmission | — *1 |  | Runs | — | — |
| 69 | Port 1 transmission error (time out) [when transmitting] | Warning | Time out error detected during transmission | — *1 |  | Runs | — | — |
| 6A | Port 1 transmission error (protocol error) [when transmitting] | Warning | Protocol (transmission procedure) error detected during transmission | — *1 |  | Runs | — | — |
| 6B | Port 1 transmission error (BCC error) [when transmitting] | Warning | Sum error detected during transmission | — *1 |  | Runs | — | — |
| 71 | Battery error [always checking] | Warning | <ul style="list-style-type: none"> Battery voltage dropped below specified value Battery not installed | — *1 |  | Runs | R7D9 | — |
| | FLASH memory error (CPU448(A)/516/548) *3 [when program writing is executed] | Warning | Data cannot be written to the backup memory. | — *1 |  | Runs | R7D9 | — |
| 94 | Port 1 No modem response (when modem is connected) | Warning | There is no response from the modem connected to the port. | — *1 |  | Runs | — | — |
| 95 | Port 1 Dial busy (when modem is connected) | Warning | The modem of the opposite party is communicating with another terminal or not ready for communication. | — *1 |  | Runs | — | — |
| 96 | Port 1 CS ON time out (when modem is connected) | Warning | The CS signal of the modem connected to the port does not turn on within the designated time. | — *1 |  | Runs | — | — |
| 97 | Port 1 Modem time out *4 (when modem is connected) | Warning | The modem connected to the port does not respond the complete of connection within the setting time (WRF03B). | — *1 |  | Runs | — | — |
| A0 | Data logging error | Warning | Detected an error in the memory board or log data. | — *1 |  | Runs | R7FE | WRF07F |

*1: Condition prior to error occurrence is restored. (If operation was in progress, the RUN LED turns ON; if operation was stopped, the RUN LED turns off)

*2: Depending on the run parameter setting, operation can continue even when an abnormal occurs.

*3: When the CPU fails in writing to the backup memory, EH-CPU448 does the treatment which is the same as the battery error. A backup memory error occurred to the CPU module if the same error after the battery exchange as well seems to occur. In this case, be careful because your program and so on isn't stored.

*4: This error code is supported by only CPU448 (Software version C416 later), EH-CPU316A (Software version B205 later), EH-CPU308A (Software version A205 later) and EH-CPU208A (Software version B105 later), CPU516/548.

How to clear the error code

Set 1 in the special internal output R7EC to clear the error code.

It is cleared also by pressing the reset switch for retentive area (R.CL) on the front of the CPU while CPU is in stop mode. Please note that if the reset switch pressed, all the retentive area is cleared.

12.2 Grammar and Assemble Error Codes

Descriptions of the grammar/assemble error codes are given below. The error codes are output as a hexadecimal to the internal output WRF001.

| Error code | Error item | Description of error | Corrective action |
|------------|---------------------------|---|--|
| H0001 | Double definition of LBL | There are 2 or more LBL commands with the same number in the program | Limit the LBL command that has 2 or more of the same number to 1. |
| H0002 | Double definition of FOR | There are 2 or more FOR commands with the same number in the program | Limit the FOR command that has 2 or more of the same number to 1. |
| H0003 | Double definition of NEXT | There are 2 or more NEXT commands with the same number in the program | Limit the NEXT command that has 2 or more of the same number to 1. |
| H0004 | Double definition of SB | There are 2 or more SB commands with the same number in the program | Limit the SB command that has 2 or more of the same number to 1. |
| H0005 | Double definition of INT | There are 2 or more INT commands with the same number in the program | Limit the INT command that has 2 or more of the same number to 1. |
| H0010 | END undefined | There is no END command prior to the INT, SB commands | Define the END command before the INT or SB command. |
| H0011 | RTS undefined | There is no RTS command corresponding to the SB command | Define the RTS command after the SB command. |
| H0012 | RTI undefined | There is no RTI command corresponding to the INT command | Define the RTI command after the INT command. |
| H0013 | SB undefined | There is no SB command corresponding to the RTS command | Define the SB command before the RTS command. |
| H0014 | INT undefined | There is no INT command corresponding to the RTI command | Define the INT command before the RTI command. |
| H0020 | RTS area error | There is an RTS command in the normal scan area or periodic scan program area | Define the RTS command within the subroutine area. |
| H0021 | RTI area error | There is an RTI command in the normal scan area or subroutine program area | Define the RTI command within the interrupt scan area. |
| H0022 | END area error | There is an END command in the periodic scan area or subroutine program area | Define the END command at the end of the normal scan area. |
| H0023 | CEND area error | There is a CEND command in the periodic scan area or subroutine program area | Define the CEND command within the normal scan area. |
| H0030 | RTS start condition error | There is a start condition in the processing box that contains an RTS command | Delete the startup condition of the processing box. |
| H0031 | RTI start condition error | There is a start condition in the processing box that contains an RTI command | Delete the startup condition of the processing box. |
| H0032 | END start condition error | There is a start condition in the processing box that contains an END command | Delete the startup condition of the processing box. |

12.3 Operation Error Codes

If an error occurs when a control command is executed, “1” is set in the operation error (ERR) special internal output “R7F3” and an error code indicating the nature of the error is set in WRF015.

To do a zero clear of the operation error, execute “R7F3=0” using forced setting from the program or peripheral device.

To do a zero clear of the error code, execute “WRF015=0” using forced setting from the program or peripheral device.

| Error code | Error name | Description of error | Originating command |
|------------|------------------------------|---|---------------------|
| H0013 | SB undefined | SBn command corresponding to the command number n in the CALn command is not programmed | CAL |
| H0015 | LBL undefined | LBLn command corresponding to the command number n in the JMPn, CJMPn commands is not programmed | JMP CJMP RSRV |
| H0016 | FOR undefined | FORn command corresponding to the command number n in the NEXTn command is not programmed | NEXT |
| H0017 | NEXT undefined | NEXTn command corresponding to the command number n in the FORn command is not programmed | FOR |
| H0040 | LBL area error | LBLn command corresponding to the command number n in the JMPn, CJMPn commands is not programmed in the same program area | JMP CJMP RSRV |
| H0041 | CAL nesting overflow | There are more than 6 levels of subroutine nesting | CAL |
| H0042 | CAL undefined | RTS command was executed without executing a CAL command | RTS |
| H0043 | FOR to NEXT error | There is a NEXTn with the same command number n prior to the FORn command | FOR |
| H0044 | NEXT area error | There is no NEXTn command with the same command number n as the FORn command, in the same program area | FOR |
| H0045 | FOR to NEXT nesting overflow | The FORn and NEXTn commands are not nested | FOR |
| H0046 | FOR nesting overflow | There are more than 6 nesting levels of FOR to NEXT | FOR NEXT |

MEMO





Chapter 13 Special Internal Outputs

The EH-150 has a special internal output area for performing status display and various other settings. The special internal output area is always kept as power failure memory.

13.1 Bit Special Internal Output Area

Definitions of the bit special internal output area (R7C0 to R7FF) are given below.

| No. | Name | Meaning | Description | Setting condition | Resetting condition |
|------|--|--|---|-------------------|---|
| R7C0 | Continue when overload error occurs (normal scan) | 0: Stop running when overload error occurs 1: Continue running when overload error occurs | Designates continue/stop running when a normal scan overload error occurs | Set by user | Cleared by user or cleared when retentive area cleared. |
| R7C1 | Continue when overload error occurs (periodic scan) | 0: Stop running when overload error occurs 1: Continue running when overload error occurs | Designates continue/stop running when a periodic-scan overload error occurs | | |
| R7C2 | Continue when overload error occurs (interrupt scan) | 0: Stop running when overload error occurs 1: Continue running when overload error occurs | Designates continue/stop running when an interrupt-scan overload error occurs | | |
| R7C3 | REMOTE RUN allowed | 0: RUN prohibited 1: RUN allowed | Designates whether operation based on the task code is allowed | | |
| R7C4 | REMOTE STOP allowed | 0: STOP prohibited 1: STOP allowed | Designates whether stop based on the task code is allowed | | |
| R7C5 | Undefined | Do not use. | | | |
| R7C6 | Undefined | Do not use. | | | |
| R7C7 | Modification during RUN allowed | 0: Modification during RUN prohibited 1: Modification during RUN allowed | Designates whether online change in RUN is allowed in the user program | Set by user | Cleared by user or cleared when retentive area cleared. |
| R7C8 | Serious failure flag | 0: No serious failure 1: Serious failure | Indicates whether there is an abnormal in the system | Set by system | |
| R7C9 | Microcomputer abnormal | 0: Normal 1: Abnormal | Indicates whether there is an abnormal in the microcomputer | | |
| R7CA | User memory abnormal | 0: Normal 1: Abnormal | Indicates whether there is an abnormal in the user memory | | |
| R7CB | Undefined | Do not use. | | | |
| R7CC | Memory size over | 0: Normal 1: Abnormal | Indicates whether the capacity set by the parameter exceeds loaded memory capacity | Set by system | Cleared by user or cleared when retentive area cleared. |
| R7CD | I/O verify mismatch | 0: Normal 1: Unmatched | Indicates whether I/O assignment and loading are matched (Mismatched information output to WRF002) | | |
| R7CE | Communication module assignment verify mismatch | 0: Normal 1: Unmatched | Indicates whether I/O assignment and loading are matched (Mismatched information output to WRF003) | | |
| R7CF | Undefined | Do not use. | | | |
| R7D0 | Remote error | 0: Normal 1: Abnormal | Indicates whether the remote module is normal (Abnormal slot number display to WRF006, detailed information output to WRF080 to WRF0DF) | Set by system | Cleared by user or cleared when retentive area cleared. |
| R7D1 | Overload error (normal scan) | 0: Normal 1: Scan time over | Indicates whether the scan execution time has exceeded the designated time | | |
| R7D2 | Overload error (periodic scan) | 0: Normal 1: Scan time over | Indicates whether the periodic scan was completed within cycle time | | |
| R7D3 | Undefined | Do not use. | | Set by system | Cleared by user or cleared when retentive area cleared. |
| R7D4 | Grammar/assemble error | 0: Normal 1: Error | Indicates whether there is a grammar error in the user program (Detailed information output to WRF001) | | |
| R7D5 | I/O module error | 0: Normal 1: Abnormal | Indicates whether there is an abnormal in the I/O module (Error slot number in WRF005) | | |

| No. | Name | Meaning | Description | Setting condition | Resetting condition |
|------|--------------------------------------|---|---|-------------------|---|
| R7D6 | Number of I/O assignment points over | 0: Normal 1: I/O assignment points over | Indicates whether the number of I/O assigned points has exceeded the maximum number | Set by system | Cleared by user or cleared when retentive area cleared. |
| R7D7 | Communication module abnormal | 0: Normal 1: Abnormal | Indicates whether there is an abnormal in the communication module (Abnormal slot number output to WRF004) | | |
| R7D8 | System bus abnormal | 0: Normal 1: Abnormal | Indicates whether there is an abnormal when the system bus is accessed | | |
| R7D9 | Battery error | 0: Normal 1: Abnormal | Indicates battery voltage is low, or back up memory failure. | | Cleared by system * |
| R7DA | Undefined | Do not use. | | | |
| R7DB | Self-diagnostic error | 0: Normal 1: Error | Indicates whether there is a self-diagnostic error (Detailed information output to WRF000) | Set by system | Cleared by user or cleared when retentive area cleared. |
| R7DC | Undefined | Do not use. | | | |
| R7DD | Communication module assignment over | 0: Normal 1: Error | Indicates whether the communication module assignment exceeds the maximum value | Set by system | Cleared by user or cleared when retentive area cleared. |
| R7DE | Link module abnormal | 0: Normal 1: Abnormal | Indicates whether there is an abnormal in the link module (Abnormal slot number displayed in WRF007, detailed information output to WRF0E0 to WRF19F) | | |
| R7DF | Undefined | Do not use. | | | |
| R7E0 | Operation switch position (STOP) | 0: Other than below. 1: RUN switch position is STOP and REMOTE setting switch position is off. | One of these is on | Set by system | Cleared by system |
| R7E1 | Operation switch position (REMOTE) | 0: Other than below. 1: When RUN switch position is STOP and REMOTE setting switch is on | | | |
| R7E2 | Operation switch position (RUN) | 0: RUN switch position is STOP 1: RUN switch position is RUN | | | |
| R7E3 | 1 scan ON after RUN | 0: From the second scan after RUN 1: 1 scan after RUN | ON  OFF | | Cleared by system |
| R7E4 | Always ON | 0: Non-status of 0 1: Always | Always outputs 1 regardless of CPU status | | |
| R7E5 | 0.02 second clock | 0: 0.01 seconds 1: 0.01 seconds | ON  OFF | | |
| R7E6 | 0.1 second clock | 0: 0.05 seconds 1: 0.05 seconds | ON  OFF | | |
| R7E7 | 1.0 second clock | 0: 0.5 seconds 1: 0.5 seconds | ON  OFF | | |
| R7E8 | Occupied flag | 0: Unoccupied 1: Occupied | Indicates occupancy status from the peripheral device | | |
| R7E9 | RUN prohibited | 0: Operation allowed 1: Operation prohibited | Indicates whether it is operation prohibited status | | |

* Battery error (R7D9) will turn off when the error factor is gone by exchanging the batteries, etc.

| No. | Name | Meaning | Description | Setting condition | Resetting condition |
|--------------|---|--|---|-------------------|---|
| R7EA | Executing an online change in RUN | 0: Not being executed 1: Being executed | Indicates whether operation is temporarily stopped (output hold) due to online change in RUN | Set by system | Cleared by system |
| R7EB | Undefined | Do not use. | | | |
| R7EC | Clear error special internal output | Clear with 1 | Clears error special internal outputs (WRF000 to F00A, R7C8 to 7DE) | Set by user | Cleared by system |
| R7ED | Undefined | Do not use. | | | |
| R7EE | Battery error display | 0: Upon error, ERR lamp flashes 1: Upon error, ERR lamp turns off | Indicates whether or not the ERR lamp is used to notify battery errors | Set by user | Cleared by user or cleared when retentive area cleared. |
| R7EF | Backup memory writing execution flag (EH-CPU104A/208A/308A/318A/448 only) | 0: Write complete 1: Write in progress | Indicates whether or not data is being written to the backup memory. | Set by system | Cleared by system |
| R7F0 | Carry flag (C) | 0: No carry 1: Carry | Indicates whether there is a carryover from the operation result | | |
| R7F1 | Overflow flag (V) | 0: No overflow 1: Overflow | Indicates whether there is overflow in the operation result | | |
| R7F2 | Shift data (SD) | 0: Shift data "0" 1: Shift data "1" | Designates the shift data used in shift commands, etc. | Set by user | Cleared by user |
| R7F3 | Operation error (ERR) | 0: Normal 1: Error | Indicates whether there is an operation error when operation is executed | Set by system | Cleared by system |
| R7F4 | Data error (DER) | 0: Normal 1: Error | Indicates whether there is a data error when operation is executed | | |
| R7F5 | Undefined | Do not use. | | | |
| R7F6 | Scan time base value specification (EH-CPU***A/448/516/548) Undefined (EH-CPU104/208/308/316) | 0: 10 ms 1: 1 ms | Specifies the time base of the scan time display (WRF010-WRF012). | Set by user | Cleared by user |
| | | Do not use. | | | |
| R7F7 | Memory board busy | 0: Standby 1: Busy | Indicates whether the memory board that was accessed during the execution of the FUN command (FUN 211 through FUN 213) is currently in use for other processing | Set by system | Cleared by system |
| R7F8 | Calendar, clock read request Undefined for the EH-CPU104 | 1: Read | Read present value of calendar, clock and set in WRF01B to WRF01F | Set by user | Cleared by system |
| R7F9 | Calendar, clock setting request Undefined for the EH-CPU104 | 1: Set | Set the data set in WRF01B to WRF01F in the calendar, clock | | |
| R7FA | Clock \pm 30 second adjustment request Undefined for the EH-CPU104 | 1: Request adjustment | When second data is 0 to 29, it becomes 0 seconds and when it is 30 to 59, +1 minute is added and second data becomes 0 | | |
| R7FB | Calendar, clock set data error Undefined for the EH-CPU104 | 0: Normal 1: Error | Indicates whether there is an error in calendar, clock set data | Set by system | |
| R7FC to R7FD | Undefined | Do not use. | | | |
| R7FE | Data logging error | 0: Normal 1: Error | Indicates whether or not there is an error in the memory board or log data | Set by system | Cleared by user or cleared when retentive area cleared. |
| R7FF | Undefined | Do not use. | | | |

13.2 Word Special Internal Output Area

Definitions of the word special internal output area (WRF000 to WRF1FF) are given below.

| No. | Name | Storage data | Description | Setting condition | Resetting condition |
|---------------|--|---|--|-------------------|-------------------------------------|
| WRF000 | Self diagnosis error code | Error code (2 digit hexadecimal, upper 2 digits are 00) | Stores the error number deleted in the CPU as a binary code | Set by system | Cleared by user |
| WRF001 (R7D4) | Grammar/assemble error details | Grammar/assemble error code (4 digit hexadecimal) | Error code for user program grammar/assemble error is stored | | |
| WRF002 (R7CD) | I/O verify mismatch details | Mismatched slot number *1 | <div>15121187430</div> <div><div>0</div><div>a</div><div>b</div><div>0</div></div> <div>a: Unit number (0 to 1)</div> <div>b: Slot number (0 to 7)</div> | | |
| WRF003 (R7CE) | Communication module I/O verify mismatch details | Mismatched module slot number *1 | Mismatched slot number is stored (lower 4 bits: 0 to 7, upper bit 0) | | |
| WRF004 (R7D7) | Communication module abnormal slot number | Slot number of the communication module with abnormal *1 | Error slot number (lower 4 bits: 0 to 7, upper bit 0) | | |
| WRF005 (R7D5) | I/O module abnormal slot number | Slot number of the I/O module with abnormal *1 | <div>15121187430</div> <div><div>0</div><div>a</div><div>b</div><div>0</div></div> <div>a: Unit number (0 to 1)</div> <div>b: Slot number (0 to A)</div> | | |
| WRF006 (R7D0) | Remote I/O master station module abnormal slot number | Slot number of the module with abnormal *1 | | | |
| WRF007 (R7DE) | Link module abnormal slot number | Slot number of the module with abnormal *1 | | | |
| WRF008 | Undefined | Do not use. | | | |
| WRF009 | Undefined | Do not use. | | | |
| WRF00A | Undefined | Do not use. | | | |
| WRF00B | Calendar and clock present value (4 digit BCD) (Nor supported by CPU104(A)) | Year | Always displays the 4 digit year | Set by system | - |
| WRF00C | | Month/day | Month/day data always displayed | | |
| WRF00D | | Day of the week | Day of the week data always displayed (Sunday: 0000 to Saturday: 0006) | | |
| WRF00E | | Hour/minute | Hour/minute data always displayed (24-hour system) | | |
| WRF00F | | Seconds | Seconds data always displayed (Lower 2 digits, upper 2 digits are 00) | | |
| WRF010 | Scan time (maximum value) | Maximum execution time for a normal scan | Maximum execution time for a normal scan is stored in 10 ms units *2 | Set by system | Cleared by system (when RUN starts) |
| WRF011 | Scan time (present value) | Present value of execution time for a normal scan | Present value of execution time for a normal scan is stored in 10 ms units *2 | | |
| WRF012 | Scan time (minimum value) | Minimum execution time for a normal scan | Minimum execution time for a normal scan is stored in 10 ms units (the first scan after RUN is HFFFF) | | |
| WRF013 | CPU status | <div>151110876543210</div> <div><div>Unused</div><div>a</div><div>b</div><div>c</div><div>d</div><div>e</div><div>f</div><div>g</div><div>h</div><div>i</div></div> <div>a: CPU type (011), c: Unused, e: Unused, g: Unused, I: CPU operation (1-RUN, 0-STOP)</div> <div>b: Battery error (1-error, 0-no error), d: Unused, f: Error (1-error, 0-no error), h: Halt (1-In halt, 0-Out of halt),</div> | | | - |

*1 If error slot number to be checked, existing information should be cleared by setting off the respective bit of special internal output (address in ()) once, or setting on R7EC.

*2 Time base of scan time can be switched to 1ms by setting R7F6 for CPU448(A)/516/548.

| No. | Name | Storage data | Description | Setting condition | Resetting condition |
|----------------|--|--|---|--------------------------|---------------------|
| WRF014 | Word internal output capacity | Number of words for word internal output (WR) | CPU104(A): H1000, CPU208(A): H2000, CPU308(A): H4400, CPU316(A): H5800, CPU448(A): HC400, CPU516 : H5800, CPU548 : HC400 | Set by system | - |
| WRF015 | Operation error code | Operation error code | Operation error code is stored (4 digit hexadecimal) | | Cleared by user |
| WRF016 | Division remainder register (lower) | Remainder data when division command executed | For a double word operation: WRF017 (upper), WRF016 (lower) | | Cleared by system |
| WRF017 | Division remainder register (upper) | | For a word operation: WRF016 only | | |
| WRF018 | Communication module startup flag | <div><div>159876543210</div><div>Unuseda b c d e f g h i</div></div> <p>Bit number corresponds to the slot number 1-startup complete 0-startup incomplete</p> | | | |
| WRF019 | Undefined | Do not use. | | | |
| WRF01A | Baud rate set value between CPU and modem | <div><div>156543210</div><div>Unuseda b c d e f</div></div> <p>a-57,600 bps b-38,400 bps c-19,200 bps d-9,600 bps e-4,800 bps f-2,400 bps The corresponding bit is set to 1. The lower bit takes priority. If all bits are 0, it is 2,400 bps.</p> | | Set by user | Cleared by user |
| WRF01B | Read and set values for calendar and clock (4 digit BCD) Not supported by CPU104(A) | Year [yyyy] | 4 digit year to be read or written. | Set by system or by user | Cleared by user |
| WRF01C | | Month/day [mmdd] | Month/date to be read or written. | | |
| WRF01D | | Day of the week data (Sunday: 0000 to Saturday: 0006) | Day of the week to be read or written. | | |
| WRF01E | | Hour/minute (24-hour system) [hhmm] | Stores the read hour/minute value or sets the set value | | |
| WRF01F | | Seconds [00ss] | Stores the read second value or sets the set value | | |
| WRF020 to F021 | Communication module status (slot 0) | Status data | <div><div>15870</div><div>Status 1Status 2</div><div>Status 3Status 4</div></div> <p>Refer to communication module specifications for details</p> | Set by system | Cleared by system |
| WRF022 to F023 | Communication module status (slot 1) | Status data | | | |
| WRF024 to F025 | Communication module status (slot 2) | Status data | | | |
| WRF026 to F027 | Communication module status (slot 3) | Status data | | | |
| WRF028 to F029 | Communication module status (slot 4) | Status data | | | |
| WRF02A to F02B | Communication module status (slot 5) | Status data | | | |
| WRF02C to F02D | Communication module status (slot 6) | Status data | | | |
| WRF02E to F02F | Communication module status (slot 7) | Status data | | | |
| WRF030 to F031 | Communication module status (slot 8) | Status data | | | |
| WRF032 to F035 | Undefined | Do not use. | | | |

| No. | Name | Meaning | Description | Setting condition | Resetting condition | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-----------|--|---|----------------------------|-------------------|---------------------|---|---|-------------|---|---|-------------|--|-----------------------------|---|----------------------------|---|---|-------------|------------|-------------|--|---------|-------|--|---|---|-----------|-------|-------|---------|-------|--------|--|-------|-------|--|-----------|-------------|------------|---------|-------|-------|--------|-------|-------|--------|-------|-------|-----------------------------|-----------------|
| WRF036 | Port 1 setting (General purpose port) (CPU308(A)/316(A)/ 448(A)/516/548) This setting is valid when port 1 is general purpose port. (DIP SW No.5:OFF) | <div>150</div> <table><tr><td colspan="4">Unused</td><td>a</td><td>b</td><td>c</td><td>d</td><td>e</td></tr></table> <div>a- Built-in termination resistor 0:OFF, 1:ON b- RS-485 c- RS-422 d- Setting bit</div> <table><tr><td></td><td colspan="2">Built-in term. resistor OFF</td><td colspan="2">Built-in term. resistor ON</td></tr><tr><td></td><td>Set by user</td><td>Set by CPU</td><td>Set by user</td><td>Set by CPU</td></tr><tr><td>RS-232C</td><td>H0003</td><td>H0002</td><td>-</td><td>-</td></tr><tr><td>RS-422</td><td>H0005</td><td>H0004</td><td>H0015</td><td>H0014</td></tr><tr><td>RS-485</td><td>H0009</td><td>H0008</td><td>H0019</td><td>H0018</td></tr></table> <div>- Please set this register manually by programming software or programming device, not by user program. (If you need to set it by user program, please do it carefully so not to be changed frequently.) - This setting will be valid immediately after changed, and saved to the backup memory. (When the setting is effective, “e” bit is reset.) - When this value is undefined at the power ON, CPU will work with default value (RS-232C). - This setting is valid only when DIP SW5 is OFF (Port 1 for general purpose).</div> | Unused | | | | a | b | c | d | e | | Built-in term. resistor OFF | | Built-in term. resistor ON | | | Set by user | Set by CPU | Set by user | Set by CPU | RS-232C | H0003 | H0002 | - | - | RS-422 | H0005 | H0004 | H0015 | H0014 | RS-485 | H0009 | H0008 | H0019 | H0018 | | | | | | | | | | | | | | |
| Unused | | | | a | b | c | d | e | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Built-in term. resistor OFF | | Built-in term. resistor ON | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Set by user | Set by CPU | Set by user | Set by CPU | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| RS-232C | H0003 | H0002 | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| RS-422 | H0005 | H0004 | H0015 | H0014 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| RS-485 | H0009 | H0008 | H0019 | H0018 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF037 | Port 1 setting (Dedicated port) (EH-CPU***A/448/ 516/548) This setting is valid when port 1 is dedicated port. (DIP SW No.5:ON) | <div>15 14 13 12 11 10 9 8 70</div> <table><tr><td>a</td><td>b</td><td>c</td><td>d</td><td>e</td><td>f</td><td>g</td><td>h</td><td colspan="2">Station No.</td></tr></table> <div>a: Setting bit 1 - Set This bit is cleared after the setting completed. b: Transmission control procedure 0 - Procedure 1 1 - Procedure 2 c: Station number presence 0 - No station number 1 - With Station number d: Built-in termination resistor 0 - OFF 1 - ON e, f: Communication interface status display (set by system)</div> <table><tr><td>e</td><td>f</td><td>Interface</td></tr><tr><td>0</td><td>0</td><td>RS-232C</td></tr><tr><td>0</td><td>1</td><td>RS-422 (Not supported by CPU104A/208A)</td></tr><tr><td>1</td><td>0</td><td>RS-485 (Not supported by CPU104A/208A)</td></tr></table> <div>g, h: Communication interface setting (set by the user)</div> <table><tr><td>g</td><td>h</td><td>Interface</td></tr><tr><td>0</td><td>0</td><td>RS-232C</td></tr><tr><td>0</td><td>1</td><td>RS-422 (Not supported by CPU104A/208A)</td></tr><tr><td>1</td><td>0</td><td>RS-485 (Not supported by CPU104A/208A)</td></tr></table> <table><tr><td>Interface</td><td>Set by user</td><td>Set by CPU</td></tr><tr><td>RS-232C</td><td>H*0**</td><td>H*0**</td></tr><tr><td>RS-422</td><td>H*1**</td><td>H*5**</td></tr><tr><td>RS-485</td><td>H*2**</td><td>H*A**</td></tr></table> <div>* : Setting value except for e,f,g,h. But, when setting is completed, bit “a” is turned off with the system. Station number: 0 to 31 in 2-digit BCD If the station number exceeds this range, the system will set 31. For more details, see Chapter 10, “Communication Specifications.” - Please set this register manually by programming software or programming device, not by user program. (If you need to set it by user program, please do it carefully so not to be changed frequently.) - This setting will be valid at the next power ON, and saved to the backup memory. Please turn off the power after the setting. (When the setting is effective, “a” bit is reset.) - When this value is undefined at the power ON, CPU will work with default value (Transmission control procedure 1, No station number, RS-232C).</div> | a | b | c | d | e | f | g | h | Station No. | | e | f | Interface | 0 | 0 | RS-232C | 0 | 1 | RS-422 (Not supported by CPU104A/208A) | 1 | 0 | RS-485 (Not supported by CPU104A/208A) | g | h | Interface | 0 | 0 | RS-232C | 0 | 1 | RS-422 (Not supported by CPU104A/208A) | 1 | 0 | RS-485 (Not supported by CPU104A/208A) | Interface | Set by user | Set by CPU | RS-232C | H*0** | H*0** | RS-422 | H*1** | H*5** | RS-485 | H*2** | H*A** | Set by system or by user | Cleared by user |
| a | b | c | d | e | f | g | h | Station No. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| e | f | Interface | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 0 | RS-232C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 1 | RS-422 (Not supported by CPU104A/208A) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 0 | RS-485 (Not supported by CPU104A/208A) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| g | h | Interface | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 0 | RS-232C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 1 | RS-422 (Not supported by CPU104A/208A) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 0 | RS-485 (Not supported by CPU104A/208A) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Interface | Set by user | Set by CPU | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| RS-232C | H*0** | H*0** | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| RS-422 | H*1** | H*5** | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| RS-485 | H*2** | H*A** | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| No. | Name | Meaning | Description | Setting condition | Resetting condition | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|---|--|-----------------------------|-----------------------------|-----------------------|-------------|-----------------|----|----|----|----|----|----|----|----|------------------------|----|----|----|----|----|----|----|----|----|----|--------------------|----|----|----|----|----|----|----|----|----|----|--------------------------|-----------------|
| WRF038 | Setting of system processing time (EH-***A/448/516/548) | 15870 | <table><tr><td>User setting time</td><td>Current operating condition</td></tr></table> <p>User setting time: 3 to 9 in 1-digit BCD If the user setting time exceeds this range, the system will set 2.</p> <p>Current system processing time: The system sets the processing time of the system currently in operation.</p> <p>The value which is actually setting in the system complies with the setting value as the following table.</p> <p>The value which an underline has is changed forcibly with the system</p> <table><tr><td>Setting value</td><td>H0</td><td>H1</td><td>H2</td><td>H3</td><td>H4</td><td>H5</td><td>H6</td><td>H7</td><td>H8</td><td>H9</td></tr><tr><td>INT0 (*1) Not exist</td><td>H2</td><td>H1</td><td>H2</td><td>H3</td><td>H4</td><td>H5</td><td>H6</td><td>H7</td><td>H8</td><td>H8</td></tr><tr><td>INT0 (*1) Exist</td><td>H2</td><td>H1</td><td>H2</td><td>H3</td><td>H2</td><td>H2</td><td>H2</td><td>H2</td><td>H2</td><td>H2</td></tr></table> <p>(*1) INT0 is 5ms periodical scan with CPU***A/448/516/548.</p> <p>- Please set this register manually by programming software or programming device, not by user program. (If you need to set it by user program, please do it carefully so not to be changed frequently.)</p> <p>- This setting will be valid immediately after changed, and saved to the backup memory. (When the setting is effective, "User setting time" is set on "current operating condition".)</p> <p>- When this value is undefined at the power ON, CPU will work with default value (H02).</p> <p>- For more details, see Chapter 8, "Operating and Stopping EH-150."</p> | User setting time | Current operating condition | Setting value | H0 | H1 | H2 | H3 | H4 | H5 | H6 | H7 | H8 | H9 | INT0 (*1) Not exist | H2 | H1 | H2 | H3 | H4 | H5 | H6 | H7 | H8 | H8 | INT0 (*1) Exist | H2 | H1 | H2 | H3 | H2 | H2 | H2 | H2 | H2 | H2 | Set by system or by user | Cleared by user |
| | User setting time | Current operating condition | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Setting value | H0 | H1 | H2 | H3 | H4 | H5 | H6 | H7 | H8 | H9 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | INT0 (*1) Not exist | H2 | H1 | H2 | H3 | H4 | H5 | H6 | H7 | H8 | H8 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| INT0 (*1) Exist | H2 | H1 | H2 | H3 | H2 | H2 | H2 | H2 | H2 | H2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Setting of system processing time (EH-CPU308/316 only of ROM Ver. 04 or later) | 15870 | <table><tr><td>User setting time</td><td>Current operating condition</td></tr></table> <p>User setting time: 5 in BCD If a value other than 5 is specified, the system processing time will vary.</p> <p>Current operating time: 00 - System processing time varies. 05 - System processing time is fixed at 5 ms.</p> <p>*The current operating condition section is set by system.</p> <p>- Please set this register manually by programming software or programming device, not by user program. (If you need to set it by user program, please do it carefully so not to be changed frequently.)</p> <p>- This setting will be valid immediately after changed, and saved to the backup memory. (When the setting is effective, "H00" or "H05" is set on "Current operating condition" by "User setting time".)</p> <p>- When this value is undefined at the power ON, CPU will work with default value (System processing time varies).</p> <p>- For more details, see Chapter 8, "Operating and Stopping EH-150."</p> | User setting time | Current operating condition | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| User setting time | Current operating condition | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Undefined (EH-CPU104/208) | Do not use. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF039 to F03A | Do not use. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF03B | Mode time out at reception sequence of Modem control, (port 1) (EH-208A/308A/316A/CPU448(A)/516/548) | 15870 | <table><tr><td>a</td><td>Unused</td><td>Time out setting time</td></tr></table> <p>a: 1 = Valid time out 0 = Invalid time out</p> <p>Time out setting time(second) : H01 to HFF (0 to 255)</p> <p>In case the most significant bit (a) is 0, the setting time is cleared when power on. See 10.4.4 At Command (3) Sequence, Note 2, Page 10-17.</p> | a | Unused | Time out setting time | Set by user | Cleared by user | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | a | Unused | Time out setting time | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Undefined | Do not use. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF03C | Modem time out (port 1) | H80**: Time out monitoring is performed for ** seconds. (The timer is set again upon reception of STX, ENQ or NAK.) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF03D to F03F | Undefined | Do not use. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| No. | Name | Meaning | Description | Setting condition | Resetting condition | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|----------------|--|---|---|-------------------|---------------------|---|---|---|---|---------------|-------------------|---|---|---|---|---|---|---|---|---|--|----------------|----------------|---------------------------|--------|-------|-------|-------|-----------|-------|-------|--------|-------|-------|-------|-----------|-------|-------|--------------------------|--|
| WRF040 to F042 | Occupied member registration area 1 | <div><div>15870</div><table><tr><td>a</td><td>Fixed as 0</td></tr><tr><td>b</td><td>c</td></tr><tr><td>d</td><td>e</td></tr></table></div> <p>a: 0- Not occupied, 1 - Read-occupied, 2 - Write-occupied</p> <p>b: Loop number c: Unit number</p> <p>d: Module number e: Port number (*)</p> <p>(*) When dedicated port: Port 1 is H02 and port 2 is H01.</p> | | a | Fixed as 0 | b | c | d | e | Set by system | Cleared by system | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| a | Fixed as 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| b | c | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| d | e | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF043 to F045 | Occupied member registration area 2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF046 to F048 | Occupied member registration area 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF049 to F04B | Occupied member registration area 4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF04C to F04F | Undefined | Do not use. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF050 | System use area | System ROM version information | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF051 | System use area | System FLASH ROM version information | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF052 to F07D | Undefined | Do not use. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF07E | Link area clear mode selection (EH-CPU308/316 of ROM Ver. 04 or later, CPU***A/448/516/548) | <div><div>150</div><table><tr><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>d</td><td>c</td><td>0</td><td>0</td><td>b</td><td>a</td></tr></table></div> <p>When a mode to clear a link area is selected, the specified link area will be cleared to 0 when the CPU status changes from RUN to STOP.</p> <p>a: 1 = Link area 1 mode switch request (this is set to 0 by system when mode switch is complete.)</p> <p>b: Link area 1: 0 = Do not clear; 1 = Clear</p> <p>c: 1 = Link area 2 mode switch request (this is set to 0 by system when mode switch is complete.)</p> <p>d: Link area 2: 0 = Do not clear; 1 = Clear</p> <table><tr><td></td><td>Selection mode</td><td>User set value</td><td>Display after mode switch</td></tr><tr><td rowspan="2">Link 1</td><td>Clear</td><td>H0003</td><td>H00*2</td></tr><tr><td>Not clear</td><td>H0001</td><td>H00*0</td></tr><tr><td rowspan="2">Link 2</td><td>Clear</td><td>H0030</td><td>H002*</td></tr><tr><td>Not clear</td><td>H0010</td><td>H001*</td></tr></table> <p>*: Retains the status before switching.</p> <p>- Please set this register manually by programming software or programming device, not by user program. (If you need to set it by user program, please do it carefully so not to be changed frequently.)</p> <p>- This setting will be valid immediately after changed, and saved to the backup memory. (When the setting is effective, “a” bit and “c” bit is reset.)</p> <p>- When this value is undefined at the power ON, CPU will work with default value (The link area 1,2 is not cleared by zero) .</p> | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | d | c | 0 | 0 | b | a | | Selection mode | User set value | Display after mode switch | Link 1 | Clear | H0003 | H00*2 | Not clear | H0001 | H00*0 | Link 2 | Clear | H0030 | H002* | Not clear | H0010 | H001* | Set by system or by user | |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | d | c | 0 | 0 | b | a | | | | | | | | | | | | | | | | | | | | | | | | |
| | Selection mode | User set value | Display after mode switch | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Link 1 | Clear | H0003 | H00*2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Not clear | H0001 | H00*0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Link 2 | Clear | H0030 | H002* | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Not clear | H0010 | H001* | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Undefined (CPU104(A)/208(A)) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF07F | Log error code | Log error code | Stores the log error code. For details, see the data logging specifications. | Set by system | Cleared by user | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF080 to F097 | Remote master 1 error flag | Remote error information (refer to separate sheet for details) | | Set by system | Cleared by system | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF098 to F0AF | Remote master 2 error flag | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF0B0 to F0C7 | Remote master 3 error flag | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF0C8 to F0DF | Remote master 4 error flag | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF0E0 to F13F | Link 1 error flag | Link information (refer to separate sheet for details) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WRF140 to F19F | Link 2 error flag | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

13.3 Remote Error Flag Area

Details of the remote error flag error are given below.

| | 15 | 14 | 13 | 12 | 11 | 10 | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 | |
|---|------------|----|----|----|----|----|---|---|--|---|---|---|----------|---|---|---|------|
| Slave station participation flag | a | | | | | | | | | | | | | | | | + 00 |
| Slave station error flag | b | | | | | | | | | | | | | | | | + 01 |
| Master station error detail information | c | d | e | f | g | h | i | j | Number of times transmission errors *1 | | | | | | | | + 02 |
| Slave station No. 0 detail information | k | l | m | n | o | p | q | r | Number of times transmission errors *2 | | | | | | | | + 03 |
| Slave station No. 1 detail information | k | l | m | n | o | p | q | r | Number of times transmission errors *2 | | | | | | | | + 04 |
| Slave station No. 2 detail information | k | l | m | n | o | p | q | r | Number of times transmission errors *2 | | | | | | | | + 05 |
| Slave station No. 3 detail information | k | l | m | n | o | p | q | r | Number of times transmission errors *2 | | | | | | | | + 06 |
| Slave station No. 4 detail information | k | l | m | n | o | p | q | r | Number of times transmission errors *2 | | | | | | | | + 07 |
| Slave station No. 5 detail information | k | l | m | n | o | p | q | r | Number of times transmission errors *2 | | | | | | | | + 08 |
| Slave station No. 6 detail information | k | l | m | n | o | p | q | r | Number of times transmission errors *2 | | | | | | | | + 09 |
| Slave station No. 7 detail information | k | l | m | n | o | p | q | r | Number of times transmission errors *2 | | | | | | | | + 0A |
| Slave station No. 8 detail information | Undefined | | | | | | | | | | | | | | | | + 0B |
| Slave station No. 9 detail information | Undefined | | | | | | | | | | | | | | | | + 0C |
| Slave station No. 10 detail information | Undefined | | | | | | | | | | | | | | | | + 0D |
| Slave station No. 11 detail information | Undefined | | | | | | | | | | | | | | | | + 0E |
| Slave station No. 12 detail information | Undefined | | | | | | | | | | | | | | | | + 0F |
| Slave station No. 13 detail information | Undefined | | | | | | | | | | | | | | | | + 10 |
| Slave station No. 14 detail information | Undefined | | | | | | | | | | | | | | | | + 11 |
| Slave station No. 15 detail information | Undefined | | | | | | | | | | | | | | | | + 12 |
| I/O verify mismatch slot No. | 0 | | | | | | | | Slave station No. | | | | Slot No. | | | | + 13 |
| I/O error slot No. | 0 | | | | | | | | Slave station No. | | | | Slot No. | | | | + 14 |
| Refresh time (maximum) | (unit: ms) | | | | | | | | | | | | | | | | + 15 |
| Refresh time (minimum) | (unit: ms) | | | | | | | | | | | | | | | | + 16 |
| Refresh time (present) | (unit: ms) | | | | | | | | | | | | | | | | + 17 |

- a: Bit number corresponds to the slave station number (1: participating, 0: non-participating)
b: Bit number corresponds to the slave station number (1: error, 0: no error)
c: Time out error (1: error, 0: no error) k: Same as c
d: Frame error (1: error, 0: no error) l: Same as d
e: System bus error (1: error, 0: no error) m: Undefined
f: Slave station I/O error (1: error, 0: no error) n: Same as f
g: Duplicate station number (1: error, 0: no error) o: Same as g
h: Slave station connection mismatch (1: error, 0: no error) p: Same as h
i: I/O information mismatch (1: error, 0: no error) q: Same as i
j: Remote points error (1: error, 0: no error) r: Undefined

*1 "Number of times transmission error" is a cumulative total of the number of c or d error occurrences.

*2 "Number of times transmission error" is a cumulative total of the number of k or l error occurrences.

13.4 Link Error Flag Area

Details of the link error flag area are given below.

| | | | | | | | | | | | | | | | | | 15 | 14 | 13 | 12 | 11 | 10 | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 | |
|---|--|------------|----|---|-----------|----|---|---|---|--|--|-----------------------------|--|----|------|----|------|------|----|------|----|----|---|---|---|---|---|---|---|---|---|---|--|
| Local station error information | | Undefined | | a | b | c | d | e | f | Undefined | | Disconnected station number | | | | | | | | + 00 | | | | | | | | | | | | | |
| | | 15 | to | | | | | | | | | | | | | 0 | | + 01 | | | | | | | | | | | | | | | |
| Link participation flag (g) | | 31 | to | | | | | | | | | | | | | 16 | | + 02 | | | | | | | | | | | | | | | |
| | | 47 | to | | | | | | | | | | | | | 32 | | + 03 | | | | | | | | | | | | | | | |
| | | 63 | to | | | | | | | | | | | | | 48 | | + 04 | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Link operation status flag (h) | | 15 | to | | | | | | | | | | | | | 0 | | + 05 | | | | | | | | | | | | | | | |
| | | 31 | to | | | | | | | | | | | | | 16 | | + 06 | | | | | | | | | | | | | | | |
| | | 47 | to | | | | | | | | | | | | | 32 | | + 07 | | | | | | | | | | | | | | | |
| | | 63 | to | | | | | | | | | | | | | 48 | | + 08 | | | | | | | | | | | | | | | |
| CPU status flag (i) | | 3 | | | | 2 | | | | 1 | | | | 0 | | | | + 09 | | | | | | | | | | | | | | | |
| | | : | | | | | | | | | | | | | | | : | | | | | | | | | | | | | | | | |
| | | : | | | | | | | | | | | | | | | : | | | | | | | | | | | | | | | | |
| | | 63 | | | | 62 | | | | 61 | | | | 60 | | | | + 18 | | | | | | | | | | | | | | | |
| Error status flag (j) *1 | | 15 | to | | | | | | | | | | | | | 0 | | + 19 | | | | | | | | | | | | | | | |
| | | 31 | to | | | | | | | | | | | | | 16 | | + 1A | | | | | | | | | | | | | | | |
| | | 47 | to | | | | | | | | | | | | | 32 | | + 1B | | | | | | | | | | | | | | | |
| | | 63 | to | | | | | | | | | | | | | 48 | | + 1C | | | | | | | | | | | | | | | |
| Station 0 to 63 Error detail information | | k | l | m | Undefined | | | | | Number of times transmission errors *2 | | | | | + 1D | | | | | | | | | | | | | | | | | | |
| | | : | | | | | | | | | | | | | | | : | | | | | | | | | | | | | | | | |
| | | : | | | | | | | | | | | | | | | : | | | | | | | | | | | | | | | | |
| | | k | l | m | Undefined | | | | | Number of times transmission errors *2 | | | | | + 5C | | | | | | | | | | | | | | | | | | |
| Refresh time (maximum) | | (Unit: ms) | | | | | | | | | | | | | | | + 5D | | | | | | | | | | | | | | | | |
| Refresh time (minimum) | | (Unit: ms) | | | | | | | | | | | | | | | + 5E | | | | | | | | | | | | | | | | |
| Refresh time (present) | | (Unit: ms) | | | | | | | | | | | | | | | + 5F | | | | | | | | | | | | | | | | |

- a: System bus error (1-error, 0-no error) b: Undefined
 c: Area error (1-error, 0-no error) d: Duplicate area error (1-error, 0-no error)
 e: Station number error (1-error, 0-no error) f: Transmission path disconnected (1-error, 0-no error)
 g: Number indicates the station number (1-participation, 0-non-participation)
 h: Number indicates the station number (1-operating, 0-stopped)
 i: Number indicates the station number (of the 4 bits, 1] 1-CPU error, 0-normal 2] Undefined 3] 1-HALT status, 0-other than HALT status 4] 1-running, 0-stopped)

| | | | |
|----|----|----|----|
| 1] | 2] | 3] | 4] |
|----|----|----|----|

- j: Number indicates the station number (1-error, 0-no error) k: Time out error (1-error, 0-no error)
 l: Frame error (1-error, 0-no error) m: Abnormal between CPU and link (1-abnormal, 0-normal)

- *1 “Error status flag” is set to 1 when one of the k, l and m errors is generated in “Error detail information.” k, l and m generate error when an error is detected while the peripheral device is communicating with the CPU of other station.
 *2 “Number of times transmission errors” is a cumulative total of the number of k or l error occurrences.

Chapter 14 Troubleshooting

14.1 Error Indication and Countermeasure Procedures

The indication locations of errors detected by individual equipment in the EH-150 system are shown in Figure 14.1. When errors occur, remedy the errors using the error code list.




Figure 14.1 Error indication of EH-150

(1) Error indication

(a) CPU module error indication

The CPU module will perform self-diagnostic tests using the microcomputer, and when there is an error the contents are indicated in the combination of the ERR and RUN lamps located in the front of the CPU module being lit/flashing/unlit. For Chapter 12 error codes and countermeasures, refer to the self-diagnosis error code list.

(b) Programmer error indication

Error codes encountered during program device operation, such as duplicate definition error, undefined error, operation error, program over, etc., will be displayed on the programming device. For detailed error codes, refer to the error code list in the programming device manual.

(c) GPCL error display

The error detected by the CPU during the GPCL operation is displayed at the bottom left of the screen.

| ON LINE PROGRAMMING | | | |
|------------------------|----------------|-----------------------|------------|
| ***** CPU STATUS ***** | | ***** PC STATUS ***** | |
| CPU TYPE | : H-300 | CPU TYPE | : H-300 |
| STATUS | : STOP | MEMORY CAPA | : 0192 [S] |
| MEMORY TYPE | : RAM | FLOW | : 0 [S] |
| CAPA | : 0192 [S] | LADDER | : 7552 [S] |
| FLOW | : 0 [S] | DATA | : 2048 [W] |
| LADDER | : 7552 [S] | MEMORY STATUS | : NOT |
| DATA | : 2048 [W] | CASSETTE TYPE | : [S] |
| BATTERY | : OK | CAPA | : [S] |
| CONTROL | : NO | BATTERY | : [S] |
| PREV. | : 10 [*10mSEC] | PRINT PORT | : CENTRO |
| CPU PORT | : HOME | BUZZER PORT | : FON |
| CPU STATUS | : STOP [MOD6] | | |
| CPU ONLINE | : H-300 | | |
| CPU PORT | : HOME | | |
| CPU CONNECT ERROR | | | |

Error display

If the cable is disconnected or the power to the master unit is turned off during the GPCL operation, "CPU CONNECTION ERROR" is displayed to indicate a connection error.

For the details of error codes, see the list of error codes in the GPCL manual.

(d) Setting in the special internal output

An error code is set in the special internal output area (such as WRF000). The smaller the error code value, the more serious the error is. When two or more errors occur, the smaller number is set. For example, if "71" (battery error) and "31" (user memory error) occur simultaneously, "31" is set. If the levels are the same, the cause code generated last will be displayed.

The clearing of error special internal output is performed by setting the special internal output R7EC to 1. The R7EC can be set to 1 either by connecting the programming device or by including a subprogram that sets the R7EC using external input within the program. (If turning R7EC on by the program, always set it on after the error cause has been verified. However, if R7EC is turned on by a program that would generate a watchdog error, the system may clear the error cause and rerun after detecting a watchdog error.)

Note: Error codes are set in hexadecimal values. Verify error codes by setting the monitor to hexadecimal display.

The range of the special internal output that is cleared when R7EC is set to 1 is shown below.

| No. | Bit special internal output | No. | Word special internal output |
|------|---|--------|---|
| R7C8 | Serious failure flag | WRF000 | Self-diagnostic error code |
| 9 | Operation microcomputer abnormal | 1 | Grammar/assemble error details |
| A | User memory abnormal | 2 | I/O verify mismatch details |
| B | I/O bus abnormal | 3 | Communication module I/O verify mismatch details |
| C | Memory size over | 4 | Communication module abnormal slot number |
| D | I/O verify mismatch | 5 | I/O module abnormal slot number |
| E | Communication module assignment verify mismatch | 6 | Remote I/O master station module abnormal slot number |
| R7CF | (Undefined) | | |
| R7D0 | Remote abnormal | 7 | Link module abnormal slot number |
| 1 | Overload error (normal scan) | 8 | (Undefined) |
| 2 | Overload error (periodical scan) | 9 | (Undefined) |
| 3 | Overload error (interrupt scan) | WRF00A | (Undefined) |
| 4 | Grammar/assemble error | | |
| 5 | I/O module abnormal | | |
| 6 | I/O assignment point over | | |
| 7 | Communication module abnormal | | |
| 8 | System bus error | | |
| 9 | Battery error | | |
| A | (Undefined) | | |
| B | Self-diagnostic error | | |
| C | (Undefined) | | |
| D | Communication module assignment over | | |
| R7DE | Link module abnormal | | |


When all of the special internal output data cannot be cleared for program execution reasons, refer to the self-diagnostic error code list and clear only the respective error flags by using forced set of the programmer or peripheral device.

Caution

If the internal output for a self-diagnostic error R7DB (WRF000) is used as a system error for the stop condition of CPU RUN, the R7DB may be turned on even with an error of the warning level (battery error, etc.), causing the CPU to stop. Therefore, do not use the internal output of the self-diagnostic error as a condition for stopping the CPU.

(2) Corrective actions when errors are generated

The process flow when an error is generated is shown below.



| Error code | Error name | Corrective action |
|------------|------------------------------------|---|
| 11 | System ROM error | Re-inspect the fixation of the CPU module to the basic base unit and restart the power supply. If the same error occurs, it is a hardware error in the CPU module, so replace the CPU module with a spare. Make sure that there are no machines, etc. that generate excessive noise. |
| 12 | System RAM error | |
| 13 | Microcomputer error | |
| 15 | System bus timeout error | |
| 16 | System program error | |
| 22 | Sequence processor error | |
| 23 | Undefined command | |
| 27 | Data memory error | |
| — | Power shut-off, power supply error | Check the basic and extended power supply voltage. |
| 31 | User memory error | The contents of the user program is destroyed. Perform initialization and transfer the program again. This is displayed when the machine is stored with a worn-out battery or without battery for a long period of time. |
| 33 | User memory size error | This may be displayed when the contents of the memory within the CPU module is unstable. If the same error is generated after initialization, replace the CPU module with a new one. |
| 34 | Grammar/assemble error | There is a grammar or assemble error in the user program. Verify the program and I/O assignment. |
| 41 | I/O information verification error | Check the I/O assignment. Check each I/O module, I/O controller fixation and expansion cable connection. |
| 43 | Remote error | Perform module settings, reset, etc. according to the error code of the malfunctioning remote module. |
| 44 | Overload error (normal scan) | Change the program so that the scan time of the user program is shorter or change the watchdog check time. |
| 45 | Overload error (periodic scan) | Change the program so that the periodic interrupt program execution time is shorter. |
| 47 | I/O assignment point over | Perform I/O assignment so that the maximum I/O points of the CPU module are not exceeded. |

| Error code | Error name | Corrective action |
|------------|---|---|
| 51 | I/O module abnormal | Check for errors in I/O modules and replace the malfunctioning module. |
| 52 | I/O transmission error | Reset the power supply for the high-function module. Set the TRNS, RECV parameters correctly. |
| 53 | I/O invalid interrupt | Check to see if the links and remote modules are assigned properly in the I/O assignment. |
| 54 | Communication module abnormal | Perform error recovery procedures according to the error code of the malfunctioning communication module. |
| 55 | Communication module transmission error | |
| 57 | Communication module I/O over assignment | Perform assignment so that the maximum number of communication module assignments is not exceeded. |
| 58 | Communication module I/O information verify error | Change the parameters or properly install the communication function module. |
| 59 | Link module abnormal | Perform error recovery procedures according to the error code of the malfunctioning link module. |
| 61 | Port 2 transmission error (parity) | Check the connection of the connector cable. Check the settings such as the transmission speed. Check to see if there are any sources of noise near the cable. |
| 62 | Port 2 transmission error (framing/overflow) | |
| 63 | Port 2 transmission error (time out) | Check the connection of the connector cable. Check to see if there are any sources of noise near the cable. Verify the protocol designations, evaluate the host computer processing and correct any errors. |
| 64 | Port 2 transmission error (protocol error) | |
| 65 | Port 2 transmission error (BCC error) | |
| 67 | Port 1 transmission error (parity) | Check the connection of the connector cable. Check the settings such as the transmission speed. Check to see if there are any sources of noise near the cable. |
| 68 | Port 1 transmission error (framing/overflow) | |
| 69 | Port 1 transmission error (timeout) | Check the connection of the connector cable. Check to see if there are any sources of noise near the cable. Verify the protocol designations, evaluate the host computer processing and correct any errors. |
| 6A | Port 1 transmission error (protocol error) | |
| 6B | Port 1 transmission error (BCC error) | |
| 71 | Battery error | Replace the battery with a new one. Verify the connection of the battery connector. |



Perform the following procedures to erase the error display.

(a) When CPU is stopped

Turn the CPU RUN switch to "STOP," then to "RUN" again.

If the cause of the error has been corrected, the ERR lamp turns off. However, the error information remains in the error special internal output, which stores the CPU error types and details. (This makes it possible to analyze the error after recovery.) To reset the error information, perform the procedures shown in (b) or press the reset switch for the power failure memory protection (R.CL SW).

(b) When the CPU is still running

1] Clear the ERR lamp only.

Set "1" in the special internal output, R7EB.

2] Clear the ERR lamp display and error special internal output.

Set "1" in the special internal output, R7EC.

14.2 Checklist for troubles

If an error is generated in the EH-150 system, check the following items. If there are no problems in the following items, contact our service department.


- (a) Power supply related items
 - Is the power voltage correct? (85 to 264 V AC)
 - Are there any warps in the power supply waveform?
 - Are there any excessive noises in the power supply?
 - Is power supplied for all basic and expansion modules?
 - Is the capacity of the power supply module greater than the total of module consumption current?
- (b) CPU related items
 - Are the initial settings (CPU initialization, I/O assignment, parameter settings, etc.) proper?
 - Are there any error codes that are output to the special internal output?
 - Is the RUN switch in the proper location?
 - Are batteries mounted properly? Is the battery life still remaining?
 - Are the CPU connectors properly connected to the base connectors?
- (c) Input module related items
 - Is the input voltage within the specifications for the module?
 - Is there any noise or chattering in the input?
 - Do the I/O assignment numbers in the program match?
 - Is the wiring done properly?
- (d) Output module related items
 - Do the module and the load power supply type (DC/AC) match?
 - Do the load voltage and current match the module specifications?
 - Is there any noise or chattering in the output waveform?
 - Is the wiring done properly?
 - Do the I/O assignment numbers in the program match?
 - Are there any unintentional overlaps in the output numbers?
- (e) Wiring related items
 - Is the FE terminal of the power supply module grounded using class-3 dedicated grounding?
 - Is the wiring between the expansions mixed up with other wires?
 - Are the power supply wiring and I/O cables separated?
 - Are there any foreign substances in the connector of each module?

| |
|---------|
| Caution |
|---------|


- (a) Be sure to replace the modules with the power supply turned off.
- (b) When returning the module for repair, please notify us of the malfunctioning effects in as much detail as possible (including error codes, malfunctioning output bit number, will not turn on or off, etc.).
- (c) The tools and devices necessary for troubleshooting are roughly as follows:
Phillips/flathead drivers, digital MultiMate, tester, oscilloscope (necessary depending on the case) etc.

14.3 Procedures to Solve

The processing flow when a malfunction has occurred is as follows:




| Major problems | Verification points | Typical causes of the problem | Reference item |
|--|--|--|----------------|
| PLC does not start | Power LED, CPU error code | Power supply abnormal, power shut off, power supply capacity shortage, module connector error, serious CPU failure | (a) |
| PLC does not operate (Not in RUN mode) | CPU error code, CPU LED, Internal output of error | I/O assignment abnormal, incorrect parameter settings, incorrect user program, syntax error, drive conditions not met, write-occupied status | (b) |
| Operation stopped (RUN stopped) | Power LED, CPU LED, CPU error code | Power supply abnormal, expansion power supply abnormal/shut off, CPU abnormal, memory abnormal, communication module abnormal, base abnormal | (c) |
| Input error | CPU LED, I/O LED Monitoring by peripheral devices | User program timings, input power supply, bad connection, input module abnormal, I/O inductive noise | (d) |
| Output error | CPU LED, I/O LED, Monitoring by peripheral devices, Forced set | User programming, bad connection, output module abnormal, I/O inductive noise | (e) |
| Peripheral device error | CPU error code, CPU, peripheral devices | Serious CPU failure, peripheral device abnormal, peripheral drive setting error, cable abnormal | (f) |



(a) PLC does not start

The CPU ERR LED does not turn off even when power is started, nor peripheral devices cannot be connected on-line.




(b) PLC does operate (Not in RUN mode)

Even if the PLC operation conditions are met, the CPU does not operate (the RUN LED does not turn on) and remains stopped. However, the peripheral devices go on-line.


Caution

If the CPU is WRITE-occupied, the CPU will not run even if the RUN switch is switched from “STOP” to “RUN.” The CPU starts running by pressing the GRS key after peripheral devices are connected.




(c) Operation stopped (RUN stopped)

[During normal operation, the CPU suddenly stops (the RUN LED turns off).]




(d) Wrong input at input module, or input module does not work (abnormal operation)


[CPU runs, but the input data is not correct.]




[No input signal.]




[I/O assignment error is generated, but data is read.]




(e) Wrong output from output module or output module will not output (abnormal operation)
 [The CPU operates, but output signals are not correct.]



[The CPU operates, but output signals are not detected.]




[I/O assignment error is generated, but output is normal.]



(f) Peripheral devices abnormal

[Peripheral devices cannot be connected.]



Chapter 15 Operation Examples

To understand the basic operation of the EH-150, this chapter explains samples of operations such as inputting simple programs and verifying operations.


The following programming devices can be used:

| | Peripheral device name | Form |
|---|--|---------------------|
| 1 | Portable graphic programmer | PGM-GPH |
| | ROM pack for portable graphic programmer | PGMPK2H |
| 2 | Command language programmer | PGM-CHH |
| 3 | H series ladder diagram command language software Ladder Editor | HL-PC3 HL-AT3E |
| | H series ladder diagram command language software Ladder Editor for Windows® version | HLW-PC3 HLW-PC3E |

* The graphic input unit (model name: GPCL01H) can be used. However, the PGMIF1H cannot be used.

(1) Operation verification procedures

An operation is verified according to the following procedures:



A personal computer and Ladder Editor for Windows® are used as the peripheral devices in the example. For details, refer to the user's manual for each peripheral device.


(2) Detailed operation example

The following explains an operation example using the module and sample program from step 1.

| Power supply | CPU | Slot 0 | Slot 1 | Slot 2 |
|--------------|-----|--------|--------|--------|
|--------------|-----|--------|--------|--------|

Power supply: EH-PSA
 Basic base: EH-BS3
 CPU: EH-CPU448
 Slot 0: EH-XD64(64-point input)
 Slot 1: EH-YT32(32-point output)
 Slot 2: EH-DUM(dummy)

Operation of program
 Turn Y100 and Y102 on and
 Y101 and Y103 off and vice
 versa, alternating at one second
 intervals.



STEP 1 Starting the Ladder Editor for Windows®

1. Start the personal computer.


Start the personal computer.

2. Start the Ladder Editor for Windows® system (GRS screen).

From the Start menu of Windows®, click
[Program] → [Hladder] → [Hladder].

As Ladder Editor for Windows® is started, the GRS screen is displayed.


Startup



3. Switching to Offline mode.


Click [Offline] in the Menu bar.

GRS screen



The Read/Edit screen is displayed.

Mode switching




STEP 2 Initialization

Settings for the CPU type, memory type and I/O assignment are performed.

1. Setting the CPU type

Click **[Utility]** → **[Environment Settings]** in the Menu bar.


Pull-down menu



The Environment Setting dialogue box is displayed. Specify the CPU type from the Ladder tag.

- Click the ▼ of the Offline CPU field to show the available CPU types in the pull-down display. Select the CPU type.
- Click the **[OK]** button.


Pull-down display of CPU types



Specify the transmission speed from the Communication tag.

- Select the transmission speed set with the DIP switches of the EH-150 main unit (in case of 10-point type CPU, the transmission speed is fixed at 4800bps).
- Specify the communication port.
- Click the **[OK]** button.

Pull-down display of CPU types




For the CPU type, select "EH-150." (However, if LADDER EDITOR for Windows® of earlier than Ver. 2.0, HL-PC3, or GPCL01H is used, select "H-302.")

* If the EH-CPU448 is used, select "H-302." (If "EH-150" is selected, 48K steps cannot be specified for the memory type.)

2. Setting the memory type

Click **[Utility] → [CPU Setting] → [CPU Information]** in the Menu bar.


Pull-down menu



The CPU Information dialogue box is displayed.


- Click the Memory Cassette/Ladder Assign button and select the memory cassette size.
- Click **[Execute]** or the **[Memory/Execute]** button.

CPU Information dialogue box



- Click the **[OK]** button in the confirmation dialogue box.


Select the memory cassette size according to the CPU model by referring to Section 7.2. If the EH-CPU448 is used, select “H-302” for the CPU type. **[Execute]**: Save to the PC memory **[Memory/Execute]**: Save to the PC memory and Window registry.



3. Assigning I/O


Click **[Utility] → [CPU Setting] → [I/O Assign]** in the Menu bar.

Pull-down menu



The I/O Assign List dialogue box is displayed. Click the ▼ of the Types field and select **[Standard]** from the pull-down display.

I/O Assign List dialogue box



There are two setting methods for the subsequent procedures.


- From the I/O Assign List
- From the I/O Assign List → Slot Setting Status

[Setting from the I/O Assign List]

- 1] Double-click the cell for the unit number and slot number to be set.


The Assignment Setting dialogue box is displayed.

The Assignment Setting dialogue box.



- 2] Click the ▼ of the data and select I/O type from the pull-down display.
 - 3] Click the [OK] button to close the Assignment Setting dialogue box.
- I/O type is set to the specified cell.


Setting of I/O type



In the same way, repeat steps 1] to 3] to assign Y32 and 16 vacant points to Slot 1 and 2 respectively.


If a wrong value has been entered, the slot is left blank by assigning [Vacant 0] and is treated as though nothing is assigned to it.

- 4] Click the [Execute] button.
- The information assigned to the PC memory is written.



- 5] Click the [OK] button in the confirmation dialogue box to close the I/O Assignment List dialogue box.

Confirmation dialogue box




[Setting from the Slot Setting Status]

Click the **[Slot]** button to display the Slot Setting Status dialogue box.


- 1] Click the ▼ of the unit and select the unit number from the pull-down display.
- 2] Click the button of the slot number to be set.

Slot Setting Status dialogue box.




- 3] Click the ▼ of the data and select the I/O type from the pull-down display.
 - 4] Click the **[OK]** button and close the Assignment Setting dialogue box.
- I/O type is set to the specified slot no.

Specification of I/O type




In the same way, repeat the steps 1] and 2] to 4] to set other unit and slot numbers in order to perform I/O assignment according to the unit to be used. In this example, Y32 and 16 vacant points are assigned to slots 1 and 2 respectively.

- 5] Click the **[Close]** button to close the Slot Setting Status dialogue box. Enter the I/O assignment set in the Slot Setting Status into the I/O Assignment List.



- 6] Click the **[Execute]** button to write the assigned information to the PC memory.
- 7] Click the **[OK]** button in the confirmation dialogue box to close the I/O Assignment List dialogue box.

Confirmation dialogue box




For online mode, it is possible to read the I/O mounted on the CPU by the "Mount" button. For details, refer to the "Reading Mounted I/O" of the programming device.

STEP 3 Program input

1. Input a program.

At first, the output window displays “there is no program” in the bottom left of the Read/Edit screen.

The cursor ■, which indicates the program input position, is placed at the top left of the screen.



[Input procedure of ladder program]

Repeat steps 1) to 4) to proceed with symbol input. The usual operations found in other Windows applications, such as cut, copy, paste, and move, can be performed on already input symbols.

- 1) Specify the input position. (Move the cursor ■ by clicking the mouse or the arrow keys.)
- 2) Click symbols in the Symbol bar.




- 3) Input the desired function (I/O, comparison expression, arithmetic expression) in the dialogue box for the symbol displayed.
- 4) Click the **[OK]** button in the dialogue box.


[Example of entering a contact]

- 1) Begin from the cursor position at the top.
- 2) Click the symbol for contact A.

The dialogue box for contacts is displayed.



- 3) Enter “R7E3” as the I/O No. in the Input field. (I/O No. (half-width alpha-numeric input) can be entered by the keyboard only, or by selecting the initial letter(s) from the pull-down menu of ▼ and by typing the rest.) Enter a proper comment.



- 4) Click the **[OK]** button.
- The dialogue closes.

When the dialogue box closes, the symbol is displayed in the Read/Edit screen and the cursor shifts.

Display of symbol

The comment is displayed under the symbol.

[Example of entering a Processing Box]

- 1] The specification of the input position can be omitted when entering symbols into the same ladder as the contact above.
- 2] Click the symbol for Processing Box.



Symbol selection

The cursor moves to the far-right portion of the screen automatically.
The dialogue box for the processing box symbol is displayed.

- 3] Input arithmetic expressions in the Expression in Processing Box text field.
Multiple lines (a maximum of 19) can be input by including line breaks

Processing Box properties


The comment for the I/O No. written to the Processing Box is displayed by clicking the Comment column.
If there are no comments, only the I/O No. is displayed.



Always enter a space before and after “=”.

- The Comment Input dialogue box is displayed by double-clicking the I/O No. displayed in the Comment column.
- Input a comment and click the **[OK]** button.

Comment Input dialogue box




- 4] Click the **[OK]** button in the Processing Box.

The input of the horizontal line symbol, which connects between symbols, may be omitted. (Symbols are connected by horizontal lines by the automatic wiring function at ladder write.)

[Example of entering a timer]


- 1) Specify the input position, or omit the specification if entering it in the same ladder.
 - 2) Click the symbol for coil.
- When the specification of the input position is omitted, the cursor automatically moves to the far-right portion of the screen.

Symbol selection



- 3) Input I/O No., time base, and the first setting value.

Coil property



The following initials of various I/O numbers can be selected from the pull-down display of the Input field:

R, L, M, Y, TD, SS, WDT, MS, TMR, CU, RCU, CTU, CTD, CL

Input values in the necessary items, such as the time base, the first setting value, and second setting value, according to the I/O No.


(Example) Coil

It is only necessary to enter values in the Input and Comment items.

- 4) Click the **[OK]** button to display the symbol at the cursor at the far-right portion of the ladder.

Symbols whose input positions for coils, arithmetic expressions, etc. are determined are automatically flushed to the right.

Display of symbols




After displaying the coil, the cursor moves to the top of the next ladder.

[Example of entering a Comparison Box]

- 1) Specify the input position
- 2) Click the symbol for Comparison Box.


Symbol selection



- 3] Input comparison expression and comment.
- 4] Click the **[OK]** button.

Comparison Box property

The comment input is valid only for I/O numbers. In this example, entering a comment for the value on the right side of the expression will not generate a comment.



The dialog box 'Comparing Box Property' has the following fields and options:


- Symbol Position: Row 2, Column 3
- Comparing Operation(S): WY10 == 0
- Left-side Comment(L): Left-side Comment
- Right-side Comment(R):
- Comparing Operator: A row of buttons including ==, S==, <, S<, <>, S<>, <=, and S<=.
- Buttons: OK and Cancel.

Always enter a space between an I/O number and comparison operator (in this case, between "WY10" and "=", as well as between a comparison operator and comparison data ("=" and "0").

[Example of entering a Knot]

- 1] Specify the input position.
 - 2] Click the symbol for Knot.
- The symbol is displayed and the cursor moves to the right.


Display of symbols



[Example of entering a Vertical Line]

- 1] Specify the input position.
 - 2] Click the symbol for Vertical Line.
- The symbol is displayed on the right side of the cursor.
The cursor does not move.


Display of symbol




In case of the Horizontal Line symbol, the cursor does move to the right after displaying the symbol, in the same way as in the Knot symbol.

2. Writing to the program memory

Perform a "ladder write" operation by either of the following methods in order to write the ladder to the program memory.

- 1] Click **[Build]** → **[Ladder write]** in the Menu bar.
- 2] Click the **[ladder write]** icon  in the tool bar.

Ladder write operation




STEP 4 Checking program errors

Check to see if the program in the memory is correct.


Click **[Utility]** → **[Check]** in the Menu bar.
The Check dialogue box is displayed.

Pull-down menu



- Click the **[All items]** or the individual check column to specify the items to be checked.
 - Click the **[Execute]** button.
- The Check Result dialogue box is displayed.


Check dialogue box



The checking of the CPU can be specified at online mode.

- Click the **[OK]** button.
- The Check Result dialogue box closes.

Check Result dialogue box



(Note)


For example, if the I/O assignment of bit Y32 is missing for unit 1, WY10 of the sample is treated as undefined; the error is displayed as in the figure to the right.

If there are any errors, correct the errors of the program before check the program again.


STEP 5 Saving the program

Save the program and comment that has been created to a floppy disk.

Click **[File]** → **[Record]** in the Menu bar, the

Record icon , or **[File]** → **[Batch Record]**.
The dialogue for Record or Batch Record is displayed.

Pull-down menu.

Record : Specify the file type and save.
Batch Record: Saves a program and all the comment files.

Record dialogue box:



Specify the directory to save in, file name, and file type.

Batch Record dialogue box:

Specify the place to save and file name.

Click the **[Save]** button to save.

Record dialogue box




File name extensions are not necessary to input.

Record and Batch Record display the results of the save operations for one file and five files respectively.

The figure to the left shows an example of a result display for the Batch Record.

Batch Record Result dialogue box.



STEP 6 Program transfer to CPU


Write the program that has been input, to the CPU. However, verify the following:

- The CPU and the personal computer connection cable are properly connected.
- The CPU power is on.
- CPU mode switch is set to “STOP.”


1. Switching to online mode.

Move to the GRS screen from the offline mode.

This can be done in two ways.

- 1] Click **[File]** → **[GRS]** in the Menu bar.
- 2] Click  (lower button) on the upper right of the screen.


GRS screen



In the GRS screen, click the **[Online]** item in the Menu bar.

The Read/Edit screen of the online mode is displayed.

GRS screen




Note) Verify again that the DIP switches are set to the transmission speed selected in the Environment Setting in step 2. (For 10-point type, it is fixed to 4,800 bps.)

2. Initializing the CPU


Click **[Utility]** → **[Initialize]** → **[CPU initialize]** in the Menu bar.

Pull-down menu




Note) Please note that programs etc. in the personal computer will be erased if [PC initialize] is selected.

The Confirmation dialogue box is displayed; click the **[Yes]** button and start the CPU initialization.




The Exit dialogue box is displayed; click the **[OK]** button to close the dialogue.



3. Transferring to the CPU

Click **[File]** → **[CPU write]** in the Menu bar.

Pull-down menu



Program transfer


CPU Read: PC (personal computer) ← CPU

CPU Write: PC (personal computer) → CPU

The CPU Write dialogue box is displayed.

Click the **[Execute]** button.


CPU write dialogue box



When the writing is completed, the result is displayed.

Click the **[Close]** button to close the dialogue box.

Display of write result.




STEP 7 Monitoring (verifying the operation)

Monitor the program execution status in the CPU.

[Ladder monitor]


Click **[Mode]** → **[Monitor]** in the Menu bar.

Pull-down menu



The Confirmation dialogue box for the program match check between PC and the CPU is displayed. Click the **[Yes]** button.


Match check



Set the CPU's RUN switch to "RUN" to begin the CPU operation.

The on/off status of the contact, timer, and current counter value are displayed.

Display of ladder monitor



To monitor and display the current value and progress value, select comparison expression, arithmetic box, and coil (timer, counter, etc.) with the mouse arrow.


[I/O monitor]

The I/O monitor can be operated while in monitor mode.

Click **[Window]** → **[I/O Monitor]** in the Menu bar.


The I/O Monitor dialogue box is displayed.

Pull-down menu




The I/O Monitor dialogue box is displayed on the Read/Edit screen at its maximum size.

The I/O monitor can be specified in the following two ways.


- 1) Click **[Edit]** → **[I/O monitor setting]** in the Menu bar.
- 2) Click the  icon in the Symbol bar.

I/O Monitor dialogue box




- Enter the starting I/O No.
- Click the number of points to be monitored.
- Click on either the **[Add]**, **[Insert]**, or **[Overwrite]** buttons.

I/O Monitor Setting dialogue box.




Monitor and display 16 points from Y100.

I/O monitor




The I/O monitor can display up to 64 I/O points (up to 64 including words/double-words).

Click the I/O No. being I/O monitored and click **[Edit]** → **[Delete]** to delete it from the monitor.

The display size of the I/O Monitor dialogue box can be changed by clicking .

Both the ladder monitor in the Read/Edit screen and the I/O Monitor can be displayed by making their display sizes smaller to check the operation.

Display of ladder and I/O monitor



Chapter 16 Daily and Periodic Inspection

In order to use the EH-150 functions in the most desirable condition and maintain the system to operate normally, it is essential to conduct daily and periodic inspections.

(1) Daily inspection

Verify the following items while the system is running.

Table 16.1 Items for daily inspection

| Item | LED display | Normal status | Main cause of error |
|---------------------|-------------|--------------------|---|
| LED of Power supply | POW | Lighting | Power supply error, etc. |
| LED of CPU *1 | RUN | Lighting (running) | Off: Microcomputer malfunction, memory error, etc. Flashing: Grammar error, watchdog error, etc. |
| | ERR | off | Lighting: Microcomputer malfunction, memory error, etc. Flashing: Battery error *2 |

*1 The EH-150 indicates error contents by lighting pattern of RUN/ERR LED. Refer to the Chapter 13 error code list for further information.

*2 If PLC power is off over one week after battery error indication, memory data may be destroyed. If PLC power is off for a long time, battery error might not be detected. In this case, memory data is lost.

(2) Periodic inspection

Turn off the power for the external I/O ladder and check the following items once every six months.

Table 16.2 Items for periodic inspection

| Part | Item | Check criteria | Remarks |
|-----------------------------------|--|--|---|
| Programming device to CPU | Check operation of programming device | All switches and display lamps work normally. | |
| Power supply | Check for voltage fluctuations | 85 to 264 V AC | Tester |
| I/O module | Output relay life | Electrical life 200,000 times Mechanical life 10 million times | Refer to the relay contact life curve (Chapter 9). |
| | LED | working properly | |
| | External power voltage | Within the specification for each I/O module | Refer to the I/O module specifications(Chapter 4). |
| Battery (Lithium battery) | Check voltage, life | ERR LED not to flash Within 2 years after replacement | |
| Installation and connecting areas | (1) All modules are securely fixed (2) All connectors fit snugly (3) All screws are tight (4) All cables are normal | No defects | Tighten Check insertion Tighten Visual check |
| Ambient environment | (1) Temperature (2) Humidity (3) Other | 0 to 55 °C 20 to 90 % RH (no condensation) No dust, foreign matter, vibration | Visual check |
| Spare parts | Check number of parts, storage condition | No defects | Visual check |
| Program | Check program contents | Compare the contents of the latest program saved and CPU contents, and make sure they are the same | Check both master and backup. |

(3) Life of the power module

Numbers of electrolytic capacitors are used in the power module. Electrolytic condensers have a lifetime and it is supposed that the life is reduced by half when the ambient temperature rise 10 °C.

When stocking spare parts, the standard for consideration is that the power module has a life of approximately 5 years when used at the rated ambient temperature (30 °C). Also, to lengthen the life of the module, consider the air circulation around the module and ambient temperature when installing it.

(4) Life of the battery

- The length of the battery life is expressed as the total time during which the power supply for the basic unit is off.
- The battery life can be determined by checking for the flashing of the ERR lamp.
- The battery life is also displayed in the bit special internal output “R7D9.”
An example of a ladder using “R7D9” is shown below.




Figure 16.1 Battery error detection ladder

- The self-diagnostic error code “71” indicates that the battery is not loaded or that it has reached its life.

Use the reference table below to determine the remaining life of battery.


As a guideline, replace the battery every two years even when the total power failure time is less than the guaranteed value shown in the table.

| Battery life (Total power failure time) [Hr] | |
|--|--------------------------|
| Guaranteed value (MIN) @55°C | Actual value (MAX) @25°C |
| 2,000 | 32,000 |

(Note)

In case of CPU448(A)/516/548, battery error flag (R7D9) is set on if backup memory writing fails. If this bit R7D9 is still on after battery replaced, backup memory is probably broken.

(5) How to replace the battery



- 1] Prepare a new battery (LIBAT-H).
 - 2] Confirm that the newest program is saved on floppy disks. If it is not saved, always save a backup of the program on floppy disks for safety purposes.
 - 3] Replace the battery while the power supply to the basic base is turned on.
 - 4] Remove the old lithium battery from the battery case, and remove the connector on the battery side.
 - 5] Insert the connector on the battery side to the CPU module connector.
Insert it so that the red lead is \oplus , and the black lead is \ominus .
 - 6] Fold the excess lead and store it in the lead storage space.
(If excess lead is not dressed properly, the wire may be severed by the front cover.)
- * When exchanging while the basic base unit power turned off, perform steps 4], 5] and 6], in less than one minute.

**Danger****Battery handling**

Be sure to use LIBAT-H. Another battery may cause to explosion. The followings are strictly prohibited : inverted battery connection, charging, disassembling, heating, throwing into fire and short circuit.

**Caution****Battery discard (Recycling)**


Exchanged old battery must be discarded properly according to local regulation.

MEMO

Appendix 1 Cable Connection Diagram


EH-150 port and cable connection [when using LADDER EDITOR for PC9801 (HL-PC3)]

<Cable: EH-RS05 + PCCB02H>



EH-150 port and cable connection [when using LADDER EDITOR for Windows® for PC9801]

<Cable: EH-RS05 + WPCB02H>




*The pin numbers ([1] to [8]) of the EH-CPU port have been changed beginning with this manual (NJI-281B(X)). For the correspondence between pin numbers and connectors, see the figure in Chapter 10, "Communication Specifications" of this manual.

Note 1: This switch is located above a dipswitch of CPU module.


EH-150 port and cable connection [when using LADDER EDITOR (HL-AT3E) for AT compatibles]

<Cable: EH-VCB02>



EH-150 port and cable connection [when using LADDER EDITOR Windows® for AT compatibles]

<Cable: EH-RS05 + WVCB02H (for Windows®)>




*The pin numbers ([1] to [8]) of the EH-CPU port have been changed beginning with this manual (NJI-281B(X)). For the correspondence between pin numbers and connectors, see the figure in Chapter 10, "Communication Specifications" of this manual.


Note 1: This switch is located above a dipswitch of CPU module.

Note 2: Set on or off according to communication speed.


EH-150 port and cable connection [when using GPCL01H] <Cable: EH-RS05 + GPCB02H>



EH-150 port and cable connection [when using a programmer] <Cable: EH-RS05 + PGCB02H>



EH-150 port and cable connection [when using the host] <Cable: EH-RS05 + Self-made cable>



*The pin numbers ([1] to [8]) of the EH-CPU port have been changed beginning with this manual (NJI-281B(X)). For the correspondence between pin numbers and connectors, see the figure in Chapter 10, "Communication Specifications" of this manual.

Note 1: This switch is located above a dipswitch of CPU module.

MEMO

Appendix 2 H-series Command Support Comparison Chart

[Basic commands and sequence commands]

| No. | Command format | Command name | EH-150 | H-64 to H-20 | H-200 | H-250 | H-252 | H-2000 H-700 H-300 | H-2002 H-1002 H-702 H-302 | H-4010 |
|-----|----------------|-----------------------------------|--------|--------------|-------|-------|-------|--------------------|---------------------------|--------|
| 1 | LD | Logical operation start | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 2 | LDI | Logical negation operation start | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 3 | AND | Contact series connection | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 4 | ANI | Contact series connection | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 5 | OR | Contact parallel connection | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 6 | ORI | Contact parallel connection | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 7 | NOT | Negation | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 8 | AND DIF | Rising edge detection | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 9 | OR DIF | Rising edge detection | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 10 | AND DFN | Falling edge detection | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 11 | OR DFN | Falling edge detection | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 12 | OUT | I/O output | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 13 | SET | Set I/O output | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 14 | RES | Reset I/O output | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 15 | MCS | Set master control | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 16 | MCR | Reset master control | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 17 | MPS | Save operation result | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 18 | MRD | Read operation result | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 19 | MPP | Clear operation result | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 20 | ANB | Logical block series connection | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 21 | ORB | Logical block parallel connection | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 22 | [] | Processing box start and end | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 23 | () | Relational box start and end | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |

* ○: Supported ×: Not supported

[Basic commands and timer/counter]

| No. | Command format | Command name | EH-150 | H-64 to H-20 | H-200 | H-250 | H-252 | H-2000 H-700 H-300 | H-2002 H-1002 H-702 H-302 | H4010 |
|-----|----------------|-----------------------------|--------|--------------|-------|-------|-------|--------------------|---------------------------|-------|
| 1 | OUT TD | On delay timer | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 2 | OUT TM | On delay timer | ○5 | × | × | × | × | × | × | × |
| 3 | OUT SS | Single shot | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 4 | OUT MS | Mono stable timer | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 5 | OUT TMR | Integral timer | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 6 | OUT WDT | Watchdog timer | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 7 | OUT CU | Counter | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 8 | OUT RCU | Ring counter | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 9 | OUT CTU | Up and down of up counter | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 10 | OUT CTD | Up and down of down counter | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 11 | OUT CL | Counter clear | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |

* ○: Supported ○5: Supported by CPU516/548 ×: Not supported

[Basic commands and relational box]

| No. | Command format | Command name | EH-150 | H-64 to H-20 | H-200 | H-250 | H-252 | H-2000 H-700 H-300 | H-2002 H-1002 H-702 H-302 | H4010 |
|-----|----------------|--------------------------|--------|--------------|-------|-------|-------|--------------------|---------------------------|-------|
| 1 | LD(s1 == s2) | = Relational box | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 2 | AND(s1 == s2) | = Relational box | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 3 | OR(s1 == s2) | = Relational box | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 4 | LD(s1 S== s2) | Signed = Relational box | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 5 | AND(s1 S== s2) | Signed = Relational box | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 6 | OR(s1 S== s2) | Signed = Relational box | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 7 | LD(s1 <> s2) | <> Relational box | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 8 | AND(s1 <> s2) | <> Relational box | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 9 | OR(s1 <> s2) | <> Relational box | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 10 | LD(s1 S<> s2) | Signed <> Relational box | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 11 | AND(s1 S<> s2) | Signed <> Relational box | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 12 | OR(s1 S<> s2) | Signed <> Relational box | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 13 | LD(s1 < s2) | < Relational box | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 14 | AND(s1 < s2) | < Relational box | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 15 | OR(s1 < s2) | < Relational box | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 16 | LD(s1 S< s2) | Signed < Relational box | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 17 | AND(s1 S< s2) | Signed < Relational box | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 18 | OR(s1 S< s2) | Signed < Relational box | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 19 | LD(s1 <= s2) | <= Relational box | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 20 | AND(s1 <= s2) | <= Relational box | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 21 | OR(s1 <= s2) | <= Relational box | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 22 | LD(s1 S<= s2) | Signed <= Relational box | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 23 | AND(s1 S<= s2) | Signed <= Relational box | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 24 | OR(s1 S<= s2) | Signed <= Relational box | ○ | × | × | ○ | ○ | ○ | ○ | ○ |

* ○: Supported ×: Not supported

[Arithmetic commands]

| No. | Command format | Command name | EH-150 | H-64 to H-20 | H-200 | H-250 | H-252 | H-2000 H-700 H-300 | H-2002 H-1002 H-702 H-302 | H4010 |
|-----|----------------|---------------------------------|--------|--------------|-------|-------|-------|--------------------|---------------------------|-------|
| 1 | d = s | Substitution statement | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 2 | d = s1 + s2 | Binary addition | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 3 | d = s1 B+ s2 | BCD addition | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 4 | d = s - s2 | Binary subtraction | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 5 | d = s1 B- s2 | BCD subtraction | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 6 | d = s1 × s2 | Binary multiplication | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 7 | d = s1 B× s2 | BCD multiplication | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 8 | d = s1 S× s2 | Signed binary multiplication | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 9 | d = s1 / s2 | Binary division | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 10 | d = s1 B/ s2 | BCD division | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 11 | d = s1 S/ s2 | Signed binary division | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 12 | d = s1 OR s2 | Logical OR | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 13 | d = s1 AND s2 | Logical AND | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 14 | d = s1 XOR s2 | Exclusive OR | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 15 | d = s1 == s2 | = Relational expression | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 16 | d = s1 S== s2 | Signed = Relational expression | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 17 | d = s1 <> s2 | ≠ Relational expression | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 18 | d = s1 S<> s2 | Signed ≠ Relational expression | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 19 | d = s1 < s2 | < Relational expression | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 20 | d = s1 S< s2 | Signed < Relational expression | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 21 | d = s1 <= s2 | <= Relational expression | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 22 | d = s1 S<= s2 | Signed <= Relational expression | ○ | × | × | ○ | ○ | ○ | ○ | ○ |

* ○: Supported ×: Not supported

[Application commands] (1/2)

| No. | Command format | Command name | EH-150 | H-64 to H-20 | H-200 | H-250 | H-252 | H-2000 H-700 H-300 | H-2002 H-1002 H-702 H-302 | H4010 |
|-----|----------------|-----------------------|--------|--------------|-------|-------|-------|--------------------|---------------------------|-------|
| 1 | BSET (d, n) | Bit set | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 2 | BRES (d, n) | Bit reset | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 3 | BTS (d, n) | Bit test | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 4 | SHR (d, n) | Shift right | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 5 | SHL (d, n) | Shift left | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 6 | ROR (d, n) | Rotate right | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 7 | ROL (d, n) | Rotate left | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 8 | LSR (d, n) | Logical shift right | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 9 | LSL (d, n) | Logical shift left | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 10 | BSR (d, n) | BCD shift right | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 11 | BSL (d, n) | BCD shift left | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 12 | WSHR (d, n) | Batch shift right | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 13 | WSHL (d, n) | Batch shift left | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 14 | WBSR (d, n) | Batch BCD shift right | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 15 | WBSL (d, n) | Batch BCD shift left | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 16 | MOV (d, s, n) | Block transfer | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 17 | COPY (d, s, n) | Copy | ○ | × | × | ○ | ○ | ○ | ○ | ○ |

* ○: Supported ×: Not supported

[Application commands] (2/2)

| No. | Command format | Command name | EH-150 | H-64 to H-20 | H-200 | H-250 | H-252 | H-2000 H-700 H-300 | H-2002 H-1002 H-702 H-302 | H4010 |
|-----|----------------|-------------------------|--------|--------------|-------|-------|-------|--------------------|---------------------------|-------|
| 18 | XCG (d, d2, n) | Block exchange | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 19 | NOT (d) | Reverse | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 20 | NEG (d) | Two's complement | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 21 | ABS (d, s) | Absolute value | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 22 | SGET (d, s) | Sign addition | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 23 | EXT (d, s) | Sign expansion | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 24 | BCD (d, s) | Binary → BCD conversion | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 25 | BIN (d, s) | BCD → Binary conversion | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 26 | DECO (d, s, n) | Decode | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 27 | ENCO (d, s, n) | Encode | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 28 | SEG (d, s) | 7 segment decode | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 29 | SQR (d, s) | Square root | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 30 | BCU (d, s) | Bit count | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 31 | SWAP (d) | Swap | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 32 | FIFIT (P, n) | FIFO initialization | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 33 | FIFWR (P, s) | FIFO write | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 34 | FIFRD (P, d) | FIFO read | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 35 | UNIT (d, s, n) | Unit | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 36 | DIST (d, s, n) | Distribute | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 37 | ADRIO (d, s) | I/O address conversion | ○ | × | × | × | ○ | ○ | ○ | ○ |

* ○: Supported ×: Not supported

[Control commands]

| No. | Command format | Command name | EH-150 | H-64 to H-20 | H-200 | H-250 | H-252 | H-2000 H-700 H-300 | H-2002 H-1002 H-702 H-302 | H4010 |
|-----|----------------|------------------------------|--------|--------------|-------|-------|-------|--------------------|---------------------------|-------|
| 1 | END | Normal scan end | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 2 | CEND (s) | Scan conditional end | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 3 | JMP n | Unconditional jump | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 4 | CJMP n (s) | Conditional jump | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 5 | RSRV n | Reserve | × | × | × | × | × | ○ | ○ | ○ |
| 6 | FREE | Reserve cancel | × | × | × | × | × | ○ | ○ | ○ |
| 7 | LBL n | Label | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 8 | FOR n (s) | FOR | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 9 | NEXT n | NEXT | ○ | × | × | ○ | ○ | ○ | ○ | ○ |
| 10 | CAL n | Call subroutine | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 11 | SB n | Start subroutine program | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 12 | RTS | RETURN SUBROUTINE | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 13 | START n | Start BASIC task | × | × | × | × | × | ○ | ○ | ○ |
| 14 | INT n | Start interrupt scan program | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 15 | RTI | RETURN INTERRUPT | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |

* ○: Supported ×: Not supported

[High-function module transfer commands]

| No. | Command format | Command name | EH-150 | H-64 to H-20 | H-200 | H-250 | H-252 | H-2000 H-700 H-300 | H-2002 H-1002 H-702 H-302 | H4010 |
|-----|-------------------|--|--------|--------------|-------|-------|-------|--------------------|---------------------------|-------|
| 1 | TRNS 0 (d, s, t) | General-purpose port transmission command | ○ | × | × | × | × | × | ○ | ○ |
| 2 | RECV 0 (d, s, t) | General-purpose port receiving command | ○ | × | × | × | × | × | ○ | ○ |
| 3 | TRNS 1 (d, s, t) | Data communication command for SIO, CLOCK | × | × | × | × | ○ | × | ○ | ○ |
| 4 | QTRNS1 (d, s, t) | High data communication command for SIO, CLOCK | × | × | × | × | × | × | ○ | ○ |
| 5 | TRNS 2 (d, s, t) | Data communication command for ASCII | × | × | × | × | × | × | ○ | ○ |
| 6 | QTRNS2 (d, s, t) | High data communication command for ASCII | × | × | × | × | × | × | ○ | ○ |
| 7 | TRNS 3 (d, s, t) | Data transmission command for POSIT-H | × | × | × | × | × | × | ○ | ○ |
| 8 | QTRNS3 (d, s, t) | High data transmission command for POSIT-H | × | × | × | × | × | × | ○ | ○ |
| 9 | RECV 3 (d, s, t) | Data receiving command for POSIT-H | × | × | × | × | × | × | ○ | ○ |
| 10 | TRNS 4 (d, s, t) | Data communication command for POSIT-2H, POSITA2H | × | × | × | × | ○ | × | ○ | ○ |
| 11 | QTRNS 4 (d, s, t) | High data communication command for POSIT-2H, POSITA2H | × | × | × | × | × | × | ○ | ○ |
| 12 | TRNS 5 (d, s, t) | Data communication command for XCU-001H | × | × | × | × | × | × | ○ | ○ |
| 13 | TRNS 6 (d, s, t) | Data communication command for XCU-232H | × | × | × | × | × | × | ○ | ○ |
| 14 | TRNS 8 (d, s, t) | Telecommunication command | ○3 | × | × | × | × | × | × | × |

○ : Supported ○1 : Supported by CPU***A/448/516/548

○3 : Supported by CPU208A/308A/316A/448(A)/516/548

○5 : Supported by CPU516/548

○2 : Supported by CPU308(A)/316(A)/448(A)/516/548

○4 : Supported by CPU308/316/**A/448/516/548

× : Not supported

[FUN commands] (1/5)

| No. | Command format | Command name | EH-150 | H-64 to H-20 | H-200 | H-250 | H-252 | H-2000 H-700 H-300 | H-2002 H-1002 H-702 H-302 | H4010 |
|-----|----------------------------|--|--------|--------------|-------|-------|-------|--------------------|---------------------------|-------|
| 1 | FUN 0 (s) (PIDIT (s)) | PID operation initialization | O2 | × | × | × | ○ | × | ○ | ○ |
| 2 | FUN 1 (s) (PIDOP (s)) | PID operation execution control | O2 | × | × | × | ○ | × | ○ | ○ |
| 3 | FUN 2 (s) (PIDCL (s)) | PID operation execution | O2 | × | × | × | ○ | × | ○ | ○ |
| 4 | FUN 4 (s) (IFR (s)) | Process stepping | ○ | × | × | × | × | × | × | ○ |
| 5 | FUN 10 (s) (SIN (s)) | SIN function | ○ | × | × | × | ○ | × | ○ | ○ |
| 6 | FUN 11 (s) (COS (s)) | COS function | ○ | × | × | × | ○ | × | ○ | ○ |
| 7 | FUN 12 (s) (TAN (s)) | TAN function | ○ | × | × | × | ○ | × | ○ | ○ |
| 8 | FUN 13 (s) (ASIN (s)) | ARC SIN function | ○ | × | × | × | ○ | × | ○ | ○ |
| 9 | FUN 14 (s) (ACOS (s)) | ARC COS function | ○ | × | × | × | ○ | × | ○ | ○ |
| 10 | FUN 15 (s) (ATAN (s)) | ARC TAN function | ○ | × | × | × | ○ | × | ○ | ○ |
| 11 | FUN 20 (s) (DSRCH (s)) | Data search | O5 | × | × | × | ○ | × | ○ | ○ |
| 12 | FUN 21 (s) (TSRCH (s)) | Table search | O5 | × | × | × | ○ | × | ○ | ○ |
| 13 | FUN 22 (s) | Check code calculation | O5 | × | × | × | × | × | × | × |
| 14 | FUN 23 (s) | Check code verifying | O5 | × | × | × | × | × | × | × |
| 15 | FUN 30 (s) (BINDA (s)) | Binary → decimal ASCII conversion (16 bit) | O1 | × | × | × | ○ | × | ○ | ○ |
| 16 | FUN 31 (s) (DBINDA (s)) | Binary → decimal ASCII conversion (32 bit) | O1 | × | × | × | ○ | × | ○ | ○ |
| 17 | FUN 32 (s) (BINHA (s)) | Binary → hexadecimal ASCII conversion (16 bit) | O1 | × | × | × | ○ | × | ○ | ○ |
| 18 | FUN 33 (s) (DBINHA (s)) | Binary → hexadecimal ASCII conversion (32 bit) | O1 | × | × | × | ○ | × | ○ | ○ |
| 19 | FUN 34 (s) (BCDDA (s)) | BCD → decimal ASCII conversion (16 bit) | O1 | × | × | × | ○ | × | ○ | ○ |
| 20 | FUN 35 (s) (DBCDDA (s)) | BCD → decimal ASCII conversion (32 bit) | O1 | × | × | × | ○ | × | ○ | ○ |
| 21 | FUN 36 (s) (DABIN (s)) | Without signed 5 digit Decimal ASCII conversion → binary conversion | O1 | × | × | × | ○ | × | ○ | ○ |
| 22 | FUN 37 (s) (DDABIN (s)) | Signed 10 digit Decimal ASCII conversion → binary conversion | O1 | × | × | × | ○ | × | ○ | ○ |
| 23 | FUN 38 (s) (HABIN (s)) | 4 digit hexadecimal ASCII → binary conversion | O1 | × | × | × | ○ | × | ○ | ○ |
| 24 | FUN 39 (s) (DHABIN (s)) | 8 digit hexadecimal ASCII → binary conversion | O1 | × | × | × | ○ | × | ○ | ○ |
| 25 | FUN 40 (s) (DABCD (s)) | 4 digit decimal ASCII → BCD conversion | O1 | × | × | × | ○ | × | ○ | ○ |

○ : Supported ○1 : Supported by CPU***A/448/516/548

○3 : Supported by CPU208A/308A/316A/448(A)/516/548

○5 : Supported by CPU516/548

○2 : Supported by CPU308(A)/316(A)/448(A)/516/548

○4 : Supported by CPU308/316/***A/448/516/548

× : Not supported

[FUN commands] (2/5)

| No. | Command format | Command name | EH-150 | H-64 to H-20 | H-200 | H-250 | H-252 | H-2000 H-700 H-300 | H-2002 H-1002 H-702 H-302 | H4010 |
|-----|----------------------------|--|--------|--------------|-------|-------|-------|--------------------|---------------------------|-------|
| 26 | FUN 41 (s) (DDABCD (s)) | 8 digit decimal ASCII → BCD conversion | ○1 | × | × | × | ○ | × | ○ | ○ |
| 27 | FUN 42 (s) (ASC (s)) | Hexadecimal binary → ASCII conversion (digit designation) | ○1 | × | × | × | ○ | × | ○ | ○ |
| 28 | FUN 43 (s) (HEX (s)) | Hexadecimal ASCII → binary conversion (digit designation) | ○1 | × | × | × | ○ | × | ○ | ○ |
| 29 | FUN 44 (s) (ASDD (s)) | Character unit | ○1 | × | × | × | ○ | × | ○ | ○ |
| 30 | FUN 45 (s) (SCMP (s)) | Character relational | ○1 | × | × | × | ○ | × | ○ | ○ |
| 31 | FUN 46 (s) (WTOB (s)) | Word → byte conversion | ○1 | × | × | × | ○ | × | ○ | ○ |
| 32 | FUN 47 (s) (WTOW (s)) | Byte → word conversion | ○1 | × | × | × | ○ | × | ○ | ○ |
| 33 | FUN 48 (s) (BSHR (s)) | Byte unit right shift | ○1 | × | × | × | ○ | × | ○ | ○ |
| 34 | FUN 49 (s) (BSHL (s)) | Byte unit left shift | ○1 | × | × | × | ○ | × | ○ | ○ |
| 35 | FUN 50 (s) (TRSET (s)) | Sampling trace set | × | × | × | × | ○ | × | ○ | ○ |
| 36 | FUN 51 (s) (TRACE (s)) | Sampling trace execution | × | × | × | × | ○ | × | ○ | ○ |
| 37 | FUN 52 (s) (TRRES (s)) | Sampling trace reset | × | × | × | × | ○ | × | ○ | ○ |
| 38 | FUN 60 (s) (BSQR (s)) | Binary square | ○1 | × | × | × | ○ | × | ○ | ○ |
| 39 | FUN 61 (s) (PGEN (s)) | Dynamic scan pulse | ○1 | × | × | × | ○ | × | ○ | ○ |
| 40 | FUN 70 (s) | High-speed counter mode set | × | ○ | × | × | × | × | × | × |
| 41 | FUN 71 (s) | High-speed counter process value read | × | ○ | × | × | × | × | × | × |
| 42 | FUN 72 (s) | High-speed counter process value write | × | ○ | × | × | × | × | × | × |
| 43 | FUN 73 (s) | High-speed counter set value read | × | ○ | × | × | × | × | × | × |
| 44 | FUN 74 (s) | High-speed counter set value write | × | ○ | × | × | × | × | × | × |
| 45 | FUN 80 (s) (ALREF (s)) | I/O refresh (All points) | ○ | × | × | × | ○ | × | × | ○ |
| 46 | FUN 81 (s) (IOREF (s)) | I/O refresh (Input/output designation) | ○ | × | × | × | ○ | × | × | ○ |
| 47 | FUN 82 (s) (SLREF (s)) | I/O refresh (Any slot) | ○ | × | × | × | ○ | × | × | ○ |
| 48 | FUN 90 (s) (ETDIT (s)) | Expansion timer initial setting | × | × | × | × | × | × | × | ○ |
| 49 | FUN 91 (s) (ETD (s)) | Expansion timer execution | × | × | × | × | × | × | × | ○ |
| 50 | FUN 97 (s) (WNRED (s)) | Expansion link area read | × | × | × | × | × | × | × | ○ |
| 51 | FUN 98 (s) (WNWRT (s)) | Expansion link area write | × | × | × | × | × | × | × | ○ |

○ : Supported ○1 : Supported by CPU***A/448/516/548

○3 : Supported by CPU208A/308A/316A/448(A)/516/548

○5 : Supported by CPU516/548

○2 : Supported by CPU308(A)/316(A)/448(A)/516/548

○4 : Supported by CPU308/316/**A/448/516/548

× : Not supported

[FUN commands] (3/5)

| No. | Command format | Command name | EH-150 | H-64 to H-20 | H-200 | H-250 | H-252 | H-2000 H-700 H-300 | H-2002 H-1002 H-702 H-302 | H4010 |
|-----|-----------------------------|---|--------|--------------|-------|-------|-------|--------------------|---------------------------|-------|
| 52 | FUN 100 (s) (INT (s)) | Flow decimal point operation (real number → integral number (word) conversion) | O2 | × | × | × | × | × | × | ○ |
| 53 | FUN 101 (s) (INTD (s)) | Flow decimal point operation (real number → integral number (double word) conversion) | O2 | × | × | × | × | × | × | ○ |
| 54 | FUN 102 (s) (FLOAT (s)) | Flow decimal point operation (integral number (word) → real number conversion) | O2 | × | × | × | × | × | × | ○ |
| 55 | FUN 103 (s) (FLOATD (s)) | Flow decimal point operation (integral number (double word) → real number conversion) | O2 | × | × | × | × | × | × | ○ |
| 56 | FUN 104 (s) (FADD (s)) | Flow decimal point operation (addition) | O2 | × | × | × | × | × | × | ○ |
| 57 | FUN 105 (s) (FSUB (s)) | Flow decimal point operation (subtraction) | O2 | × | × | × | × | × | × | ○ |
| 58 | FUN 106 (s) (FMUL (s)) | Flow decimal point operation (multiplication) | O2 | × | × | × | × | × | × | ○ |
| 59 | FUN 107 (s) (FDIV (s)) | Flow decimal point operation (division) | O2 | × | × | × | × | × | × | ○ |
| 60 | FUN 108 (s) (FRAD (s)) | Flow decimal point operation (angle → radian conversion) | O2 | × | × | × | × | × | × | ○ |
| 61 | FUN 109 (s) (FDEG (s)) | Flow decimal point operation (radian → angle conversion) | O2 | × | × | × | × | × | × | ○ |
| 62 | FUN 110 (s) (FSIN (s)) | Flow decimal point operation (SIN) | O2 | × | × | × | × | × | × | ○ |
| 63 | FUN 111 (s) (FCOS (s)) | Flow decimal point operation (COS) | O2 | × | × | × | × | × | × | ○ |
| 64 | FUN 112 (s) (FTAN (s)) | Flow decimal point operation (TAN) | O2 | × | × | × | × | × | × | ○ |
| 65 | FUN 113 (s) (FASIN (s)) | Flow decimal point operation (ARC SIN) | O2 | × | × | × | × | × | × | ○ |
| 66 | FUN 114 (s) (FACOS (s)) | Flow decimal point operation (ARC COS) | O2 | × | × | × | × | × | × | ○ |
| 67 | FUN 115 (s) (FATAN (s)) | Flow decimal point operation (ARC TAN) | O2 | × | × | × | × | × | × | ○ |
| 68 | FUN 116 (s) (FSQR (s)) | Flow decimal point operation (square) | O2 | × | × | × | × | × | × | ○ |
| 69 | FUN 117 (s) (FEXP (s)) | Flow decimal point operation (characteristic) | O2 | × | × | × | × | × | × | ○ |
| 70 | FUN 118 (s) (FLOG (s)) | Flow decimal point operation (napierian logarithm) | O2 | × | × | × | × | × | × | ○ |
| 71 | FUN 120 (s) (INDXD (s)) | Index setting (argument d) | O1 | × | × | × | × | × | × | ○ |
| 72 | FUN 121 (s) (INDXS (s)) | Index setting (argument s) | O1 | × | × | × | × | × | × | ○ |
| 73 | FUN 122 (s) (INDXC (s)) | Index cancel | O1 | × | × | × | × | × | × | ○ |
| 74 | FUN 123 (s) (INC (s)) | Increment (INC) | O4 | × | × | × | × | × | × | ○ |
| 75 | FUN 124 (s) (INCD (s)) | Double word increment (DINC) | O4 | × | × | × | × | × | × | ○ |

○ : Supported ○1 : Supported by CPU***A/448/516/548

○3 : Supported by CPU208A/308A/316A/448(A)/516/548

○5 : Supported by CPU516/548

○2 : Supported by CPU308(A)/316(A)/448(A)/516/548

○4 : Supported by CPU308/316/***A/448/516/548

× : Not supported

[FUN commands] (4/5)

| No. | Command format | Command name | EH-150 | H-64 to H-20 | H-200 | H-250 | H-252 | H-2000 H-700 H-300 | H-2002 H-1002 H-702 H-302 | H4010 |
|-----|-----------------------------|--|--------|--------------|-------|-------|-------|--------------------|---------------------------|-------|
| 76 | FUN 125 (s) (DEC (s)) | Decrement (DEC) | O4 | × | × | × | × | × | × | ○ |
| 77 | FUN 126 (s) (DECD (s)) | Double word decrement (DECD) | O4 | × | × | × | × | × | × | ○ |
| 78 | FUN 127 (s) (BITTOW (s)) | Expansion of bit data to word data | O1 | × | × | × | × | × | × | ○ |
| 79 | FUN 128 (s) (WTOBIT (s)) | Expansion of word data to bit data | O1 | × | × | × | × | × | × | ○ |
| 80 | FUN 133 (s) (FIBMOV (s)) | File memory block transfer | × | × | × | × | × | × | × | ○ |
| 81 | FUN 134 (s) (FIBCHG (s)) | File memory block exchange | × | × | × | × | × | × | × | ○ |
| 82 | FUN 135 (s) (FIWRED (s)) | File memory word unit read | × | × | × | × | × | × | × | ○ |
| 83 | FUN 136 (s) (FIWVRT (s)) | File memory word unit write | × | × | × | × | × | × | × | ○ |
| 84 | FUN 162 (s) | Explicit message execution (DeviceNet) | O5 | × | × | × | × | × | × | × |
| 85 | FUN 163 (s) | Explicit message setting (DeviceNet) | O5 | × | × | × | × | × | × | × |
| 86 | FUN 190 (s) | Inverter control command | O5 | × | × | × | × | × | × | × |
| 87 | FUN200 (s) (XYR/W (s)) | X, Y area read/write command | O1 | × | × | × | × | × | × | × |
| 88 | FUN201 (s) (SCR/W (s)) | Status control area read/write command | O1 | × | × | × | × | × | × | × |
| 89 | FUN 210 (s) (LOGIT (s)) | Initial setting for data logging | O2 | × | × | × | × | × | × | × |
| 90 | FUN 211 (s) (LOGWRT (s)) | Log data write | O2 | × | × | × | × | × | × | × |
| 91 | FUN 212 (s) (LOGCLR (s)) | Log data clear | O2 | × | × | × | × | × | × | × |
| 92 | FUN 213 (s) (LOGRED (s)) | Log data read | O2 | × | × | × | × | × | × | × |
| 93 | FUN 254 (s) (BOXC (s)) | BOX comment | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| 94 | FUN 255 (s) (MEMC (s)) | Memo comment | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |

○ : Supported ○1 : Supported by CPU***A/448/516/548

○3 : Supported by CPU208A/308A/316A/448(A)/516/548

○5 : Supported by CPU516/548

○2 : Supported by CPU308(A)/316(A)/448(A)/516/548

○4 : Supported by CPU308/316/***A/448/516/548

× : Not supported

MEMO

Appendix 3 Index of Instruction

[Symbol]

| | |
|-----|-----------|
| () | 5-4, 5-35 |
| [] | 5-4, 5-34 |

[A]

| | |
|-----------------|-------------|
| ABS (d, s) | 5-12,5-110 |
| ACOS (s) | 5-16,5-202 |
| ADRIO(d, s) | 5-13,5-129 |
| ALREF (s) | 5-16 |
| ANB | 5-4,5-32 |
| AND | 5-3 |
| AND n | 5-23 |
| AND DFN | 5-3 |
| AND DFN n | 5-27 |
| AND DIF | 5-3 |
| AND DIF n | 5-26 |
| AND (s1 < s2) | 5-6,5-58 |
| AND (s1 <= s2) | 5-6,5-60 |
| AND (s1 S< s2) | 5-6,5-59 |
| AND (s1 S<= s2) | 5-6,5-61 |
| AND (s1 S<> s2) | 5-5,5-57 |
| AND (s1 S== s2) | 5-5,5-54 |
| AND (s1 <> s2) | 5-5,5-56 |
| AND (s1 == s2) | 5-5,5-55 |
| ANI | 5-3 |
| ANI n | 5-23 |
| ASC (s) | 5-18,5-217 |
| ASIN (s) | 5-16, 5-201 |
| ATAN (s) | 5-16,5-203 |

[B]

| | |
|------------|------------|
| BCD(d, s) | 5-12,5-113 |
| BCDDA (s) | 5-18,5-208 |
| BCU(d, s) | 5-13,5-119 |
| BIN(d, s) | 5-12,5-114 |
| BINDA (s) | 5-18,5-204 |
| BINHA (s) | 5-18,5-206 |
| BITTOW (s) | 5-19,5-265 |
| BOXC (s) | 5-17,5-298 |
| BRES(d, n) | 5-10,5-86 |
| BSET(d, n) | 5-10,5-85 |
| BSHL (s) | 5-19,5-229 |
| BSHR (s) | 5-19,5-227 |
| BSL(d, n) | 5-11,5-98 |
| BSQR(s) | 5-231 |
| BSR(d, n) | 5-11,5-97 |
| BTOW (s) | 5-18,5-226 |
| BTS(d, n) | 5-10,5-87 |

[C]

| | |
|---------------|------------|
| CAL n | 5-14,5-139 |
| CEND(s) | 5-14,5-131 |
| CJMP n (s) | 5-14,5-133 |
| COPY(d, s, n) | 5-11,5-105 |
| COS (s) | 5-16,5-199 |

[D]

| | |
|-------------|----------|
| d=s | 5-7,5-62 |
| d=s1 / s2 | 5-8,5-71 |
| d=s1 <= s2 | 5-9,5-83 |
| d=s1 == s2 | 5-9,5-77 |
| d=s1 AND s2 | 5-8,5-75 |
| d=s1 B- s2 | 5-7,5-67 |
| d=s1 B/ s2 | 5-8,5-72 |
| d=s1 B+ s2 | 5-7,5-65 |
| d=s1 B× s2 | 5-8,5-69 |
| d=s1 OR s2 | 5-8,5-74 |
| d=s1 S/ s2 | 5-8,5-73 |
| d=s1 S< s2 | 5-9,5-82 |

| | |
|----------------|------------|
| d=s1 S<= s2 | 5-9,5-84 |
| d=s1 S<> s2 | 5-9,5-80 |
| d=s1 S== s2 | 5-9,5-78 |
| d=s1 S× s2 | 5-8,5-70 |
| d=s1 XOR s2 | 5-8,5-76 |
| d=s1 + s2 | 5-7,5-64 |
| d=s1 <> s2 | 5-9,5-79 |
| d=s1 < s2 | 5-9,5-81 |
| d=s1 × s2 | 5-8,5-68 |
| d=s1 - s2 | 5-7,5-66 |
| DABCD (s) | 5-18,5-215 |
| DABIN (s) | 5-18,5-210 |
| DBCDDA (s) | 5-18,5-209 |
| DBINDA (s) | 5-18,5-250 |
| DBINHA (s) | 5-18,5-207 |
| DDABCD (s) | 5-18,5-216 |
| DDABIN (s) | 5-18,5-211 |
| DEC (s) | 5-17,5-263 |
| DECD (s) | 5-17,5-264 |
| DECO (d, s, n) | 5-12,5-115 |
| DHABIN (s) | 5-18,5-214 |
| DIST (d, s, n) | 5-13,5-127 |

[E]

| | |
|----------------|------------|
| ENCO (d, s, n) | 5-12,5-116 |
| END | 5-14,5-130 |
| EXT (d, s) | 5-12,5-112 |

[F]

| | |
|--------------|------------|
| FACOS (s) | 5-17,5-253 |
| FADD (s) | 5-16,5-243 |
| FASIN (s) | 5-17,5-252 |
| FATAN (s) | 5-17,5-254 |
| FCOS (s) | 5-17,5-250 |
| FDEG (s) | 5-17,5-248 |
| FDIV (s) | 6-17,5-246 |
| FEXP (s) | 5-17,5-256 |
| FIFTT (P, n) | 5-13,5-121 |
| FIFRD (P, d) | 5-13,5-123 |
| FIFWR (P, s) | 5-13,5-122 |
| FLOAT (s) | 5-16,5-241 |
| FLOATD (s) | 5-16,5-242 |
| FLOG (s) | 5-17,5-257 |
| FMUL (s) | 5-16,5-245 |
| FOR n (s) | 5-14,5-136 |
| FRAD (s) | 5-17,5-247 |
| FSIN (s) | 5-17,5-249 |
| FSQR (s) | 5-17,5-255 |
| FSUB (s) | 5-16,5-244 |
| FTAN (s) | 5-17,5-251 |
| FUN 0 (s) | 5-16,5-171 |
| FUN 1 (s) | 5-16,5-172 |
| FUN 2 (s) | 5-16,5-173 |
| FUN 4 (s) | 5-16,5-187 |
| FUN 10 (s) | 5-16,5-190 |
| FUN 11 (s) | 5-16,5-191 |
| FUN 12 (s) | 5-16,5-192 |
| FUN 13 (s) | 5-16,5-193 |
| FUN 14 (s) | 5-16,5-194 |
| FUN 15 (s) | 5-16,5-195 |
| FUN 20 (s) | 5-16,5-196 |
| FUN 21 (s) | 5-16,5-197 |
| FUN 22 (s) | 5-16,5-198 |
| FUN 23 (s) | 5-16,5-201 |
| FUN 30 (s) | 5-16,5-204 |
| FUN 31 (s) | 5-16,5-205 |
| FUN 32 (s) | 5-16,5-206 |
| FUN 33 (s) | 5-16,5-207 |
| FUN 34 (s) | 5-16,5-208 |
| FUN 35 (s) | 5-17,5-209 |
| FUN 36 (s) | 5-17,5-210 |
| FUN 37 (s) | 5-17,5-211 |

| | |
|------------------|------------|
| FUN 38 (s)..... | 5-17,5-213 |
| FUN 39 (s)..... | 5-17,5-214 |
| FUN 40 (s)..... | 5-17,5-215 |
| FUN 41 (s)..... | 5-17,5-216 |
| FUN 42 (s)..... | 5-17,5-217 |
| FUN 43 (s)..... | 5-17,5-219 |
| FUN 44 (s)..... | 5-17,5-221 |
| FUN 45 (s)..... | 5-17,5-223 |
| FUN 46 (s)..... | 5-17,5-225 |
| FUN 47 (s)..... | 5-17,5-226 |
| FUN 48 (s)..... | 5-17,5-227 |
| FUN 49 (s)..... | 5-17,5-229 |
| FUN 60 (s)..... | 5-17,5-231 |
| FUN 61 (s)..... | 5-17,5-232 |
| FUN 80 (s)..... | 5-17,5-234 |
| FUN 81 (s)..... | 5-18,5-235 |
| FUN 82 (s)..... | 5-18,5-236 |
| FUN 100 (s)..... | 5-18,5-239 |
| FUN 101 (s)..... | 5-18,5-240 |
| FUN 102 (s)..... | 5-18,5-241 |
| FUN 103 (s)..... | 5-18,5-242 |
| FUN 104 (s)..... | 5-18,5-243 |
| FUN 105 (s)..... | 5-18,5-244 |
| FUN 106 (s)..... | 5-18,5-245 |
| FUN 107 (s)..... | 5-18,5-246 |
| FUN 108 (s)..... | 5-18,5-247 |
| FUN 109 (s)..... | 5-18,5-248 |
| FUN 110 (s)..... | 5-18,5-249 |
| FUN 111 (s)..... | 5-18,5-250 |
| FUN 112 (s)..... | 5-18,5-251 |
| FUN 113 (s)..... | 5-18,5-252 |
| FUN 114 (s)..... | 5-18,5-253 |
| FUN 115 (s)..... | 5-18,5-254 |
| FUN 116 (s)..... | 5-18,5-255 |
| FUN 117 (s)..... | 5-18,5-256 |
| FUN 118 (s)..... | 5-18,5-257 |
| FUN 120 (s)..... | 5-19,5-258 |
| FUN 121 (s)..... | 5-19,5-259 |
| FUN 122 (s)..... | 5-19,5-260 |
| FUN 123 (s)..... | 5-19,5-261 |
| FUN 124 (s)..... | 5-19,5-262 |
| FUN 125 (s)..... | 5-19,5-263 |
| FUN 126 (s)..... | 5-19,5-264 |
| FUN 127 (s)..... | 5-19,5-265 |
| FUN 128 (s)..... | 5-19,5-266 |
| FUN 162 (s)..... | 5-19,5-267 |
| FUN 163 (s)..... | 5-19,5-268 |
| FUN 190 (s)..... | 5-19,5-271 |
| FUN 200 (s)..... | 5-19,5-282 |
| FUN 201 (s)..... | 5-19,5-287 |
| FUN 210 (s)..... | 5-19,5-292 |
| FUN 211 (s)..... | 5-19,5-303 |
| FUN 212 (s)..... | 5-20,5-306 |
| FUN 213 (s)..... | 5-20,5-308 |
| FUN 254 (s)..... | 5-20,5-312 |
| FUN 255 (s)..... | 5-20,5-312 |

[H]

| | |
|----------------|------------|
| HABIN (s)..... | 5-18,5-213 |
| HEX (s)..... | 5-18,5-219 |

[I]

| | |
|----------------|-------------|
| IFR (s)..... | 5-16, 5-195 |
| INC (s)..... | 5-17,5-261 |
| INCD(s)..... | 5-17,5-262 |
| INDXC (s)..... | 5-19,5-260 |
| INDXD (s)..... | 5-19,5-258 |
| INDXS (s)..... | 5-19,5-259 |
| INT n..... | 5-14,5-142 |
| INTD(s)..... | 5-16,5-240 |
| INTW(s)..... | 5-16,5-239 |
| IOREF (s)..... | 5-16 |

[J]

| | |
|------------|------------|
| JMP n..... | 5-14,5-132 |
|------------|------------|

[L]

| | |
|----------------------|------------|
| LBL n..... | 5-14,5-135 |
| LD..... | 5-3 |
| LD (s1 < s2)..... | 5-6,5-58 |
| LD (s1 <= s2)..... | 5-6,5-60 |
| LD (s1 < > s2)..... | 5-5,5-56 |
| LD (s1 S< s2)..... | 5-6,5-59 |
| LD (s1 S<= s2)..... | 5-6,5-61 |
| LD (s1 S< > s2)..... | 5-5,5-57 |
| LD (s1 S== s2)..... | 5-5,5-55 |
| LD (s1==s2)..... | 5-5,5-54 |
| LD n..... | 5-22 |
| LDI..... | 5-3 |
| LDI n..... | 5-22 |
| LOGCLR (s)..... | 5-17,5-292 |
| LOGIT (s)..... | 5-17,5-278 |
| LOGRED (s)..... | 5-17,5-294 |
| LOGWRT (s)..... | 5-17,5-289 |
| LSL (d, n)..... | 5-10,5-96 |
| LSR (d, n)..... | 5-10,5-95 |

[M]

| | |
|--------------------|------------|
| MCR..... | 5-3 |
| MCR n..... | 5-30 |
| MCS..... | 5-3 |
| MCS n..... | 5-30 |
| MEMC (s)..... | 5-17,5-298 |
| MOV (d, s, n)..... | 5-11,5-103 |
| MPP..... | 5-4,5-31 |
| MPS..... | 5-4,5-31 |
| MRD..... | 5-4,5-31 |

[N]

| | |
|--------------|------------|
| NEG (d)..... | 5-12,5-109 |
| NEXT n..... | 5-14,5-137 |
| NOT..... | 5-3,5-25 |
| NOT (d)..... | 5-12,5-108 |

[O]

| | |
|----------------------|----------|
| OR..... | 5-3 |
| OR n..... | 5-24 |
| OR DFN..... | 5-3 |
| OR DFN n..... | 5-27 |
| OR DIF..... | 5-3 |
| OR DIF n..... | 5-26 |
| OR (s1 < s2)..... | 5-6,5-58 |
| OR (s1 <= s2)..... | 5-6,5-60 |
| OR (s1 S< s2)..... | 5-6,5-59 |
| OR (s1 S<= s2)..... | 5-6,5-61 |
| OR (s1 S< > s2)..... | 5-5,5-57 |
| OR (s1 S== s2)..... | 5-5,5-55 |
| OR (s1 < > s2)..... | 5-5,5-56 |
| OR(s1==s2)..... | 5-5,5-54 |
| ORB..... | 5-4,5-33 |
| ORI..... | 5-3 |
| ORI n..... | 5-24 |
| OUT..... | 5-3 |
| OUT n..... | 5-28 |
| OUT CL..... | 5-4 |
| OUT CL n s..... | 5-53 |
| OUT CTD..... | 5-4 |
| OUT CTD n..... | 5-51 |
| OUT CTU..... | 5-4 |
| OUT CTU n s..... | 5-51 |
| OUT CU..... | 5-4 |
| OUT CU n s..... | 5-47 |
| OUT MS..... | 5-4 |
| OUT MS n t s..... | 5-41 |
| OUT RCU..... | 5-4 |
| OUT RCU n s..... | 5-49 |

OUT SS5-4
 OUT SS n t s 5-39
 OUT TD.....5-4
 OUT TD n t s 5-36
 OUT TMR.....5-4
 OUT TMR n t s 5-43
 OUT WDT.....5-4
 OUT WDT n t s1 s2 5-45

[P]

PGEN (s)..... 5-232
 PIDCL(s)..... 5-16,5-181
 PIDIT (s)..... 5-15,5-179
 PIDOP (s)..... 5-16,5-180

[R]

RECV 0 (d, s, t) 5-15,5-154
 RES5-3
 RES n..... 5-29
 ROL (d, n)5-10,5-93
 ROR (d, n)5-10,5-92
 RTI..... 5-14,5-143
 RTS 5-14,5-141

[S]

SADD (s) 5-18,5-221
 SB n..... 5-14,5-140
 SCMP (s) 5-18,5-223
 SCR/W (s) 5-19,5-273
 SEG (d, s)..... 5-12,5-117
 SET5-3
 SET n..... 5-29
 SGET (d, s) 5-12,5-111
 SHL (d, n)5-10,5-91
 SHR (d, n)5-10,5-89
 SIN (s)..... 5-16,5-198
 SLREF (s) 5-16
 SQR (d, s) 5-13,5-118
 SWAP (d)..... 5-13,5-120

[T]

TAN (s)..... 5-16,5-200
 TRNS 0 (d, s, t)..... 5-15,5-145
 TRNS 8 (d, s, t)..... 5-15,5-160

[U]

UNIT(d, s, n) 5-13,5-125

[W][X]

WBSL (d, n) 5-11,5-102
 WBSR (d, n) 5-11,5-101
 XCG(d1, d2, n)..... 5-11,5-107
 WSHL (d, n) 5-11,5-100
 WSHR (d, n)5-11,5-99
 WTOB (s) 5-18,5-225
 WTOBIT (s) 5-19,5-267
 XYR/W (s) 5-19,5-268

MEMO